



FCC PART 95 MEASUREMENT AND TEST REPORT

For

3M Company

Personal Safety Division 3M Center, St. Paul Minnesota, United States

FCC ID: Y9ZMT4610W6

Report Type: Original Report	Product Type: WS™ Litecom Plus Headset
Report Number: RSZ190505001-00C	
Report Date: 2019-07-10	
Jacob Kong <i>Jacob Kong</i>	
Reviewed By: RF Engineer	
Test Laboratory: Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn	

Note: This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA* or any agency of the Federal Government. * This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk “*”.

The information marked # is provided by the applicant, the laboratory is not responsible for its authenticity.

TABLE OF CONTENTS

GENERAL INFORMATION.....	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
OBJECTIVE	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST METHODOLOGY	3
MEASUREMENT UNCERTAINTY	4
TEST FACILITY	4
SYSTEM TEST CONFIGURATION.....	5
DESCRIPTION OF TEST CONFIGURATION	5
DESCRIPTION OF CHANNEL LIST	5
EQUIPMENT MODIFICATIONS	5
SUPPORT EQUIPMENT LIST AND DETAILS	5
BLOCK DIAGRAM OF TEST SETUP	6
SUMMARY OF TEST RESULTS	7
TEST EQUIPMENT LIST	8
FCC §1.1307 (b) (1) & §2.1093 – RF EXPOSURE.....	9
APPLICABLE STANDARD	9
FCC §95.587(b)(1) – ANTENNA REQUIREMENT	11
APPLICABLE STANDARD	11
ANTENNA CONNECTOR CONSTRUCTION	11
FCC §2.1046 & §95.567 - RF OUTPUT POWER.....	12
APPLICABLE STANDARD	12
TEST PROCEDURE	12
TEST DATA	12
FCC §2.1047 & §95.575 - MODULATION CHARACTERISTIC	13
APPLICABLE STANDARD	13
TEST PROCEDURE	13
TEST DATA	13
FCC §2.1049 & §95.573 - AUTHORIZED BANDWIDTH AND EMISSION MASK.....	24
APPLICABLE STANDARD	24
TEST PROCEDURE	24
TEST DATA	24
FCC §2.1053 & §95.579- RADIATED SPURIOUS EMISSION	27
APPLICABLE STANDARD	27
TEST PROCEDURE	27
TEST DATA	27
FCC §2.1055 (d) & §95.565 - FREQUENCY STABILITY	29
APPLICABLE STANDARD	29
TEST PROCEDURE	29
TEST DATA	29

GENERAL INFORMATION

Product Description for Equipment Under Test (EUT)

Product	WST TM Litecom Plus Headset
Tested Model	MT73H7A4610WS6NA
Multiple Models [#]	MT73H7*4610WS6NA (* means A, B or P3E.)
Frequency Range	FRS: 462.5625-462.7125 MHz, 462.5500-462.7250 MHz, 467.5625-467.7125 MHz
Transmit Power	19.10 dBm
Testing Bandwidth	9.936 kHz
Modulation Technique	FM
Antenna Specification	Integrated Antenna
Voltage Range	DC 3.7 V from battery or DC 5.0V from adapter
Date of Test	2019-05-23~2019-05-30
Sample serial number	190505001
Received date	2019-05-05
Sample/EUT Status	Good condition
Adapter information	Model: DSA-5PFU1-05-FCA 050100 Input: AC 100-240V, 50/60Hz, 0.2A Output: DC 5V, 1A

Notes: This series products model: MT73H7*4610WS6NA (* means A, B or P3E.) and MT73H7A4610WS6NA are electrically schematics. Model MT73H7A4610WS6NA was selected for fully testing, the detailed information can be referred to the declaration which was stated and guaranteed by the applicant.

Objective

This report is prepared on behalf of 3M Company in accordance with Part 2 and Part 95, Subpart A & Subpart B of the Federal Communication Commissions rules.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DSS&DTS submissions with FCC ID: Y9ZMT4610W6.

Test Methodology

All tests and measurements indicated in this document were performed in accordance with Part 95 Subpart A, Subpart B of the Federal Communication Commissions rules with TIA-603-D, Land Mobile FM or PM-Communications Equipment-Measurement and Performance Standards.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		±5%
RF Output Power with Power meter		±0.73dB
RF conducted test with spectrum		±1.6dB
Emissions, Radiated	Below 1GHz	±4.75dB
	Above 1GHz	±4.88dB
Temperature		±1 °C
Humidity		±6%
Supply voltages		±0.4%

Note: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 342867, the FCC Designation No. : CN1221.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062B.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in a typical fashion (as normally used by a typical user).

Description of Channel List

FRS:

Channel No.	Channel Frequency (MHz)	Channel No.	Channel Frequency (MHz)
1	462.5625	12	467.6625
2	462.5875	13	467.6875
3	462.6125	14	467.7125
4	462.6375	15	462.5500
5	462.6625	16	462.5750
6	462.6875	17	462.6000
7	462.7125	18	462.6250
8	467.5625	19	462.6500
9	467.5875	20	462.6750
10	467.6125	21	462.7000
11	467.6375	22	462.7250


Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
/	/	/	/

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Results
§1.1307 (b) (1) & §2.1093	RF Exposure	Compliance
§95.587(b)(1)	Antenna Requirement	Compliance
§2.1046, §95.567	RF Output Power	Compliance
§2.1047, §95.575	Modulation Characteristic	Compliance
§2.1049, §95.573	Authorized Bandwidth & Emission Mask	Compliance
§2.1053, §95.579	Spurious Radiated Emissions	Compliance
§2.1055(d), §95.565	Frequency Stability	Compliance

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test					
Sunol Sciences	Horn Antenna	DRH-118	A052604	2017-12-22	2020-12-21
Rohde & Schwarz	Signal Analyzer	FSEM	845987/005	2018-06-23	2019-06-23
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2017-12-22	2020-12-21
COM-POWER	Pre-amplifier	PA-122	181919	2018-11-12	2019-11-12
Sonoma Instrument	Amplifier	310N	186238	2018-11-12	2019-11-12
Agilent	Signal Generator	N5183A	MY51040755	2018-12-03	2019-12-03
COM POWER	Dipole Antenna	AD-100	41000	NCR	NCR
A.H. System	Horn Antenna	SAS-200/571	135	2018-09-01	2021-08-31
Rohde & Schwarz	EMI Test Receiver	ESR	1316.3003K03-101746-zn	2018-07-11	2019-07-11
UTiFLEX MICRO-C0AX	RF Cable	UFA147A-2362-100100	MFR64639231029-003	2018-11-12	2019-11-12
Ducommun Technologies	RF Cable	104PEA	218124002	2018-11-12	2019-11-12
Ducommun Technologies	RF Cable	RG-214	1	2019-05-21	2019-11-19
Ducommun technologies	RF Cable	RG-214	2	2018-11-12	2019-11-12
RF Conducted test					
WEINSCHEL	10dB Attenuator	5324	N/A	Each Time	
HP Agilent	RF Communication Test Set	8920B	3325U00859	2019-01-15	2020-01-15
HP	Microwave frequency counter	5343A	2232A00827	2016-08-29	2019-08-29
Fluke	Digital Multimeter	287	19000011	2019-04-12	2020-04-12
ESPEC	Temperature & Humidity Chamber	EL-10KA	9107726	2019-01-05	2020-01-05
Long Wei	DC Power Supply	TPR-6420D	398363	NCR	NCR
N/A	Notch Filter	SKU 5G3	ATR0205-04-13	N/A	N/A
Rohde Schwarz	EMI Test Receiver	ESR	1316.3003K03-101746-zn	2018-07-11	2019-07-11
Ducommun Technologies	RF Cable	RG-214	3	Each Time	

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1307 (b) (1) & §2.1093 – RF EXPOSURE

Applicable Standard

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

1. $f(\text{GHz})$ is the RF channel transmit frequency in GHz.
2. Power and distance are rounded to the nearest mW and mm before calculation.
3. The result is rounded to one decimal place for comparison.
4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

For worst case:

Frequency (MHz)	Maximum Tune-up power		Calculated Distance (mm)	Calculated Value	Threshold (1-g SAR)	SAR Test Exclusion
	(dBm)	(mW)				
467.6375	20	100	40	1.7	3.0	Yes

When standalone SAR exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR value must be estimated according to the following to determine the simultaneous transmission SAR test exclusion criteria:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})/x}] \text{ W/kg}$, for test separation distances ≤ 50 mm; where $x=7.5$ for 1-g SAR

So, the calculated value for FRS is 0.23 W/kg

Refer to the DSS and DTS report, the highest Calculated Value for 2.4G band is 0.13 W/kg

The sum of 2.4G&FRS transmits simultaneously calculated value is $0.23\text{W/kg} + 0.13\text{W/kg} = 0.36\text{W/kg}$, less than the limit 1.6W/kg

Result: Compliance

Calculated Distance: 40mm



FCC §95.587(b)(1) – ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 95.587, (b) Antenna. The antenna of each FRS transmitter type must meet the following requirements.

(1) The antenna must be a non-removable integral part of the FRS transmitter type.

Antenna Connector Construction

The EUT has an integral antenna arrangement, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

FCC §2.1046 & §95.567 - RF OUTPUT POWER

Applicable Standard

Per FCC §2.1046, and §95.567, Each FRS transmitter type must be designed such that the effective radiated power (ERP) on channels 8 through 14 does not exceed 0.5 Watts and the ERP on channels 1 through 7 and 15 through 22 does not exceed 2.0 Watts.

Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load, which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the emissions were measured by the substitution.

Test Data

Environmental Conditions

Temperature:	24 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa

The testing was performed by Andy Yu on 2019-05-30.

Test Mode: Transmitting

Indicated		Table Angle Degree	Test Ant.		Substituted			Absolute Level (dBm)	ERP (mW)	Limit (mw)
Frequency (MHz)	S.A. Reading (dBμV)		Height (m)	Polar (H/V)	Substituted level (dBm)	Cable Loss (dB)	Ant. Gain (dB)			
462.6375MHz FRS										
462.6375	90.41	315	2.0	H	16.3	0.47	0.0	15.83	38.28	2000
462.6375	89.98	8	2.1	V	19.5	0.47	0.0	19.03	79.98	2000
467.6375MHz FRS										
467.6375	90.43	284	1.5	H	15.6	0.50	0.0	15.10	32.36	500
467.6375	91.40	215	1.7	V	19.6	0.50	0.0	19.10	81.28	500

Test Result: Compliance.

FCC §2.1047 & §95.575 - MODULATION CHARACTERISTIC**Applicable Standard**

Per FCC §2.1047 and §95.575: Each FRS transmitter type must be designed such that the peak frequency deviation does not exceed 2.5 kHz, and the highest audio frequency contributing substantially to modulation must not exceed 3.125 kHz.

Test Procedure

Test Method: TIA/EIA-603-D

Test Data**Environmental Conditions**

Temperature:	24 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa

The testing was performed by Kieroy Luo on 2019-05-27.


Please refer to the following tables and plots.

Test Mode: Transmitting

MODULATION LIMITING

Carrier Frequency: 462.6375MHz


Audio Frequency (Hz)	Instantaneous		Steady-state		FCC Limit [kHz]
	DEVIATION (@+20dB) [kHz]	DEVIATION (@-20dB) [kHz]	DEVIATION (@+20dB) [kHz]	DEVIATION (@-20dB) [kHz]	
300	2.416	0.074	2.405	0.068	2.5
400	2.273	0.101	2.271	0.096	2.5
500	2.195	0.103	2.182	0.097	2.5
600	2.103	0.132	2.086	0.127	2.5
700	2.233	0.131	2.220	0.128	2.5
800	2.181	0.147	2.167	0.141	2.5
900	1.971	0.161	1.966	0.159	2.5
1000	1.837	0.181	1.821	0.179	2.5
1200	1.871	0.203	1.861	0.202	2.5
1400	1.989	0.242	1.985	0.239	2.5
1600	2.033	0.257	2.018	0.253	2.5
1800	2.078	0.298	2.065	0.297	2.5
2000	2.119	0.303	2.111	0.296	2.5
2100	2.156	0.332	2.145	0.328	2.5
2200	2.163	0.336	2.146	0.330	2.5
2300	2.164	0.352	2.154	0.349	2.5
2400	2.195	0.348	2.181	0.348	2.5
2500	2.199	0.367	2.197	0.366	2.5
2600	2.178	0.386	2.174	0.384	2.5
2700	2.178	0.383	2.167	0.382	2.5
2800	2.171	0.389	2.162	0.383	2.5
2900	2.160	0.412	2.155	0.410	2.5
3000	1.941	0.412	1.932	0.406	2.5



Audio Frequency Response

Carrier Frequency: 462.6375 MHz


Audio Frequency (Hz)	Response Attenuation (dB)
300	-15.29
400	-9.47
500	-5.88
600	-4.07
700	-2.55
800	-1.37
900	-0.63
1000	0.00
1200	1.54
1400	2.50
1600	3.56
1800	4.43
2000	4.76
2100	5.14
2200	5.37
2300	5.64
2400	5.68
2500	5.71
2600	5.95
2700	5.83
2800	6.06
2900	5.95
3000	5.84



Audio frequency lows pass filter response

Carrier Frequency: 462.6375 MHz, Channel Separation=12.5 kHz


Audio Frequency (kHz)	Response Attenuation (dB)	Limit (dB)
1.0	0.0	/
3.0	-19.9	0.0
4.0	-77.0	-12.5
5.0	-87.8	-22.2
6.0	-87.5	-30.1
7.0	-86.9	-36.8
8.0	-89.2	-42.6
9.0	-87.9	-47.7
10.0	-88.2	-52.3
12.0	-89.3	-60.2
14.0	-89.7	-66.9
16.0	-90.3	-72.7
18.0	-91.6	-77.8
20.0	-89.3	-82.5



MODULATION LIMITING

Carrier Frequency: 467.6375MHz


Audio Frequency (Hz)	Instantaneous		Steady-state		FCC Limit [kHz]
	DEVIATION (@+20dB) [kHz]	DEVIATION (@-20dB) [kHz]	DEVIATION (@+20dB) [kHz]	DEVIATION (@-20dB) [kHz]	
300	2.418	0.073	2.405	0.068	2.5
400	2.275	0.094	2.261	0.081	2.5
500	2.197	0.096	2.193	0.100	2.5
600	2.111	0.130	2.100	0.110	2.5
700	2.234	0.125	2.216	0.126	2.5
800	2.186	0.146	2.168	0.136	2.5
900	1.975	0.160	1.959	0.155	2.5
1000	1.846	0.174	1.835	0.171	2.5
1200	1.877	0.196	1.869	0.178	2.5
1400	1.992	0.235	1.980	0.220	2.5
1600	2.035	0.254	2.018	0.251	2.5
1800	2.083	0.293	2.071	0.283	2.5
2000	2.123	0.297	2.115	0.286	2.5
2100	2.156	0.325	2.154	0.314	2.5
2200	2.166	0.332	2.150	0.331	2.5
2300	2.172	0.351	2.164	0.332	2.5
2400	2.196	0.346	2.187	0.341	2.5
2500	2.202	0.360	2.187	0.355	2.5
2600	2.187	0.383	2.170	0.372	2.5
2700	2.183	0.376	2.180	0.374	2.5
2800	2.174	0.384	2.163	0.384	2.5
2900	2.165	0.407	2.149	0.404	2.5
3000	1.946	0.405	1.933	0.401	2.5



Audio Frequency Response

Carrier Frequency: 467.6375 MHz


Audio Frequency (Hz)	Response Attenuation (dB)
300	-14.99
400	-9.68
500	-6.09
600	-4.04
700	-2.69
800	-1.47
900	-0.57
1000	0.00
1200	0.27
1400	2.52
1600	3.56
1800	4.86
2000	5.40
2100	5.98
2200	6.37
2300	6.50
2400	6.62
2500	7.17
2600	7.49
2700	7.55
2800	7.68
2900	8.08
3000	8.07



Audio frequency lows pass filter response

Carrier Frequency: 467.6375 MHz, Channel Separation=12.5 kHz

Audio Frequency (kHz)	Response Attenuation (dB)	Limit (dB)
1.0	0.0	/
3.0	-19.42	0.0
4.0	-76.50	-12.5
5.0	-87.54	-22.2
6.0	-88.00	-30.1
7.0	-87.11	-36.8
8.0	-88.76	-42.6
9.0	-87.89	-47.7
10.0	-88.29	-52.3
12.0	-89.01	-60.2
14.0	-89.31	-66.9
16.0	-90.48	-72.7
18.0	-91.61	-77.8
20.0	-88.92	-82.5



FCC §2.1049 & §95.573 - AUTHORIZED BANDWIDTH AND EMISSION MASK

Applicable Standard

According to §95.573. Each FRS transmitter type must be designed such that the occupied bandwidth does not exceed 12.5 kHz.

Test Procedure

TIA-603-D, section 2.2.11

Test Data

Environmental Conditions

Temperature:	24 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa

The testing was performed by Kieroy Luo on 2019-05-27.

Test Mode: Transmitting

Item	Frequency (MHz)	OBW (kHz)	Limit (kHz)	Result
FRS	462.6250	9.936	12.5	Pass
FRS	467.6375	9.936	12.5	Pass

Emission Designator Per CFR 47 §2.201& §2.202&, $B_n = 2M + 2D$:

Emission Designator 11K0F3E In this case, the maximum modulating frequency is 3.0 kHz with a 2.5 kHz deviation. $BW = 2(M+D) = 2*(3.0 \text{ kHz} + 2.5 \text{ kHz}) = 11 \text{ kHz} \rightarrow 11K0$
F3E portion of the designator represents an FM voice transmission Therefore, the entire designator for 12.5 kHz channel spacing FM mode is 11K0F3E.

Ref 30.5 dBm * Att 15 dB * RBW 300 Hz * VBW 3 kHz SWT 560 ms Marker 1 [T1] 20.93 dBm 462.63750000 MHz

30 Offset 10 5 dB


1 PK MAXH

OBW 9.935891436 kHz Temp 1 [T1 OBW] 1.82 dBm 462.632532051 MHz Temp 2 [T1 OBW] 1.79 dBm 462.642467949 MHz

3dB


Center 462.6375 MHz 5 kHz / Span 50 kHz

Emission Mask, 462.6375 MHz




Page 25 of 30

OBW, 467.6375 MHz



Date: 27.MAY.2019 16:22:45

Emission Mask, 467.6375 MHz



Date: 27.MAY.2019 16:20:22

FCC §2.1053 & §95.579- RADIATED SPURIOUS EMISSION

Applicable Standard

FCC §2.1053 and §95.579. Each FRS transmitter type must be designed to satisfy the applicable unwanted emissions limits in this paragraph.

(a) *Attenuation requirements.* The power of unwanted emissions must be attenuated below the carrier power output in Watts (P) by at least:

(1) 25 dB (decibels) in the frequency band 6.25 kHz to 12.5 kHz removed from the channel center frequency.

(2) 35 dB in the frequency band 12.5 kHz to 31.25 kHz removed from the channel center frequency.

(3) $43 + 10 \log (P)$ dB in any frequency band removed from the channel center frequency by more than 31.25 kHz.

(b) *Measurement bandwidths.* The power of unwanted emissions in the frequency bands specified in paragraphs (a)(1) and (2) of this section is measured with a reference bandwidth of 300 Hz. The power of unwanted emissions in the frequency range specified in paragraph (a)(3) is measured with a reference bandwidth of at least 30 kHz.

(c) *Measurement conditions.* The requirements in this section apply to each FRS transmitter type both with and without the connection of permitted attachments, such as an external speaker, microphone and/or power cord.

Test Procedure

The transmitter was placed on a wooden turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to tenth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in dB = $10 \lg (\text{TXpwr in Watts}/0.001)$ - the absolute level

Spurious attenuation limit in dB = $43 + 10 \log_{10} (\text{power out in Watts})$

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Leo Huang on 2019-05-23.

Test Mode: Transmitting

Indicated		Table Angle Degree	Test Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
Frequency (MHz)	Receiver Reading (dBuV)		Height (m)	Polar (H/V)	Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)			
FRS 462.6375MHz										
925.275	67.02	295	1.9	H	-30.2	1.24	0.0	-31.44	-13	18.44
925.275	72.88	149	1.0	V	-23.4	1.24	0.0	-24.64	-13	11.64
1387.9125	43.76	35	1.2	H	-64.5	1.60	7.90	-58.20	-13	45.20
1387.9125	49.49	313	2.4	V	-59.1	1.60	7.90	-52.80	-13	39.80
FRS 467.6375MHz										
935.275	50.47	20	1.1	H	-50.1	1.37	0.0	-51.47	-13	38.47
935.275	61.55	328	1.3	V	-37.8	1.37	0.0	-39.17	-13	26.17
1402.9125	43.01	146	1.4	H	-65.3	1.60	7.90	-59.00	-13	46.00
1402.9125	43.30	331	1.2	V	-65.3	1.60	7.90	-59.00	-13	46.00

Note:

- 1) Absolute Level = Substituted Level - Cable loss + Antenna Gain
- 2) Margin = Limit- Absolute Level

FCC§2.1055 (d) & §95.565 - FREQUENCY STABILITY**Applicable Standard**

According to FCC §2.1055(a) (1), the frequency stability shall be measured with variation of ambient temperature from -30 °C to +50 °C, and according to FCC 2.1055(d) (2), the frequency stability shall be measured with reducing primary supply voltage to the battery operating end point which is specified by the manufacturer.

According to FCC §95.565, Each FRS transmitter type must be designed such that the carrier frequencies remain within ± 2.5 parts-per-million of the channel center frequencies specified in §95.563 during normal operating conditions.

Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to a Frequency Counter via feed-through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the Frequency Counter.

Frequency Stability vs. Voltage (item 1 or item 2 will be chosen according to different condition) :

☐1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

☒2) For hand carried, battery powered equipment, reduce primary supply voltage to the battery operating end point which shall be specified by the manufacturer.

The output frequency was recorded for each voltage.

Test Data**Environmental Conditions**

Temperature:	24 °C
Relative Humidity:	50 %
ATM Pressure:	101.0 kPa

The testing was performed by Kieroy Luo on 2019-05-27.

Test Mode: Transmitting

FRS

Reference Frequency: 462.6375 MHz, Limit: ± 2.5 ppm			
Environment Temperature (°C)	Power Supplied (V _{DC})	Measurement Frequency (MHz)	Frequency Error (ppm)
Frequency Stability Ver. Temperature			
50	3.7	462.637429	-0.153
40	3.7	462.637433	-0.145
30	3.7	462.637425	-0.162
20	3.7	462.637438	-0.134
10	3.7	462.637442	-0.125
0	3.7	462.637434	-0.143
-10	3.7	462.637424	-0.164
-20	3.7	462.637425	-0.162
-30	3.7	462.637434	-0.143
Frequency Stability Ver. Input Voltage			
20	3.15	462.637435	-0.140
	4.25	462.637451	-0.106

Reference Frequency: 467.6375 MHz, Limit: ± 2.5 ppm			
Environment Temperature (°C)	Power Supplied (V _{DC})	Measurement Frequency (MHz)	Frequency Error (ppm)
Frequency Stability Ver. Temperature			
50	3.7	467.637428	-0.154
40	3.7	467.637421	-0.169
30	3.7	467.637420	-0.171
20	3.7	467.637439	-0.130
10	3.7	467.637440	-0.128
0	3.7	467.637426	-0.158
-10	3.7	467.637443	-0.122
-20	3.7	467.637435	-0.139
-30	3.7	467.637422	-0.167
Frequency Stability Ver. Input Voltage			
20	3.15	467.637439	-0.130
	4.25	467.637426	-0.158

***** END OF REPORT *****