

TEST REPORT

For

Bluetooth Module

MODEL No.: SYBLE02

FCC ID: YA3-SYBLE02

IC: 10186A-SYBLE02

Trade Mark: CHAMPION, CPE

REPORT NO: ES190726020W

ISSUE DATE: September 10, 2019

Prepared for

Champion Power Equipment, Inc.

12039 Smith Avenue, Santa Fe Springs, CA90670, USA

Prepared by

EMTEK(SHENZHEN) CO., LTD.

**Bldg 69, Majialong Industry Zone, Nanshan District, Shenzhen,
Guangdong, China**

TEL: 86-755-26954280

FAX: 86-755-26954282

Table of Contents

1	TEST RESULT CERTIFICATION	3
2	EUT TECHNICAL DESCRIPTION	4
3	SUMMARY OF TEST RESULT	5
4	TEST METHODOLOGY	6
	4.1 GENERAL DESCRIPTION OF APPLIED STANDARDS	6
	4.2 MEASUREMENT EQUIPMENT USED	6
	4.3 DESCRIPTION OF TEST MODES	7
5	FACILITIES AND ACCREDITATIONS	8
	5.1 FACILITIES	8
	5.2 LABORATORY ACCREDITATIONS AND LISTINGS	8
6	TEST SYSTEM UNCERTAINTY	9
7	SETUP OF EQUIPMENT UNDER TEST	10
	7.1 RADIO FREQUENCY TEST SETUP 1	10
	7.2 RADIO FREQUENCY TEST SETUP 2	10
	7.3 CONDUCTED EMISSION TEST SETUP	11
	7.4 SUPPORT EQUIPMENT	12
8	TEST REQUIREMENTS	13
	8.1 DTS BANDWIDTH	13
	8.2 MAXIMUM PEAK CONDUCTED OUTPUT POWER	17
	8.3 MAXIMUM POWER SPECTRAL DENSITY	20
	8.4 UNWANTED EMISSIONS IN NON-RESTRICTED FREQUENCY BANDS	23
	8.5 RADIATED SPURIOUS EMISSION	28
	8.6 CONDUCTED EMISSIONS TEST	40
	8.7 ANTENNA APPLICATION	45

1 TEST RESULT CERTIFICATION

Applicant:	Champion Power Equipment, Inc. 12039 Smith Avenue, Santa Fe Springs, CA90670, USA
Manufacturer:	Zhejiang Yaofeng Power Technology Co., Ltd. Daming Road, Nine li Industrial-Commercial Park, Chengnan, Shaoxing City, Zhejiang, China
Manufacturer of Electronic Modules	Shaoxing Siyuan Technology Co., Ltd. Changfeng Industrial Zone, Pingshui new city, Keqiao District, Shaoxing, Zhejiang, China
EUT Description:	Bluetooth Module
Model Number:	SYBLE02
Trade Mark:	CHAMPION, CPE
File Number:	ES190726020W

Measurement Procedure Used:


APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 2 2018, Subpart J FCC 47 CFR Part 15 2018, Subpart C IC RSS-GEN, Issue 5, March 2019 IC RSS-247 Issue 2, February 2017.	PASS


The above equipment was tested by EMTEK(SHENZHEN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 2 2018 & IC RSS-GEN, Issue 5 March 2019 and Part 15.247 2018 & IC RSS-247 Issue 2, February 2017.

The test results of this report relate only to the tested sample identified in this report

Date of Test : July 26,2019 to August 26, 2019

Prepared by : 
Doris Su /Editor

Reviewer : 
Joe Xia/Editor

Approve & Authorized Signer : 
Lisa Wang/Manager



2 EUT TECHNICAL DESCRIPTION

Characteristics	Description
Data Rate	1Mbps for GFSK modulation
Modulation	GFSK modulation (1Mbps)
Operating Frequency Range	2402-2480MHz
Number of Channels	40 channels
Transmit Power Max	10.05 dBm
Antenna Type	Dipole antenna
Antenna Gain	3.3dBi
Power supply	DC 3.3V
Temperature Range	-20°C~70°C
Product SW/HW version	V1.0
Radio SW/HW version	V1.0
Test SW Version	V1.0

Note: for more details, please refer to the User's manual of the EUT.

3 SUMMARY OF TEST RESULT

FCC Part Clause	Test Parameter	Verdict	Remark
15.247(a)(2) & RSS-247.5.2(a)	DTS (6dB) Bandwidth	PASS	
RSS-Gen.6.7	99% Occupied Bandwidth	PASS	
15.247(b)(3) & RSS-247.5.4(d)	Maximum Peak Conducted Output Power	PASS	
15.247(e) & RSS-247.5.2(b)	Maximum Power Spectral Density Level	PASS	
15.247(d) & RSS-247.5.5	Unwanted Emission Into Non-Restricted Frequency Bands	PASS	
15.247(d) 15.209 & RSS-247.5.5	Unwanted Emission Into Restricted Frequency Bands (conducted)	PASS	
15.247(d) 15.209 & RSS-Gen 6.13	Radiated Spurious Emission	PASS	
15.207 & RSS-Gen 8.8	Conducted Emission Test	PASS	
15.203 & RSS-Gen 6.8	Antenna Application	PASS	
	NOTE1: N/A (Not Applicable) NOTE2: According to FCC OET KDB 558074, the report use radiated measurements in the restricted frequency bands. In addition, the radiated test is also performed to ensure the emissions emanating from the device cabinet also comply with the applicable limits.		

RELATED SUBMITTAL(S) / GRANT(S):

This submittal(s) (test report) is intended for FCC ID: YA3-SYBLE02 filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

This submittal(s) (test report) is intended for IC: 10186A-SYBLE02 filing to comply with RSS 247 Clause 5 of the IC

4 TEST METHODOLOGY

4.1 GENERAL DESCRIPTION OF APPLIED STANDARDS

According to its specifications, the EUT must comply with the requirements of the following standards:

FCC 47 CFR Part 2, Subpart J

FCC 47 CFR Part 15, Subpart C

IC RSS-GEN, Issue 5, March 2019

IC RSS-247 Issue 2, February 2017

FCC KDB 558074 D01 15.247 Meas Guidance V05r02

4.2 MEASUREMENT EQUIPMENT USED

4.2.1 Conducted Emission Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	DUE CAL.
Test Receiver	Rohde & Schwarz	ESCS30	828985/018	05/18/2019	May 17, 2020
L.I.S.N.	Schwarzbeck	NNLK8129	8129203	05/18/2019	May 17, 2020
50Ω Coaxial Switch	Anritsu	MP59B	M20531	05/18/2019	May 17, 2020

4.2.2 Radiated Emission Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	DUE CAL.
EMI Test Receiver	Rohde & Schwarz	ESU	1302.6005.26	May 19, 2019	May 18, 2020
Pre-Amplifier	HP	8447F	2944A07999	May 18, 2019	May 17, 2020
Bilog Antenna	Schwarzbeck	VULB9163	142	May 18, 2019	May 17, 2020
Loop Antenna	ARA	PLA-1030/B	1029	May 18, 2019	May 17, 2020
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170399	May 19, 2019	May 18, 2020
Horn Antenna	Schwarzbeck	BBHA 9120	D143	May 18, 2019	May 17, 2020
Cable	Schwarzbeck	AK9513	ACRX1	May 19, 2019	May 18, 2020
Cable	Rosenberger	N/A	FP2RX2	May 19, 2019	May 18, 2020
Cable	Schwarzbeck	AK9513	CRPX1	May 19, 2019	May 18, 2020
Cable	Schwarzbeck	AK9513	CRRX2	May 19, 2019	May 18, 2020

4.2.3 Radio Frequency Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LASTCAL.	DUE CAL.
EMI Test Receiver	Rohde & Schwarz	ESU	1302.6005.26	May 19, 2019	May 18, 2020
Spectrum Analyzer	Agilent	E4407B	88156318	May 19, 2019	May 18, 2020
Signal Analyzer	Agilent	N9010A	My53470879	May 19, 2019	May 18, 2020
Power meter	Anritsu	ML2495A	0824006	May 19, 2019	May 18, 2020
Power sensor	Anritsu	MA2411B	0738172	May 19, 2019	May 18, 2020

Remark: Each piece of equipment is scheduled for calibration once a year.

4.3 DESCRIPTION OF TEST MODES

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (Bluetooth 4.2 with BLE mode:1Mbps) were used for all test.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Frequency and Channel list for Bluetooth 4.2 with BLE mode:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	19	2440
1	2404	20	2442	37	2476
2	2406	21	2444	38	2478
...	39	2480

Note: $f_c=2402\text{MHz}+k \times 1\text{MHz}$ $k=1$ to 39

Test Frequency and channel for Bluetooth 4.2 with BLE mode:

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	19	2440	39	2480

5 FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

Bldg 69, Majialong Industry Zone District, Nanshan District, Shenzhen, China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

5.2 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

EMC Lab. : Accredited by CNAS, 2018.11.30
The certificate is valid until 2022.10.28
The Laboratory has been assessed and proved to be in compliance with
CNAS-CL01:2018 (identical to ISO/IEC 17025:2017)
The Certificate Registration Number is L2291.

Accredited by TUV Rheinland Shenzhen 2016.5.19
The Laboratory has been assessed according to the requirements
ISO/IEC 17025.

Accredited by FCC, August 06, 2018
The certificate is valid until August 07, 2020
Designation Number: CN1204
Test Firm Registration Number: 882943

Accredited by A2LA, August 08, 2018
The certificate is valid until August 31, 2020
The Certificate Number is 4321.01.

Accredited by Industry Canada, November 09, 2018
The Conformity Assessment Body Identifier is CN0008.

Name of Firm : EMTEK (SHENZHEN) CO., LTD.
Site Location : Bldg 69, Majialong Industry Zone, Nanshan District, Shenzhen,
Guangdong, China

6 TEST SYSTEM UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:


Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-5}$
Maximum Peak Output Power Test	$\pm 1.0\text{dB}$
Conducted Emissions Test	$\pm 2.0\text{dB}$
Radiated Emission Test	$\pm 2.0\text{dB}$
Power Density	$\pm 2.0\text{dB}$
Occupied Bandwidth Test	$\pm 1.0\text{dB}$
Band Edge Test	$\pm 3\text{dB}$
All emission, radiated	$\pm 3\text{dB}$
Antenna Port Emission	$\pm 3\text{dB}$
Temperature	$\pm 0.5^{\circ}\text{C}$
Humidity	$\pm 3\%$

Measurement Uncertainty for a level of Confidence of 95%

7 SETUP OF EQUIPMENT UNDER TEST

7.1 RADIO FREQUENCY TEST SETUP 1

The Bluetooth 4.2 with BLE mode component's antenna ports(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.



7.2 RADIO FREQUENCY TEST SETUP 2

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.

Below 30MHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna (loop antenna). The Antenna should be positioned with its plane vertical at the specified distance from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. The center of the loop shall be 1 m above the ground. For certain applications, the loop antenna plane may also need to be positioned horizontally at the specified distance from the EUT.


30MHz-1GHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).


Above 1GHz:

The EUT is placed on a turntable 1.5 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).


(a) Radiated Emission Test Set-Up, Frequency Below 30MHz



(b) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(c) Radiated Emission Test Set-Up, Frequency above 1000MHz




7.3 CONDUCTED EMISSION TEST SETUP

The mains cable of the EUT (maybe per AC/DC Adapter) must be connected to LISN. The LISN shall be placed 0.8 m from the boundary of EUT and bonded to a ground reference plane for LISN mounted on top of the ground reference plane. This distance is between the closest points of the LISN and the EUT. All other units of the EUT and associated equipment shall be at least 0.8m from the LISN.

Ground connections, where required for safety purposes, shall be connected to the reference ground point of the LISN and, where not otherwise provided or specified by the manufacturer, shall be of same length as the mains cable and run parallel to the mains connection at a separation distance of not more than 0.1 m.

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.



7.4 SUPPORT EQUIPMENT

AC Adapter	Model:ASW0595-12010002A Input:AC 100-240V~ 50/60Hz 0.3A Output:DC 12V1A
------------	---

Notes:

- 1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.*
- 2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.*

8 TEST REQUIREMENTS

8.1 DTS BANDWIDTH

8.1.1 Applicable Standard

According to FCC Part 15.247(a)(2) & RSS-247 and RSS-247 and KDB 558074 D01 15.247 Meas Guidance V05r02

8.1.2 Conformance Limit

The minimum -6 dB bandwidth shall be at least 500 kHz.

8.1.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

8.1.4 Test Procedure

The EUT was operating in Bluetooth 4.2 with BLE mode mode and controlled its channel. Printed out the test result from the spectrum by hard copy function.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously

Set RBW = 100 kHz and 1%-5% OBW for 99% BANDWIDTH

Set the video bandwidth (VBW) $\geq 3 \times RBW$.

Set Span=2 times OBW

Set Detector = Peak.

Set Trace mode = max hold.

Set Sweep = auto couple.

Allow the trace to stabilize.

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.


Measure and record the results in the test report.

Test Results

Temperature : 25°C Test Date : Aug 26, 2019
Humidity : 55 % Test By: KK


Operation Mode	Channel Number	Channel Frequency (MHz)	-6dB Bandwidth (KHz)	99% Bandwidth(KHz)	Limit (KHz)	Verdict
Bluetooth 4.2 DTS	0	2402	733.7	1463	>500	PASS
	19	2440	781.5	1536	>500	PASS
	39	2480	746.7	1558	>500	PASS

Test Model DTS -6 Bandwidth
Bluetooth 4.2 with BLE mode
Channel 0: 2402MHz




Date: 26 AUG.2019 11:54:21

Test Model DTS -6 Bandwidth
Bluetooth 4.2 with BLE mode
Channel 19: 2440MHz




Date: 26 AUG.2019 11:56:15

Test Model DTS -6 Bandwidth
Bluetooth 4.2 with BLE mode
Channel 39: 2480MHz




Date: 26 AUG.2019 11:57:05

Test Model DTS 99% Bandwidth
Bluetooth 4.2 with BLE mode
Channel 0: 2402MHz




Date: 26 AUG.2019 11:58:12

Test Model DTS 99% Bandwidth
Bluetooth 4.2 with BLE mode
Channel 19: 2440MHz



Date: 26 AUG.2019 11:58:29

Test Model DTS 99% Bandwidth
Bluetooth 4.2 with BLE mode
Channel 39: 2480MHz



Date: 26 AUG.2019 11:58:47

8.2 MAXIMUM PEAK CONDUCTED OUTPUT POWER

8.2.1 Applicable Standard

According to FCC Part 15.247(b)(3) & RSS-247 and KDB 558074 D01 15.247 Meas Guidance V05r02

8.2.2 Conformance Limit

The maximum peak conducted output power of the intentional radiator for systems using digital modulation in the 2400 - 2483.5 MHz bands shall not exceed: 1 Watt (30dBm).

8.2.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

8.2.4 Test Procedure

■ According to FCC Part 15.247(b)(3) & IC RSS-247

As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. For smart system, Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Set the RBW \cong DTS bandwidth (about 1MHz).

Set VBW = 3*RBW (about 3MHz)

Set the span \cong 3*RBW

Set Sweep time = auto couple.

Set Detector = peak.

Set Trace mode = max hold.

Allow trace to fully stabilize. Use peak marker function to determine the peak amplitude level.

■ According to FCC Part 15.247(b)(4) & IC RSS-247:


Conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Test Results

Temperature : 25°C Test Date : Aug 26, 2019
 Humidity : 55 % Test By: KK


Operation Mode	Channel Number	Channel Frequency (MHz)	Measurement Level (dBm)	Limit (dBm)	Verdict
Bluetooth 4.2DTS	0	2402	9.9	30	PASS
	19	2440	9.9	30	PASS
	39	2480	10.05	30	PASS

Test Model	Maximum Conducted Output Power	
	Bluetooth 4.2 with BLE mode	
	Channel 0: 2402MHz	GFSK modulation




Date: 26.AUG.2019 11:50:57

Test Model	Maximum Conducted Output Power	
	Bluetooth 4.2 with BLE mode	
	Channel 19: 2440MHz	GFSK modulation



Date: 26.AUG.2019 11:51:44



8.3 MAXIMUM POWER SPECTRAL DENSITY

8.3.1 Applicable Standard

According to FCC Part 15.247(e) & RSS-247 Clause 5 and KDB 558074 D01 15.247 Meas Guidance V05r02

8.3.2 Conformance Limit

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

8.3.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

8.3.4 Test Procedure

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance

The transmitter output (antenna port) was connected to the spectrum analyzer

Set analyzer center frequency to DTS channel center frequency.

Set the span to 1.5 times the DTS bandwidth.

Set the RBW to: 3 kHz

Set the VBW to: 10 kHz.

Set Detector = peak.

Set Sweep time = auto couple.

Set Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level within the RBW.


8.3.5 Test Results

Temperature : 25°C Test Date : Aug 26, 2019
Humidity : 55 % Test By: KK

Operation Mode	Channel Number	Channel Frequency (MHz)	Measurement Level (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
Bluetooth 4.2 DTS	0	2402	2.49	=<8	PASS
	19	2440	2.95	=<8	PASS
	39	2480	2.93	=<8	PASS
Note: N/A					

Test Model


Power Spectral Density
Bluetooth 4.2 with BLE mode
Channel 0: 2402MHz



Date: 26 AUG.2019 11:59:36

Test Model


Power Spectral Density
Bluetooth 4.2 with BLE mode
Channel 19: 2440MHz



Date: 26 AUG.2019 11:59:52

Test Model

Power Spectral Density
Bluetooth 4.2 with BLE mode
Channel 39: 2480MHz



Date: 26 AUG.2019 12:00:10

8.4 UNWANTED EMISSIONS IN NON-RESTRICTED FREQUENCY BANDS

8.4.1 Applicable Standard

According to FCC Part 15.247(d) & RSS-247 and KDB 558074 D01 15.247 Meas Guidance V05r02

8.4.2 Conformance Limit

According to FCC Part 15.247(d) & RSS-247:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

8.4.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

8.4.4 Test Procedure

The transmitter output (antenna port) was connected to the spectrum analyzer

■ Reference level measurement

Establish a reference level by using the following procedure:

Set instrument center frequency to DTS channel center frequency.

Set the span to = 1.5 times the DTS bandwidth.

Set the RBW = 100 kHz.

Set the VBW $\geq 3 \times$ RBW.

Set Detector = peak.

Set Sweep time = auto couple.

Set Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum PSD level.

Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

■ Emission level measurement

Set the center frequency and span to encompass frequency range to be measured.

Set the RBW = 100 kHz.

Set the VBW = 300 kHz.

Set Detector = peak

Sweep time = auto couple.

Trace mode = max hold.


Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements. Report the three highest emissions relative to the limit.


8.4.5 Test Results

Test Model PSD(Power Spectral Density) RBW=100kHz
Bluetooth 4.2 with BLE mode
Channel 0: 2402MHz




Date: 26 AUG.2019 12:01:20

Test Model Unwanted Emissions in non-restricted frequency bands
Bluetooth 4.2 with BLE mode
Channel 0: 2402MHz




Date: 26 AUG.2019 12:02:17

Test Model Band edge
Bluetooth 4.2 with BLE mode
Channel 0: 2402MHz




Date: 26 AUG.2019 12:01:57

Test Model PSD(Power Spectral Density) RBW=100kHz
Bluetooth 4.2 with BLE mode
Channel 19: 2440MHz




Date: 26 AUG.2019 12:02:54

Test Model Unwanted Emissions In Non-Restricted Frequency Bands
Bluetooth 4.2 with BLE mode
Channel 19: 2440MHz




Date: 26 AUG.2019 12:03:25

Test Model PSD(Power Spectral Density) RBW=100kHz
Bluetooth 4.2 with BLE mode
Channel 39: 2480MHz




Date: 26 AUG.2019 12:03:57

Test Model Unwanted Emissions In Non-Restricted Frequency Bands
Bluetooth 4.2 with BLE mode
Channel 39: 2480MHz



Date: 26 AUG.2019 12:04:46

Test Model Band edge
Bluetooth 4.2 with BLE mode
Channel 39: 2480MHz



Date: 26 AUG.2019 12:04:28

8.5 RADIATED SPURIOUS EMISSION

8.5.1 Applicable Standard

According to FCC Part 15.247(d) & RSS-Gen 6.13 and 15.209 and KDB 558074 D01 15.247 Meas Guidance V05r02

8.5.2 Conformance Limit

According to FCC Part 15.247(d) & IC RSS-Gen 6.13: radiated emissions which fall in the restricted bands, must also comply with the radiated emission limits.

According to FCC Part15.205 & IC RSS-Gen 6.13, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

According to FCC Part15.205 & IC RSS-Gen, the level of any transmitter spurious emission in Restricted bands shall not exceed the level of the emission specified in the following table

Restricted Frequency(MHz)	Field Strength ($\mu\text{V/m}$)	Field Strength ($\text{dB}\mu\text{V/m}$)	Measurement Distance
0.009-0.490	2400/F(KHz)	20 log ($\mu\text{V/m}$)	300
0.490-1.705	2400/F(KHz)	20 log ($\mu\text{V/m}$)	30
1.705-30	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

8.5.3 Test Configuration

Test according to clause 7.2 radio frequency test setup 2

8.5.4 Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz(1GHz to 25GHz), 100 kHz for $f < 1$ GHz(30MHz to 1GHz)

VBW \geq RBW

Sweep = auto

Detector function = peak

Temperature : 24°C Test Date : Aug 25, 2019
 Humidity : 53 % Test By: KK
 Test mode: BT 4.2 with BLE mode Frequency: Channel 19: 2440MHz

Freq. (MHz)	Ant. Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
3052.75	V	44.02	34.21	74.00	54.00	-29.98	-19.79
4879.40	V	50.34	40.05	74.00	54.00	-23.66	-13.95
7942.80	V	55.57	45.93	74.00	54.00	-18.43	-8.07
3062.10	H	43.63	33.58	74.00	54.00	-30.37	-20.42
7966.60	H	55.83	45.87	74.00	54.00	-18.17	-8.13
9652.15	H	58.60	46.95	74.00	54.00	-15.40	-7.05

Temperature : 24°C Test Date : Aug 25, 2019
 Humidity : 53 % Test By: KK
 Test mode: BT 4.2 with BLE mode Frequency: Channel 39: 2480MHz

Freq. (MHz)	Ant. Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
2581.85	V	42.38	32.59	74.00	54.00	-31.62	-21.41
4959.30	V	47.36	37.48	74.00	54.00	-26.64	-16.52
8106.00	V	54.92	44.18	74.00	54.00	-19.08	-9.82
2581.85	H	42.65	32.45	74.00	54.00	-31.35	-21.55
4960.15	H	48.03	38.55	74.00	54.00	-25.97	-15.45
11171.10	H	62.95	48.19	74.00	54.00	-11.05	-5.81

- Note:**
- (1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).
 - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 - (3) Data of measurement within this frequency range shown " -- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

■ Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz

Temperature : 24°C Test Date : Aug 25, 2019
 Humidity : 55 % Test By: KK
 Test mode: BT 4.2 with BLE mode Frequency: Channel 0: 2402MHz


Frequency (MHz)	Polarity	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	Margin (dB)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)	Margin (dB)
2387.760	H	46.80	74.00	-27.20	36.14	54.00	-17.86
2387.760	V	46.80	74.00	-27.20	36.29	54.00	-17.71

Temperature : 28°C Test Date : Aug 25, 2019
 Humidity : 55 % Test By: KK
 Test mode: BT 4.2 with BLE mode Frequency: Channel 39: 2480MHz


Frequency (MHz)	Polarity	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	Margin (dB)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)	Margin (dB)
2483.559	H	51.95	74.00	-22.05	40.58	54.00	-13.42
2485.195	V	51.39	74.00	-22.61	40.15	54.00	-13.85

- Note:** (1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).
 (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
 (3) Data of measurement within this frequency range shown "--" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.


Test Model Spurious Emission in Restricted Band 2310-2390MHz
Bluetooth 4.2 with BLE mode
Channel 0: 2402MHz H



Test Model Spurious Emission in Restricted Band 2483.5-2500MHz
Bluetooth 4.2 with BLE mode
Channel 0: 2402MHz V




■ Spurious Emission below 1GHz (30MHz to 1GHz)



Site Radiated Emission 3m #1 Polarization: *Horizontal* Temperature: 24
 Limit: FCC Part15 Class B 3M Radiation Power: AC 120V/60Hz Humidity: 55 %
 Mode:TX(GFSK, 2402MHz)
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	*	122.4039	44.40	-23.78	20.62	43.50	-22.88	QP		
2		127.6645	45.18	-24.61	20.57	43.50	-22.93	QP		
3		206.3975	37.61	-22.30	15.31	43.50	-28.19	QP		
4		301.4223	37.62	-18.94	18.68	46.00	-27.32	QP		
5		457.5072	36.17	-16.21	19.96	46.00	-26.04	QP		
6		768.7481	30.83	-8.26	22.57	46.00	-23.43	QP		



Site Radiated Emission 3m #1

Polarization: **Vertical**

Temperature: 24

Limit: FCC Part15 Class B 3M Radiation


Power: AC 120V/60Hz

Humidity: 55 %

Mode:TX(GFSK, 2402MHz)


Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Antenna Height cm	Table Degree degree	Comment
1		55.4147	41.19	-19.89	21.30	40.00	-18.70	QP			
2		112.5241	52.52	-22.24	30.28	43.50	-13.22	QP			
3		117.3602	55.51	-23.08	32.43	43.50	-11.07	QP			
4	*	122.4038	57.01	-23.78	33.23	43.50	-10.27	QP			
5		126.7723	56.89	-24.40	32.49	43.50	-11.01	QP			
6		457.5072	36.17	-16.21	19.96	46.00	-26.04	QP			



Site Radiated Emission 3m #1 Polarization: **Horizontal** Temperature: 24
 Limit: FCC Part15 Class B 3M Radiation Power: AC 120V/60Hz Humidity: 55 %
 Mode:TX(GFSK, 2440MHz)
 Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Antenna Height cm	Table Degree	Comment
1		55.2207	32.63	-19.85	12.78	40.00	-27.22	QP			
2		116.9493	40.99	-23.01	17.98	43.50	-25.52	QP			
3		122.8338	42.64	-23.82	18.82	43.50	-24.68	QP			
4	*	127.6645	44.62	-24.61	20.01	43.50	-23.49	QP			
5		134.5591	44.46	-25.69	18.77	43.50	-24.73	QP			
6		273.2339	38.58	-19.66	18.92	46.00	-27.08	QP			



Site Radiated Emission 3m #1

Polarization: *Vertical*

Temperature: 24

Limit: FCC Part15 Class B 3M Radiation


Power: AC 120V/60Hz

Humidity: 55 %

Mode:TX(GFSK, 2440MHz)


Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Antenna Height cm	Table Degree	Comment
1		55.2207	41.30	-19.85	21.45	40.00	-18.55	QP			
2		112.5243	51.86	-22.24	29.62	43.50	-13.88	QP			
3		117.3602	55.01	-23.08	31.93	43.50	-11.57	QP			
4	*	122.8339	57.01	-23.82	33.19	43.50	-10.31	QP			
5		126.3285	56.56	-24.29	32.27	43.50	-11.23	QP			
6		133.1510	54.29	-25.52	28.77	43.50	-14.73	QP			



Site Radiated Emission 3m #1 Polarization: **Vertical** Temperature: 24
 Limit: FCC Part15 Class B 3M Radiation Power: AC 120V/60Hz Humidity: 55 %
 Mode:TX(GFSK, 2480MHz)
 Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Antenna Height cm	Table Degree degree	Comment
1		55.2207	40.78	-19.85	20.93	40.00	-19.07	QP			
2		112.1304	51.80	-22.18	29.62	43.50	-13.88	QP			
3		116.9494	54.60	-23.01	31.59	43.50	-11.91	QP			
4	*	121.9755	56.45	-23.75	32.70	43.50	-10.80	QP			
5		126.7723	56.36	-24.40	31.96	43.50	-11.54	QP			
6		506.4790	33.20	-14.38	18.82	46.00	-27.18	QP			



Site Radiated Emission 3m #1

Polarization: **Horizontal**

Temperature: 24

Limit: FCC Part15 Class B 3M Radiation

Power: AC 120V/60Hz

Humidity: 55 %

Mode:TX(GFSK, 2480MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		55.0274	32.69	-19.80	12.89	40.00	-27.11			QP
2		122.4040	42.74	-23.78	18.96	43.50	-24.54			QP
3	*	128.5629	44.53	-24.83	19.70	43.50	-23.80			QP
4		134.5591	45.04	-25.69	19.35	43.50	-24.15			QP
5		273.2340	38.54	-19.66	18.88	46.00	-27.12			QP
6		296.1836	37.43	-18.96	18.47	46.00	-27.53			QP

8.6 CONDUCTED EMISSIONS TEST

8.6.1 Applicable Standard

According to FCC Part 15.207(a) & IC RSS-Gen 8.8

8.6.2 Conformance Limit

Frequency(MHz)	Conducted Emission Limit	
	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

8.6.3 Test Configuration


Test according to clause 7.3 conducted emission test setup

8.6.4 Test Procedure

The EUT was placed on a table which is 0.8m above ground plane.
Maximum procedure was performed on the highest emissions to ensure EUT compliance.
Repeat above procedures until all frequency measured were complete.


8.6.5 Test Results

PASS




Site site #1 Phase: **N** Temperature: 24
 Limit: (CE)FCC PART 15 class B_QP Power: AC 120V/60Hz Humidity: 55 %
 Mode: TX Continue
 Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1500	33.74	10.07	43.81	66.00	-22.19	QP	
2		0.1500	12.43	10.07	22.50	56.00	-33.50	AVG	
3		0.2040	28.32	10.08	38.40	63.45	-25.05	QP	
4		0.2040	9.66	10.08	19.74	53.45	-33.71	AVG	
5		0.3060	21.84	10.09	31.93	60.08	-28.15	QP	
6		0.3060	4.74	10.09	14.83	50.08	-35.25	AVG	
7		0.5500	19.85	10.08	29.93	56.00	-26.07	QP	
8		0.5500	7.16	10.08	17.24	46.00	-28.76	AVG	
9		0.9620	13.06	9.88	22.94	56.00	-33.06	QP	
10		0.9620	-2.33	9.88	7.55	46.00	-38.45	AVG	
11		17.6480	15.96	10.64	26.60	60.00	-33.40	QP	
12		17.6480	7.68	10.64	18.32	50.00	-31.68	AVG	




Site site #1 Phase: **L1** Temperature: 24
 Limit: (CE)FCC PART 15 class B_QP Power: AC 120V/60Hz Humidity: 55 %
 Mode: TX Continue
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1		0.1500	33.40	10.07	43.47	66.00	-22.53	QP	
2		0.1500	14.16	10.07	24.23	56.00	-31.77	AVG	
3		0.2420	25.90	10.08	35.98	62.03	-26.05	QP	
4		0.2420	7.57	10.08	17.65	52.03	-34.38	AVG	
5	*	0.5420	24.83	10.09	34.92	56.00	-21.08	QP	
6		0.5420	8.84	10.09	18.93	46.00	-27.07	AVG	
7		0.9740	15.47	9.87	25.34	56.00	-30.66	QP	
8		0.9740	-0.48	9.87	9.39	46.00	-36.61	AVG	
9		1.4540	13.11	9.89	23.00	56.00	-33.00	QP	
10		1.4620	-1.85	9.89	8.04	46.00	-37.96	AVG	
11		17.6080	15.49	10.64	26.13	60.00	-33.87	QP	
12		17.6080	7.02	10.64	17.66	50.00	-32.34	AVG	



Site site #1 Phase: **L1** Temperature: 24
 Limit: (CE)FCC PART 15 class B_QP Power: AC 240V/60Hz Humidity: 55 %
 Mode: TX Continue
 Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV	dBuV	dB		
1		0.1500	45.30	10.10	55.40	66.00	-10.60	QP	
2		0.1500	10.30	10.10	20.40	56.00	-35.60	AVG	
3	*	0.1820	44.00	10.09	54.09	64.39	-10.30	QP	
4		0.1820	22.50	10.09	32.59	54.39	-21.80	AVG	
5		0.2140	38.60	10.09	48.69	63.05	-14.36	QP	
6		0.2140	6.20	10.09	16.29	53.05	-36.76	AVG	
7		0.2540	37.30	10.09	47.39	61.63	-14.24	QP	
8		0.2540	23.30	10.09	33.39	51.63	-18.24	AVG	
9		0.3060	33.80	10.08	43.88	60.08	-16.20	QP	
10		0.3060	14.90	10.08	24.98	50.08	-25.10	AVG	
11		0.3303	30.40	10.08	40.48	59.44	-18.96	QP	
12		0.3303	9.30	10.08	19.38	49.44	-30.06	AVG	



Site site #1 Phase: **N** Temperature: 24
 Limit: (CE)FCC PART 15 class B_QP Power: AC 240V/60Hz Humidity: 55 %
 Mode: TX Continue
 Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1500	45.80	10.07	55.87	66.00	-10.13	QP	
2		0.1500	10.70	10.07	20.77	56.00	-35.23	AVG	
3		0.1700	43.20	10.08	53.28	64.96	-11.68	QP	
4		0.1700	10.10	10.08	20.18	54.96	-34.78	AVG	
5		0.1900	42.80	10.08	52.88	64.04	-11.16	QP	
6		0.1900	25.00	10.08	35.08	54.04	-18.96	AVG	
7		0.2100	39.30	10.08	49.38	63.21	-13.83	QP	
8		0.2100	6.10	10.08	16.18	53.21	-37.03	AVG	
9		0.2420	38.30	10.08	48.38	62.03	-13.65	QP	
10		0.2420	24.20	10.08	34.28	52.03	-17.75	AVG	
11		0.2540	37.70	10.09	47.79	61.63	-13.84	QP	
12		0.2540	21.70	10.09	31.79	51.63	-19.84	AVG	

8.7 ANTENNA APPLICATION

8.7.1 Antenna Requirement

Standard	Requirement
FCC CRF Part 15.203 & IC RSS-Gen 6.7	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

For intentional device, according to FCC 47 CFR Section 15.203 & IC RSS-Gen 6.7, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b) & IC RSS-Gen 6.7, if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

8.7.2 Result

The EUT'S antenna is a dipole antenna. The antenna's gain is 3.3 dBi and meets the requirement, please refer to the internal photos.