



FCC RF Test Report

APPLICANT : ATrack Technology Inc.
EQUIPMENT : GPS/GSM/GPRS Tracker
BRAND NAME : ATrack
MODEL NAME : AT1(internal GPS antenna)/AT1E(external GPS antenna)
FCC ID : YA7-ATVT1038
STANDARD : FCC 47 CFR Part 2, 22(H), 24(E)
CLASSIFICATION : PCS Licensed Transmitter (PCB)
Tx/Rx FREQUENCY RANGE : GSM850 : 824.2 ~ 848.8 MHz /
869.2 ~ 893.8 MHz
GSM1900 : 1850.2 ~ 1909.8 MHz /
1930.2 ~ 1989.8 MHz
MAX. ERP/EIRP POWER : GSM850 (GSM) : 0.04 W
GSM1900 (GSM) : 0.57 W
EMISSION DESIGNATOR : GMSK : 250KGXW

The product was received on Jul. 06, 2010 and completely tested on Oct. 30, 2010. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI / TIA / EIA-603-C-2004 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:

Anderson Chiu

Anderson Chiu / Deputy Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.



TABLE OF CONTENTS

REVISION HISTORY..... 3

SUMMARY OF TEST RESULT 4

1 GENERAL DESCRIPTION 5

 1.1 Applicant..... 5

 1.2 Manufacturer 5

 1.3 Feature of Equipment Under Test..... 5

 1.4 Testing Site..... 6

 1.5 Applied Standards 6

 1.6 Ancillary Equipment List..... 6

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST 7

 2.1 Test Mode..... 7

 2.2 Connection Diagram of Test System 8

3 TEST RESULT..... 9

 3.1 Conducted Output Power Measurement..... 9

 3.2 Effective Radiated Power and Effective Isotropic Radiated Power Measurement 11

 3.3 Occupied Bandwidth Measurement 14

 3.4 Band Edge Measurement..... 17

 3.5 Conducted Emission Measurement 20

 3.6 Field Strength of Spurious Radiation Measurement 26

 3.7 Frequency Stability Measurement..... 36

4 LIST OF MEASURING EQUIPMENT 39

5 UNCERTAINTY OF EVALUATION 40

APPENDIX A. PHOTOGRAPHS OF EUT

APPENDIX B. SETUP PHOTOGRAPHS



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG070628	Rev. 01	Initial issue of report	Nov. 05, 2010



SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	§2.1046	N/A	Conducted Output Power	N/A	PASS	-
3.2	§22.913(a)(2)	RSS-132(4.4) SRSP-503(5.1.3)	Effective Radiated Power	< 7 Watts	PASS	-
3.2	§24.232(c)	RSS-133 (6.4) SRSP-510(5.1.2)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
3.3	§2.1049 §22.917(a) §24.238(a)	N/A	Occupied Bandwidth	N/A	PASS	-
3.4	§2.1051 §22.917(a) §24.238(a)	RSS-132 (4.5.1) RSS-133 (6.5.1)	Band Edge Measurement	< 43+10log ₁₀ (P[Watts])	PASS	-
3.5	§2.1051 §22.917(a) §24.238(a)	RSS-132 (4.5.1) RSS-133 (6.5.1)	Conducted Emission	< 43+10log ₁₀ (P[Watts])	PASS	-
3.6	§2.1053 §22.917(a) §24.238(a)	RSS-132 (4.5.1) RSS-133 (6.5.1)	Field Strength of Spurious Radiation	< 43+10log ₁₀ (P[Watts])	PASS	Under limit 6.90 dB at 9396 MHz
3.7	§2.1055 §22.355 §24.235	RSS-132(4.3) RSS-133(6.3)	Frequency Stability for Temperature & Voltage	< 2.5 ppm	PASS	-

1 General Description

1.1 Applicant

ATrack Technology Inc.

9F., No. 285, Sec. 2, Tiding Blvd., Neihu Dist., Taipei City 11493, Taiwan (R.O.C.)

1.2 Manufacturer

ATrack Technology Inc.

9F., No. 285, Sec. 2, Tiding Blvd., Neihu Dist., Taipei City 11493, Taiwan (R.O.C.)

1.3 Feature of Equipment Under Test

Product Feature & Specification	
Equipment	GPS/GSM/GPRS Tracker
Brand Name	ATrack
Model Name	AT1(internal GPS antenna)/AT1E(external GPS antenna)
FCC ID	YA7-ATVT1038
Sample 1	EUT with Internal GPS Antenna
Sample 2	EUT with External GPS Antenna
Tx Frequency	GSM850 : 824 MHz ~ 849 MHz GSM1900 : 1850 MHz ~ 1910 MHz
Rx Frequency	GSM850 : 869 MHz ~ 894 MHz GSM1900 : 1930 MHz ~ 1990 MHz
Maximum Output Power to Antenna	GSM850 : 31.61 dBm GSM1900 : 28.16 dBm
Maximum ERP/EIRP	GSM850 (GSM) : 0.04 W (16.32 dBm) GSM1900 (GSM) : 0.57 W (27.57 dBm)
Antenna Type	Fixed Internal Antenna
HW Version	1.0
SW Version	1.04
Type of Modulation	GMSK
Type of Emission	250KGXW
EUT Stage	Production Unit

Remark:

1. For other wireless features of this EUT, the test report will be issued separately.
2. This test report recorded only product characteristics and test results of PCS Licensed Transmitter (PCB).
3. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Testing Site

Test Site	SPORTON INTERNATIONAL INC.		
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978		
Test Site No.	Sporton Site No.		FCC/IC Registration No.
	TH02-HY	03CH05-HY	722060/4086B-1

1.5 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ Preliminary Guidance for Receiving Applications for Certification of 3G Device. May 9, 2006.
- ♦ FCC 47 CFR Part 2, 22(H), 24(E)
- ♦ ANSI / TIA / EIA-603-C-2004
- ♦ IC RSS-132 Issue 2
- ♦ IC RSS-133 Issue 5

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B (DoC), recorded in a separate test report.

1.6 Ancillary Equipment List

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU200	N/A	N/A	Unshielded, 1.8 m

2 Test Configuration of Equipment Under Test

2.1 Test Mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range.

Frequency range investigated for radiated emission is as follows:

1. 30 MHz to 9000 MHz for GSM850.
2. 30 MHz to 19000 MHz for GSM1900.

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	<ul style="list-style-type: none"> ■ GSM Link for Sample 2 ■ GSM Link for Sample 1 	<ul style="list-style-type: none"> ■ GSM Link
GSM 1900	<ul style="list-style-type: none"> ■ GSM Link for Sample 2 ■ GSM Link for Sample 1 	<ul style="list-style-type: none"> ■ GSM Link


Note: The maximum power levels are GSM mode for GMSK link, only these modes were used for all tests.

The conducted power tables are as follows:


Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GSM	31.61	31.53	31.60	28.16	27.50	27.62
GPRS 8	31.60	31.52	31.60	28.08	27.43	27.56
GPRS 10	31.60	31.52	31.60	28.07	27.42	27.55

2.2 Connection Diagram of Test System

<EUT with Internal GPS Antenna>



<EUT with External GPS Antenna>



3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.


3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

3.1.3 Test Procedures

1. The transmitter output port was connected to base station.
2. Set EUT at maximum power through base station.
3. Select lowest, middle, and highest channels for each band and different modulation.

3.1.4 Test Setup



3.1.5 Test Result of Conducted Output Power

Cellular Band				
Modes	Channel	Frequency (MHz)	Conducted Power (dBm)	Conducted Power (Watts)
GSM850 (GSM)	128 (Low)	824.2	31.61	1.45
	189 (Mid)	836.4	31.53	1.42
	251 (High)	848.8	31.60	1.45

PCS Band				
Modes	Channel	Frequency (MHz)	Conducted Power (dBm)	Conducted Power (Watts)
GSM1900 (GSM)	512 (Low)	1850.2	28.16	0.65
	661 (Mid)	1880.0	27.50	0.56
	810 (High)	1909.8	27.62	0.58

3.2 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

3.2.1 Description of the ERP/EIRP Measurement

ERP/EIRP is measured by substitution method according to ANSI / TIA / EIA-603-C-2004. The ERP of mobile transmitters must not exceed 7 Watts and the EIRP of mobile transmitters are limited to 2 Watts.


3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

1. The EUT was placed on a turntable with 1.0 meter height in a fully anechoic chamber.
2. The EUT was set at 1.2 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiated power.
4. The height of the receiving antenna is adjusted to look for the maximum ERP/EIRP.
5. Taking the record of maximum ERP/EIRP.
6. A dipole antenna was substituted in place of the EUT and was driven by a signal generator.
7. The conducted power at the terminal of the dipole antenna is measured.
8. Repeat step 3 to step 5 to get the maximum ERP/EIRP of the substitution antenna.
9. $ERP/EIRP = P_s + E_t - E_s + G_s = P_s + R_t - R_s + G_s$
Ps (dBm) : Input power to substitution antenna.
Gs (dBi or dBd) : Substitution antenna Gain.
 $E_t = R_t + AF$
 $E_s = R_s + AF$
AF (dB/m) : Receive antenna factor
Rt : The highest received signal in spectrum analyzer for EUT.
Rs : The highest received signal in spectrum analyzer for substitution antenna.

3.2.4 Test Setup





3.2.5 Test Result of ERP

GSM850 (GSM) Radiated Power ERP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-34.44	-48.12	0.00	-1.08	12.60	0.02
836.40	-34.78	-48.28	0.00	-0.93	12.57	0.02
848.80	-34.12	-48.35	0.00	-0.76	13.47	0.02
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBd)	ERP (dBm)	ERP (W)
824.20	-32.67	-47.97	0.00	-1.08	14.22	0.03
836.40	-32.01	-48.01	0.00	-0.93	15.07	0.03
848.80	-30.97	-48.05	0.00	-0.76	16.32	0.04

3.2.6 Test Result of EIRP

GSM1900 (GSM) Radiated Power EIRP						
Horizontal Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-30.47	-51.88	0.00	1.96	23.37	0.22
1880.00	-29.20	-52.99	0.00	2.00	25.79	0.38
1909.80	-29.28	-54.28	0.00	1.98	26.98	0.50
Vertical Polarization						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)
1850.20	-29.49	-52.13	0.00	1.96	24.60	0.29
1880.00	-27.60	-53.17	0.00	2.00	27.57	0.57
1909.80	-28.93	-54.13	0.00	1.98	27.18	0.52

3.3 Occupied Bandwidth Measurement

3.3.1 Description of Occupied Bandwidth Measurement

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

3.3.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The 99% and 26 dB occupied bandwidth (BW) of the middle channel for the highest RF powers were measured.

3.3.4 Test Setup






3.3.5 Test Result (Plots) of Occupied Bandwidth


Band :	GSM 850	Power Stage :	High
Test Mode :	GSM Link		

99% Occupied Bandwidth Plot on Channel 189



Date: 28.OCT.2010 03:58:50

26dB Bandwidth Plot on Channel 189




Date: 28.OCT.2010 03:57:31




Band :	GSM 1900	Power Stage :	High
Test Mode :	GSM Link		

99% Occupied Bandwidth Plot on Channel 661



Date: 28.OCT.2010 03:50:38

26dB Bandwidth Plot on Channel 661



Date: 28.OCT.2010 03:49:19

3.4 Band Edge Measurement

3.4.1 Description of Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

3.4.2 Measuring Instruments


See list of measuring instruments of this test report.

3.4.3 Test Procedures

1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
2. The band edges of low and high channels for the highest RF powers were measured. Setting RBW as roughly BW/100.

3.4.4 Test Setup

<Conducted Band Edge >






3.4.5 Test Result (Plots) of Conducted Band Edge


Band :	GSM850	Power Stage :	High
Test Mode :	GSM Link		

Lower Band Edge Plot on Channel 128



Date: 28.OCT.2010 04:00:54

Higher Band Edge Plot on Channel 251




Date: 28.OCT.2010 04:01:20




Band :	GSM1900	Power Stage :	High
Test Mode :	GSM Link		

Lower Band Edge Plot on Channel 512



Date: 28.OCT.2010 03:52:40

Higher Band Edge Plot on Channel 810



Date: 28.OCT.2010 03:53:07

3.5 Conducted Emission Measurement

3.5.1 Description of Conducted Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.


3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

3.5.3 Test Procedures

1. The EUT was connected to spectrum analyzer and base station via power divider.
2. The middle channel for the highest RF power within the transmitting frequency was measured.
3. The conducted spurious emission for the whole frequency range was taken.

3.5.4 Test Setup






3.5.5 Test Result (Plots) of Conducted Emission


Band :	GSM850	Channel :	CH189
Test Mode :	GSM Link		

Conducted Emission Plot between 30MHz ~ 1GHz



Date: 28.OCT.2010 04:11:59


Conducted Emission Plot between 1GHz ~ 3GHz



Date: 28.OCT.2010 04:12:49




Conducted Emission Plot between 3GHz ~ 7GHz



Date: 28.OCT.2010 04:13:01

Conducted Emission Plot between 7GHz ~ 9GHz




Date: 28.OCT.2010 04:13:13




Band :	GSM1900	Channel :	CH661
Test Mode :	GSM Link		

Conducted Emission Plot between 30MHz ~ 1GHz



Date: 28.OCT.2010 04:16:46


Conducted Emission Plot between 1GHz ~ 3GHz



Date: 28.OCT.2010 04:17:00




Conducted Emission Plot between 3GHz ~ 7GHz



Date: 28.OCT.2010 04:17:12


Conducted Emission Plot between 7GHz ~ 13.6GHz



Date: 28.OCT.2010 04:17:24



Conducted Emission Plot between 13.6GHz ~ 19.1GHz



Date: 28.OCT.2010 04:17:37

3.6 Field Strength of Spurious Radiation Measurement

3.6.1 Description of Field Strength of Spurious Radiated Measurement

The radiated spurious emission was measured by substitution method according to ANSI / TIA / EIA-603-C-2004. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.


3.6.2 Measuring Instruments

See list of measuring instruments of this test report.

3.6.3 Test Procedures

1. The EUT was placed on a rotatable wooden table with 0.8 meter about ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, Sweep = 500ms, Taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
11. $ERP \text{ (dBm)} = EIRP - 2.15$


3.6.4 Test Setup





3.6.5 Test Result of Field Strength of Spurious Radiated


Band :	GSM850	Temperature :	23~24°C
Test Mode :	GSM Link for Sample 2	Relative Humidity :	49~52%
Test Engineer :	Cona Huang	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-48.72	-13	-35.72	-31.23	-49.91	2.15	5.49	H	Pass
2509	-48.22	-13	-35.22	-33.8	-50.11	2.38	6.41	H	Pass
3345	-53.97	-13	-40.97	-41.07	-57.3	2.86	8.34	H	Pass
4182	-49.15	-13	-36.15	-39.8	-53.09	3.26	9.35	H	Pass
5854	-32.49	-13	-19.49	-29.27	-37.26	3.95	10.87	H	Pass
6691	-40.27	-13	-27.27	-38.41	-45.09	4.36	11.33	H	Pass




Band :	GSM850	Temperature :	23~24°C
Test Mode :	GSM Link for Sample 2	Relative Humidity :	49~52%
Test Engineer :	Cona Huang	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-47.81	-13	-34.81	-30.32	-49	2.15	5.49	V	Pass
2509	-48.78	-13	-35.78	-34.36	-50.67	2.38	6.41	V	Pass
3345	-54.75	-13	-41.75	-41.85	-58.08	2.86	8.34	V	Pass
5854	-34.46	-13	-21.46	-31.24	-39.23	3.95	10.87	V	Pass
6691	-35.08	-13	-22.08	-33.22	-39.9	4.36	11.33	V	Pass
7527	-44.24	-13	-31.24	-46.69	-50.11	4.60	12.62	V	Pass




Band :	GSM850	Temperature :	23~24°C
Test Mode :	GSM Link for Sample 1	Relative Humidity :	49~52%
Test Engineer :	Cona Huang	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-49.19	-13	-36.19	-31.7	-50.38	2.15	5.49	H	Pass
2509	-51.09	-13	-38.09	-36.67	-52.98	2.38	6.41	H	Pass
3345	-54.55	-13	-41.55	-41.65	-57.88	2.86	8.34	H	Pass
4182	-50.49	-13	-37.49	-41.14	-54.43	3.26	9.35	H	Pass
5854	-48.22	-13	-35.22	-45	-52.99	3.95	10.87	H	Pass



Band :	GSM850	Temperature :	23~24°C
Test Mode :	GSM Link for Sample 1	Relative Humidity :	49~52%
Test Engineer :	Cona Huang	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		




Trace: (Discrete)
 Site : 03CH05-HY
 Condition : FCC PART22H/24E HF_EIRP_101023 VERTICAL
 Power : DC 12V
 Project : FG 070628

Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
1672	-51.92	-13	-38.92	-34.43	-53.11	2.15	5.49	V	Pass
2509	-48.08	-13	-35.08	-33.66	-49.97	2.38	6.41	V	Pass
4182	-50.40	-13	-37.40	-41.05	-54.34	3.26	9.35	V	Pass
7527	-44.12	-13	-31.12	-46.57	-49.99	4.60	12.62	V	Pass




Band :	GSM1900	Temperature :	23~24°C
Test Mode :	GSM Link for Sample 2	Relative Humidity :	49~52%
Test Engineer :	Cona Huang	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-33.66	-13	-20.66	-21.77	-39.79	2.92	9.06	H	Pass
5636	-27.51	-13	-14.51	-22.9	-34.43	3.90	10.83	H	Pass
7520	-30.66	-13	-17.66	-32.25	-38.68	4.59	12.62	H	Pass
9396	-24.68	-13	-11.68	-26.2	-32.64	5.39	13.36	H	Pass
11280	-41.87	-13	-28.87	-47.94	-49.28	5.93	13.34	H	Pass
13160	-40.49	-13	-27.49	-48.7	-47.55	6.42	13.49	H	Pass
15040	-41.06	-13	-28.06	-50.84	-48.37	6.67	13.98	H	Pass
16920	-39.98	-13	-26.98	-52.26	-45.76	7.6	13.38	H	Pass




Band :	GSM1900	Temperature :	23~24°C
Test Mode :	GSM Link for Sample 2	Relative Humidity :	49~52%
Test Engineer :	Cona Huang	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-27.73	-13	-14.73	-15.84	-33.86	2.92	9.06	V	Pass
5636	-21.90	-13	-8.90	-17.29	-28.82	3.90	10.83	V	Pass
7520	-34.66	-13	-21.66	-36.25	-42.68	4.59	12.62	V	Pass
9396	-19.90	-13	-6.90	-21.42	-27.86	5.39	13.36	V	Pass
11280	-35.94	-13	-22.94	-42.01	-43.35	5.93	13.34	V	Pass
13160	-32.38	-13	-19.38	-40.59	-39.44	6.42	13.49	V	Pass
15040	-31.04	-13	-18.04	-40.82	-38.35	6.67	13.98	V	Pass
16920	-35.84	-13	-22.84	-48.12	-41.62	7.6	13.38	V	Pass




Band :	GSM1900	Temperature :	23~24°C
Test Mode :	GSM Link for Sample 1	Relative Humidity :	49~52%
Test Engineer :	Cona Huang	Polarization :	Horizontal
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-36.21	-13	-23.21	-24.32	-42.34	2.92	9.06	H	Pass
5636	-25.27	-13	-12.27	-20.66	-32.19	3.90	10.83	H	Pass
7520	-28.34	-13	-15.34	-29.93	-36.36	4.59	12.62	H	Pass
9396	-42.79	-13	-29.79	-44.31	-50.75	5.39	13.36	H	Pass
11280	-38.58	-13	-25.58	-44.65	-45.99	5.93	13.34	H	Pass
15040	-42.10	-13	-29.10	-51.88	-49.41	6.67	13.98	H	Pass



Band :	GSM1900	Temperature :	23~24°C
Test Mode :	GSM Link for Sample 1	Relative Humidity :	49~52%
Test Engineer :	Cona Huang	Polarization :	Vertical
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.		



Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	Result
3760	-35.41	-13	-22.41	-23.52	-41.54	2.92	9.06	V	Pass
5636	-27.01	-13	-14.01	-22.4	-33.93	3.90	10.83	V	Pass
7520	-28.79	-13	-15.79	-30.38	-36.81	4.59	12.62	V	Pass
9396	-35.75	-13	-22.75	-37.27	-43.71	5.39	13.36	V	Pass
11280	-33.82	-13	-20.82	-39.89	-41.23	5.93	13.34	V	Pass
15040	-39.03	-13	-26.03	-48.81	-46.34	6.67	13.98	V	Pass

3.7 Frequency Stability Measurement

3.7.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.7.2 Measuring Instruments

See list of measuring instruments of this test report.


3.7.3 Test Procedures for Temperature Variation

1. The EUT was set up in the thermal chamber and connected with the base station.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized for three hours. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.
4. If the EUT can not be turned on at -30°C , the testing lowest temperature will be raised in 10°C step until the EUT can be turned on.

3.7.4 Test Procedures for Voltage Variation

1. The EUT was placed in a temperature chamber at $25\pm 5^{\circ}\text{C}$ and connected with the base station.
2. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

3.7.5 Test Setup



3.7.6 Test Result of Temperature Variation

Band :	GSM 850	Channel :	189
Limit (ppm) :	2.5		
Temperature (°C)	GSM		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	N/A	N/A	PASS
-20	14	0.02	
-10	-19	-0.02	
0	-24	-0.03	
10	-18	-0.02	
20	-33	-0.04	
30	-23	-0.03	
40	-28	-0.03	
50	-25	-0.03	

Note:

1. The EUT stops transmitting at temperatures -30°C.
2. The manufacturer declared that the EUT could work properly between temperatures -20°C~70°C.



Band :	GSM 1900	Channel :	661
Limit (ppm) :	2.5		

Temperature (°C)	GSM		Result
	Freq. Dev. (Hz)	Deviation (ppm)	
-30	N/A	N/A	PASS
-20	-14	-0.01	
-10	-20	-0.01	
0	-30	-0.02	
10	-16	-0.01	
20	-17	-0.01	
30	-26	-0.01	
40	-30	-0.02	
50	-45	-0.02	

Note:

1. The EUT stops transmitting at temperatures -30°C.
2. The manufacturer declared that the EUT could work properly between temperatures -20°C~70°C.

3.7.7 Test Result of Voltage Variation

Band & Channel	Mode	Voltage (Volt)	Freq. Dev. (Hz)	Deviation (ppm)	Limit (ppm)	Result
GSM 850 CH189	GSM	24	-41	-0.05	2.5	PASS
		9	-98	-0.12		
		40	-76	-0.09		
GSM 1900 CH661	GSM	24	-54	-0.03		
		9	-66	-0.03		
		40	-54	-0.03		

Note: Normal Voltage = 24V.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Due Date	Remark
System Simulator	R&S	CMU200	117995	N/A	Mar. 19, 2009	Mar. 18, 2011	Conducted (TH02-HY)
Spectrum Analyzer	R&S	FSP30	101329	9kHz~30GHz	Apr. 26, 2010	Apr. 25, 2011	Conducted (TH02-HY)
Thermal Chamber	Ten Billion	TTH-D35P	TBN-930701	N/A	Jul. 30,2010	Jul. 29, 2011	Conducted (TH02-HY)
Spectrum Analyzer	R&S	FSP30	101352	9KHz-40GHz	Nov. 02, 2009	Nov. 01, 2010	Radiation (03CH05-HY)
Amplifier	COM-POWER	PA-103	161069	1KHz - 1GHz	Mar. 29, 2010	Mar. 28, 2011	Radiation (03CH05-HY)
Bilog Antenna	SCHAFFNER	CBL6111C	2726	30MHz ~ 1GHz	Oct. 31, 2009	Oct. 30, 2010	Radiation (03CH05-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA917025 1	15GHz- 40GHz	Oct. 18, 2010	Oct. 17, 2011	Radiation (03CH05-HY)
Pre Amplifier	Agilent	8449B	3008A01917	1GHz- 26.5GHz	Nov. 11, 2009	Nov. 10, 2010	Radiation (03CH05-HY)
Turn Table	HD	Deis HD 2000	420/611	0 - 360 degree	N/A	N/A	Radiation (03CH05-HY)
Antenna Mast	HD	MA 240	240/666	1 m - 4 m	N/A	N/A	Radiation (03CH05-HY)
Horn Antenna	ESCO	3117	00066584	1GHz ~ 18GHz	Aug. 05, 2010	Aug. 04, 2011	Radiation (03CH05-HY)
Horn Antenna	Training Research	AH-0801	95119	8GHz~18GHz	Nov. 02, 2009	Nov. 01, 2010	Radiation (03CH05-HY)
Loop Antenna	R&S	HFH2-Z2	860004/001	9 kHz~30 MHz	Jul. 29, 2010	Jul. 28, 2011	Radiation (03CH05-HY)
System Simulator	R&S	CMU200	117997	N/A	May 14, 2009	May 13, 2011	Radiation (03CH05-HY)

5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Contribution	Uncertainty of X_i		$u(X_i)$
	dB	Probability Distribution	
Receiver Reading	0.41	Normal (k=2)	0.21
Antenna Factor Calibration	0.83	Normal (k=2)	0.42
Cable Loss Calibration	0.25	Normal (k=2)	0.13
Pre-Amplifier Gain Calibration	0.27	Normal (k=2)	0.14
RCV/SPA Specification	2.50	Rectangular	0.72
Antenna Factor Interpolation for Frequency	1.00	Rectangular	0.29
Site Imperfection	1.43	Rectangular	0.83
Mismatch	+0.39 / -0.41	U-Shape	0.28
Combined Standard Uncertainty $Uc(y)$	1.27		
Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.54		

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Contribution	Uncertainty of X_i		$u(X_i)$	C_i	$C_i * u(X_i)$
	dB	Probability Distribution			
Receiver Reading	± 0.10	Normal (k=2)	0.10	1	0.10
Antenna Factor Calibration	± 1.70	Normal (k=2)	0.85	1	0.85
Cable Loss Calibration	± 0.50	Normal (k=2)	0.25	1	0.25
Receiver Correction	± 2.00	Rectangular	1.15	1	1.15
Antenna Factor Directional	± 1.50	Rectangular	0.87	1	0.87
Site Imperfection	± 2.80	Triangular	1.14	1	1.14
Mismatch Receiver VSWR $\Gamma_1 = 0.197$ Antenna VSWR $\Gamma_2 = 0.194$ Uncertainty = $20\text{Log}(1-\Gamma_1*\Gamma_2)$	+0.34 / -0.35	U-Shape	0.244	1	0.244
Combined Standard Uncertainty $Uc(y)$	2.36				
Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.72				



Appendix A. Photographs of EUT

Please refer to Sporton report number EP070628 as below.