

FCC Test Report (BT-LE)

Report No.: RFBCYA-WTW-P21030934-3

FCC ID: YAIWB17

Test Model: WB17

Received Date: Mar. 25, 2021

Test Date: May 24 to June 16, 2021

Issued Date: July 21, 2021

Applicant: InnoComm Mobile Technology Corporation

Address: 3F, No. 6, Hsin Ann Rd., Hsinchu Science Park, Hsinchu 300092, Taiwan

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan

Test Location: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan

**FCC Registration /
Designation Number:** 723255 / TW2022



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Table of Contents

Release Control Record	4
1 Certificate of Conformity.....	5
2 Summary of Test Results	6
2.1 Measurement Uncertainty	6
2.2 Modification Record	6
3 General Information.....	7
3.1 General Description of EUT (BT-LE)	7
3.2 Description of Test Modes	9
3.2.1 Test Mode Applicability and Tested Channel Detail	10
3.3 Duty Cycle of Test Signal	12
3.4 Description of Support Units	13
3.4.1 Configuration of System under Test	13
3.5 General Description of Applied Standards and References	14
4 Test Types and Results	15
4.1 Radiated Emission and Bandedge Measurement.....	15
4.1.1 Limits of Radiated Emission and Bandedge Measurement	15
4.1.2 Test Instruments	16
4.1.3 Test Procedures.....	20
4.1.4 Deviation from Test Standard	20
4.1.5 Test Setup.....	21
4.1.6 EUT Operating Conditions.....	22
4.1.7 Test Results (Mode 1).....	23
4.1.8 Test Results (Mode 2).....	31
4.2 Conducted Emission Measurement	39
4.2.1 Limits of Conducted Emission Measurement	39
4.2.2 Test Instruments	39
4.2.3 Test Procedures.....	40
4.2.4 Deviation from Test Standard	40
4.2.5 Test Setup.....	40
4.2.6 EUT Operating Conditions.....	40
4.2.7 Test Results	41
4.3 6dB Bandwidth Measurement	43
4.3.1 Limits of 6dB Bandwidth Measurement	43
4.3.2 Test Setup.....	43
4.3.3 Test Instruments	43
4.3.4 Test Procedure	43
4.3.5 Deviation from Test Standard	43
4.3.6 EUT Operating Conditions.....	43
4.3.7 Test Results	44
4.4 Conducted Output Power Measurement.....	45
4.4.1 Limits of Conducted Output Power Measurement	45
4.4.2 Test Setup.....	45
4.4.3 Test Instruments	45
4.4.4 Test Procedures.....	45
4.4.5 Deviation from Test Standard	45
4.4.6 EUT Operating Conditions.....	45
4.4.7 Test Results	46
4.5 Power Spectral Density Measurement.....	47
4.5.1 Limits of Power Spectral Density Measurement	47
4.5.2 Test Setup.....	47
4.5.3 Test Instruments	47
4.5.4 Test Procedure	47
4.5.5 Deviation from Test Standard	47

4.5.6 EUT Operating Condition	47
4.5.7 Test Results	48
4.6 Conducted Out of Band Emission Measurement	49
4.6.1 Limits of Conducted Out of Band Emission Measurement.....	49
4.6.2 Test Setup.....	49
4.6.3 Test Instruments	49
4.6.4 Test Procedure	49
4.6.5 Deviation from Test Standard	49
4.6.6 EUT Operating Condition	49
4.6.7 Test Results	49
5 Pictures of Test Arrangements.....	52
Annex A - Band-Edge Measurement.....	53
Appendix – Information of the Testing Laboratories	57

Release Control Record

Issue No.	Description	Date Issued
RFBCYA-WTW-P21030934-3	Original release.	July 21, 2021

1 Certificate of Conformity

Product: Wireless Audio Module

Brand: InnoComm

Test Model: WB17

Sample Status: Engineering sample

Applicant: InnoComm Mobile Technology Corporation

Test Date: May 24 to June 16, 2021

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.247)
ANSI C63.10: 2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :  , **Date:** July 21, 2021
Claire Kuan / Specialist

Approved by :  , **Date:** July 21, 2021
Clark Lin / Technical Manager

2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.247)			
FCC Clause	Test Item	Result	Remarks
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -12.17 dB at 0.56797 MHz.
15.205 / 15.209 / 15.247(d)	Radiated Emissions and Band Edge Measurement	PASS	Meet the requirement of limit. Minimum passing margin is -8.6 dB at 2390.00 MHz.
15.247(d)	Antenna Port Emission	PASS	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	Antenna connector is i-pex(MHF) not a standard connector.

Note:

- For 2.4 GHz band compliance with rule 15.247(d) of the band-edge items, the test plots were recorded in Annex A.
- Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (±)
Conducted Emissions at mains ports	150kHz ~ 30MHz	1.9 dB
Conducted emissions	-	2.5 dB
Radiated Emissions up to 1 GHz	9kHz ~ 30MHz	3.1 dB
	30MHz ~ 1GHz	5.4 dB
Radiated Emissions above 1 GHz	1GHz ~ 18GHz	5.0 dB
	18GHz ~ 40GHz	5.3 dB

2.2 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 General Description of EUT (BT-LE)

Product	Wireless Audio Module
Brand	InnoComm
Test Model	WB17
Status of EUT	Engineering sample
Power Supply Rating	5 Vdc from host equipment
Modulation Type	GFSK
Modulation Technology	DTS
Transfer Rate	Up to 2 Mbps
Operating Frequency	2.402 ~ 2.480 GHz
Number of Channel	40
Output Power	8.851 mW
Antenna Type	Refer to Note
Antenna Connector	Refer to Note
Accessory Device	NA
Data Cable Supplied	NA

Note:

1. There are Bluetooth and WLAN (2.4GHz & 5GHz) technology used for the EUT.
2. Simultaneously transmission condition.

Condition	Technology	
1	WLAN (2.4GHz)	Bluetooth
2	WLAN (5GHz)	Bluetooth

Note: The emission of the simultaneous operation has been evaluated and no non-compliance was found.

3. The antennas provided to the EUT, please refer to the following table:

Antenna Set	RF Chain No.	Antenna Net Gain (dBi)	Frequency Range (GHz)	Antenna Type	Connector Type	Cable Length (mm)
Ant. Set 1	0	5.26	2.4~2.4835GHz	PCB	i-pex(MHF)	172
		6.27	5.15~5.85GHz			
	1	5.26	2.4~2.4835GHz	PCB	i-pex(MHF)	172
		6.27	5.15~5.85GHz			
	BT	5.26	2.4~2.4835GHz	PCB	i-pex(MHF)	172
Ant. Set 2	0	5	2.4~2.4835GHz	Dipole	i-pex(MHF)	NA
		5	5.15~5.85GHz			
	1	5	2.4~2.4835GHz	Dipole	i-pex(MHF)	NA
		5	5.15~5.85GHz			
	BT	5	2.4~2.4835GHz	PCB	i-pex(MHF)	NA
Ant. Set 3	0	-0.96	2.4~2.4835GHz	PCB	i-pex(MHF)	520
		-1.35	5.15~5.85GHz			
	1	-0.96	2.4~2.4835GHz	PCB	i-pex(MHF)	520
		-1.35	5.15~5.85GHz			
	BT	-0.96	2.4~2.4835GHz	PCB	i-pex(MHF)	520
Ant. Set 4	0	4.56	2.4~2.4835GHz	PCB	i-pex(MHF)	210
		2.09	5.15~5.85GHz			
	1	4.56	2.4~2.4835GHz	PCB	i-pex(MHF)	210
		2.09	5.15~5.85GHz			
	BT	4.56	2.4~2.4835GHz	PCB	i-pex(MHF)	210
Ant. Set 5	0	2.9	2.4~2.4835GHz	PCB	i-pex(MHF)	250
		2.77	5.15~5.85GHz			
	1	2.9	2.4~2.4835GHz	PCB	i-pex(MHF)	250
		2.77	5.15~5.85GHz			
	BT	2.9	2.4~2.4835GHz	PCB	i-pex(MHF)	250
Ant. Set 6	0	0.94	2.4~2.4835GHz	PCB	i-pex(MHF)	300
		2.91	5.15~5.85GHz			
	1	0.94	2.4~2.4835GHz	PCB	i-pex(MHF)	300
		2.91	5.15~5.85GHz			
	BT	0.94	2.4~2.4835GHz	PCB	i-pex(MHF)	300
Ant. Set 7	0	4.42	2.4~2.4835GHz	PCB	i-pex(MHF)	387
		3.76	5.15~5.85GHz			
	1	4.42	2.4~2.4835GHz	PCB	i-pex(MHF)	387
		3.76	5.15~5.85GHz			
	BT	4.42	2.4~2.4835GHz	PCB	i-pex(MHF)	387
Ant. Set 8	0	2.76	2.4~2.4835GHz	PCB	i-pex(MHF)	245
		-	5.15~5.85GHz			
	1	2.76	2.4~2.4835GHz	PCB	i-pex(MHF)	24
		-	5.15~5.85GHz			
	BT	2.66	2.4~2.4835GHz	PCB	i-pex(MHF)	245
Ant. Set 9	0	5.13	2.4~2.4835GHz	PCB	i-pex(MHF)	228
		-	5.15~5.85GHz			
	1	5.13	2.4~2.4835GHz	PCB	i-pex(MHF)	228
		-	5.15~5.85GHz			
	BT	5.13	2.4~2.4835GHz	PCB	i-pex(MHF)	228

Note: Antenna Set. 1 & 2 was selected for final test.

4. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

5. The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

3.2 Description of Test Modes

40 channels are provided to this EUT:

CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

3.2.1 Test Mode Applicability and Tested Channel Detail

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE $\geq$ 1G	RE<1G	PLC	APCM	
1	√	√	-	-	With Dipole antenna (Ant. Set 2)
2	√	√	√	√	With PCB antenna (Ant. Set 1)

Where **RE $\geq$ 1G:** Radiated Emission above 1GHz & Bandedge Measurement

RE<1G: Radiated Emission below 1GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

Note: The EUT's PCB antenna had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **Z-place**.

Radiated Emission Test (Above 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
0 to 39	0, 19, 39	GFSK	1
0 to 39	0, 19, 39	GFSK	2

Radiated Emission Test (Below 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
0 to 39	19	GFSK	1

Power Line Conducted Emission Test:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
0 to 39	19	GFSK	1

Antenna Port Conducted Measurement:

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
0 to 39	0, 19, 39	GFSK	1
0 to 39	0, 19, 39	GFSK	2

Test Condition:

Applicable to	Environmental Conditions	Input Power (System)	Tested By
RE $\geq$ 1G	25deg. C, 65%RH,	120Vac, 60Hz	Ryan Du Nelson Teng
RE<1G	25deg. C, 65%RH,	120Vac, 60Hz	Ryan Du
PLC	25deg. C, 75%RH	120Vac, 60Hz	Ryan Du
APCM	25deg. C, 60%RH	120Vac, 60Hz	Kevin Ko

3.3 Duty Cycle of Test Signal

Duty cycle of test signal is < 98 %, duty factor shall be considered.

BT-LE 1M: Duty cycle = 0.404 ms/1.243 ms = 0.325, Duty factor = $10 \cdot \log(1/\text{Duty cycle}) = 4.88 \text{ dB}$

BT-LE 2M: Duty cycle = 2.141 ms/3.72 ms = 0.576, Duty factor = $10 \cdot \log(1/\text{Duty cycle}) = 2.40 \text{ dB}$




3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	Laptop	Lenovo	20U5S01X00 L14	PF-28LKK7	NA	Provided by Lab
B.	Test Tool	INNOCOMM	N/A	NA	NA	Supplied by client
C.	Adapter	Lenovo	ADLX45YLC3D	NA	NA	Provided by Lab

ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	DC Cable	1	1.8	No	0	Provided by Lab
2.	AC Cable	1	0.9	No	0	Provided by Lab
3.	Micro USB Cable	1	1	Yes	0	Provided by Lab
4.	Micro USB Cable	1	1.2	Yes	0	Provided by Lab

3.4.1 Configuration of System under Test



3.5 General Description of Applied Standards and References

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards and references:

Test Standard:

FCC Part 15, Subpart C (15.247)

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

References Test Guidance:

KDB 558074 D01 15.247 Meas Guidance v05r02

All test items have been performed as a reference to the above KDB test guidance.

4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

Note:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.1.2 Test Instruments

For Radiated Emission below 1GHz test:

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver Keysight	N9038A	MY54450088	July 06, 2020	July 05, 2021
Pre-Amplifier EMCI	EMC001340	980142	May 24, 2021	May 23, 2022
Loop Antenna Electro-Metrics	EM-6879	264	Mar. 05, 2021	Mar. 04, 2022
RF Cable	5D-FB	LOOPCAB-001	Jan. 07, 2021	Jan. 06, 2022
RF Cable	5D-FB	LOOPCAB-002	Jan. 07, 2021	Jan. 06, 2022
Pre-Amplifier Mini-Circuits	ZFL-1000VH2	QA0838008	Oct. 20, 2020	Oct. 19, 2021
Trilog Broadband Antenna SCHWARZBECK	VULB 9168	9168-361	Nov. 05, 2020	Nov. 04, 2021
RF Cable	8D	966-3-1	Mar. 16, 2021	Mar. 15, 2022
RF Cable	8D	966-3-2	Mar. 16, 2021	Mar. 15, 2022
RF Cable	8D	966-3-3	Mar. 16, 2021	Mar. 15, 2022
Fixed attenuator Mini-Circuits	UNAT-5+	PAD-3m-3-01	Sep. 24, 2020	Sep. 23, 2021
Software	ADT_Radiated_V8.7.08	NA	NA	NA
Antenna Tower & Turn Table Max-Full	MF-7802	MF780208406	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in 966 Chamber No. 3.
3. Tested Date: May 29, 2021

For Radiated Emission above 1GHz (BT-LE 1M) test:

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver Keysight	N9038A	MY54450088	July 06, 2020	July 05, 2021
Horn_Antenna SCHWARZBECK	BBHA9120-D	9120D-406	Nov. 22, 2020	Nov. 21, 2021
Pre-Amplifier EMCI	EMC12630SE	980384	Jan. 11, 2021	Jan. 10, 2022
RF Cable	EMC104-SM-SM-1500	180504	Apr. 26, 2021	Apr. 25, 2022
RF Cable	EMC104-SM-SM-2000	180601	June 09, 2020	June 08, 2021
RF Cable	EMC104-SM-SM-6000	180602	June 09, 2020	June 08, 2021
Spectrum Analyzer Keysight	N9030A	MY54490679	July 13, 2020	July 12, 2021
Pre-Amplifier EMCI	EMC184045SE	980387	Jan. 11, 2021	Jan. 10, 2022
Horn_Antenna SCHWARZBECK	BBHA 9170	BBHA9170519	Nov. 22, 2020	Nov. 21, 2021
RF Cable	EMC102-KM-KM-1200	160924	Jan. 11, 2021	Jan. 10, 2022
RF Cable	EMC-KM-KM-4000	200214	Mar. 10, 2021	Mar. 09, 2022
Software	ADT_Radiated_V8.7.08	NA	NA	NA
Antenna Tower & Turn Table Max-Full	MF-7802	MF780208406	NA	NA
Boresight Antenna Fixture	FBA-01	FBA-SIP01	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in 966 Chamber No. 3.
3. Tested Date: May 24 to 28, 2021

For Radiated Emission above 1GHz (BT-LE 2M) test:

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver Keysight	N9038A	MY54450088	July 06, 2020	July 05, 2021
Horn_Antenna SCHWARZBECK	BBHA9120-D	9120D-406	Nov. 22, 2020	Nov. 21, 2021
Pre-Amplifier EMCI	EMC12630SE	980384	Jan. 11, 2021	Jan. 10, 2022
RF Cable	EMC104-SM-SM-1500	180504	Apr. 26, 2021	Apr. 25, 2022
RF Cable	EMC104-SM-SM-2000	180601	June 08, 2021	June 07, 2022
RF Cable	EMC104-SM-SM-6000	210201	May 13, 2021	May 12, 2022
Spectrum Analyzer Keysight	N9030A	MY54490679	July 13, 2020	July 12, 2021
Pre-Amplifier EMCI	EMC184045SE	980387	Jan. 11, 2021	Jan. 10, 2022
Horn_Antenna SCHWARZBECK	BBHA 9170	BBHA9170519	Nov. 22, 2020	Nov. 21, 2021
RF Cable	EMC102-KM-KM-1200	160924	Jan. 11, 2021	Jan. 10, 2022
RF Cable	EMC-KM-KM-4000	200214	Mar. 10, 2021	Mar. 09, 2022
Software	ADT_Radiated_V8.7.08	NA	NA	NA
Antenna Tower & Turn Table Max-Full	MF-7802	MF780208406	NA	NA
Boresight Antenna Fixture	FBA-01	FBA-SIP01	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in 966 Chamber No. 3.
3. Tested Date: June 15 to 16, 2021

For other test items:

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Spectrum Analyzer R&S	FSV40	101516	Mar. 08, 2021	Mar. 07, 2022
Power meter Anritsu	ML2495A	1529002	July 22, 2020	July 21, 2021
Power sensor Anritsu	MA2411B	1339443	July 22, 2020	July 21, 2021
10dB Attenuator Woken	MDCS18N-10	MDCS18N-10-01	Apr. 13, 2021	Apr. 12, 2022
Software	ADT_RF Test Software V6.6.5.4	NA	NA	NA

- NOTE:**
1. The test was performed in Oven room 2.
 2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 3. Tested Date: June 03, 2021

4.1.3 Test Procedures

For Radiated emission below 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

For Radiated emission above 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $< 98\%$) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 Deviation from Test Standard


No deviation.

4.1.5 Test Setup


For Radiated emission below 30MHz



For Radiated emission 30MHz to 1GHz



For Radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT Operating Conditions

- Placed the EUT on the testing table.
- Controlling software (adb paste command BT+BLE SOP.doc) has been activated to set the EUT under transmission condition continuously at specific channel frequency.

4.1.7 Test Results (Mode 1)

Above 1GHz Data:

BT-LE 1M

RF Mode	TX BT_LE-1M	Channel	CH 0 : 2402 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2378.35	56.0 PK	74.0	-18.0	1.65 H	297	57.2	-1.2
2	2378.35	43.8 AV	54.0	-10.2	1.65 H	297	45.0	-1.2
3	*2402.00	98.7 PK			1.65 H	297	99.9	-1.2
4	*2402.00	97.5 AV			1.65 H	297	98.7	-1.2
5	4804.00	43.1 PK	74.0	-30.9	1.39 H	95	39.4	3.7
6	4804.00	32.9 AV	54.0	-21.1	1.39 H	95	29.2	3.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2351.23	56.1 PK	74.0	-17.9	1.27 V	147	57.2	-1.1
2	2351.23	43.6 AV	54.0	-10.4	1.27 V	147	44.7	-1.1
3	*2402.00	104.0 PK			1.27 V	147	105.2	-1.2
4	*2402.00	103.0 AV			1.27 V	147	104.2	-1.2
5	4804.00	41.7 PK	74.0	-32.3	1.73 V	173	38.0	3.7
6	4804.00	30.6 AV	54.0	-23.4	1.73 V	173	26.9	3.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX BT_LE-1M	Channel	CH 19 : 2440 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.00	98.2 PK			1.71 H	293	99.4	-1.2
2	*2440.00	97.0 AV			1.71 H	293	98.2	-1.2
3	4880.00	42.8 PK	74.0	-31.2	1.39 H	84	39.0	3.8
4	4880.00	32.6 AV	54.0	-21.4	1.39 H	84	28.8	3.8
5	7320.00	45.4 PK	74.0	-28.6	1.61 H	127	35.8	9.6
6	7320.00	32.4 AV	54.0	-21.6	1.61 H	127	22.8	9.6
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.00	104.3 PK			1.33 V	141	105.5	-1.2
2	*2440.00	103.0 AV			1.33 V	141	104.2	-1.2
3	4880.00	42.3 PK	74.0	-31.7	1.84 V	181	38.5	3.8
4	4880.00	31.2 AV	54.0	-22.8	1.84 V	181	27.4	3.8
5	7320.00	45.6 PK	74.0	-28.4	2.01 V	136	36.0	9.6
6	7320.00	33.3 AV	54.0	-20.7	2.01 V	136	23.7	9.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX BT_LE-1M	Channel	CH 39 : 2480 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	98.8 PK			1.77 H	306	99.9	-1.1
2	*2480.00	97.4 AV			1.77 H	306	98.5	-1.1
3	2483.50	54.5 PK	74.0	-19.5	1.77 H	306	55.6	-1.1
4	2483.50	43.6 AV	54.0	-10.4	1.77 H	306	44.7	-1.1
5	4960.00	43.3 PK	74.0	-30.7	1.40 H	112	39.3	4.0
6	4960.00	33.0 AV	54.0	-21.0	1.40 H	112	29.0	4.0
7	7440.00	45.4 PK	74.0	-28.6	1.58 H	137	35.7	9.7
8	7440.00	32.5 AV	54.0	-21.5	1.58 H	137	22.8	9.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	104.6 PK			1.24 V	157	105.7	-1.1
2	*2480.00	103.6 AV			1.24 V	157	104.7	-1.1
3	2483.50	55.9 PK	74.0	-18.1	1.24 V	157	57.0	-1.1
4	2483.50	44.0 AV	54.0	-10.0	1.24 V	157	45.1	-1.1
5	4960.00	42.0 PK	74.0	-32.0	1.78 V	175	38.0	4.0
6	4960.00	30.7 AV	54.0	-23.3	1.78 V	175	26.7	4.0
7	7440.00	44.5 PK	74.0	-29.5	2.01 V	120	34.8	9.7
8	7440.00	32.8 AV	54.0	-21.2	2.01 V	120	23.1	9.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

BT-LE 2M

RF Mode	TX BT_LE-2M	Channel	CH 0 : 2402 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	54.8 PK	74.0	-19.2	1.08 H	65	56.0	-1.2
2	2390.00	43.5 AV	54.0	-10.5	1.08 H	65	44.7	-1.2
3	*2402.00	97.8 PK			1.08 H	65	99.0	-1.2
4	*2402.00	93.8 AV			1.08 H	65	95.0	-1.2
5	4804.00	43.7 PK	74.0	-30.3	1.46 H	108	40.0	3.7
6	4804.00	33.2 AV	54.0	-20.8	1.46 H	108	29.5	3.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	54.9 PK	74.0	-19.1	1.57 V	341	56.1	-1.2
2	2390.00	43.5 AV	54.0	-10.5	1.57 V	341	44.7	-1.2
3	*2402.00	101.2 PK			1.57 V	341	102.4	-1.2
4	*2402.00	97.3 AV			1.57 V	341	98.5	-1.2
5	4804.00	41.6 PK	74.0	-32.4	1.77 V	164	37.9	3.7
6	4804.00	30.2 AV	54.0	-23.8	1.77 V	164	26.5	3.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX BT_LE-2M	Channel	CH 19 : 2440 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.00	97.4 PK			1.29 H	103	98.6	-1.2
2	*2440.00	92.6 AV			1.29 H	103	93.8	-1.2
3	4880.00	43.9 PK	74.0	-30.1	1.39 H	116	40.1	3.8
4	4880.00	33.4 AV	54.0	-20.6	1.39 H	116	29.6	3.8
5	7320.00	44.8 PK	74.0	-29.2	1.54 H	124	35.1	9.7
6	7320.00	32.1 AV	54.0	-21.9	1.54 H	124	22.4	9.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.00	101.1 PK			1.28 V	82	102.3	-1.2
2	*2440.00	97.4 AV			1.28 V	82	98.6	-1.2
3	4880.00	42.1 PK	74.0	-31.9	1.73 V	182	38.3	3.8
4	4880.00	30.7 AV	54.0	-23.3	1.73 V	182	26.9	3.8
5	7320.00	44.8 PK	74.0	-29.2	1.99 V	134	35.1	9.7
6	7320.00	33.3 AV	54.0	-20.7	1.99 V	134	23.6	9.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX BT_LE-2M	Channel	CH 39 : 2480 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	97.3 PK			1.31 H	105	98.5	-1.2
2	*2480.00	92.7 AV			1.31 H	105	93.9	-1.2
3	2483.50	54.7 PK	74.0	-19.3	1.31 H	105	55.9	-1.2
4	2483.50	43.5 AV	54.0	-10.5	1.31 H	105	44.7	-1.2
5	4960.00	43.2 PK	74.0	-30.8	1.42 H	115	39.2	4.0
6	4960.00	32.7 AV	54.0	-21.3	1.42 H	115	28.7	4.0
7	7440.00	45.5 PK	74.0	-28.5	1.54 H	124	35.8	9.7
8	7440.00	32.5 AV	54.0	-21.5	1.54 H	124	22.8	9.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	101.3 PK			1.23 V	88	102.5	-1.2
2	*2480.00	97.5 AV			1.23 V	88	98.7	-1.2
3	2483.50	54.6 PK	74.0	-19.4	1.23 V	88	55.8	-1.2
4	2483.50	44.1 AV	54.0	-9.9	1.23 V	88	45.3	-1.2
5	4960.00	42.6 PK	74.0	-31.4	1.81 V	184	38.6	4.0
6	4960.00	31.2 AV	54.0	-22.8	1.81 V	184	27.2	4.0
7	7440.00	44.4 PK	74.0	-29.6	2.01 V	126	34.7	9.7
8	7440.00	32.5 AV	54.0	-21.5	2.01 V	126	22.8	9.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.


Below 1GHz Data:

RF Mode	TX BT_LE-1M	Channel	CH 19 : 2440 MHz
Frequency Range	9kHz ~ 1GHz	Detector Function	Quasi-Peak (QP)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	30.41	29.2 QP	40.0	-10.8	1.50 H	42	38.6	-9.4
2	60.71	28.2 QP	40.0	-11.8	1.50 H	37	37.1	-8.9
3	88.23	30.1 QP	43.5	-13.4	2.50 H	241	44.0	-13.9
4	139.36	30.5 QP	43.5	-13.0	2.00 H	227	38.6	-8.1
5	214.12	26.3 QP	43.5	-17.2	2.00 H	147	36.9	-10.6
6	458.91	26.5 QP	46.0	-19.5	1.50 H	45	28.4	-1.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.




RF Mode	TX BT_LE-1M	Channel	CH 19 : 2440 MHz
Frequency Range	9kHz ~ 1GHz	Detector Function	Quasi-Peak (QP)

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	61.12	31.3 QP	40.0	-8.7	1.00 V	142	40.4	-9.1
2	84.96	26.5 QP	40.0	-13.5	1.50 V	55	40.2	-13.7
3	110.09	25.4 QP	43.5	-18.1	1.00 V	167	36.3	-10.9
4	146.78	25.3 QP	43.5	-18.2	1.50 V	163	32.9	-7.6
5	185.88	24.4 QP	43.5	-19.1	1.00 V	142	34.2	-9.8
6	539.82	29.3 QP	46.0	-16.7	1.00 V	133	29.7	-0.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.



4.1.8 Test Results (Mode 2)

Above 1GHz Data:

BT-LE 1M

RF Mode	TX BT_LE-1M	Channel	CH 0 : 2402 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2340.81	56.3 PK	74.0	-17.7	1.48 H	192	57.4	-1.1
2	2340.81	44.9 AV	54.0	-9.1	1.48 H	192	46.0	-1.1
3	*2402.00	102.2 PK			1.48 H	192	103.4	-1.2
4	*2402.00	101.0 AV			1.48 H	192	102.2	-1.2
5	4804.00	42.4 PK	74.0	-31.6	1.29 H	154	38.7	3.7
6	4804.00	32.0 AV	54.0	-22.0	1.29 H	154	28.3	3.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2352.45	56.6 PK	74.0	-17.4	3.37 V	278	57.7	-1.1
2	2352.45	44.9 AV	54.0	-9.1	3.37 V	278	46.0	-1.1
3	*2402.00	96.3 PK			3.37 V	278	97.5	-1.2
4	*2402.00	94.9 AV			3.37 V	278	96.1	-1.2
5	4804.00	41.6 PK	74.0	-32.4	1.59 V	119	37.9	3.7
6	4804.00	31.2 AV	54.0	-22.8	1.59 V	119	27.5	3.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX BT_LE-1M	Channel	CH 19 : 2440 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.00	105.5 PK			1.46 H	195	106.7	-1.2
2	*2440.00	104.4 AV			1.46 H	195	105.6	-1.2
3	4880.00	42.4 PK	74.0	-31.6	1.24 H	162	38.6	3.8
4	4880.00	32.1 AV	54.0	-21.9	1.24 H	162	28.3	3.8
5	7320.00	44.8 PK	74.0	-29.2	1.83 H	205	35.2	9.6
6	7320.00	32.2 AV	54.0	-21.8	1.83 H	205	22.6	9.6
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.00	102.0 PK			3.39 V	276	103.2	-1.2
2	*2440.00	100.7 AV			3.39 V	276	101.9	-1.2
3	4880.00	42.0 PK	74.0	-32.0	1.63 V	114	38.2	3.8
4	4880.00	31.1 AV	54.0	-22.9	1.63 V	114	27.3	3.8
5	7320.00	45.0 PK	74.0	-29.0	2.63 V	75	35.4	9.6
6	7320.00	32.8 AV	54.0	-21.2	2.63 V	75	23.2	9.6

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX BT_LE-1M	Channel	CH 39 : 2480 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	106.0 PK			1.46 H	196	107.1	-1.1
2	*2480.00	104.8 AV			1.46 H	196	105.9	-1.1
3	2483.50	56.2 PK	74.0	-17.8	1.46 H	196	57.3	-1.1
4	2483.50	44.6 AV	54.0	-9.4	1.46 H	196	45.7	-1.1
5	4960.00	42.1 PK	74.0	-31.9	1.32 H	156	38.1	4.0
6	4960.00	31.9 AV	54.0	-22.1	1.32 H	156	27.9	4.0
7	7440.00	45.2 PK	74.0	-28.8	1.71 H	222	35.5	9.7
8	7440.00	32.3 AV	54.0	-21.7	1.71 H	222	22.6	9.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	101.8 PK			3.44 V	272	102.9	-1.1
2	*2480.00	100.5 AV			3.44 V	272	101.6	-1.1
3	2483.50	55.1 PK	74.0	-18.9	3.44 V	272	56.2	-1.1
4	2483.50	44.6 AV	54.0	-9.4	3.44 V	272	45.7	-1.1
5	4960.00	41.5 PK	74.0	-32.5	1.61 V	120	37.5	4.0
6	4960.00	31.1 AV	54.0	-22.9	1.61 V	120	27.1	4.0
7	7440.00	45.3 PK	74.0	-28.7	2.67 V	82	35.6	9.7
8	7440.00	33.0 AV	54.0	-21.0	2.67 V	82	23.3	9.7

BT-LE 2M

RF Mode	TX BT_LE-2M	Channel	CH 0 : 2402 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	56.5 PK	74.0	-17.5	1.59 H	187	57.7	-1.2
2	2390.00	45.4 AV	54.0	-8.6	1.59 H	187	46.6	-1.2
3	*2402.00	97.8 PK			1.59 H	187	99.0	-1.2
4	*2402.00	94.7 AV			1.59 H	187	95.9	-1.2
5	4804.00	41.6 PK	74.0	-32.4	1.89 H	193	37.8	3.8
6	4804.00	30.5 AV	54.0	-23.5	1.89 H	193	26.7	3.8
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	54.7 PK	74.0	-19.3	1.16 V	258	55.9	-1.2
2	2390.00	45.4 AV	54.0	-8.6	1.16 V	258	46.6	-1.2
3	*2402.00	96.3 PK			1.16 V	258	97.5	-1.2
4	*2402.00	93.1 AV			1.16 V	258	94.3	-1.2
5	4804.00	42.5 PK	74.0	-31.5	1.79 V	179	38.7	3.8
6	4804.00	30.9 AV	54.0	-23.1	1.79 V	179	27.1	3.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX BT_LE-2M	Channel	CH 19 : 2440 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.00	97.5 PK			1.56 H	202	98.7	-1.2
2	*2440.00	94.4 AV			1.56 H	202	95.6	-1.2
3	4880.00	42.1 PK	74.0	-31.9	1.87 H	196	38.3	3.8
4	4880.00	30.9 AV	54.0	-23.1	1.87 H	196	27.1	3.8
5	7320.00	44.5 PK	74.0	-29.5	2.03 H	123	34.8	9.7
6	7320.00	32.8 AV	54.0	-21.2	2.03 H	123	23.1	9.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.00	97.3 PK			1.13 V	253	98.5	-1.2
2	*2440.00	94.1 AV			1.13 V	253	95.3	-1.2
3	4880.00	42.3 PK	74.0	-31.7	1.77 V	168	38.5	3.8
4	4880.00	30.8 AV	54.0	-23.2	1.77 V	168	27.0	3.8
5	7320.00	44.5 PK	74.0	-29.5	1.94 V	128	34.8	9.7
6	7320.00	33.0 AV	54.0	-21.0	1.94 V	128	23.3	9.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

RF Mode	TX BT_LE-2M	Channel	CH 39 : 2480 MHz
Frequency Range	1GHz ~ 25GHz	Detector Function	Peak (PK) Average (AV)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	100.4 PK			1.66 H	173	101.6	-1.2
2	*2480.00	96.3 AV			1.66 H	173	97.5	-1.2
3	2483.50	56.1 PK	74.0	-17.9	1.66 H	173	57.3	-1.2
4	2483.50	45.2 AV	54.0	-8.8	1.66 H	173	46.4	-1.2
5	4960.00	43.2 PK	74.0	-30.8	1.86 H	194	39.2	4.0
6	4960.00	31.5 AV	54.0	-22.5	1.86 H	194	27.5	4.0
7	7440.00	44.4 PK	74.0	-29.6	2.05 H	117	34.7	9.7
8	7440.00	32.2 AV	54.0	-21.8	2.05 H	117	22.5	9.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	97.1 PK			1.09 V	256	98.3	-1.2
2	*2480.00	93.8 AV			1.09 V	256	95.0	-1.2
3	2483.50	56.2 PK	74.0	-17.8	1.09 V	256	57.4	-1.2
4	2483.50	45.2 AV	54.0	-8.8	1.09 V	256	46.4	-1.2
5	4960.00	42.7 PK	74.0	-31.3	1.75 V	184	38.7	4.0
6	4960.00	31.2 AV	54.0	-22.8	1.75 V	184	27.2	4.0
7	7440.00	44.7 PK	74.0	-29.3	1.94 V	118	35.0	9.7
8	7440.00	33.0 AV	54.0	-21.0	1.94 V	118	23.3	9.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.


Below 1GHz Data:

RF Mode	TX BT_LE-2M	Channel	CH 19 : 2440 MHz
Frequency Range	9kHz ~ 1GHz	Detector Function	Quasi-Peak (QP)

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	30.86	29.5 QP	40.0	-10.5	1.50 H	57	39.0	-9.5
2	61.16	28.4 QP	40.0	-11.6	1.50 H	69	37.5	-9.1
3	88.75	30.2 QP	43.5	-13.3	2.50 H	143	44.0	-13.8
4	139.90	30.5 QP	43.5	-13.0	2.00 H	158	38.6	-8.1
5	214.60	26.4 QP	43.5	-17.1	2.00 H	146	37.0	-10.6
6	459.51	26.3 QP	46.0	-19.7	1.50 H	73	28.2	-1.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.




RF Mode	TX BT_LE-2M	Channel	CH 19 : 2440 MHz
Frequency Range	9kHz ~ 1GHz	Detector Function	Quasi-Peak (QP)

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	61.03	31.1 QP	40.0	-8.9	1.00 V	162	40.1	-9.0
2	84.89	26.3 QP	40.0	-13.7	1.50 V	68	40.0	-13.7
3	110.03	25.2 QP	43.5	-18.3	1.00 V	157	36.1	-10.9
4	146.71	25.1 QP	43.5	-18.4	1.50 V	197	32.7	-7.6
5	185.81	24.2 QP	43.5	-19.3	1.00 V	134	34.0	-9.8
6	539.73	29.1 QP	46.0	-16.9	1.00 V	162	29.5	-0.4

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.



4.2 Conducted Emission Measurement

4.2.1 Limits of Conducted Emission Measurement

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2.2 Test Instruments

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver R&S	ESCS 30	847124/029	Oct. 20, 2020	Oct. 19, 2021
Line-Impedance Stabilization Network (for EUT) R&S	ESH3-Z5	848773/004	Oct. 27, 2020	Oct. 26, 2021
Line-Impedance Stabilization Network (for Peripheral) R&S	ESH3-Z5	835239/001	Mar. 26, 2021	Mar. 25, 2022
50 ohms Terminator	50	3	Oct. 26, 2020	Oct. 25, 2021
RF Cable	5D-FB	COCCAB-001	Sep. 26, 2020	Sep. 25, 2021
Fixed attenuator EMCI	STI02-2200-10	005	Aug. 29, 2020	Aug. 28, 2021
Software BVADT	BVADT_Cond_V7.3.7.4	NA	NA	NA

Note:

1. The calibration interval of the above test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Conduction 1.
3. Tested Date: May 29, 2021

4.2.3 Test Procedures


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

4.2.4 Deviation from Test Standard

No deviation.

4.2.5 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT Operating Conditions

Same as 4.1.6.


4.2.7 Test Results

RF Mode	TX BT_LE-1M	Channel	CH 19 : 2440 MHz
Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15391	9.95	37.66	22.73	47.61	32.68	65.79	55.79	-18.18	-23.11
2	0.16172	9.95	37.34	18.54	47.29	28.49	65.38	55.38	-18.09	-26.89
3	0.17344	9.96	33.66	17.55	43.62	27.51	64.79	54.79	-21.17	-27.28
4	0.56406	10.00	28.67	21.81	38.67	31.81	56.00	46.00	-17.33	-14.19
5	1.96094	10.07	21.75	9.54	31.82	19.61	56.00	46.00	-24.18	-26.39
6	13.36719	10.73	18.25	11.87	28.98	22.60	60.00	50.00	-31.02	-27.40

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




RF Mode	TX BT_LE-1M	Channel	CH 19 : 2440 MHz
Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	9.92	40.42	24.38	50.34	34.30	66.00	56.00	-15.66	-21.70
2	0.16172	9.93	38.82	20.68	48.75	30.61	65.38	55.38	-16.63	-24.77
3	0.24766	9.95	24.48	8.58	34.43	18.53	61.84	51.84	-27.41	-33.31
4	0.56797	9.97	31.29	23.86	41.26	33.83	56.00	46.00	-14.74	-12.17
5	2.02734	10.04	23.81	14.05	33.85	24.09	56.00	46.00	-22.15	-21.91
6	11.76172	10.49	24.81	19.09	35.30	29.58	60.00	50.00	-24.70	-20.42

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




4.3 6dB Bandwidth Measurement

4.3.1 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 Test Setup



4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.3.4 Test Procedure

- a. Set resolution bandwidth (RBW) = 100kHz
- b. Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
- c. Trace mode = max hold.
- d. Sweep = auto couple.
- e. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

4.3.5 Deviation from Test Standard

No deviation.

4.3.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.


4.3.7 Test Results

BT-LE 1M

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
0	2402	0.72	0.5	Pass
19	2440	0.72	0.5	Pass
39	2480	0.71	0.5	Pass

BT-LE 2M

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
0	2402	1.26	0.5	Pass
19	2440	1.26	0.5	Pass
39	2480	1.27	0.5	Pass




4.4 Conducted Output Power Measurement

4.4.1 Limits of Conducted Output Power Measurement

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30dBm)

4.4.2 Test Setup



4.4.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.4.4 Test Procedures

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

Average power sensor was used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

4.4.5 Deviation from Test Standard

No deviation.

4.4.6 EUT Operating Conditions

Same as Item 4.3.6.

4.4.7 Test Results

FOR PEAK POWER

BT-LE 1M

Channel	Frequency (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass/Fail
0	2402	8.337	9.21	30	Pass
19	2440	8.851	9.47	30	Pass
39	2480	7.745	8.89	30	Pass

BT-LE 2M

Channel	Frequency (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass/Fail
0	2402	8.204	9.14	30	Pass
19	2440	8.091	9.08	30	Pass
39	2480	7.482	8.74	30	Pass

FOR AVERAGE POWER

BT-LE 1M

Channel	Frequency (MHz)	Average Power (mW)	Average Power (dBm)
0	2402	7.586	8.80
19	2440	8.054	9.06
39	2480	6.966	8.43

BT-LE 2M


Channel	Frequency (MHz)	Average Power (mW)	Average Power (dBm)
0	2402	7.261	8.61
19	2440	7.145	8.54
39	2480	6.683	8.25

4.5 Power Spectral Density Measurement

4.5.1 Limits of Power Spectral Density Measurement

The Maximum of Power Spectral Density Measurement is 8dBm in any 3 kHz.

4.5.2 Test Setup



4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.5.4 Test Procedure

- Set analyzer center frequency to DTS channel center frequency.
- Set the span to 1.5 times the DTS bandwidth.
- Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set the VBW $\geq 3 \times \text{RBW}$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.

4.5.5 Deviation from Test Standard

No deviation.

4.5.6 EUT Operating Condition

Same as Item 4.3.6.


4.5.7 Test Results

BT-LE 1M

Channel	Freq. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Pass /Fail
0	2402	-6.14	8	Pass
19	2440	-6.01	8	Pass
39	2480	-6.67	8	Pass

BT-LE 2M

Channel	Freq. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Pass /Fail
0	2402	-10.44	8	Pass
19	2440	-10.47	8	Pass
39	2480	-11.10	8	Pass




4.6 Conducted Out of Band Emission Measurement

4.6.1 Limits of Conducted Out of Band Emission Measurement

Below 20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 Test Setup



4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.6.4 Test Procedure

MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW $\geq$ 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

MEASUREMENT PROCEDURE OOB

1. Set RBW = 100 kHz.
2. Set VBW $\geq$ 300 kHz.
3. Detector = peak.
4. Sweep = auto couple.
5. Trace Mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum amplitude level.

4.6.5 Deviation from Test Standard

No deviation.

4.6.6 EUT Operating Condition



The software provided by client enabled the EUT to transmit and receive data at lowest and highest channel frequencies individually.

4.6.7 Test Results



The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.

BT-LE 1M



CH 0




CH 19




CH 39



CH 0 Band edge





CH 39 Band edge





BT-LE 2M



CH 0




CH 19




CH 39



CH 0 Band edge



CH 39 Band edge




5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).


Annex A - Band-Edge Measurement

Test Mode 1


BT-LE 1M




BT-LE 2M



Test Mode 2
BT-LE 1M



BT-LE 2M



Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---