



FCC PART 22 AND 90 TEST REPORT

For

Hytera Communications Corporation Limited

Hytera Tower, Hi-Tech Industrial Park North, 9108# Beihuan Road, Nanshan District, Shenzhen, People's Republic of China

FCC ID: YAMBD61XU1

Report Type: Original Report	Product Type: Digital Portable Radio
Report Number: RDG160919006-00A	
Report Date: 2016-09-26	
Reviewed By: Dean Liu RF Engineer	<i>Dean Liu</i>
Approved By: Ivan Cao Assistant Manager	<i>Ivan Cao</i>
Test Laboratory: Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.(Dongguan). This report may contain data or test methods that are not covered by the NVLAP accreditation scope and shall be marked with an asterisk "*" and noted.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
TEST FACILITY	4
SYSTEM TEST CONFIGURATION.....	5
DESCRIPTION OF TEST CONFIGURATION	5
SUPPORT EQUIPMENT LIST AND DETAILS	5
BLOCK DIAGRAM OF TEST SETUP	5
SUMMARY OF TEST RESULTS	6
FCC §1.1310 & §2.1093 - RF EXPOSURE.....	7
APPLICABLE STANDARD	7
TEST RESULT	7
FCC §2.1046 & § 22.727&§90.205- RF OUTPUT POWER	8
APPLICABLE STANDARD	8
TEST PROCEDURE	8
TEST EQUIPMENT LIST AND DETAILS.....	8
TEST DATA	8
FCC §2.1047 & §90.207 - MODULATION CHARACTERISTIC.....	10
APPLICABLE STANDARD	10
TEST PROCEDURE	10
TEST EQUIPMENT LIST AND DETAILS.....	10
TEST DATA	10
FCC §2.1049& §22.357 & § 22.731 & §90.209 & §90.210 – OCCUPIED BANDWIDTH & EMISSION MASK	14
APPLICABLE STANDARD	14
TEST EQUIPMENT LIST AND DETAILS.....	15
TEST PROCEDURE	15
TEST DATA	15
FCC §2.1051& §22.861 & §90.210 - SPURIOUS EMISSIONS AT ANTENNA TERMINALS.....	23
APPLICABLE STANDARD	23
TEST EQUIPMENT LIST AND DETAILS.....	23
TEST PROCEDURE	24
TEST DATA	24
FCC §2.1053 & §22.861 & §90.210 - RADIATED SPURIOUS EMISSIONS	29
APPLICABLE STANDARD	29
TEST EQUIPMENT LIST AND DETAILS.....	29
TEST PROCEDURE	29
TEST DATA	30
FCC §2.1055 & § 22.355 & §90.213- FREQUENCY STABILITY	32
APPLICABLE STANDARD	32
TEST EQUIPMENT LIST AND DETAILS.....	32

TEST PROCEDURE32
TEST DATA32
FCC §90.214 - TRANSIENT FREQUENCY BEHAVIOR.....34
APPLICABLE STANDARD34
TEST EQUIPMENT LIST AND DETAILS.....34
TEST PROCEDURE34
TEST DATA35

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *Hytera Communications Corporation Limited's* product, model: *BD612 U(1)* (FCC ID: *YAMBD61XU1*) (the "EUT") in this report is a *Digital Portable Radio*, which was measured approximately: 12 cm (H) x 5.8 cm (W) x 3.5 cm (D), rated input voltage: DC7.2V Li-ion battery or DC12.0V charging from adapter.

Adapter Information:

P/N: PS1014

MODEL: HKA01212010-XQ

INPUT: AC 100-240V, 50/60Hz, 0.5A

OUTPUT: DC 12.0V, 1.0A

Note: The series product, model BD612 U(1), BD615 U(1), BD616 U(1), BD618 U(1) are electrically identical, the difference between them are just the model name, we selected BD612 U(1) for fully testing, the details were explained in the declaration letter.

** All measurement and test data in this report was gathered from production sample serial number: 160919006 (assigned by BAACL, Dongguan). The EUT was received on 2016-09-20.*

Objective

This test report is prepared on behalf of *Hytera Communications Corporation Limited*. in accordance with Part 2, Part 22 and Part 90 of the Federal Communications Commission rules.

Related Submittal(s)/Grant(s)

No related submittal(s).

Test Methodology

All tests and measurements indicated in this document were performed in accordance with the Code of federal Regulations Title 47 Part 2, Sub-part J as well as the following individual parts:

Part 22 – Public Mobile Service

Part 90 – Private Land Digital Portable Radio Service

Applicable Standards: TIA-603-D.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 02, 2015. The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in a test mode.


EUT Specification:

Operating Frequency Band	400-406 MHz; 406.1-470 MHz
Modulation Mode	FM/4FSK
Channel Spacing	12.5 kHz
Rated Output Power	High: 4W Low: 1W

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
N/A	Terminal Load(50 Ω)	N/A	N/A

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Results
§1.1310 and §2.1093	RF Exposure	Compliant
§2.1046; § 22.727;§90.205	RF Output Power	Compliant
§2.1047;§90.207	Modulation Characteristic	Compliant
§2.1049;§22.357;§ 22.731;§90.209; §90.210	Occupied Bandwidth & Emission Mask	Compliant
§2.1051; §22.861;§90.210	Spurious Emission at Antenna Terminal	Compliant
§2.1053; §22.861;§90.210	Spurious Radiated Emissions	Compliant
§2.1055; § 22.355;§90.213	Frequency Stability	Compliant
§90.214	Transient Frequency Behavior	Compliant

Test time: 2016.09.22~2016.09.23

FCC §1.1310 & §2.1093 - RF EXPOSURE

Applicable Standard

FCC§1.1310 and §2.1093.

Test Result

Compliant, please refer to the SAR report: RDG160919006-20A.

FCC §2.1046 & § 22.727 & §90.205- RF OUTPUT POWER

Applicable Standard

FCC §2.1046, § 22.727 and §90.205.

Test Procedure

Conducted RF Output Power:

TIA-603-D section 2.2.1

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

Spectrum Analyzer setting:

RBW	VBW
100 kHz	300 kHz

Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2015-11-23	2016-11-22
Weinschel Corp	Attenuator(20dB)	53-20-34	LN749	2016-05-07	2017-05-06
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2016-05-05	2017-05-04

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	29.2 °C
Relative Humidity:	42 %
ATM Pressure:	100.7 kPa

The testing was performed by Gavin Xu on 2016-09-22.

Test Result: Compliant. Please refer to following tables.

FCC Part 90:

Modulation	Channel Spacing (kHz)	f _c (MHz)	Conducted Output Power (W)		Note
			High	Low	
FM	12.5	400.0125	4.07	1.06	Not for FCC Review
		453.2125	4.09	1.12	/
		469.9875	4.06	1.09	/
4FSK		400.0125	4.05	1.05	Not for FCC Review
		453.2125	4.08	1.06	/
		469.9875	4.06	1.08	/

FCC Part 22:

Modulation	Channel Spacing (kHz)	f _c (MHz)	Conducted Output Power (W)		Note
			High	Low	
FM	12.5	454.0125	4.04	1.09	/
4FSK		454.0125	4.05	1.07	/

Note: The rated high power is 4W (36 dBm) and low power is 1W (30 dBm).

FCC §2.1047 & §90.207 - MODULATION CHARACTERISTIC

Applicable Standard

FCC§2.1047 & §90.207:

- (a) Equipment which utilizes voice modulated communication shall show the frequency response of the audio modulating circuit over a range of 100 to 5000 Hz. for equipment which is required to have a low pass filter, the frequency response of the filter, or all of the circuitry installed between the modulation limited and the modulated stage shall be supplied.
- (b) Equipment which employs modulation limiting, a curve showing the percentage of modulation versus the modulation input voltage shall be supplied.

Test Procedure

Test Method: TIA/EIA-603 2.2.3

Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Due Date
HP	RF Communications Test Set	8920A	00 235	2016-7-11	2017-7-11
Weinschel Corp	Attenuator(20dB)	53-20-34	LN749	2016-05-07	2017-05-06
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2016-05-05	2017-05-04

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	29.2 °C
Relative Humidity:	42 %
ATM Pressure:	100.7 kPa


The testing was performed by Gavin Xu on 2016-09-22.

Test Result: Compliant. Please refer to following table and plots.

MODULATION LIMITING

Carrier Frequency: 453.2125MHz, Channel Spacing = 12.5 kHz


Audio Frequency (Hz)	Instantaneous		Steady-state		Limit [kHz]
	Deviation (@+20dB) [kHz]	Deviation (@-20dB) [kHz]	Deviation (@+20dB) [kHz]	Deviation (@-20dB) [kHz]	
300	0.978	0.109	0.956	0.087	2.5
400	1.207	0.108	1.187	0.092	2.5
500	1.574	0.128	1.553	0.106	2.5
600	1.735	0.137	1.714	0.121	2.5
700	1.771	0.147	1.751	0.128	2.5
800	1.844	0.164	1.821	0.148	2.5
900	1.943	0.167	1.926	0.151	2.5
1000	2.103	0.185	2.086	0.169	2.5
1200	2.102	0.212	2.087	0.186	2.5
1400	2.042	0.225	2.026	0.209	2.5
1600	1.967	0.257	1.945	0.234	2.5
1800	1.929	0.267	1.907	0.251	2.5
2000	1.889	0.278	1.866	0.262	2.5
2200	1.806	0.289	1.782	0.273	2.5
2400	1.997	0.315	1.975	0.289	2.5
2600	1.991	0.331	1.976	0.315	2.5
2800	1.987	0.354	1.968	0.338	2.5
3000	1.716	0.335	1.697	0.321	2.5



Audio Frequency Response

Carrier Frequency: 453.2125 MHz, Channel Spacing = 12.5 kHz


Audio Frequency Hz	Response Attenuation dB
300	-11.17
400	-8.57
500	-6.13
600	-4.44
700	-3.12
800	-2.01
900	-0.96
1000	0.00
1200	1.57
1400	2.88
1600	3.89
1800	4.71
2000	5.36
2200	5.96
2400	6.46
2600	7.16
2800	7.97
3000	7.54



Audio Frequency Low Pass Filter Response

Carrier Frequency: 435 MHz, Channel Spacing = 12.5 kHz, high power level

Audio Frequency	Response Attenuation	Limit
kHz	dB	dB
3.0	-2.7	0.0
3.5	-9.4	-6.7
4.0	-15.1	-12.5
5.0	-25.4	-22.2
7.0	-39.3	-36.8
10.0	-54.8	-52.3
15.0	-72.3	-69.9
20.0	-85.5	-82.5
30.0	-85.6	-82.5
50.0	-85.4	-82.5
70.0	-85.6	-82.5



FCC §2.1049 & §22.357 & § 22.731 & §90.209 & §90.210 – OCCUPIED BANDWIDTH & EMISSION MASK

Applicable Standard

FCC §2.1049, §22.357, § 22.731, §90.209 and §90.210

Applicable Emission Masks

Frequency band (MHz)	Mask for equipment with audio low pass filter	Mask for equipment without audio low pass filter
Below 25	A or B	A or C
25-50	B	C
72-76	B	C
150-174	B, D, or E	C, D or E
150 paging only	B	C
220-222	F	F
421-512	B, D, or E	C, D, or E
450 paging only	B	G
806-809/851-854	B	H
809-824/854-869	B	G
896-901/935-940	I	J
902-928	K	K
929-930	B	G
4940-4990 MHz	L or M	L or M
5850-5925		
All other bands	B	C

Emission Mask D—12.5 kHz channel bandwidth equipment. For transmitters designed to operate with a 12.5 kHz channel bandwidth, any emission must be attenuated below the power (P) of the highest emission contained within the authorized bandwidth as follows:

- (1) On any frequency from the center of the authorized bandwidth f_0 to 5.625 kHz removed from f_0 : Zero dB.
- (2) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 5.625 kHz but no more than 12.5 kHz: At least $7.27(f_d - 2.88 \text{ kHz})$ dB.
- (3) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 12.5 kHz: At least $50 + 10 \log(P)$ dB or 70 dB, whichever is the lesser attenuation.
- (4) The reference level for showing compliance with the emission mask shall be established using a resolution bandwidth sufficiently wide (usually two or three times the channel bandwidth) to capture the true peak emission of the equipment under test. In order to show compliance with the emission mask up to and including 50 kHz removed from the edge of the authorized bandwidth, adjust the resolution bandwidth to 100 Hz with the measuring instrument in a peak hold mode. A sufficient number of sweeps must be measured to insure that the emission profile is developed. If video filtering is used, its bandwidth must not be less than the instrument resolution bandwidth. For emissions beyond 50 kHz from the edge of the authorized bandwidth, see paragraph (o) of this section. If it can be shown that use of the above instrumentation settings do not accurately represent the true interference potential of the equipment under test, an alternate procedure may be used provided prior Commission approval is obtained.

§22.357 Emission types.

Any authorized station in the Public Mobile Services may transmit emissions of any type(s) that comply with the applicable emission rule, i.e. §22.359, §22.861 or §22.917

§22.731 Emission limitations.

Upon application for multichannel operation, the FCC may authorize emission bandwidths wider than those specified in §22.357, provided that spectrum utilization is equal to or better than that achieved by single channel operation.

Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2015-11-23	2016-11-22
HP	RF Communications Test Set	8920A	00 235	2016-07-11	2017-07-11
Weinschel Corp	Attenuator(20dB)	53-20-34	LN749	2016-05-07	2017-05-06
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2016-05-05	2017-05-04

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

Test Data

Environmental Conditions

Temperature:	28.7~29.2 °C
Relative Humidity:	42~43 %
ATM Pressure:	100.7 kPa

The testing was performed by Gavin Xu from 2016-09-22 to 2016-09-23.

Test Result: Compliant. Please refer to the following tables and plots.

FCC Part 90:

Modulation Mode	Channel Spacing	f _c	26 dB Bandwidth	99% Occupied Bandwidth	Power Level
		MHz	kHz	kHz	
FM	12.5 kHz	453.2125	10.400	10	High
			10.400	10	Low
4FSK	12.5 kHz		9.500	6.8	High
			9.400	6.8	Low

FCC Part 22:

Modulation Mode	Channel Spacing	f _c	26 dB Bandwidth	99% Occupied Bandwidth	Power Level
		MHz	kHz	kHz	
FM	12.5 kHz	454.0125	10.400	10	High
			10.400	10	Low
4FSK			9.600	6.8	High
			9.000	6.7	Low

Note: Emission bandwidth was based on calculation method instead of measurement.

Emission Designator

Per CFR 47 §2.201& §2.202&, Bn = 2M + 2D

For FM Mode (Channel Spacing: 12.5 kHz)

Emission Designator 11K0F3E

In this case, the maximum modulating frequency is 3.0 kHz with a 2.5 kHz deviation.

$$BW = 2(M+D) = 2*(3.0 \text{ kHz} + 2.5 \text{ kHz}) = 11 \text{ kHz} = \rightarrow 11K0$$

F3E portion of the designator represents an FM voice transmission

Therefore, the entire designator for 12.5 kHz channel spacing FM mode is 11K0F3E.

For Digital Mode (Channel Spacing: 12.5 kHz)

Emission Designator 7K60F1D and 7K60F1E


The 99% energy rule (title 47CFR 2.1049) was used for digital mode. It basically states that 99% of the modulation energy falls within X kHz, in this case, 7.60 kHz. The emission mask was obtained from 47CFR 90.210(d).

F1D and F1E portion of the designator indicates digital information.

Therefore, the entire designator for 12.5 kHz channel spacing digital mode is 7K60F1D and 7K60F1E.


Part 90:

Occupied Bandwidth – FM, 453.2125 MHz, High Power Level




Date: 22.SEP.2016 20:16:59

Emission Mask - Type D




Date: 22.SEP.2016 20:18:09

Occupied Bandwidth – FM, 453.2125 MHz, Low Power Level




Date: 22.SEP.2016 20:14:16

Emission Mask - Type D




Date: 22.SEP.2016 20:12:42

Occupied Bandwidth –4FSK, 453.2125 MHz, High Power Level




Date: 22.SEP.2016 19:32:33

Emission Mask - Type D




Date: 22.SEP.2016 19:33:45

Occupied Bandwidth – 4FSK, 453.2125 MHz, Low Power Level



Date: 22.SEP.2016 19:27:41


Emission Mask - Type D



Date: 22.SEP.2016 19:26:18


Part 22:

Occupied Bandwidth –FM, 454.0125 MHz, High Power Level




Date: 23.SEP.2016 23:18:17

Occupied Bandwidth – FM, 454.0125 MHz, Low Power Level




Date: 23.SEP.2016 23:19:48

Occupied Bandwidth –4FSK, 454.0125 MHz, High Power Level



Date: 22.SEP.2016 19:36:46

Occupied Bandwidth – 4FSK, 454.0125 MHz, Low Power Level



Date: 22.SEP.2016 19:40:17

FCC §2.1051& §22.861 & §90.210 - SPURIOUS EMISSIONS AT ANTENNA TERMINALS

Applicable Standard

Emission Mask D—12.5 kHz channel bandwidth equipment. For transmitters designed to operate with a 12.5 kHz channel bandwidth, any emission must be attenuated below the power (P) of the highest emission contained within the authorized bandwidth as follows:

- (1) On any frequency from the center of the authorized bandwidth f_0 to 5.625 kHz removed from f_0 : Zero dB.
- (2) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 5.625 kHz but no more than 12.5 kHz: At least $7.27(f_d - 2.88 \text{ kHz})$ dB.
- (3) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 12.5 kHz: At least $50 + 10 \log(P)$ dB or 70 dB, whichever is the lesser attenuation.
- (4) The reference level for showing compliance with the emission mask shall be established using a resolution bandwidth sufficiently wide (usually two or three times the channel bandwidth) to capture the true peak emission of the equipment under test. In order to show compliance with the emission mask up to and including 50 kHz removed from the edge of the authorized bandwidth, adjust the resolution bandwidth to 100 Hz with the measuring instrument in a peak hold mode. A sufficient number of sweeps must be measured to insure that the emission profile is developed. If video filtering is used, its bandwidth must not be less than the instrument resolution bandwidth. For emissions beyond 50 kHz from the edge of the authorized bandwidth, see paragraph (o) of this section. If it can be shown that use of the above instrumentation settings do not accurately represent the true interference potential of the equipment under test, an alternate procedure may be used provided prior Commission approval is obtained.

§22.861 Emission limitations.

- (a) Out of band emissions. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2015-11-23	2016-11-22
R&S	Spectrum Analyzer	FSEM	DE23437	2015-11-23	2016-11-22
HP	RF Communications Test Set	8920A	00 235	2016-07-11	2017-07-11
Weinschel Corp	Attenuator(20dB)	53-20-34	LN749	2016-05-07	2017-05-06
Mini-Circuits	HIGH PASS FILTER	BHP-550+	YZU15801121	2016-05-05	2017-05-04
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2016-05-05	2017-05-04

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

Adjust the spectrum analyzer for the following settings:


- 1) Resolution Bandwidth = 100 kHz for spurious emissions below 1 GHz, and 1 MHz for spurious emissions above 1 GHz.
- 2) Video Bandwidth ≥ 3 times the resolution bandwidth.
- 3) Sweep Speed ≤ 2000 Hz per second.
- 4) Detector Mode = peak.

Test Data**Environmental Conditions**


Temperature:	29.2 °C
Relative Humidity:	42 %
ATM Pressure:	100.7 kPa

The testing was performed by Gavin Xu on 2016-09-22.

FCC PART 90 453.2125 MHz – FM Mode, High Power




Date: 22.SEP.2016 10:37:22




Date: 22.SEP.2016 10:39:03

FCC PART 90 453.2125 MHz -4FSK Mode,High Power




Date: 22.SEP.2016 10:31:19




Date: 22.SEP.2016 10:30:40

FCC PART 22 454.0125 MHz –FM Mode,High Power




Date: 22.SEP.2016 10:48:28




Date: 22.SEP.2016 10:47:52

FCC PART 22 454.0125 MHz -4FSK Mode,High Power



Date: 22.SEP.2016 10:47:00



Date: 22.SEP.2016 10:47:29

FCC §2.1053 & §22.861 & §90.210 - RADIATED SPURIOUS EMISSIONS

Applicable Standard

FCC §2.1053 and §22.861 and §90.210

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HP	Signal Generator	1026	320408	2015-11-23	2016-11-22
Sunol Sciences	Antenna	JB3	A060611-3	2014-07-28	2017-07-27
EMCO	Adjustable Dipole Antenna	3121C	9109-753	N/A	N/A
HP	Amplifier	8447E	2434A02181	2016-09-01	2017-09-01
R&S	EMI Test Receiver	ESCI	100224	2016-09-01	2017-09-01
Mini-Circuit	Amplifier	ZVA-213-S+	054201245	2016-02-19	2017-02-19
TDK RF	Horn Antenna	HRN-0118	130 084	2015-09-06	2018-09-06
ETS-Lindgren	Horn Antenna	3115	9808-5557	2015-09-06	2018-09-06
Agilent	Spectrum Analyzer	E4440A	SG43360054	2015-11-23	2016-11-22
N/A	Coaxial Cable	14m	N/A	2016-05-06	2017-05-06
N/A	Coaxial Cable	8m	N/A	2016-05-06	2017-05-06
Mini-Circuits	HIGH PASS FILTER	BHP-550+	YZU15801121	2016-05-05	2017-05-04
Weinschel Corp	Terminal Load(100W)	1440-3	MD447	/	/

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load, which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to teeth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

For part 90:

Spurious emissions in dB = 10 lg (TXpwr in Watts/0.001)-the absolute level

Spurious attenuation limit in dB = 50 + 10 Log₁₀ (power out in Watts) for EUT with a 12.5 kHz channel bandwidth.

For part 22:

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log (P) dB.

Test Data

Environmental Conditions

Temperature:	27.9°C
Relative Humidity:	65 %
ATM Pressure:	100.7 kPa

The testing was performed by Gavin Xu on 2016-09-23.

Test Mode: Transmitting (FM mode, high power level)

Frequency	Polar	S.A. Reading	S.G. Level	Antenna Gain	Cable Loss	Absolute Level	Limit	Margin
MHz	H/V	dBμV	dBm	dBd/dBi	dB	dBm	dBm	dB
Frequency: 453.2125 MHz, for FCC PART 90								
906.425	H	23.46	-50.8	0.0	1	-51.8	-20.0	31.8
906.425	V	21.76	-49.2	0.0	1	-50.2	-20.0	30.2
1359.638	H	39.17	-61.2	8.7	1.4	-53.9	-20.0	33.9
1359.638	V	37.85	-62.5	8.7	1.4	-55.2	-20.0	35.2
1812.850	H	36.89	-63.2	11.1	1.3	-53.4	-20.0	33.4
1812.850	V	36.78	-63.6	11.1	1.3	-53.8	-20.0	33.8
2266.063	H	36.24	-59.8	11.1	2.2	-50.9	-20.0	30.9
2266.063	V	36.28	-59.5	11.1	2.2	-50.6	-20.0	30.6
2719.275	H	35.39	-61.4	13.1	2.3	-50.6	-20.0	30.6
2719.275	V	35.69	-62.7	13.1	2.3	-51.9	-20.0	31.9
3172.488	H	34.68	-62.9	13.5	2.3	-51.7	-20.0	31.7
3172.488	V	35.73	-61.2	13.5	2.3	-50.0	-20.0	30.0
3625.700	H	33.88	-61.6	14.1	2.2	-49.7	-20.0	29.7
3625.700	V	34.76	-60.3	14.1	2.2	-48.4	-20.0	28.4
Frequency: 454.0125 MHz, for FCC PART 22								
908.025	H	22.99	-51.2	0.0	1	-52.2	-13.0	39.2
908.025	V	22.93	-48	0.0	1	-49.0	-13.0	36.0
1362.038	H	40.39	-60	8.7	1.4	-52.7	-13.0	39.7
1362.038	V	38.22	-62.1	8.7	1.4	-54.8	-13.0	41.8
1816.050	H	38.33	-61.7	11.2	1.3	-51.8	-13.0	38.8
1816.050	V	36.96	-63.3	11.2	1.3	-53.4	-13.0	40.4
2270.063	H	36.80	-59.3	11.1	2.2	-50.4	-13.0	37.4
2270.063	V	36.37	-59.4	11.1	2.2	-50.5	-13.0	37.5
2724.075	H	35.51	-61.4	13.1	2.3	-50.6	-13.0	37.6
2724.075	V	36.15	-62.2	13.1	2.3	-51.4	-13.0	38.4
3178.088	H	33.63	-64	13.5	2.3	-52.8	-13.0	39.8
3178.088	V	34.60	-62.2	13.5	2.3	-51.0	-13.0	38.0
3632.100	H	34.56	-60.9	14.1	2.2	-49.0	-13.0	36.0
3632.100	V	34.36	-60.6	14.1	2.2	-48.7	-13.0	35.7

Test Mode: Transmitting (4FSK mode, high power level)

Frequency	Polar	S.A. Reading	S.G. Level	Antenna Gain	Cable Loss	Absolute Level	Limit	Margin
MHz	H/V	dB μ V	dBm	dBd/dBi	dB	dBm	dBm	dB
Frequency:453.2125 MHz, for FCC PART 90								
906.425	H	23.18	-51.1	0.0	1	-52.1	-20.0	32.1
906.425	V	23.72	-47.2	0.0	1	-48.2	-20.0	28.2
1359.638	H	39.40	-60.9	8.7	1.4	-53.6	-20.0	33.6
1359.638	V	37.14	-63.2	8.7	1.4	-55.9	-20.0	35.9
1812.850	H	36.08	-64	11.1	1.3	-54.2	-20.0	34.2
1812.850	V	36.37	-64	11.1	1.3	-54.2	-20.0	34.2
2266.063	H	35.90	-60.1	11.1	2.2	-51.2	-20.0	31.2
2266.063	V	36.35	-59.4	11.1	2.2	-50.5	-20.0	30.5
2719.275	H	36.49	-60.3	13.1	2.3	-49.5	-20.0	29.5
2719.275	V	36.59	-61.8	13.1	2.3	-51.0	-20.0	31.0
3172.488	H	34.31	-63.3	13.5	2.3	-52.1	-20.0	32.1
3172.488	V	34.37	-62.5	13.5	2.3	-51.3	-20.0	31.3
3625.700	H	34.99	-60.5	14.1	2.2	-48.6	-20.0	28.6
3625.700	V	34.75	-60.3	14.1	2.2	-48.4	-20.0	28.4
Frequency:454.0125 MHz, for FCC PART 22								
908.025	H	24.73	-49.5	0.0	1	-50.5	-13.0	37.5
908.025	V	23.58	-47.3	0.0	1	-48.3	-13.0	35.3
1362.038	H	40.58	-59.8	8.7	1.4	-52.5	-13.0	39.5
1362.038	V	37.49	-62.8	8.7	1.4	-55.5	-13.0	42.5
1816.050	H	36.32	-63.7	11.2	1.3	-53.8	-13.0	40.8
1816.050	V	36.76	-63.5	11.2	1.3	-53.6	-13.0	40.6
2270.063	H	36.90	-59.2	11.1	2.2	-50.3	-13.0	37.3
2270.063	V	36.04	-59.7	11.1	2.2	-50.8	-13.0	37.8
2724.075	H	35.73	-61.2	13.1	2.3	-50.4	-13.0	37.4
2724.075	V	35.75	-62.6	13.1	2.3	-51.8	-13.0	38.8
3178.088	H	34.75	-62.8	13.5	2.3	-51.6	-13.0	38.6
3178.088	V	34.48	-62.4	13.5	2.3	-51.2	-13.0	38.2
3632.100	H	34.50	-61	14.1	2.2	-49.1	-13.0	36.1
3632.100	V	34.08	-60.9	14.1	2.2	-49.0	-13.0	36.0

Note:

- 1) The unit of Antenna Gain is dBd for frequency below 1GHz, and the unit of Antenna Gain is dBi for frequency above 1GHz.
- 2) Absolute Level = SG Level - Cable loss + Antenna Gain
- 3) Margin = Limit-Absolute Level

FCC §2.1055 & § 22.355 & §90.213- FREQUENCY STABILITY**Applicable Standard**

FCC §2.1055, § 22.355, §90.213

Test Equipment List and Details

Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2015-11-23	2016-11-22
Dongzhixu	High Temperature Test Chamber	DP1000	201105083-3	2016-09-10	2017-09-09
UNI-T	Multimeter	UT39A	M130199938	2016-04-02	2017-04-02
Weinschel Corp	Attenuator(20dB)	53-20-34	LN749	2016-05-07	2017-05-06
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2016-05-05	2017-05-04

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to DC power supply and the RF output was connected to a frequency counter via feed-through attenuators. The EUT was placed inside the temperature chamber. The power leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the counter.

The frequency stability shall be measured with variation of primary supply voltage as follows:

- (1) Vary primary supply voltage from 85 to 115 percent of the nominal value.
- (2) For hand carried, battery powered equipment, reduce primary supply voltage to the battery operating end point which shall be specified by the manufacturer.

Test Data**Environmental Conditions**

Temperature:	29.2 °C
Relative Humidity:	42 %
ATM Pressure:	100.7 kPa

The testing was performed by Gavin Xu on 2016-09-22.

Test Mode: Transmitting

FCC PART 90:

Reference Frequency: 435 MHz, Limit: 2.5 ppm			
Temperature	Voltage	Measured	Frequency Error
°C	V _{DC}	MHz	ppm
-30	7.2	453.212706	0.45
-20	7.2	453.212701	0.44
-10	7.2	453.212709	0.46
0	7.2	453.212712	0.47
10	7.2	453.212714	0.47
20	7.2	453.212702	0.45
30	7.2	453.212716	0.48
40	7.2	453.212695	0.43
50	7.2	453.212711	0.47
60	7.2	453.212712	0.47
25	6.7	453.212713	0.47
	7.2	453.212714	0.47

FCC PART 22:

Reference Frequency: 454.0125 MHz, Limit: 5.0 ppm			
Temperature	Voltage	Measured	Frequency Error
°C	V _{DC}	MHz	ppm
-30	7.2	454.012709	0.46
-20	7.2	454.012713	0.47
-10	7.2	454.012689	0.42
0	7.2	454.012701	0.44
10	7.2	454.012714	0.47
20	7.2	454.012704	0.45
30	7.2	454.012693	0.43
40	7.2	454.012695	0.43
50	7.2	454.012717	0.48
60	7.2	454.012714	0.47
25	6.7	454.012713	0.47
	7.2	454.012708	0.46

Note: The extreme voltage is declared by the manufacturer.

FCC §90.214 - TRANSIENT FREQUENCY BEHAVIOR

Applicable Standard

Regulations: FCC §90.214

Test method: ANSI/TIA-603-D 2010, section 2.2.19.3

Test Equipment List and Details


Manufacturer	Description	Model No.	Serial No.	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	DE31388	2015-11-23	2016-11-22
HP	Signal Generator	8648A	3426A00831	2015-12-15	2016-12-14
Weinschel Corp	Attenuator(20dB)	53-20-34	LN749	2016-05-07	2017-05-06
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2016-05-05	2017-05-04

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

- a) Connect the EUT and test equipment as shown on the following block diagram.
- b) Set the Spectrum Analyzer to measure FM deviation, and tune the RF frequency to the transmitter assigned frequency.
- c) Set the signal generator to the assigned transmitter frequency and modulate it with a 1 kHz tone at ± 12.5 kHz deviation and set its output level to -100dBm.
- d) Turn on the transmitter.
- e) Supply sufficient attenuation via the RF attenuator to provide an input level to the Spectrum Analyzer that is 40 dB below the maximum allowed input power when the transmitter is operating at its rated power level. Note this power level on the Spectrum Analyzer as P_0 .
- f) Turn off the transmitter.
- g) Adjust the RF level of the signal generator to provide RF power equal to P_0 . This signal generator RF level shall be maintained throughout the rest of the measurement.
- h) Remove the attenuation 1, so the input power to the Spectrum Analyzer is increased by 30 dB when the transmitter is turned on.
- i) Adjust the vertical amplitude control of the spectrum analyzer to display the 1000 Hz at ± 4 divisions vertically centered on the display. Set trigger mode of the Spectrum Analyzer to "Video", and tune the "trigger level" on suitable level. Then set the "trigger offset" to -10ms for turn on and -15ms for turn off.
- j) Turn on the transmitter and the transient wave will be captured on the screen of Spectrum Analyzer. Observe the stored display. The instant when the 1 kHz test signal is completely suppressed is considered to be t_{on} . The trace should be maintained within the allowed divisions during the period t_1 and t_2 .

k) Then turn off the transmitter, and another transient wave will be captured on the screen of Spectrum Analyzer. The trace should be maintained within the allowed divisions during the period t_3 .



Test Data

Environmental Conditions


Temperature:	29.2 °C
Relative Humidity:	42 %
ATM Pressure:	100.7 kPa

The testing was performed by Gavin Xu on 2016-09-22.

Channel Spacing (kHz)	Transient Period (ms)	Maximum frequency difference	Result
12.5	<10(t_1)	± 12.5 kHz	Pass
	<25(t_2)	± 6.25 kHz	
	<10(t_3)	± 12.5 kHz	


Please refer to the following plots.

Turn on – 453.2125 MHz, High power level



Date: 22.SEP.2016 14:43:26

Turn off – 453.2125 MHz, High power level



Date: 22.SEP.2016 14:41:38

***** END OF REPORT *****