



中认信通

CHINA CERTIFICATION ICT CO., LTD (DONGGUAN)



MAXIMUM PERMISSIBLE EXPOSURE EVALUATION REPORT

Applicant: Hytera Communications Corporation Limited

Address: Hytera Tower, Hi-Tech Industrial Park North, 9108# Beihuan Road, Nanshan District, Shenzhen, 518057 China

FCC ID: YAMMD612VHF

Product Name: Digital Mobile Radio

Model Number: MD612 VHF, MD615 VHF, MD616 VHF,
MD618 VHF, MD619 VHF, MD622 VHF,
MD625 VHF, MD626 VHF, MD628 VHF,
MD629 VHF, MD61X, MD62X

Standard(s): 47 CFR §1.1310, 47 CFR §2.1091

The above equipment has been tested and found compliant with the requirement of the relative standards by China Certification ICT Co., Ltd (Dongguan)

Report Number: CR22080001-00E

Date Of Issue: 2022-09-16

Reviewed By: Sun Zhong

Sun Zhong

Title: Manager

Test Laboratory: China Certification ICT Co., Ltd (Dongguan)

No. 113, Pingkang Road, Dalang Town, Dongguan,
Guangdong, China
Tel: +86-769-82016888

Test Facility

The Test site used by China Certification ICT Co., Ltd (Dongguan) to collect test data is located on the No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 442868, the FCC Designation No. : CN1314.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0123.

Declarations

China Certification ICT Co., Ltd (Dongguan) is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test (EUT)

EUT Name:	Digital Mobile Radio
EUT Model:	MD612 VHF,MD622 VHF
Multiple Models:	MD615 VHF, MD616 VHF, MD618 VHF, MD619 VHF, MD625 VHF, MD626 VHF, MD628 VHF, MD629 VHF, MD61X, MD62X
Rated Input Voltage:	DC 13.6V from Vehicle Battery
Serial Number:	CR22080001-RF-S1(Model: MD612 VHF) CR22080001-RF-S2(Model: MD622 VHF)
EUT Received Date:	2022.08.02
EUT Received Status:	Good
<p>Note: The Multiple models are electrically identical with the test model. Please refer to the declaration letter for more detail, which was provided by manufacturer.</p>	

1.1.2 Conducted Output power ▲:

Operation Modes	Operation Frequency (MHz)	Maximum Conducted Power including Tune-up Tolerance	
		(dBm)	(mW)
Bluetooth	2402-2480	7	5.01
VHF	136-174	47.5	56234.13
<p>Note: The Above Parameters were provided by the manufacturer. The Bluetooth and UHF can transmit simultaneously.</p>			

1.1.3 Antenna Information Detail ▲:

Antenna Chain		Antenna Type	input impedance (Ohm)	Frequency Range	Antenna Gain
Bluetooth	Zhejiang Haitong Communication Electronics Co., Ltd	LDS	50	2400-2500MHz	0.72 dBi
VHF	KENBOTONG TECHNOLOGY CO., LTD.	Helical	50	136-174MHz	0 dBi

2. MAXIMUM PERMISSIBLE EXPOSURE (MPE)

2.1 Applicable Standard

According to 1.1310, 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for Maximum Permissible Exposure (MPE)

Limits for Occupational/Controlled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E , H or S (minutes)
0.3- 3.0	614	1.63	(100)*	6
3.0 - 30	1842/f	4.89/f	(900/f ²)*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	f/300	6
1500-100,000	/	/	5	6

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz;

* = Plane-wave equivalent power density;

2.2 MPE Calculation

Prediction of power density at the distance of the applicable MPE limit

$$S = PG/4\pi R^2$$

Where: S = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

2.3 MPE Results

For VHF:

Frequency (MHz)	Antenna Gain		Maximum Average output power including Tune-up Tolerance (mW)	Operation Duty Cycle (%)	Evaluation Distance (cm)	Power Density (mW/cm ²)	Power Density Limit (mW/cm ²)
	(dBi)	(numeric)					
136-174	0	1.0	56234.13	50	55	0.74	1.0

For Bluetooth:

Frequency (MHz)	Antenna Gain		Conducted output power including Tune-up Tolerance		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
	(dBi)	(numeric)	(dBm)	(mW)			
2402-2480	0.72	1.18	7	5.01	20.00	0.001	1.0

simultaneously transmit:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

$$=S_{VHF}/S_{limit-VHF} + S_{BT}/S_{limit-BT}$$

$$=0.74/1.0+0.001/1.0$$

$$=0.741$$

Result: The device meet FCC MPE at 55 cm distance for Occupational/Controlled condition.

===== END OF REPORT =====