



Shenzhen Huatongwei International Inspection Co., Ltd.

Keji S,12th , Road, Hi-tech Industrial Park, Shenzhen, Guangdong, China

Phone:86-755-26748099 Fax:86-755-26748089 http://www.szhtw.com.cn



MPE TEST REPORT

FCC Per 47 CFR 2.1091(b)

Report Reference No......: **TRE1112009202**

FCC ID: **YAMMD78XG-U1**

Compiled by
(position+printed name+signature)...: File administrators Eric Zhang

Eric Zhang

Supervised by
(position+printed name+signature)...: Test Engineer Wenliang Li

Wenliang Li

Approved by
(position+printed name+signature)...: Manager Wenliang Li

Wenliang Li

Date of issue.....: Dec 27, 2011

Testing Laboratory Name: **Shenzhen Huatongwei International Inspection Co., Ltd**

Address: Keji Nan No.12 Road, Hi-tech Park, Shenzhen, China

Applicant's name.....: **Hytera Communications Corporation Ltd.**

Address: HYT Tower,Hi-Tech Industrial Park North,Nanshan District,Shenzhen China.518057

Test specification:

Standard: **FCC Per 47 CFR 2.1091(b)**

TRF Originator.....: Shenzhen Huatongwei International Inspection CO., Ltd

Master TRF.....: Dated 2006-06

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description: Digital Mobile Radio

Trade Mark: 

Manufacturer: **Hytera Communications Corporation Ltd.**

Model/Type reference.....: MD782G U(1)/ MD785G U(1)/ MD786G U(1)/ MD788G U(1)

Listed Models: /

Ratings: DC 13.60V

Modulation: FM&4FSK

Rated Power: 45 Watts(46.53 dBm)/5 Watts(36.99 dBm)

Channel Separation.....: 12.5KHz

Frequency Range: From 400 MHz to 470 MHz

Result.....: **Positive**

MPE TEST REPORT

Test Report No. :	TRE1112009202	Dec 27, 2011
		Date of issue

Equipment under Test : Digital Mobile Radio

Model /Type : MD782G U(1)/ MD785G U(1)/ MD786G U(1)/ MD788G U(1)

Listed Models : /

Applicant : **Hytera Communications Corporation Ltd.**

Address : HYT Tower,Hi-Tech Industrial Park North,Nanshan District,Shenzhen China.518057

Manufacturer : **Hytera Communications Corporation Ltd.**

Address : HYT Tower,Hi-Tech Industrial Park North,Nanshan District,Shenzhen China.518057

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

- 1. MEASUREMENT UNCERTAINTY 4**

- 2. METHOD OF MEASUREMENT 4**
 - 2.1. EME measurements made on trunk mounted antennas 4**
 - 2.1.1. External vehicle EME measurement4
 - 2.1.2. Internal vehicle EME measurement4
 - 2.2. EME measurements made on center roof mounted antennas 4**
 - 2.2.1. External vehicle EME measurement4
 - 2.2.2. Internal vehicle EME measurement4

- 3. APPROVED ACCESSORIES..... 5**

- 4. TEST RESULT 5**

- 5. CONCLUSION 7**

- 6. ANTENNA LOCATION DRAWING 8**

- 7. PROBE CALIBRATION CERTIFICATES..... 9**

1. Measurement Uncertainty

The information below presents an estimate of the possible errors that are associated with the measurement system.

<u>Description</u>	<u>Error</u>
NARDA Survey Meter	± 3%
Repeatability Accuracy	± 7%

2. Method of measurement

2.1. EME measurements made on trunk mounted antennas

2.1.1. External vehicle EME measurement

(Antenna mounted in trunk center)

With the survey meter and probe, take ten (10) measurements, at the standard test distance of 60 cm to the antenna, from the back of the vehicle in a vertical line and then average the results. These measurements are taken and recorded at every twenty (20) centimeters over a range starting at twenty (20) centimeters above ground and ending at 2.0 meters.

2.1.2. Internal vehicle EME measurement

(Antenna mounted in trunk center)

While rotating survey meter probe through 180 degrees to ensure that the highest level is found, scan the inside of the vehicle, both front and back seating areas, for the highest level in each location. After the highest level is found, scan vertically making two (2) additional measurements within an area approximately 40 cm wide (representing the width of a person) so as to have a total of three (3) measured points as indicated below that will be averaged

- a) Head area
- b) Chest area
- c) Lower Trunk area

2.2. EME measurements made on center roof mounted antennas

2.2.1. External vehicle EME measurement

With the survey meter and probe, take ten (10) measurements, at the standard test distance of 110 cm from the vehicle-mounted antenna, in a vertical line and then average the results. These measurements are taken and recorded at every twenty (20) centimeters over a range starting at twenty (20) centimeters above ground and ending at 2.0 meters; this would be representative of a person standing next to a vehicle during a mobile radio transmission.

2.2.2. Internal vehicle EME measurement

While rotating survey meter probe through 180 degrees to ensure that the highest level is found, scan the inside of the vehicle, both front and back seating areas, for the highest level in each location. After the highest level is found, scan vertically making two (2) additional measurements within an area approximately 40 cm wide (representing the width of a person) so as to have a total of three (3) measured points as indicated below that will be averaged.

- a) Head area
- b) Chest area
- c) Lower Trunk area

3. Approved Accessories

Antenna:

Model: TQC-400DII
Roof Mount 400-470 MHz
Gain: 5.5 dBi

Vehicle:

Band: BYD
Model: F6

4. Test Result

Measurement Information			
Measurement Freq.(MHz)	400.5000	435.0000	469.5000
Raw Data Power(W)	47.21	47.42	47.53
Controlled Limit(mW/cm ²)	1.3350	1.4500	1.5650
Uncontrolled Limit(mW/cm ²)	0.2670	0.2900	0.3130
Cal.	1.00	1.00	1.00
Antenna / gain(dBi)	Whip / 5.5	Whip / 5.5	Whip / 5.5
External Vehicle Power Density(50% duty)	average over body/2		
Internal Vehicle Power Density(50% duty)	average over (head/chest/leg)/2		

External Vehicle MPE Assessment at 450.5000 MHz						
Antenna Location	Antenna/gain	Meas. Distance (cm)	E/H Field	Calibration Factor	Average Over Body	Pwr. Density (mW/cm ²)
Trunk	Whip / 5.5	60	E	1.00	0.48	0.24
Measurement grid						
Test position	Height (cm)	% of controlled limit	Test position	Height (cm)	% of controlled limit	
1	20	8.1	6	120	29.7	
2	40	10.4	7	140	21.6	
3	60	13.3	8	160	14.4	
4	80	18.4	9	180	13.2	
5	100	30.1	10	200	12.1	

External Vehicle MPE Assessment at 435.0000 MHz						
Antenna Location	Antenna/gain	Meas. Distance (cm)	E/H Field	Calibration Factor	Average Over Body	Pwr. Density (mW/cm ²)
Trunk	Whip / 5.5	60	E	1.00	0.48	0.25
Measurement grid						
Test position	Height (cm)	% of controlled limit	Test position	Height (cm)	% of controlled limit	
1	20	8.5	6	120	31.2	
2	40	11.9	7	140	22.8	
3	60	15.3	8	160	15.3	
4	80	23.5	9	180	13.6	
5	100	30.7	10	200	10.7	

External Vehicle MPE Assessment at 469.5000 MHz						
Antenna Location	Antenna/gain	Meas. Distance (cm)	E/H Field	Calibration Factor	Average Over Body	Pwr. Density (mW/cm ²)
Trunk	Whip / 5.5	60	E	1.00	0.52	0.26
Measurement grid						
Test position	Height (cm)	% of controlled limit	Test position	Height (cm)	% of controlled limit	
1	20	8.4	6	120	26.3	
2	40	12.9	7	140	23.5	
3	60	13.4	8	160	10.9	
4	80	17.2	9	180	11.2	
5	100	25.0	10	200	9.8	

External Vehicle MPE Assessment at 400.5000 MHz						
Antenna Location	Antenna/gain	Meas. Distance (cm)	E/H Field	Calibration Factor	Average Over Body	Pwr. Density (mW/cm ²)
Trunk	Whip / 5.5	110	E	1.00	0.42	0.21
Measurement grid						
Test position	Height (cm)	% of controlled limit	Test position	Height (cm)	% of controlled limit	
1	20	5.1	6	120	11.4	
2	40	6.2	7	140	12.1	
3	60	5.8	8	160	11.5	
4	80	5.2	9	180	8.3	
5	100	8.6	10	200	4.7	

Internal Vehicle MPE Assessment at 400.5000 MHz						
Antenna Location	Antenna/gain	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head,Chest,Leg Back/Front Seats (mW/cm ²)	Pwr. Density of Higher Level (mW/cm ²)
Trunk	Whip / 5.5	Highest Reading	E	1.00	0.360/0.028	0.180/0.014
Measurement grid						
Test position	% of controlled limit Head		% of controlled limit Chest		% of controlled limit Leg	
Back Seat	10.2		6.4		3.3	
Front Sea	3.0		1.1		1.0	

Internal Vehicle MPE Assessment at 435.0000 MHz						
Antenna Location	Antenna/gain	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head,Chest,Leg Back/Front Seats (mW/cm ²)	Pwr. Density of Higher Level (mW/cm ²)
Trunk	Whip / 5.5	Highest Reading	E	1.00	0.320/0.0022	0.160/0.0011
Measurement grid						
Test position	% of controlled limit Head		% of controlled limit Chest		% of controlled limit Leg	
Back Seat	3.8		4.7		1.8	
Front Sea	5.3		5.2		1.4	


Internal Vehicle MPE Assessment at 469.5000 MHz						
Antenna Location	Antenna/gain	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head,Chest,Leg Back/Front Seats (mW/cm ²)	Pwr. Density of Higher Level (mW/cm ²)
Trunk	Whip / 5.5	Highest Reading	E	1.00	0.300/0.006	0.150/0.003
Measurement grid						
Test position	% of controlled limit Head		% of controlled limit Chest		% of controlled limit Leg	
Back Seat	12.4		11.5		8.1	
Front Sea	8.8		10.3		4.7	

Internal Vehicle MPE Assessment at 469.5000 MHz						
Antenna Location	Antenna/gain	Meas. Distance (cm)	E/H Field	Calibration Factor	Average over Head,Chest,Leg Back/Front Seats (mW/cm ²)	Pwr. Density of Higher Level (mW/cm ²)
Roof	Whip / 5.5	Highest Reading	E	1.00	0.240/0.010	0.120/0.005
Measurement grid						
Test position	% of controlled limit Head		% of controlled limit Chest		% of controlled limit Leg	
Back Seat	2.5		3.7		6.3	
Front Sea	1.7		1.2		1.8	


5. Conclusion

The measurement results comply with the FCC Limit Per 47 CFR 2.1091 (b) for the controlled RF Exposure.









6. Antenna Location Drawing



1 - Roof (center)
2 - Trunk (center)



7. Probe Calibration Certificates

	华南国家计量测试中心 广东省计量科学研究院 SOUTH CHINA NATIONAL CENTER OF METROLOGY GUANGDONG INSTITUTE OF METROLOGY	  校准 CNAS L0730
<h1>校准证书</h1> <h2>CALIBRATION CERTIFICATE</h2>		
证书编号 Certificate No.	WWD20101583	第 1 页, 共 3 页 Page of
委托方 Client	深圳华通威国际检验有限公司	
委托方地址 Add. of Client	深圳市南山区高新技术产业园科技南12路	
计量器具名称 Description	场强仪	
型号规格 Model/Type	FM5004/HI-6005	
制造厂 Manufacturer	AR	
出厂编号 Serial No.	300239/00064170	设备编号 Equipment No.
接收日期 Date of Receipt	2010年 10月 28日 Y M D	
结论 Conclusion	见校准结果页	
校准日期 Date of Calibration	2010年 11月 3日 Y M D	
批准人 Approved Signatory		
核 验 Inspected by		
校 准 Calibrated by		
	 证书专用章	
		
本中心地址: 中国广州市广园中路松柏东街30号 邮政编码: 510405 电话: (8620)86594172 传真: (8620)86590743 投诉电话: (8620)26296063 E-mail: scm@scm.com.cn Add: No.30, Songbaidong Street, Guangyuanzhong Road, Guangzhou, P. R. China Post Code: 510405 Tel: (8620)86594172 Fax: (8620)86590743 Complaint Tel: (8620)26296063 101028n07 1		



华南国家计量测试中心
广东省计量科学研究院
SOUTH CHINA NATIONAL CENTER OF METROLOGY
GUANGDONG INSTITUTE OF METROLOGY



说明

证书编号 WWD20101583
Certificate No.

DIRECTIONS

第 2 页, 共 3 页
Page of

1. 本中心是国家质量监督检验检疫总局在华南地区设立的国家法定计量检定机构, 计量授权证书号是: (国)法计(2007)01043号、(国)法计(2007)01032号。本中心是中国合格评定国家认可委员会(CNAS)认可实验室, 认可证书号为: CNAS L0730。

This laboratory is the National Legal Metrological Verification Institution in southern China set up by the General Administration of Quality Supervision, Inspection and Quarantine of the People's Republic of China (AQSIQ) under authorization certificates No.(2007)01043 & (2007)01032. This laboratory is accredited by China National Accreditation Service for Conformity Assessment under Laboratory Accreditation Certification No. CNAS L0730.

2. 本中心所出具的数据均可溯源至国家计量基准和国际单位制(SI)。

All data issued by this laboratory are traceable to national primary standards and International System of Units (SI).

3. 本次校准的技术依据:

Reference documents for the calibration:

IEEE 1309-2005 Calibration of electromagnetic field sensors and probes, excluding antennas, from 9 kHz to 40 HGz 频率为9KHz~40GHz的电磁场传感器和探头(天线除外)的校准
JJG 561-1988 RJ-3型近区电场测量仪试行检定规程 V. R. of Model RJ-3 Near-Zone Electric-Field Measuring Instruments

4. 本次校准所使用的主要计量标准器具:

Major standards of measurement used in the calibration:

设备名称/型号 Name of Equipment /Model	编号 Serial No.	证书号/有效期 Certificate No. /Due Date	计量特性 Metrological Characteristic
场强标准 TEM Cell /8801	014	WWD20100034 /2011-01-12	±1 dB
功率放大器 Power Amplifier /100W1000B	305581	WWS20100786 /2011-07-15	增益: $U_{rel}=1$ dB (k=2) Gain: $U_{rel}=1$ dB (k=2)
信号发生器 Signal Generator /E8267C	US42340272	WWS20100376 /2011-04-18	电平: $U_{rel}=0.20$ dB 频率: $U_{rel}=1 \times 10^{-8}$ (k=2) Level: $U_{rel}=0.20$ dB, Frequency: $U_{rel}=1 \times 10^{-8}$ (k=2)
电场探头/读出装置 Electromagnetic Field Meter/reader /EP183/8053A	000WJ40805&1420K211 37	XDdj2010-1988 /2011-09-24	$U=(0.94 \sim 1.3)$ dB, k=2

5. 校准地点、环境条件:

Place and environmental conditions of the calibration:

地点 无线电室 (Radio Lab.) Place	温度 (20±5) °C Temperature	相对湿度 <80 % RH
-------------------------------	-----------------------------	------------------

6. 被校准仪器限制使用条件:

Limiting condition of the instrument calibrated:

注: 1. 本证书校准结果只与受校准仪器有关。

2. 未经本中心书面批准, 不得部分复制此证书。

Note: 1. The results relate only to the items calibrated.

2. This certificate shall not be reproduced except in full, without the written approval of our laboratory.



华南国家计量测试中心
广东省计量科学研究院
SOUTH CHINA NATIONAL CENTER OF METROLOGY
GUANGDONG INSTITUTE OF METROLOGY



校准结果
RESULTS OF CALIBRATION

证书编号 WWD20101583
Certificate No.

原始记录号 020101583
Record No.

第 3 页, 共 3 页
Page of

1 场强测量准确度 (见表1)

Field Strength Measuring Accuracy (See Table 1)

表1 (Table 1)

探头 Probe	频率 Frequency	标准值 Reference Value	被检表示值 Indication Value	误差 (dB) Error	允许误差 MPE	结论 Conclusion
HI-6005	27 MHz	1 V/m	1.08 V/m	+0.67	±2.0 dB	合格(Pass)
	27 MHz	2 V/m	2.21 V/m	+0.87	±2.0 dB	合格(Pass)
	27 MHz	5 V/m	5.07 V/m	+0.12	±2.0 dB	合格(Pass)
	27 MHz	10 V/m	9.93 V/m	-0.06	±2.0 dB	合格(Pass)
	27 MHz	20 V/m	19.29 V/m	-0.31	±2.0 dB	合格(Pass)

2 频率响应 (见表2)

Frequency Response (See Table 2)

表2 (Table 2)

探头 Probe	频率 Frequency	标准值 Reference Value	被检表示值 Indication Value	误差 (dB) Error	允许误差 MPE	结论 Conclusion
HI-6005	100 kHz	10 V/m	8.30 V/m	-1.62	N/A	合格(Pass)
	1 MHz	10 V/m	9.83 V/m	-0.15	N/A	合格(Pass)
	10 MHz	10 V/m	10.44 V/m	+0.37	N/A	合格(Pass)
	27 MHz	10 V/m	9.93 V/m	-0.06	±2.0 dB	合格(Pass)
	50 MHz	10 V/m	9.74 V/m	-0.23	±2.0 dB	合格(Pass)
	100 MHz	10 V/m	9.82 V/m	-0.16	±2.0 dB	合格(Pass)
	200 MHz	10 V/m	9.68 V/m	-0.28	±2.0 dB	合格(Pass)
	300 MHz	10 V/m	9.36 V/m	-0.57	±2.0 dB	合格(Pass)
	1 GHz	10 V/m	9.12 V/m	-0.80	±2.0 dB	合格(Pass)
	2 GHz	10 V/m	9.76 V/m	-0.21	±2.0 dB	合格(Pass)
	3 GHz	10 V/m	9.03 V/m	-0.89	N/A	合格(Pass)

说明(Note):

1 测量结果的扩展不确定度:

Expanded uncertainty of measurement:

$U=1.5 \text{ dB}, k=2$

(依据 JJF1059-1999 测量不确定度评定与表示)

(In accordance with JJF1059-1999 Evaluation and Expression of Uncertainty in Measurement)

2 建议校准周期不超过1年。

The period of calibration advised within one year.

.....End of Report.....