



No. 1 Workshop, M-10, Middle section, Science & Technology Park,
 Shenzhen, Guangdong, China 518057
 Telephone: +86 (0) 755 2601 2053
 Fax: +86 (0) 755 2671 0594
 Email: ee.shenzhen@sgs.com

Report No.: SZEM180100098203
 Page: 1 of 8

RF Exposure Evaluation Report

Application No.: SZEM1801000982CR
Applicant: Hytera Communications Corporation Limited.
Address of Applicant: Hytera Tower, Hi-Tech Industrial Park North, 9108# Beihuan Road, Nanshan District, Shenzhen, People's Republic of China
Manufacturer: Hytera Communications Corporation Limited.
Address of Manufacturer: of Hytera Tower, Hi-Tech Industrial Park North, 9108# Beihuan Road, Nanshan District, Shenzhen, People's Republic of China
Factory: Hytera Communications Corporation Limited Baolong Branch
Address of Factory: Plant No.3, Hi-Tech Park, Baolong Industrial Area, Longgang District, Shenzhen, People's Republic of China
Product Name: Digital Mobile Radio
 * MD782i U(1), MD782iG U(1), MD780i U(1), MD780iG U(1), MD785i U(1), MD785iG U(1), MD786i U(1), MD786iG U(1), MD788i U(1), MD788iG U(1), MD782s U(1), MD782sG U(1), MD780s U(1), MD780sG U(1), MD785s U(1), MD785sG U(1), MD786s U(1), MD786sG U(1), MD788s U(1), MD788sG U(1) *
Model No.(EUT): Please refer to section 4.1 of this report which indicates which model was actually tested and which were electrically identical.
Trade Mark: Hytera
FCC ID: YAMMD78XIU1
Standards: 47 CFR Part 1.1307 (2016)
 47 CFR Part 1.1310 (2016)
Date of Receipt: 2018-05-23
Date of Test: 2018-05-25 to 2018-06-08
Date of Issue: 2018-06-12

| | |
|----------------------|--------------|
| Test Result : | PASS* |
|----------------------|--------------|

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Keny Xu

EMC Laboratory Manager


The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



2 Version

| Revision Record | | | | |
|-----------------|---------|------------|----------|----------|
| Version | Chapter | Date | Modifier | Remark |
| 01 | | 2018-06-12 | | Original |
| | | | | |
| | | | | |

| | | | | |
|--------------------------|--|---|--|--|
| Authorized for issue by: | | | | |
| | |  | | |
| | | Edison Li /Project Engineer | | |
| | |  | | |
| | | Eric Fu /Reviewer | | |



3 Contents

| | Page |
|---|-------------|
| 1 COVER PAGE..... | 1 |
| 2 VERSION | 2 |
| 3 CONTENTS | 3 |
| 4 GENERAL INFORMATION..... | 4 |
| 4.1 GENERAL DESCRIPTION OF EUT | 4 |
| 4.2 TEST LOCATION | 5 |
| 4.3 TEST FACILITY | 5 |
| 4.4 DEVIATION FROM STANDARDS..... | 5 |
| 4.5 ABNORMALITIES FROM STANDARD CONDITIONS | 5 |
| 4.6 OTHER INFORMATION REQUESTED BY THE CUSTOMER | 5 |
| 5 RF EXPOSURE EVALUATION..... | 6 |
| 5.1 RF EXPOSURE COMPLIANCE REQUIREMENT | 6 |
| 5.1.1 <i>Limits</i> | 6 |
| 5.1.2 <i>Test Procedure</i> | 6 |
| 5.1.3 <i>EUT RF Exposure Evaluation</i> | 7-8 |



4 General Information

4.1 General Description of EUT

| | |
|---------------------|--|
| Power supply: | 13.6VDC |
| Cable: | DC cable: 3100cm unshielded Control cable: 170cm unshielded Microphone: 100cm unshielded |
| Internal source: | More than 108MHz |
| Sample Type: | Fixed device |
| Frequency Range: | 400MHz to 470MHz |
| Modulation Type: | FM for Analog; 4FSK for Digital |
| Channel Separation: | 12.5KHz/25KHz for FM, 12.5KHz for 4FSK |
| Number of Channels: | The equipment is able to operate on any designated channel within the specified frequency range. |
| Antenna Type: | External |
| Antenna Gain: | 5.5dBi |

Remark:

Model No.: MD782i U(1), MD782iG U(1), MD780i U(1), MD780iG U(1), MD785i U(1), MD785iG U(1), MD786i U(1), MD786iG U(1), MD788i U(1), MD788iG U(1), MD782s U(1), MD782sG U(1), MD780s U(1), MD780sG U(1), MD785s U(1), MD785sG U(1), MD786s U(1), MD786sG U(1), MD788s U(1), MD788sG U(1)

Only the model MD782i U(1) was tested, since the electrical circuit design, layout, components used, internal wiring and functions were identical for all the above models, with only difference is the Item number and the sales areas for marketing purpose.



4.2 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China
518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

No tests were sub-contracted.

4.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

- **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

- **Industry Canada (IC)**

Two 3m Semi-anechoic chambers and the 10m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1, 4620C-2, 4620C-3..

4.4 Deviation from Standards

None.

4.5 Abnormalities from Standard Conditions

None.

4.6 Other Information Requested by the Customer

None.



5 RF Exposure Evaluation

5.1 RF Exposure Compliance Requirement

5.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

| Frequency range (MHz) | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm ²) | Averaging time (minutes) |
|--|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| (A) Limits for Occupational/Controlled Exposures | | | | |
| 0.3–3.0 | 614 | 1.63 | *(100) | 6 |
| 3.0–30 | 1842/f | 4.89/f | *(900/f ²) | 6 |
| 30–300 | 61.4 | 0.163 | 1.0 | 6 |
| 300–1500 | | | f/300 | 6 |
| 1500–100,000 | | | 5 | 6 |
| (B) Limits for General Population/Uncontrolled Exposure | | | | |
| 0.3–1.34 | 614 | 1.63 | *(100) | 30 |
| 1.34–30 | 824/f | 2.19/f | *(180/f ²) | 30 |
| 30–300 | 27.5 | 0.073 | 0.2 | 30 |
| 300–1500 | | | f/1500 | 30 |
| 1500–100,000 | | | 1.0 | 30 |

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

The limit of MPE is f/300 mW/cm² . If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

5.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.



5.1.3 EUT RF Exposure Evaluation

1) Test Results

The best case gain of the antenna is 5.5dBi. 5.5dB logarithmic terms convert to numeric result is nearly 3.55.

Low Power:

| FM | | 400~470MHz | | | | | |
|-----------------|----------------------------|--------------------------------|-------------------------|-----------------------------------|----------------------------------|-------------------------------------|-------------------------------------|
| Frequency (MHz) | Maximun Antenna Gain (dBi) | Maximum Antenna Gain (Numeric) | Peak Output Power (dBm) | Max Tune-up tolerance power (dBm) | Max Tune-up tolerance power (mW) | Power density (mW/cm ²) | Minimum Distance to Human body (cm) |
| 400.025 | 5.5 | 3.55 | 43.89 | 44 | 25118.86 | 1.33 | 72.93 |
| 450.025 | 5.5 | 3.55 | 43.85 | 44 | 25118.86 | 1.50 | 68.76 |
| 459.125 | 5.5 | 3.55 | 43.91 | 44 | 25118.86 | 1.53 | 68.08 |
| 469.975 | 5.5 | 3.55 | 43.92 | 44 | 25118.86 | 1.57 | 67.28 |
| 400.025 | 5.5 | 3.55 | 29.66 | 30 | 1000.00 | 1.33 | 14.55 |
| 450.025 | 5.5 | 3.55 | 29.86 | 30 | 1000.00 | 1.50 | 13.72 |
| 459.125 | 5.5 | 3.55 | 29.88 | 30 | 1000.00 | 1.53 | 13.58 |
| 469.975 | 5.5 | 3.55 | 29.78 | 30 | 1000.00 | 1.57 | 13.43 |
| 4FSK | | 400~470MHz | | | | | |
| Frequency (MHz) | Maximun Antenna Gain (dBi) | Maximum Antenna Gain (Numeric) | Peak Output Power (dBm) | Max Tune-up tolerance power (dBm) | Max Tune-up tolerance power (mW) | Power density (mW/cm ²) | Minimum Distance to Human body (cm) |
| 400.025 | 5.5 | 3.55 | 43.94 | 44 | 25118.86 | 1.33 | 72.93 |
| 450.025 | 5.5 | 3.55 | 43.86 | 44 | 25118.86 | 1.50 | 68.76 |
| 459.125 | 5.5 | 3.55 | 43.98 | 44 | 25118.86 | 1.53 | 68.08 |
| 469.975 | 5.5 | 3.55 | 43.96 | 44 | 25118.86 | 1.57 | 67.28 |
| 400.025 | 5.5 | 3.55 | 29.84 | 30 | 1000.00 | 1.33 | 14.55 |
| 450.025 | 5.5 | 3.55 | 30.00 | 30 | 1000.00 | 1.50 | 13.72 |
| 459.125 | 5.5 | 3.55 | 29.98 | 30 | 1000.00 | 1.53 | 13.58 |
| 469.975 | 5.5 | 3.55 | 29.97 | 30 | 1000.00 | 1.57 | 13.43 |



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM180100098203

Page: 8 of 8

High Power:

| FM | | 400~470MHz | | | | | |
|-----------------|----------------------------|--------------------------------|-------------------------|-----------------------------------|----------------------------------|-------------------------------------|-------------------------------------|
| Frequency (MHz) | Maximun Antenna Gain (dBi) | Maximum Antenna Gain (Numeric) | Peak Output Power (dBm) | Max Tune-up tolerance power (dBm) | Max Tune-up tolerance power (mW) | Power density (mW/cm ²) | Minimum Distance to Human body (cm) |
| 400.025 | 5.5 | 3.55 | 46.51 | 46.53 | 44977.99 | 1.33 | 97.62 |
| 450.025 | 5.5 | 3.55 | 46.52 | 46.53 | 44977.99 | 1.50 | 92.03 |
| 459.125 | 5.5 | 3.55 | 46.50 | 46.53 | 44977.99 | 1.53 | 91.12 |
| 469.975 | 5.5 | 3.55 | 46.48 | 46.53 | 44977.99 | 1.57 | 90.06 |
| 400.025 | 5.5 | 3.55 | 29.96 | 30 | 1000.00 | 1.33 | 14.56 |
| 450.025 | 5.5 | 3.55 | 30.00 | 30 | 1000.00 | 1.50 | 13.72 |
| 459.125 | 5.5 | 3.55 | 29.98 | 30 | 1000.00 | 1.53 | 13.59 |
| 469.975 | 5.5 | 3.55 | 29.89 | 30 | 1000.00 | 1.57 | 13.43 |
| 4FSK | | 400~470MHz | | | | | |
| Frequency (MHz) | Maximun Antenna Gain (dBi) | Maximum Antenna Gain (Numeric) | Peak Output Power (dBm) | Max Tune-up tolerance power (dBm) | Max Tune-up tolerance power (mW) | Power density (mW/cm ²) | Minimum Distance to Human body (cm) |
| 400.025 | 5.5 | 3.55 | 46.46 | 46.53 | 44977.99 | 1.33 | 97.62 |
| 450.025 | 5.5 | 3.55 | 46.51 | 46.53 | 44977.99 | 1.50 | 92.03 |
| 459.125 | 5.5 | 3.55 | 46.49 | 46.53 | 44977.99 | 1.53 | 91.12 |
| 469.975 | 5.5 | 3.55 | 46.48 | 46.53 | 44977.99 | 1.57 | 90.06 |
| 400.025 | 5.5 | 3.55 | 29.67 | 30 | 1000.00 | 1.33 | 14.56 |
| 450.025 | 5.5 | 3.55 | 29.40 | 30 | 1000.00 | 1.50 | 13.72 |
| 459.125 | 5.5 | 3.55 | 29.95 | 30 | 1000.00 | 1.53 | 13.59 |
| 469.975 | 5.5 | 3.55 | 29.79 | 30 | 1000.00 | 1.57 | 13.43 |

For Low power:

44 dBm is the declared maximum rated power, 30dBm is the declared low rated power by manufacturer

For High power:

46.53 dBm is the declared maximum rated power, 30dBm is the declared low rated power by manufacturer

To satisfy RF exposure requirements, a separation distance of 97.62 cm or more should be maintained between this device and persons during device operation. To ensure compliance, operations at closer than this distance is not recommended.

End of Report