

FCC PART 22, 74, 80 and 90

TEST REPORT

For

Hytera Communications Co., Ltd.

Hyt Tower, Hi-Tech Industrial Park North, Nanshan District, Shenzhen, China

FCC ID: YAMPD50XVHF

Report Type: **Product Type:** Class II Permissive Change Digital Portable Radio Candy, Li **Test Engineer:** Candy Li **Report Number:** RSZ140410001-00AA1 **Report Date:** 2014-05-27 Jimmy Xiao Jimmy Xiao **Reviewed By:** RF Engineer Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building, Prepared By: ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

TABLE OF CONTENTS

GENERAL INFORMATION	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
Objective	3
RELATED SUBMITTAL(S)/GRANT(S)	
TEST METHODOLOGY	
TEST FACILITY	4
SYSTEM TEST CONFIGURATION	5
DESCRIPTION OF TEST CONFIGURATION	5
EQUIPMENT MODIFICATIONS	5
SUPPORT EQUIPMENT LIST AND DETAILS	5
BLOCK DIAGRAM OF TEST SETUP	5
SUMMARY OF TEST RESULTS	6
FCC §1.1307(b) & §2.1093 - RF EXPOSURE	7
APPLICABLE STANDARD	
FCC §2.1053 & §22.861 & §74.461 & § 80.211 & §90.210 - RADIATED SPURIOUS EMISSIO	NS8
APPLICABLE STANDARD	8
TEST EQUIPMENT LIST AND DETAILS	8
TEST PROCEDURE	
Test Data	9
PRODUCT SIMILARITY DECLARATION LETTER	11

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *Hytera Communications Co., Ltd.*'s product, model number: *PD562 VHF (FCC ID: YAMPD50XVHF)* or the "EUT" in this report was a *Digital Portable Radio*, which was measured approximately: 234 mm (L) x 59 mm (W) x 45 mm (H), rated with input voltage: DC 7.4V battery.

Note: This series products model: PD560 VHF, PD562 VHF, PD565 VHF, PD566 VHF, PD568 VHF and HD565 VHF are electrically identical, they have the same PCB layout and schematic, the differences among them is just the model due to marketing purpose, model PD562 VHF was selected for fully testing, the detailed information can be referred to the attached declaration letter that stated and guaranteed by the applicant.

* All measurement and test data in this report was gathered from production sample serial number: 1404053 (Assigned by BACL, Shenzhen). The EUT supplied by the applicant was received on 2014-04-10.

Objective

This test report is prepared on behalf of *Hytera Communications Co.*, *Ltd.* in accordance with Part 2, and Part 90 of the Federal Communication Commissions rules.

This is a CIIPC application of the device, the differences between the original device and the current one are as follows:

- 1. Adding the display screen and keyboard (8 buttons) in new products, they have the same main board and transmitter module between the new models and original models.
- 2. Changing the model, the original models are PD500 VHF, PD502 VHF, PD505 VHF, PD506 VHF, PD508 VHF and HD505 VHF, and the new models are PD560VHF, PD562VHF, PD565VHF, PD566 VHF, PD568 VHF and HD565 VHF.

For the change made to the device, the test item "spurious radiated emissions" was performed.

Related Submittal(s)/Grant(s)

No related submittal.

Test Methodology

All tests and measurements indicated in this document were performed in accordance with the Code of federal Regulations Title 47 Part 2, Sub-part J as well as the following individual parts:

Part 22 – Public Mobile Service

Part 74 – Experimental Radio, Auxiliary, Special Broadcast and other Program Distributonal Service

Part 80 – Stantions in the Maritme Service

Part 90 - Private Land Mobile Radio Service

Applicable Standards: TIA 603-D and ANSI 63.4-2009.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement uncertainty with radiated emission is 5.91 dB for 30MHz-1GHz.and 4.92 dB for above 1GHz, 1.95dB for conducted measurement.

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on December 06, 2010. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in a test mode which has been done in the factory.


Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details

Manufacturer	Description	Serial Number		
N/A	50 ohm Load	N/A	N/A	

Block Diagram of Test Setup



§ 80.207;§90.209; §90.210 §2.1051; §22.861; §74.461;

> § 80.211;§90.210 §2.1053; §22.861;

<u>§74.461;</u> § 80.211;§90.210 §2.1055; § 22.355;

\$74.464; \$ 80.209; \$90.213 \$90.214

FCC Rules Description of Test Results §1.1307(b), §2.1093 RF Exposure Compliance §2.1046; § 22.727; §74.461; § 80.215; RF Output Power Compliance* §90.205 §2.1047; §74.463; Modulation Characteristic Compliance* §80.213;§90.207 §2.1049;§22.357;§ 22.731; §74.462; § 80.205; Occupied Bandwidth & Emission Mask Compliance*

Compliance*: Please referred to FCC ID: YAMPD50XVHF granted on 2014-04-11, report No.: RSZ131120002-00A, which was tested by Bay Area Compliance Laboratories Corp.

Spurious Emission at Antenna Terminal

Spurious Radiated Emissions

Frequency Stability

Transient Frequency Behavior

Report No.: RSZ140410001-00AA1

Compliance*

Compliance

Compliance*

Compliance*

FCC §1.1307(b) & §2.1093 - RF EXPOSURE

Applicable Standard

According to FCC §1.1307(b) and §2.1093, protable device operates Part 90 should be subjected to rountine environmental evaluation for RF exposure prior or equipment authorization or use.

Result: Compliance.

Please refer to SAR Report Number: RSZ140410001-20BA1

FCC §2.1053 & §22.861 & §74.461 & § 80.211 & §90.210 - RADIATED SPURIOUS EMISSIONS

Applicable Standard

FCC §2.1053, §22.861, §74.461, § 80.211 and §90.210

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date	
Rohde & Schwarz	EMI Test Receiver	ESCI	101122	2013-09-25	2014-09-25	
HP	Amplifier	8447E	1937A01046	2013-09-30	2014-09-30	
Sunol Sciences	Broadband Antenna	JB1	A040904-2	2011-11-28	2014-11-27	
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2013-11-12	2014-11-12	
Sunol Sciences	Horn Antenna	DRH-118	A052304	2011-12-01	2014-11-30	
HP	Synthesized Sweeper	8341B	2624A00116	2014-05-09	2015-05-09	
Mini-Circuits	Mini-Circuits Amplifier		5969001149	2014-04-03	2015-04-03	
A.H. System	A.H. System Horn Antenna		135	2012-02-11	2015-02-10	
COM POWER	COM POWER Dipole Antenna		041000	NCR	NCR	

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load, which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to teeth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in dB =10 1g (TXpwr in Watts/0.001)-the absolute level

Spurious attenuation limit in dB = $43+10 \text{ Log}_{10}$ (power out in Watts)

Spurious attenuation limit in dB = $50+10 \text{ Log}_{10}$ (power out in Watts) for EUT with a 12.5 kHz channel bandwidth.

Test Data

Environmental Conditions

Temperature:	26 ℃
Relative Humidity:	55 %
ATM Pressure:	101.0 kPa

The testing was performed by Candy Li on 2014-05-08.

Test Mode: Transmitting

30MHz - 5GHz:

	Pacaivar	Receiver Turn		Rx Antenna		Substituted			FCC	
Frequency (MHz) Ro	Reading (dBµV) Table Angle Degree	Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)	Absolute Level (dBm)	Limit (dBm)	Margin (dB)	
	Analog Modulation (159.0 MHz), For FCC Part 22/74/80/90									
636	33.62	182	1.7	Н	-63.4	0.57	0	-63.97	-20	43.97
636	37.99	65	1.4	V	-59.0	0.57	0	-59.57	-20	39.57
795	34.70	323	1.2	Н	-62.3	0.65	0	-62.95	-20	42.95
795	38.38	173	1.4	V	-58.6	0.65	0	-59.25	-20	39.25
1431	45.93	196	1.2	Н	-54.7	0.88	9.00	-46.58	-20	26.58
1431	57.27	250	2.2	V	-44.2	0.88	9.00	-36.08	-20	16.08
Digital Modulation (159.0 MHz), For FCC Part 22/74/80/90										
636	33.58	286	1.2	Н	-63.4	0.57	0	-63.97	-20	43.97
636	37.97	114	2.0	V	-59.0	0.57	0	-59.57	-20	39.57
795	35.26	156	2.3	Н	-61.7	0.65	0	-62.35	-20	42.35
795	38.92	181	2.3	V	-58.1	0.65	0	-58.75	-20	38.75
1431	44.43	201	1.9	Н	-56.2	0.88	9.00	-48.08	-20	28.08
1431	54.79	254	2.4	V	-46.7	0.88	9.00	-38.58	-20	18.58

Note:

Absolute Level = SG Level - Cable loss + Antenna Gain

Margin = Limit- Absolute Level



Hytera Communications Co.,Ltd.
HYT Tower, Hi-Tech Industrial Park North, Nanshan District, Shenzhen China
Tel: +86-0755-26972999- 1210 Fax: 0755-86137130

2014-1-14

Product Similarity Declaration

To Whom It May Concern,

We, Hytera Communications Corporation Ltd., hereby declare that our Digital Portable Radio, Model Number: PD560 VHF,PD565 VHF,PD566 VHF,PD568 VHF,HD565 VHF are electrically identical with PD562 VHF that was certified by BACL. There are named differently due to market purpose.

Please contact me if you have any question.

Signature:

Lei Xiong

General Director

***** END OF REPORT *****