



MPE TEST REPORT

FCC Per 47 CFR 2.1091(b)

Report Reference No	WE11030046
FCC ID	YAMRD98XU2
Compiled by (position+printed name+signature)...	File administrators Eric Zhang 
Supervised by (position+printed name+signature)...	Test Engineer Wenliang Li 
Approved by (position+printed name+signature)...	Manager Jimmy Li 
Date of issue	Apr 25, 2011
Testing Laboratory Name	Shenzhen Huatongwei International Inspection Co., Ltd
Address	Keji Nan No.12 Road, Hi-tech Park, Shenzhen, China
Applicant's name	Hytera Communications Corporation Ltd.
Address	HYT Tower, Hi-Tech Industrial Park North, Nanshan District, Shenzhen China. 518057
Test specification:	
Standard	FCC Per 47 CFR 2.1091(b) OET Bulletin 65 Supplement C [June 2001]
TRF Originator	Shenzhen Huatongwei International Inspection CO., Ltd
Master TRF	Dated 2006-06
Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.	
This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.	
Test item description	Digital Base Station Repeater
Trade Mark	
Manufacturer	Hytera Communications Corporation Ltd.
Model/Type reference	RD982 U(2)/ RD985 U(2)/ RD986 U(2)/ RD988 U(2)
Listed Models	/
Channel Separation	12.5KHz
Modulation	FM&4FSK
Ratings	DC 13.60 V
Frequency Range	From 450 MHz to 520 MHz
Rated Power	5Watt(36.99dBm)-50Watt(46.99dBm) Continuous
Result	Positive

M P E T E S T R E P O R T

FCC ID :	YAMRD98XU2	Apr 25, 2011
		Date of issue

Equipment under Test : Digital Base Station Repeater

Model /Type : RD982 U(2)/ RD985 U(2)/ RD986 U(2)/ RD988 U(2)

Listed Models : /

Applicant : **Hytera Communications Corporation Ltd.**

Address : HYT Tower,Hi-Tech Industrial Park North,Nanshan District,Shenzhen China.518057

Manufacturer : **Hytera Communications Corporation Ltd.**

Address : HYT Tower,Hi-Tech Industrial Park North,Nanshan District,Shenzhen China.518057

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

1.	<u>SUMMARY</u>	<u>4</u>
1.1.	EUT configuration	4
1.2.	Product Description	4
1.3.	Equipment under Test	4
1.4.	Note	5
2.	<u>TEST ENVIRONMENT.....</u>	<u>6</u>
2.1.	Address of the test laboratory	6
2.2.	Environmental conditions	6
2.3.	Statement of the measurement uncertainty	6
3.	<u>METHOD OF MEASUREMENT</u>	<u>6</u>
3.1.	Applicable Standard	6
3.2.	Limit	7
3.3.	MPE Calculation Method	7
4.	<u>CONCLUSION</u>	<u>8</u>

1. SUMMARY

1.1. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

- - supplied by the manufacturer
- - supplied by the lab

● Power Cable	Length (m) :	3
	Shield :	Unshield
	Detachable :	Detachable
○ Multimeter	Manufacturer :	/
	Model No. :	/

1.2. Product Description

The Hytera Communications Corporation Ltd.'s Model: RD982 U(2)/ RD985 U(2)/ RD986 U(2)/ RD988 U(2) or the "EUT" as referred to in this report; more general information as follows:

Name of EUT	Digital Base Station Repeater	
Model Number	RD982 U(2)/ RD985 U(2)/ RD986 U(2)/ RD988 U(2)	
FCC ID	YAMRD98XU2	
Rated Output Power	5Watt(36.99dBm)-50Watt(46.99dBm) Continuous	
Operation Type	The repeater cannot operate on multi-channels	
Support data rate	9.6kbps	
Modulation Type	FM for Analog Voice	
	4FSK for Digital Voice/Digital Data	
	Analog	11K0F3E for 12.5KHz Channel Separation
	Digital	7K60FXD for Digital Data only 7K60FXW for Digital Data & Digital Voice
Channel Separation	Analog Voice	12.5KHz
	Digital Voice/Data	12.5KHz
Antenna Type	External	
Frequency Range	From 450 MHz to 520 MHz	
Maximum Output Power	Analog	50.00 W for 12.5 KHz Channel Separation
	Digital	50.35 W for 12.5 KHz Channel Separation

Note: The product has the same digital working characters when operating in both two digitized voice/data mode (7K60FXD and 7K60FXW). So only one set of test results for digital modulation modes are provided in this test report.

1.3. Equipment under Test

Power supply system utilised

Power supply voltage	:	<input type="radio"/> 120V / 60 Hz	<input type="radio"/> 115V / 60Hz
		<input type="radio"/> 12 V DC	<input type="radio"/> 24 V DC
		<input checked="" type="radio"/> Other (specified in blank below)	

DC 13.60 V

Test frequency list

Modulation Type	Test Channel	Test Frequency
Analog/FM	Low Channel	450.5000 MHz
	Middle Channel	485.0000 MHz
	High Channel	519.5000 MHz
Digital/4FSK	Low Channel	450.5000 MHz
	Middle Channel	485.0000 MHz
	High Channel	519.5000 MHz

1.4. Note

1. The EUT is a U frequency band (450-520MHz) Digital Base Station Repeater, The functions of the EUT listed as below:

	Test Standards	Reference Report
Radio	FCC Part 90	WE11030045
MPE	FCC Oet 65	WE11030046

2. TEST ENVIRONMENT

2.1. Address of the test laboratory

Shenzhen Huatongwei International Inspection Co., Ltd
Keji Nan No.12 Road, Hi-tech Park, Shenzhen, China
Phone: 86-755-26715686 Fax: 86-755-26748089

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 (2009) and CISPR Publication 22.

2.2. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 ° C
Humidity:	30-60 %
Atmospheric pressure:	950-1050mbar

2.3. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen Huatongwei International Inspection Co., Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen Huatongwei laboratory is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.24 dB	(1)
Radiated Emission	1~18GHz	5.16 dB	(1)
Radiated Emission	18-40GHz	5.54 dB	(1)
Conducted Disturbance	0.15~30MHz	3.39 dB	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3. Method of measurement

3.1. Applicable Standard

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

OET Bulletin 65 Supplement C [June 2001]: Evaluating Compliance with FCC Guidelines for Human Exposure to Radio frequency Electromagnetic Fields

3.2. Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

3.3. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

From the peak EUT RF output power, the minimum mobile separation distance, R=3.5 m, as well as the maximum gain of the used antenna is 6.5 dBi, the RF power density can be obtained.

TEST RESULTS

For FM Modulation @ 12.5 KHz Channel Separation @ Rated High Power

Test Frequency (MHz)	Minimum Separation Distance (cm)	Output Power (dBm)	Output Power (mW)	Antenna Gain (Nemeric)	Power Density Limit (mW/cm ²)	Power Density At 350 cm (mW/cm ²)	Test Results
450.5000	350.00	46.82	48083.90	4.4668	1.5017	0.1395	Compliance
485.0000	350.00	46.99	50003.50	4.4668	1.6167	0.1451	Compliance
519.5000	350.00	46.85	48417.20	4.4668	1.7317	0.1405	Compliance

For 4FSK Modulation @ 12.5 KHz Channel Separation @ Rated High Power

Test Frequency (MHz)	Minimum Separation Distance (cm)	Output Power (dBm)	Output Power (mW)	Antenna Gain (Nemeric)	Power Density Limit (mW/cm ²)	Power Density At 350 cm (mW/cm ²)	Test Results
450.5000	350.00	46.82	48083.90	4.4668	1.5017	0.1395	Compliance
485.0000	350.00	47.02	50350.10	4.4668	1.6167	0.1461	Compliance
519.5000	350.00	46.92	49204.00	4.4668	1.7317	0.1428	Compliance

For FM Modulation @ 12.5 KHz Channel Separation @ Rated Low Power

Test Frequency (MHz)	Minimum Separation Distance (cm)	Output Power (dBm)	Output Power (mW)	Antenna Gain (Nemeric)	Power Density Limit (mW/cm ²)	Power Density At 350 cm (mW/cm ²)	Test Results
450.5000	350.00	36.63	4602.60	4.4668	1.5017	0.0134	Compliance
485.0000	350.00	36.74	4720.60	4.4668	1.6167	0.0137	Compliance
519.5000	350.00	36.92	4920.40	4.4668	1.7317	0.0143	Compliance

For 4FSK Modulation @ 12.5 KHz Channel Separation @ Rated Low Power

Test Frequency (MHz)	Minimum Separation Distance (cm)	Output Power (dBm)	Output Power (mW)	Antenna Gain (Nemeric)	Power Density Limit (mW/cm ²)	Power Density At 350 cm (mW/cm ²)	Test Results
450.5000	350.00	36.71	4688.10	4.4668	1.5017	0.0136	Compliance
485.0000	350.00	36.72	4698.90	4.4668	1.6167	0.0136	Compliance
519.5000	350.00	36.86	4852.90	4.4668	1.7317	0.0141	Compliance

4. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 (b) for the controlled RF Exposure.

.....**End of Report**.....