

## FCC PART 24D & PART 90

### TEST REPORT

For

## Hytera Communications Co., Ltd.

HYT Tower, Hi-Tech Industrial Park North,  
Nanshan District, Shenzhen, China

**FCC ID: YAMX1PU5**

<b>Report Type:</b> Class II Permissive Change	<b>Product Type:</b> Digital Portable Radio
<b>Test Engineer:</b> Bell Hu	<i>Bell Hu</i>
<b>Report Number:</b> RSZ131225001-00A1	
<b>Report Date:</b> 2014-01-22	
<b>Reviewed By:</b> RF Engineer	<i>Jimmy Xiao</i>
<b>Prepared By:</b> Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 <a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a>	

**Note:** This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

## TABLE OF CONTENTS

<b>GENERAL INFORMATION</b> .....	<b>3</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
OBJECTIVE.....	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST METHODOLOGY.....	3
TEST FACILITY.....	4
<b>SYSTEM TEST CONFIGURATION</b> .....	<b>5</b>
DESCRIPTION OF TEST CONFIGURATION.....	5
EQUIPMENT MODIFICATIONS.....	5
<b>SUMMARY OF TEST RESULTS</b> .....	<b>6</b>
<b>FCC §2.1049 &amp; §24.131 &amp; §90.209 &amp; §90.210 – EMISSION MASK</b> .....	<b>7</b>
APPLICABLE STANDARD.....	7
TEST EQUIPMENT LIST AND DETAILS.....	7
TEST PROCEDURE.....	8
TEST DATA.....	8

## GENERAL INFORMATION

---

### Product Description for Equipment under Test (EUT)

The *Hytera Communications Co., Ltd.*'s product, model number: *XIp U(5) (FCC ID: YAMX1PU5)* or the "EUT" in this report was a *Digital Portable Radio*, which was measured approximately: 21.1 cm (L) x 6.0 cm (W) x 2.1 cm (H), rated with input voltage: DC 7.4V battery.

*\* All measurement and test data in this report was gathered from production sample serial number: 1312119 (Assigned by BACL, Shenzhen). The EUT supplied by the applicant was received on 2013-12-08.*

### Objective

This test report is prepared on behalf of *Hytera Communications Co., Ltd.* in accordance with Part 2, and Part 24D, 90 of the Federal Communication Commissions rules.

This is a CIIPC application of the device for adding emission mask of G, H and J.

### Related Submittal(s)/Grant(s)

No related submittal(s).

### Test Methodology

All tests and measurements indicated in this document were performed in accordance with the Code of federal Regulations Title 47 Part 2, Sub-part J as well as the following individual parts:

Part 24 – Personal Communications Service  
Part 90 – Private Land Mobile Radio Service

Applicable Standards: TIA 603-D and ANSI 63.4-2009.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement uncertainty with radiated emission is 5.91 dB for 30MHz-1GHz.and 4.92 dB for above 1GHz, 1.95dB for conducted measurement.

## **Test Facility**

The test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on December 06, 2010. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

## **SYSTEM TEST CONFIGURATION**

---

### **Description of Test Configuration**

The system was configured for testing in a test mode which has been done in the factory.

### **Equipment Modifications**

No modification was made to the EUT tested.

**SUMMARY OF TEST RESULTS**

FCC Rules	Description of Test	Results
§2.1093	RF Exposure	Compliance*
§2.1046; § 24.132; §90.205	RF Output Power	Compliance*
§2.1047; §90.207	Modulation Characteristic	Compliance*
§2.1049; § 24.131; §90.209; §90.210	Occupied Bandwidth & Emission Mask	Compliance
§2.1051; § 24.133; §90.210	Spurious Emission at Antenna Terminal	Compliance*
§2.1053; § 24.133; §90.210	Spurious Radiated Emissions	Compliance*
§2.1055; § 24.135; §90.213	Frequency Stability	Compliance*
§90.214	Transient Frequency Behavior	Not Applicable

Compliance\*: Please refer to the report number RSZ130508001-00B granted on 2013-08-08, with FCC ID: YAMX1PU5.

## **FCC §2.1049 & §24.131 & §90.209 & §90.210 – EMISSION MASK**

### **Applicable Standard**

FCC §2.1049, §90.209 and §90.210

Emission Mask G. For transmitters that are not equipped with an audio low-pass filter, the power of any emission must be attenuated below the unmodulated carrier power (P) as follows:

- (1) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (fd in kHz) of more than 10 kHz, but no more than 250 percent of the authorized bandwidth: At least 116 log (fd/6.1) dB, or 50 + 10 log (P) dB, or 70 dB, whichever is the lesser attenuation;
- (2) On any frequency removed from the center of the authorized bandwidth by more than 250 percent of the authorized bandwidth: At least 43 + 10 log (P) dB.

Emission Mask H. For transmitters that are not equipped with an audio low-pass filter, the power of any emission must be attenuated below the unmodulated carrier power (P) as follows:

- (1) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (fd in kHz) of 4 kHz or less: Zero dB.
- (2) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (fd in kHz) of more than 4 kHz, but no more than 8.5 kHz: At least 107 log (fd/4) dB;
- (3) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (fd in kHz) of more than 8.5 kHz, but no more than 15 kHz: At least 40.5 log (fd/1.16) dB;
- (4) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (fd in kHz) of more than 15 kHz, but no more than 25 kHz: At least 116 log (fd/6.1) dB;
- (5) On any frequency removed from the center of the authorized bandwidth by more than 25 kHz: At least 43 + log (P) dB.

Emission Mask J. For transmitters that are not equipped with an audio low-pass filter, the power of any emission must be attenuated below the unmodulated carrier power of the transmitter (P) as follows:

- (1) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (fd in kHz) of more than 2.5 kHz, but no more than 6.25 kHz: At least 53 log (fd/2.5) dB;
- (2) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (fd in kHz) of more than 6.25 kHz, but no more than 9.5 kHz: At least 103 log (fd/3.9) dB;
- (3) On any frequency removed from the center of the authorized bandwidth by a displacement frequency (fd in kHz) of more than 9.5 kHz: At least 157 log (fd/5.3) dB, or 50 + 10 log (P) dB or 70 dB, whichever is the lesser attenuation.

### **Test Equipment List and Details**

<b>Manufacturer</b>	<b>Description</b>	<b>Model No.</b>	<b>Serial No.</b>	<b>Calibration Date</b>	<b>Calibration Due Date</b>
R&S	Signal analyzer	FSV	-	2013-11-28	2014-11-27

**Test Procedure**

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

The resolution bandwidth of the spectrum analyzer was set at 300 Hz and the spectrum was recorded in the frequency band  $\pm 50$  kHz from the carrier frequency.


**Test Data**

**Environmental Conditions**

<b>Temperature:</b>	22 °C
<b>Relative Humidity:</b>	35 %
<b>ATM Pressure:</b>	101.0 kPa

The testing was performed by Bell Hu on 2013-12-09.


**806.5 MHz, Emission Mask H**



Date: 9.DEC.2013 17:33:51




### 809.5 MHz, Emission Mask G



Date: 9.DEC.2013 17:00:36


### 851.5 MHz, Emission Mask H



Date: 9.DEC.2013 14:36:32



**939.5 MHz, Emission Mask J**



Date: 9.DEC.2013 16:34:47

**\*\*\*\*\* END OF REPORT \*\*\*\*\***