

RF Exposure Report

Report No.: MFBFBE-WTW-P21070951A

FCC ID: YAW529027-Z

Test Model: PVS6

Received Date: 2022/4/14

Test Date: 2022/5/19

Issued Date: 2022/6/22

Applicant: SunPower Corporation

Address: 1414 Harbour Way South Suite 1901, Richmond, CA 94804, USA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan

Test Location: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan

**FCC Registration /
Designation Number:** 723255 / TW2022



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specifically mentioned, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE)	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
2.4 Antenna Gain	6
2.5 Calculation Result	7
Appendix	8

Release Control Record

Issue No.	Description	Date Issued
MFBFBE-WTW-P21070951A	Original release.	2022/6/22

1 Certificate of Conformity

Product: SunPower Monitoring System with PVS6

Brand: SUNPOWER

Test Model: PVS6

Sample Status: Engineering sample

Applicant: SunPower Corporation

Test Date: 2022/5/19

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : Vivian Huang , **Date:** 2022/6/22
Vivian Huang / Specialist

Approved by : May Chen , **Date:** 2022/6/22
May Chen / Manager

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	f/1500	30
1500-100,000	1.0	30

f = Frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

$$Pd = (Pout * G) / (4 * \pi * r^2)$$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 25 cm away from the body of the user. So, this device is classified as **Mobile Device**.

2.4 Antenna Gain

WLAN							
Ant No.	Chain No.	Brand	Model	Antenna Net Gain (dBi)	Frequency rang (GHz)	Antenna type	Connector type
1	Chain 0 (Including BT)	airgain	65-031-212002B	2.2	2.4~2.4835	PCB	I-PEX
				3.8	5.15~5.25		
				4.2	5.725~5.85		
2	Chain 1 (WLAN use only)	airgain	65-031-212003B	4.2	2.4~2.4835	PCB	I-PEX
				4.1	5.15~5.25		
				4.8	5.725~5.85		
LTE							
Ant No.	Brand	Model	Antenna Gain (dBi)	Frequency rang (MHz)	Antenna type	Connector type	
4	airgain	65-031-212001B	2.7	1850~1910	PCB	I-PEX	
				1710~1755			
				698~716			

*The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

2.5 Calculation Result

Operation Mode	Evaluation Frequency (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Test Result
WLAN 2.4GHz	2412-2462	762.15	4.2	25	0.25524	1	Pass
WLAN 5GHz (U-NII-1)	5180-5240	199.38	4.1	25	0.06525	1	Pass
WLAN 5GHz (U-NII-3)	5745-5825	268.355	4.8	25	0.10319	1	Pass
Bluetooth	2402-2480	5.26	2.2	25	0.00111	1	Pass
LTE <Worst band>	2412-2462	110	2.7	25	0.03758	0.46647	Pass

Note:

- Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

Conclusion:

The formula of calculated the MPE is:

$$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$$

CPD = Calculation power density

LPD = Limit of power density

$$\text{WLAN 2.4GHz} + \text{Bluetooth} + \text{LTE} = 0.25524 / 1 + 0.00111 / 1 + 0.03758 / 0.46647 = 0.33691$$

$$\text{WLAN 5GHz} + \text{Bluetooth} + \text{LTE} = 0.10319 / 1 + 0.00111 / 1 + 0.03758 / 0.46647 = 0.18486$$

Therefore the maximum calculations of above situations are less than the "1" limit.

Appendix

LTE module

MPE Evaluation for FCC ID: XMR2020BG95M1

Operation Mode	Evaluation Frequency (MHz)	The Worst Case		Max Avg. Power		Directional Gain	Power Density (mW/cm ²)		Ratio
		Channel Number	Freq. (MHz)	mW	dBm		dBi	Value	
LTE (Band 2)	1850.7-1909.3	18607	1850.7	158.49	22.00	2.70	0.03758	1	0.03758
LTE (Band 4)	1710.7-1754.3	19957	1710.7	158.49	22.00	2.70	0.03758	1	0.03758
LTE (Band 12)	699.7-715.3	23017	699.7	158.49	22.00	2.70	0.03758	0.46647	0.08056

*Distance = 25 cm

--- END ---