

TEST REPORT
No.: 18-1-0048601T01a-C2

According to:

FCC Regulations

Part 15.205
Part 15.209
Part 15.407

ISED-Regulations

RSS-Gen, Issue 5
RSS-247, Issue 2

for

Robert Bosch Car Multimedia GmbH

AIVIV20
Navigationsystem with WLAN and Bluetooth

FCC ID: YBN-AIVIV20
ISED: 9595A-AIVIV20

1

Laboratory Accreditation and Listings		
  Deutsche Akkreditierungsstelle D-PL-12047-01-01 D-PL-12047-01-03 D-PL-12047-01-04 Accredited EMC-Test Laboratory	 Industry Canada Reg. No.: 3462D-1 Reg. No.: 3462D-2 Reg. No.: 3462D-3	 Voluntary Controls for Electromagnetic Emissions Reg. No.: 4452, C-20009, T-20006, G-20013
 AUTHORIZED RF LABORATORY	 Lab Code: 20011130-00	 MRA US-EU 0003
accredited according to DIN EN ISO/IEC 17025		
CETECOM GmbH Laboratory Radio Communications & Electromagnetic Compatibility Im Teelbruch 116 • 45219 Essen • Germany Registered in Essen, Germany, Reg. No.: HRB Essen 8984 Tel.: + 49 (0) 20 54 / 95 19-954 • Fax: + 49 (0) 20 54 / 95 19-964 E-mail: info@cetecom.com • Internet: www.cetecom.com		
Laboratory Accreditation and Listings		

Table of Contents

1. SUMMARY OF TEST RESULTS.....	3
1.1. Tests measurement overview according to US CFR Title 47, Subpart 15C	3
1.2. Attestation:.....	6
2. ADMINISTRATIVE DATA	7
2.1. Identification of the testing laboratory.....	7
2.2. Test location	7
2.3. Organizational items	7
2.4. Applicant's details	7
2.5. Manufacturer's details	7
3. EQUIPMENT UNDER TEST (EUT).....	8
3.1. Certification Data of Main EUT declared by Applicant	8
3.2. WLAN 5 GHz 802.11a/n Technical Data Of Main EUT as Declared by Applicant	10
3.3. EUT: Type, S/N etc. and short descriptions used in this test report	11
3.4. Auxiliary Equipment (AE): Type, S/N etc. and short descriptions.....	11
3.5. EUT set-ups	11
3.6. EUT operating modes	12
3.7. Worst case identification	14
4. DESCRIPTION OF TEST SYSTEM SET-UP'S	15
4.1. Test system set-up for conducted measurements on antenna port	15
4.2. Test system set-up for radiated magnetic field measurements below 30 MHz.....	17
4.3. Test system set-up for radiated electric field measurement 30 MHz to 1 GHz	18
4.4. Test system set-up for radiated electric field measurement above 1 GHz	19
5. MEASUREMENTS	20
5.1. Duty-Cycle.....	20
5.2. General Limit – Maximum power output conducted and maximum EIRP power.....	21
5.3. RF Parameter - 6dB, 26 dB and 99% occupied Bandwidth	26
5.4. RF Parameter – Peak Power Spectral Density (PPSD).....	29
5.5. RF-Parameter – Frequency Stability.....	32
5.6. General Limit - Radiated field strength emissions below 30 MHz.....	34
5.7. General Limit - Radiated field strength emissions, 30 MHz - 1 GHz.....	37
5.8. General Limit - Radiated emissions, above 1 GHz.....	41
5.9. RF-Parameter - Radiated Band-Edge compliance measurements.....	45
5.10. Measurement uncertainties	48
6. ABBREVIATIONS USED IN THIS REPORT	49
7. ACCREDITATION DETAILS OF CETECOM'S LABORATORIES AND TEST SITES	49
8. INSTRUMENTS AND ANCILLARY.....	50
9. VERSIONS OF TEST REPORTS (CHANGE HISTORY)	54
END OF TEST REPORT	54

Table of annex

	Total pages
Annex 1: Test result diagrams (separate document) CETECOM-TR18-1-0048601T01a-A1	259
Annex 2: External photographs of EUT (separate document) CETECOM- TR18-1-0048601T03a-A2	6
Annex 3: Internal photographs of EUT (separate document supplied by customer)	--
Annex 4: Test set-up photographs (separate document) CETECOM- TR18-1-0048601T03a -A4	6

1. Summary of test results

The test results apply exclusively to the test samples as presented in this report. The CETECOM GmbH does not assume responsibility for any conclusions and generalizations taken in conjunction with other specimens or samples of the type of the item presented to tests. Also we refer on special conditions which the applicant should fulfill according §2.927 to §2.948, special focus regarding modification of the equipment and availability of sample equipment for market surveillance tests.

The presented Equipment Under Test (in this report, hereinafter referred as EUT) supports radiofrequency technologies with WLAN technology and operating frequency range at 5.150 to 5.850 GHz according to IEE 802.11 a. The EUT integrates a WLAN transmitter. Other implemented wireless technologies were not considered within this test report.

Following test cases have been performed to show compliance with valid Part 15.407/15.209 of the FCC CFR Title 47 Rules, Edition 2017 and ISED RSS-247 Issue 2/RSS-Gen Issue 5 standards.

1.1. Tests measurement overview according to US CFR Title 47, Subpart 15C

Test cases	Port	References and Limits			EUT set-up	EUT op. mode	Result
		FCC Standard	RSS Standard	Test limit			
TX-Mode							
99% occupied bandwidth	Antenna terminal (conducted)	2.1049(h)	RSS-Gen, Issue 5 Chapter 6.6	99% Power bandwidth	2	1	Pass
26 dB bandwidth	Antenna terminal (conducted)	§15.303 + §15.407(a) (2) (5)	RSS-Gen, Issue 5 Chapter 6.6	26 dB spectral density bandwidth	2	1	Pass
Duty-Cycle	Antenna terminal (conducted)	KDB789033 + ANSI C63.10:2013	KDB789033 + ANSI C63.10:2013	No Limit Criteria	2	1	Pass
Transmitter frequency stability	Antenna terminal (conducted)	§ 2.1055 + §15.407(g)	RSS-Gen, Issue 5: Chapter 6.11	Operation within designated operational band	2	1	Pass

Maximum output power	Antenna terminal (conducted)	§15.407(a) (1)(iv) 5.15-5.25 GHz Client devices (2) 5.25-5.35 GHz & 5.47-5.725 GHz (3) 5.725-5.85 GHz	RSS-247, Issue 2 Chapter 6.2.1.1 6.2.2.1 6.2.3.1 6.2.4.1	Power Limits (if Antenna Gain < 6 dBi) 250 mW lesser of 250mW or 11dBm+10logB 1 W		2	1	Pass
Peak Power Spectral density	Antenna terminal (conducted)	§15.407(a) (1)(iv) 5.15-5.25 GHz Client devices (2) 5.25-5.35 GHz & 5.47-5.725 GHz (3) 5.725-5.85 GHz	RSS-247, Issue 2 Chapter 6.2.1.1 6.2.2.1 6.2.3.1 6.2.4.1	Power Spectral Density Limits (if Antenna Gain < 6 dBi) 11dBm/MHz 11dBm/MHz 30dBm/500kHz		2	1	Pass
Maximum e.i.r.p. power	Antenna terminal (conducted) + Antenna Gain	§15.407(a) (1)(iv) 5.15-5.25 GHz Client devices (2) 5.25-5.35 GHz & 5.47-5.725 GHz (3) 5.725-5.85 GHz	RSS-247, Issue 2 Chapter 6.2.1.1 6.2.2.1 6.2.3.1 6.2.4.1	e.i.r.p. Limits (if Antenna Gain < 6 dBi) 250 mW + 6 dBi lesser of 250mW or 11dBm+10logB + 6 dBi 1 W + 6 dBi		2	1	Pass
Antenna gain information	Antenna terminal (conducted)	§15.407(a) (1)(2)(3)	RSS-247, Issue 2 chapter 6.2.1.1 6.2.2.1 6.2.3.1 6.2.4.1	< 6dBi or if Antenna directional Gain > 6dBi reduction of Max. power & power spectral density by the amount in dB that the directional gain of the antenna exceeds 6 dBi		--	--	Measured Antenna Gain.

General field strength emissions within restricted bands + Band-Edge compliance radiated	Enclosure + Inter-connecting cables (radiated)	§15.407(b) (1)(2)(3)(4)(5)(6) (7)(8) §15.205 + §15.209	RSS-Gen, Issue 5 + RSS-247, Issue 2 Chapter 6.2.1.2 , 6.2.2.2 6.2.3.2, + 6.2.4.2 RSS-Gen, Issue 5 + RSS-247, Issue 2 Chapter 6.2.1.2 , 6.2.2.2 6.2.3.2, + 6.2.4.2	5150-5250 MHz 5250-5350 MHz 5470-5725 MHz all emissions outside operating band shall not exceed -27 dBm/MHz e.i.r.p. 5725-5850 MHz Spectrum Mask acc. to (4)(i) Restricted band limits + General field strength limits	1	1	Pass
Transmit power control + Dynamic frequency selection (DFS)	Antenna terminal (conducted)	§15.407 (h1)(h2)	RSS-Gen, Issue 5 + RSS-247, Issue 2 Chapter 6.3	Requirements: Masters Active clients Passive clients	2	3	Pass *1)
Discontinuous transmissions + Device security	FIRMWARE	§15.407(c) + §15.407(i)	RSS-247, Issue 2 Chapter 6.4 a + b + c	No transmissions in case of either absence of information to transmit or operational failure + Protection of firmware by unauthorized parties	--	--	Not tested Applicants declaration of implementation
AC-Power Lines Conducted Emissions	AC-Power lines or Battery Charger	§15.207(a)	RSS-Gen, Issue 5 : Chapter 8.8 Table 2	AC Power line conducted limits	--	--	Not applicable

Remark 1) Please refer to separate FCC RF Test Report CETECOM_18-1-0239001T03a

RF-Exposure Evaluation (separation distance user to RF-radiating element greater 20cm)							
Test cases	Port	References & Limits			EUT set-up	EUT Op mode	Result
		FCC Standard	RSS Section	Test Limit			
Radio frequency radiation exposure requirements	Cabinet + Inter-connecting cables (radiated)	§1.1310(b) §2.1091 §2.1093	RSS-102 Issue 5	SAR-Limits FCC: 1.1310(b)	1	1	See separate test reports CETECOM_TR 18-1-0048601T05a
				RF-Field Strength Limits: FCC: “general population/uncontrolled” environment Table 1 ISED: Table 4	1	1	

1.2. Attestation:

I declare that all measurements were performed by me or under my supervision and that all measurements have been performed and are correct to my best knowledge and belief to Innovation , Science and Economic Development (ISED) Canada standards. All requirements as shown in above table are met in accordance with enumerated standards.

The current version of the Test Report CETECOM_TR18-1-0048601T01a-C2 replaces the Test Report CETECOM_TR18-1-0048601T01a-C1 dated 2019-01-30. The replaced test report is herewith invalid.

.....
Dipl.-Ing. Niels Jeß
Responsible for test section

.....
B.Sc. Mohamed Ahmed
Responsible for test report

2. Administrative Data

2.1. Identification of the testing laboratory

Company name:	CETECOM GmbH
Address:	Im Teelbruch 116 45219 Essen - Kettwig Germany
Responsible for testing laboratory:	Dipl.-Ing. Niels Jeß

2.2. Test location

2.2.1. Test laboratory “CTC”

Company name:	see chapter 2.1. Identification of the testing laboratory
---------------	---

2.3. Organizational items

Responsible for test report and Project leader:	B.Sc. Mohamed Ahmed Dipl.-Ing. N. Perez
Receipt of EUT:	2018-08-20
Date(s) of test:	2018-08-22 - 2018-12-18
Date of report:	2019-02-04
<hr/>	
Version of template: 13.02	

2.4. Applicant's details

Applicant's name:	Robert Bosch Car Multimedia GmbH
Address:	Robert-Bosch-Straße 200 31139 Hildesheim Germany
Contact :	Mr. Salvatore Miraglia

2.5. Manufacturer's details

Manufacturer's name:	see applicant's details
Address:	see applicant's details

3. Equipment under test (EUT)

3.1. Certification Data of Main EUT declared by Applicant

Model Nr.	AIVIV20
Type	Navigationsystem with WLAN and Bluetooth
FCC ID	AIVIV20
IC/ ISED	YBN-AIVIV20
Frequency range (US/Canada -bands)	<input checked="" type="checkbox"/> 5150 MHz (Channel 36) to 5250 MHz (Channel 48) <input checked="" type="checkbox"/> for 20/40/80 MHz BW <input checked="" type="checkbox"/> 5250 MHz (Channel 52) to 5350 MHZ (Channel 64) <input checked="" type="checkbox"/> for 20/40/80MHz BW <input checked="" type="checkbox"/> 5470 MHz (Channel 100) to 5725 MHZ (Channel 140) <input checked="" type="checkbox"/> for 20/40/80MHz BW <input checked="" type="checkbox"/> 5725 MHz (Channel 149) to 5850 MHZ (Channel 165) <input checked="" type="checkbox"/> for 20/40/80MHz BW
Type of modulation	See chapter 3.2
Antenna Type	<input checked="" type="checkbox"/> Integrated <input type="checkbox"/> External, no RF- connector <input type="checkbox"/> External, separate RF-connector
Antenna Model	PCB Antenna
Max. Antenna Gain	3.8 dBi

Max. Conducted Output Power	RMS [dBm]
U-NII-1	802.11a: 8.2 802.11n20: 8.25 802.11ac20: 4.25 802.11n40: 8.51 802.11ac40: 4.32 802.11ac80: 3.94
U-NII-2A	802.11a: 8.02 802.11n20: 7.94 802.11ac20: 3.78 802.11n40: 8.15 802.11ac40: 4.02 802.11ac80: 3.57
U-NII-2C	802.11a: 8.07 802.11n20: 8.1 802.11ac20: 3.98 802.11n40: 7.81 802.11ac40: 3.97 802.11ac80: 3.03
U-NII-3	802.11a: 8.08 802.11n20: 8.1 802.11ac20: 4.37 802.11n40: 8.23 802.11ac40: 4.06 802.11ac80: 3.59
Installed options	<input checked="" type="checkbox"/> 802.11 a/n/ac <input checked="" type="checkbox"/> 802.11 b/g/n (not tested within this report) <input checked="" type="checkbox"/> Bluetooth LE (not tested within this report) <input checked="" type="checkbox"/> Bluetooth EDR (not tested within this report)
Power supply	<input type="checkbox"/> Internal battery Li-Io, range 3.5V to 4.1V <input type="checkbox"/> over AC/DC adapter: 110V/60 Hz <input checked="" type="checkbox"/> Nominal Test Voltage : 13.5 V DC with external power supply
Special EMI components	--
EUT sample type	<input type="checkbox"/> Production <input checked="" type="checkbox"/> Pre-Production <input type="checkbox"/> Engineering
FCC label attached	<input type="checkbox"/> yes <input checked="" type="checkbox"/> no

Remark:

3.2. WLAN 5 GHz 802.11a/n Technical Data Of Main EUT as Declared by Applicant

Firmware Version	--		
Frequency Channel B.W. (USA bands only)**	U-NII 1: 5150-5250 MHz	<input checked="" type="checkbox"/> Ch 36 40 44 48	<input checked="" type="checkbox"/> Bandwidth 20 MHz
		<input checked="" type="checkbox"/> Ch. 38 46	<input checked="" type="checkbox"/> Bandwidth 40 MHz
		<input checked="" type="checkbox"/> Ch. 42	<input checked="" type="checkbox"/> Bandwidth 80 MHz
	U-NII2A: 5250-5350 MHz	<input checked="" type="checkbox"/> Ch 52 56 60 64	<input checked="" type="checkbox"/> Bandwidth 20 MHz
		<input checked="" type="checkbox"/> Ch. 54 62	<input checked="" type="checkbox"/> Bandwidth 40 MHz
		<input checked="" type="checkbox"/> Ch. 58	<input checked="" type="checkbox"/> Bandwidth 80 MHz
U-NII 2C: 5470-5725 MHz		<input checked="" type="checkbox"/> Ch 100 104 108	
		<input checked="" type="checkbox"/> Ch 112 116 120	<input checked="" type="checkbox"/> Bandwidth 20 MHz
		<input checked="" type="checkbox"/> Ch 124 128 132	
		<input checked="" type="checkbox"/> Ch 136 140	
		<input checked="" type="checkbox"/> Ch. 102 110 118	<input checked="" type="checkbox"/> Bandwidth 40 MHz
		<input checked="" type="checkbox"/> Ch 126 134	
		<input checked="" type="checkbox"/> Ch 106 122	<input checked="" type="checkbox"/> Bandwidth 80 MHz
		<input checked="" type="checkbox"/> Ch 149 153 157	<input checked="" type="checkbox"/> Bandwidth 20 MHz
U-NII 3: 5725 -5850 MHz		<input checked="" type="checkbox"/> Ch 161 165	
		<input checked="" type="checkbox"/> Ch 151 159	<input checked="" type="checkbox"/> Bandwidth 40 MHz
		<input checked="" type="checkbox"/> Ch 155	<input checked="" type="checkbox"/> Bandwidth 80 MHz
802.11a – Mode OFDM Modulation Data Rates	<input checked="" type="checkbox"/> BPSK 6 Mbps / 9 Mbps		
	<input checked="" type="checkbox"/> QPSK 12 Mbps / 18 Mbps		
	<input checked="" type="checkbox"/> 16-QAM 24 Mbps / 36 Mbps		
	<input checked="" type="checkbox"/> 64-QAM 48 Mbps / 54 Mbps		
802.11n – Mode OFDM Modulation Data Rates	<input checked="" type="checkbox"/> HT20 (MCS0 – MCS7) 7.2/14.4/21.7/28.9/43.3/57.8/65/72.2 Mbps		
	<input checked="" type="checkbox"/> HT40 (MCS0 – MCS7) 15/30/45/60/90/120/135/150 Mbps		
802.11ac – Mode OFDM Modulation Data Rates	<input checked="" type="checkbox"/> HT20 (MCS0 – MCS9) 7.2/14.4/21.7/28.9/43.3/57.8/65/72.2 Mbps		
	<input checked="" type="checkbox"/> HT40 (MCS0 – MCS9) 15/30/45/60/90/120/135/150 Mbps		
	<input checked="" type="checkbox"/> HT80 (MCS0 – MCS9) 7.2/14.4/21.7/28.9/43.3/57.8/65/72.2 Mbps		
Power Supply	<input checked="" type="checkbox"/> Nominal Test Voltage : 13.5V DC with external power supply		
Special EMI Components	--		
EUT sample type	<input type="checkbox"/> Production	<input checked="" type="checkbox"/> Pre-Production	<input type="checkbox"/> Engineering
FCC label attached	<input type="checkbox"/> yes	<input checked="" type="checkbox"/> no	

3.3. EUT: Type, S/N etc. and short descriptions used in this test report

Short description*)	EUT	Type	S/N serial number	HW hardware status	SW software status
EUT A S06	AIVIV20	Navigationsystem with WLAN and Bluetooth	0005021	Version D	283C37820R
EUT B S04	AIVIV20	Navigationsystem with WLAN and Bluetooth	0005013	Version D	283C37820R

*) EUT short description is used to simplify the identification of the EUT in this test report.

3.4. Auxiliary Equipment (AE): Type, S/N etc. and short descriptions

AE short description *)	Auxiliary Equipment	Type	S/N serial number	HW hardware status	SW software status
AE 1	USB-cable (Dongle)	0,38m	S7291GC0003 79	Version-D1	--
AE 2	Power Supply Cable	--	--	--	--
AE 3	Notebook	Lenovo X200S	LVZT1DG	--	--

*) AE short description is used to simplify the identification of the auxiliary equipment in this test report.

3.5. EUT set-ups

EUT set-up no.*)	Combination of EUT and AE	Description
set. 1	EUT A + AE 1 + AE 2	Radiated measurement set-up
set. 2	EUT B + AE 1 + AE 2	Conducted measurement set-up

*) EUT set-up no. is used to simplify the identification of the EUT set-up in this test report.

3.6. EUT operating modes

EUT operating mode no.*1)	Description of operating modes	Additional information
op. 1	TX-Mode Burst 20MHz	With help of special test firmware WLAN is switched to a bandwidth of 20MHz and a continuous traffic mode in burst mode (duty cycle >98%) was set-up *2)
op. 2	TX-Mode Burst 40MHz	With help of special test firmware WLAN is switched to a bandwidth of 40MHz and a continuous traffic mode in burst mode (duty cycle >98%) was set-up *2)
op. 3	TX-Mode Burst 80MHz	With help of special test firmware WLAN is switched to a bandwidth of 80MHz and a continuous traffic mode in burst mode (duty cycle >98%) was set-up *2)
op. 4	Normal mode	

*1) EUT operating mode no. is used to simplify the test report.

*2) Please refer to document "Instructions_RadioTypeApproval_9_6_2017" dated 2017-06-09 for additional information regarding operating mode setup and output power levels.

3.6.1. Test tool information

Labtool version: 2.0.0.75

Labtool date: Mar 18 2015 (15:56:06)

The following settings have been done under SW Labtool:

Make the main settings which only have to be set once (per session):

30 0 (Choose the 2,4G band) or 30 1 (Choose the 5G band)

112 0 (20 MHz Bandwidth) or 112 1 (40 MHz Bandwidth) or 112 4 (80 MHz Bandwidth)

Q:\MB\cTP\06_Models_Test_Results\B-Sample\SB032_cTP_My\03_Inbetriebnahme\labtool_for_wi...

```
Enter option: 1
Name: DutApiClass
Interface: EtherNet
Version: 2.0.0.75
Date: Mar 18 2015 (15:56:06)

Note:

Q:\MB\cIP\06_Models_Test_Results\B-Sample\SB032_cTP_My\03_Inbetriebnahme\labto...
ol_for_win_22075_p22\setup.ini
Dut's IP 192.168.1.40:9930
Host's IP 192.168.1.1:9931
DutIf_UdpIp::delay 0
DutIf_UdpIp::vg_IfSpy 0
TCP connecting...
DutIf_InitConnection: 0

W87xx <802.11a/g/b/n/ac> TEST MENU

Enter option: 30 0
DutIf_SetModeAG: 0x0
Enter option: 112 0
DutIf_SetChannelBw: 0x00000000
Enter option: _
```

Now the parameters for Channel, Power level and modulation group has to be done:

22 1 14 0

```
Enter option: 22 1 17 0
DutIf_SetRfChannel: 0x0
DutIf_SetRfPowerCal: 0x0
Enter option:
```

For 802.11b the Power level is always 14 and the modulation group is 0

For 802.11g the Power level is always 11 and the modulation group is 1

For 802.11n (2,4GHz) the Power level is always 11 and the modulation group is 1

For 802.11n (5GHz) the Power level is always 10 and the modulation group is 1

For 802.11a the Power level is always 10 and the modulation group is 1

For 802.11ac the Power level is always 6 and the modulation group is 1

If a continuous burst is required use instead of the command 25 the command 17:

17 1 4

```
Enter option: 17 1 4
DutIf_SetIxDataRate: 0x00000000
TRPC IID: 2
DutIf_SetIxContMode: 0x00000000
Enter option:
```

11b		11g/a		11n		11ac	
ID	DataRate	ID	DataRate	ID	DataRate	ID	DataRate
1	1M	6	6M	15	MCS0	101	VHT_SS1_MCS0
2	2M	7	9M	16	MCS1	102	VHT_SS1_MCS1
3	5.5M	8	12M	17	MCS2	103	VHT_SS1_MCS2
4	11M	9	18M	18	MCS3	104	VHT_SS1_MCS3
		10	24M	19	MCS4	105	VHT_SS1_MCS4
		11	36M	20	MCS5	106	VHT_SS1_MCS5
		12	48M	21	MCS6	107	VHT_SS1_MCS6
		13	54M	22	MCS7	108	VHT_SS1_MCS7
						109	VHT_SS1_MCS8
						110	VHT_SS1_MCS9

In order to stop the TX:

17 0

```
Enter option: 17 0
DutIf_SetTxContMode: 0x00000000
Enter option:
```

3.7. Worst case identification

The following WLAN modes were used for testing

WLAN Mode	Data Rate
802.11a	18Mbps
802.11n, 20MHz bandwidth	MCS7
802.11ac, 20MHz bandwidth	MCS1
802.11n, 40MHz bandwidth	MCS3
802.11ac, 40MHz bandwidth	MCS4
802.11ac, 80MHz bandwidth	MCS1

4. Description of test system set-up's

4.1. Test system set-up for conducted measurements on antenna port


Conducted Set-up W1

Conducted RF-Setup 1 (W1 Set-up)

General description:

The EUT's RF-signal is coupled out by a suitable antenna coupling connector (1). The signal is first attenuated (2) then connected to the power meter (3) for conducted power measurements. The specific attenuation loss is determined prior to the measurement within a set-up attenuation measurement. These are then taken into account by correcting the measurement readings.

Schematic:



Testing method:

ANSI C63.10:2013,
KDB 789033 D02 General UNII Test Procedures New Rules v01r04

Used Equipment


	Passive Elements	Test Equipment	Remark:
	<input checked="" type="checkbox"/> 20 dB Attenuator <input checked="" type="checkbox"/> Low loss RF-cables <input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> Power Meter <input checked="" type="checkbox"/> DC-Power Supply <input checked="" type="checkbox"/> Spectrum-Analyser	See List of equipment under each test case and chapter 8 for calibration info

Measurement uncertainty

See chapter 5.7

Conducted Set-up W2**Conducted RF-Setup 2 (W2 Set-up)****General description:**

The EUT's RF-signal is coupled out by a suitable antenna coupling connector (1). The signal is first attenuated (2) then connected to spectrum-analyzer (4) for RF-conducted measurements. The specific attenuation loss is determined prior to the measurement within a set-up attenuation measurement. These are then taken into account by correcting the measurement readings of the spectrum-analyzer.

Schematic:**Testing method:**

ANSI C63.10:2013,
KDB 789033 D02 General UNII Test Procedures New Rules v01r04

Used Equipment

Passive Elements	Test Equipment	Remark:
<input checked="" type="checkbox"/> 20 dB Attenuator <input checked="" type="checkbox"/> Low loss RF-cables	<input checked="" type="checkbox"/> Power Meter <input checked="" type="checkbox"/> DC-Power Supply <input checked="" type="checkbox"/> Spectrum-Analyser	See List of equipment under each test case and chapter 8 for calibration info

Measurement uncertainty

See chapter 5.7


4.2. Test system set-up for radiated magnetic field measurements below 30 MHz

Specification: ANSI C63.4-2014 §5.3, §8.2.1, §8.3.1.1+§8.3.2.1 , ANSI C63.10-2013 chapter 6.4 (§6.4.4.2)

General Description: Evaluating the radiated field emissions are done first by an exploratory emission measurement and a final measurement for most critical frequencies determined.

The loop antenna was placed at 1 m height above ground plane and 3 m measurement distance from set-up for investigations. Because of reduced measurement distance, correction data were applied, as stated in chapter “General Limit - Radiated field strength emissions below 30 MHz“. The tests are performed in the semi anechoic room recognized by the regulatory commission.

Schematic:



Testing method:

Exploratory, preliminary measurement
The EUT and its associated accessories are placed on a non-conductive position manipulator (tipping device) of 0.8 m height which is placed on the turntable. By rotating the turntable (step 90°, range 0° to 360°) and the EUT itself either on 3-orthogonal axis (portable equipment) or 2-orthogonal axis (defined operational position of EUT), the emission spectrum was recorded. The loop antenna was moved at least to 2-perpendicular axes (antenna vector in direction of EUT and parallel to EUT) in order to maximize the emissions. The results are documented in a diagram. Critical frequencies (low margin to limit) are saved within a data reduction table for further investigations. If various operating modes are supported, further investigations are made to find the worst-case. Also the interconnection cables and equipment position were varied in order to maximize the emissions.

Final measurement on critical frequencies

Based on the exploratory measurements, the most critical frequencies are re-measured by maintaining the EUT's worst-case operation mode, cable position, etc.

First a frequency zoom around the critical frequency is done to locate the frequency more precisely. After this step, for all identified critical frequencies, the maximum peak was determined.

Following parameters were varied: the turntable angle continuously in the range 0 to 360 degree, the EUT itself either over 3-orthogonal axis (not defined usage position) or 2-orthogonal axis (defined usage position).

On the determined worst-case position, a final measurement with necessary bandwidth and detector according standard has been carried out.

Formula:

$$E_C = E_R + AF + C_L + D_F - G_A$$

$$M = L_T - E_C$$

AF = Antenna factor

C_L = Cable loss

D_F = Distance correction factor

E_C = Electrical field – corrected value

E_R = Receiver reading

G_A = Gain of pre-amplifier (if used)

L_T = Limit

M = Margin

All units are dB-units, positive margin means value is below limit.

Distance correction:

Reference for applied correction (extrapolating) factors due to reduced measurement distance:


ANSI C63.10:2013, §6.4.4.2 - Equations (2) + (3) + (4)

4.3. Test system set-up for radiated electric field measurement 30 MHz to 1 GHz

Specification: ANSI C63.4-2014 chapter 8.2.3, ANSI C63.10-2013 chapter 6.5

General Description: Evaluating the field emissions have to be done first by an exploratory emissions measurement and a final measurement for most critical frequencies. The tests are performed in a NSA-compliant semi anechoic room (SAR) recognized by the regulatory commissions.

Schematic:



Testing method:

Exploratory, preliminary measurements

The EUT and its associated accessories are placed on a non-conductive position manipulator (tipping device) of 0.8 m height which is placed on the turntable. By rotating the turntable (range 0° to 360°, step 90°) and the EUT itself either on 3-orthogonal axis (portable equipment) or 2-orthogonal axis (defined operational position of EUT) the emission spectrum and it's characteristics was recorded with an EMI-receiver, broadband antenna and software.

Measurement antenna: horizontal and vertical, heights: 1,0 m and 1,82 m as worst-case determined by an exploratory emission measurements. The results are documented in a diagram. Critical frequencies (low margin to limit) are saved within a table for further investigations. If various operating modes are supported, further investigations are made to find the worst-case of them. Also the interconnection cables and equipment position were varied in order to maximize the emissions.

Formula:

$$E_C = E_R + AF + C_L + D_F - G_A \quad (1)$$

$$M = L_T - E_C \quad (2)$$

Final measurement on critical frequencies

Based on the exploratory measurements, the most critical frequencies are re-measured by maintaining the EUT's worst-case operation mode, cable position, etc. either on 10m OATS or 3m semi-anechoic room.

First a frequency zoom around the critical frequency is done to locate the frequency more precisely. After this step, for all identified critical frequencies, the maximum peak was determined.

Following parameters were varied: the turntable angle continuously in the range 0 to 360 degree, the EUT itself either over 3-orthogonal axis (not defined usage position) or 2-orthogonal axis (defined usage position). The measurement antenna height between 1 m and 4 m.

On the determined worst-case position, a final measurement with necessary bandwidth and detector according standard has been carried out.

AF = Antenna factor

C_L = Cable loss

D_F = Distance correction factor (if used)

E_C = Electrical field – corrected value

E_R = Receiver reading

G_A = Gain of pre-amplifier (if used)

L_T = Limit

M = Margin


All units are dB-units, positive margin means value is below limit.

4.4. Test system set-up for radiated electric field measurement above 1 GHz

Specification: ANSI C63.4-2014 chapter 8.3, ANSI C63.10-2013 chapter 6.6.3.3 & 6.6.4

General Description: Evaluating the emissions have to be done first by an exploratory emissions measurement and a final measurement for most critical frequencies. The tests are performed in a CISPR 18-1-4:2010 compliant fully anechoic room (FAR) recognized by the regulatory commission. The measurement distance was set to 3 meter for frequencies up to 18 GHz and 2 meter above 18 GHz. A logarithmic periodic antenna is used for the frequency range 30 MHz to 1 GHz. Horn antennas are used for frequency range 1 GHz to 40 GHz. The EUT is aligned within 3 dB beam width of the measurement antenna with three orthogonal axis measurements on the EUT.

Schematic:



Testing method:

Exploratory, preliminary measurements

The EUT and its associated accessories are placed on a non-conductive position manipulator (tipping device) of 1.55 m height which is placed on the turntable. By rotating the turntable (range 0° to 360°, step 15°) and the EUT itself either on 3-orthogonal axis (portable equipment) or 2-orthogonal axis (defined operational position of EUT) the emission spectrum and it's characteristics was recorded with an EMI-receiver, broadband antenna and software. The measurements are performed in horizontal and vertical polarization of the measurement antennas. The results are documented in a diagram. Critical frequencies (low margin to limit) are saved within a table for further investigations. If various operating modes are supported, further investigations are made to find the worst-case of them. Also the interconnection cables and equipment position were varied in order to maximize the emissions.

Final measurement on critical frequencies

Based on the exploratory measurements, the most critical frequencies are re-measured by maintaining the EUT's worst-case operation mode, cable position, etc.

First a frequency zoom around the critical frequency is done to locate the frequency more precisely. After this step, for all identified critical frequencies, the maximum peak was determined. Following parameters were varied: the turntable angle continuously in the range 0 to 360 degree, the EUT itself over 3-orthogonal axis and the height for EUT with large dimensions.

On the determined worst-case position, a final measurement with necessary bandwidth and detector according standard has been carried out. On the determined worst-case position, a final measurement with necessary bandwidth and detector according standard has been carried out.

Formula:

$$E_C = E_R + AF + C_L + D_F - G_A \quad (1)$$

$$M = L_T - E_C \quad (2)$$

E_C = Electrical field – corrected value

E_R = Receiver reading

M = Margin

L_T = Limit

AF = Antenna factor

C_L = Cable loss

D_F = Distance correction factor (if used)

G_A = Gain of pre-amplifier (if used)

All units are dB-units, positive margin means value is below limit.

5. Measurements

5.1. Duty-Cycle

5.1.1. Test location and equipment (for reference numbers please see chapter 'List of test equipment')

Ambient Climatic conditions	Temperature: (22±2)°C		Rel. humidity: (45±15)%		
test site	<input type="checkbox"/> 441 EMI SAR	<input type="checkbox"/> 348 EMI cond.	<input type="checkbox"/> 443 EMI FAR	<input type="checkbox"/> 347 Radio.lab.	<input type="checkbox"/> 337 OATS <input checked="" type="checkbox"/> TS 8997
equipment	<input type="checkbox"/> 331 HC 4055	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
spectr. analys.	<input checked="" type="checkbox"/> 683 FSU26	<input type="checkbox"/> 120 FSEM	<input type="checkbox"/> 264 FSEK	<input type="checkbox"/>	<input type="checkbox"/>
power meter	<input type="checkbox"/> 262 NRV-S	<input type="checkbox"/> 266 NRV-Z31	<input type="checkbox"/> 265 NRV-Z33	<input type="checkbox"/> 261 NRV-Z55	<input type="checkbox"/> 356 NRV-Z1
multimeter	<input type="checkbox"/> 341 Fluke 112	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
DC power	<input type="checkbox"/> 086 LNG50-10	<input type="checkbox"/> 087 EA3013	<input type="checkbox"/> 354 NGPE 40	<input type="checkbox"/> 349 car battery	<input type="checkbox"/> 350 Car battery <input checked="" type="checkbox"/> 463 HP3245A
line voltage	<input checked="" type="checkbox"/> 13.5 V DC		<input type="checkbox"/> 060 120 V 60 Hz via PAS 5000		
otherwise	<input type="checkbox"/> 530 Attenuator 10dB	<input checked="" type="checkbox"/> K4 Cable			

The necessary duty-cycle correction factor is determined on nominal conditions on one channel in each operable frequency-band. It is assumed that no noticeable changes occur when tested on other channels or climatic conditions. The Duty-Cycle was constant, means without variations.

5.1.2. Results

- The results were corrected in order to evaluate for worst-case result each time when average values are necessary for example average radiated emissions or similar
- No correction necessary: Duty-Cycle > 98%

5.2. General Limit – Maximum power output conducted and maximum EIRP power

5.2.1. Test location and equipment (for reference numbers please see chapter 'List of test equipment')

test location	<input checked="" type="checkbox"/> CETECOM Essen (Chapter. 2.2.1)	<input type="checkbox"/> 443 System CTC-FAR-EMI-	<input type="checkbox"/> Please see Chapter. 2.2.3
test site	<input type="checkbox"/> 441 EMI SAR	<input type="checkbox"/> 487 SAR NSA	<input type="checkbox"/> TS 8997
receiver	<input type="checkbox"/> 377 ESCS30	<input type="checkbox"/> 001 ESS	<input type="checkbox"/> 489 ESU 40
spectr. analys.	<input checked="" type="checkbox"/> 584 FSU	<input type="checkbox"/> 120 FSEM	<input type="checkbox"/> 264 FSEK
antenna	<input type="checkbox"/> 574 BTA-L	<input type="checkbox"/> 133 EMCO3115	<input type="checkbox"/> 302 BBHA9170
signaling	<input type="checkbox"/> 392 MT8820A	<input type="checkbox"/> 436 CMU	<input type="checkbox"/> 547 CMU
otherwise	<input type="checkbox"/> 266 NRV-Z31	<input type="checkbox"/> 600 NRVD	<input type="checkbox"/> 110 USB LWL
DC power	<input checked="" type="checkbox"/> 671 EA-3013S	<input type="checkbox"/> 463 HP3245A	<input type="checkbox"/> 459 EA 2032-50
otherwise	<input type="checkbox"/> 331 HC 4055	<input type="checkbox"/> 248 6 dB Attenuator	<input type="checkbox"/> 529 Power divider
			<input type="checkbox"/> - cable OTA20
Supply voltage	<input checked="" type="checkbox"/> 13.5V DC		<input type="checkbox"/> K 4 Cable kit
		<input type="checkbox"/> 060 110 V 60 Hz via PAS 5000	

5.2.2. Reference

FCC	<input checked="" type="checkbox"/> Part 15 Subpart C, §15.407(a)(1)(2)(3)(4)
ISED	<input checked="" type="checkbox"/> RSS-247, Issue 2
ANSI	<input checked="" type="checkbox"/> C63.10-2013
KDB Guidance no.	<input checked="" type="checkbox"/> 789033 D02 General UNII test procedures v01r03: Subchapter E, Method PM (3)(a) <input checked="" type="checkbox"/> 662911 D01 V02r01 (MIMO, Smart-antenna)
Limits (For the band 5600–5650 MHz, no operation in Canada is permitted)	<p><input checked="" type="checkbox"/> U-NII 1: 5.15-5.25 GHz: FCC Outdoor access point: 1W + antenna gain max. 6dBi + Elevation > 30° 21 dBm EIRP FCC Indoor Access Point: 1W + antenna gain max. 6dBi FCC Mobile & Portable client: 250mW + antenna gain max. 6dBi</p> <p>ISED: <input type="checkbox"/> E.I.R.P. max. 200mW or $10+10\log_{10}(B)$ whichever power is less <input checked="" type="checkbox"/> OEM device installed on vehicles: 30mW EIRP or $1.76 + 10\log_{10}(B) + \text{TPC capability}$ <input checked="" type="checkbox"/> U-NII2: 5.25-5.35 GHz: FCC: lesser of 250mW or $11\text{dBm}+10\log_{10}(B)$</p> <p>ISED: <input type="checkbox"/> max. conducted output power: 250mW or $11\text{dBm}+10\log_{10}(B) + \text{Antenna gain} < 6\text{dBi}$ <input type="checkbox"/> EIRP Elevation Mask requierements if max. EIRP>200mW <input type="checkbox"/> Max. EIRP 1Watt or $17+10\log_{10}(B)$ whichever power less <input checked="" type="checkbox"/> OEM device installed on vehicles: 30mW EIRP or $1.76 + 10\log_{10}(B) + \text{TPC capability}$ <input checked="" type="checkbox"/> U-NII2extension: 5.470-5.725 GHz: FCC: lesser of 250mW or $11\text{dBm}+10\log_{10}(B) + \text{Antenna gain} < 6\text{dBi}$</p> <p>ISED: <input checked="" type="checkbox"/> Lesser of: lesser of 250mW or $11\text{dBm}+10\log_{10}(B)$ <input checked="" type="checkbox"/> Max. EIRP 1Watt or $17+10\log_{10}(B)$ whichever power less <input type="checkbox"/> TPC required if MAX. EIRP > 500mW <input checked="" type="checkbox"/> U-NII3: 5.725-5.850 GHz: FCC/ISED: <input checked="" type="checkbox"/> max. conducted power: 1 Watt (30dBm) <input checked="" type="checkbox"/> Antenna gain less 6dBi <input type="checkbox"/> Antenna gain more 6dBi (-> reduction necessary)</p>

5.2.3. EUT settings:

The EUT was instructed to send with maximum power (if adjustable) according applicants instructions.
Different modulation characteristics have been checked, e.g. data rates which EUT can operate.
Three operating frequencies within each operating band have been selected.

5.2.4. Test condition and measurement test set-up

Signal link to test system (if used):	<input type="checkbox"/> air link	<input type="checkbox"/> cable connection	<input checked="" type="checkbox"/> none
EUT-grounding	<input checked="" type="checkbox"/> none	<input type="checkbox"/> with power supply	<input type="checkbox"/> additional connection
Equipment set up	<input checked="" type="checkbox"/> table top 1.5m height		<input type="checkbox"/> floor standing
Climatic conditions	Temperature: (22±3°C)		
General measurement procedures	Rel. humidity: (40±20)% Please see chapter "Test system set-up for conducted RF-measurement at antenna Port" (W1 Set-up)		

5.2.5. Results

APPLICANT'S DECLARED ANTENNA CHARACTERISTICS:

- Directional Gain < 6 dBi (measured: difference between measured conducted and radiated eirp. power)
 Directional Gain > 6 dBi (measured / applicant's declaration) -> conducted power reduction necessary

The PCB Antenna has the following max. gain:

UNII-1: 3.8 dBi
UNII-2A: 3.8 dBi
UNII-2C: 1.9 dBi
UNII-2C: 0.8 dBi

Different modulation types and data rates were tested in order to find the maximum peak conducted output power. **Enclosed are only the maximum values for each modulation format**, pls. compare separate document A1 for all results.

The EUT complies to the band edge requirement under provision that the power level is adjusted.

The 5GHz WLAN a mode power level for type approval is set to 10dBm.

The 5GHz WLAN n mode power level for type approval is set to 10dBm.

The 5GHz WLAN ac mode power level for type approval is set to 6dBm.

5.2.5.1. FCC AND ISED REQUIREMENTS

a mode HT 20:

Operational bands:	U-NII 1	U-NII 2A	U-NII 2C	U-NII 3
FCC&IC-Limits output power [dBm]	24.00	24.00	23.92	30.00
FCC-Limits EIRP [dBm]	30.00	30.00	30.00	36.00
IC-Limits EIRP [dBm]	13.96	13.96	29.15	36.00

Limit Check:	Limit Check:			
Highest conducted power value over channels and modulations:	8.20	8.02	8.07	8.08
Margin to Limit output power:	15.80	15.98	15.86	21.92
Declared antenna Gain max:	3.80	3.80	1.90	0.80
EIRP	12.00	11.82	9.97	8.88
FCC Margin to Limit EIRP:	18.00	18.18	20.04	27.12
IC Margin to Limit EIRP:	1.96	2.14	9.97	8.88
FCC Verdict:	pass	pass	pass	pass
IC Verdict:	pass	pass	pass	pass

n mode HT 20:

Operational bands:	U-NII 1	U-NII 2A	U-NII 2C	U-NII 3
FCC&IC-Limits output power [dBm]	24.00	24.00	24.00	30.00
FCC-Limits EIRP [dBm]	30.00	30.00	30.00	36.00
IC-Limits EIRP [dBm]	14.22	14.22	29.46	36.00
Limit Check:	Limit Check:			
Highest conducted power value over channels and modulations:	8.25	7.94	8.10	8.10
Margin to Limit output power:	15.75	16.06	15.90	21.90
Declared antenna Gain max:	3.80	3.80	1.90	0.80
EIRP	12.05	11.74	10.00	8.90
FCC Margin to Limit EIRP:	17.95	18.26	20.00	27.10
IC Margin to Limit EIRP:	2.17	2.48	10.00	8.90
FCC Verdict:	pass	pass	pass	pass
IC Verdict:	pass	pass	pass	pass

ac mode HT 20:

Operational bands:	U-NII 1	U-NII 2A	U-NII 2C	U-NII 3
FCC&IC-Limits output power [dBm]	24.00	24.00	24.00	30.00
FCC-Limits EIRP [dBm]	30.00	30.00	29.46	36.00
IC-Limits EIRP [dBm]	14.22	14.22	29.45	36.00
Limit Check:	Limit Check:			
Highest conducted power value over channels and modulations:	4.25	3.78	3.98	4.37
Margin to Limit output power:	19.75	20.23	20.02	25.63
Declared antenna Gain max:	3.80	3.80	1.90	0.80
EIRP	8.05	7.58	5.88	5.17
FCC Margin to Limit EIRP:	21.95	22.43	23.58	30.83
IC Margin to Limit EIRP:	6.17	6.65	23.57	30.83
FCC Verdict:	pass	pass	pass	pass
IC Verdict:	pass	pass	pass	pass

n mode HT 40:

Operational bands:	U-NII 1	U-NII-2A	U-NII 2C	U-NII-3
FCC&IC-Limits [dBm]	24.00	24.00	24.00	30.00
FCC-Limits [dBm]	36.00	30.00	30.00	36.00
IC-Limits [dBm]	14.77	14.77	30.00	36.00
Limit Check:	Limit Check:			
Highest conducted power value over channels and modulations:	8.51	8.15	7.81	8.23
Margin to Limit output power:	15.49	15.85	16.19	21.77
Declared antenna Gain max:	3.80	3.80	1.90	0.80
EIRP	12.31	11.95	9.71	9.03
FCCMargin to Limit EIRP	11.69	18.05	20.29	26.97
IC Margin to Limit EIRP	2.46	2.82	20.29	26.97
Verdict:	pass	pass	pass	pass
Verdict:	pass	pass	pass	pass

ac mode HT 40:

Operational bands:	U-NII 1	U-NII-2A	U-NII 2C	U-NII-3
FCC&IC-Limits [dBm]	24.00	24.00	24.00	30.00
FCC-Limits [dBm]	30.00	30.00	30.00	36.00
IC-Limits [dBm]	14.77	14.77	30.00	36.00
Limit Check:	Limit Check:			
Highest conducted power value over channels and modulations:	4.32	4.02	3.79	4.06
Margin to Limit output power:	19.68	19.98	20.21	25.94
Declared antenna Gain max:	3.80	3.80	1.90	0.80
EIRP	8.12	7.82	5.69	4.86
FCCMargin to Limit EIRP	15.88	22.18	24.31	31.14
IC Margin to Limit EIRP	6.65	6.95	24.31	31.14
FCC Verdict:	pass	pass	pass	pass
IC Verdict:	pass	pass	pass	pass

ac mode HT 80:

Operational bands:	U-NII 1	U-NII 2A	U-NII 2C	U-NII 3
FCC&IC-Limits output power [dBm]	24.00	24.00	24.00	30.00
FCC-Limits EIRP [dBm]	30.00	30.00	30.00	36.00
IC-Limits EIRP [dBm]	14.77	14.77	30.00	36.00
Limit Check:	Limit Check:			
Highest conducted power value over channels and modulations in dBm:	3.94	3.57	3.58	3.59
Margin to Limit output power:	20.06	20.43	20.42	26.41
Declared antenna Gain max:	3.80	3.80	1.90	0.80
EIRP	7.74	7.37	5.48	4.39
Margin to Limit EIRP:	22.26	22.63	24.52	31.61
Margin to Limit EIRP:	7.03	7.40	24.52	31.61
FCC Verdict:	pass	pass	pass	pass
IC Verdict:	pass	pass	pass	pass

Remark: See diagrams in separate Annex 1**RSS 247 section 6.2.3
Frequency band 5600-5650MHz****Until further notice, devices subject to this section shall not be capable of transmitting in the band 5600-5650 MHz.** This restriction is for the protection of Environment Canada's weather radars operating in this band.**Verdict: Pass**

5.3. RF Parameter - 6dB, 26 dB and 99% occupied Bandwidth

5.3.1. Test location and equipment (for reference numbers please see chapter 'List of test equipment')

test location	<input checked="" type="checkbox"/> CETECOM Essen (Chapter. 2.2.1)	<input type="checkbox"/> 443 System CTC-FAR-EMI-	<input type="checkbox"/> Please see Chapter. 2.2.3
test site	<input type="checkbox"/> 441 EMI SAR	<input type="checkbox"/> 487 SAR NSA	<input type="checkbox"/> 347 Radio.lab.
receiver	<input type="checkbox"/> 377 ESCS30	<input type="checkbox"/> 001 ESS	<input checked="" type="checkbox"/> TS 8997
spectr. analys.	<input checked="" type="checkbox"/> 584 FSU	<input type="checkbox"/> 120 FSEM	<input type="checkbox"/> 489 ESU 40
antenna	<input type="checkbox"/> 574 BTA-L	<input type="checkbox"/> 133 EMCO3115	<input type="checkbox"/> 302 BBHA9170
signaling	<input type="checkbox"/> 392 MT8820A	<input type="checkbox"/> 436 CMU	<input type="checkbox"/> 547 CMU
otherwise	<input type="checkbox"/> 266 NRV-Z31	<input type="checkbox"/> 600 NRVD	<input type="checkbox"/> 110 USB LWL
DC power	<input checked="" type="checkbox"/> 671 EA-3013S	<input type="checkbox"/> 463 HP3245A	<input type="checkbox"/> 482 Filter Matrix
			<input type="checkbox"/> 378 RadiSense
			<input type="checkbox"/> 693 TS8997
			<input type="checkbox"/> 494 AG6632A
			<input type="checkbox"/> 498 NGPE 40
otherwise	<input type="checkbox"/> 331 HC 4055	<input type="checkbox"/> 248 6 dB Attenuator	<input type="checkbox"/> 529 Power divider
			<input type="checkbox"/> - cable OTA20
	<input type="checkbox"/> 530 10dB Attenuator		<input type="checkbox"/> K 4 Cable kit
Supply voltage	<input checked="" type="checkbox"/> 13.5V DC		<input type="checkbox"/> 060 110 V 60 Hz via PAS 5000

5.3.2. Test condition and measurement test set-up

link to test system (if used):	<input type="checkbox"/> air link	<input checked="" type="checkbox"/> cable connection	<input type="checkbox"/>
Climatic conditions	Temperature: (22±3°C)	Rel. humidity: (40±20)%	

5.3.3. References of occupied and emission bandwidth

FCC	<input checked="" type="checkbox"/> FCC 2.202 for information <input checked="" type="checkbox"/> Part 15 Subpart C, §15.407(e)
ISED	RSS-Gen, Issue 5, chapter 4.6.1 RSS-247, Issue 2
ANSI	<input checked="" type="checkbox"/> C63.10-2013
KDB Guidance no.	<input checked="" type="checkbox"/> 789033 D02 General UNII test procedures v01r04, Subchapter C
Limits	<input checked="" type="checkbox"/> necessary for maximum power limits depending of B <input checked="" type="checkbox"/> FCC/ISED: decision if DFS necessary for decision if due 26dBc emissions falling in 5250-5350MHz band <input checked="" type="checkbox"/> FCC §15.407(e)/ISED: minimum 500kHz for band 5725-5850MHz

5.3.4. EUT Settings:

The EUT was instructed to send with different power/ data rates (if adjustable) according applicants instructions. Different modulation characteristics have been checked, e.g. data rates which EUT can operate.

5.3.5. Measurement method:

The measurement was performed with the RBW set to approximately 1% of the emission bandwidth. The span was set to cover the complete carrier. Three carrier frequencies were used for showing the compliance with this requirement. A DELTA Marker method was set to measure the bandwidth compared to the highest In-Band power. The operating modes have been varied for **26 dB bandwidth** (e.g. data rate, modulation scheme, etc.).

Also the **99% occupied bandwidth** was measured. Two markers are placed on frequency points such that left to lower f-marker and right to higher f-marker only 1% of the TX-power is contained. Between the markers, 99% of the power is laying. The RBW value is readjusted and the measurement repeated until the RBW/EBW ratio is around 1%. The operating modes have been taken the maximum data rates, which had been found out at the output power conducted measurements.

5.3.6. Spectrum-Analyzer Settings: (check if accord. KDB)

Span	Set as to fully display the emissions and at least 26 dB below the PEAK level
Resolution Bandwidth (RBW)	Set to approx. 1% ...3% of the emission width
Video Bandwidth (VBW)	3 times the resolution bandwidth
Sweep time	Coupled and low enough to have no gaps within power envelope
Detector	PK (26 dB BW)/Sample (99% OBW)
Sweep mode	Repetitive Mode, MAX-HOLD

5.3.7. Results:

Set-up no.:	1					
Op. Mode:	1 (WLAN 5 GHz a Mode B.W. 20 MHz Power Settings: 10)					
	Channel No.	Nominal bandwidth	6 dB Bandwidth [MHz]	26 dB Bandwidth [MHz]	99% Occupied Bandwidth [MHz]	Diagram no.
UN-II-1	36	20	16.5	19.60	16.60	Remark 1
UN-II-2A	64		16.6	19.80	16.60	Remark 1
UN-II-2C	100		16.5	19.60	16.40	Remark 1
UN-NII-3	149		16.5	19.60	16.60	Remark 1

Remark 1: See diagrams in separate annex TR18-1-0048601T01a-A1

Set-up no.:	1					
Op. Mode:	1 (WLAN 5 GHz n Mode B.W. 20 MHz Power Settings: 10)					
	Channel No.	Nominal bandwidth	6 dB Bandwidth [MHz]	26 dB Bandwidth [MHz]	99% Occupied Bandwidth [MHz]	Diagram no.
UN-II-1	40	20	17.9	20.00	17.60	Remark 1
UN-II-2A	52		17.9	20.20	17.60	Remark 1
UN-II-2C	116		17.9	20.00	17.60	Remark 1
UN-NII-3	157		17.8	20.20	17.60	Remark 1

Remark 1: See diagrams in separate annex TR18-1-0048601T01a-A1

Set-up no.:	2					
Op. Mode:	1 (WLAN 5 GHz ac Mode B.W. 20 MHz Power Settings: 6)					
	Channel No.	Nominal bandwidth	6 dB Bandwidth [MHz]	26 dB Bandwidth [MHz]	99% Occupied Bandwidth [MHz]	Diagram no.
UN-II-1	48	20	17.8	20.20	17.60	Remark 1
UN-II-2A	56		17.5	20.20	17.60	Remark 1
UN-II-2C	140		17.7	20.00	17.60	Remark 1
UN-NII-3	149		17.7	20.20	17.60	Remark 1

Remark 1: See diagrams in separate annex TR18-1-0048601T01a-A1

Set-up no.:	2					
Op. Mode:	1 (WLAN 5 GHz n Mode B.W. 40 MHz Power Settings: 10)					
	Channel No.	Nominal bandwidth	6 dB Bandwidth [MHz]	26 dB Bandwidth [MHz]	99% Occupied Bandwidth [MHz]	Diagram no.
UN-II-1	38	40	35.9	40.45	36.25	Remark 1
UN-II-2A	54		35.9	40.45	36.25	Remark 1
UN-II-2C	102		35.6	39.55	36.25	Remark 1
UN-NII-3	151		36.3	40.45	36.25	Remark 1

Remark 1: See diagrams in separate annex TR18-1-0048601T01a-A1

Set-up no.:	2					
Op. Mode:	1 (WLAN 5 GHz ac Mode B.W. 40 MHz Power Settings: 6)					
	Channel No.	Nominal bandwidth	6 dB Bandwidth [MHz]	26 dB Bandwidth [MHz]	99% Occupied Bandwidth [MHz]	Diagram no.
UN-II-1	46	40	35.9	39.85	36.25	Remark 1
UN-II-2A	62		36	40.15	36.25	Remark 1
UN-II-2C	102		35.5	40.15	36.25	Remark 1
UN-NII-3	159		36	40.15	36.25	Remark 1

Remark 1: See diagrams in separate annex TR18-1-0048601T01a-A1

Set-up no.:	2					
Op. Mode:	1 (WLAN 5 GHz ac Mode B.W. 80 MHz Power Settings: 6)					
	Channel No.	Nominal bandwidth	6 dB Bandwidth [MHz]	26 dB Bandwidth [MHz]	99% Occupied Bandwidth [MHz]	Diagram no.
UN-II-1	42	80	75.6	84.00	76.00	Remark 1
UN-II-2A	58		75.4	83.00	76.00	Remark 1
UN-II-2C	106		76.5	84.00	76.50	Remark 1
UN-NII-3	155		76.5	83.00	76.00	Remark 1

Remark 1: See diagrams in separate annex TR18-1-0048601T01a-A1

5.3.8. Verdict (assignment): pass

5.4. RF Parameter – Peak Power Spectral Density (PPSD)

5.4.1. Test location and equipment (for reference numbers please see chapter 'List of test equipment')

test location	<input checked="" type="checkbox"/> CETECOM Essen (Chapter. 2.2.1)	<input type="checkbox"/> 443 System CTC-FAR-EMI-	<input type="checkbox"/> Please see Chapter. 2.2.3
test site	<input type="checkbox"/> 441 EMI SAR	<input type="checkbox"/> 487 SAR NSA	<input type="checkbox"/> 347 Radio.lab.
receiver	<input type="checkbox"/> 377 ESCS30	<input type="checkbox"/> 001 ESS	<input checked="" type="checkbox"/> TS 8997
spectr. analys.	<input checked="" type="checkbox"/> 584 FSU	<input type="checkbox"/> 120 FSEM	<input type="checkbox"/> 489 ESU 40
antenna	<input type="checkbox"/> 574 BTA-L	<input type="checkbox"/> 133 EMCO3115	<input type="checkbox"/> 302 BBHA9170
signaling	<input type="checkbox"/> 392 MT8820A	<input type="checkbox"/> 436 CMU	<input type="checkbox"/> 547 CMU
otherwise	<input type="checkbox"/> 266 NRV-Z31	<input type="checkbox"/> 600 NRVD	<input type="checkbox"/> 110 USB LWL
DC power	<input checked="" type="checkbox"/> 671 EA-3013S	<input type="checkbox"/> 463 HP3245A	<input type="checkbox"/> 459 EA 2032-50
otherwise	<input type="checkbox"/> 331 HC 4055	<input type="checkbox"/> 248 6 dB Attenuator	<input type="checkbox"/> 529 Power divider
	<input type="checkbox"/> 530 10dB Attenuator		<input type="checkbox"/> - cable OTA20
Supply voltage	<input checked="" type="checkbox"/> 13.5V DC	<input type="checkbox"/> 060 110 V 60 Hz via PAS 5000	

5.4.2. References

FCC	<input checked="" type="checkbox"/> Part 15 Subpart C, §15.407(a)(1)(2)(3)(4)
ISED	<input checked="" type="checkbox"/> RSS-247, Issue 2: chapter 6.2 and subchapters
ANSI	<input checked="" type="checkbox"/> C63.10-2013
KDB Guidances no.	<input checked="" type="checkbox"/> 789033 D02 General UNII test procedures v01r04: Subchapter F <input checked="" type="checkbox"/> 922611 D01 Multiple transmitter output v02r01
Limits [dBm/MHz]	<input checked="" type="checkbox"/> U-NII 1: 5.15-5.25 GHz: FCC Outdoor access point: 17dBm/MHz FCC Indoor Access Point: 17dBm/MHz FCC Mobile & Portable client: 11dBm/MHz ISED: <input checked="" type="checkbox"/> vehicle equipment by OEM <input checked="" type="checkbox"/> other device: 10 dBm/MHz <input checked="" type="checkbox"/> U-NII2: 5.25-5.35 GHz: FCC/ ISED: 11dBm <input checked="" type="checkbox"/> U-NII2+extension: 5.47-5.725 GHz: FCC/ ISED: 11dBm/MHz
Limits [dBm/500kHz]	<input checked="" type="checkbox"/> U-NII3: 5.725-5.85 GHz: FCC/ ISED: 30dBm/500kHz

Remark: --

5.4.3. EUT settings

- different channels have been measured for each transmitting sub-band
- The EUT was instructed to send with maximum power (if adjustable) according applicants instructions
- MIMO applicable measurement techniques (KDB 992611)
- no MIMO applicable

5.4.4. Measurement Method:

SA-1: The procedures were followed for measuring the average power spectrum as described under chapter "maximum conducted output power": steps (i) to (viii). The measurements have been performed for each output RF-port if applicable. A screenshot and data bins transfer for further calculations were recorded. If the device contains more than one RF-output port, MIMO calculation procedures have been followed according KDB662911, Chapter E.2 a) "Measure and sum spectra across the outputs". Resulting maximum PSD is reported for the MIMO condition.

The measured value is corrected due to external measuring set-up path losses and the resulting value is compared with the standard requirement. If the limit is E.I.R.P limit the antenna gain is added, eventually the array gain for MIMO systems.

5.4.4.1. Results:

Set-up no.:	2				
Op. Mode:	1 (20MHz nominal bandwidth)				
Band	Channel No.	Nominal bandwidth	Power spectral density [dBm/MHz]		Diagram no.
			a-Mode	n20-Mode	
UN-II-1	36	20	-2.44	--	--
	40		--	-1.72	--
	48		--	--	-8.91
UN-II-2A	52	20	--	-3.59	--
	56		--	--	-7.13
	64		-3.39	--	--
UN-II-2C	100	20	-3.22	--	--
	116		--	-4.272	--
	140		--	--	-8.93
UN-NII-3	149	20	-7.22	--	--
	157		--	-6.1	--
	165		--	--	-11.65

Remark 1: Only results for worst case modes are displayed, for additional information please refer to diagrams in separate annex TR18-1-0048601T01a-A1

Set-up no.:	2				
Op. Mode:	1 (40MHz nominal bandwidth)				
Band	Channel No.	Nominal bandwidth	Power spectral density [dBm/MHz]		
			n40-Mode	ac40-Mode	
UN-II-1	38	40	-4.595	--	Remark 1
	46		--	-10.284	Remark 1
UN-II-2A	54	40	-4.904	--	Remark 1
	62		--	-10.29	Remark 1
UN-II-2C	102		-5.067	-11.164	Remark 1
UN-NII-3	151		-8.778	--	Remark 1
	159		--	-13.82	Remark 1

Remark 1: Only results for worst case modes are displayed, for additional information please refer to diagrams in separate annex TR18-1-0048601T01a-A1

Set-up no.:	2			
Op. Mode:	1 (80MHz nominal bandwidth)			
Band	Channel No.	Nominal bandwidth	Power spectral density [dBm/MHz]	
			AC80-Mode	
UN-II-1	42	80	-13.129	Remark 1
	58		-12.606	Remark 1
UN-II-2C	106		-14.273	Remark 1
UN-II-3	155		-16.267	Remark 1

Remark 1: Only results for worst case modes are displayed, for additional information please refer to diagrams in separate annex TR18-1-0048601T01a-A1

5.4.5. Verdict: Passed

5.5. RF-Parameter – Frequency Stability

5.5.1. Test location and equipment (for reference numbers please see chapter 'List of test equipment')

test location	<input checked="" type="checkbox"/> CETECOM Essen (Chapter. 2.2.1)	<input type="checkbox"/> 443 System CTC-FAR-EMI-	<input type="checkbox"/> Please see Chapter. 2.2.3
test site	<input type="checkbox"/> 441 EMI SAR	<input type="checkbox"/> 487 SAR NSA	<input type="checkbox"/> 337 OATS <input checked="" type="checkbox"/> 347 Radio.lab.
receiver	<input type="checkbox"/> 377 ESCS30	<input type="checkbox"/> 001 ESS	<input checked="" type="checkbox"/> 489 ESU 40 <input type="checkbox"/> 620 ESU 26
otherwise	<input type="checkbox"/> 600 NRVD	<input type="checkbox"/> 357 NRV-Z1	<input checked="" type="checkbox"/> 693 TS8997
spectr. analys.	<input type="checkbox"/> 683 FSU	<input type="checkbox"/> 120 FSEM	<input type="checkbox"/> 264 FSEK <input type="checkbox"/> 714 FSW 67
power supply	<input type="checkbox"/> 456 EA 3013A	<input type="checkbox"/> 457 EA 3013A	<input type="checkbox"/> 459 EA 2032-50 <input type="checkbox"/> 268 EA- 3050 <input type="checkbox"/> 494 AG6632A <input type="checkbox"/> 354 NGPE 40
otherwise	<input checked="" type="checkbox"/> 613 20 dB Attenuator	<input type="checkbox"/> 248 6 dB Attenuator	<input type="checkbox"/> 529 Power divider <input type="checkbox"/> - cable OTA20 <input type="checkbox"/> 530 10dB Atten <input type="checkbox"/> K5 Cable
Supply voltage	<input type="checkbox"/> 230 V 50 Hz via public mains	<input checked="" type="checkbox"/> 13.5 V DC	

5.5.2. Requirements:

ISED	<input checked="" type="checkbox"/> RSS-Gen, Issue5 , Chapter 6.11
Remark	Frequency stability is a measure of frequency drift due to temperature and supply voltage variations, with reference to the frequency measured at an appropriate reference temperature and the rated supply voltage.

5.5.3. EUT settings

For FHSS-systems hopping mode was switched-off so fixed two different channels could be measured.
The EUT was instructed to send with maximum power (if adjustable) according applicants instructions.

5.5.4. Measurement method

1. The First Measurement was done at Normal Temperature +20°C and $\pm 15\%$ of the supply voltage.
2. The Second Measurement was done at 3 different Temperatures -20°C (-4°F), +20°C (+68°F) and +50°C (+122°F), and the nominal supply Voltage
3. Also the 99% emission bandwidth was measured. Two markers are placed on frequency points such that left to lower f-marker and right to higher f-marker only 1% of the TX-power is contained. Between the markers, 99% of the power is laying.

5.5.5. Spectrum-Analyzer Settings

Span	Set as to fully display the emissions and approximate 20dB below the PEAK level
Resolution Bandwidth (RBW)	Set to approx. 1% ...3% of the emission width
Video Bandwidth (VBW)	3 times the resolution bandwidth
Sweep time	Coupled and low enough to have no gaps within power envelope
Detector	Sample (if bin width: Span/no. of frequency points SA < 0.5*RBW SA otherwise Peak detector)
Sweep mode	Repetitive Mode, Max hold

5.6. General Limit - Radiated field strength emissions below 30 MHz

5.6.1. Test location and equipment

test location	<input checked="" type="checkbox"/> CETECOM Essen (Chapter. 2.2.1)	<input type="checkbox"/> Please see Chapter. 2.2.2	<input type="checkbox"/> Please see Chapter. 2.2.3
test site	<input checked="" type="checkbox"/> 441 EMI SAR	<input type="checkbox"/> 487 SAR NSA	<input type="checkbox"/> 347 Radio.lab.
receiver	<input type="checkbox"/> 377 ESCS30	<input checked="" type="checkbox"/> 001 ESS	<input type="checkbox"/>
spectr. analys.	<input type="checkbox"/> 584 FSU	<input type="checkbox"/> 120 FSEM	<input type="checkbox"/> 264 FSEK
antenna	<input type="checkbox"/> 574 BTA-L	<input type="checkbox"/> 133 EMC03115	<input type="checkbox"/> 302 BBHA9170
signaling	<input type="checkbox"/> 392 MT8820A	<input type="checkbox"/> 371 CBT32	<input type="checkbox"/> 547 CMU
otherwise	<input type="checkbox"/> 400 FTC40x15E	<input type="checkbox"/> 401 FTC40x15E	<input type="checkbox"/> 110 USB LWL
DC power	<input type="checkbox"/> 671 EA-3013S	<input checked="" type="checkbox"/> 457 EA 3013A	<input type="checkbox"/> 459 EA 2032-50
Supply voltage	<input type="checkbox"/> 230 V 50 Hz via public mains	<input checked="" type="checkbox"/> 13.5 V DC	<input type="checkbox"/>

5.6.2. Requirements

FCC	Part 15, Subpart C, §15.205 & §15.209		
ANSI	C63.10-2013		
Frequency [MHz]	Field strength limit [μ V/m]	Distance [m]	Remarks
0.009 – 0.490	2400/f (kHz)	67.6 – 20Log(f) (kHz)	300
0.490 – 1.705	24000/f (kHz)	87.6 – 20Log(f) (kHz)	30
1.705 – 30	30	29.5	30

5.6.3. Test condition and test set-up

Signal link to test system (if used):	<input type="checkbox"/> air link	<input type="checkbox"/> cable connection	<input checked="" type="checkbox"/> none
EUT-grounding	<input checked="" type="checkbox"/> none	<input type="checkbox"/> with power supply	<input type="checkbox"/> additional connection
Equipment set up	<input checked="" type="checkbox"/> table top	<input type="checkbox"/> floor standing	
Climatic conditions	Temperature: (22±3°C)	Rel. humidity: (40±20)%	
EMI-Receiver or Analyzer Settings	Scan data	<input checked="" type="checkbox"/> 9 – 150 kHz RBW/VBW = 200 Hz Scan step = 80 Hz <input checked="" type="checkbox"/> 150 kHz – 30 MHz RBW/VBW = 9 kHz Scan step = 4 kHz <input type="checkbox"/> other:	
	Scan-Mode Detector Mode: Sweep-Time	<input checked="" type="checkbox"/> 6 dB EMI-Receiver Mode <input type="checkbox"/> 3dB Spectrum analyser Mode Peak (pre-measurement) and Quasi-PK/Average (final if applicable) Repetitive-Scan, max-hold Coupled – calibrated display if continuous signal otherwise adapted to EUT's individual transmission duty-cycle	
General measurement procedures	Please see chapter "Test system set-up radiated magnetic field measurements below 30 MHz"		

5.6.4. Radiated Field Strength Emissions – 9 kHz to 30 MHz Results

Radiated Field Strength Emissions – 9 kHz to 30 MHz								
Temperature :+21 °C		Technology: WLAN 5 GHz 802.11a/n			TX-Fixed Channel (Modulated)			
Diagr No. (Remark 1)	Test Settings			Set- up no.	Used detector		Verdict	
	Mode B.W. Data Rate	Frequency Band - Channel (Frequency)			PK	AV	QP	
2.01a	a Mode 20 MHz 18 Mbit U-NII-1-Ch 36 5180 MHz Standing			1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
2.01b	a Mode 20 MHz 18 Mbit U-NII-1-Ch 36 5180 MHz laying			1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
2.02a	a Mode 20 MHz 18 Mbit U-NII-2A-Ch 64 5320 MHz Standing			1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
2.02b	a Mode 20 MHz 18 Mbit U-NII-2A-Ch 64 5320 MHz Laying			1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
2.03a	a Mode 20 MHz 18 Mbit U-NII-2C-Ch 100 5500 MHz Standing			1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
2.03b	a Mode 20 MHz 18 Mbit U-NII-2C-Ch 100 5500 MHz Laying			1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
2.04a	a Mode 20 MHz 18 Mbit U-NII-3-Ch 149 5745 MHz Standing			1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
2.04b	a Mode 20 MHz 18 Mbit U-NII-3-Ch 149 5745 MHz Laying			1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass

Remark 1: See diagrams in separate Annex 1, only worst case modulation was tested

5.7. General Limit - Radiated field strength emissions, 30 MHz - 1 GHz

5.7.1. Test location and equipment

test location	<input checked="" type="checkbox"/> CETECOM Essen (Chapter. 2.2.1)	<input type="checkbox"/> Please see Chapter. 2.2.2	<input type="checkbox"/> Please see Chapter. 2.2.3
test site	<input checked="" type="checkbox"/> 441 EMI SAR	<input checked="" type="checkbox"/> 487 SAR NSA	
receiver	<input type="checkbox"/> 377 ESCS30	<input checked="" type="checkbox"/> 001 ESS	<input type="checkbox"/> 489 ESU 40
spectr. analys.	<input type="checkbox"/> 584 FSU	<input type="checkbox"/> 120 FSEM	<input type="checkbox"/> 264 FSEK
antenna	<input checked="" type="checkbox"/> 574 BTA-L	<input type="checkbox"/> 133 EMC03115	<input type="checkbox"/> 302 BBHA9170
signaling	<input type="checkbox"/> 392 MT8820A	<input type="checkbox"/> 371 CBT32	<input type="checkbox"/> 547 CMU
otherwise	<input type="checkbox"/> 400 FTC40x15E	<input type="checkbox"/> 401 FTC40x15E	<input type="checkbox"/> 110 USB LWL
DC power	<input type="checkbox"/> 671 EA-3013S	<input checked="" type="checkbox"/> 457 EA 3013A	<input type="checkbox"/> 459 EA 2032-50
Supply voltage	<input type="checkbox"/> 230 V 50 Hz via public mains	<input checked="" type="checkbox"/> 13.5V DC	

5.7.2. Requirements/Limits

FCC	<input type="checkbox"/> Part 15 Subpart B, §15.109, class B <input checked="" type="checkbox"/> Part 15 Subpart C, §15.209 @ frequencies defined in §15.205	
ANSI	<input type="checkbox"/> C63.4-2014 <input checked="" type="checkbox"/> C63.10-2013	
Limit	Frequency [MHz]	Radiated emissions limits, 3 meters
		<input type="checkbox"/> QUASI Peak [μ V/m] <input type="checkbox"/> QUASI-Peak [dB μ V/m]
	30 - 88	100 40.0
	88 - 216	150 43.5
	216 - 960	200 46.0
	above 960	500 54.0

5.7.3. Restricted bands of operation (FCC §15.205 / RSS-Gen, Issue 5)

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.20725-4.20775	37.5-38.25	1645.5-1646.5	9.3-9.5
6.215-6.218	73-74.6	1660-1710	10.6-12.7
6.26775-6.26825	74.8-75.2	1718.8-1722.2	13.25-13.4
6.31175-6.31225	108-121.94	2200-2300	14.47-14.5
8.291-8.294	123-138	2310-2390	15.35-16.2
8.362-8.366	149.9-150.05	2483.5-2500	17.7-21.4
8.37625-8.38675	156.52475-156.52525	2690-2900	22.01-23.12
8.41425-8.41475	156.7-156.9	3260-3267	23.6-24.0
12.29-12.293	162.0125-167.17	3332-3339	31.2-31.8
12.51975-12.52025	167.72-173.2	3345.8-3358	36.43-36.5
12.57675-12.57725	240-285	3600-4400	--
13.36-13.41	322-335.4	--	--

Remark: only spurious emissions are allowed within these frequency bands not exceeding the limits per §15.209

5.7.4. Test condition and measurement test set-up

Signal link to test system (if used):	<input type="checkbox"/> air link <input type="checkbox"/> cable connection <input checked="" type="checkbox"/> none
EUT-grounding	<input checked="" type="checkbox"/> none <input type="checkbox"/> with power supply <input type="checkbox"/> additional connection
Equipment set up	<input checked="" type="checkbox"/> table top 0.8m height <input type="checkbox"/> floor standing
Climatic conditions	Temperature: (22±3°C) Rel. humidity: (40±20)%
EMI-Receiver (Analyzer) Settings	Scan frequency range: <input checked="" type="checkbox"/> 30 – 1000 MHz <input type="checkbox"/> other: <input checked="" type="checkbox"/> 6 dB EMI-Receiver Mode <input type="checkbox"/> 3 dB spectrum analyser mode Scan-Mode Detector RBW/VBW Mode: Scan step Sweep-Time
General measurement procedures	Please see chapter "Test system set-up for electric field measurement in the range 30 MHz to 1 GHz"

5.7.5. Radiated Field Strength Emissions – 30 MHz to 1 GHz Results

Radiated Field Strength Emissions – 30 MHz to 1 GHz							
Temperature :+21 °C		Technology: WLAN 5 GHz 802.11a			TX-Fixed Channel (Modulated)		
Diagr No. (Remark 1)	Test Settings Mode B.W. Data Rate Frequency Band - Channel (Frequency)	Set- up no.	OP- mode no.	Used detector			Verdict
				PK	AV	QP	
3.01a	a Mode 20 MHz 18 Mbit U-NII-1-Ch 36 5180 MHz Standing	1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
3.01b	a Mode 20 MHz 18 Mbit U-NII-1-Ch 36 5180 MHz laying	1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
3.02a	a Mode 20 MHz 18 Mbit U-NII-2A-Ch 64 5320 MHz Standing	1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
3.02b	a Mode 20 MHz 18 Mbit U-NII-2A-Ch 64 5320 MHz Laying	1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
3.03a	a Mode 20 MHz 18 Mbit U-NII-2C-Ch 100 5500 MHz Standing	1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
3.03b	a Mode 20 MHz 18 Mbit U-NII-2C-Ch 100 5500 MHz Laying	1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
3.04a	a Mode 20 MHz 18 Mbit U-NII-3-Ch 149 5745 MHz Standing	1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
3.04b	a Mode 20 MHz 18 Mbit U-NII-3-Ch 149 5745 MHz Laying	1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
3.05a	n Mode 20 MHz MCS7 U-NII-1-Ch 40 5200 MHz Standing	1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
3.05b	n Mode 20 MHz MCS7 U-NII-1-Ch 40 5200 MHz laying	1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
3.06a	n Mode 20 MHz MCS7 U-NII-2A-Ch 52 5260 MHz Standing	1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
3.06b	n Mode 20 MHz MCS7 U-NII-2A-Ch 52 5260 MHz Laying	1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
3.07a	n Mode 20 MHz MCS7 U-NII-2C-Ch 116 5580 MHz Standing	1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
3.07b	n Mode 20 MHz MCS7 U-NII-2C-Ch 116 5580 MHz Laying	1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
3.08a	n Mode 20 MHz MCS7 U-NII-3-Ch 157 5785 MHz Standing	1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
3.08b	n Mode 20 MHz MCS7 U-NII-3-Ch 157 5785 MHz Laying	1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass

3.09a	ac Mode 20 MHz MCS1 U-NII-1-Ch 48 5240 MHz Standing	1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
3.09b	ac Mode 20 MHz MCS1 U-NII-1-Ch 48 5240 MHz laying	1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
3.10a	ac Mode 20 MHz MCS1 U-NII-2A-Ch 56 5280 MHz Standing	1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
3.10b	ac Mode 20 MHz MCS1 U-NII-2A-Ch 56 5280 MHz Laying	1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
3.11a	ac Mode 20 MHz MCS1 U-NII-2C-Ch 140 5700 MHz Standing	1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
3.11b	ac Mode 20 MHz MCS1 U-NII-2C-Ch 140 5700 MHz Laying	1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
3.12a	ac Mode 20 MHz MCS1 U-NII-3-Ch 165 5825 MHz Standing	1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
3.12b	ac Mode 20 MHz MCS1 U-NII-3-Ch 165 5825 MHz Laying	1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
3.13a	n Mode 40 MHz MCS3 U-NII-1-Ch 38 5190 MHz Standing	1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
3.13b	n Mode 40 MHz MCS3 U-NII-1-Ch 38 5190 MHz laying	1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
3.14a	n Mode 40 MHz MCS3 U-NII-2A-Ch 54 5270 MHz Standing	1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
3.14b	n Mode 40 MHz MCS3 U-NII-2A-Ch 54 5270 MHz Laying	1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
3.15a	n Mode 40 MHz MCS3 U-NII-2C-Ch 102 5510 MHz Standing	1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
3.15b	n Mode 40 MHz MCS3 U-NII-2C-Ch 102 5510 MHz Laying	1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
3.16a	n Mode 40 MHz MCS3 U-NII-3-Ch 151 5755 MHz Standing	1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
3.16b	n Mode 40 MHz MCS3 U-NII-3-Ch 151 5755 MHz Laying	1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
3.17a	ac Mode 40 MHz MCS4 U-NII-1-Ch 46 5230 MHz Standing	1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
3.17b	ac Mode 40 MHz MCS4 U-NII-1-Ch 46 5230 MHz laying	1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
3.18a	ac Mode 40 MHz MCS4 U-NII-2A-Ch 62 5310 MHz Standing	1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
3.18b	ac Mode 40 MHz MCS4 U-NII-2A-Ch 62 5310 MHz Laying	1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
3.19a	ac Mode 40 MHz MCS4 U-NII-2C-Ch 134 5670 MHz Standing	1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
3.19b	ac Mode 40 MHz MCS4 U-NII-2C-Ch 134 5670 MHz Laying	1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
3.20a	ac Mode 40 MHz MCS4 U-NII-3-Ch 159 5795 MHz Standing	1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
3.20b	ac Mode 40 MHz MCS4 U-NII-3-Ch 159 5795 MHz Laying	1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass

3.21a	ac Mode 80 MHz MCS1 U-NII-1-Ch 42 5210 MHz Standing	1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
3.21b	ac Mode 80 MHz MCS1 U-NII-1-Ch 42 5210 MHz laying	1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
3.22a	ac Mode 80 MHz MCS1 U-NII-2A-Ch 58 5290 MHz Standing	1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
3.22b	ac Mode 80 MHz MCS1 U-NII-2A-Ch 58 5290 MHz Laying	1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
3.23a	ac Mode 80 MHz MCS1 U-NII-2C-Ch 106 5530 MHz Standing	1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
3.23b	ac Mode 80 MHz MCS1 U-NII-2C-Ch 106 5530 MHz Laying	1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
3.24a	ac Mode 80 MHz MCS1 U-NII-3-Ch 155 5775 MHz Standing	1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass
3.24b	ac Mode 80 MHz MCS1 U-NII-3-Ch 155 5775 MHz Laying	1	1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pass

5.8. General Limit - Radiated emissions, above 1 GHz

5.8.1. Test location and equipment FAR

test site	<input type="checkbox"/> 441 EMI SAR	<input type="checkbox"/> 348 EMI cond.	<input checked="" type="checkbox"/> 443 EMI FAR	<input type="checkbox"/> 347 Radio.lab.	<input type="checkbox"/> 337 OATS	<input type="checkbox"/>
spectr. analys.	<input type="checkbox"/> 584 FSU	<input type="checkbox"/> 120 FSEM	<input type="checkbox"/> 264 FSEK	<input checked="" type="checkbox"/> 489 ESU 40	<input type="checkbox"/> C	<input type="checkbox"/>
antenna meas	<input type="checkbox"/> 574 BTA-L	<input type="checkbox"/> 289 CBL 6141	<input type="checkbox"/> 608 HL 562	<input checked="" type="checkbox"/> 549 HL025	<input checked="" type="checkbox"/> 302 BBHA9170	<input type="checkbox"/> 477 GPS
antenna meas	<input type="checkbox"/> 123 HUF-Z2	<input type="checkbox"/> 132 HUF-Z3	<input type="checkbox"/> 030 HFH-Z2	<input type="checkbox"/> 376 BBHA9120E		<input type="checkbox"/>
antenna subst	<input type="checkbox"/> 071 HUF-Z2	<input type="checkbox"/> 020 EMCO3115	<input type="checkbox"/> 063 LP 3146	<input type="checkbox"/> 303 BBHA9170	<input type="checkbox"/> C	<input type="checkbox"/>
multimeter	<input type="checkbox"/> 341 Fluke 112	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/> C	<input type="checkbox"/>
signaling	<input type="checkbox"/> 392 MT8820A	<input type="checkbox"/> 371 CBT32	<input type="checkbox"/> 547 CMU	<input type="checkbox"/> 594 CMW		
DCpower	<input type="checkbox"/> 611 E3632A	<input checked="" type="checkbox"/> 087 EA3013	<input type="checkbox"/> 354 NGPE 40	<input type="checkbox"/> 349 car battery	<input type="checkbox"/> 350 Car battery	<input type="checkbox"/>
Supply voltage	<input type="checkbox"/> 230 V 50 Hz via public mains		<input checked="" type="checkbox"/> 13.5 V DC			

5.8.2. Requirements/Limits

FCC	<input type="checkbox"/> Part 15 Subpart B, §15.109 class B <input checked="" type="checkbox"/> Part 15 Subpart C, §15.209 for frequencies defined in §15.205 <input checked="" type="checkbox"/> Part 15 Subpart C, §15.407(b)(1)(2)(3)(4)(5)(6)(7)(8)			
ANSI	<input type="checkbox"/> C63.4-2014 <input checked="" type="checkbox"/> C63.10-2013			
Frequency [MHz]	Limits			
	AV [μ V/m]	AV [dB μ V/m]	Peak [μ V/m]	Peak [dB μ V/m] or [dBm/MHz]
above 1 GHz for frequencies as defined in §15.205	500	54.0	5000	74.0 dB μ V/m
§15.407(b)(1)(2)(3)(4)	--	--	--	(b)(1): 5.15-5.25GHz: -27dBm eirp (b)(2): 5.25-5.35GHz: -27dBm eirp (b)(3): 5.47-5.725 GHz: -27dBm eirp (b)(4): 5725-5.85GHz: Spectrum mask

5.8.3. Test condition and measurement test set-up

Signal link to test system (if used):	<input type="checkbox"/> air link	<input type="checkbox"/> cable connection	<input checked="" type="checkbox"/> none
EUT-grounding	<input checked="" type="checkbox"/> none	<input type="checkbox"/> with power supply	<input type="checkbox"/> additional connection
Equipment set up	<input checked="" type="checkbox"/> table top 1.5m height		<input type="checkbox"/> floor standing
Climatic conditions	Temperature: (22±3°C) Rel. humidity: (40±20)%		
Spectrum-Analyzer settings	Scan frequency range: <input checked="" type="checkbox"/> 1 – 18 GHz <input type="checkbox"/> 18 – 25 GHz <input checked="" type="checkbox"/> 18 – 40 GHz <input type="checkbox"/> other: <input checked="" type="checkbox"/> 6 dB EMI-Receiver Mode <input type="checkbox"/> 3 dB Spectrum analyser Mode Scan-Mode Peak and Average Detector 1 MHz / 3 MHz RBW/VBW Repetitive-Scan, max-hold Mode: 400 kHz Scan step Coupled – calibrated display if CW signal otherwise adapted to EUT's individual duty-cycle Sweep-Time		
General measurement procedures	Please see chapter "Test system set-up for radiated electric field measurements above 1 GHz"		

5.8.4. Radiated Field Strength Emissions – 1 GHz to 40 GHz Results

Radiated Field Strength Emissions – 1 GHz to 7 GHz

Temperature :+21 °C		Technology: WLAN 5 GHz 802.11a/n			TX-Fixed Channel (Modulated)			
Diagr No. (Remark 1)	Test Settings Mode B.W. Data Rate Channel	Set- up no.	OP- mode no.	Used detector			Verdict	
				PK	AV	QP		
4.01a	a Mode 20 MHz 18 Mbit U-NII-1-Ch 36 5180 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass	
4.02a	a Mode 20 MHz 18 Mbit U-NII-2A-Ch 64 5320 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass	
4.03a	a Mode 20 MHz 18 Mbit U-NII-2C-Ch 100 5500 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass	
4.04a	a Mode 20 MHz 18 Mbit U-NII-3-Ch 149 5745 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass	
4.05a	n Mode 20 MHz MCS7 U-NII-1-Ch 40 5200 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass	
4.06a	n Mode 20 MHz MCS7 U-NII-2A-Ch 52 5260 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass	
4.07a	n Mode 20 MHz MCS7 U-NII-2C-Ch 116 5580 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass	
4.08a	n Mode 20 MHz MCS7 U-NII-3-Ch 157 5785 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass	
4.09a	ac Mode 20 MHz MCS1 U-NII-1-Ch 48 5240 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass	
4.10a	ac Mode 20 MHz MCS1 U-NII-2A-Ch 56 5280 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass	
4.11a	ac Mode 20 MHz MCS1 U-NII-2C-Ch 140 5700 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass	
4.12a	ac Mode 20 MHz MCS1 U-NII-3-Ch 165 5825 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass	
4.13a	n Mode 40 MHz MCS3 U-NII-1-Ch 38 5190 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass	
4.14a	n Mode 40 MHz MCS3 U-NII-2A-Ch 54 5270 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass	
4.15a	n Mode 40 MHz MCS3 U-NII-2C-Ch 102 5510 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass	
4.16a	n Mode 40 MHz MCS3 U-NII-3-Ch 151 5755 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass	
4.17a	ac Mode 40 MHz MCS4 U-NII-1-Ch 46 5230MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass	
4.18a	ac Mode 40 MHz MCS4 U-NII-2A-Ch 62 5310 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass	
4.19a	ac Mode 40 MHz MCS4 U-NII-2C-Ch 134 5670 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass	
4.20a	ac Mode 40 MHz MCS4 U-NII-3-Ch 159 5795 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass	
4.21a	ac Mode 80 MHz MCS1 U-NII-1-Ch 42 5210MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass	
4.22a	ac Mode 80 MHz MCS1 U-NII-2A-Ch 58 5290 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass	
4.23a	ac Mode 80 MHz MCS1 U-NII-2C-Ch 106 5530 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass	
4.24a	ac Mode 80 MHz MCS1 U-NII-3-Ch 155 5575 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass	

5.8.5. Radiated Field Strength Emissions – 7 GHz to 18 GHz Results

Radiated Field Strength Emissions – 7 GHz to 18 GHz							
Temperature :+21 °C		Technology: WLAN 5 GHz 802.11a/n			TX-Fixed Channel (Modulated)		
Diagram No. (Remark 1)	Test Settings Mode B.W. Data Rate Channel	Set-up no.	OP-mode no.	Used detector			Verdict
				PK	AV	QP	
4.01b	a Mode 20 MHz 18 Mbit U-NII-1-Ch 36 5180 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.02b	a Mode 20 MHz 18 Mbit U-NII-2A-Ch 64 5320 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.03b	a Mode 20 MHz 18 Mbit U-NII-2C-Ch 100 5500 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.04b	a Mode 20 MHz 18 Mbit U-NII-3-Ch 149 5745 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.05b	n Mode 20 MHz MCS7 U-NII-1-Ch 40 5200 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.06b	n Mode 20 MHz MCS7 U-NII-2A-Ch 52 5260 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.07b	n Mode 20 MHz MCS7 U-NII-2C-Ch 116 5580 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.08b	n Mode 20 MHz MCS7 U-NII-3-Ch 157 5785 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.09b	ac Mode 20 MHz MCS1 U-NII-1-Ch 48 5240 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.10b	ac Mode 20 MHz MCS1 U-NII-2A-Ch 56 5280 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.11b	ac Mode 20 MHz MCS1 U-NII-2C-Ch 140 5700 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.12b	ac Mode 20 MHz MCS1 U-NII-3-Ch 165 5825 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.13b	n Mode 40 MHz MCS3 U-NII-1-Ch 38 5190 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.14b	n Mode 40 MHz MCS3 U-NII-2A-Ch 54 5270 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.15b	n Mode 40 MHz MCS3 U-NII-2C-Ch 102 5510 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.16b	n Mode 40 MHz MCS3 U-NII-3-Ch 151 5755 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.17b	ac Mode 40 MHz MCS4 U-NII-1-Ch 46 5230MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.18b	ac Mode 40 MHz MCS4 U-NII-2A-Ch 62 5310 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.19b	ac Mode 40 MHz MCS4 U-NII-2C-Ch 134 5670 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.20b	ac Mode 40 MHz MCS4 U-NII-3-Ch 159 5795 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.21b	ac Mode 80 MHz MCS1 U-NII-1-Ch 42 5210MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.22b	ac Mode 80 MHz MCS1 U-NII-2A-Ch 58 5290 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.23b	ac Mode 80 MHz MCS1 U-NII-2C-Ch 106 5530 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.24b	ac Mode 80 MHz MCS1 U-NII-3-Ch 155 5575 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass

5.8.6. Radiated Field Strength Emissions – 18 GHz to 40 GHz Results

Radiated Field Strength Emissions – 18 GHz to 40 GHz

Temperature :+21 °C		Technology: WLAN 5 GHz 802.11a/n		TX-Fixed Channel (Modulated)			
Diagram No. (Remark 1)	Test Settings Mode B.W. Data Rate Channel	Set-up no.	OP-mode no.	Used detector			Verdict
				PK	AV	QP	
4.01c	a Mode 20 MHz 18 Mbit U-NII-1-Ch 36 5180 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.02c	a Mode 20 MHz 18 Mbit U-NII-2A-Ch 64 5320 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.03c	a Mode 20 MHz 18 Mbit U-NII-2C-Ch 100 5500 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.04c	a Mode 20 MHz 18 Mbit U-NII-3-Ch 149 5745 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.05c	n Mode 20 MHz MCS7 U-NII-1-Ch 40 5200 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.06c	n Mode 20 MHz MCS7 U-NII-2A-Ch 52 5260 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.07c	n Mode 20 MHz MCS7 U-NII-2C-Ch 116 5580 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.08c	n Mode 20 MHz MCS7 U-NII-3-Ch 157 5785 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.09c	ac Mode 20 MHz MCS1 U-NII-1-Ch 48 5240 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.10c	ac Mode 20 MHz MCS1 U-NII-2A-Ch 56 5280 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.11c	ac Mode 20 MHz MCS1 U-NII-2C-Ch 140 5700 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.12c	ac Mode 20 MHz MCS1 U-NII-3-Ch 165 5825 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.13c	n Mode 40 MHz MCS3 U-NII-1-Ch 38 5190 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.14c	n Mode 40 MHz MCS3 U-NII-2A-Ch 54 5270 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.15c	n Mode 40 MHz MCS3 U-NII-2C-Ch 102 5510 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.16c	n Mode 40 MHz MCS3 U-NII-3-Ch 151 5755 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.17c	ac Mode 40 MHz MCS4 U-NII-1-Ch 46 5230MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.18c	ac Mode 40 MHz MCS4 U-NII-2A-Ch 62 5310 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.19c	ac Mode 40 MHz MCS4 U-NII-2C-Ch 134 5670 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.20c	ac Mode 40 MHz MCS4 U-NII-3-Ch 159 5795 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.21c	ac Mode 80 MHz MCS1 U-NII-1-Ch 42 5210MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.22c	ac Mode 80 MHz MCS1 U-NII-2A-Ch 58 5290 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.23c	ac Mode 80 MHz MCS1 U-NII-2C-Ch 106 5530 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass
4.24c	ac Mode 80 MHz MCS1 U-NII-3-Ch 155 5575 MHz	1	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	Pass

5.9. RF-Parameter - Radiated Band-Edge compliance measurements

5.9.1. Test location and equipment FAR

test site	<input type="checkbox"/> 441 EMI SAR	<input type="checkbox"/> 348 EMI cond.	<input checked="" type="checkbox"/> 443 EMI FAR	<input type="checkbox"/> 347 Radio.lab.	<input type="checkbox"/> 337 OATS	<input type="checkbox"/>
spectr. analys.	<input type="checkbox"/> 584 FSU	<input type="checkbox"/> 120 FSEM	<input checked="" type="checkbox"/> 264 FSEK	<input checked="" type="checkbox"/> 714 FSW67	<input type="checkbox"/>	<input type="checkbox"/>
antenna meas	<input type="checkbox"/> 574 BTA-L	<input type="checkbox"/> 289 CBL 6141	<input type="checkbox"/> 608 HL 562	<input checked="" type="checkbox"/> 549 HL025	<input type="checkbox"/> 302 BBHA9170	<input type="checkbox"/> 477 GPS
antenna meas	<input type="checkbox"/> 123 HUF-Z2	<input type="checkbox"/> 132 HUF-Z3	<input type="checkbox"/> 030 HFH-Z2	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
antenna subst	<input type="checkbox"/> 071 HUF-Z2	<input type="checkbox"/> 020 EMCO3115	<input type="checkbox"/> 063 LP 3146	<input type="checkbox"/> 303 BBHA9170	<input type="checkbox"/>	<input type="checkbox"/>
multimeter	<input type="checkbox"/> 341 Fluke 112	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
signaling	<input type="checkbox"/> 392 MT8820A	<input type="checkbox"/> 371 CBT32	<input type="checkbox"/> 547 CMU	<input type="checkbox"/> 594 CMW		
DC power	<input type="checkbox"/> 611 E3632A	<input checked="" type="checkbox"/> 087 EA3013	<input type="checkbox"/> 354 NGPE 40	<input type="checkbox"/> 349 car battery	<input type="checkbox"/> 350 Car battery	<input type="checkbox"/>
Supply voltage	<input type="checkbox"/> 230 V 50 Hz via public mains		<input checked="" type="checkbox"/> 13.5 V DC			

5.9.2. Requirements/Limits

FCC	<input type="checkbox"/> Part 15 Subpart B, §15.109 class B <input checked="" type="checkbox"/> Part 15 Subpart C, §15.209 for frequencies defined in §15.205 <input type="checkbox"/> Part 15 Subpart C, §15.407(b)(1)(2)(3)(4)			
ISED	<input checked="" type="checkbox"/> RSS-Gen., Issue 5, Chapter 8.9, Table 5+7 (transmitter licence exempt) <input type="checkbox"/> RSS-Gen., Issue 5, Chapter 7.3, Table 3 (receiver) <input type="checkbox"/> ICES-003, Issue 6, Chapter 6.2.2, Table 7 (class B) <input type="checkbox"/> RSS-247, Issue 2, Chapter 5.5 <input checked="" type="checkbox"/> RSS-247, Issue 2, Chapter 6.2			
ANSI	<input type="checkbox"/> C63.4-2014 <input checked="" type="checkbox"/> C63.10-2013			
Frequency [MHz]	Limits			
above 1 GHz for frequencies as defined in §15.205 or RSS-Gen., Issue 9, §8.9 - Table 5	AV [μ V/m]	AV [$\text{dB}\mu\text{V}/\text{m}$]	Peak [$\mu\text{V}/\text{m}$]	Peak [$\text{dB}\mu\text{V}/\text{m}$] or [dBm/MHz]
	500	54.0	5000	74.0 $\text{dB}\mu\text{V}/\text{m}$
§15.407(b)(1)(2)(3)(4)	--	--	--	(b)(1): 5.15-5.25GHz: -27dBm eirp (b)(2): 5.25-5.35GHz: -27dBm eirp (b)(3): 5.47-5.725 GHz: -27dBm eirp (-17dBm/MHz eirp) (b)(4): 5725-5.85GHz: Spectrum mask
RSS-247, Issue 2	--	--	--	\$6.2.1.2 \$6.2.2.2 \$6.2.3.3 -27dBm/MHz (68.2 $\text{dB}\mu\text{V}/\text{m}$)
				Spectrum mask 27 to 15.6dBm 15.6dBm to 10dBm

5.9.3. Test condition and measurement test set-up

Signal link to test system (if used):	<input type="checkbox"/> air link	<input type="checkbox"/> cable connection	<input checked="" type="checkbox"/> none
EUT-grounding	<input checked="" type="checkbox"/> none	<input type="checkbox"/> with power supply	<input type="checkbox"/> additional connection
Equipment set up	<input checked="" type="checkbox"/> table top 1.5m height	<input type="checkbox"/> floor standing	
Climatic conditions	Temperature: (22±3°C)	Rel. humidity: (40±20)%	
Spectrum-Analyzer settings	Scan frequency range: Scan-Mode Detector RBW/VBW Mode: Scan step Sweep-Time	<input type="checkbox"/> 1 – 18 GHz <input type="checkbox"/> 18 – 25 GHz <input type="checkbox"/> 18 – 40 GHz <input checked="" type="checkbox"/> other: see diagrams <input type="checkbox"/> 6 dB EMI-Receiver Mode <input checked="" type="checkbox"/> 3 dB Spectrum analyzer Mode Peak and Average Left band-edge: 100kHz/300kHz Right band-edge: 1 MHz / 3 MHz Repetitive-Scan, max-hold 40kHz or 400 kHz Coupled – calibrated display if CW signal otherwise adapted to EUT's individual duty-cycle	
General measurement procedures	Please see chapter "Test system set-up for radiated electric field measurements above 1 GHz" for general measurements procedures in anechoic chamber.		

5.9.7. Results for restricted emissions in 5250-5350MHz band when TX operable in 5150-5250MHz band**Requirement Canada RSS-247, Issue 2, Chapter 6.2.1.2**

See annex 1 for results

Diagram No.	Mode	Channel No.	Occupied Bandwidth [MHz]	Channel Power [dBm]	Max. Power within band 5250 to 5350MHz (measured approx. 1% of OBW) [dBm]	Attenuation in regards to CH PWR [dBc]	Limit [dBc]	Verdict
35.01a								
35.01b	a	48	16,67	15,71	-27,36	43,07	26	pass
35.01c								
35.02a								
35.02b	n20	48	17,756	15,71	-27,97	43,68	26	pass
35.03c								
35.03a								
35.03b	ac20	48	17,726	13,21	-28,74	41,95	26	pass
35.03c								
35.04a								
35.04b	n40	46	36,075	15,53	-31,08	46,61	26	pass
35.04c								
35.05a								
35.05b	ac40	46	36,104	11,06	-35,63	46,69	26	pass
35.05c								
35.06a								
35.06b	ac80	42	75,898	10,72	-34,04	44,76	26	pass
35.06c								

Verdict: Pass

5.9.8. Results for restricted emissions in 5150-5250MHz band when TX operable in 5250-5350MHz band**Requirement Canada RSS-247, Issue 2, Chapter 6.2.2.2 b**

See annex 1 for results

Diagram No.	Mode	Channel No.	Peak EIRP [dBm]	Peak Value at band edge [dBm]	Max. power density at 5250MHz point on operable channel [dBm/MHz]	Limit [dBm/MHz]	Verdict
9.02a_step2	a	52	90,60	61,10	-29,50	10	pass
9.06a_step2	n20	52	89,84	61,78	-28,06	10	pass
9.10a_step2	ac20	52	84,65	58,50	-26,15	10	pass
9.14a_step2	n40	54	71,77	56,53	-15,24	10	pass
9.18a_step2	ac40	54	66,50	52,24	-14,26	10	pass
9.22a_step2	ac80	58	83,11	56,31	-26,80	10	pass

Verdict: Pass

5.10. Measurement uncertainties

The reported uncertainties are calculated based on the standard uncertainty multiplied with the appropriate coverage factor **k**, such that a confidence level of approximately 95% is achieved.

For uncertainty determination, each component used in the concrete measurement set-up was taken in account and it's contribution to the overall uncertainty according it's statistical distribution calculated.

Following table shows expectable uncertainties for each measurement type performed.

RF-Measurement	Reference	Frequency range	Calculated uncertainty based on a confidence level of 95%							Remarks
Conducted emissions (U CISPR)	CISPR 16-2-1	9 kHz - 150 kHz 150 kHz - 30 MHz	4.0 dB 3.6 dB							-
Radiated emissions Enclosure	CISPR 16-2-3	30 MHz - 1 GHz 1 GHz - 18 GHz	4.2 dB 5.1 dB							E-Field
Disturbance power	CISPR 16-2-2	30 MHz - 300 MHz	-							-
Power Output radiated	-	30 MHz - 4 GHz	3.17 dB							Substitution method
Power Output conducted	-	Set-up No.	Cel-C1	Cel-C2	BT1	W1	W2	--	--	
		9 kHz - 12.75 GHz	N/A	0.60	0.7	0.25	N/A	--	--	-
		12.75 - 26.5GHz	N/A	0.82	--	N/A	N/A	--	--	
Conducted emissions on RF-port	-	9 kHz - 2.8 GHz	0.70	N/A	0.70	N/A	0.69	--	--	N/A - not applicable
		2.8 GHz - 12.75GHz	1.48	N/A	1.51	N/A	1.43	--	--	
		12.75 GHz - 18GHz	1.81	N/A	1.83	N/A	1.77	--	--	
		18 GHz - 26.5GHz	1.83	N/A	1.85	N/A	1.79	--	--	
Occupied bandwidth	-	9 kHz - 4 GHz	0.1272 ppm (Delta Marker)							Frequency error
			1.0 dB							Power
Emission bandwidth	-	9 kHz - 4 GHz	0.1272 ppm (Delta Marker)							Frequency error
			See above: 0.70 dB							Power
Frequency stability	-	9 kHz - 20 GHz	0.0636 ppm							-
Radiated emissions Enclosure	-	150 kHz - 30 MHz 30 MHz - 1 GHz 1 GHz - 20 GHz	5.0 dB 4.2 dB 3.17 dB							Magnetic field E-field Substitution

Table: measurement uncertainties, valid for conducted/radiated measurements

6. Abbreviations used in this report

The abbreviations	
ANSI	American National Standards Institute
AV . AVG. CAV	Average detector
EIRP	Equivalent isotropically radiated power. determined within a separate measurement
EGPRS	Enhanced General Packet Radio Service
EUT	Equipment Under Test
FCC	Federal Communications Commission. USA
IC	Industry Canada
n.a.	not applicable
Op-Mode	Operating mode of the equipment
PK	Peak
RBW	resolution bandwidth
RF	Radio frequency
RSS	Radio Standards Specification. Documents from Industry Canada
Rx	Receiver
TCH	Traffic channel
Tx	Transmitter
QP	Quasi peak detector
VBW	Video bandwidth
ERP	Effective radiated power

7. Accreditation details of CETECOM's laboratories and test sites

Ref.-No.	Accreditation Certificate	Valid for laboratory area or test site	Accreditation Body
-	D-PL-12047-01-01	All laboratories and test sites of CETECOM GmbH. Essen	DAkkS. Deutsche Akkreditierungsstelle GmbH
337 487 558 348 348	(MRA US-EU 0003)	Radiated Measurements 30 MHz to 1 GHz. 3 m / 10 m (OATS) Radiated Measurements 30 MHz to 1 GHz. 3 m (SAR) Radiated Measurements above 1 GHz. 3 m (FAR) Mains Ports Conducted Interference Measurements Telecommunication Ports Conducted Interference Measurem.	FCC. Federal Communications Commission Laboratory Division. USA
337 487 550 558	3462D-1 3462D-2 3462D-2 3462D-3	Radiated Measurements 30 MHz to 1 GHz. 3 m / 10 m (OATS) Radiated Measurements 30 MHz to 1 GHz. 3 m (SAR) Radiated Measurements 1 GHz to 6 GHz. 3 m (SAR) Radiated Measurements above 1 GHz. 3 m (FAR)	ISED. Industry Canada Certification and Engineering Bureau
487 550 348 348	R-2666 G-301 C-2914 T-1967	Radiated Measurements 30 MHz to 1 GHz. 3 m (SAR) Radiated Measurements 1 GHz to 6 GHz. 3 m (SAR) Mains Ports Conducted Interference Measurements Telecommunication Ports Conducted Interference Measurem.	VCCI. Voluntary Control Council for Interference by Information Technology Equipment. Japan

OATS = Open Area Test Site. SAR = Semi Anechoic Room. FAR = Fully Anechoic Room

8.1.3. Legend

Note / remarks	Calibrated during system calibration:
1a	System CTC-SAR-EMS (Ref.-No. 442)
1b	System-CTC-EMS-Conducted (Ref.-No. 335)
1c	System CTC-FAR-EMI-RSE (Ref.-No . 443)
1d	System CTC-SAR-EMI (Ref.-No . 441)
1e	System CTC-OATS (EMI radiated) (Ref.-No. 337)
1 f	System CTC-CTIA-OTA (Ref.-No . 420)
1 g	System CTC-FAR-EMS (Ref.-No . 444)
2	Calibration or equipment check immediately before measurement
3	Regulatory maintained equipment for functional check or support purpose
4	Ancillary equipment without calibration e.g. mechanical equipment or monitoring equipment
5	Test System

Interval of calibration	12 M	12 month
	24 M	24 month
	36 M	36 month
	24/12 M	Calibration every 24 months. between this every 12 months internal validation
	36/12 M	Calibration every 36 months. between this every 12 months internal validation
	Pre-m	Check before starting the measurement
	-	Without calibration

9. Versions of test reports (change history)

Version	Applied changes	Date of release
--	Initial release	2018-12-28
C1	Output power updated, 6dB Bandwidth results added	2019-01-30
C2	Output Power limits updated	2019-02-04

END OF TEST REPORT