

## RF Exposure Evaluation declaration

Product Name : Wireless N 150 Home Router  
Model No. : W150NR  
FCC ID. : YC3W150NR

Applicant : KEEBOX, Inc.

Address : P.O. Box 2290, Gardena, CA 90247 U.S.A.

Date of Receipt : 2009/03/24  
Date of Declaration : 2010/06/10  
Report No. : 104234R-RF-US-Exp  
Report Version : V1.0

The declaration results relate only to the samples calculated.

The declaration shall not be reproduced except in full without the written approval of Quietek Corporation.

## 1. RF Exposure Evaluation

### 1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

#### LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula:  $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

$G$  = gain of antenna in linear scale

$\pi$  = 3.1416

$R$  = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance  $r$  where the MPE limit is reached.

### 1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

### 1.3. Test Result of RF Exposure Evaluation

Product	Wireless N 150 Home Router
Test Mode	Mode 1: Transmit
Test Condition	RF Exposure Evaluation

#### Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.8dBi or 1.51 in linear scale.

#### Output Power into Antenna & RF Exposure Evaluation Distance:

IEEE 802.11b			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
1	2412	76.2079	0.02395
6	2437	76.5597	0.02407
11	2462	78.3430	0.02463

IEEE 802.11g			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
1	2412	234.4229	0.07369
6	2437	235.5049	0.07403
11	2462	260.6154	0.08192

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm<sup>2</sup>.

Product	Wireless N 150 Home Router
Test Mode	Mode 1: Transmit
Test Condition	RF Exposure Evaluation

### Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.8dBi or 1.58 in linear scale. IEEE 802.11n (ANT A (20M))

### Output Power into Antenna & RF Exposure Evaluation Distance:

IEEE 802.11n (ANT A (20MHz))			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
1	2412	179.4734	0.02279
6	2437	180.3018	0.05667
11	2462	189.6706	0.05962

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm<sup>2</sup>.

Product	Wireless N 150 Home Router
Test Mode	Mode 1: Transmit
Test Condition	RF Exposure Evaluation

### Antenna Gain

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.8dBi or 1.58 in linear scale. IEEE 802.11n (ANT A (40M))

### Output Power into Antenna & RF Exposure Evaluation Distance:

IEEE 802.11n (ANT A (40M))			
WLAN Function			
Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
3	2422	186.6380	0.05867
6	2437	187.9317	0.05907
9	2452	196.7886	0.06186

The power density Pd (4th column) at a distance of 20 cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm<sup>2</sup>.