



SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, TaoYuan Hsien, Taiwan, R.O.C.
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / www.sporton.com.tw

FCC RADIO TEST REPORT

Applicant's company	KEEBOX , Inc.
Applicant Address	P.O. Box 2290 , Gardena , CA 90247 U.S.A.
FCC ID	YC3W150NRV2

Product Name	Wireless N 150 Home Router
Brand Name	KEEBOX
Model Name	W150NR
Test Rule	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	2400 ~ 2483.5MHz
Received Date	Jan. 14, 2011
Final Test Date	Jun. 28, 2012
Submission Type	Original Equipment



Statement

Test result included is only for the 802.11b/g part of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.10-2009** and **47 CFR FCC Part 15 Subpart C**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



Table of Contents

1. CERTIFICATE OF COMPLIANCE	1
2. SUMMARY OF THE TEST RESULT	2
3. GENERAL INFORMATION	3
3.1. Product Details	3
3.2. Accessories	3
3.3. Table for Filed Antenna	3
3.4. Table for Carrier Frequencies	3
3.5. Table for Test Modes	4
3.6. Table for Testing Locations.....	4
3.7. Table for Supporting Units	4
3.8. Table for Parameters of Test Software Setting	5
3.9. Test Configurations.....	6
4. TEST RESULT	8
4.1. AC Power Line Conducted Emissions Measurement	8
4.2. Maximum Conducted Output Power Measurement.....	12
4.3. Power Spectral Density Measurement.....	14
4.4. 6dB Spectrum Bandwidth Measurement	19
4.5. Radiated Emissions Measurement.....	24
4.6. Band Edge Emissions Measurement.....	36
4.7. Antenna Requirements	41
5. LIST OF MEASURING EQUIPMENTS	42
6. TEST LOCATION	44
7. TAF CERTIFICATE OF ACCREDITATION	45
APPENDIX A. PHOTOGRAPHS OF EUT	A1 ~ A8
APPENDIX B. TEST PHOTOS	B1 ~ B6
APPENDIX C. MAXIMUM PERMISSIBLE EXPOSURE	C1 ~C3



History of This Test Report

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR250920	Rev. 01	Initial issue of report	Jun. 28, 2012



1. CERTIFICATE OF COMPLIANCE

Product Name : Wireless N 150 Home Router
Brand Name : KEEBOX
Model Name : W150NR
Applicant : KEEBOX , Inc.
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.247

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Jan. 14, 2011 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.

A handwritten signature in blue ink that reads 'Jordan Hsiao'. The signature is written in a cursive style and is positioned above a horizontal line.

Jordan Hsiao

SPORTON INTERNATIONAL INC.

2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	15.55 dB
4.2	15.247(b)(3)	Maximum Conducted Output Power	Complies	3.42 dB
4.3	15.247(e)	Power Spectral Density	Complies	19.62 dB
4.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
4.5	15.247(d)	Radiated Emissions	Complies	0.39 dB
4.6	15.247(d)	Band Edge Emissions	Complies	0.31 dB
4.7	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.3dB	Confidence levels of 95%
Maximum Conducted Output Power	±0.8dB	Confidence levels of 95%
Power Spectral Density	±0.5dB	Confidence levels of 95%
6dB Spectrum Bandwidth	±8.5×10 ⁻⁸	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	±0.8dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	±1.9dB	Confidence levels of 95%
Radiated / Band Edge Emissions (1GHz~18GHz)	±1.9dB	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	±1.9dB	Confidence levels of 95%
Temperature	±0.7°C	Confidence levels of 95%
Humidity	±3.2%	Confidence levels of 95%
DC / AC Power Source	±1.4%	Confidence levels of 95%

3. GENERAL INFORMATION

3.1. Product Details

Items	Description
Power Type	From Power Adapter
Modulation	DSSS for IEEE 802.11b ; OFDM for IEEE 802.11g
Data Modulation	DSSS (BPSK / QPSK / CCK) ; OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	DSSS (1/ 2/ 5.5/11) ; OFDM (6/9/12/18/24/36/48/54)
Frequency Range	2400 ~ 2483.5MHz
Channel Number	11
Channel Band Width (99%)	11b: 15.04 MHz ; 11g: 16.52 MHz
Conducted Output Power	11b: 21.50 dBm ; 11g: 26.58 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

3.2. Accessories

Power	Brand	Model	Rating
Adapter	AMIGO	AMS47-0501000FU	Input: 100-240VAC, 50/60Hz, 0.2A Output: 5VDC, 1.0A

3.3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Antenna Gain	Cable Loss	Test Gain
A	Wha Yu Group	C381-510175(SSR-02481)	Dipole Antenna	NA	2.00	0.60	1.40

3.4. Table for Carrier Frequencies

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz	-	-

3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Line Conducted Emissions	Normal Link	Auto	-	-
Maximum Peak Conducted Output Power	11b/BPSK	1 Mbps	1/6/11	A
	11g/BPSK	6 Mbps	1/6/11	A
Power Spectral Density 6dB Spectrum Bandwidth	11b/BPSK	1 Mbps	1/6/11	A
	11g/BPSK	6 Mbps	1/6/11	A
Radiated Emissions 9kHz~1GHz	Normal Link	Auto	-	-
Radiated Emissions 1GHz~10 th Harmonic	11b/BPSK	1 Mbps	1/6/11	A
	11g/BPSK	6 Mbps	1/6/11	A
Band Edge Emissions	11b/BPSK	1 Mbps	1/11	A
	11g/BPSK	6 Mbps	1/11	A

3.6. Table for Testing Locations

Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.	VCCI Reg. No
03CH03-CB	SAC	Hsin Chu	187376	IC 4086	-
CO01-CB	Conduction	Hsin Chu	187376	IC 4086	-
TH01-CB	OVEN Room	Hsin Chu	-	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC); Fully Anechoic Chamber (FAC).

Please refer section 6 for Test Site Address.

3.7. Table for Supporting Units

Support Unit	Brand	Model	FCC ID
Notebook	DELL	D400	QDS-BRCM1005-D
Notebook	DELL	D400	QDS-BRCM1005-D
Notebook	DELL	D400	QDS-BRCM1005-D
HUB	Laneed	ETHERHUB-16	N/A
LOAD	N/A	N/A	N/A

3.8. Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Power Parameters of IEEE 802.11b/g


Test Software Version	QA 1.0.0.1		
Frequency	2412 MHz	2437 MHz	2462 MHz
IEEE 802.11b	13	15	15
IEEE 802.11g	17	1B	12

During the test, "QA 1.0.0.1" under WIN XP was executed the test program to control the EUT continuously transmit RF signal.


3.9. Test Configurations

3.9.1. Radiation Emissions Test Configuration


Test Configuration: 30MHz~1GHz



Test Configuration: Above 1GHz



3.9.2. AC Power Line Conduction Emissions Test Configuration



4. TEST RESULT

4.1. AC Power Line Conducted Emissions Measurement

4.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

4.1.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.4. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 KHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

4.1.4. Test Setup Layout



LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω . LISN can be placed on top of, or immediately beneath, reference ground plane.
 - (3.1) All other equipment powered from additional LISN(s).
 - (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
 - (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

4.1.5. Test Deviation


There is no deviation with the original standard.

4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.


4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	21°C	Humidity	56.4%
Test Engineer	Sin Chang	Phase	Line
Configuration	Normal Link		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.18739	46.19	-17.97	64.15	45.93	0.06	0.20	QP
2	0.18739	30.02	-24.14	54.15	29.76	0.06	0.20	AVERAGE
3	0.28178	37.72	-23.04	60.76	37.48	0.04	0.20	QP
4	0.28178	22.38	-28.38	50.76	22.14	0.04	0.20	AVERAGE
5	0.38113	37.73	-20.52	58.25	37.50	0.03	0.20	QP
6	0.38113	24.33	-23.92	48.25	24.10	0.03	0.20	AVERAGE
7	8.546	36.89	-23.11	60.00	36.28	0.31	0.30	QP
8	8.546	27.01	-22.99	50.00	26.40	0.31	0.30	AVERAGE
9	19.740	35.70	-24.30	60.00	34.39	0.81	0.50	QP
10	19.740	26.37	-23.63	50.00	25.06	0.81	0.50	AVERAGE
11	23.018	25.41	-24.59	50.00	23.89	1.02	0.50	AVERAGE
12	23.018	32.44	-27.56	60.00	30.92	1.02	0.50	QP

Temperature	21°C	Humidity	56.4%
Test Engineer	Sin Chang	Phase	Neutral
Configuration	Normal Link		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.18739	45.14	-19.02	64.15	44.85	0.09	0.20	QP
2	0.18739	32.48	-21.68	54.15	32.19	0.09	0.20	AVERAGE
3	0.28178	25.76	-25.01	50.76	25.48	0.08	0.20	AVERAGE
4	0.28178	37.44	-23.33	60.76	37.16	0.08	0.20	QP
5	0.47865	30.81	-15.55	46.36	30.61	0.07	0.13	AVERAGE
6	0.47865	40.14	-16.22	56.36	39.94	0.07	0.13	QP
7	8.412	41.77	-18.23	60.00	41.11	0.34	0.32	QP
8	8.412	33.13	-16.87	50.00	32.47	0.34	0.32	AVERAGE
9	13.551	27.74	-22.26	50.00	26.81	0.53	0.40	AVERAGE
10	13.551	37.20	-22.80	60.00	36.27	0.53	0.40	QP
11	18.721	30.16	-19.84	50.00	28.91	0.75	0.50	AVERAGE
12	18.721	40.12	-19.88	60.00	38.87	0.75	0.50	QP

Note:

Level = Read Level + LISN Factor + Cable Loss.

4.2. Maximum Conducted Output Power Measurement

4.2.1. Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the peak power meter

Power Meter Parameter	Setting
Bandwidth	50MHz bandwidth is greater than the EUT emission bandwidth
Detector	Peak

4.2.3. Test Procedures

Spectrum Parameter	Setting
RF Output Power Method	<input checked="" type="checkbox"/> ANSI C63.10 clause 6.10.2.1 (a) power meter method
RF Output Power Method	<input type="checkbox"/> ANSI C63.10 clause 6.10.2.1 (b) channel integration method
RF Output Power Method	<input type="checkbox"/> ANSI C63.10 clause 6.10.3.1 Method 1 - spectral trace averaging
RF Output Power Method	<input type="checkbox"/> ANSI C63.10 clause 6.10.3.2 Method 2 - zero-span mode with trace averaging

4.2.4. Test Setup Layout



4.2.5. Test Deviation

There is no deviation with the original standard.

4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.2.7. Test Result of Maximum Conducted Output Power

Temperature	18°C	Humidity	26%
Test Engineer	Satoshi Yang	Configurations	802.11b/g

Configuration IEEE 802.11b

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	20.40	30.00	Complies
6	2437 MHz	21.50	30.00	Complies
11	2462 MHz	21.24	30.00	Complies

Configuration IEEE 802.11g

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	25.85	30.00	Complies
6	2437 MHz	26.58	30.00	Complies
11	2462 MHz	24.47	30.00	Complies

4.3. Power Spectral Density Measurement

4.3.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of Spectrum Analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Set the analyzer span to 5-30% greater than the EBW.
RB	100 kHz
VB	300 kHz
Detector	RMS
Trace	Single Sweep
Sweep Time	$\geq 10 \times (\text{number of measurement points in sweep}) \times (\text{transmission symbol period})$.

4.3.3. Test Procedures

1. Use this procedure when the maximum conducted output power in the fundamental emission is used to demonstrate compliance. The EUT must be configured to transmit continuously at full power over the measurement duration.
2. Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span/RBW}$ (use of a greater number of measurement points than this minimum requirement is recommended).
3. Use the peak marker function to determine the maximum level in any 100 kHz band segment within the fundamental EBW.
4. Scale the observed power level to an equivalent level in 3 kHz by adjusting (reducing) the measured power by a bandwidth correction factor (BWCF) where: $\text{BWCF} = 10\log(3 \text{ kHz}/100 \text{ kHz} = -15.2 \text{ dB})$.
5. The resulting PSD level must be $\leq 8 \text{ dBm}$.

4.3.4. Test Setup Layout



4.3.5. Test Deviation

There is no deviation with the original standard.

4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.3.7. Test Result of Power Spectral Density

Temperature	18°C	Humidity	26%
Test Engineer	Satoshi Yang	Configurations	802.11b/g


Configuration IEEE 802.11b

Channel	Frequency	Power Density (dBm/100kHz)	BWCF factor (100KHz to 3KHz)	Power Density (dBm/3kHz)	Max. Limit (dBm/3kHz)	Result
1	2412 MHz	-0.55	-15.23	-15.78	8.00	Complies
6	2437 MHz	-0.44	-15.23	-15.67	8.00	Complies
11	2462 MHz	-0.35	-15.23	-15.58	8.00	Complies

Configuration IEEE 802.11g


Channel	Frequency	Power Density (dBm/100kHz)	BWCF factor (100KHz to 3KHz)	Power Density (dBm/3kHz)	Max. Limit (dBm/3kHz)	Result
1	2412 MHz	0.94	-15.23	-14.29	8.00	Complies
6	2437 MHz	3.61	-15.23	-11.62	8.00	Complies
11	2462 MHz	-2.14	-15.23	-17.37	8.00	Complies

Power Density Plot on Configuration IEEE 802.11b / 2412 MHz




Date: 28.JUN.2012 13:47:01

Power Density Plot on Configuration IEEE 802.11b / 2437 MHz




Date: 28.JUN.2012 13:48:24

Power Density Plot on Configuration IEEE 802.11b / 2462 MHz




Date: 28.JUN.2012 13:49:41

Power Density Plot on Configuration IEEE 802.11g / 2412 MHz




Date: 28.JUN.2012 13:54:48

Power Density Plot on Configuration IEEE 802.11g / 2437 MHz



Date: 28.JUN.2012 13:53:28

Power Density Plot on Configuration IEEE 802.11g / 2462 MHz



Date: 28.JUN.2012 13:51:42

4.4. 6dB Spectrum Bandwidth Measurement

4.4.1. Limit

For digital modulation systems, the minimum 6dB bandwidth shall be at least 500 kHz.

4.4.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RB	100 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.4.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
2. The resolution bandwidth of 100 kHz and the video bandwidth of 100 kHz were used.
3. Measured the spectrum width with power higher than 6dB below carrier.
4. Measuring multiple antennas, the connector is required to link with spectrum analyzer through a combiner.

4.4.4. Test Setup Layout



4.4.5. Test Deviation

There is no deviation with the original standard.

4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.4.7. Test Result of 6dB Spectrum Bandwidth

Temperature	18°C	Humidity	26%
Test Engineer	Satoshi Yang	Configurations	802.11b/g


Configuration IEEE 802.11b

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	12.12	15.04	500	Complies
6	2437 MHz	12.12	15.04	500	Complies
11	2462 MHz	12.12	15.04	500	Complies

Configuration IEEE 802.11g


Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	16.56	16.48	500	Complies
6	2437 MHz	16.56	16.52	500	Complies
11	2462 MHz	16.56	16.48	500	Complies

6 dB Bandwidth Plot on Configuration IEEE 802.11b / 2412 MHz




Date: 17.JAN.2011 07:59:12

6 dB Bandwidth Plot on Configuration IEEE 802.11b / 2437 MHz




Date: 17.JAN.2011 08:01:40

6 dB Bandwidth Plot on Configuration IEEE 802.11b / 2462 MHz




Date: 17.JAN.2011 08:03:52

6 dB Bandwidth Plot on Configuration IEEE 802.11g / 2412 MHz




Date: 17.JAN.2011 08:07:02

6 dB Bandwidth Plot on Configuration IEEE 802.11g / 2437 MHz



Date: 17.JAN.2011 08:09:36

6 dB Bandwidth Plot on Configuration IEEE 802.11g / 2462 MHz



Date: 17.JAN.2011 08:11:42

4.5. Radiated Emissions Measurement

4.5.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1MHz / 1MHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

4.5.3. Test Procedures


1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

4.5.4. Test Setup Layout

For radiated emissions below 30MHz



For radiated emissions above 30MHz



Above 10 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1.5m.

Distance extrapolation factor = $20 \log (\text{specific distance [3m]} / \text{test distance [1.5m]})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor [6 dB].

4.5.5. Test Deviation

There is no deviation with the original standard.

4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.5.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	24.5°C	Humidity	57%
Test Engineer	Sam Chen	Test Date	Mar. 25, 2011

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

4.5.8. Results of Radiated Emissions (30MHz~1GHz)


Temperature	24.5°C	Humidity	57%
Test Engineer	Sam Chen	Configurations	Normal Link

Horizontal



	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1	45.52	30.80	40.00	-9.20	48.72	0.70	27.80	9.18	0	100	Peak	HORIZONTAL
2	140.58	35.65	43.50	-7.85	50.33	1.40	27.39	11.31	0	100	Peak	HORIZONTAL
3	250.19	32.47	46.00	-13.53	44.90	1.90	27.00	12.67	0	100	Peak	HORIZONTAL
4	359.80	34.63	46.00	-11.37	44.61	2.22	27.32	15.12	0	100	Peak	HORIZONTAL
5	500.45	35.29	46.00	-10.71	43.11	2.70	28.10	17.58	0	100	Peak	HORIZONTAL
6	600.36	35.96	46.00	-10.04	42.34	2.90	28.10	18.82	0	100	Peak	HORIZONTAL
7 P	839.95	40.44	46.00	-5.56	43.95	3.38	27.52	20.63	0	100	Peak	HORIZONTAL
8	960.23	32.84	54.00	-21.16	34.92	3.62	27.16	21.46	0	100	Peak	HORIZONTAL

Vertical



	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 p	35.82	36.62	40.00	-3.38	49.11	0.54	27.80	14.77	0	400	Peak	VERTICAL
2 !	50.37	35.76	40.00	-4.24	55.38	0.70	27.80	7.48	0	400	Peak	VERTICAL
3	140.58	36.51	43.50	-6.99	51.19	1.40	27.39	11.31	0	400	Peak	VERTICAL
4	250.19	32.49	46.00	-13.51	44.92	1.90	27.00	12.67	0	400	Peak	VERTICAL
5	359.80	34.20	46.00	-11.80	44.18	2.22	27.32	15.12	0	400	Peak	VERTICAL
6	500.45	33.27	46.00	-12.73	41.09	2.70	28.10	17.58	0	400	Peak	VERTICAL
7	600.36	35.77	46.00	-10.23	42.15	2.90	28.10	18.82	0	400	Peak	VERTICAL
8	839.95	36.76	46.00	-9.24	40.27	3.38	27.52	20.63	0	400	Peak	VERTICAL

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.5.9. Results for Radiated Emissions (1GHz~10th Harmonic)

Temperature	24.5°C	Humidity	57%
Test Engineer	Satoshi Yang	Configurations	802.11b CH 1
Test Date	Jan. 15, 2011		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 a	4823.96	51.47	54.00	-2.53	49.02	4.26	35.20	33.39	303	153	Average	HORIZONTAL
2 p	4823.99	53.66	74.00	-20.34	51.21	4.26	35.20	33.39	303	153	Peak	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 p	4823.95	54.45	74.00	-19.55	52.00	4.26	35.20	33.39	280	117	Peak	VERTICAL
2 a	4823.96	52.30	54.00	-1.70	49.85	4.26	35.20	33.39	280	117	Average	VERTICAL

Temperature	24.5°C	Humidity	57%
Test Engineer	Satoshi Yang	Configurations	802.11b CH 6
Test Date	Jan. 15, 2011		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1	4873.94	55.05	74.00	-18.95	52.44	4.33	35.20	33.48	299	149	Peak	HORIZONTAL
2 a	4873.97	53.32	54.00	-0.68	50.71	4.33	35.20	33.48	299	149	Average	HORIZONTAL
3 p	7314.48	55.73	74.00	-18.27	49.28	5.37	35.43	36.51	258	124	Peak	HORIZONTAL
4 l	7314.72	51.06	54.00	-2.94	44.61	5.37	35.43	36.51	258	124	Average	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 p	4873.97	55.78	74.00	-18.22	53.17	4.33	35.20	33.48	279	117	Peak	VERTICAL
2 a	4873.97	52.85	54.00	-1.15	50.24	4.33	35.20	33.48	279	117	Average	VERTICAL
3	7313.64	55.49	74.00	-18.51	49.04	5.37	35.43	36.51	62	100	Peak	VERTICAL
4 l	7314.72	50.51	54.00	-3.49	44.06	5.37	35.43	36.51	62	100	Average	VERTICAL

Temperature	24.5°C	Humidity	57%
Test Engineer	Satoshi Yang	Configurations	802.11b CH 11
Test Date	Jan. 15, 2011		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 a	4923.97	52.85	54.00	-1.15	50.08	4.39	35.20	33.58	323	135	Average	HORIZONTAL
2	4924.00	54.81	74.00	-19.19	52.04	4.39	35.20	33.58	323	135	Peak	HORIZONTAL
3 l	7389.76	50.57	54.00	-3.43	44.01	5.41	35.46	36.61	112	123	Average	HORIZONTAL
4 p	7389.92	55.42	74.00	-18.58	48.86	5.41	35.46	36.61	112	123	Peak	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 l	4923.97	51.81	54.00	-2.19	49.04	4.39	35.20	33.58	277	115	Average	VERTICAL
2	4923.99	54.64	74.00	-19.36	51.87	4.39	35.20	33.58	277	115	Peak	VERTICAL
3 a	7389.72	52.93	54.00	-1.07	46.37	5.41	35.46	36.61	63	100	Average	VERTICAL
4 p	7389.96	57.63	74.00	-16.37	51.07	5.41	35.46	36.61	63	100	Peak	VERTICAL

Temperature	24.5°C	Humidity	57%
Test Engineer	Satoshi Yang	Configurations	802.11g CH 1
Test Date	Jan. 15, 2011		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 a	4823.92	42.10	54.00	-11.90	39.65	4.26	35.20	33.39	301	123	Average	HORIZONTAL
2 p	4825.92	55.91	74.00	-18.09	53.46	4.26	35.20	33.39	301	123	Peak	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 a	4823.92	42.85	54.00	-11.15	40.40	4.26	35.20	33.39	279	100	Average	VERTICAL
2 p	4825.88	57.06	74.00	-16.94	54.61	4.26	35.20	33.39	279	100	Peak	VERTICAL

Temperature	24.5°C	Humidity	57%
Test Engineer	Satoshi Yang	Configurations	802.11g CH 6
Test Date	Jan. 15, 2011		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1	4874.12	47.25	54.00	-6.75	44.64	4.33	35.20	33.48	303	150	Average	HORIZONTAL
2	4875.80	60.43	74.00	-13.57	57.82	4.33	35.20	33.48	303	150	Peak	HORIZONTAL
3 p	7312.72	67.53	74.00	-6.47	61.08	5.37	35.43	36.51	255	126	Peak	HORIZONTAL
4 a	7313.16	53.61	54.00	-0.39	47.16	5.37	35.43	36.51	255	126	Average	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1	4874.12	44.66	54.00	-9.34	42.05	4.33	35.20	33.48	280	100	Average	VERTICAL
2	4875.72	58.09	74.00	-15.91	55.48	4.33	35.20	33.48	280	100	Peak	VERTICAL
3 a	7312.60	53.44	54.00	-0.56	46.99	5.37	35.43	36.51	63	100	Average	VERTICAL
4 p	7312.72	67.59	74.00	-6.41	61.14	5.37	35.43	36.51	63	100	Peak	VERTICAL

Temperature	24.5°C	Humidity	57%
Test Engineer	Satoshi Yang	Configurations	802.11g CH 11
Test Date	Jan. 15, 2011		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1	4920.24	51.58	74.00	-22.42	48.85	4.39	35.20	33.54	295	134	Peak	HORIZONTAL
2	4924.12	37.59	54.00	-16.41	34.82	4.39	35.20	33.58	295	134	Average	HORIZONTAL
3 p	7381.50	59.28	74.00	-14.72	52.73	5.39	35.45	36.61	113	122	Peak	HORIZONTAL
4 a	7383.12	43.16	54.00	-10.84	36.61	5.39	35.45	36.61	255	126	Average	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1	4924.08	35.09	54.00	-18.91	32.32	4.39	35.20	33.58	321	100	Average	VERTICAL
2	4925.88	49.12	74.00	-24.88	46.35	4.39	35.20	33.58	321	100	Peak	VERTICAL
3 p	7379.32	62.22	74.00	-11.78	55.67	5.39	35.45	36.61	63	100	Peak	VERTICAL
4 a	7388.08	45.00	54.00	-9.00	38.44	5.41	35.46	36.61	63	100	Average	VERTICAL

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.6. Band Edge Emissions Measurement

4.6.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	100 KHz / 100 KHz for Peak

4.6.3. Test Procedures

1. The test procedure is the same as section 4.5.3, only the frequency range investigated is limited to 100MHz around bandedges.
2. In case the emission is fail due to the used RB/VB is too wide, marker-delta method of FCC Public Notice DA00-705 will be followed.

4.6.4. Test Setup Layout

This test setup layout is the same as that shown in section 4.5.4.

4.6.5. Test Deviation

There is no deviation with the original standard.

4.6.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.6.7. Test Result of Band Edge and Fundamental Emissions

Temperature	24.5°C	Humidity	57%
Test Engineer	Satoshi Yang	Configurations	802.11b CH 1, 6, 11
Test Date	Jan. 15, 2011		

Channel 1

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1	2390.00	54.62	74.00	-19.38	23.69	2.88	0.00	28.05	34	100	Peak	VERTICAL
2	2390.00	44.42	54.00	-9.58	13.49	2.88	0.00	28.05	34	100	Average	VERTICAL
3 a	2409.20	98.34	54.00			2.88	0.00	28.09	34	100	Average	VERTICAL
4 p	2409.40	101.87	74.00			2.88	0.00	28.09	34	100	Peak	VERTICAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1	2389.40	54.16	74.00	-19.84	23.25	2.86	0.00	28.05	34	100	Peak	VERTICAL
2	2390.00	43.69	54.00	-10.31	12.76	2.88	0.00	28.05	34	100	Average	VERTICAL
3 a	2435.20	102.07	54.00			2.89	0.00	28.18	34	100	Average	VERTICAL
4 p	2436.20	105.62	74.00			2.89	0.00	28.18	34	100	Peak	VERTICAL
5	2483.50	43.74	54.00	-10.26	12.55	2.93	0.00	28.26	34	100	Average	VERTICAL
6	2484.50	54.15	74.00	-19.85	22.96	2.93	0.00	28.26	34	100	Peak	VERTICAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 11

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 a	2463.80	101.09	54.00			2.91	0.00	28.22	2	100	Average	VERTICAL
2 p	2464.60	104.63	74.00			2.91	0.00	28.22	2	100	Peak	VERTICAL
3	2483.50	58.89	74.00	-15.11	27.70	2.93	0.00	28.26	2	100	Peak	VERTICAL
4 l	2483.50	50.96	54.00	-3.04	19.77	2.93	0.00	28.26	2	100	Average	VERTICAL

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	24.5°C	Humidity	57%
Test Engineer	Satoshi Yang	Configurations	802.11g CH 1, 6, 11
Test Date	Jan. 15, 2011		

Channel 1

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1	2390.00	69.64	74.00	-4.36	38.71	2.88	0.00	28.05	45	106	Peak	VERTICAL
2	2390.00	52.88	54.00	-1.12	21.95	2.88	0.00	28.05	45	106	Average	VERTICAL
3 p	2416.20	105.30	74.00			2.89	0.00	28.09	45	106	Peak	VERTICAL
4 a	2417.60	96.05	54.00			2.89	0.00	28.13	45	106	Average	VERTICAL

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 6

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1	2389.60	55.51	74.00	-18.49	24.60	2.86	0.00	28.05	34	100	Peak	VERTICAL
2	2390.00	44.42	54.00	-9.58	13.49	2.88	0.00	28.05	34	100	Average	VERTICAL
3 a	2435.80	98.94	54.00			2.89	0.00	28.18	34	100	Average	VERTICAL
4 p	2436.20	108.22	74.00			2.89	0.00	28.18	34	100	Peak	VERTICAL
5	2483.50	55.51	74.00	-18.49	24.32	2.93	0.00	28.26	34	100	Peak	VERTICAL
6	2483.50	44.95	54.00	-9.05	13.76	2.93	0.00	28.26	34	100	Average	VERTICAL

Item 3, 4 are the fundamental frequency at 2437 MHz.

Channel 11

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 p	2466.20	104.67	74.00			2.91	0.00	28.22	2	157	Peak	VERTICAL
2 a	2469.00	95.96	54.00			2.93	0.00	28.26	2	157	Average	VERTICAL
3	2483.50	69.36	74.00	-4.64	38.17	2.93	0.00	28.26	2	157	Peak	VERTICAL
4	2483.50	53.69	54.00	-0.31	22.50	2.93	0.00	28.26	2	157	Average	VERTICAL

Item 1, 2 are the fundamental frequency at 2462 MHz.


Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


For Emission not in Restricted Band

Low Band Edge Plot on Configuration IEEE 802.11b / 2412 MHz




Date: 17.JAN.2011 08:00:52

High Band Edge Plot on Configuration IEEE 802.11b / 2462 MHz




Date: 17.JAN.2011 08:05:33

Low Band Edge Plot on Configuration IEEE 802.11g / 2412 MHz



Date: 17.JAN.2011 08:08:42

High Band Edge Plot on Configuration IEEE 802.11g / 2462 MHz



Date: 17.JAN.2011 08:13:22

4.7. Antenna Requirements

4.7.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

4.7.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMI Test Receiver	R&S	ESCS 30	100377	9kHz ~ 2.75GHz	Sep. 01,2010	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150kHz ~ 100MHz	Oct. 28,2010	Conduction (CO01-CB)
V- LISN	Schwarzbeck	NSLK 8127	8127-478	9K ~ 30MHz	Nov. 16, 2010	Conduction (CO01-CB)
PULSE LIMITER	R&S	ESH3-Z2	100430	9K-30MHz	Jan. 04, 2011	Conduction (CO01-CB)
COND Cable	-	Cable	-	0.15MHz~30MHz	Dec. 04,2010	Conduction (CO01-CB)
BILOG ANTENNA	Schaffner	CBL6112D	22021	20MHz ~ 2GHz	Oct. 25, 2010	Radiation (03CH03-CB)
Horn Antenna	EMCO	3115	00075790	750MHz~18GHz	Nov. 09, 2010	Radiation (03CH03-CB)
Pre-Amplifier	Agilent	8449B	3008A02097	1GHz ~ 26.5GHz	Jul. 04, 2010	Radiation (03CH03-CB)
Pre-Amplifier	Agilent	8447D	2944A10940	0.1MHz ~ 1.3GHz	Nov. 09, 2010	Radiation (03CH03-CB)
Loop Antenna	R&S	HFH2-Z2	860004/001	9 kHz - 30 MHz	Sep. 09, 2010*	Radiation (03CH01-CB)
Spectrum analyzer	R&S	FSP	100304	9kHz ~ 40GHz	Nov. 15, 2010	Radiation (03CH03-CB)
Spectrum analyzer	R&S	FSP30	100023	9KHz~30GHz	Mar. 05, 2010	Conducted (TH01-CB)
Spectrum analyzer	R&S	FSP30	100023	9KHz~30GHz	Mar. 05, 2012	Conducted (TH01-CB)
Spectrum analyzer	R&S	FSV30	101026	9KHz~30GHz	Jul. 23,2010	Conducted (TH01-CB)
Temp. and Humidity Chamber	Ten Billion	TTH-D3SP	TBN-931011	-30~100 degree	May 21, 2010	Conducted (TH01-CB)
Temp. and Humidity Chamber	Ten Billion	TTH-D3SP	TBN-931011	-30~100 degree	May 21, 2012	Conducted (TH01-CB)
Thermo-Hygro Meter	N/A	HC 520	#1	15~70 degree	Nov. 02, 2010	Conducted (TH01-CB)
Signal Generator	R&S	SMR40	100302	10MHz-40GHz	Nov. 19, 2010	Conducted (TH01-CB)
RF Power Divider	HP	11636A	00306	2GHz ~ 18GHz	N/A	Conducted (TH01-CB)
RF Power Splitter	Anaren	44100	1839	2GHz ~ 18GHz	N/A	Conducted (TH01-CB)
RF Power Splitter	Anaren	42100	17930	2GHz ~ 18GHz	N/A	Conducted (TH01-CB)
Signal generator	R&S	SMU200A	102782	10MHz-40GHz	Mar. 09, 2010	Conducted (TH01-CB)
Signal generator	R&S	SMU200A	102782	10MHz-40GHz	Mar. 09, 2012	Conducted (TH01-CB)
Horn Antenna	COM-POWER	AH-118	071187	1GHz – 18GHz	Apr. 16, 2010	Conducted (TH01-CB)
Horn Antenna	COM-POWER	AH-118	071187	1GHz – 18GHz	Apr. 16, 2012	Conducted (TH01-CB)

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Horn Antenna	COM-POWER	AH-118	071042	1GHz – 18GHz	Oct. 14, 2010	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-7	-	1 GHz – 26.5 GHz	Nov. 17, 2010	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-8	-	1 GHz – 26.5 GHz	Nov. 17, 2010	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-9	-	1 GHz – 26.5 GHz	Nov. 17, 2010	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-10	-	1 GHz – 26.5 GHz	Nov. 17, 2010	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-11	-	1 GHz – 26.5 GHz	Nov. 17, 2010	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-12	-	1 GHz – 26.5 GHz	Nov. 17, 2010	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-13	-	1 GHz – 26.5 GHz	Nov. 17, 2010	Conducted (TH01-CB)
Power Sensor	Anritsu	MA2411B	0917223	300MHz~40GHz	Sep. 13, 2010	Conducted (TH01-CB)
Power Meter	Anritsu	ML2495A	1035008	300MHz~40GHz	Sep. 08, 2010	Conducted (TH01-CB)

Note: Calibration Interval of instruments listed above is one year.

6. TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 nd Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

7. TAF CERTIFICATE OF ACCREDITATION



Certificate No. : L1190-091230

財團法人全國認證基金會
Taiwan Accreditation Foundation

Certificate of Accreditation

This is to certify that

Sporton International Inc.
EMC & Wireless Communications Laboratory
No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien,
Taiwan, R.O.C.

is accredited in respect of laboratory

Accreditation Criteria	: ISO/IEC 17025:2005
Accreditation Number	: 1190
Originally Accredited	: December 15, 2003
Effective Period	: January 10, 2010 to January 09, 2013
Accredited Scope	: Testing Field, see described in the Appendix
Specific Accreditation Program	: Accreditation Program for Designated Testing Laboratory for Commodities Inspection Accreditation Program for Telecommunication Equipment Testing Laboratory Accreditation Program for BSMI Mutual Recognition Arrangement with Foreign Authorities

Jay-san Chen

Jay-San Chen
President, Taiwan Accreditation Foundation
Date : December 30, 2009

Pl, total 22 pages

The Appendix forms an integral part of this Certificate, which shall be invalid when use without the Appendix