

FCC TEST REPORT

Reference No. : GPWL2004000702EG

Applicant : Pittasoft Co., Ltd.

Equipment Under Test (EUT) :

Product Name : Blackvue Connectivity Module

Model Name : CM100GLTE-M

Applied Standards : FCC Part 15 Subpart B

ANSI C 63.4:2014



FCC ID : YCK-CM100GLTE-M

Date of Receipt : April 6, 2020

Date of Test : May 12, 2020

Date of Issue : June 10, 2020

Test Results : Complied

Tested by	:	 ----- Yongtae Yu
Reviewed by	:	 ----- Paul Kang

This test report does not assure KOLAS accreditation.

- 1) The results of this test report are effective only to the items tested.
- 2) The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received.

Remarks :

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This Test Report cannot be reproduced, except in full

Contents

1. General Information.....	4
1.1 Client Information.....	4
1.2 Test Laboratory.....	4
1.3 General Information of E.U.T.	4
1.4 Operating Modes and Conditions.....	5
1.5 Auxiliary Equipments	5
1.6 Cable List.....	5
1.7 System Configurations.....	5
1.8 Test System Layout	6
1.9 Modifications.....	6
1.10 Applicable Standards for Testing	6
1.11 Summary of Test Results.....	6
2. Emission Test.....	7
2.1 Test Results.....	7
2.2 Test Method and Limits.....	7
2.2.1 Test Method.....	7
2.2.2 Test Limits.....	7
2.3 Radiated Emission	8
2.3.1 Test Equipments	8
2.3.2 Test Site.....	8
2.3.3 Environment Conditions and data	8
Appendix A : Radiated Emission	10

Revision History

Revision	Report Number	Description
0	F690501-RF-EMG000177	Initial
1		
2		

1. General Information

1.1 Client Information

Applicant : Pittasoft Co., Ltd.
 - Address of Applicant : A 4th floor, ABN Tower, 331, Pangyo-ro, Bundang-gu, Seongnam-si, Gyeonggi-do, Republic of Korea

Manufacturer : Pittasoft Co., Ltd.
 - Address of Manufacturer : A 4th floor, ABN Tower, 331, Pangyo-ro, Bundang-gu, Seongnam-si, Gyeonggi-do, Republic of Korea

Factory : SMT SCOUT Co., Ltd.
 - Address of Factory : 38 Dangeong-ro, Gunpo-si, Gyeonggi-do, Republic of Korea, 15849

1.2 Test Laboratory

Name and Address : SGS Korea Co., Ltd.
 - Giheung 1 Laboratory : 35, Giheungdanji-ro 121beon-gil, Giheung-gu, Yongin-si, Gyeonggi-do, Republic of Korea
 - Giheung 2 Laboratory : 23, Giheungdanji-ro 24beon-gil, Giheung-gu, Yongin-si, Gyeonggi-do, Republic of Korea
 - Gunpo Laboratory : 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, 15807, Republic of Korea.

Phone : + 82 31 428 5700
 Fax : + 82 31 427 2370
 e-mail : paul.kang@sgs.com

1.3 General Information of E.U.T.

Classification	Description
Product Name	Blackvue Connectivity Module
Model Name	CM100GLTE-M
Serial No.	CM1MNAAJ300001
Highest Internal Frequency	1 850 MHz ~ 1 990 MHz
EMI Classification	Class B
Test Voltage	120 V~, 60 Hz (for Travel Adapter), 12 Vd.c. (for Battery)
Operating Voltage	5.0 Vd.c. 2.0 A (Minimum 2.7 Vd.c. ~ Maximum 5.5 Vd.c.)
Operating Temperature	(-)35 °C ~ (+)75 °C
S/W Version	CM100GLTE-M_VER_0.90
H/W Version	CM100GLTE-M_ES_V02
Function	This device is an LTE-M connection used in Dash Cam.

1.4 Operating Modes and Conditions

Operating Mode	Percussor
1) LTE Category M1 B2 Idle	Standby ((LTE Category M1 B2) Mode

1.5 Auxiliary Equipments

Description	Model	Serial No.	Manufacturer
Travel Adapter	EP-TA200	R37MA8S2NF1SE3	SAMSUNG
Power Module	KM001	-	Chargerlab
Car Battery	-	-	-
Dash Cam	BLACKVUE Cloud	-	Pittasoft Co., Ltd.

1.6 Cable List

Start		END		Cable Spec.		Used core
Name	I/O Port	Name	I/O Port	Length	Shield	
Radiated Emission(Below 1 GHz) Test						
Car Battery	AC OUT	Dash Cam	AC IN	4.2	Unshield	No
Dash Cam	DC OUT	EUT	DC IN	1.5	Unshield	No
Radiated Emission(Above 1 GHz) Test						
AC Source	AC OUT	Travel Adapter	AC IN	-	-	-
Travel Adapter	DC OUT	Power Module	DC IN	-	-	-
Power Module	USB	EUT	-	1.5	Unshield	No

1.7 System Configurations

Description	Model	Serial No.	Manufacturer
Main Board	CM100LTE_PP_V02	-	-
Antenna	-	-	-

Note. Antenna Requirement


For intentional device, according to FCC 47 CFR Section §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The antennas have unique connectors.

- Antenna gain


Category	Antenna Gain(dB i)
GSM1900	3.0
LTE FDD 2	3.0
LTE FDD 4	1.25
LTE FDD 12	1.8
LTE FDD 39	3.0

1.8 Test System Layout

- Radiated Emission(Below 1 GHz) Test



- Radiated Emission(Above 1 GHz) Test



1.9 Modifications

- There was no modified item during the test.

1.10 Applicable Standards for Testing

standards	Status	Deviation
FCC Part 15 Subpart B	Applicable	No Deviation

1.11 Summary of Test Results

Test Item	Basic Standards	Results
Radiated Emission	ANSI C 63.4:2014 FCC Part 15 Subpart B	Complied

Note: Test methods of all test items are performed according to the basic standards in this table.

EMISSION

2.1 Test Results

Test Items	Basic Standards	Test Results
Radiated Emission	ANSI C 63.4:2014, FCC Part 15 Subpart B	Complied

2.2 Test Method and Limits

2.2.1 Test Method

Test Items	Measuring Frequency Range	RBW	Measuring Distance
Radiated Emission	30 MHz ~ 1 GHz	120 kHz	10 m&3 m
	Above 1 GHz	1 MHz	3 m

2.2.2 Test Limits

-Radiated Emission Limits below 1 GHz

Frequency Range	Limits(dB(μ V/m))		Class
	Quasi-peak		
30 MHz ~ 88 MHz	39.1		Class A
88 MHz ~ 216 MHz	43.5		
216 MHz ~ 960 MHz	46.4		
960 MHz ~ 1 GHz	49.5		
30 MHz ~ 88 MHz	40		Class B
88 MHz ~ 216 MHz	43.5		
216 MHz ~ 960 MHz	46		
960 MHz ~ 1 GHz	54		

-Radiated Emission Limits above 1 GHz (3m method)

Frequency Range	Limits(dB(μ V/m))		Class
	Average	Peak	
Above 1 GHz	59.5	79.5	Class A
Above 1 GHz	54	74	Class B

2.3 Radiated Emission

The initial preliminary exploratory scans were performed at 3 m distance over the measuring frequency range(30 MHz to 18 GHz) using a max hold mode incorporating a Peak detector and using the software of EP5RE(Version Ver5.3.70 from TOYO). The final test data was measured using a Quasi-Peak detector below 1 GHz at 3 m distance and a Peak and Average detector above 1 GHz at 3 m distance. Measurements were made with the antenna positioned in both the horizontal and vertical planes of polarization. The antenna height was varied from 1 m to 4 m and the EUT was rotated 360° to find the maximum emitting point for each frequency.

2.3.1 Test Equipments

Description	Model No.	Manufacturer	S/N	Cal Due. Date
Horn Antenna	HF906	R & S	100326	2021.02.14
Signal Conditioning Unit	SCU 18	R & S	10117	2020.06.12
Test Receiver	ESU26	R & S	100109	2021.02.18
Bilog Antenna	VULB9163	SCHWARZBECK	396	2021.03.21
Amplifier	8447F	HP	2944A03909	2020.08.07
Wideband Radio Communication Tester	CMW500	R & S	144032	2020.05.14
3m SEMI-ANECHOIC CHAMBER	-	SY CORPORATION	-	-

Note : The Bilog Antenna calibration period is 2 years, but the other equipment calibration period are 1 year.

2.3.2 Test Site

3m SEMI-ANECHOIC CHAMBER Gunpo Laboratory (Below 1 GHz, Above 1 GHz)

2.3.3 Environment Conditions and data

- Below 1 GHz

Temperature (Minimum 22.2, Maximum 22.5) °C,
 Humidity (Minimum 33.0, Maximum 37.0) % R.H.,
 Atmospheric Pressure (Minimum 100.4, Maximum 100.4) kPa

Test Date : May 12, 2020

- Above 1 GHz

Temperature (Minimum 22.2, Maximum 22.5) °C,
 Humidity (Minimum 33.0, Maximum 37.0) % R.H.,
 Atmospheric Pressure (Minimum 100.4, Maximum 100.4) kPa

Test Date : May 12, 2020

- Below 1 GHz (3 m method)

Freq. (MHz)	Level (dB(μV))	Pol. (H/V)	A (°)	H (cm)	AF (dB/m)	CL (dB)	Amp. (dB)	Result (dB(μV/m))	Limit (dB(μV/m))	Margin (dB)
97.29	36.10	V	5	100	16.60	1.05	28.01	25.74	43.50	17.76
188.84	47.00	H	300	100	16.08	1.50	27.64	36.94	43.50	6.56
261.55	42.30	H	295	100	18.57	1.68	27.42	35.13	46.00	10.87
377.58	47.70	H	274	100	20.75	2.32	27.88	42.89	46.00	3.11
457.37	46.30	H	225	100	21.95	2.68	28.54	42.39	46.00	3.61
717.69	38.10	H	319	100	25.65	3.46	28.75	38.46	46.00	7.54

Measurement Uncertainty (Horizontal) : 5.01 dB (The confidential level is about 95%, k=2)

Measurement Uncertainty (Vertical) : 5.38 dB (The confidential level is about 95%, k=2)

- Note 1:
- AF = Antenna Factor
 - CL = Cable Loss
 - Amp = Amplifier Gain
 - POL H = Horizontal
 - POL V = Vertical
 - A : Angle
 - H : Height
 - Margin = Limit – Result
 - Result = Level + AF + CL – Amp

- Above 1 GHz (3 m method)

Freq. (MHz)	Level (dB(μV))		Pol. (H/V)	A (°)	H (cm)	AF (dB)	CL (dB)	Amp. (dB)	CF (dB)	F/S (dB(μV/m))	Limit (dB(μV/m))	Margin (dB)
	Peak	C-AV										
14917.33	33.60	-	H	259	100	40.67	16.00	44.43	0.00	45.84	74.00	28.16
14917.33	-	21.30	H	259	100	40.67	16.00	44.43	0.00	33.54	54.00	20.46
15031.37	32.70	-	V	277	100	40.44	15.69	44.43	0.00	44.40	74.00	29.60
15031.37	-	21.00	V	277	100	40.44	15.69	44.43	0.00	32.70	54.00	21.30
15629.92	33.70	-	H	342	200	40.20	16.60	45.09	0.00	45.41	74.00	28.59
15629.92	-	21.80	H	342	200	40.20	16.60	45.09	0.00	33.51	54.00	20.49
15758.83	33.20	-	V	144	200	40.30	16.73	45.23	0.00	45.00	74.00	29.00
15758.83	-	21.20	V	144	200	40.30	16.73	45.23	0.00	33.00	54.00	21.00
16028.71	34.20	-	H	249	200	40.66	16.98	45.52	0.00	46.32	74.00	27.68
16028.71	-	22.10	H	249	200	40.66	16.98	45.52	0.00	34.22	54.00	19.78
16309.21	34.00	-	V	87	200	41.32	17.07	45.72	0.00	46.67	74.00	27.33
16309.21	-	21.40	V	87	200	41.32	17.07	45.72	0.00	34.07	54.00	19.93
16527.37	34.70	-	H	272	100	41.45	17.15	45.87	0.00	47.43	74.00	26.57
16527.37	-	22.10	H	272	100	41.45	17.15	45.87	0.00	34.83	54.00	19.17
16878.00	34.90	-	V	257	100	41.76	17.39	46.11	0.00	47.94	74.00	26.06
16878.00	-	22.00	V	257	100	41.76	17.39	46.11	0.00	35.04	54.00	18.96
17405.00	36.70	-	V	48	100	42.72	18.32	46.36	0.00	51.38	74.00	22.62
17405.00	-	22.00	V	48	100	42.72	18.32	46.36	0.00	36.68	54.00	17.32
17560.12	38.60	-	H	154	100	43.34	18.59	46.42	0.00	54.11	74.00	19.89
17560.12	-	23.10	H	154	100	43.34	18.59	46.42	0.00	38.61	54.00	15.39

Measurement Uncertainty (Horizontal) : 5.33 dB (The confidential level is about 95%, k=2)


Measurement Uncertainty (Vertical) : 5.35 dB (The confidential level is about 95%, k=2)

- Note 1:
- AF = Antenna Factor
 - CL = Cable Loss
 - Amp = Amplifier Gain
 - POL H = Horizontal
 - POL V = Vertical
 - A : Angle
 - H : Height
 - Margin = Limit – Result
 - Result = Level + AF + CL – Amp


See Appendix A (Radiated Emission)

Appendix A : Radiated Emission

Below 1 GHz



Above 1 GHz



- End of the Report -