

# TEST REPORT



**Dt&C Co., Ltd.**

42, Yurim-ro, 154Beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea, 17042  
Tel : 031-321-2664, Fax : 031-321-1664

1. Report No : DRTFCC2403-0034

2. Customer

- Name (FCC) : Pittasoft Co., Ltd. / Name (IC) : PITTASOFT CO., LTD.
- Address (FCC) : A 4th floor, ABN Tower, 331, Pangyo-ro, Bundang-gu Seongnam-si, Gyeonggi-do  
South Korea 13488
- Address (IC) : A 4th floor, ABN Tower, 331, Pangyo-ro, Bundang-gu, Seongnam-s Gyeonggi-do  
08506 Korea (Republic Of)

3. Use of Report : FCC & IC Certification

4. Product Name / Model Name : Car DashCam / DR970X Box-2CH Plus  
FCC ID : YCK-DR970XBOXP  
IC : 23402-DR970XBOXP

5. FCC Regulation(s): Part 15.247  
IC Standard(s): RSS-247 Issue 3, RSS-Gen Issue 5  
Test Method used: KDB558074 D01v05r02, ANSI C63.10-2013



6. Date of Test : 2024.01.22 ~ 2024.02.14

7. Location of Test :  Permanent Testing Lab  On Site Testing

8. Testing Environment : See appended test report.

9. Test Result : Refer to the attached test result.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.  
This test report is not related to KOLAS accreditation.

Affirmation	Tested by	Technical Manager
	Name : SeungMin Gil  (Signature)	Name : JaeJin Lee  (Signature)

2024 . 03 . 29 .

**Dt&C Co., Ltd.**

If this report is required to confirmation of authenticity, please contact to [report@dtnc.net](mailto:report@dtnc.net)

## Test Report Version

Test Report No.	Date	Description	Revised by	Reviewed by
DRTFCC2403-0034	Mar, 29. 2024	Initial issue	SeungMin Gil	JaeJin Lee

# Table of Contents

<b>1. General Information</b>	<b>4</b>
1.1. Description of EUT	4
1.2. Declaration by the applicant / manufacturer	4
1.3. Testing Laboratory	5
1.4. Testing Environment	5
1.5. Measurement Uncertainty	5
1.6. Test Equipment List	6
<b>2. Test Methodology</b>	<b>7</b>
2.1. EUT Configuration	7
2.2. EUT Exercise	7
2.3. General Test Procedures	7
2.4. Instrument Calibration	7
2.5. Description of Test Modes	8
<b>3. Antenna Requirements</b>	<b>9</b>
<b>4. Summary of Test Result</b>	<b>10</b>
<b>5. Test Result</b>	<b>11</b>
5.1. Maximum Peak Output Power	11
5.1.1. Test Setup	11
5.1.2. Test Procedures	11
5.1.3. Test Results	11
5.2. 6 dB Bandwidth	14
5.2.1. Test Setup	14
5.2.2. Test Procedures	14
5.2.3. Test Results	14
5.3. Power Spectral Density	31
5.3.1. Test Setup	31
5.3.2. Test Procedures	31
5.3.3. Test Results	31
5.4. Unwanted Emissions (Conducted)	48
5.4.1. Test Setup	48
5.4.2. Test Procedures	48
5.4.3. Test Results	49
5.5. Unwanted Emissions (Radiated)	113
5.5.1. Test Setup	115
5.5.2. Test Procedures	115
5.5.3. Test Results	116
5.6. AC Power-Line Conducted Emissions	120
5.6.1. Test Setup	120
5.6.2. Test Procedures	120
5.6.3. Test Results	120
5.7. Occupied Bandwidth	121
5.7.1. Test Setup	121
5.7.2. Test Procedures	121
5.7.3. Test Results	121
<b>APPENDIX I</b>	<b>138</b>
<b>APPENDIX II</b>	<b>139</b>
<b>APPENDIX III</b>	<b>142</b>

## 1. General Information

### 1.1. Description of EUT

<b>Equipment Class</b>	Digital Transmission System (DTS)
<b>Product Name</b>	Car DashCam
<b>Model Name</b>	DR970X Box-2CH Plus
<b>Add Model Name</b>	DR970X Box-2CH IR Plus, DR970X Box-2CH Truck Plus, DR970X Box-2CH DMS Plus
<b>Hardware Version</b>	V1.0
<b>Software Version</b>	V1.000
<b>EUT Serial Number</b>	Radiated: 97XBK3MAE00043, Conducted : 97XBK3MAE00039
<b>Power Supply</b>	DC 12 V, DC 24 V
<b>Modulation Technique</b>	<ul style="list-style-type: none"> <li>▪ 802.11b: CCK, DSSS</li> <li>▪ 802.11g/n: OFDM</li> </ul>
<b>Antenna Specification</b>	Antenna Type: Chip Antenna Gain: 1.88 dBi (PK)

Band	Mode	Tx. frequency(MHz)	Max. conducted power(dBm)	Antenna gain(dBi)	Max. e.i.r.p (dBm)
2.4 GHz	802.11b	2 412 ~ 2 462	16.90	1.88	18.78
	802.11g	2 412 ~ 2 462	21.55	1.88	23.43
	802.11n (HT20)	2 412 ~ 2 462	20.84	1.88	22.72
	802.11n (HT40)	2 422 ~ 2 452	19.64	1.88	21.52

Note:  $e.i.r.p = P_{cond} + G_{EUT}$

$P_{cond}$  = measured power at feedpoint of the EUT antenna, in dBm (Peak Conducted Output Power)

$G_{EUT}$  = gain of the EUT radiating element (antenna), in dBi

### 1.2. Declaration by the applicant / manufacturer

N/A

### 1.3. Testing Laboratory

<b>Dt&amp;C Co., Ltd.</b>		
The 3 m test site and conducted measurement facility used to collect the radiated data are located at the 42, Yurim-ro, 154beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, Korea 17042.		
The test site complies with the requirements of Part 2.948 according to ANSI C63.4-2014.		
- FCC & IC MRA Designation No. : KR0034		
- ISED#: 5740A		
<a href="http://www.dtnet.net">www.dtnet.net</a>		
Telephone	:	+ 82-31-321-2664
FAX	:	+ 82-31-321-1664

### 1.4. Testing Environment

Ambient Condition	
▪ Temperature	+20 °C ~ +23 °C
▪ Relative Humidity	+35 % ~ +39 %

### 1.5. Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with requirements of ANSI C63.4-2014 and ANSI C63.10-2013. All measurement uncertainty values are shown with a coverage factor of  $k = 2$  to indicate a 95 % level of confidence.

Parameter	Measurement uncertainty
Antenna-port conducted emission	0.9 dB (The confidence level is about 95 %, $k = 2$ )
Radiated emission (1 GHz Below)	5.0 dB (The confidence level is about 95 %, $k = 2$ )
Radiated emission (1 GHz ~ 18 GHz)	4.8 dB (The confidence level is about 95 %, $k = 2$ )
Radiated emission (18 GHz Above)	4.9 dB (The confidence level is about 95 %, $k = 2$ )

### 1.6. Test Equipment List

Type	Manufacturer	Model	Cal.Date (yy/mm/dd)	Next.Cal.Date (yy/mm/dd)	S/N
Spectrum Analyzer	Agilent Technologies	N9020A	23/12/15	24/12/15	MY50410399
Spectrum Analyzer	Agilent Technologies	N9020A	23/06/23	24/06/23	US47360812
Spectrum Analyzer	Agilent Technologies	N9020A	23/12/15	24/12/15	MY48010133
Receiver	Rohde Schwarz	ESCI3	23/06/23	24/06/23	100798
DC Power Supply	H.P	6622A	23/12/15	24/12/15	3448A03760
DC Power Supply	SM techno	SDP30-5D	23/06/23	24/06/23	305DMG291
DC Power Supply	SM techno	SDP30-5D	23/06/23	24/06/23	305DMG304
Multimeter	FLUKE	17B+	23/12/15	24/12/15	36390701WS
Signal Generator	Rohde Schwarz	SMBV100A	23/12/15	24/12/15	255571
Signal Generator	ANRITSU	MG3695C	23/12/15	24/12/15	173501
Thermohygrometer	BODYCOM	BJ5478	23/12/15	24/12/15	120612-1
Thermohygrometer	BODYCOM	BJ5478	23/12/15	24/12/15	120612-2
Thermohygrometer	BODYCOM	BJ5478	23/06/23	24/06/23	N/A
Loop Antenna	ETS-Lindgren	6502	23/11/09	24/11/09	00060496
Hybrid Antenna	Schwarzbeck	VULB 9160	23/12/15	24/12/15	3362
Horn Antenna	ETS-Lindgren	3117	23/06/23	24/06/23	00143278
Horn Antenna	A.H.Systems Inc.	SAS-574	23/06/23	24/06/23	155
PreAmplifier	tsj	MLA-0118-B01-40	23/12/15	24/12/15	1852267
PreAmplifier	tsj	MLA-1840-J02-45	23/06/23	24/06/23	16966-10728
PreAmplifier	H.P	8447D	23/12/15	24/12/15	2944A07774
High Pass Filter	Wainwright Instruments	WHKX12-935-1000-15000-40SS	23/06/23	24/06/23	8
High Pass Filter	Wainwright Instruments	WHKX10-2838-3300-18000-60SS	23/06/23	24/06/23	1
High Pass Filter	Wainwright Instruments	WHNX8.0/26.5-6SS	23/06/23	24/06/23	3
Attenuator	Hefei Shunze	SS5T2.92-10-40	23/06/23	24/06/23	16012202
Attenuator	Aeroflex/Weinschel	56-3	23/06/23	24/06/23	Y2370
Attenuator	SMAJK	SMAJK-2-3	23/06/23	24/06/23	3
Attenuator	SMAJK	SMAJK-2-3	23/06/23	24/06/23	2
Attenuator	Aeroflex/Weinschel	86-10-11	23/06/23	24/06/23	408
Power Meter & Wide Bandwidth Sensor	Anritsu	ML2496A MA2411B	23/12/15	24/12/15	1338004 1911481
Cable	DT&C	Cable	24/01/03	25/01/03	G-2
Cable	HUBER+SUHNER	SUCOFLEX 100	24/01/03	25/01/03	G-3
Cable	DT&C	Cable	24/01/03	25/01/03	G-4
Cable	OMT	YSS21S	24/01/03	25/01/03	G-5
Cable	Junkosha	MWX241	24/01/03	25/01/03	mmW-1
Cable	Junkosha	MWX241	24/01/03	25/01/03	mmW-4
Cable	HUBER+SUHNER	SUCOFLEX100	24/01/03	25/01/03	M-1
Cable	HUBER+SUHNER	SUCOFLEX100	24/01/03	25/01/03	M-2
Cable	JUNKOSHA	MWX241/B	24/01/03	25/01/03	M-3
Cable	JUNKOSHA	J12J101757-00	24/01/03	25/01/03	M-7
Cable	HUBER+SUHNER	SUCOFLEX106	24/01/03	25/01/03	M-9
Cable	DT&C	Cable	24/01/03	25/01/03	RFC-46
Test Software	tsj	Radiated Emission Measurement	NA	NA	Version 2.00.0185

Note1: The measurement antennas were calibrated in accordance to the requirements of ANSI C63.5-2017.

Note2: The cable is not a regular calibration item, so it has been calibrated by Dt&C itself.

## 2. Test Methodology

The measurement procedures described in the ANSI C63.10-2013 and the guidance provided in KDB558074 D01v05r02 were used in measurement of the EUT.

The EUT was tested per the guidance of KDB558074 D01v05r02. And ANSI C63.10-2013 was used to reference appropriate EUT setup and maximizing procedures of radiated spurious emission and AC line conducted emission testing.

### 2.1. EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

### 2.2. EUT Exercise

The EUT was operated in the test mode to fix the TX frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

### 2.3. General Test Procedures

#### Conducted Emissions

The power-line conducted emission test procedure is not described on the KDB558074 D01v05r02.

So this test was fulfilled with the requirements in Section 6.2 of ANSI C63.10-2013.

The EUT is placed on the wooden table, which is 0.8 m above ground plane and the conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-peak and Average detector.

#### Radiated Emissions

Basically the radiated tests were performed with KDB558074 D01v05r02. But some requirements and procedures like test site requirements, EUT setup and maximizing procedure were fulfilled with the requirements in Section 5 and 6 of the ANSI C63.10-2013 as stated on section 12.1 of the KDB558074 D01v05r02.

The EUT is placed on a non-conductive table. For emission measurements at or below 1 GHz, the table height is 80 cm. For emission measurements above 1 GHz, the table height is 1.5 m. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3 m away from the receiving antenna, which varied from 1 m to 4 m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.

### 2.4. Instrument Calibration

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

## 2.5. Description of Test Modes

The EUT has been tested with the operating condition for maximizing the emission characteristics. A test program is used to control the EUT for staying in continuous transmitting.

### Transmitting Configuration of EUT

Mode	Data rate
802.11b	1 Mbps ~ 11 Mbps
802.11g	6 Mbps ~ 54 Mbps
802.11n(HT20)	MCS 0 ~ MCS 7
802.11n(HT40)	MCS 0 ~ MCS 7

### EUT Operation test setup

- **Test Software:** Realtek 11ac 8821C USB WLAN 0.0003.07.20190211
- **Power setting:** Refer to the table below.

### Test Mode

Test mode	Worst case data rate	Setting Power	Tested Frequency (MHz)		
TM 1	802.11b 1 Mbps	35	2 412	2 437	2 462
TM 2	802.11g 6 Mbps	42	2 412	2 437	2 462
TM 3	802.11n(HT20) MCS 0	40	2 412	2 437	2 462
TM 4	802.11n(HT40) MCS 0	35	2 422	2 437	2 452

Note1: The worst case data rate was determined according to the power measurements.

Note2: The power measurement results for all modes and data rate were reported.



### 3. Antenna Requirements

▣ **According to Part 15.203**

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

**The antenna is permanently attached on the device.**

**Therefore this E.U.T complies with the requirement of Part 15.203**

## 4. Summary of Test Result

FCC part section(s)	RSS section(s)	Test Description	Limit	Test Condition	Status Note 1
15.247(a)	RSS-247[5.2]	6 dB Bandwidth	> 500 kHz	Conducted	<b>C</b>
15.247(b)	RSS-247[5.4]	Maximum Peak Output Power	< 1 Watt (conducted), FCC & IC < 4 Watt (e.i.r.p), IC		<b>C</b>
15.247(d)	RSS-247[5.5]	Unwanted Emissions(Conducted)	20 dBc in any 100 kHz BW		<b>C</b>
15.247(e)	RSS-247[5.2]	Power Spectral Density	< 8 dBm / 3 kHz		<b>C</b>
-	RSS-Gen[6.7]	Occupied Bandwidth (99 %)	NA		<b>C</b>
15.247(d) 15.205 15.209	RSS-247[5.5] RSS-Gen[8.9] RSS-Gen[8.10]	Unwanted Emissions(Radiated)	Part 15.209 limits (Refer to section 5.5)	Radiated	<b>C</b> Note 2
15.207	RSS-Gen[8.8]	AC Power-Line Conducted Emissions	Part 15.207 limits (Refer to section 5.6)	AC Line Conducted	<b>NA</b> Note 3
15.203	-	Antenna Requirements	Part 15.203 (Refer to section 3)	-	<b>C</b>
Note 1: <b>C</b> =Comply <b>NC</b> =Not Comply <b>NT</b> =Not Tested <b>NA</b> =Not Applicable Note 2: This test item was performed in three orthogonal EUT positions and the worst case data was reported. Note 3: This device is installed in a car. Therefore the power source is a battery of car.					

## 5. Test Result


### 5.1. Maximum Peak Output Power

#### ■ Test Requirements and limit, Part 15.247(b) & RSS-247 [5.4]

The maximum permissible conducted output power is 1 Watt.

The e.i.r.p. shall not exceed 4 W, except as provided in section 5.4(e) of RSS-247.

#### 5.1.1. Test Setup



#### 5.1.2. Test Procedures

- KDB558074 D01v05r02 - Section 8.3.1.3
- ANSI C63.10-2013 – Section 11.9.1.3

##### RBW ≥ DTSPKPM1 Peak-reading power meter method

The maximum conducted output powers were measured using a broadband peak RF power meter which has greater video bandwidth than DUT's DTS bandwidth and utilize a fast-responding diode detector.

- KDB558074 D01v05r02 - Section 8.3.2.3
- ANSI C63.10-2013 – Section 11.9.2.3

##### Method AVGPM-G

The average conducted output powers were measured using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Since this measurement is made only during the ON time of the transmitter, no duty cycle correction is required.

#### 5.1.3. Test Results

- Refer to the next page

**- Power Supply: 24 V**

Mode	Freq. (MHz)	Det.	Maximum Peak Conducted Output Power (dBm)							
			Data Rate (Mbps)							
			1	2	5.5	11	-	-	-	-
802.11b	2 412	PK	<b>16.72</b>	16.70	16.66	16.71	-	-	-	-
		AV	13.99	13.72	13.76	13.88	-	-	-	-
	2 437	PK	16.21	16.15	16.12	16.14	-	-	-	-
		AV	13.51	13.42	13.45	13.48	-	-	-	-
	2 462	PK	15.69	15.57	15.58	15.62	-	-	-	-
		AV	13.04	12.83	12.86	12.88	-	-	-	-

Mode	Freq. (MHz)	Det.	Maximum Peak Conducted Output Power (dBm)							
			Data Rate (Mbps)							
			6	9	12	18	24	36	48	54
802.11g	2 412	PK	<b>21.55</b>	21.12	20.78	20.65	20.76	20.98	20.73	21.25
		AV	12.32	12.02	12.06	12.14	12.30	12.29	12.30	12.31
	2 437	PK	20.73	20.32	20.03	19.89	19.98	20.30	20.27	20.63
		AV	11.97	11.67	11.69	11.74	11.88	11.86	11.82	11.93
	2 462	PK	20.53	20.13	19.88	19.73	19.80	19.99	20.10	20.30
		AV	12.05	11.87	11.89	11.93	12.03	12.01	11.98	12.04

Mode	Freq. (MHz)	Det.	Maximum Peak Conducted Output Power (dBm)							
			Data Rate (MCS)							
			0	1	2	3	4	5	6	7
802.11n (HT20)	2 412	PK	<b>20.63</b>	20.32	19.87	19.55	20.40	19.55	19.97	19.37
		AV	11.23	11.02	11.11	11.09	11.22	11.22	11.16	11.18
	2 437	PK	19.88	19.56	19.21	19.03	19.56	19.16	19.35	18.97
		AV	10.98	10.78	10.83	10.81	10.92	10.93	10.90	10.89
	2 462	PK	19.37	19.05	18.78	18.57	19.23	19.02	19.12	18.78
		AV	11.01	10.83	10.82	10.86	10.89	10.95	10.89	10.90

Mode	Freq. (MHz)	Det.	Maximum Peak Conducted Output Power (dBm)							
			Data Rate (MCS)							
			0	1	2	3	4	5	6	7
802.11n (HT40)	2 422	PK	<b>19.42</b>	19.40	19.16	19.05	18.96	18.20	18.49	18.16
		AV	9.29	9.10	9.18	9.22	9.27	9.28	9.26	9.18
	2 437	PK	19.26	19.17	18.87	18.92	18.72	18.11	18.32	18.10
		AV	8.79	8.66	8.68	8.70	8.73	8.76	8.74	8.68
	2 452	PK	18.88	18.72	18.56	18.61	18.53	18.03	18.21	18.01
		AV	8.50	8.33	8.34	8.37	8.40	8.42	8.38	8.36

**- Power Supply: 12 V**

Mode	Freq. (MHz)	Det.	Maximum Peak Conducted Output Power (dBm)							
			Data Rate (Mbps)							
			1	2	5.5	11	-	-	-	-
802.11b	2 412	PK	<b>16.90</b>	16.77	16.73	16.79	-	-	-	-
		AV	14.11	13.79	13.84	14.03	-	-	-	-
	2 437	PK	16.43	16.33	16.34	16.35	-	-	-	-
		AV	13.83	13.53	13.67	13.71	-	-	-	-
	2 462	PK	15.99	15.75	15.78	15.93	-	-	-	-
		AV	13.30	13.10	13.23	13.24	-	-	-	-

Mode	Freq. (MHz)	Det.	Maximum Peak Conducted Output Power (dBm)							
			Data Rate (Mbps)							
			6	9	12	18	24	36	48	54
802.11g	2 412	PK	<b>21.53</b>	21.08	20.75	20.67	21.44	20.91	20.71	21.20
		AV	12.40	12.16	12.17	12.23	12.38	12.36	12.38	12.31
	2 437	PK	20.80	20.41	20.13	19.99	20.62	20.11	20.03	20.70
		AV	12.03	11.71	11.73	11.79	12.00	11.98	11.97	11.97
	2 462	PK	20.74	20.36	20.08	19.94	20.56	20.17	20.10	20.53
		AV	12.12	11.98	11.99	12.03	12.10	12.07	12.05	12.05

Mode	Freq. (MHz)	Det.	Maximum Peak Conducted Output Power (dBm)							
			Data Rate (MCS)							
			0	1	2	3	4	5	6	7
802.11n (HT20)	2 412	PK	<b>20.84</b>	20.55	20.06	19.61	20.66	19.78	20.14	19.55
		AV	11.38	11.12	11.23	11.20	11.34	11.35	11.27	11.29
	2 437	PK	20.04	19.77	19.46	19.26	19.74	19.42	19.53	19.13
		AV	11.13	10.99	11.04	11.02	11.12	11.06	11.02	11.03
	2 462	PK	19.59	19.26	18.93	18.77	19.46	19.23	19.42	18.91
		AV	11.16	11.03	11.04	11.06	11.07	11.09	10.98	11.05

Mode	Freq. (MHz)	Det.	Maximum Peak Conducted Output Power (dBm)							
			Data Rate (MCS)							
			0	1	2	3	4	5	6	7
802.11n (HT40)	2 422	PK	<b>19.64</b>	19.62	19.35	19.22	19.13	18.43	18.66	18.38
		AV	9.41	9.26	9.28	9.39	9.35	9.37	9.33	9.29
	2 437	PK	19.44	19.39	19.08	19.12	18.97	18.36	18.55	18.32
		AV	8.99	8.79	8.83	8.90	8.93	8.97	8.95	8.89
	2 452	PK	19.05	18.93	18.80	18.90	18.76	18.21	18.39	18.20
		AV	8.71	8.56	8.55	8.58	8.61	8.63	8.59	8.57

## 5.2. 6 dB Bandwidth

### ■ Test Requirements and limit, Part 15.247(a) & RSS-247 [5.2]

The bandwidth at 6 dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the EUT's antenna terminal while the EUT is operating in transmission mode at the appropriate frequencies.

**The minimum permissible 6 dB bandwidth is 500 kHz.**

#### 5.2.1. Test Setup

Refer to the APPENDIX I.

#### 5.2.2. Test Procedures

- KDB558074 D01v05r02 - Section 8.2
- ANSI C63.10-2013 – Section 11.8.2

1. Set resolution bandwidth (RBW) = 100 kHz
2. Set the video bandwidth (VBW)  $\geq 3 \times$  RBW.
3. Detector = **Peak**.
4. Trace mode = **max hold**.
5. Sweep = **auto couple**.
6. Allow the trace to stabilize.
7. Option 1 - Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Option 2 - The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described above (i.e., RBW = 100 kHz, VBW  $\geq 3 \times$  RBW, peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be  $\geq 6$  dB.


#### 5.2.3. Test Results

Test Mode	Frequency	Test Results (MHz)	
		DC 24 V	DC 12 V
TM 1	2 412	10.09	10.12
	2 437	10.07	10.11
	2 462	10.06	10.13
TM 2	2 412	16.36	16.34
	2 437	16.35	16.37
	2 462	16.38	16.34
TM 3	2 412	16.81	16.84
	2 437	16.80	16.70
	2 462	17.06	16.90
TM 4	2 422	35.38	35.26
	2 437	35.39	35.53
	2 452	35.17	35.55

- Power Supply: 24 V


6 dB Bandwidth

TM 1 & 2 412




6 dB Bandwidth

TM 1 & 2 437



6 dB Bandwidth


TM 1 & 2 462






6 dB Bandwidth

TM 2 & 2 412




6 dB Bandwidth

TM 2 & 2 437




6 dB Bandwidth

TM 2 & 2 462




6 dB Bandwidth

TM 3 & 2 412




6 dB Bandwidth

TM 3 & 2 437




6 dB Bandwidth

TM 3 & 2 462




6 dB Bandwidth

TM 4 & 2 422




6 dB Bandwidth

TM 4 & 2 437



6 dB Bandwidth


TM 4 & 2 452



- Power Supply: 12 V


6 dB Bandwidth

TM 1 & 2 412




6 dB Bandwidth

TM 1 & 2 437



6 dB Bandwidth


TM 1 & 2 462






6 dB Bandwidth

TM 2 & 2 412




6 dB Bandwidth

TM 2 & 2 437




6 dB Bandwidth

TM 2 & 2 462




6 dB Bandwidth

TM 3 & 2 412




6 dB Bandwidth

TM 3 & 2 437




6 dB Bandwidth

TM 3 & 2 462




6 dB Bandwidth

TM 4 & 2 422




6 dB Bandwidth

TM 4 & 2 437



6 dB Bandwidth

TM 4 & 2 452



### 5.3. Power Spectral Density

#### ■ Test requirements and limit, Part 15.247(e) & RSS-247 [5.2]

The peak power density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating in transmission mode at the appropriate frequencies.

**The power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.**

#### 5.3.1. Test Setup

Refer to the APPENDIX I.

#### 5.3.2. Test Procedures

- KDB558074 D01v05r02 - Section 8.4
- ANSI C63.10-2013 – Section 11.10.2

#### Method PKPSD (peak PSD)

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to **1.5 times** the DTS bandwidth.
3. Set the RBW : **3 kHz ≤ RBW ≤ 100 kHz**.
4. Set the VBW ≥ **3 x RBW**.
5. Detector = **peak**.
6. Sweep time = **auto couple**.
7. Trace mode = **max hold**.
8. Allow trace to fully stabilize.
9. Use the **peak marker function** to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.


#### 5.3.3. Test Results

Test Mode	Frequency	RBW	PKPSD (dBm)		Limit (dBm)
			DC 24 V	DC 12 V	
TM 1	2 412	3 kHz	-8.31	-9.35	8.00
	2 437	3 kHz	-8.77	-9.79	8.00
	2 462	3 kHz	-9.14	-9.94	8.00
TM 2	2 412	3 kHz	-12.93	-13.27	8.00
	2 437	3 kHz	-13.45	-13.87	8.00
	2 462	3 kHz	-13.72	-14.59	8.00
TM 3	2 412	3 kHz	-14.65	-14.85	8.00
	2 437	3 kHz	-15.12	-15.52	8.00
	2 462	3 kHz	-15.49	-15.64	8.00
TM 4	2 422	3 kHz	-19.81	-19.82	8.00
	2 437	3 kHz	-20.16	-20.55	8.00
	2 452	3 kHz	-20.11	-20.62	8.00

- Power Supply: 24 V


Power Spectral Density

TM 1 & 2 412



Power Spectral Density


TM 1 & 2 437






Power Spectral Density

TM 1 & 2 462




Power Spectral Density

TM 2 & 2 412




Power Spectral Density

TM 2 & 2 437




Power Spectral Density

TM 2 & 2 462




Power Spectral Density

TM 3 & 2 412




Power Spectral Density

TM 3 & 2 437




Power Spectral Density

TM 3 & 2 462




Power Spectral Density

TM 4 & 2 422




Power Spectral Density

TM 4 & 2 437



Power Spectral Density


TM 4 & 2 452



- Power Supply: 12 V


Power Spectral Density

TM 1 & 2 412



Power Spectral Density


TM 1 & 2 437






Power Spectral Density

TM 1 & 2 462




Power Spectral Density

TM 2 & 2 412




Power Spectral Density

TM 2 & 2 437




Power Spectral Density

TM 2 & 2 462




Power Spectral Density

TM 3 & 2 412




Power Spectral Density

TM 3 & 2 437




Power Spectral Density

TM 3 & 2 462




Power Spectral Density

TM 4 & 2 422




Power Spectral Density

TM 4 & 2 437



Power Spectral Density

TM 4 & 2 452



## 5.4. Unwanted Emissions (Conducted)

### ■ Test requirements and limit, Part 15.247(d) & RSS-247 [5.5]

In any 100 kHz bandwidth outside of the authorized frequency band, the power shall be attenuated according to the following conditions :

If the peak output power procedure is used to measure the fundamental emission power to demonstrate compliance to 15.247(b)(3) requirements, then the peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum measured in-band peak PSD level.

If the average output power procedure is used to measure the fundamental emission power to demonstrate compliance to 15.247(b)(3) requirements, then the power in any 100 kHz outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum measured inband average PSD level.

In either case, attenuation to levels below the general emission limits specified in §15.209(a) is not required.

#### 5.4.1. Test Setup

Refer to the APPENDIX I including path loss

#### 5.4.2. Test Procedures

- KDB558074 D01v05r02 - Section 8.5
- ANSI C63.10-2013 – Section 11.11

#### Reference level measurement

1. Set instrument center frequency to DTS channel center frequency.
2. Set the span to  $\geq 1.5$  times the DTS bandwidth.
3. Set the RBW = 100 kHz.
4. Set the VBW  $\geq 3 \times$  RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum PSD level  
**LIMIT LINE = 20 dB below of the reference level.**

#### Emission level measurement

1. Set the center frequency and span to encompass frequency range to be measured.
2. Set the RBW = 100 kHz.(Actual 1 MHz , See below note)
3. Set the VBW  $\geq 3 \times$  RBW.(Actual 3 MHz, See below note)
4. Detector = peak.
5. Ensure that the number of measurement points  $\geq$  span / RBW
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow the trace to stabilize (this may take some time, depending on the extent of the span).
9. Use the peak marker function to determine the maximum amplitude level.

**Note:** The unwanted emission(conducted) was tested with below settings.

Frequency range	RBW	VBW	Detector	Trace	Sweep Point
9 kHz ~ 30 MHz	100 kHz	300 kHz	Peak	Max Hold	40 001
30 MHz ~ 10 GHz	1 MHz	3 MHz			
10 GHz ~ 25 GHz	1 MHz	3 MHz			

If the emission level with above setting was close to the limit (ie, less than 3 dB margin) then zoom scan is required using RBW = 100 kHz, VBW = 300 kHz, SPAN = 100 MHz and BINS = 2 001 to get accurate emission level within 100 kHz BW.




5.4.3. Test Results


- Power Supply: 24 V

TM 1 & 2412

Reference



Low Band-edge



### Conducted Spurious Emissions

