



FCC RF Test Report

APPLICANT : Lenovo Mobile Communication Technology Ltd.
EQUIPMENT : Mobile Cellular Phone
BRAND NAME : Lenovo
MODEL NAME : Lenovo K53a48
FCC ID : YCNK53A48
STANDARD : 47 CFR Part 2, 22(H), 27(M)
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)

The product was received on Jun. 20, 2016 and completely tested on Sep. 03, 2016. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA / EIA-603-D-2010 and the testing has shown the tested sample to be in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

Prepared by: James Huang / Manager



Approved by: Jones Tsai / Manager

SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China



TABLE OF CONTENTS

REVISION HISTORY..... 3
SUMMARY OF TEST RESULT 4
1 GENERAL DESCRIPTION 5
1.1. Applicant 5
1.2. Manufacturer 5
1.3. Product Feature of Equipment Under Test..... 5
1.4. Product Specification of Equipment Under Test..... 6
1.5. Modification of EUT 6
1.6. Specification of Accessory 6
1.7. Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator 7
1.8. Testing Location 8
1.9. Applicable Standards 8
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST 9
2.1 Test Mode 9
2.2 Connection Diagram of Test System 11
2.3 Support Unit used in test configuration and system 12
2.4 Measurement Results Explanation Example 12
2.5 Frequency List of Low/Middle/High Channels 13
3 CONDUCTED TEST ITEMS 15
3.1 Measuring Instruments 15
3.2 Test Setup 15
3.3 Test Result of Conducted Test 15
3.4 Conducted Output Power 16
3.5 Peak-to-Average Ratio 16
3.6 Occupied Bandwidth 17
3.7 Conducted Band Edge 18
3.8 Conducted Spurious Emission 20
3.9 Frequency Stability 21
4 RADIATED TEST ITEMS 22
4.1 Measuring Instruments 22
4.2 Test Setup 22
4.3 Test Result of Radiated Test 22
4.4 Effective Radiated Power and Effective Isotropic Radiated Power 23
4.5 Radiated Spurious Emission 25
5 LIST OF MEASURING EQUIPMENT 26
6 UNCERTAINTY OF EVALUATION 27
APPENDIX A. TEST RESULTS OF CONDUCTED TEST
APPENDIX B. TEST RESULTS OF RADIATED TEST
APPENDIX C. TEST SETUP PHOTOGRAPHS



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG662003B	Rev. 01	Initial issue of report	Sep. 23, 2016



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	Reporting Only	PASS	-
3.5	N/A	Peak-to-Average Ratio	<13 dB	PASS	-
3.6	§2.1049	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§2.1051 §22.917(a)	Conducted Band Edge Measurement (Band 5)	$< 43+10\log_{10}(P[\text{Watts}])$	PASS	-
	§27.53(m)(4)	Conducted Band Edge Measurement (Band 7) (Band 38) (Band 41)	§27.53(m)(4)		
3.8	§2.1051 §22.917(a)	Conducted Spurious Emission (Band 5)	$< 43+10\log_{10}(P[\text{Watts}])$	PASS	-
	§2.1051 §27.53(m)(4)	Conducted Spurious Emission Band 7) (Band 38) (Band 41)	$< 55+10\log_{10}(P[\text{Watts}])$		
3.9	§2.1055 §22.355	Frequency Stability Temperature & Voltage	$< 2.5 \text{ ppm for Part 22H}$	PASS	-
	§2.1055 §27.54		Within Authorized Band		
4.4	§22.913(a)(2)	Effective Radiated Power (Band 5)	ERP < 7 Watt	PASS	-
	§27.50(h)(2)	Equivalent Isotropic Radiated Power (Band 7) (Band 38) (Band 41)	EIRP < 2Watt		
4.5	§2.1053 §22.917(a)	Radiated Spurious Emission (Band 5)	$< 43+10\log_{10}(P[\text{Watts}])$	PASS	Under limit 21.37 dB at 5180.000 MHz
	§2.1053 §27.53(m)(4)	Radiated Spurious Emission (Band 7) (Band 38) (Band 41)	$< 55+10\log_{10}(P[\text{Watts}])$		



1 General Description

1.1. Applicant

Lenovo Mobile Communication Technology Ltd.

No.999, Qishan North 2nd Road, Information & Optoelectronics Park, Torch Hi-tech Industry Development Zone, Xiamen, P. R. China

1.2. Manufacturer

Motorola Mobility LLC

222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.3. Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Lenovo
Model Name	Lenovo K53a48
FCC ID	YCNK53A48
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/DC-HSDPA/ HSPA+(16QAM uplink is not supported)/LTE/ WLAN 2.4GHz 802.11b/g/n HT20/ Bluetooth v3.0 + EDR/Bluetooth v4.0 LE/Bluetooth v4.2 LE
IMEI Code	Conducted: 861576030103839/861576030103847 Radiation: 861576030071572/861576030071580 ERP/EIRP: 861886030041651/861886030041669
HW Version	82939_1_13
SW Version	K53_S022_160815_ROW
EUT Stage	Identical Prototype

1.4. Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	LTE Band 5 : 824.7 MHz ~ 848.3 MHz LTE Band 7 : 2502.5 MHz ~ 2567.5 MHz LTE Band 38 : 2572.5MHz ~ 2617.5MHz LTE Band 41 : 2498.5 MHz ~ 2687.5 MHz
Rx Frequency	LTE Band 5 : 869.7 MHz ~ 893.3 MHz LTE Band 7 : 2622.5MHz ~ 2687.5 MHz LTE Band 38 : 2572.5MHz ~ 2617.5MHz LTE Band 41 : 2498.5 MHz ~ 2687.5 MHz
Bandwidth	LTE Band 5 : 1.4MHz / 3MHz / 5MHz / 10MHz LTE Band 7 : 5MHz/ 10MHz / 15MHz / 20MHz LTE Band 38 : 5MHz / 10MHz / 15MHz / 20MHz LTE Band 41 : 5MHz / 10MHz / 15MHz / 20MHz
Maximum Output Power to Antenna	LTE Band 5 : 24.07 dBm LTE Band 7 : 22.06 dBm LTE Band 38 : 24.72 dBm LTE Band 41 : 24.87 dBm
Type of Modulation	QPSK / 16QAM

1.5. Modification of EUT

No modifications are made to the EUT during all test items.

1.6. Specification of Accessory

Specification of Accessory				
AC Adapter 1	Brand Name	Lenovo (Acbel)	Model Name	C-P35
	Power Rating	I/P: 100-240Vac, 300mA, O/P: 5.2Vdc, 2000mA		
AC Adapter 2	Brand Name	Lenovo (Huntkey)	Model Name	C-P35
	Power Rating	I/P: 100-240Vac, 500mA, O/P: 5.2Vdc, 2000mA		
Battery	Brand Name	Lenovo (SCUD)	Model Name	BL270
	Power Rating	3.85Vdc, 4000mAh		
Earphone	Brand Name	N/A	Model Name	NLD-EM127E-96SH-6
	Signal Line Type	1.1 meter, non-shielded cable, without ferrite core		
USB Cable	Brand Name	Lenovo(Starw)	Model Name	XJ-007070
	Signal Line Type	1.0 meter, non-shielded cable, without ferrite core		
LCD Panel	Brand Name	TIANMA	Model Name	TL055VDXP64-00
Camera_ Front	Brand Name	Q-Tech	Model Name	FX219BQS
Camera _ Rear	Brand Name	Sunny	Model Name	A16S05J-200
CTP Module	Brand Name	O-FILM	Model Name	Black : MCF-055-2594
				White : MCF-055-2594-01
				Golden : MCF-055-2594-02



1.7. Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

LTE Band 5		QPSK			16QAM		
BW(MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum ERP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum ERP(W)	
1.4	1M10G7D	-	0.0637	1M10W7D	-	0.0484	
3	2M73G7D	-	0.0557	2M71W7D	-	0.0516	
5	4M50G7D	-	0.0574	4M51W7D	-	0.0490	
10	9M03G7D	0.0111	0.0564	9M03W7D	-	0.0437	
LTE Band 7		QPSK			16QAM		
BW(MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	
5	4M50G7D	-	0.3681	4M50W7D	-	0.2692	
10	9M15G7D	0.0039	0.3681	9M03W7D	-	0.2630	
15	13M4G7D	-	0.3436	13M5W7D	-	0.2754	
20	18M4G7D	-	0.3273	18M4W7D	-	0.2466	
LTE Band 38		QPSK			16QAM		
BW(MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	
5	4M53G7D	-	0.2286	4M49W7D	-	0.1663	
10	9M05G7D	0.0025	0.2065	9M03W7D	-	0.1972	
15	13M5G7D	-	0.1977	13M5W7D	-	0.1629	
20	18M5G7D	-	0.1897	18M4W7D	-	0.1862	
LTE Band 41		QPSK			16QAM		
BW(MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	
5	4M54G7D	-	0.4375	4M50W7D	-	0.3707	
10	9M01G7D	0.0024	0.4365	9M05W7D	-	0.3648	
15	13M4G7D	-	0.4571	13M5W7D	-	0.3381	
20	18M4G7D	-	0.4295	18M4W7D	-	0.3020	



1.8. Testing Location

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.		
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958		
Test Site No.	Sporton Site No.		FCC Registration No.
	TH01-KS	03CH03-KS	306251

1.9. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 2, 22(H), 27(M)
- ANSI / TIA / EIA-603-D-2010
- FCC KDB 971168 D01 Power Meas. License Digital Systems v02r02

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas. License Digital Systems v02r02 with maximum output power.

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes to find the maximum emission.


Test Items	Band	Bandwidth (MHz)						Modulation		RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	1	Half	Full	L	M	H
Max. Output Power	5	v	v	v	v	-	-	v	v	v	v	v	v	v	v
	7	-	-	v	v	v	v	v	v	v	v	v	v	v	v
	38	-	-	v	v	v	v	v	v	v	v	v	v	v	v
	41	-	-	v	v	v	v	v	v	v	v	v	v	v	v
Peak-to-Average Ratio	5				v	-	-	v	v	v		v	v	v	v
	7	-	-				v	v	v	v		v	v	v	v
	38	-	-				v	v	v	v		v	v	v	v
	41	-	-				v	v	v	v		v	v	v	v
26dB and 99% Bandwidth	5	v	v	v	v	-	-	v	v			v	v	v	v
	7	-	-	v	v	v	v	v	v			v	v	v	v
	38	-	-	v	v	v	v	v	v			v	v	v	v
	41	-	-	v	v	v	v	v	v			v	v	v	v
Conducted Band Edge	5	v	v	v	v	-	-	v	v	v		v	v		v
	7	-	-	v	v	v	v	v	v	v		v	v		v
	38	-	-	v	v	v	v	v	v	v		v	v		v
	41	-	-	v	v	v	v	v	v	v		v	v		v
Conducted Spurious Emission	5	v	v	v	v	-	-	v	v	v	v		v	v	v
	7	-	-	v	v	v	v	v	v	v			v	v	v
	38	-	-	v	v	v	v	v	v	v			v	v	v
	41	-	-	v	v	v	v	v	v	v			v	v	v
Frequency Stability	5				v	-	-	v				v		v	
	7	-	-		v			v				v		v	
	38	-	-		v			v				v		v	
	41	-	-		v			v				v		v	




Test Items	Band	Bandwidth (MHz)						Modulation		RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	1	Half	Full	L	M	H
E.R.P/ E.I.R.P.	5	v	v	v	v	-	-	v	v	v	v		v	v	v
	7	-	-	v	v	v	v	v	v	v			v	v	v
	38	-	-	v	v	v	v	v	v	v			v	v	v
	41	-	-	v	v	v	v	v	v	v			v	v	v
Radiated Spurious Emission	5	v	v	v	v	-	-	v		v				v	
	7	-	-	v	v	v	v	v		v				v	
	38	-	-	v	v	v	v	v		v				v	
	41	-	-	v	v	v	v	v		v				v	
Note	<ol style="list-style-type: none"> 1. The mark "v " means that this configuration is chosen for testing 2. The mark "- " means that this bandwidth is not supported. 3. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported. 														

2.2 Connection Diagram of Test System

For LTE Band 5, 7, 41



For LTE Band 38





2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	LTE Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	GWINSTEK	GPS-3030D	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss.

Following shows an offset computation example with cable loss 4.3 dB.

Example :

$$\begin{aligned} \text{Offset}(dB) &= \text{RF cable loss}(dB). \\ &= 4.3 \text{ (dB)} \end{aligned}$$



2.5 Frequency List of Low/Middle/High Channels

LTE Band 5 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
10	Channel	20450	20525	20600
	Frequency	829	836.5	844
5	Channel	20425	20525	20625
	Frequency	826.5	836.5	846.5
3	Channel	20415	20525	20635
	Frequency	825.5	836.5	847.5
1.4	Channel	20407	20525	20643
	Frequency	824.7	836.5	848.3

LTE Band 7 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	20850	21100	21350
	Frequency	2510	2535	2560
15	Channel	20825	21100	21375
	Frequency	2507.5	2535	2562.5
10	Channel	20800	21100	21400
	Frequency	2505	2535	2565
5	Channel	20775	21100	21425
	Frequency	2502.5	2535	2567.5



LTE Band 38 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	37850	38000	38150
	Frequency	2580	2595	2610
15	Channel	37825	38000	38175
	Frequency	2577.5	2595	2612.5
10	Channel	37800	38000	38200
	Frequency	2575	2595	2615
5	Channel	37775	38000	38225
	Frequency	2572.5	2595	2617.5

LTE Band 41 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	39750	40620	41490
	Frequency	2506	2593	2680
15	Channel	39725	40620	41515
	Frequency	2503.5	2593	2682.5
10	Channel	39700	40620	41540
	Frequency	2501	2593	2685
5	Channel	39675	40620	41565
	Frequency	2498.5	2593	2687.5


3 Conducted Test Items

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.2 Test Setup


3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied Bandwidth ,Conducted Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.



3.4 Conducted Output Power

3.4.1 Description of the Conducted Output Power Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to force the EUT transmitting at maximum output power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

3.4.2 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through the system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure and record the power level from the system simulator.

3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 5.7.1.
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.



3.6 Occupied Bandwidth

3.6.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.6.2 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 4.2.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
(this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.



3.7 Conducted Band Edge

3.7.1 Description of Conducted Band Edge Measurement

22.917(a)

For operations in the 824 – 849 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power P(Watts) in a 100kHz bandwidth. However, in the 1MHz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

27.53(m)(4)

For mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log (P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log (P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log (P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less that $43 + 10 \log (P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log (P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.



3.7.2 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 6.0.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The band edges of low and high channels for the highest RF powers were measured.
4. Set RBW \geq 1% EBW in the 1MHz band immediately outside and adjacent to the band edge.
5. Beyond the 1 MHz band from the band edge, RBW=1MHz was used.
6. Set spectrum analyzer with RMS detector.
7. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
8. Offset has included the duty factor for LTE Band 38/41. Duty factor = $10 \log (1/x)$, where x is the measured duty cycle
9. Checked that all the results comply with the emission limit line.

Example:

The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

$$= P(W) - [43 + 10\log(P)] \text{ (dB)}$$

$$= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)} = -13\text{dBm}.$$

10. For LTE Band 7, 38, 41, the other 40 dB, and 55 dB have additionally applied same calculation above.



3.8 Conducted Spurious Emission

3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

For Band 7,38,41:

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $55 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.8.2 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 6.0.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
7. Set spectrum analyzer with RMS detector.
8. Taking the record of maximum spurious emission.
9. Offset has included the duty factor for LTE Band 38/41. Duty factor = $10 \log (1/x)$, where x is the measured duty cycle
10. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
11. The limit line is derived from $43 + 10 \log(P)$ dB below the transmitter power P(Watts)
= $P(W) - [43 + 10 \log(P)]$ (dB)
= $[30 + 10 \log(P)]$ (dBm) - $[43 + 10 \log(P)]$ (dB)
= -13dBm.
12. For Band 7, 38, 41
The limit line is derived from $55 + 10 \log(P)$ dB below the transmitter power P(Watts)
= $P(W) - [55 + 10 \log(P)]$ (dB)
= $[30 + 10 \log(P)]$ (dBm) - $[55 + 10 \log(P)]$ (dB)
= -25dBm.



3.9 Frequency Stability

3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.9.2 Test Procedures for Temperature Variation

1. The testing follows FCC KDB 971168 v02r02 Section 9.0.
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.9.3 Test Procedures for Voltage Variation

1. The testing follows FCC KDB 971168 v02r02 Section 9.0.
2. The EUT was placed in a temperature chamber at $20\pm 5^{\circ}\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
4. The variation in frequency was measured for the worst case.


4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup

4.2.1 For radiated test from 30MHz to 1GHz



4.2.2 For radiated test above 1GHz



4.3 Test Result of Radiated Test

Please refer to Appendix B.



4.4 Effective Radiated Power and Effective Isotropic Radiated Power

4.4.1 Description of the ERP/EIRP Measurement

Effective radiated power output measurements by substitution method according to ANSI / TIA / EIA-603-D-2010, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v02r02. Mobile and portable (hand-held) stations operating are limited to average ERP of 7 watts with LTE band 5.

Equivalent isotropic radiated power output measurements by substitution method according to ANSI / TIA / EIA-603-D-2010, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v02r02. Mobile and portable (hand-held) stations operating are limited to average EIRP of 2 watts with LTE band 7 / 38 / 41.

4.4.2 Test Procedures

1. The EUT was placed on a non-conductive rotating platform (0.8 meters for frequency below 1GHz and 1.5 meter for frequency above 1GHz) in a semi-anechoic chamber. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and a spectrum analyzer with RMS detector per section 5. of KDB 971168 D01.
2. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power. The maximum emission was recorded from analyzer power level (LVL) from the 360 degrees rotation of the turntable and the test antenna raised and lowered over a range from 1 to 4 meters in both horizontally and vertically polarized orientations.
3. Effective Isotropic Radiated Power (EIRP) was measured by substitution method according to TIA/EIA-603-D. The EUT was replaced by the substitution antenna at same location, and then a known power from S.G. was applied into the dipole antenna through a Tx cable, and then recorded the maximum Analyzer reading through raised and lowered the test antenna. The correction factor (in dB) = S.G. - Tx Cable loss + Substitution antenna gain - Analyzer reading. Then the EUT's EIRP was calculated with the correction factor, $EIRP = LVL + \text{Correction factor}$ and $ERP = EIRP - 2.15$. Take the record of the output power at substitution antenna.



	LTE Average					
LTE BW	1.4M	3M	5M	10M	15M	20M
Span	3MHz	6MHz	10MHz	20MHz	30MHz	40MHz
RBW	30kHz	100kHz	100kHz	300kHz	300kHz	300kHz
VBW	100kHz	300kHz	300kHz	1MHz	1MHz	1MHz
Detector	RMS	RMS	RMS	RMS	RMS	RMS
Trace	Average	Average	Average	Average	Average	Average
Average Type	Power	Power	Power	Power	Power	Power
Sweep Count	100	100	100	100	100	100



4.5 Radiated Spurious Emission

4.5.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI / TIA / EIA-603-D-2010. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

For Band 7, 38, 41

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $55 + 10 \log (P)$ dB.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.5.2 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 5.8 and ANSI / TIA-603-D-2010 Section 2.2.12.
2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
= P(W)- [43 + 10log(P)] (dB)
= [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)
= -13dBm.

12. For Band 7, 38, 41:

The limit line is derived from $55 + 10\log(P)$ dB below the transmitter power P(Watts)
EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain
ERP (dBm) = EIRP - 2.15



5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Aug. 09, 2016	Aug. 23, 2016~ Sep. 03, 2016	Aug. 08, 2017	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-960502	-40~+150°C	Oct. 24, 2015	Aug. 23, 2016~ Sep. 03, 2016	Oct. 23, 2016	Conducted (TH01-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150244	10Hz~44GHz	Apr. 22, 2016	Aug. 29, 2016	Apr. 21, 2017	Radiation (03CH03-KS)
Bilog Antenna	TeseQ	CBL6112D	35406	25MHz~2GHz	Apr. 16, 2016	Aug. 29, 2016	Apr. 15, 2017	Radiation (03CH03-KS)
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1356	1GHz~18GHz	Apr. 16, 2016	Aug. 29, 2016	Apr. 15, 2017	Radiation (03CH03-KS)
SHF-EHF Horn	com-power	AH-840	101070	18GHz~40GHz	Oct. 10, 2015	Aug. 29, 2016	Oct. 09, 2016	Radiation (03CH02-KS)
Amplifier	SONOMA	310N	187289	9kHz~1GHz	Aug. 09, 2016	Aug. 29, 2016	Aug. 08, 2017	Radiation (03CH03-KS)
high gain Amplifier	MITEQ	AMF-7D-00 101800-30-1	1943529	1GHz~18GHz	Jan. 20, 2016	Aug. 29, 2016	Jan. 19, 2017	Radiation (03CH03-KS)
Amplifier	Agilent	8449B	3008A02370	1GHz~26.5GHz	Oct. 24, 2015	Aug. 29, 2016	Oct. 23, 2016	Radiation (03CH03-KS)
Amplifier	MITEQ	TTA1840-35 -HG	1887435	18GHz~40GHz	Jan. 20, 2016	Aug. 29, 2016	Jan. 19, 2017	Radiation (03CH03-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Aug. 29, 2016	NCR	Radiation (03CH03-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Aug. 29, 2016	NCR	Radiation (03CH03-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Aug. 29, 2016	NCR	Radiation (03CH03-KS)

NCR: No Calibration Required



6 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.5dB
---	-------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.5dB
---	-------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.6dB
---	-------



Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)

LTE Band 5 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	23.48	23.30	23.47
10	1	25		24.07	23.99	24.04
10	1	49		23.44	23.34	23.27
10	25	0		22.79	22.73	22.77
10	25	12		22.75	22.71	22.69
10	25	25		22.71	22.69	22.69
10	50	0		22.79	22.70	22.77
10	1	0	16-QAM	22.39	22.32	22.51
10	1	25		22.39	22.44	22.37
10	1	49		22.38	22.33	22.22
10	25	0		21.72	21.79	21.72
10	25	12		21.74	21.98	21.76
10	25	25		21.73	21.65	21.77
10	50	0		21.68	21.77	21.85
5	1	0	QPSK	23.63	23.49	23.47
5	1	12		23.88	23.68	23.93
5	1	24		23.43	23.39	23.31
5	12	0		22.62	22.75	22.70
5	12	7		22.71	22.69	22.76
5	12	13		22.68	22.67	22.54
5	25	0		22.64	22.68	22.64
5	1	0	16-QAM	22.27	22.93	22.30
5	1	12		22.63	22.99	22.65
5	1	24		22.28	22.37	22.23
5	12	0		21.69	21.51	21.56
5	12	7		21.72	21.76	21.56
5	12	13		21.76	21.82	21.63
5	25	0		21.82	21.66	21.51



LTE Band 5 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
3	1	0	QPSK	23.60	23.58	23.40
3	1	8		23.80	23.73	23.73
3	1	14		23.68	23.63	23.40
3	8	0		22.68	22.67	22.66
3	8	4		22.70	22.69	22.54
3	8	7		22.77	22.70	22.59
3	15	0		22.68	22.65	22.63
3	1	0	16-QAM	22.40	22.46	22.37
3	1	8		22.33	22.41	22.31
3	1	14		22.42	22.53	22.30
3	8	0		21.85	21.48	21.75
3	8	4		21.75	21.81	21.57
3	8	7		21.85	21.73	21.57
3	15	0		21.77	21.72	21.70
1.4	1	0	QPSK	23.73	23.60	23.43
1.4	1	3		23.76	23.72	23.67
1.4	1	5		23.72	23.69	23.68
1.4	3	0		23.83	23.91	23.66
1.4	3	1		23.83	23.92	23.67
1.4	3	3		23.82	23.77	23.67
1.4	6	0		22.76	22.65	22.48
1.4	1	0	16-QAM	22.49	22.45	22.31
1.4	1	3		22.45	22.39	22.82
1.4	1	5		22.42	22.41	22.66
1.4	3	0		22.62	22.60	22.61
1.4	3	1		22.65	22.69	22.55
1.4	3	3		22.73	22.81	22.67
1.4	6	0		21.75	21.68	21.57



LTE Band 7 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
20	1	0	QPSK	21.54	21.48	21.51
20	1	49		21.91	21.97	22.06
20	1	99		21.52	21.76	21.51
20	50	0		20.98	21.12	21.06
20	50	24		21.02	21.13	21.15
20	50	50		20.90	20.97	20.99
20	100	0		21.02	21.05	21.07
20	1	0	16-QAM	20.92	20.86	20.88
20	1	49		20.84	20.97	20.94
20	1	99		20.65	20.78	20.51
20	50	0		20.14	20.15	20.10
20	50	24		20.15	20.15	20.19
20	50	50		20.02	20.08	20.08
20	100	0		20.04	20.02	20.09
15	1	0	QPSK	21.61	21.88	21.85
15	1	37		21.94	22.04	22.02
15	1	74		21.62	21.72	21.54
15	36	0		20.94	21.01	21.04
15	36	20		20.96	21.07	20.90
15	36	39		20.90	21.02	20.96
15	75	0		20.97	21.06	21.03
15	1	0	16-QAM	20.88	20.76	20.56
15	1	37		21.14	20.60	20.35
15	1	74		20.58	20.60	20.27
15	36	0		19.89	20.03	20.07
15	36	20		20.00	20.10	20.03
15	36	39		19.98	19.96	20.02
15	75	0		19.92	20.06	20.04



LTE Band 7 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	21.52	21.72	21.68
10	1	25		21.97	22.03	22.03
10	1	49		21.60	21.63	21.54
10	25	0		20.97	21.01	20.89
10	25	12		20.97	21.07	21.00
10	25	25		20.89	21.03	20.92
10	50	0		20.97	21.06	20.88
10	1	0	16-QAM	20.41	20.76	20.60
10	1	25		21.25	20.72	20.67
10	1	49		20.39	20.57	20.45
10	25	0		19.93	20.14	20.09
10	25	12		19.94	20.32	20.02
10	25	25		19.96	20.17	20.14
10	50	0		20.02	20.14	20.14
5	1	0	QPSK	21.40	21.64	21.57
5	1	12		21.70	21.87	21.80
5	1	24		21.59	21.51	21.63
5	12	0		20.74	21.03	20.83
5	12	7		20.74	21.08	20.80
5	12	13		20.80	20.95	20.74
5	25	0		20.84	21.08	20.83
5	1	0	16-QAM	20.77	21.14	20.38
5	1	12		20.97	21.21	21.05
5	1	24		20.84	20.49	20.61
5	12	0		19.77	20.16	20.01
5	12	7		19.79	20.21	19.99
5	12	13		19.57	20.10	19.83
5	25	0		19.88	20.06	19.99



LTE Band 38 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
20	1	0	QPSK	24.41	24.21	24.08
20	1	49		24.72	24.57	24.52
20	1	99		24.30	24.26	23.85
20	50	0		23.66	23.33	23.29
20	50	24		23.69	23.36	23.33
20	50	50		23.42	23.22	23.16
20	100	0		23.61	23.28	23.20
20	1	0	16-QAM	23.15	23.10	23.06
20	1	49		23.39	23.13	23.13
20	1	99		22.97	22.95	22.85
20	50	0		22.53	22.28	22.33
20	50	24		22.66	22.48	22.33
20	50	50		22.61	22.63	22.20
20	100	0		22.44	22.58	22.15
15	1	0	QPSK	24.41	24.26	24.13
15	1	37		24.66	24.70	24.53
15	1	74		24.58	24.25	24.06
15	36	0		23.55	23.52	23.24
15	36	20		23.49	23.61	23.29
15	36	39		23.41	23.29	23.20
15	75	0		23.46	23.30	23.16
15	1	0	16-QAM	23.34	23.09	22.83
15	1	37		23.31	23.26	23.19
15	1	74		23.11	22.92	22.77
15	36	0		22.46	22.52	22.32
15	36	20		22.64	22.47	22.38
15	36	39		22.46	22.48	22.14
15	75	0		22.64	22.45	22.23



LTE Band 38 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	24.40	24.31	24.27
10	1	25		24.60	24.15	24.56
10	1	49		24.50	24.03	23.92
10	25	0		23.47	23.32	23.23
10	25	12		23.60	23.34	23.31
10	25	25		23.48	23.29	23.17
10	50	0		23.54	23.31	23.18
10	1	0	16-QAM	23.21	22.93	22.95
10	1	25		23.32	23.18	23.02
10	1	49		23.17	22.85	22.83
10	25	0		22.89	22.55	22.47
10	25	12		22.70	22.66	22.45
10	25	25		22.50	22.52	22.29
10	50	0		22.41	22.45	22.24
5	1	0	QPSK	24.38	24.00	23.91
5	1	12		24.50	24.16	24.26
5	1	24		24.31	23.86	24.04
5	12	0		23.54	23.50	23.19
5	12	7		23.44	23.65	23.28
5	12	13		23.46	23.52	23.17
5	25	0		23.37	23.48	23.20
5	1	0	16-QAM	23.26	23.12	22.91
5	1	12		23.54	23.22	23.11
5	1	24		23.11	22.99	22.83
5	12	0		22.61	22.33	22.27
5	12	7		22.51	22.41	22.29
5	12	13		22.51	22.49	22.15
5	25	0		22.65	22.72	22.28



LTE Band 41 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
20	1	0	QPSK	24.12	24.20	23.68
20	1	49		24.76	24.70	24.02
20	1	99		24.35	24.32	23.68
20	50	0		23.23	23.31	22.76
20	50	24		23.50	23.37	22.96
20	50	50		23.21	23.27	22.75
20	100	0		23.32	23.31	22.83
20	1	0	16-QAM	22.97	23.07	22.45
20	1	49		23.04	23.35	22.50
20	1	99		23.05	23.02	22.29
20	50	0		22.19	22.33	21.84
20	50	24		22.22	22.70	21.73
20	50	50		22.11	22.36	21.83
20	100	0		22.30	22.69	21.80
15	1	0	QPSK	24.03	24.87	23.91
15	1	37		24.71	24.42	24.15
15	1	74		24.55	23.58	23.75
15	36	0		23.23	23.38	22.84
15	36	20		23.26	23.32	22.81
15	36	39		23.17	23.37	22.69
15	75	0		23.26	23.06	22.76
15	1	0	16-QAM	22.79	23.35	22.45
15	1	37		23.00	23.05	22.72
15	1	74		22.85	22.30	22.41
15	36	0		22.07	22.66	21.96
15	36	20		22.37	22.37	21.83
15	36	39		22.23	22.44	21.72
15	75	0		22.37	23.00	22.19



LTE Band 41 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	24.42	24.20	23.80
10	1	25		24.85	24.21	24.00
10	1	49		24.52	24.17	23.70
10	25	0		23.48	23.48	22.74
10	25	12		23.43	23.43	22.84
10	25	25		23.37	23.32	22.66
10	50	0		23.34	23.36	22.71
10	1	0	16-QAM	23.11	23.03	22.44
10	1	25		23.00	23.20	22.66
10	1	49		22.88	22.95	22.21
10	25	0		22.61	22.60	22.15
10	25	12		22.69	22.68	22.12
10	25	25		22.58	22.42	22.03
10	50	0		22.54	22.43	21.79
5	1	0	QPSK	24.08	24.30	23.41
5	1	12		24.22	24.50	23.77
5	1	24		24.07	24.00	23.48
5	12	0		23.24	23.34	22.77
5	12	7		23.17	23.61	22.73
5	12	13		23.25	23.59	22.76
5	25	0		23.29	23.31	22.83
5	1	0	16-QAM	23.00	23.11	22.49
5	1	12		23.07	23.33	22.48
5	1	24		22.77	23.06	22.50
5	12	0		22.59	22.45	21.88
5	12	7		22.28	22.54	21.76
5	12	13		22.22	22.46	21.86
5	25	0		22.50	22.63	22.02



Peak-to-Average Ratio

Mode	LTE Band 5 / 10MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	Full RB	Result
Lowest CH	4.12	5.22	5.25	6.23	PASS
Middle CH	4.75	4.99	5.94	6.00	
Highest CH	4.17	5.28	5.39	6.23	

Mode	LTE Band 7 / 20MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	Full RB	Result
Lowest CH	4.32	4.75	4.99	5.8	PASS
Middle CH	4.52	5.01	5.59	6.03	
Highest CH	4.2	4.87	5.33	5.83	

Mode	LTE Band 38 / 20MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	Full RB	Result
Lowest CH	6.23	7.1	5.45	5.33	PASS
Middle CH	4.03	5.28	7.13	5.48	
Highest CH	3.83	5.86	5.22	6.43	

Mode	LTE Band 41 / 20MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	Full RB	Result
Lowest CH	4.7	5.39	5.62	6.2	PASS
Middle CH	5.48	5.83	6.09	5.71	
Highest CH	4.9	5.3	5.39	6.12	




LTE Band 5 / 10MHz / QPSK

Lowest Channel / 1RB



Date: 23 AUG 2016 23:50:30

Lowest Channel / Full RB



Date: 23 AUG 2016 23:50:13

Middle Channel / 1RB



Date: 23 AUG 2016 23:50:43

Middle Channel / Full RB



Date: 23 AUG 2016 23:51:02

Highest Channel / 1RB



Date: 23 AUG 2016 23:49:36

Highest Channel / Full RB




Date: 23 AUG 2016 23:49:56



LTE Band 5 / 10MHz / 16QAM

Lowest Channel / 1RB



Date: 23 AUG 2016 23:46:38

Lowest Channel / Full RB




Date: 23 AUG 2016 23:46:49

Middle Channel / 1RB



Date: 23 AUG 2016 23:46:59

Middle Channel / Full RB



Date: 23 AUG 2016 23:47:21

Highest Channel / 1RB



Date: 23 AUG 2016 23:47:35

Highest Channel / Full RB



Date: 23 AUG 2016 23:47:48



LTE Band 7 / 20MHz / QPSK

Lowest Channel / 1RB



Date: 24 AUG 2016 01:20:06

Lowest Channel / Full RB




Date: 24 AUG 2016 01:20:34

Middle Channel / 1RB



Date: 24 AUG 2016 01:21:55

Middle Channel / Full RB




Date: 24 AUG 2016 01:21:42

Highest Channel / 1RB



Date: 24 AUG 2016 01:22:37

Highest Channel / Full RB



Date: 24 AUG 2016 01:22:51




LTE Band 7 / 20MHz / 16QAM

Lowest Channel / 1RB



Date: 24 AUG 2016 01:19:40

Lowest Channel / Full RB




Date: 24 AUG 2016 01:21:12

Middle Channel / 1RB



Date: 24 AUG 2016 01:22:09

Middle Channel / Full RB



Date: 24 AUG 2016 01:21:27

Highest Channel / 1RB



Date: 24 AUG 2016 01:22:23

Highest Channel / Full RB



Date: 24 AUG 2016 01:23:06




LTE Band 38 / 20MHz / QPSK

Lowest Channel / 1RB



Date: 27 AUG 2016 16:22:46

Lowest Channel / Full RB



Date: 27 AUG 2016 16:21:28

Middle Channel / 1RB




Date: 27 AUG 2016 16:23:10

Middle Channel / Full RB




Date: 27 AUG 2016 16:28:55

Highest Channel / 1RB



Date: 27 AUG 2016 16:30:05

Highest Channel / Full RB



Date: 27 AUG 2016 16:31:08



LTE Band 38 / 20MHz / 16QAM

Lowest Channel / 1RB




Date: 27 AUG 2016 16:22:17

Lowest Channel / Full RB




Date: 27 AUG 2016 16:22:00

Middle Channel / 1RB




Date: 27 AUG 2016 16:24:10

Middle Channel / Full RB




Date: 27 AUG 2016 16:28:33

Highest Channel / 1RB



Date: 27 AUG 2016 16:30:30

Highest Channel / Full RB




Date: 27 AUG 2016 16:30:44




LTE Band 41 / 20MHz / QPSK

Lowest Channel / 1RB



Date: 3.SEP.2016 15:30:17

Lowest Channel / Full RB




Date: 3.SEP.2016 15:34:05

Middle Channel / 1RB



Date: 3.SEP.2016 15:35:35

Middle Channel / Full RB




Date: 3.SEP.2016 15:38:35

Highest Channel / 1RB



Date: 3.SEP.2016 15:41:28

Highest Channel / Full RB




Date: 3.SEP.2016 15:39:16




LTE Band 41 / 20MHz / 16QAM

Lowest Channel / 1RB




Date: 3.SEP.2016 15:31:00

Lowest Channel / Full RB




Date: 3.SEP.2016 15:33:30

Middle Channel / 1RB




Date: 3.SEP.2016 15:36:49

Middle Channel / Full RB




Date: 3.SEP.2016 15:38:02

Highest Channel / 1RB



Date: 3.SEP.2016 15:40:48

Highest Channel / Full RB



Date: 3.SEP.2016 15:40:11



26dB Bandwidth

Mode	LTE Band 5 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.26	1.27	2.96	3.03	4.93	4.95	9.69	9.91	-	-	-	-
Middle CH	1.25	1.26	2.99	2.98	4.90	5.00	9.79	9.83	-	-	-	-
Highest CH	1.26	1.25	3.00	3.01	4.91	4.85	9.79	9.97	-	-	-	-

Mode	LTE Band 7 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	-	-	-	-	4.955	4.845	9.77	9.85	14.535	14.326	20.18	20.06
Middle CH	-	-	-	-	4.905	4.925	9.69	10.01	14.386	14.446	20.14	20.14
Highest CH	-	-	-	-	4.935	4.915	9.87	9.97	14.296	14.236	20.22	20.06


Mode	LTE Band 38 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	-	-	-	-	4.795	4.975	9.71	9.61	14.565	14.206	20.1	20.3
Middle CH	-	-	-	-	5.005	4.855	9.63	9.65	14.326	14.176	20.1	20.26
Highest CH	-	-	-	-	4.835	4.945	9.69	9.67	14.116	14.266	20.02	20.02

Mode	LTE Band 41 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	-	-	-	-	4.825	4.765	9.61	9.75	14.386	14.565	20.34	20.02
Middle CH	-	-	-	-	4.815	5.065	9.75	9.63	14.146	14.236	20.06	20.1
Highest CH	-	-	-	-	4.825	4.945	9.63	9.63	14.535	14.206	20.06	20.1




LTE Band 5

Lowest Channel / 1.4MHz / QPSK




Date: 23 AUG 2016 21:36:21

Lowest Channel / 1.4MHz / 16QAM




Date: 23 AUG 2016 21:36:11

Middle Channel / 1.4MHz / QPSK




Date: 23 AUG 2016 21:51:14

Middle Channel / 1.4MHz / 16QAM




Date: 23 AUG 2016 21:51:25

Highest Channel / 1.4MHz / QPSK



Date: 23 AUG 2016 21:53:46

Highest Channel / 1.4MHz / 16QAM




Date: 23 AUG 2016 21:53:57




LTE Band 5

Lowest Channel / 3MHz / QPSK




Date: 23 AUG 2016 22:08:50

Lowest Channel / 3MHz / 16QAM




Date: 23 AUG 2016 22:09:00

Middle Channel / 3MHz / QPSK




Date: 23 AUG 2016 22:23:53

Middle Channel / 3MHz / 16QAM




Date: 23 AUG 2016 22:24:04

Highest Channel / 3MHz / QPSK



Date: 23 AUG 2016 22:26:25

Highest Channel / 3MHz / 16QAM




Date: 23 AUG 2016 22:26:35




LTE Band 5

Lowest Channel / 5MHz / QPSK




Date: 23 AUG 2016 22:41:29

Lowest Channel / 5MHz / 16QAM




Date: 23 AUG 2016 22:41:39

Middle Channel / 5MHz / QPSK




Date: 23 AUG 2016 22:56:32

Middle Channel / 5MHz / 16QAM




Date: 23 AUG 2016 22:56:43

Highest Channel / 5MHz / QPSK



Date: 23 AUG 2016 22:59:04

Highest Channel / 5MHz / 16QAM




Date: 23 AUG 2016 22:59:14




LTE Band 5

Lowest Channel / 10MHz / QPSK




Date: 23 AUG 2016 23:14:08

Lowest Channel / 10MHz / 16QAM




Date: 23 AUG 2016 23:14:18

Middle Channel / 10MHz / QPSK




Date: 23 AUG 2016 23:29:11

Middle Channel / 10MHz / 16QAM




Date: 23 AUG 2016 23:29:22

Highest Channel / 10MHz / QPSK



Date: 23 AUG 2016 23:31:43

Highest Channel / 10MHz / 16QAM



Date: 23 AUG 2016 23:31:53