

**FCC RF Exposure Exemption report**

**for**

**Radar rear light**

**Model No.: Gardia R300**

**FCC ID: YDM-DE2201**

**of**

Applicant: Bryton Inc.

Address: 3F-1., No.79-1, Zhouzi St., Neihu Dist., Taipei City 114, Taiwan

Tested and Prepared

by

**Worldwide Testing Services (Taiwan) Co., Ltd.**

**FCC Registration No.: TW1477, TW1072**

**Industry Canada filed test laboratory Reg. No.: 20037, 5107A**



**Report No.: W6M22206-21912-EE**

6F, NO. 58, LANE 188, RUEY-KUANG RD., NEIHU TAIPEI 114, TAIWAN, R.O.C.  
TEL: 886-2-66068877      FAX: 886-2-66068879      E-mail: [wts@wts-lab.com](mailto:wts@wts-lab.com)



Registration number: W6M22206-21912-EE

FCC ID: YDM-DE2201

**TABLE OF CONTENTS**

**1 GENERAL INFORMATION.....2**

1.1 NOTES.....2

1.2 TESTING LABORATORY .....3

1.3 APPLICATION DETAILS .....3

1.4 GENERAL INFORMATION OF TEST ITEM.....4

1.5 POWER SETTING .....5

1.6 DUTY CYCLE AND FACTOR.....5

1.7 TEST STANDARDS.....5

**2 TEST CONFIGURATION .....8**

2.1 TEST ENVIRONMENT .....8

2.2 MEASUREMENT UNCERTAINTY .....8

2.3 TEST EQUIPMENT LIST.....8

**3 EQUIVALENT ISOTROPIC RADIATED POWER (EIRP).....9**

3.1 EXEMPTION LIMITS FOR ROUTINE EVALUATION.....9



# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22206-21912-EE

FCC ID: YDM-DE2201

## 1 General Information

### 1.1 Notes

The purpose of conformity testing is to increase the probability of adherence to the essential requirements or conformity specifications, as appropriate.

The complexity of the technical specifications, however, means that full and thorough testing is impractical for both technical and economic reasons.

Furthermore, there is no guarantee that a test sample which has passed all the relevant tests conforms to a specification.

Neither is there any guarantee that such a test sample will interwork with other genuinely open systems.

The existence of the tests nevertheless provides the confidence that the test sample possesses the qualities as maintained and that its performance generally conforms to representative cases of communications equipment.

Laboratory disclaimer-

1. The test results of this test report relate exclusively to the item tested as specified in 1.5.
2. The test report may only be reproduced or published in full.
3. Reproduction or publication of extracts from the report requires the prior written approval of the Worldwide Testing Services(Taiwan) Co., Ltd.
4. Antenna gain is provided by applicant and laboratory issue relevant data and results.

### **Tester:**

February 22, 2023

Ken Kang

Date

WTS-Lab.

Name

Signature

### **Technical responsibility for area of testing:**

February 22, 2023

Kevin Wang

Date

WTS

Name

Signature



# **Worldwide Testing Services(Taiwan) Co., Ltd.**

Registration number: W6M22206-21912-EE

FCC ID: YDM-DE2201

## **1.2 Testing laboratory**

### **1.2.1 Location**

10m OATS

No.5-1, Lishui, Shuang Sing Village, Wanli Dist.,  
New Taipei City 207, Taiwan (R.O.C.)

3 meter semi-anechoic chamber

No.35, Aly. 21, Ln. 228, Ankang Rd., Neihu Dist.,  
Taipei City 114, Taiwan (R.O.C.)

Tel: 886-2-6613-0228

Worldwide Testing Services (Taiwan) Co., Ltd.

6F., No. 58, Ln. 188, Ruiguang Rd., Neihu Dist.,  
Taipei City 114, Taiwan (R.O.C.)

Tel: 886-2-6606-8877

### **1.2.2 Details of accreditation status**

Accredited testing laboratory

FCC filed test laboratory Reg. No.: TW1477, TW1072

Industry Canada filed test laboratory Reg. No.: 20037, 5107A

**Test location, where different from Worldwide Testing Services (Taiwan) Co., Ltd. :**

Name: ./.

Accredited no.: ./.

Street: ./.

Town: ./.

Country: ./.

## **1.3 Application details**

### **Approval holder**

Name: Bryton Inc.

Street: 3F-1., No.79-1, Zhouzi St., Neihu Dist.,

Town: Taipei City 114,

Country: Taiwan

### **Manufacturer: (if applicable)**

1.

Name: Pan-international Precision Electronic Co.,Ltd

Street: Xinlian Indl. Area , Hu-men ,

Town: Dongguan ,Guangdong ,

Country: China



# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22206-21912-EE

FCC ID: YDM-DE2201

2.

Name: Q.S.C INDUSTRY CO.LTD  
 Street: 5F., No. 193-2, Zhongxing N. St., Sanchong Dist.,  
 Town: New Taipei City  
 Country: Taiwan

Date of receipt of test item: June 17, 2022

Date of test: from June 20, 2022 to December 19, 2022

## 1.4 General information of Test item

Type of test item: Radar rear light  
 Model no.: Gardia R300  
 Multi-listing model no.: ./.  
 Brand name: Bryton  
 Power supply: Battery: 3.7V, 1000mAh, 3.7Wh  
 USB 5Vd.c.  
 Type of antenna: PCB antenna  
 Antenna gain: 0 dBi (for BLE, ANT+) 、 8 dBi (for 24 GHz)

### Technical data

Mode	Channel(Frequency)	Conducted Power (dBm)
BLE	Ch 0 : 2402 MHz	-0.10
	Ch 19 : 2440 MHz	-0.18
	Ch 39 : 2480 MHz	-0.10
ANT+	2457 MHz	-0.43

Mode	Frequency	Field Strength (dBuV/m)
24 GHz	24.2 GHz	99.8

Operation modes: Duplex  
 Modulation type: GFSK (for BLE, ANT+)  
 FMCW (for 24 GHz)

Sample no.: #01

Special statement: ./.

### Classification:

Fixed Device	<input type="checkbox"/>
Mobile Device (Human Body distance > 20cm)	<input checked="" type="checkbox"/>
Portable Device (Human Body distance < 20cm)	<input type="checkbox"/>



Registration number: W6M22206-21912-EE  
 FCC ID: YDM-DE2201

## 1.5 Power setting


Modulation mode	Channel		
	Ch 0 : 2402 MHz	Ch 19 : 2440 MHz	Ch 39 : 2480 MHz
1Mbps	0	0	0

## 1.6 Duty cycle and factor

The duty factor is computed as  $[10 \log (1 / D)]$ , where D is the duty cycle.

Mode	T <sub>on</sub> (ms)	T <sub>on</sub> +T <sub>off</sub> (ms)	Duty cycle (%)	1/T - VBW (kHz)
BLE	0.413	0.629	65.66%	2.42
ANT+	1.091	1.181	92.38%	0.92


### Duty cycle plot BLE



Date: 15.DEC.2022 14:47:06




Registration number: W6M22206-21912-EE  
FCC ID: YDM-DE2201



Date: 15.DEC.2022 14:52:31


ANT+



Date: 16.DEC.2022 17:39:10



Registration number: W6M22206-21912-EE  
FCC ID: YDM-DE2201




Date: 16.DEC.2022 17:34:49

## 1.7 Test standards

47 CFR PART 15 SUBPART C § 15.247 (2021-10)





Registration number: W6M22206-21912-EE

FCC ID: YDM-DE2201

**2 Test configuration**

**2.1 Test environment**

Relative humidity content: 20 ... 75 %

Air pressure: 86 ... 103 kPa

Extreme conditions parameters: ./.

**2.2 Measurement uncertainty**

Test item Name	Uncertainty
Estimation Result of Uncertainty of Conducted Output Power Measurement (Peak Output Power (transmitter))	Expanded Uncertainty : 1.48 dB

The decision rule is: Measurement uncertainty is not included in the calculation of test results.

**2.3 Test Equipment List**

**RF Conducted**

No.	Test equipment	Type	Serial No.	Manufacturer	Cal. Date	Next Cal. Date
ETSTW-CE 009	TEMP.&HUMIDITY CHAMBER	GTH-225-40-1P-U	MAA0305-009	GIANT FORCE	2022/8/3	2023/8/2
ETSTW-RE 050	Attenuator 10dB	50HF-010-1	None	JFW	2022/2/18	2023/2/17
ETSTW-RE 051	Attenuator 6dB	50HF-006-1	None	JFW	2022/2/18	2023/2/17
ETSTW-RE 053	Attenuator 3dB	50HF-003-1	None	JFW	2022/2/18	2023/2/17
ETSTW-RE 055	SPECTRUM ANALYZER	FSU 26	200074	R&S	2022/3/28	2023/3/27
ETSTW-RE 060	Attenuator 30dB	5015-30	F651012z-01	ATM	2022/2/18	2023/2/17
ETSTW-RE 099	DC Block	50DB-007-1	None	JFW	2022/2/18	2023/2/17
ETSTW-RE 112	AC POWER SOURCE	TFC-1005	T-0A023536	T-Power	Function test	
ETSTW-RE 127	RF Switch Box	RFS-01	None	WTS	2022/2/18	2023/2/17
ETSTW-RE 153	Signal Analyzer	FSV40	101929	R&S	2022/10/3	2023/10/2
ETSTW-GSM 023	Power Divider	4901.19.A	None	SUHNER	2022/9/2	2023/9/1
ETSTW-Cable 027	Microwave Cable	SUCOFLEX 104	279083	HUBER+SUHNER	2022/5/6	2023/5/5
ETSTW-Cable 030	Microwave Cable	SUCOFLEX 104 (S_Cable 9)	279067	HUBER+SUHNER	2022/2/18	2023/2/17
ETSTW-Cable 045	Microwave Cable	SUCOFLEX 104	325536	HUBER+SUHNER	2022/10/21	2023/10/20
ETSTW-Cable 058	Microwave Cable	SUCOFLEX 104	none	HUBER+SUHNER	2022/5/27	2023/5/26
WTSTW-SW 008	Signal studio	Agilent	None	AUDIX	Version 2.0.0.1	



Registration number: W6M22206-21912-EE

FCC ID: YDM-DE2201

**3 Equivalent Isotropic Radiated Power (EIRP)**

FCC Rule: 15.247

EIRP = max. conducted output power + antenna gain

BLE

$EIRP = -0.10 \text{ dBm} + (0 \text{ dBi [antenna gain claimed by manufacturer]}) = -0.10 \text{ dBm} = 0.9772 \text{ mW}$

ANT+

$EIRP = -0.43 \text{ dBm} + (0 \text{ dBi [antenna gain claimed by manufacturer]}) = -0.43 \text{ dBm} = 0.9057 \text{ mW}$

24G

$EIRP = 99.8 \text{ dBuV/m} (= -7.2 \text{ dBm}) + (8 \text{ dBi [antenna gain claimed by manufacturer]}) = 0.8 \text{ dBm} = 1.2023 \text{ mW}$

**3.1 Exemption Limits for Routine Evaluation**

**according to 47 CFR FCC Part 2 Subpart J, section 2.1091**

FCC OET Bulletin 65 Edition 97.01 determines the equations for predicting RF fields and applicable limits.

The prediction for power density in the far-field but will over-predict power density in the near field, where it could be used for walking a “worst case” or conservative prediction.

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 20 cm normally can be maintained between the user and the device.

**MPE Calculation Method**

**(A) Limits for Occupational/Controlled Exposure**

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f <sup>2</sup> )*	6
30-300	61.4	0.163	1.0	6
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6

**(B) Limits for General Population/Uncontrolled Exposure**

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	f/1500	30
1500-100,000	--	--	1.0	30

f = frequency in MHz

\*Plane-wave equivalent power density



Registration number: W6M22206-21912-EE

FCC ID: YDM-DE2201

E = Electric field (V/m) P = output power (W) G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

mW/cm<sup>2</sup>.

BLE

Established separation distance is 20 cm.

Operating frequency band: 2402-2480 MHz

The product meets RF exposure requirement.

Because the power density of 0.0002 mW/cm<sup>2</sup> at 2480 MHz is below the power density limit of 1 mW/cm<sup>2</sup>.

ANT+

Established separation distance is 20 cm.

Operating frequency band: 2402-2480 MHz

The product meets RF exposure requirement.

Because the power density of 0.0002 mW/cm<sup>2</sup> at 2457 MHz is below the power density limit of 1 mW/cm<sup>2</sup>.

24G

Established separation distance is 20 cm.

Operating frequency band: 24.15-24.25 GHz

The product meets RF exposure requirement.

Because the power density of 0.0003 mW/cm<sup>2</sup> at 24.2 GHz is below the power density limit of 1 mW/cm<sup>2</sup>.