

# FCC RADIO TEST REPORT

according to

47 CFR FCC Part 15 Subpart C § 15.247

**Equipment** : Web Pad  
**Model No.** : DT390XX (X: Blank or A~Z)  
**Brand Name** : DTR  
**Filing Type** : New Application  
**Applicant** : DT Research Inc.  
6F,NO.1 ,NingPo E. St., Taipei, 100 Taiwan, R.O.C.  
**FCC ID** : YE3DT390  
**Manufacturer** : DT Research Inc.  
6F,NO.1 ,NingPo E. St., Taipei, 100 Taiwan, R.O.C.  
**Received Date** : May 18, 2010  
**Final Test Date** : Jun. 02, 2010

## Statement

**Test result included is only for the Bluetooth part of the product.**

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.4-2003** and **47 CFR FCC Part 15 Subpart C**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



**SPORTON International Inc.**

No.52 Hwa Ya 1<sup>st</sup> Rd, Hwa Ya Technology Park, Kwei-Shan Hsiang, Taoyuan Hsien, Taiwan, R.O.C.

**Table of Contents**

**1 SUMMARY OF THE TEST RESULT ..... 2**

**2 GENERAL INFORMATION..... 3**

2.1 Product Details ..... 3

2.2 Accessories ..... 3

2.3 Table for Filed Antenna ..... 3

2.4 Table for Carrier Frequencies ..... 3

2.5 Table for Test Modes ..... 4

2.6 Table for Testing Locations ..... 4

2.7 Table for Supporting Units..... 4

2.8 Table for Parameters of Test Software Setting ..... 5

2.9 EUT Operation during Test ..... 5

2.10 Test Configurations ..... 6

**3 TEST RESULT ..... 8**

3.1 AC Power Line Conducted Emissions Measurement..... 8

3.2 Maximum Peak Output Power Measurement..... 12

3.3 Hopping Channel Separation Measurement ..... 14

3.4 Number of Hopping Frequency Measurement ..... 19

3.5 Dwell Time Measurement..... 21

3.6 Radiated Emissions Measurement..... 28

3.7 Band Edge and Fundamental Emissions Measurement ..... 40

3.8 Antenna Requirements..... 45

**4 LIST OF MEASURING EQUIPMENTS ..... 46**

**5 TEST LOCATION..... 48**

**6 TAF CERTIFICATE OF ACCREDITATION ..... 49**

**APPENDIX A. TEST PHOTOS ..... A1 ~ A6**

**APPENDIX B. PHOTOGRAPHS OF EUT ..... B1 ~ B42**

### History of This Test Report

Original Issue Date: Jun. 03, 2010

Report No.: FR051151

No additional attachment.

Additional attachment were issued as following record:

| Attachment No. | Issue Date | Description |
|----------------|------------|-------------|
|                |            |             |
|                |            |             |
|                |            |             |
|                |            |             |
|                |            |             |
|                |            |             |
|                |            |             |
|                |            |             |
|                |            |             |
|                |            |             |
|                |            |             |
|                |            |             |
|                |            |             |
|                |            |             |
|                |            |             |

# CERTIFICATE OF COMPLIANCE

according to

47 CFR FCC Part 15 Subpart C § 15.247

Equipment : Web Pad  
Model No. : DT390XX (X: Blank or A~Z)  
Brand Name : DTR  
Applicant : DT Research Inc.  
6F,NO.1 ,NingPo E. St., Taipei, 100  
Taiwan, R.O.C.

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on May 18, 2010 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.



Wayne Hsu / Vice Manager

## **SPORTON International Inc.**

No.52 Hwa Ya 1<sup>st</sup> Rd, Hwa Ya Technology Park, Kwei-Shan Hsiang, Taoyuan Hsien, Taiwan, R.O.C.

**1 SUMMARY OF THE TEST RESULT**

| Applied Standard: 47 CFR FCC Part 15 Subpart C |              |                                     |          |             |
|--|--------------|-------------------------------------|----------|-------------|
| Part   | Rule Section | Description of Test                 | Result   | Under Limit |
| 3.1  | 15.207       | AC Power Line Conducted Emissions   | Complies | 7.53 dB     |
| 3.2  | 15.247(b)(1) | Maximum Peak Conducted Output Power | Complies | 30.28 dB    |
| 3.3  | 15.247(a)(1) | Hopping Channel Separation          | Complies | -           |
| 3.4  | 15.247(b)(1) | Number of Hopping Frequency         | Complies | -           |
| 3.5  | 15.247(a)(1) | Dwell Time                          | Complies | -           |
| 3.6  | 15.247(d)    | Radiated Emissions                  | Complies | 3.05 dB     |
| 3.7  | 15.247(d)    | Band Edge Emissions                 | Complies | 1.72 dB     |
| 3.8  | 15.203       | Antenna Requirements                | Complies | -           |

| Test Items                                  | Uncertainty           | Remark                   |
|---|-----------------------|--------------------------|
| AC Power Line Conducted Emissions           | ±2.3dB                | Confidence levels of 95% |
| Maximum Peak Conducted Output Power         | ±0.8dB                | Confidence levels of 95% |
| Hopping Channel Separation                  | ±8.5×10 <sup>-8</sup> | Confidence levels of 95% |
| Radiated Emissions (9kHz~30MHz)             | ±0.8dB                | Confidence levels of 95% |
| Radiated Emissions (30MHz~1000MHz)          | ±1.9dB                | Confidence levels of 95% |
| Radiated / Band Edge Emissions (1GHz~18GHz) | ±1.9dB                | Confidence levels of 95% |
| Radiated Emissions (18GHz~40GHz)            | ±1.9dB                | Confidence levels of 95% |
| Temperature                                 | ±0.7                  | Confidence levels of 95% |
| Humidity                                    | ±3.2%                 | Confidence levels of 95% |
| DC / AC Power Source                        | ±1.4%                 | Confidence levels of 95% |

## 2 GENERAL INFORMATION

### 2.1 Product Details

Only the radio detail of Bluetooth is shown in this report. For more detailed features description, please refer to the manufacturer's specifications or user's manual.

| Items                    | Description                                   |
|--------------------------|---|
| Power Type               | 19V from adapter ; 7.4VDC from Li-ion Battery |
| Modulation               | FHSS (GFSK/ $\pi/4$ -DQPSK/ 8DPSK)            |
| Data Rate (Mbps)         | GFSK: 1/ $\pi/4$ -DQPSK: 2/ 8DPSK: 3          |
| Frequency Range          | 2400 ~ 2483.5MHz                              |
| Channel Number           | 79  |
| Channel Band Width (99%) | 1.212 MHz                                     |
| Conducted Output Power   | -0.28 dBm                                     |

### 2.2 Accessories

| Power          | Brand     | Model        | Rating  |
|----------------|-----------|--------------|---|
| AC Adapter     | EDACPOWER | EA10402H-190 | INPUT : 100V-240V~1.0A, 50-60Hz<br>OUTPUT : 19V 2.36A |
| Li-ion Battery | -         | ACC-006-18   | 7.4VDC, 3760mAh, 27.8Wh                               |
| Other          |           |              |   |
| Cradle         |           |              |   |

### 2.3 Table for Filed Antenna

| Ant. | Antenna Type | Connector      | Gain (dBi) |
|------|--------------|----------------|------------|
| A    | Chip Antenna | Fixed on Board | 1.30       |

### 2.4 Table for Carrier Frequencies

| Frequency Band | Channel No. | Frequency |
|----------------|-------------|-----------|
| 2400~2483.5MHz | 0           | 2402 MHz  |
|                | 1           | 2403 MHz  |
|                | :           | :         |
|                | 38          | 2440 MHz  |
|                | 39          | 2441 MHz  |
|                | 40          | 2442 MHz  |
|                | :           | :         |
|                | 77          | 2479 MHz  |
|                | 78          | 2480 MHz  |

**2.5 Table for Test Modes**

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

| Test Items                    | Mode                        | Data Rate                 | Channel             |
|-------------------------------|-----------------------------|---------------------------|---------------------|
| AC Power Conducted Emissions  | Normal Mode                 | Auto                      | -                   |
| Max. Conducted Output Power   | GFSK/ $\pi$ /4-DQPSK/ 8DPSK | 1 Mbps/ 2 Mbps/<br>3 Mbps | 0/39/78             |
| Hopping Channel Separation    | 8DPSK                       | 3 Mbps                    | 0~1/39~40/77<br>~78 |
| Number of Hopping Frequency   | 8DPSK                       | 3 Mbps                    | 0~78                |
| Dwell Time                    | DH1/DH3/DH5                 | 3 Mbps                    | 0/39/78             |
| Radiated Emissions Below 1GHz | Normal Mode                 | Auto                      | -                   |
| Radiated Emissions Above 1GHz | GFSK                        | 1 Mbps                    | 0/39/78             |
| Fundamental Emissions         | GFSK/ $\pi$ /4-DQPSK/ 8DPSK | 1 Mbps/ 2 Mbps/<br>3 Mbps | 0/39/78             |
| Band Edge Emissions           | 8DPSK                       | 3 Mbps                    | 0/78                |

**2.6 Table for Testing Locations**

| Test Site No. | Site Category | Location | FCC Reg. No. | IC File No. |
|---------------|---------------|----------|--------------|-------------|
| CO01-HY       | Conduction    | Hwa Ya   | 643075       | IC 4086C    |
| TH01-HY       | OVEN Room     | Hwa Ya   | -            | -           |
| 03CH03-HY     | SAC           | Hwa Ya   | 643075       | IC 4086B    |

Semi Anechoic Chamber (SAC).

**2.7 Table for Supporting Units**

| Support Unit                     | Brand  | Model    | FCC ID | Remark    |
|----------------------------------|--------|----------|--------|-----------|
| iPod nano x3                     | Apple  | A1199    | N/A    | Conducted |
| Headset                          | HAMA   | -        | N/A    |           |
| Notebook<br>(Remote Workstation) | DELL   | D505     | DoC    |           |
| AP<br>(Remote Workstation)       | EDIMAX | BR2604WG | DoC    |           |

Note: The EUT was tested alone only for radiated emissions tested.

**2.8 Table for Parameters of Test Software Setting**

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

**Power Parameters of Bluetooth**

| <b>Test Software Version</b> | <b>Blue Test</b> |          |          |
|------------------------------|------------------|----------|----------|
| Frequency                    | 2402 MHz         | 2441 MHz | 2480 MHz |
| Power Parameters ( 1Mbps )   | 63               | 63       | 63       |
| Power Parameters ( 2Mbps )   | 120              | 120      | 120      |
| Power Parameters ( 3Mbps )   | 160              | 160      | 160      |

**2.9 EUT Operation during Test**

Conducted Emissions:

An executive program, "EMCTEST.EXE" under WIN XP, which generates a complete line of continuously repeating "H" pattern was used as the test software.

The program was executed as follows :

- a. Turn on the power of all equipment.
- b. The NB reads the test program from the hard disk drive and runs it.
- c. The NB sends "H" messages to the panel and the displays "H" patterns on the screen.
- d. The NB sends messages to the modem.
- e. The NB sends "H" messages to the internal hard disk, and the hard disk reads and writes the message.
- f. Repeat the steps from c to f.

At the same time, the following programs were executed:

- Executed "Winthrx.exe" to read/write data from internal Hard Disk and iPod.
- Executed "Media player.exe" to play audio and video.
- Executed "Wireless" to link with the remote workstation to receive and transmit data by AP.

Radiated Emissions:


- Executed "Blue Test" to keep transmitting signals at fixed frequency.




## 2.10 Test Configurations

### 2.10.1 Radiation Emissions Test Configuration

For radiated emissions 9kHz~1GHz



**For radiated emissions above 1GHz**



### 3 TEST RESULT

#### 3.1 AC Power Line Conducted Emissions Measurement

##### 3.1.1 Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

**Class B**

| Frequency (MHz) | QP Limit (dBuV) | AV Limit (dBuV) |
|-----------------|-----------------|-----------------|
| 0.15~0.5        | 66~56           | 56~46           |
| 0.5~5           | 56              | 46              |
| 5~30            | 60              | 50              |

##### 3.1.2 Measuring Instruments and Setting


Please refer to section 4 of equipments list in this report. The following table is the setting of the receiver.

| Receiver Parameters | Setting  |
|---------------------|----------|
| Attenuation         | 10 dB    |
| Start Frequency     | 0.15 MHz |
| Stop Frequency      | 30 MHz   |
| IF Bandwidth        | 9 KHz    |

##### 3.1.3 Test Procedures

1. The EUT warm up about 15 minutes then start test.
2. Configure the EUT according to ANSI C63.4. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
3. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
4. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
5. The frequency range from 150 KHz to 30 MHz was searched.
6. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
7. The measurement has to be done between each power line and ground at the power terminal.

3.1.4 Test Setup Layout



LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω. LISN can be placed on top of, or immediately beneath, reference ground plane.
- (3.1) All other equipment powered from additional LISN(s).
- (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
- (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

3.1.5 Test Deviation

There is no deviation with the original standard.


**3.1.6 EUT Operation during Test**

The EUT was placed on the test table and programmed in normal function.

**3.1.7 Results of AC Power Line Conducted Emissions Measurement**


|                        |              |                      |             |
|------------------------|--------------|----------------------|-------------|
| <b>Final Test Date</b> | May 27, 2010 | <b>Test Site No.</b> | CO01-HY     |
| <b>Temperature</b>     | 27.9         | <b>Humidity</b>      | 56%         |
| <b>Test Engineer</b>   | Ace          | <b>Configuration</b> | Normal Mode |

*Line*



|    | Freq   | Level | Over Limit | Limit Line | Read Level | Probe Factor | Cable Loss | Remark  |
|----|--------|-------|------------|------------|------------|--------------|------------|---------|
|    | MHz    | dBuV  | dB         | dBuV       | dBuV       | dB           | dB         |         |
| 1  | 0.200  | 56.08 | -7.53      | 63.61      | 55.94      | 0.08         | 0.06       | QP      |
| 2  | 0.200  | 42.89 | -10.72     | 53.61      | 42.75      | 0.08         | 0.06       | Average |
| 3  | 0.315  | 45.75 | -14.10     | 59.85      | 45.59      | 0.09         | 0.07       | QP      |
| 4  | 0.315  | 32.83 | -17.02     | 49.85      | 32.67      | 0.09         | 0.07       | Average |
| 5  | 0.524  | 44.24 | -11.76     | 56.00      | 44.05      | 0.10         | 0.09       | QP      |
| 6  | 0.524  | 32.25 | -13.75     | 46.00      | 32.06      | 0.10         | 0.09       | Average |
| 7  | 0.672  | 41.38 | -14.62     | 56.00      | 41.17      | 0.10         | 0.11       | QP      |
| 8  | 0.672  | 22.65 | -23.35     | 46.00      | 22.44      | 0.10         | 0.11       | Average |
| 9  | 4.635  | 41.20 | -14.80     | 56.00      | 40.85      | 0.19         | 0.16       | QP      |
| 10 | 4.635  | 26.41 | -19.59     | 46.00      | 26.06      | 0.19         | 0.16       | Average |
| 11 | 19.240 | 39.98 | -20.02     | 60.00      | 39.26      | 0.40         | 0.32       | QP      |
| 12 | 19.240 | 31.89 | -18.11     | 50.00      | 31.17      | 0.40         | 0.32       | Average |

Neutral



|    | Freq   | Level | Over Limit | Limit Line | Read Level | Probe Factor | Cable Loss | Remark  |
|----|--------|-------|------------|------------|------------|--------------|------------|---------|
|    | MHz    | dBuV  | dB         | dBuV       | dBuV       | dB           | dB         |         |
| 1  | 0.200  | 55.84 | -7.77      | 63.61      | 55.72      | 0.06         | 0.06       | QP      |
| 2  | 0.200  | 40.86 | -12.75     | 53.61      | 40.74      | 0.06         | 0.06       | Average |
| 3  | 0.302  | 46.28 | -13.91     | 60.19      | 46.14      | 0.07         | 0.07       | QP      |
| 4  | 0.302  | 32.16 | -18.03     | 50.19      | 32.02      | 0.07         | 0.07       | Average |
| 5  | 0.398  | 38.29 | -19.61     | 57.90      | 38.15      | 0.07         | 0.07       | QP      |
| 6  | 0.398  | 25.38 | -22.52     | 47.90      | 25.24      | 0.07         | 0.07       | Average |
| 7  | 0.523  | 40.95 | -15.05     | 56.00      | 40.78      | 0.08         | 0.09       | QP      |
| 8  | 0.523  | 30.04 | -15.96     | 46.00      | 29.87      | 0.08         | 0.09       | Average |
| 9  | 0.630  | 37.28 | -18.72     | 56.00      | 37.10      | 0.08         | 0.10       | QP      |
| 10 | 0.630  | 21.47 | -24.53     | 46.00      | 21.29      | 0.08         | 0.10       | Average |
| 11 | 18.720 | 40.58 | -19.42     | 60.00      | 39.85      | 0.41         | 0.32       | QP      |
| 12 | 18.720 | 32.15 | -17.85     | 50.00      | 31.42      | 0.41         | 0.32       | Average |

Note:

Level = Read Level + LISN Factor + Cable Loss.

**3.2 Maximum Peak Output Power Measurement**

**3.2.1 Limit**

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, the limit for peak output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceeds 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

**3.2.2 Measuring Instruments and Setting**


Please refer to section 4 of equipments list in this report. The following table is the setting of the power meter.

| <b>Power Meter Parameter</b> | <b>Setting</b>     |
|------------------------------|--------------------|
| Filter No.                   | Auto               |
| Measurement time             | 0.135 s ~ 26 s     |
| Used Peak Sensor             | NRV-Z32 (model 04) |

**3.2.3 Test Procedures**

1. The transmitter output (antenna port) was connected to the power meter.
2. Turn on the EUT and power meter and then record the peak power value.
3. Repeat above procedures on all channels needed to be tested.

**3.2.4 Test Setup Layout**



**3.2.5 Test Deviation**

There is no deviation with the original standard.

**3.2.6 EUT Operation during Test**

The EUT was programmed to be in continuously transmitting mode.

**3.2.7 Test Result of Maximum Peak Output Power**

|                        |               |                       |                          |
|------------------------|---------------|-----------------------|--------------------------|
| <b>Final Test Date</b> | Jun. 01, 2010 | <b>Test Site No.</b>  | TH01-HY                  |
| <b>Temperature</b>     | 25            | <b>Humidity</b>       | 61%                      |
| <b>Test Engineer</b>   | Ian           | <b>Configurations</b> | GFSK / π/4-DQPSK / 8DPSK |

**1Mbps**

| Channel | Frequency | Conducted Power (dBm) | Max. Limit (dBm) | Result          |
|---------|-----------|-----------------------|------------------|-----------------|
| 0       | 2402 MHz  | -0.28                 | 30.00            | <b>Complies</b> |
| 39      | 2441 MHz  | -1.46                 | 30.00            | <b>Complies</b> |
| 78      | 2480 MHz  | -2.26                 | 30.00            | <b>Complies</b> |

**2Mbps**

| Channel | Frequency | Conducted Power (dBm) | Max. Limit (dBm) | Result          |
|---------|-----------|-----------------------|------------------|-----------------|
| 0       | 2402 MHz  | -0.89                 | 30.00            | <b>Complies</b> |
| 39      | 2441 MHz  | -2.23                 | 30.00            | <b>Complies</b> |
| 78      | 2480 MHz  | -3.26                 | 30.00            | <b>Complies</b> |

**3Mbps**

| Channel | Frequency | Conducted Power (dBm) | Max. Limit (dBm) | Result          |
|---------|-----------|-----------------------|------------------|-----------------|
| 0       | 2402 MHz  | -0.90                 | 30.00            | <b>Complies</b> |
| 39      | 2441 MHz  | -2.29                 | 30.00            | <b>Complies</b> |
| 78      | 2480 MHz  | -3.21                 | 30.00            | <b>Complies</b> |



**3.3 Hopping Channel Separation Measurement**

**3.3.1 Limit**

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

**3.3.2 Measuring Instruments and Setting**


Please refer to section 4 of equipments list in this report. The following table is the setting of spectrum analyzer.

| Spectrum Parameter | Setting   |
|--------------------|---|
| Attenuation        | Auto  |
| Span Frequency     | > Measurement Bandwidth or Channel Separation           |
| RB                 | 100 kHz (20dB Bandwidth) / 100 kHz (Channel Separation) |
| VB                 | 100 kHz (20dB Bandwidth) / 100 kHz (Channel Separation) |
| Detector           | Peak  |
| Trace              | Max Hold  |
| Sweep Time         | Auto  |

**3.3.3 Test Procedures**

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. The resolution bandwidth of 100 kHz and the video bandwidth of 100 kHz were utilized for 20 dB bandwidth measurement.
3. The resolution bandwidth of 100 kHz and the video bandwidth of 100 kHz were utilized for channel separation measurement.

**3.3.4 Test Setup Layout**



**3.3.5 Test Deviation**

There is no deviation with the original standard.

**3.3.6 EUT Operation during Test**

The EUT was programmed to be in continuously transmitting mode.


**3.3.7 Test Result of Hopping Channel Separation**

|                        |               |                       |         |
|------------------------|---------------|-----------------------|---------|
| <b>Final Test Date</b> | Jun. 01, 2010 | <b>Test Site No.</b>  | TH01-HY |
| <b>Temperature</b>     | 25            | <b>Humidity</b>       | 61%     |
| <b>Test Engineer</b>   | Ian           | <b>Configurations</b> | 8DPSK   |

| <b>Frequency</b> | <b>Ch. Separation (MHz)</b> | <b>20dB Bandwidth (MHz)</b> | <b>99% Occupied Bandwidth (MHz)</b> | <b>Result</b>   |
|------------------|-----------------------------|-----------------------------|-------------------------------------|-----------------|
| 2402 MHz         | 1.000                       | 1.380                       | 1.212                               | <b>Complies</b> |
| 2441 MHz         | 1.000                       | 1.368                       | 1.196                               | <b>Complies</b> |
| 2480 MHz         | 1.000                       | 1.368                       | 1.204                               | <b>Complies</b> |


**Ch. Separation Limits: >2/3 of 20dB bandwidth**

20 dB Bandwidth Plot on Channel 0 / 2402 MHz




Date: 31.MAY.2010 22:30:53

20 dB Bandwidth Plot on Channel 39 / 2441 MHz




Date: 31.MAY.2010 22:32:40

20 dB Bandwidth Plot on Channel 78 / 2480 MHz




Date: 31.MAY.2010 22:29:03

Channel Separation Plot on Channel 0~1 / 2402 MHz ~ 2403 MHz




Date: 1.JUN.2010 09:14:03

Channel Separation Plot on Channel 39~40 / 2441 MHz ~ 2442 MHz



Date: 1.JUN.2010 09:16:59

Channel Separation Plot on Channel 77~78 / 2479 MHz ~ 2480 MHz



Date: 1.JUN.2010 09:19:50

**3.4 Number of Hopping Frequency Measurement**

**3.4.1 Limit**

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels.

**3.4.2 Measuring Instruments and Setting**


Please refer to section 4 of equipments list in this report. The following table is the setting of spectrum analyzer.

| Spectrum Parameters | Setting                     |
|---------------------|-----------------------------|
| Attenuation         | Auto                        |
| Span Frequency      | > Operating Frequency Range |
| RB                  | 100 kHz                     |
| VB                  | 100 kHz                     |
| Detector            | Peak                        |
| Trace               | Max Hold                    |
| Sweep Time          | Auto                        |

**3.4.3 Test Procedures**

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. The resolution bandwidth of 100 kHz and the video bandwidth of 100 kHz were utilized.
3. Observe frequency hopping in 2400MHz~2483.5MHz, there are at least 75 non-overlapping channels.

**3.4.4 Test Setup Layout**



**3.4.5 Test Deviation**

There is no deviation with the original standard.

**3.4.6 EUT Operation during Test**


The EUT was programmed to be in continuously transmitting mode.

3.4.7 Test Result of Number of Hopping Frequency

|                        |              |                       |         |
|------------------------|--------------|-----------------------|---------|
| <b>Final Test Date</b> | May 31, 2010 | <b>Test Site No.</b>  | TH01-HY |
| <b>Temperature</b>     | 25           | <b>Humidity</b>       | 61%     |
| <b>Test Engineer</b>   | Ian          | <b>Configurations</b> | 8DPSK   |

| Modulation Type | Channel No. | Frequency (MHz) | Hopping Ch. (Channels) | Min. Limit (Channels) | Test Result |
|-----------------|-------------|-----------------|------------------------|-----------------------|-------------|
| 8DPSK           | 0 ~ 78      | 2402 ~ 2480     | 79                     | 75                    | Complies    |

Number of Hopping Channel Plot on Channel 0~78 / 2402 MHz ~ 2480 MHz



Date: 31.MAY.2010 23:08:40

**3.5 Dwell Time Measurement**

**3.5.1 Limit**

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

**3.5.2 Measuring Instruments and Setting**

Please refer to section 4 of equipments list in this report. The following table is the setting of spectrum analyzer.


| Spectrum Parameter | Setting        |
|--------------------|----------------|
| Attenuation        | Auto           |
| Span Frequency     | 0 MHz          |
| RB                 | 1 MHz          |
| VB                 | 1 MHz          |
| Detector           | Peak           |
| Trace              | Single Trigger |

**3.5.3 Test Procedures**

1. The transmitter output (antenna port) was connected to the spectrum analyzer
2. Set RBW of spectrum analyzer to 1MHz and VBW to 1MHz.
3. Use a video trigger with the trigger level set to enable triggering only on full pulses.
4. Sweep Time is more than once pulse time.
5. Set the center frequency on any frequency would be measure and set the frequency span to zero span.
6. Measure the maximum time duration of one single pulse.
7. Set the EUT for DH5, DH3 and DH1 packet transmitting.
8. Measure the maximum time duration of one single pulse.
9. DH5 Packet permit maximum  $1600 / 79 / 6 = 3.37$  hops per second in each channel (5 time slots RX, 1 time slot TX). So, the dwell time is the time duration of the pulse times  $3.37 \times 31.6 = 106.6$  within 31.6 seconds
10. DH3 Packet permit maximum  $1600 / 79 / 4 = 5.06$  hops per second in each channel (3 time slots RX, 1 time slot TX). So, the dwell time is the time duration of the pulse times  $5.06 \times 31.6 = 160$  within 31.6 seconds.
11. DH1 Packet permit maximum  $1600 / 79 / 2 = 10.12$  hops per second in each channel (1 time slot RX, 1 time slot TX). So, the dwell time is the time duration of the pulse times  $10.12 \times 31.6 = 320$  within 31.6 seconds.



**3.5.4 Test Setup Layout**



**3.5.5 Test Deviation**

There is no deviation with the original standard.

**3.5.6 EUT Operation during Test**


The EUT was programmed to be in continuously transmitting mode.

**3.5.7 Test Result of Dwell Time**

|                        |              |                       |                         |
|------------------------|--------------|-----------------------|-------------------------|
| <b>Final Test Date</b> | May 31, 2010 | <b>Test Site No.</b>  | TH01-HY                 |
| <b>Temperature</b>     | 25           | <b>Humidity</b>       | 61%                     |
| <b>Test Engineer</b>   | Ian          | <b>Configurations</b> | 8DPSK<br>3DH1/3DH3/3DH5 |


| Data Packet | Frequency | Pulse Duration (ms) | Dwell Time (s) | Limits (s) | Test Result     |
|-------------|-----------|---------------------|----------------|------------|-----------------|
| DH5         | 2402 MHz  | 3.0800              | 0.3285         | 0.4000     | <b>Complies</b> |
| DH3         | 2402 MHz  | 1.8400              | 0.2944         | 0.4000     | <b>Complies</b> |
| DH1         | 2402 MHz  | 0.5600              | 0.1792         | 0.4000     | <b>Complies</b> |
| DH5         | 2441 MHz  | 3.0800              | 0.3285         | 0.4000     | <b>Complies</b> |
| DH3         | 2441 MHz  | 1.8800              | 0.3008         | 0.4000     | <b>Complies</b> |
| DH1         | 2441 MHz  | 0.5800              | 0.1856         | 0.4000     | <b>Complies</b> |
| DH5         | 2480 MHz  | 3.0800              | 0.3285         | 0.4000     | <b>Complies</b> |
| DH3         | 2480 MHz  | 1.8200              | 0.2912         | 0.4000     | <b>Complies</b> |
| DH1         | 2480 MHz  | 0.5600              | 0.1792         | 0.4000     | <b>Complies</b> |

DH5 Dwell Time Plot on Channel 0 / 2402 MHz




Date: 31.MAY.2010 22:55:47

DH3 Dwell Time Plot on Channel 0 / 2402 MHz




Date: 31.MAY.2010 22:52:15

DH1 Dwell Time Plot on Channel 0 / 2402 MHz




Date: 31.MAY.2010 22:41:48

DH5 Dwell Time Plot on Channel 39 / 2441 MHz




Date: 31.MAY.2010 22:56:57

DH3 Dwell Time Plot on Channel 39 / 2441 MHz




Date: 31.MAY.2010 22:50:15

DH1 Dwell Time Plot on Channel 39 / 2441 MHz




Date: 31.MAY.2010 22:43:37

DH5 Dwell Time Plot on Channel 78 / 2480 MHz




Date: 31.MAY.2010 22:58:18

DH3 Dwell Time Plot on Channel 78 / 2480 MHz



Date: 31.MAY.2010 22:48:37

DH1 Dwell Time Plot on Channel 78 / 2480 MHz



Date: 31.MAY.2010 22:45:46

**3.6 Radiated Emissions Measurement**

**3.6.1 Limit**

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

| <b>Frequencies (MHz)</b> | <b>Field Strength (micorvolts/meter)</b> | <b>Measurement Distance (meters)</b> |
|--------------------------|--|--------------------------------------|
| 0.009~0.490              | 2400/F(KHz)                              | 300                                  |
| 0.490~1.705              | 24000/F(KHz)                             | 30                                   |
| 1.705~30.0               | 30                                       | 30                                   |
| 30~88                    | 100                                      | 3                                    |
| 88~216                   | 150                                      | 3                                    |
| 216~960                  | 200                                      | 3                                    |
| Above 960                | 500                                      | 3                                    |

**3.6.2 Measuring Instruments and Setting**

Please refer to section 4 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

| <b>Spectrum Parameter</b>                 | <b>Setting</b>                                 |
|---|--|
| Attenuation                               | Auto   |
| Start Frequency                           | 1000 MHz                                       |
| Stop Frequency                            | 10th carrier harmonic                          |
| RB / VB (Emission in restricted band)     | 1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average |
| RB / VB (Emission in non-restricted band) | 1MHz / 1MHz for peak                           |

| <b>Receiver Parameter</b> | <b>Setting</b>                   |
|---------------------------|----------------------------------|
| Attenuation               | Auto                             |
| Start ~ Stop Frequency    | 9kHz~150kHz / RB 200Hz for QP    |
| Start ~ Stop Frequency    | 150kHz~30MHz / RB 9kHz for QP    |
| Start ~ Stop Frequency    | 30MHz~1000MHz / RB 120kHz for QP |


**3.6.3 Test Procedures**

1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.




3.6.4 Test Setup Layout

For radiated emissions below 30MHz



For radiated emissions above 30MHz



Above 10 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.

Distance extrapolation factor =  $20 \log (\text{specific distance [3m]} / \text{test distance [1m]})$  (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor [9.54 dB].

3.6.5 Test Deviation

There is no deviation with the original standard.

3.6.6 EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

**3.6.7 Results of Radiated Emissions (9kHz~30MHz)**

|                        |              |                      |           |
|------------------------|--------------|----------------------|-----------|
| <b>Final Test Date</b> | May 18, 2010 | <b>Test Site No.</b> | 03CH03-HY |
| <b>Temperature</b>     | 27.9         | <b>Humidity</b>      | 56%       |
| <b>Test Engineer</b>   | Eddie        |                      |           |

| <b>Freq. (MHz)</b> | <b>Level (dBuV)</b> | <b>Over Limit (dB)</b> | <b>Limit Line (dBuV)</b> | <b>Remark</b> |
|--------------------|---------------------|------------------------|--------------------------|---------------|
| -                  | -                   | -                      | -                        | See Note      |

Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.


Distance extrapolation factor =  $40 \log(\text{specific distance} / \text{test distance})$  (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

3.6.8 Results of Radiated Emissions (30MHz~1GHz)


|                        |              |                       |             |
|------------------------|--------------|-----------------------|-------------|
| <b>Final Test Date</b> | May 18, 2010 | <b>Test Site No.</b>  | 03CH03-HY   |
| <b>Temperature</b>     | 27.9         | <b>Humidity</b>       | 56%         |
| <b>Test Engineer</b>   | Eddie        | <b>Configurations</b> | Normal Mode |

Horizontal



|     | Freq    | Level  | Over Limit | Limit Line | ReadAntenna | Cable | Preamp | Ant   | Table | Remark |      |
|-----|---------|--------|------------|------------|-------------|-------|--------|-------|-------|--------|------|
|     | MHz     | dBuV/m | dB         | dBuV/m     | dBuV        | dB    | dB     | cm    | deg   |        |      |
| 1   | 175.500 | 36.05  | -7.45      | 43.50      | 50.15       | 9.88  | 3.30   | 27.28 | ---   | ---    | Peak |
| 2 @ | 238.550 | 42.95  | -3.05      | 46.00      | 53.24       | 12.62 | 3.96   | 26.87 | ---   | ---    | Peak |
| 3   | 312.270 | 40.90  | -5.10      | 46.00      | 49.37       | 13.90 | 4.52   | 26.89 | ---   | ---    | Peak |
| 4   | 498.510 | 41.27  | -4.73      | 46.00      | 46.04       | 17.26 | 6.15   | 28.18 | ---   | ---    | Peak |
| 5   | 614.910 | 35.91  | -10.09     | 46.00      | 36.71       | 19.98 | 7.36   | 28.15 | ---   | ---    | Peak |
| 6   | 719.670 | 35.64  | -10.36     | 46.00      | 37.00       | 19.13 | 7.47   | 27.95 | ---   | ---    | Peak |

Vertical



|   | Freq    | Level  | Over Limit | Limit Line | ReadAntenna Level | Antenna Factor | Cable Loss | Preamp Factor | Ant Pos | Table Pos | Remark |
|---|---------|--------|------------|------------|-------------------|----------------|------------|---------------|---------|-----------|--------|
|   | MHz     | dBuV/m | dB         | dBuV/m     | dBuV              | dB/m           | dB         | dB            | cm      | deg       |        |
| 1 | 39.700  | 32.60  | -7.40      | 40.00      | 46.13             | 13.25          | 1.02       | 27.80         | ---     | ---       | QP     |
| 2 | 238.550 | 40.44  | -5.56      | 46.00      | 50.73             | 12.62          | 3.96       | 26.87         | ---     | ---       | Peak   |
| 3 | 315.180 | 35.41  | -10.59     | 46.00      | 43.87             | 13.94          | 4.51       | 26.91         | ---     | ---       | Peak   |
| 4 | 498.510 | 39.24  | -6.76      | 46.00      | 44.01             | 17.26          | 6.15       | 28.18         | ---     | ---       | Peak   |
| 5 | 614.910 | 41.37  | -4.63      | 46.00      | 42.17             | 19.98          | 7.36       | 28.15         | ---     | ---       | Peak   |
| 6 | 715.790 | 42.78  | -3.22      | 46.00      | 42.78             | 0.00           | 0.00       | 0.00          | ---     | ---       | Peak   |

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.


Emission level (dBUV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

3.6.9 Results for Radiated Emissions (1GHz~10<sup>th</sup> Harmonic)

|                        |              |                       |           |
|------------------------|--------------|-----------------------|-----------|
| <b>Final Test Date</b> | May 19, 2010 | <b>Test Site No.</b>  | 03CH03-HY |
| <b>Temperature</b>     | 27.9         | <b>Humidity</b>       | 56%       |
| <b>Test Engineer</b>   | Eddie        | <b>Configurations</b> | Channel 0 |


Horizontal



|   | Freq     | Level  | Over Limit | Limit Line | ReadAntenna Level | Antenna Factor | Cable Loss | Preamp Factor | Ant Pos | Table Pos | Remark |
|---|----------|--------|------------|------------|-------------------|----------------|------------|---------------|---------|-----------|--------|
|   | MHz      | dBuV/m | dB         | dBuV/m     | dBuV              | dB/m           | dB         | dB            | cm      | deg       |        |
| 1 | 4804.000 | 47.93  | -6.07      | 54.00      | 44.37             | 33.12          | 2.70       | 32.25         | ---     | ---       | PK     |
| 2 | 7206.000 | 48.33  |            |            | 40.90             | 35.66          | 4.50       | 32.73         | ---     | ---       | PERK   |
| 3 | 9608.000 | 53.84  |            |            | 42.64             | 38.18          | 5.29       | 32.27         | ---     | ---       | PERK   |

Note: The items 2 and 3 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.7.7).

**Vertical**




|   | Freq     | Level  | Over Limit | Limit Line | ReadAntenna Level | Antenna Factor | Cable Loss | Preamp Factor | Ant Pos | Table Pos | Remark |
|---|----------|--------|------------|------------|-------------------|----------------|------------|---------------|---------|-----------|--------|
|   | MHz      | dBuV/m | dB         | dBuV/m     | dBuV              | dB/m           | dB         | dB            | cm      | deg       |        |
| 1 | 4808.000 | 47.02  | -6.98      | 54.00      | 43.46             | 33.12          | 2.70       | 32.25         | ---     | ---       | PK     |
| 2 | 7206.000 | 49.18  |            |            | 41.75             | 35.66          | 4.50       | 32.73         | ---     | ---       | PEAK   |
| 3 | 9608.000 | 53.42  |            |            | 42.22             | 38.18          | 5.29       | 32.27         | ---     | ---       | PEAK   |

Note: The items 2 and 3 are on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.7.7).

|                        |              |                       |            |
|------------------------|--------------|-----------------------|------------|
| <b>Final Test Date</b> | May 19, 2010 | <b>Test Site No.</b>  | 03CH03-HY  |
| <b>Temperature</b>     | 27.9         | <b>Humidity</b>       | 56%        |
| <b>Test Engineer</b>   | Eddie        | <b>Configurations</b> | Channel 39 |


**Horizontal**



|   | Freq     | Level  | Over Limit | Limit Line | ReadAntenna Level | Antenna Factor | Cable Loss | Preamp Factor | Ant Pos | Table Pos | Remark |
|---|----------|--------|------------|------------|-------------------|----------------|------------|---------------|---------|-----------|--------|
|   | MHz      | dBuV/m | dB         | dBuV/m     | dBuV              | dB/m           | dB         | dB            | cm      | deg       |        |
| 1 | 4884.000 | 48.64  | -5.36      | 54.00      | 45.11             | 33.26          | 2.60       | 32.33         | ---     | ---       | PK     |
| 2 | 7322.000 | 49.80  | -4.20      | 54.00      | 41.66             | 35.92          | 4.65       | 32.42         | ---     | ---       | PK     |
| 3 | 9764.000 | 54.16  |            |            | 42.77             | 38.32          | 5.42       | 32.35         | ---     | ---       | PEAK   |

Note: The item 3 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.7.7).

Vertical




|   | Freq     | Level  | Over Limit | Limit Line | ReadAntenna Level | Antenna Factor | Cable Loss | Preamp Factor | Ant Pos | Table Pos | Remark |
|---|----------|--------|------------|------------|-------------------|----------------|------------|---------------|---------|-----------|--------|
|   | MHz      | dBuV/m | dB         | dBuV/m     | dBuV              | dB/m           | dB         | dB            | cm      | deg       |        |
| 1 | 4884.000 | 48.58  | -5.42      | 54.00      | 45.05             | 33.26          | 2.60       | 32.33         | ---     | ---       | PK     |
| 2 | 7323.000 | 49.78  | -4.22      | 54.00      | 41.63             | 35.92          | 4.65       | 32.42         | ---     | ---       | PK     |
| 3 | 9764.000 | 53.77  |            |            | 42.37             | 38.32          | 5.42       | 32.35         | ---     | ---       | PEAK   |

Note: The item 3 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.7.7).



|                        |              |                       |            |
|------------------------|--------------|-----------------------|------------|
| <b>Final Test Date</b> | May 19, 2010 | <b>Test Site No.</b>  | 03CH03-HY  |
| <b>Temperature</b>     | 27.9         | <b>Humidity</b>       | 56%        |
| <b>Test Engineer</b>   | Eddie        | <b>Configurations</b> | Channel 78 |


**Horizontal**



|   | Freq     | Level  | Over Limit | Limit Line | ReadAntenna Level | Antenna Factor | Cable Loss | Preamp Factor | Ant Pos | Table Pos | Remark |
|---|----------|--------|------------|------------|-------------------|----------------|------------|---------------|---------|-----------|--------|
|   | MHz      | dBuV/m | dB         | dBuV/m     | dBuV              | dB/m           | dB         | dB            | cm      | deg       |        |
| 1 | 4964.000 | 47.42  | -6.58      | 54.00      | 43.88             | 33.43          | 2.51       | 32.40         | ---     | ---       | PK     |
| 2 | 7448.000 | 50.28  | -3.72      | 54.00      | 41.36             | 36.19          | 4.85       | 32.12         | ---     | ---       | PK     |
| 3 | 9920.000 | 54.35  |            |            | 42.78             | 38.44          | 5.55       | 32.42         | ---     | ---       | Peak   |

Note: The item 3 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.7.7).

Vertical



|   | Freq     | Level  | Over Limit | Limit Line | ReadAntenna Level | Antenna Factor | Cable Loss | Preamp Factor | Ant Pos | Table Pos | Remark |
|---|----------|--------|------------|------------|-------------------|----------------|------------|---------------|---------|-----------|--------|
|   | MHz      | dBuV/m | dB         | dBuV/m     | dBuV              | dB/m           | dB         | dB            | cm      | deg       |        |
| 1 | 4964.000 | 46.69  | -7.31      | 54.00      | 43.15             | 33.43          | 2.51       | 32.40         | ---     | ---       | PK     |
| 2 | 7440.000 | 50.29  | -3.71      | 54.00      | 41.43             | 36.19          | 4.80       | 32.12         | ---     | ---       | PK     |
| 3 | 9920.000 | 55.20  |            |            | 43.63             | 38.44          | 5.55       | 32.42         | ---     | ---       | PEAK   |

Note: The item 3 is on un-restricted band, so the limit is -20dB for the field strength of the fundamental emissions (see section 3.7.7).

The amplitude of spurious emissions, which are attenuated by more than 20dB below, the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

**3.7 Band Edge and Fundamental Emissions Measurement**

**3.7.1 Limit**

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

| <b>Frequencies (MHz)</b> | <b>Field Strength (micorvolts/meter)</b> | <b>Measurement Distance (meters)</b> |
|--------------------------|--|--------------------------------------|
| 0.009~0.490              | 2400/F(KHz)                              | 300                                  |
| 0.490~1.705              | 24000/F(KHz)                             | 30                                   |
| 1.705~30.0               | 30                                       | 30                                   |
| 30~88                    | 100                                      | 3                                    |
| 88~216                   | 150                                      | 3                                    |
| 216~960                  | 200                                      | 3                                    |
| Above 960                | 500                                      | 3                                    |

**3.7.2 Measuring Instruments and Setting**

Please refer to section 4 of equipments list in this report. The following table is the setting of the spectrum analyzer.

| <b>Spectrum Parameter</b>                 | <b>Setting</b>                                 |
|---|--|
| Attenuation                               | Auto   |
| Span Frequency                            | 100 MHz  |
| RB / VB (Emission in restricted band)     | 1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average |
| RB / VB (Emission in non-restricted band) | 1MHz/1MHz for Peak                             |

**3.7.3 Test Procedures**

1. The test procedure is the same as section 3.5.3, only the frequency range investigated is limited to 100MHz around band edges.
2. In case the emission is fail due to the used RB/VB is too wide, marker-delta method of FCC Public Notice DA00-705 will be followed.

**3.7.4 Test Setup Layout**

This test setup layout is the same as that shown in section 3.6.4.

**3.7.5 Test Deviation**

There is no deviation with the original standard.

**3.7.6 EUT Operation during Test**

The EUT was programmed to be in continuously transmitting mode.

3.7.7 Test Result of Band Edge and Fundamental Emissions

|                        |              |                       |                   |
|------------------------|--------------|-----------------------|-------------------|
| <b>Final Test Date</b> | May 18, 2010 | <b>Test Site No.</b>  | 03CH03-HY         |
| <b>Temperature</b>     | 27.9         | <b>Humidity</b>       | 56%               |
| <b>Test Engineer</b>   | Eddie        | <b>Configurations</b> | Channel 0, 39, 78 |

1Mbps

Channel 0

|     | Freq     | Level  | Over Limit | Limit Line | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Ant Pos | Table Pos | Remark  |
|-----|----------|--------|------------|------------|------------|----------------|------------|---------------|---------|-----------|---------|
|     | MHz      | dBuV/m | dB         | dBuV/m     | dBuV       | dB/m           | dB         | dB            | cm      | deg       |         |
| 1   | 2340.020 | 56.15  | -17.85     | 74.00      | 25.53      | 28.06          | 2.56       | 0.00          | ---     | ---       | Peak    |
| 2 @ | 2401.770 | 96.84  |            |            | 66.08      | 28.17          | 2.58       | 0.00          | ---     | ---       | Peak    |
| 1   | 2322.540 | 42.71  | -11.29     | 54.00      | 12.15      | 28.02          | 2.54       | 0.00          | ---     | ---       | Average |
| 2 @ | 2401.770 | 96.26  |            |            | 65.50      | 28.17          | 2.58       | 0.00          | ---     | ---       | Average |

The item 2 is Fundamental Emissions.

Channel 39

|     | Freq     | Level  | Over Limit | Limit Line | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Ant Pos | Table Pos | Remark  |
|-----|----------|--------|------------|------------|------------|----------------|------------|---------------|---------|-----------|---------|
|     | MHz      | dBuV/m | dB         | dBuV/m     | dBuV       | dB/m           | dB         | dB            | cm      | deg       |         |
| 1 X | 2440.530 | 93.47  |            |            | 62.58      | 28.29          | 2.61       | 0.00          | ---     | ---       | Peak    |
| 1 @ | 2441.100 | 92.87  |            |            | 61.98      | 28.29          | 2.61       | 0.00          | ---     | ---       | Average |

The item 1 is Fundamental Emissions.

Channel 78

|     | Freq     | Level  | Over Limit | Limit Line | Read Level | Antenna Factor | Cable Loss | Preamp Factor | Ant Pos | Table Pos | Remark  |
|-----|----------|--------|------------|------------|------------|----------------|------------|---------------|---------|-----------|---------|
|     | MHz      | dBuV/m | dB         | dBuV/m     | dBuV       | dB/m           | dB         | dB            | cm      | deg       |         |
| 1 X | 2479.860 | 89.78  |            |            | 58.79      | 28.36          | 2.63       | 0.00          | ---     | ---       | Peak    |
| 2   | 2483.500 | 57.93  | -16.07     | 74.00      | 26.94      | 28.36          | 2.63       | 0.00          | ---     | ---       | Peak    |
| 1 @ | 2480.050 | 89.17  |            |            | 58.18      | 28.36          | 2.63       | 0.00          | ---     | ---       | Average |
| 2   | 2483.500 | 52.28  | -1.72      | 54.00      | 21.29      | 28.36          | 2.63       | 0.00          | ---     | ---       | Average |

The item 1 is Fundamental Emissions.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

**2Mbps**

**Channel 0**

|     | Freq     | Level  | Over Limit | Limit Line | ReadAntenna Level | Antenna Factor | Cable Loss | Preamp Factor | Ant Pos | Table Pos | Remark  |
|-----|----------|--------|------------|------------|-------------------|----------------|------------|---------------|---------|-----------|---------|
|     | MHz      | dBuV/m | dB         | dBuV/m     | dBuV              | dB/m           | dB         | dB            | cm      | deg       |         |
| 1   | 2314.370 | 55.66  | -18.34     | 74.00      | 25.13             | 27.98          | 2.54       | 0.00          | ---     | ---       | Peak    |
| 2 X | 2401.770 | 95.85  |            |            | 65.09             | 28.17          | 2.58       | 0.00          | ---     | ---       | Peak    |
| 1   | 2321.210 | 42.74  | -11.26     | 54.00      | 12.18             | 28.02          | 2.54       | 0.00          | ---     | ---       | Average |
| 2 X | 2402.340 | 72.92  |            |            | 42.16             | 28.17          | 2.58       | 0.00          | ---     | ---       | Average |

An item 2 is Fundamental Emissions.

**Channel 39**

|     | Freq     | Level  | Over Limit | Limit Line | ReadAntenna Level | Antenna Factor | Cable Loss | Preamp Factor | Ant Pos | Table Pos | Remark  |
|-----|----------|--------|------------|------------|-------------------|----------------|------------|---------------|---------|-----------|---------|
|     | MHz      | dBuV/m | dB         | dBuV/m     | dBuV              | dB/m           | dB         | dB            | cm      | deg       |         |
| 1 X | 2441.100 | 92.79  |            |            | 61.90             | 28.29          | 2.61       | 0.00          | ---     | ---       | Peak    |
| 1 X | 2441.100 | 70.94  |            |            | 40.05             | 28.29          | 2.61       | 0.00          | ---     | ---       | Average |

An item 1 is Fundamental Emissions.

**Channel 78**

|     | Freq     | Level  | Over Limit | Limit Line | ReadAntenna Level | Antenna Factor | Cable Loss | Preamp Factor | Ant Pos | Table Pos | Remark  |
|-----|----------|--------|------------|------------|-------------------|----------------|------------|---------------|---------|-----------|---------|
|     | MHz      | dBuV/m | dB         | dBuV/m     | dBuV              | dB/m           | dB         | dB            | cm      | deg       |         |
| 1 X | 2479.860 | 88.83  |            |            | 57.84             | 28.36          | 2.63       | 0.00          | ---     | ---       | Peak    |
| 2   | 2483.500 | 58.53  | -15.47     | 74.00      | 27.54             | 28.36          | 2.63       | 0.00          | ---     | ---       | Peak    |
| 1 X | 2480.050 | 68.51  |            |            | 37.52             | 28.36          | 2.63       | 0.00          | ---     | ---       | Average |
| 2   | 2483.500 | 46.85  | -7.15      | 54.00      | 15.86             | 28.36          | 2.63       | 0.00          | ---     | ---       | Average |

An item 1 is Fundamental Emissions.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

3Mbps

Channel 0

|     | Freq     | Level  | Over Limit | Limit Line | ReadAntenna Level | Antenna Factor | Cable Loss | Preamp Factor | Ant Pos | Table Pos | Remark  |
|-----|----------|--------|------------|------------|-------------------|----------------|------------|---------------|---------|-----------|---------|
|     | MHz      | dBuV/m | dB         | dBuV/m     | dBuV              | dB/m           | dB         | dB            | cm      | deg       |         |
| 1   | 2377.450 | 55.13  | -18.87     | 74.00      | 24.41             | 28.13          | 2.58       | 0.00          | ---     | ---       | Peak    |
| 2 X | 2401.770 | 95.61  |            |            | 64.85             | 28.17          | 2.58       | 0.00          | ---     | ---       | Peak    |
| 1   | 2322.540 | 42.67  | -11.33     | 54.00      | 12.11             | 28.02          | 2.54       | 0.00          | ---     | ---       | Average |
| 2 @ | 2401.770 | 91.86  |            |            | 61.10             | 28.17          | 2.58       | 0.00          | ---     | ---       | Average |

The item 2 is Fundamental Emissions.

Channel 39

|     | Freq     | Level  | Over Limit | Limit Line | ReadAntenna Level | Antenna Factor | Cable Loss | Preamp Factor | Ant Pos | Table Pos | Remark  |
|-----|----------|--------|------------|------------|-------------------|----------------|------------|---------------|---------|-----------|---------|
|     | MHz      | dBuV/m | dB         | dBuV/m     | dBuV              | dB/m           | dB         | dB            | cm      | deg       |         |
| 1 X | 2441.100 | 92.91  |            |            | 62.02             | 28.29          | 2.61       | 0.00          | ---     | ---       | Peak    |
| 1 @ | 2441.100 | 88.99  |            |            | 58.10             | 28.29          | 2.61       | 0.00          | ---     | ---       | Average |

The item 1 is Fundamental Emissions.

Channel 78

|     | Freq     | Level  | Over Limit | Limit Line | ReadAntenna Level | Antenna Factor | Cable Loss | Preamp Factor | Ant Pos | Table Pos | Remark  |
|-----|----------|--------|------------|------------|-------------------|----------------|------------|---------------|---------|-----------|---------|
|     | MHz      | dBuV/m | dB         | dBuV/m     | dBuV              | dB/m           | dB         | dB            | cm      | deg       |         |
| 1 X | 2479.860 | 88.84  |            |            | 57.85             | 28.36          | 2.63       | 0.00          | ---     | ---       | Peak    |
| 2   | 2483.500 | 59.90  | -14.10     | 74.00      | 28.91             | 28.36          | 2.63       | 0.00          | ---     | ---       | Peak    |
| 1 @ | 2480.050 | 84.87  |            |            | 53.88             | 28.36          | 2.63       | 0.00          | ---     | ---       | Average |
| 2   | 2483.500 | 50.47  | -3.53      | 54.00      | 19.48             | 28.36          | 2.63       | 0.00          | ---     | ---       | Average |

The item 1 is Fundamental Emissions.

Note:


Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

For Emission not in Restricted Band


|                 |               |                |         |
|-----------------|---------------|----------------|---------|
| Final Test Date | Jun. 02, 2010 | Test Site No.  | TH01-HY |
| Temperature     | 25            | Humidity       | 61%     |
| Test Engineer   | Ian           | Configurations | 8DPSK   |

Low Band Edge Plot on Channel 0 / 2402 MHz



Date: 2.JUN.2010 11:11:41

High Band Edge Plot on Channel 78 / 2480 MHz



Date: 2.JUN.2010 11:09:02

### **3.8 Antenna Requirements**

#### **3.8.1 Limit**

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited.

#### **3.8.2 Antenna Connector Construction**

Please refer to section 2.3 in this test report; antenna connector complied with the requirements.



**4 LIST OF MEASURING EQUIPMENTS**

| Instrument            | Manufacturer      | Model No.      | Serial No.     | Characteristics | Calibration Date | Remark               |
|-----------------------|-------------------|----------------|----------------|-----------------|------------------|----------------------|
| EMC Receiver          | R&S               | ESCS 30        | 100132         | 9kHz – 2.75GHz  | Sep. 01, 2009    | Conduction (CO01-HY) |
| LISN                  | MessTec           | NNB-2/16Z      | 2001/004       | 9kHz – 30MHz    | Jan. 19, 2010    | Conduction (CO01-HY) |
| LISN (Support Unit)   | MessTec           | NNB-2/16Z      | 2001/009       | 9kHz – 30MHz    | Mar. 01, 2010    | Conduction (CO01-HY) |
| EMI Filter            | LINDGREN          | LRE-2060       | 1004           | < 450Hz         | N/A              | Conduction (CO01-HY) |
| EMI Filter            | LINDGREN          | N6006          | 201052         | 0 – 60Hz        | N/A              | Conduction (CO01-HY) |
| RF Cable-CON          | HUBER+SUHNER      | RG213/U        | 07611832010001 | 9kHz – 30MHz    | May 05, 2010     | Conduction (CO01-HY) |
| Isolation Transformer | Erika Fiedler OHG | D-65396 Walluf | 58             | 45MHz-2.15GHz   | N/A              | Conduction (CO01-HY) |

Note: Calibration Interval of instruments listed above is one year.

| Instrument                 | Manufacturer | Model No.    | Serial No.  | Characteristics | Calibration Date | Remark              |
|----------------------------|--------------|--------------|-------------|-----------------|------------------|---------------------|
| Spectrum Analyzer          | R&S          | FSU26.5      | 100015      | 20Hz ~ 26.5GHz  | Oct. 29, 2009    | Conducted (TH01-HY) |
| Power Sensor               | R&S          | NRV-Z32      | 100057      | 30MHz ~ 6GHz    | Jul. 31, 2009    | Conducted (TH01-HY) |
| DC Power Source            | G.W.         | GPC-6030D    | C671845     | DC 1V ~ 60V     | Mar. 12, 2010    | Conducted (TH01-HY) |
| Temp. and Humidity Chamber | Giant Force  | GTH-225-20-S | MAB0103-001 | N/A             | Aug. 06, 2009    | Conducted (TH01-HY) |
| RF CABLE-1m                | Jye Bao      | RG142        | CB034-1m    | 20MHz ~ 7GHz    | Dec. 02, 2009    | Conducted (TH01-HY) |
| RF CABLE-2m                | Jye Bao      | RG142        | CB035-2m    | 20MHz ~ 1GHz    | Dec. 02, 2009    | Conducted (TH01-HY) |
| Signal Generator           | R&S          | SMR40        | 100116      | 10MHz ~ 40GHz   | Mar. 24, 2010    | Conducted (TH01-HY) |
| Power Sensor               | Anritsu      | MA2411B      | 0917017     | 300MHz~40GHz    | Dec. 03, 2009    | Conducted (TH01-HY) |
| Power Meter                | Anritsu      | ML2495A      | 0949003     | 300MHz~40GHz    | Dec. 03, 2009    | Conducted (TH01-HY) |

Note: Calibration Interval of instruments listed above is one year.

| Instrument      | Manufacturer | Model No. | Serial No.  | Characteristics | Calibration Date | Remark              |
|-----------------|--------------|-----------|-------------|-----------------|------------------|---------------------|
| AC Power Source | HPC          | HPA-500W  | HPA-9100024 | AC 0 ~ 300V     | Jul. 12, 2009*   | Conducted (TH01-HY) |

Note: Calibration Interval of instruments listed above is two year.

| Instrument               | Manufacturer   | Model No.    | Serial No.  | Characteristics      | Calibration Date | Remark                   |
|--------------------------|----------------|--------------|-------------|----------------------|------------------|--------------------------|
| 3m Semi Anechoic Chamber | SIDT FRANKONIA | SAC-3M       | 03CH03-HY   | 30 MHz - 1 GHz<br>3m | Jun. 07, 2009    | Radiation<br>(03CH03-HY) |
| Amplifier                | SCHAFFNER      | COA9231A     | 18667       | 9 kHz - 2 GHz        | Jan. 24, 2010    | Radiation<br>(03CH03-HY) |
| Amplifier                | Agilent        | 8449B        | 3008A02120  | 1 GHz - 26.5 GHz     | Jul. 21, 2009    | Radiation<br>(03CH01-HY) |
| Spectrum Analyzer        | R&S            | FSP40        | 100004      | 9 kHz - 40 GHz       | Oct. 03, 2009    | Radiation<br>(03CH03-HY) |
| Bilog Antenna            | SCHAFFNER      | CBL 6112D    | 22237       | 30 MHz - 1 GHz       | Sep. 26, 2009    | Radiation<br>(03CH03-HY) |
| Horn Antenna             | EMCO           | 3115         | 6741        | 1GHz ~ 18GHz         | May. 20, 2010    | Radiation<br>(03CH03-HY) |
| Horn Antenna             | SCHWARZBECK    | BBHA9170     | BBHA9170154 | 15 GHz - 40 GHz      | Jan. 11, 2010    | Radiation<br>(03CH03-HY) |
| RF Cable-R03m            | Jye Bao        | RG142        | CB021       | 30 MHz - 1 GHz       | Jan. 05, 2010    | Radiation<br>(03CH03-HY) |
| RF Cable-HIGH            | SUHNER         | SUCOFLEX 106 | 03CH03-HY   | 1 GHz - 40 GHz       | Jan. 05, 2010    | Radiation<br>(03CH03-HY) |
| Turn Table               | HD             | DS 420       | 420/650/00  | 0 - 360 degree       | N/A              | Radiation<br>(03CH03-HY) |
| Antenna Mast             | HD             | MA 240       | 240/560/00  | 1 m - 4 m            | N/A              | Radiation<br>(03CH03-HY) |

Note: Calibration Interval of instruments listed above is one year.

| Instrument   | Manufacturer | Model No. | Serial No. | Characteristics | Calibration Date | Remark                   |
|--------------|--------------|-----------|------------|-----------------|------------------|--------------------------|
| Loop Antenna | R&S          | HFH2-Z2   | 860004/001 | 9 kHz - 30 MHz  | Jul. 28, 2008*   | Radiation<br>(03CH03-HY) |

Note: Calibration Interval of instruments listed above is one year.

**5 TEST LOCATION**

|        |  |
|--------|--|
| SHIJR  | ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C.<br>TEL : 886-2-2696-2468<br>FAX : 886-2-2696-2255 |
| HWA YA | ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.<br>TEL : 886-3-327-3456<br>FAX : 886-3-318-0055         |
| LINKOU | ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C<br>TEL : 886-2-2601-1640<br>FAX : 886-2-2601-1695               |
| DUNGHU | ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C.<br>TEL : 886-2-2631-4739<br>FAX : 886-2-2631-9740            |
| JUNGHE | ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C.<br>TEL : 886-2-8227-2020<br>FAX : 886-2-8227-2626           |
| NEIHU  | ADD : 4Fl., No. 339, Hsin Hu 2 <sup>nd</sup> Rd., Taipei 114, Taiwan, R.O.C.<br>TEL : 886-2-2794-8886<br>FAX : 886-2-2794-9777         |
| JHUBEI | ADD : No.8, Lane 728, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C.<br>TEL : 886-3-656-9065<br>FAX : 886-3-656-9085       |

6 TAF CERTIFICATE OF ACCREDITATION



Certificate No. : L1190-100107

**財團法人全國認證基金會**  
**Taiwan Accreditation Foundation**

## Certificate of Accreditation

This is to certify that

**Sporton International Inc.**  
**EMC & Wireless Communications Laboratory**  
No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien,  
Taiwan, R.O.C.

**is accredited in respect of laboratory**

|                                       |  |
|---------------------------------------|--|
| <b>Accreditation Criteria</b>         | : ISO/IEC 17025:2005   |
| <b>Accreditation Number</b>           | : 1190   |
| <b>Originally Accredited</b>          | : December 15, 2003  |
| <b>Effective Period</b>               | : January 10, 2010 to January 09, 2013   |
| <b>Accredited Scope</b>               | : Testing Field, see described in the Appendix   |
| <b>Specific Accreditation Program</b> | : Accreditation Program for Designated Testing Laboratory for Commodities Inspection<br>Accreditation Program for Telecommunication Equipment Testing Laboratory<br>Accreditation Program for BSMI Mutual Recognition Arrangement with Foreign Authorities |



Jay-San Chen  
President, Taiwan Accreditation Foundation  
Date : January 07, 2010

P1, total 21 pages



# **Annex**

## **Declaration for Bluetooth Device acc to Part 15.247**



## **1 Output power and channel separation of a Bluetooth device in the different operating modes:**

The different operating modes (data-mode, acquisition-mode) of a Bluetooth device has no influence on the output power and the channel spacing. There is only one transmitter which is driven by identical input parameters concerning these two parameters.

Only a different hopping sequence will be used. For this reason the check of these RF parameters in one op-mode is sufficient.

## **2 Frequency range of a Bluetooth device:**

Hereby we declare that the maximum frequency of this device is: 2402 – 2480 MHz. This is according to the Bluetooth Core Specification (+ critical errata) for devices which will be operated in the USA.

This was checked during the Bluetooth Qualification tests (Test Case: TRM/CA/04-E). Other frequency ranges ( e.g. for Spain, France, Japan) which are allowed according the Core Specification are not supported by this device.

## **3 Co-ordination of the hopping sequence in data mode to avoid simultaneous occupancy by multiple transmitters:**

Bluetooth units which want to communicate with other units must be organised in a structure called piconet. This piconet consist of max. 8 Bluetooth units. One unit is the master the other seven are the slaves. The master co-ordinates frequency occupation in this piconet for all units. As the master hop sequence is derived from its BD address which is unique for each Bluetooth device, additional masters intending to establish new piconets will always use different hop sequences.

## **4 Example of a hopping sequence in data mode:**

Example of a 79 hopping sequence in data mode:

40, 21, 44, 23, 42, 53, 46, 55, 48, 33, 52, 35, 50, 65, 54, 67,  
56, 37, 60, 39, 58, 69, 62, 71, 64, 25, 68, 27, 66, 57, 70, 59,  
72, 29, 76, 31, 74, 61, 78, 63, 01, 41, 05, 43, 03, 73, 07, 75,  
09, 45, 13, 47, 11, 77, 15, 00, 64, 49, 66, 53, 68, 02, 70, 06,  
01, 51, 03, 55, 05, 04



## **5 Equally average use of frequencies in data mode and behaviour for short transmissions:**

The generation of the hopping sequence in connection mode depends essentially on two input values:

1. LAP/UAP of the master of the connection
2. Internal master clock

The LAP (lower address part) are the 24 LSB's of the 48 BD\_ADDRESS. The BD\_ADDRESS is an unambiguous number of every Bluetooth unit. The UAP (upper address part) are the 24 MSB's of the 48 BD\_ADDRESS.

The internal clock of a Bluetooth unit is derived from a free running clock which is never adjusted and is never turned off. For synchronisation with other units only offset are used. It has no relation to the time of the day. Its resolution is at least half the RX/TX slot length of 312.5  $\mu$ s. The clock has a cycle of about one day (23h30). In most case it is implemented as 28 bit counter. For the deriving of the hopping sequence the entire

LAP (24 bits), 4 LSB's (4 bits) (Input 1) and the 27 MSB's of the clock (Input 2) are used. With this input values different mathematical procedures (permutations, additions, XOR- operations) are performed to generate the sequence. This will be done at the beginning of every new transmission.

Regarding short transmissions the Bluetooth system has the following behaviour:

The first connection between the two devices is established, a hopping sequence was generated. For transmitting the wanted data the complete hopping sequence was not used. The connection ended.

The second connection will be established. A new hopping sequence is generated. Due to the fact that the Bluetooth clock has a different value, because the period between the two transmission is longer (and it cannot be shorter) than the minimum resolution of the clock (312.5  $\mu$ s). The hopping sequence will always differ from the first one.

## **6 Receiver input bandwidth and behaviour for repeated single or multiple packets:**

The input bandwidth of the receiver is 1 MHz. In every connection one Bluetooth device is the master and the other one is the slave. The master determines the hopping sequence (see chapter 5). The slave follows this sequence. Both devices shift between RX and TX time slot according to the clock of the master.

Additionally the type of connection (e.g. single or multislot packet) is set up at the beginning of the connection. The master adapts its hopping frequency and its TX/RX timing according to the packet type of the connection. Also the slave of the connection will use these settings.

Repeating of a packet has no influence on the hopping sequence. The hopping sequence generated by the master of the connection will be followed in any case. That means, a repeated packet will not be send on the same frequency, it is send on the next frequency of the hopping sequence.



## 7 Dwell time in data mode

The dwell time of 0.3797s within a 30 second period in data mode is independent from the packet type (packet length). The calculation for a 30 second period is as follows:

Dwell time = time slot length \* hop rate / number of hopping channels \* 30s

Example for a DH1 packet (with a maximum length of one time slot) Dwell time =  $625 \mu\text{s} * 1600 \text{ 1/s} / 79 * 30\text{s} = 0.3797\text{s}$  (in a 30s period)

For multislot packet the hopping is reduced according to the length of the packet. Example for a DH5 packet (with a maximum length of five time slots)

Dwell time =  $5 * 625 \mu\text{s} * 1600 * 1/5 * 1/\text{s} / 79 * 30\text{s} = 0.3797\text{s}$  (in a 30s period).

This is according to the Bluetooth Core Specification V 1.0B (+ critical errata) for all Bluetooth devices. Therefore all Bluetooth devices **comply** with the FCC dwell time requirement in data mode. This was checked during the Bluetooth Qualification tests. The Dwell time in hybrid mode is measured and stated in the test report.

## 8 Channel Separation in hybrid mode

The nominal channel spacing of the Bluetooth system is 1MHz independent of the operating mode.

The maximum "initial carrier frequency tolerance" which is allowed for Bluetooth is  $f_{\text{center}} = 75 \text{ kHz}$ .

This was checked during the Bluetooth Qualification tests (Test Case: TRM/CA/07-E) for three frequencies (2402, 2441, 2480 MHz).

Additionally an example for the channel separation is given in the test report

## 9 Derivation and examples for a hopping sequence in hybrid mode

For the generation of the inquiry and page hop sequences the same procedures as described for the data mode are used (see chapter 5), but this time with different input vectors:

- For the inquiry hop sequence, a predefined fixed address is always used. This results in the same 32 frequencies used by all devices doing an inquiry but every time with a different start frequency and phase in this sequence.
- For the page hop sequence, the device address of the paged unit is used as input vector. This results in the use of a subset of 32 frequencies which is specific for that initial state of the connection establishment between the two units. A page to different devices would result in a different subset of 32 frequencies.

So it is ensured that also in hybrid mode the frequency use is equally averaged.

Example of a hopping sequence in inquiry mode:

48, 50, 09, 13, 52, 54, 41, 45, 56, 58, 11, 15, 60, 62, 43, 47, 00, 02, 64, 68, 04, 06, 17, 21, 08, 10, 66, 70, 12, 14, 19, 23





Example of a hopping sequence in paging mode:

08, 57, 68, 70, 51, 02, 42, 40, 04, 61, 44, 46, 63, 14, 50, 48, 16, 65, 52, 54, 67, 18,  
58, 56, 20, 53, 60, 62, 55, 06, 66, 64

## **10 Receiver input bandwidth and synchronisation in hybrid mode:**

The receiver input bandwidth is the same as in the data mode (1 MHz). When two Bluetooth devices establish contact for the first time, one device sends an inquiry access code, the other device is scanning for this inquiry access code. If two devices have been connected previously and want to start a new transmission, a similar procedure takes place. The only difference is, instead of the inquiry access code, a special access code, derived from the BD\_ADDRESS of the paged device will be, will be sent by the master of this connection.

Due to the fact that both units have been connected before (in the inquiry procedure) the paging unit has timing and frequency information about the page scan of the paged unit. For this reason the time to establish the connection is reduced considerable.

## **11 Spread rate / data rate of the direct sequence signal**

The Spread rate / Data rate in inquiry and paging mode can be defined via the access code. The access code is the only criterion for the system to check if there is a valid transmission or not. If you regard the presence of a valid access code as one bit of information, and compare it with the length of the access code of 68 bits, the Spread rate / Data rate will be 68/1.

## **12 Spurious emission in hybrid mode**

The dwell time in hybrid mode is shorter than in data mode. For this reason the spurious emissions average level in data mode is worst case. The spurious emissions peak level is the same for both modes.

## **13 Peak power spectral density measurement**

Since the transmitter is only active for some milliseconds on one channel you would get a result with many interruptions if using a sweep time of e.g. 1s as stated in the FCC rules. Therefore a fast sweep in maxhold function is used instead and the EUT is activated several times until the measurement curve has stabilized.