



KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:

KES-RF1-21T0184

Page (34) of (48)


Mode: EDR
Transfer rate: 3 Mbps(Worst case)
Distance of measurement: 3 meter
Channel: 00

- Spurious


Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 014.45	47.64	Peak	H	-11.08	-	36.56	74.00	37.44
1 289.07	47.84	Peak	V	-9.62	-	38.22	74.00	35.78
1 866.41	49.69	Peak	H	-5.54	-	44.15	74.00	29.85
1 866.41	50.66	Peak	V	-5.54	-	45.12	74.00	28.88

- Band edge

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
2 375.56	43.88	Peak	V	-2.83	-	41.05	74.00	32.95
2 376.16	45.54	Peak	H	-2.82	-	42.72	74.00	31.28
2 384.69	45.76	Peak	H	-2.79	-	42.97	74.00	31.03
2 388.70	45.52	Peak	V	-2.77	-	42.75	74.00	31.25



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr



Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.



KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:


KES-RF1-21T0184

Page (36) of (48)

Mode: EDR
Transfer rate: 3 Mbps(Worst case)
Distance of measurement: 3 meter
Channel: 40

- Spurious

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 045.10	45.67	Peak	H	-10.92	-	34.75	74.00	39.25
1 627.64	45.69	Peak	V	-7.44	-	38.25	74.00	35.75
1 866.41	48.19	Peak	H	-5.54	-	42.65	74.00	31.35
1 866.41	50.92	Peak	V	-5.54	-	45.38	74.00	28.62



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr




KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:

KES-RF1-21T0184

Page (37) of (48)



Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.

This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr



KES Co., Ltd.

3701, 40, Simin-daero 365beon-gil,
Dongan-gu, Anyang-si, Gyeonggi-do, 14057, Korea
Tel: +82-31-425-6200 / Fax: +82-31-424-0450
www.kes.co.kr

Report No.:

KES-RF1-21T0184

Page (38) of (48)


Mode: EDR
Transfer rate: 3 Mbps(Worst case)
Distance of measurement: 3 meter
Channel: 78

- Spurious


Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
1 249.88	50.79	Peak	V	-9.83	-	40.96	74.00	33.04
1 627.64	44.85	Peak	H	-7.44	-	37.41	74.00	36.59
1 866.41	48.36	Peak	H	-5.54	-	42.82	74.00	31.18
1 866.41	49.92	Peak	V	-5.54	-	44.38	74.00	29.62

- Band edge

Frequency (MHz)	Level (dBμV)	Detect mode	Ant. Pol. (H/V)	CF (dB)	DCF (dB)	Field strength (dBμV/m)	Limit (dBμV/m)	Margin (dB)
2 484.40	47.90	Peak	H	-2.40	-	45.50	74.00	28.50
2 485.82	46.09	Peak	V	-2.39	-	43.70	74.00	30.30
2 499.03	45.78	Peak	V	-2.34	-	43.44	74.00	30.56
2 499.19	45.62	Peak	H	-2.34	-	43.28	74.00	30.72



This report shall not be reproduced except in full, without the written approval of KES Co., Ltd.
The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
The authenticity of the test report, contact shchoi@kes.co.kr




Note.

1. No spurious emission were detected above 3 GHz.
2. Average test would be performed if the peak result were greater than the average limit.

Test results (18 GHz to 30 GHz) – Worst case

Mode:	BDR
Transfer rate:	1 Mbps
Distance of measurement:	3 meter
Channel:	78(Worst case)



Note.

1. No spurious emission were detected above 18 GHz.