

## 11 FCC §1.1307(b) (1) & §2.1091 - RF EXPOSURE

### 11.1 Applicable Standard

According to FCC §1.1310 and §2.1091 (Mobile Devices) RF exposure is calculated.

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
<b>Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

Note: f = frequency in MHz

\* = Plane-wave equivalent power density

### 11.2 MPE Prediction

Predication of MPE limit at a given distance, Equation from FCC OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

#### 850 MHz Cellular Band, Uplink:

Maximum peak output power at antenna input terminal (dBm): 10.2

Maximum peak output power at antenna input terminal (mW): 10.47

Prediction distance (cm): 20

Prediction frequency (MHz): 836.6

Antenna Gain, typical (dBi): 3.0

Maximum Antenna Gain (numeric): 2

Power density at predication frequency and distance (mW/cm<sup>2</sup>): 0.0042

MPE limit for uncontrolled exposure at predication frequency (mW/cm<sup>2</sup>): 0.558

**850 MHz Cellular Band, Downlink:**Maximum peak output power at antenna input terminal (dBm): 15.15Maximum peak output power at antenna input terminal (mW): 32.73Prediction distance (cm): 20Prediction frequency (MHz): 881.6Antenna Gain, typical (dBi): 6.0Maximum Antenna Gain (numeric): 3.98Power density at predication frequency and distance (mW/cm<sup>2</sup>): 0.0259MPE limit for uncontrolled exposure at predication frequency (mW/cm<sup>2</sup>): 0.588**Test Result**

For Uplink, the highest power density level at 20 cm is 0.0042mW/cm<sup>2</sup>, which is below the uncontrolled exposure limit of 0.558 mW/cm<sup>2</sup> at 836.6 MHz.

For Downlink, the highest power density level at 20 cm is 0.0259mW/cm<sup>2</sup>, which is below the uncontrolled exposure limit of 0.588 mW/cm<sup>2</sup> at 881.6 MHz.

So the indoor antenna prediction distance should be greater then 20 cm, and outdoor antenna prediction distance should be greater then 20 cm.