

Appendix 5

RF Exposure Information

FCC ID: YFA20010121
IC ID: 12260A-20010121

Maximum transmitter power:

Frequency (MHz)	Maximum peak field strength (dB μ V/m)	Maximum transmitter power (mW)
2410	95.2	0.6057
2440	95.7	0.6796
2472	99.3	1.5570

Note: The maximum peak field strength was taken from table of "Subclause 15.249(a)/RSS-210 B.10(a) – Field Strength of Fundamental and Harmonics".

For FCC

According to KDB 447498 D01:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 5 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$
 ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

Result:

$$(0.6057/5) \cdot \sqrt{2.410} = 0.188 < 3.0$$

$$(0.6796/5) \cdot \sqrt{2.440} = 0.212 < 3.0$$

$$(1.5570/5) \cdot \sqrt{2.472} = 0.490 < 3.0$$

Conclusion:

No SAR is required.

For ISED

According to table 1 in RSS-102 Issue 6, below exemption limit is applied

Frequency: 2472 MHz

At separation distance of ≤ 5 mm

Exemption limits: 3mW

Results:

max. power of channel = 1.5570 mW < 3mW

Conclusion:

The maximum peak output power of the transmitter is less than the SAR evaluation exemption threshold and hence it complies with the RSS-102 RF exposure requirement.