

Produkte  
Products

<b>Prüfbericht - Nr.:</b> <b>14051135 001</b>			<b>Seite 1 von 17</b> <i>Page 1 of 17</i>		
<i>Test Report No.:</i>					
<b>Auftraggeber:</b> <i>Client:</i>		<b>Stadlbauer Marketing + Vertrieb GmbH</b> <b>Rennbahn Allee1, 5412 Puch, Salzburg.</b> <b>Austria</b>			
<b>Gegenstand der Prüfung:</b> <i>Test Item:</i>		<b>GO!!! Plus WIRELESS+ Speed Controller</b>			
<b>Bezeichnung:</b> <i>Identification:</i>	<b>20061668</b>	<b>Serien-Nr.:</b> <i>Serial No.:</i>	<b>Engineering sample</b>		
<b>Wareneingangs-Nr.:</b> <i>Receipt No.:</i>	<b>A000611846-001</b>	<b>Eingangsdatum:</b> <i>Date of Receipt:</i>	<b>31.08.2017</b>		
<b>Prüfört:</b> <i>Testing Location:</i>	<b>TÜV Rheinland Hong Kong Ltd.</b> 3-4, 11/F., Fou Wah Industrial Building, 10-16 Pun Shan Street, Tsuen Wan, N.T., Hong Kong  <b>Hong Kong Productivity Council</b> HKPC Building, 78 Tat Chee Avenue, Kowloon, Hong Kong				
<b>Zustand des Prüfgegenstandes bei Anlieferung:</b> <i>Condition of test item at delivery:</i>		Test samples are not damaged and suitable for testing.			
<b>Prüfgrundlage:</b> <i>Test Specification:</i>	<b>FCC Part 15 Subpart C</b> <b>RSS-247 Issue 2</b> <b>ANSI C63.10-2013</b>				
<b>Prüfergebnis:</b> <i>Test Results:</i>	<b>Das vorstehend beschriebene Gerät wurde geprüft und entspricht oben genannter Prüfgrundlage.</b> The above mentioned product was tested and <b>passed</b> .				
<b>Prüflaboratorium:</b> <i>Testing Laboratory:</i>	<b>TÜV Rheinland Hong Kong Ltd.</b> 3-4, 11/F., Fou Wah Industrial Building, 10-16 Pun Shan Street, Tsuen Wan, N.T., Hong Kong				
<b>geprüft/ tested by:</b>			<b>kontrolliert/ reviewed by:</b>		
12.07.2017      Kevin Wong Project Manager			12.07.2017      Benny Lau Senior Project Manager		
Datum <i>Date</i>	Name/Stellung <i>Name/Position</i>	Unterschrift <i>Signature</i>	Datum <i>Date</i>	Name/Stellung <i>Name/Position</i>	Unterschrift <i>Signature</i>
<b>Sonstiges:</b> <i>Other Aspects</i>			<b>FCC ID: YFA20061668</b> <b>IC: 12260A-20061668</b>		
<b>Abkürzungen:</b> P(ass) = entspricht Prüfgrundlage F(ail) = entspricht nicht Prüfgrundlage N/A = nicht anwendbar N/T = nicht getestet			<b>Abbreviations:</b> P(ass) = passed F(ail) = failed N/A = not applicable N/T = not tested		
<p><b>Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.</b></p> <p><i>This test report relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any safety mark on this or similar products.</i></p>					

## Table of Content

	Page
<b>Cover Page .....</b>	<b>1</b>
<b>Table of Content .....</b>	<b>2</b>
<b>Product information.....</b>	<b>4</b>
Manufacturers declarations .....	4
Product function and intended use .....	4
Submitted documents.....	4
Independent Operation Modes .....	4
Related Submittal(s) Grants .....	5
Remark .....	5
<b>Test Set-up and Operation Mode.....</b>	<b>6</b>
Principle of Configuration Selection .....	6
Test Operation and Test Software.....	6
Special Accessories and Auxiliary Equipment.....	6
Countermeasures to achieve EMC Compliance.....	6
<b>Test Methodology .....</b>	<b>7</b>
Radiated Emission .....	7
Field Strength Calculation.....	7
<b>Test Setup Diagram .....</b>	<b>8</b>
<b>List of Test and Measurement Instruments.....</b>	<b>10</b>
<b>Measurement Uncertainty .....</b>	<b>11</b>
<b>Results FCC Part 15 – Subpart C / RSS-247 Issue 2.....</b>	<b>12</b>
FCC 15.203 – Antenna Requirement 1.....	Pass..... 12
FCC 15.204 – Antenna Requirement 2.....	N/A..... 12
RSS-Gen 6.3 – External Control.....	Pass..... 12
RSS-Gen 8.3 – Antenna Requirement .....	Pass..... 12
FCC 15.207 / RSS-Gen 8.8 – Conducted Emission on AC Mains.....	N/A..... 13
FCC 15.247 (a)(2) / RSS-247 5.2 – 6dB Bandwidth Measurement.....	Pass..... 13
RSS-Gen 6.6 – Occupied Bandwidth.....	Pass..... 13
FCC 15.247(b)(3) / RSS-247 5.4 – Maximum Peak Conducted Output Power.....	Pass..... 14
FCC 15.247(e) / RSS-247 5.2 – Power Spectral Density.....	Pass..... 14

<b>FCC 15.247(d) / RSS-247 5.5 – Spurious Conducted Emissions .....</b>	<b>Pass.....</b>	<b>15</b>
<b>FCC 15.205 / RSS-Gen 8.9 – Radiated Emissions in Restricted Frequency Bands....</b>	<b>Pass.....</b>	<b>16</b>
<b>Appendix 1 – Test protocols .....</b>		<b>19 pages</b>
<b>Appendix 2 – Test setup .....</b>		<b>3 pages</b>
<b>Appendix 3 – EUT External Photos .....</b>		<b>5 pages</b>
<b>Appendix 4 – EUT Internal Photos .....</b>		<b>4 pages</b>
<b>Appendix 5 – RF exposure information.....</b>		<b>2 pages</b>

## Product information

### Manufacturers declarations

	<b>Transceiver</b>
Operating frequency range	2410 - 2472 MHz
Type of modulation	GFSK
Number of channels	32
Channel separation	2 MHz
Type of antenna	PCB Antenna
Antenna gain (dBi)	0 dBi
Power level	fix
Type of equipment	stand alone radio device
Connection to public utility power line	Yes
Nominal voltage	V <sub>nom</sub> : 1.5VDC
Independent Operation Modes	Transmitting

### Product function and intended use

The equipment under test (EUT) is a race track controller integrated with Bluetooth Low Energy connectivity, powered by battery only. The controller can connect to the race track via BLE function to control the speed of the car which on the track.

**FCC ID: YFA20061668 / IC: 12260A-20061668**

<b>Models</b>	<b>Product description</b>
20061668	GO!!! Plus WIRELESS+ Speed Controller

### Submitted documents

Circuit Diagram  
 Block Diagram  
 Technical Description  
 User manual  
 Label

### Independent Operation Modes

The basic operation modes are:

- Transmitting mode.

For further information refer to User Manual

### **Related Submittal(s) Grants**

This is a single application for certification of the transmitter.

### **Remark**

The test results in this test report are only relevant to the tested sample and does not involve any assessment in the production.

## Test Set-up and Operation Mode

### Principle of Configuration Selection

**Emission:** The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

### Test Operation and Test Software

Test operation should refer to test methodology.

- For radiated emission test, a test mode enabled sample provided by client was used. The method of changing the operation channel was also provided by client.

The setting of the RF output power expected by the customer shall be fixed on the firmware of the final end product.

- For conducted emission testing, a normal functioning sample with AC/DC adaptor mentioned in next section provided by client was used.

### Special Accessories and Auxiliary Equipment

- none

### Countermeasures to achieve EMC Compliance

- none

## Test Methodology

### Radiated Emission

The radiated emission measurements of the transmitter part were performed according to the procedures in ANSI C63.10-2013.

For measurement below 1GHz - the equipment under test (EUT) was placed at the middle of the 80 cm height turntable. For measurement above 1GHz - the EUT was placed at the middle of the 1.5 m height turntable and RF absorbing material was placed on ground plane between turntable and measuring antenna. During the testing, the EUT was operated standalone and arranged for maximum emissions. The EUT was tested in three orthogonal planes.

The investigation is performed with the EUT rotated 360°, the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations. Repeat the measurement steps until the maximum emissions were obtained.

All radiated tests were performed at an antenna to EUT with 3 meters distance, unless stated otherwise in particular parts of this test report.

### Field Strength Calculation

The field strength at 3 m was established by adding the meter reading of the spectrum analyzer to the factors associated with antenna correction factor, cable loss, preamplifiers and filter attenuation.

The equation is expressed as follow:

$$FS = R + AF + CF + FA - PA$$

Where FS = Field Strength in dBuV/m at 3 meters.

R = Reading of Spectrum Analyzer in dBuV.

AF = Antenna Factor in dB.

CF = Cable Attenuation Factor in dB.


FA = Filter Attenuation Factor in dB.

PA = Preamplifier Factor in dB.

FA and PA are only be used for the measuring frequency above 1 GHz.


## Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test




**Note:** Measurements above 1 GHz are done with a table height of 1.5m. In addition, there is RF absorbing material on the floor of the test site for above 1GHz measurement.

Diagram of Measurement Equipment Configuration for Mains Conduction Measurement (if applicable)





**Diagram of Equipment Configuration for Antenna-port Conducted Measurement (if applicable)**



## List of Test and Measurement Instruments

**Hong Kong Productivity Council (FCC/ IC Registration number: 90656/ 4780A-1)**

### Radiated Emission

Equipment	Manufacturer	Type	Cal. Date	Due Date
Semi-anechoic Chamber	Frankonia	Nil	25-Apr-17	25-Apr-18
Test Receiver	R & S	ESU26	11-Jul-17	11-Jul-18
Active Loop Antenna	EMCO	6502	27-Oct-16	27-Oct-17
Bi-conical Antenna	R & S	HK116	1-Sep-15	1-Sep-17
Log Periodic Antenna	R & S	HL223	1-Sep-15	1-Sep-17
Standard Gain Horn	ETS-Lindgren	3160-07	3-Mar-16	3-Mar-18
Standard Gain Horn	ETS-Lindgren	3160-08	3-Mar-16	3-Mar-18
Standard Gain Horn	ETS-Lindgren	3160-10	3-Mar-16	3-Mar-18
Double-Ridged Waveguide Horn	EMCO	3116	17-Jun-16	17-Jun-18
Double-Ridged Waveguide Horn	EMCO	3117	22-Jun-16	22-Jun-18
Coaxial cable	Harbour	LL335	10-Jun-16	10-Jun-18
High Frequency Cable	Pasternack	PE3VNA4001-3M	27-Jan-17	27-Jan-18
Microwave amplifier 0.5-26.5GHz, 25dB gain	HP	83017A	18-Jul-16	18-Jul-18
Preamplifier 18GHz to 40GHz with cable (EMC656)	A.H. Systems, Inc.	PAM-1840VH	27-Jan-17	27-Jan-18
High Pass Filter (cutoff freq. =1000MHz)	Trilithic	23042	28-Oct-15	28-Oct-17

### TÜV Rheinland Hong Kong Ltd

#### Radio Test

Equipment	Manufacturer	Type	Cal. Date	Due Date
Spectrum Analyzer	R&S	FSV40	22 Jan 2017	22 Jan 2018

## Measurement Uncertainty

The estimated combined standard uncertainty for power-line conducted emissions measurements is  $\pm 2.42\text{dB}$ .

The estimated combined standard uncertainty for radiated emissions measurements is  $\pm 4.81\text{dB}$  (9kHz to 30MHz) and  $\pm 4.62\text{dB}$  (30MHz to 200MHz) and  $\pm 5.67\text{dB}$  (200MHz to 1000MHz) and is  $\pm 5.07\text{dB}$  (1GHz to 8.2GHz) and  $\pm 4.58\text{dB}$  (8.2GHz to 12.4GHz) and  $\pm 4.78\text{dB}$  (12.4GHz to 18GHz)

The estimated combined standard uncertainty for antenna conducted emission is  $\pm 2.1\text{dB}$

The reported expanded uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor of  $k=2$ , which for the level of confidence is approximately 95%.

## Results FCC Part 15 – Subpart C / RSS-247 Issue 2

FCC 15.203 – Antenna Requirement 1		Pass
<b>FCC Requirement:</b> No antenna other than that furnished by the responsible party shall be used with the device		
<b>Results</b>	: a) Antenna type : b) Manufacturer and model no : c) Peak Gain	Integral PCB antenna N/A 0 dBi
<b>Verdict</b>	: Pass	

FCC 15.204 – Antenna Requirement 2		N/A
<b>FCC Requirement:</b> An intentional radiator may be operated only with the antenna with which it is authorized. If an antenna is marketed with the intentional radiator, it shall be of a type which is authorized with the intentional radiator.		
<b>Results</b>	: Only one integral antenna can be used.	
<b>Verdict</b>	: N/A	

RSS-Gen 6.3 – External Control		Pass
<b>IC Requirement</b> : The device shall not have any external controls accessible to the user that enable it to be adjusted, selected or programmed to operate in violation of the limits prescribed in the applicable RSS.		
<b>Results</b>	: The device does not have any transmitter external controls accessible to the user that can be adjusted and operated in violation of the limits of this standard.	
<b>Verdict</b>	: Pass	

RSS-Gen 8.3 – Antenna Requirement		Pass
<b>IC Requirement</b> : When a measurement at the antenna connector is used to determine RF output power, the effective gain of the device's antenna shall be stated, based on measurement or on data from the antenna manufacturer.		
<b>Results</b>	: a) Antenna type : b) Manufacturer : c) model no : d) Gain with reference to an isotropic radiator	Fixed Integral wire antenna N/A N/A 0 dBi
<b>Verdict</b>	: Pass	

<b>FCC 15.207 / RSS-Gen 8.8 – Conducted Emission on AC Mains</b>	<b>N/A</b>
There is no AC power input or output ports on the EUT.	

FCC 15.247 (a)(2) / RSS-247 5.2 – 6dB Bandwidth Measurement		Pass	
FCC Requirement: Systems using digital modulation techniques may operate in the 902 – 928 MHz, 2400 – 2483.5 MHz, and 5725 – 5850 MHz bands. The minimum 6dB bandwidth shall be at least 500kHz.			
Test Specification : ANSI C63.10 – 2013 Mode of operation : TX mode Port of testing : Temporary antenna port Detector : Peak Supply voltage : 1.5 VDC Temperature : 23°C Humidity : 50%			
Results : For test protocols please refer to Appendix 1			
Channel frequency (MHz)	6 dB left (MHz)	6 dB right (MHz)	6dB bandwidth (kHz)
2410	2409.652	2410.426	774.000
2440	2439.628	2440.456	828.000
2472	2471.634	2472.492	858.000

RSS-Gen 6.6 – Occupied Bandwidth		Pass	
IC Requirement : N/A			
Test Specification : RSS-Gen Mode of operation : Tx mode Port of testing : Temporary antenna port Detector : Peak Supply voltage : 1.5 VDC Temperature : 23°C Humidity : 50%			
Results : Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types.  For test protocols refer to Appendix 1.			
Frequency (MHz)	Left (MHz)	Right (MHz)	99% bandwidth (MHz)
2410	2409.470	2410.620	1.150
2440	2439.460	2440.610	1.150
2472	2471.490	2472.630	1.140

<b>FCC 15.247(b)(3) / RSS-247 5.4 – Maximum Peak Conducted Output Power</b>			<b>Pass</b>
<b>FCC Requirement:</b> For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850MHz bands: 1 Watt (30dBm)			
Test Specification : ANSI C63.10 – 2013 Mode of operation : TX mode Port of testing : Temporary antenna port Detector : Peak Supply voltage : 1.5 VDC Temperature : 23°C Humidity : 50%			
<b>Results</b> : For test protocols please refer to Appendix 1			
<b>Frequency (MHz)</b>	<b>Measured Output Power (dBm)</b>	<b>Limit (W/dBm)</b>	<b>Verdict</b>
2410	-6.25	1 / 30.0	Pass
2440	-5.42	1 / 30.0	Pass
2472	-5.01	1 / 30.0	Pass

<b>FCC 15.247(e) / RSS-247 5.2 – Power Spectral Density</b>			<b>Pass</b>
<b>FCC Requirement:</b> For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.			
Test Specification : ANSI C63.10 – 2013 Mode of operation : TX mode Port of testing : Temporary antenna port Detector : Peak Supply voltage : 1.5 VDC Temperature : 23°C Humidity : 50%			
<b>Results</b> : For test protocols please refer to Appendix 1.			
<b>Operating frequency (MHz)</b>	<b>Power density (dBm)</b>	<b>Limit (dBm)</b>	<b>Verdict</b>
2410	-9.72	8.0	Pass
2440	-8.82	8.0	Pass
2472	-7.32	8.0	Pass

FCC 15.247(d) / RSS-247 5.5 – Spurious Conducted Emissions					Pass
<b>FCC Requirement:</b> In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.					
Test Specification : ANSI C63.10 – 2013 Mode of operation : TX mode Port of testing : Temporary antenna port Detector : Peak Supply voltage : 1.5 VDC Temperature : 23 °C Humidity : 50 %					
<b>Results</b> : Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and data rate.  Only the worst cases is shown below. For test protocols refer to Appendix 1					
Operating frequency (MHz)	Spurious frequency (MHz)	Spurious Level (dBm)	Reference value (dBm)	Delta (dB)	Verdict
2410	4820.000	-40.98	-9.72	31.26	Pass
2440	2628.000	-55.72	-8.82	46.90	Pass
	4880.000	-33.82	-8.82	25.00	Pass
2472	2492.000	-50.47	-7.32	43.15	Pass
	4940.000	-32.47	-7.32	25.15	Pass

<b>FCC 15.205 / RSS-Gen 8.9 – Radiated Emissions in Restricted Frequency Bands</b>			<b>Pass</b>
<b>FCC Requirement:</b> In any 100kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in section 15.205(a), must also comply with the radiated emission limits specified in section 15.205(c).			
Test Specification : ANSI C63.10 – 2013 Mode of operation : TX mode Port of testing : Enclosure Detector : Peak Supply voltage : 1.5 VDC Temperature : 23°C Humidity : 50%			
<b>Results</b> : Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and data rate.  All three transmit frequency modes comply with the field strength within the restricted bands. There is no spurious found below 30MHz.			
Mode: 2410MHz TX		Vertical Polarization	
<b>Freq MHz</b>	<b>Level dBuV/m</b>	<b>Limit/ Detector dBuV/m</b>	
2390.417	46.18	74.0 / PK	
2390.417	32.52	54.0 / AV	
4819.808	61.32	74.0 / PK	
4816.839	38.43	54.0 / AV	
Mode: 2410MHz TX		Horizontal Polarization	
<b>Freq MHz</b>	<b>Level dBuV/m</b>	<b>Limit/ Detector dBuV/m</b>	
2390.096	45.23	74.0 / PK	
2390.096	32.46	54.0 / AV	
4819.551	68.70	74.0 / PK	
4819.967	38.50	54.0 / AV	
Mode: 2440MHz TX		Vertical Polarization	
<b>Freq MHz</b>	<b>Level dBuV/m</b>	<b>Limit/ Detector dBuV/m</b>	
4879.904	64.70	74.0 / PK	
4880.128	38.83	54.0 / AV	
Mode: 2440MHz TX		Horizontal Polarization	
<b>Freq MHz</b>	<b>Level dBuV/m</b>	<b>Limit/ Detector dBuV/m</b>	
4880.160	69.20	74.0 / PK	
4880.160	38.69	54.0 / AV	



Mode: 2472MHz TX		Vertical Polarization	
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m	
2483.404	45.49	74.0 / PK	
2483.404	32.50	54.0 / AV	
4944.705	67.66	74.0 / PK	
4944.705	38.77	54.0 / AV	
Mode: 2472MHz TX		Horizontal Polarization	
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m	
2482.750	48.99	74.0 / PK	
2482.750	32.50	54.0 / AV	
4943.487	64.23	74.0 / PK	
4943.840	38.86	54.0 / AV	