

# Appendix 5

## RF Exposure Information

FCC ID: YFA370410530  
IC ID: 12260A-370410530

**Maximum transmitter power:**

Frequency (MHz)	Maximum peak output power (dBm)	Output power (mW)
2418	4.87	3.070
2440	3.27	2.124
2465	3.17	2.075

Note: The maximum peak field strength was taken from table of “Subclause 15.249(a)/RSS-210 B.10(a) – Field Strength of Fundamental and Harmonics”.

**For FCC**

According to KDB 447498 D01:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤5 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$

for 1-g SAR and ≤7.5 for 10-g extremity SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

**Result:**

$$(3.070/5) \cdot \sqrt{2418} = 0.955 < 3.0$$

$$(2.124/5) \cdot \sqrt{2440} = 0.664 < 3.0$$

$$(2.075/5) \cdot \sqrt{2465} = 0.652 < 3.0$$

**Conclusion:**

No SAR is required.

**For ISED**

According to table 1 in RSS-102 Issue 5, below exemption limit is applied

Frequency: 2418MHz

At separation distance of ≤ 5mm

Exemption limits: 4mW

**Results:**

max. power of channel = 3.07mW < 4mW

**Conclusion:**

The maximum peak output power of the transmitter is less than the SAR evaluation exemption threshold and hence it complies with the RSS-102 RF exposure requirement