



|  |  |   |                             |  |
|--|--|---|-----------------------------|--|
| <b>Prüfbericht-Nr.:</b><br><i>Test Report No.:</i>   | <b>CN23BR6N 001</b>  | <b>Auftrags-Nr.:</b><br><i>Order No.:</i>   | <b>158269339</b>            | <b>Seite 1 von 16</b><br><i>Page 1 of 16</i>     |
| <b>Kunden-Referenz-Nr.:</b><br><i>Client Reference No.:</i>  | <b>N/A</b>   | <b>Auftragsdatum:</b><br><i>Order date:</i>   | <b>20.04.2023</b>           |  |
| <b>Auftraggeber:</b><br><i>Client:</i>   | <b>Carrera Toys GmbH</b><br><b>Rennbahn Allee 1, 5412 Puch, Salzburg, Austria</b>          |   |                             |  |
| <b>Prüfgegenstand:</b><br><i>Test item:</i>  | <b>Short Range Device - Remote Control Toy Transmitter (2.4GHz)</b>                        |   |                             |  |
| <b>Bezeichnung / Typ-Nr.:</b><br><i>Identification / Type No.:</i>   | <b>370410539</b>   |   |                             |  |
| <b>Auftrags-Inhalt:</b><br><i>Order content:</i>   | <b>FCC and ISED Certification</b>  |   |                             |  |
| <b>Prüfgrundlage:</b><br><i>Test specification:</i>  | <b>FCC Part 15 Subpart C, ANSI C63.10-2013</b><br><b>RSS-210 Issue 10, RSS-Gen Issue 5</b> |   |                             |  |
| <b>Wareneingangsdatum:</b><br><i>Date of receipt:</i>  | <b>24.04.2023</b>  |        |                             |  |
| <b>Prüfmuster-Nr.:</b><br><i>Test sample No.:</i>  | <b>A003462855-001</b>  |   |                             |  |
| <b>Prüfzeitraum:</b><br><i>Testing period:</i>   | <b>27.04.2023 - 28.04.2023</b>   |   |                             |  |
| <b>Ort der Prüfung:</b><br><i>Place of testing:</i>  | <b>Hong Kong</b>   |   |                             |  |
| <b>Prüflaboratorium:</b><br><i>Testing laboratory:</i>   | <b>TÜV Rheinland Hong Kong Ltd.</b>  |   |                             |  |
| <b>Prüfergebnis*:</b><br><i>Test result*:</i>  | <b>Pass</b>  |   |                             |  |
| <b>geprüft von / tested by:</b>  |  | <b>kontrolliert von / reviewed by:</b>  |                             |  |
|   |  |      |                             |  |
| <b>Datum</b><br><i>Date</i>  | <b>Name / Stellung</b><br><i>Name / Position</i>   | <b>Unterschrift</b><br><i>Signature</i>   | <b>Datum</b><br><i>Date</i> | <b>Name / Stellung</b><br><i>Name / Position</i> |
| 05.05.2023   | Eddy Tsang / Engineer  |   | 05.05.2023                  | Sharon Li / Unit Senior Manager                  |
| <b>Sonstiges / Other:</b>  |  | <b>FCC ID: YFA370410539</b><br><b>IC ID: 12260A-370410539</b>                             |                             |  |
| <p>"Decision Rule" document announced in our website (<a href="https://www.tuv.com/landingpage/en/qm-gcn/">https://www.tuv.com/landingpage/en/qm-gcn/</a>) describes the statement of conformity and its rule of enforcement for test results are applicable throughout this test report.</p>  |  |   |                             |  |
| <b>Zustand des Prüfgegenstandes bei Anlieferung:</b><br><i>Condition of the test item at delivery:</i>   |  | <b>Prüfmuster vollständig und unbeschädigt</b><br><i>Test item complete and undamaged</i> |                             |  |
| <p>* Legende: 1 = sehr gut    2 = gut    3 = befriedigend    4 = ausreichend    5 = mangelhaft<br/> P(ass) = entspricht o.g. Prüfgrundlage(n)    F(ail) = entspricht nicht o.g. Prüfgrundlage(n)    N/A = nicht anwendbar    N/T = nicht getestet</p> <p>Legend: 1 = very good    2 = good    3 = satisfactory    4 = sufficient    5 = poor<br/> P(ass) = passed a.m. test specification(s)    F(ail) = failed a.m. test specification(s)    N/A = not applicable    N/T = not tested</p> |  |   |                             |  |
| <p><b>Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.</b><br/> <i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i></p>                        |  |   |                             |  |

# Table of Content

|  | <b>Page</b>  |
|--|--------------|
| <b>Cover Page</b> .....  | <b>1</b>     |
| <b>Table of Content</b> .....  | <b>2</b>     |
| <b>Product information</b> .....   | <b>4</b>     |
| Manufacturers declarations .....   | 4            |
| Product function and intended use .....  | 4            |
| Submitted documents.....   | 4            |
| Independent Operation Modes .....  | 4            |
| Related Submittal(s) Grants .....  | 4            |
| Remark .....   | 4            |
| <b>Test Set-up and Operation Mode</b> .....                                      | <b>5</b>     |
| Principle of Configuration Selection .....                                       | 5            |
| Test Operation and Test Software .....   | 5            |
| Special Accessories and Auxiliary Equipment .....                                | 5            |
| <b>Test Methodology</b> .....  | <b>6</b>     |
| Radiated Emission .....  | 6            |
| Field Strength Calculation.....  | 6            |
| <b>Test Setup Diagram</b> .....  | <b>7</b>     |
| <b>Test Facility</b> .....   | <b>8</b>     |
| Test Laboratory Information .....  | 8            |
| <b>List of Test and Measurement Instruments</b> .....                            | <b>9</b>     |
| <b>Measurement Uncertainty</b> .....   | <b>10</b>    |
| <b>Results FCC Part 15 – Subpart C / RSS-210 Issue 10</b> .....                  | <b>11</b>    |
| FCC 15.203 – Antenna Requirement 1 .....   | Pass..... 11 |
| FCC 15.204 – Antenna Requirement 2 .....   | Pass..... 11 |
| RSS-Gen 6.3 – External Control.....  | Pass..... 11 |
| RSS-Gen 8.3 – Antenna Requirement .....  | Pass..... 11 |
| FCC 15.207 / RSS-Gen 8.8 – Conducted Emission on AC Mains .....                  | N/A..... 11  |
| FCC 15.215 (c) – 20 dB Bandwidth .....   | Pass..... 12 |
| RSS-Gen 6.6 – Occupied Bandwidth.....  | Pass..... 12 |
| FCC 15.249(a) / RSS-210 B.10(a) – Field Strength of Fundamental and Harmonics .. | Pass..... 13 |
| FCC 15.249(d), 15.205 / RSS-210 B.10(b) – Out Of Band Radiated Emission .....    | Pass..... 16 |

|  |                |
|--|----------------|
| <b>Appendix 1 – Test protocols .....</b>         | <b>5 pages</b> |
| <b>Appendix 2 – Test setup .....</b>             | <b>3 pages</b> |
| <b>Appendix 3 – EUT External Photos .....</b>    | <b>4 pages</b> |
| <b>Appendix 4 – EUT Internal Photos .....</b>    | <b>4 pages</b> |
| <b>Appendix 5 – RF exposure information.....</b> | <b>2 pages</b> |

## Product information

### Manufacturers declarations

|   | <b>Transmitter</b>          |
|---|-----------------------------|
| Operating frequency range               | 2405 - 2475MHz              |
| Type of modulation                      | GFSK                        |
| Number of channels                      | 70                          |
| Type of antenna                         | Fixed Integral wire antenna |
| Power level                             | fix                         |
| Connection to public utility power line | No                          |
| Nominal voltage                         | 3.0 VDC                     |

### Product function and intended use

The equipment under test (EUT) is a radio control toy transmitter operating at 2.4GHz. It is powered by battery only.

FCC ID: YFA370410539 / IC ID: 12260A-370410539

| <b>Models</b> | <b>Product description</b>                                   |
|---------------|--|
| 370410539     | Short Range Device - Remote Control Toy Transmitter (2.4GHz) |

### Submitted documents

Nil

### Independent Operation Modes

The basic operation modes are:

- Transmitting mode.

For further information refer to User Manual

### Related Submittal(s) Grants

This is a single application for certification of the transmitter.

### Remark

The test results in this test report are only relevant to the tested sample and does not involve any assessment in the production.

## Test Set-up and Operation Mode

### Principle of Configuration Selection

**Emission:** The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

### Test Operation and Test Software

Test operation should refer to test methodology.

- Test mode samples with maximum RF output power and duty cycle and capable to transmit continuously at the lowest, middle and highest frequency channels is provided by the applicant for the testing.

### Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:

- None

## Test Methodology

### Radiated Emission

The radiated emission measurements of the transmitter part were performed according to the procedures in ANSI C63.10-2013.

For measurement below 1GHz - the equipment under test (EUT) was placed at the middle of the 80 cm height turntable. For measurement above 1GHz - the EUT was placed at the middle of the 1.5 m height turntable and RF absorbing material was placed on ground plane between turntable and measuring antenna. During the testing, the EUT was operated standalone and arranged for maximum emissions. The EUT was tested in three orthogonal planes.

The investigation is performed with the EUT rotated 360°, the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations. Repeat the measurement steps until the maximum emissions were obtained.

All radiated tests were performed at an antenna to EUT with 3 meters distance, unless stated otherwise in particular parts of this test report.

### Field Strength Calculation

The field strength at 3 m was established by adding the meter reading of the spectrum analyzer to the factors associated with antenna correction factor, cable loss, preamplifiers and filter attenuation.

The equation is expressed as follow:


$$FS = R + AF + CF + FA - PA$$

Where FS = Field Strength in dBuV/m at 3 meters.  
R = Reading of Spectrum Analyzer in dBuV.  
AF = Antenna Factor in dB.  
CF = Cable Attenuation Factor in dB.  
FA = Filter Attenuation Factor in dB.  
PA = Preamplifier Factor in dB.

FA and PA are only be used for the measuring frequency above 1 GHz.


## Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test



Note: Measurements above 1 GHz are done with a table height of 1.5m. In addition, there is RF absorbing material on the floor of the test site for above 1GHz measurement.

Diagram of Measurement Equipment Configuration for Mains Conduction Measurement (if applicable)



## Test Facility

### Test Laboratory Information

TÜV Rheinland Hong Kong Ltd.

Address: 3-4/F, Fou Wah Industrial Building, 10-16 Pun Shan Street, Tsuen Wan, N.T., Hong Kong

Tel.: +852 2192 1000

Fax: +852 2192 1001

Email [service-gc@tuv.com](mailto:service-gc@tuv.com)

The test facility is recognized or accredited by the following organizations:

#### FCC

Test Firm Registration Number : 371735

#### ISED/IC

Test Site Registration Number : 26152



## List of Test and Measurement Instruments

### Radiated Emission

| Equipment                                       | Manufacturer          | Type                  | Cal. Date | Due Date  |
|---|-----------------------|-----------------------|-----------|-----------|
| Semi-anechoic Chamber                           | Frankonia             | Nil                   | 3-Mar-23  | 3-Mar-24  |
| Multi-functional Anechoic Chamber               | Albatross             | Nil                   | 4-Jan-23  | 4-Jan-24  |
| Test Receiver                                   | R & S                 | ESU40                 | 9-Mar-23  | 9-Mar-24  |
| Active Loop Antenna                             | EMCO                  | 6502                  | 3-Nov-22  | 3-Nov-24  |
| Bi-conical Antenna                              | R & S                 | HK116                 | 24-Oct-22 | 24-Oct-24 |
| Log Periodic Antenna                            | R & S                 | HL223                 | 25-Oct-22 | 25-Oct-24 |
| Standard Gain Horn                              | ETS-Lindgren          | 3160-07               | 25-Nov-22 | 25-Nov-24 |
| Standard Gain Horn                              | ETS-Lindgren          | 3160-08               | 25-Nov-22 | 25-Nov-24 |
| Standard Gain Horn                              | ETS-Lindgren          | 3160-10               | 30-Nov-22 | 30-Nov-24 |
| Double-Ridged Waveguide Horn                    | EMCO                  | 3116                  | 30-Nov-22 | 30-Nov-24 |
| Double-Ridged Waveguide Horn                    | EMCO                  | 3117                  | 21-Nov-22 | 21-Nov-24 |
| Coaxial cable                                   | Harbour               | SF118/11n/11n/12000.0 | 3-Aug-22  | 3-Aug-24  |
| High Frequency Cable                            | Pasternack            | PE3VNA4001-3M         | 29-Jan-23 | 29-Jan-25 |
| Microwave amplifier 0.5-26.5GHz, 25dB gain      | COM-POWER Corporation | PAM-118A              | 3-Mar-23  | 3-Mar-24  |
| Preamplifier 18GHz to 40GHz with cable (EMC656) | A.H. Systems, Inc.    | PAM-1840VH            | 27-Jan-23 | 27-Jan-24 |
| High Pass Filter (cutoff freq. =1000MHz)        | Trilithic             | 23042                 | 30-Oct-21 | 30-Oct-23 |

### Radio Test

| Equipment                    | Manufacturer | Type  | Cal. Date | Due Date  |
|------------------------------|--------------|-------|-----------|-----------|
| Signal and Spectrum Analyzer | R & S        | FSP30 | 31-Jan-23 | 31-Jan-24 |

## Measurement Uncertainty

The estimated combined standard uncertainty for power-line conducted emissions measurements is  $\pm 2.42$ dB.

The estimated combined standard uncertainty for radiated emissions measurements is  $\pm 4.81$ dB (9kHz to 30MHz) and  $\pm 4.62$ dB (30MHz to 200MHz) and  $\pm 5.67$ dB (200MHz to 1000MHz) and is  $\pm 5.07$ dB (1GHz to 8.2GHz) and  $\pm 4.58$ dB (8.2GHz to 12.4GHz) and  $\pm 4.78$ dB (12.4GHz to 18GHz)

The reported expanded uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor of  $k=2$ , which for the level of confidence is approximately 95%.

## Results FCC Part 15 – Subpart C / RSS-210 Issue 10

|  |  |                             |
|--|--|-----------------------------|
| <b>FCC 15.203 – Antenna Requirement 1</b>  |  | <b>Pass</b>                 |
| <b>FCC Requirement:</b> No antenna other than that furnished by the responsible party shall be used with the device  |  |                             |
| <b>Results:</b>  | a) Antenna type:   | Fixed Integral wire antenna |
|  | b) Manufacturer and model no:  | N/A                         |
|  | c) Peak Gain:  | 0 dBi                       |
| <b>Verdict:</b>  | Pass   |                             |
| <b>FCC 15.204 – Antenna Requirement 2</b>  |  | <b>Pass</b>                 |
| <b>FCC Requirement:</b> An intentional radiator may be operated only with the antenna with which it is authorized. If an antenna is marketed with the intentional radiator, it shall be of a type which is authorized with the intentional radiator. |  |                             |
| <b>Results:</b>  | Only one integral antenna can be used.   |                             |
| <b>Verdict:</b>  | Pass   |                             |
| <b>RSS-Gen 6.3 – External Control</b>  |  | <b>Pass</b>                 |
| <b>IC Requirement:</b> The device shall not have any external controls accessible to the user that enable it to be adjusted, selected or programmed to operate in violation of the limits prescribed in the applicable RSS.                          |  |                             |
| <b>Results:</b>  | The device does not have any transmitter external controls accessible to the user that can be adjusted and operated in violation of the limits of this standard. |                             |
| <b>Verdict:</b>  | Pass   |                             |
| <b>RSS-Gen 8.3 – Antenna Requirement</b>   |  | <b>Pass</b>                 |
| <b>IC Requirement:</b> When a measurement at the antenna connector is used to determine RF output power, the effective gain of the device's antenna shall be stated, based on measurement or on data from the antenna manufacturer.                  |  |                             |
| <b>Results:</b>  | a) Antenna type:   | Fixed Integral wire antenna |
|  | b) Manufacturer  | N/A                         |
|  | c) Model no  | N/A                         |
|  | d) Gain with reference to an isotropic radiator:   | 0 dBi                       |
| <b>Verdict:</b>  | Pass   |                             |
| <b>FCC 15.207 / RSS-Gen 8.8 – Conducted Emission on AC Mains</b>   |  | <b>N/A</b>                  |
| There is no AC power input or output ports on the EUT.   |  |                             |

| <b>FCC 15.215 (c) – 20 dB Bandwidth</b>   |                  | <b>Pass</b> |                   |             |
|---|------------------|-------------|-------------------|-------------|
| Test Specification : ANSI C63.10 – 2013<br>Test date : 28.04.2023<br>Mode of operation : Tx mode<br>Port of testing : Antenna port<br>Supply voltage : 3.0 VDC<br>Temperature : 20°C<br>Humidity : 55%                  |                  |             |                   |             |
| Requirement: The intentional radiators must be designed to ensure that the 20dB bandwidth of the emission, is contained within the frequency band designated in the rule section under which the equipment is operated. |                  |             |                   |             |
| <b>Results:</b> Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types.<br>For test protocols refer to Appendix 1.                  |                  |             |                   |             |
| Frequency (MHz)   | 20 dB left (MHz) | Limit (MHz) | 20 dB right (MHz) | Limit (MHz) |
| 2405  | 2404.388         | > 2400      | 2405.598          | < 2483.5    |
| 2439  | 2438.393         | > 2400      | 2439.683          | < 2483.5    |
| 2475  | 2474.388         | > 2400      | 2475.688          | < 2483.5    |

| <b>RSS-Gen 6.6 – Occupied Bandwidth</b>  |            | <b>Pass</b> |                     |  |
|--|------------|-------------|---------------------|--|
| <b>FCC/ IC Requirement : N/A</b>   |            |             |                     |  |
| Test Specification : RSS-Gen<br>Test date : 28.04.2023<br>Mode of operation : Tx mode<br>Port of testing : Antenna port<br>Supply voltage : 3.0 VDC<br>Temperature : 20°C<br>Humidity : 55%            |            |             |                     |  |
| <b>Results:</b> Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types.<br>For test protocols refer to Appendix 1. |            |             |                     |  |
| Frequency (MHz)  | Left (MHz) | Right (MHz) | 99% bandwidth (MHz) |  |
| 2405   | 2404.433   | 2405.555    | 1.123               |  |
| 2439   | 2438.428   | 2439.568    | 1.140               |  |
| 2475   | 2474.418   | 2475.583    | 1.165               |  |

| <b>FCC 15.249(a) / RSS-210 B.10(a) – Field Strength of Fundamental and Harmonics</b>  |                 |                            | <b>Pass</b> |
|---|-----------------|----------------------------|-------------|
| Test Specification : ANSI C63.10 – 2013<br>Test date : 27.04.2023<br>Mode of operation : Tx mode<br>Port of testing : Enclosure<br>Frequency range : 9kHz – 25GHz<br>Supply voltage : 3.0 VDC<br>Temperature : 21°C<br>Humidity : 59% |                 |                            |             |
| Requirement: The field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following limit.  |                 |                            |             |
| <b>Results:</b> PASS  |                 |                            |             |
| Fundamental Frequency 2405MHz   |                 | Vertical Polarization      |             |
| Frequency<br>MHz  | Level<br>dBuV/m | Limit / Detector<br>dBuV/m |             |
| 2405.000  | 77.5            | 114.0 / PK                 |             |
| 2405.000  | 41.8            | 94.0 / AV                  |             |
| Fundamental Frequency 2405MHz   |                 | Horizontal Polarization    |             |
| Frequency<br>MHz  | Level<br>dBuV/m | Limit / Detector<br>dBuV/m |             |
| 2405.038  | 80.9            | 114.0 / PK                 |             |
| 2405.038  | 44.9            | 94.0 / AV                  |             |
| Harmonics 2405MHz   |                 | Vertical Polarization      |             |
| Frequency<br>MHz  | Level<br>dBuV/m | Limit / Detector<br>dBuV/m |             |
| 4809.503  | 50.0            | 74.0 / PK                  |             |
| 4809.503  | 28.1            | 54.0 / AV                  |             |
| Harmonics 2405MHz   |                 | Horizontal Polarization    |             |
| Frequency<br>MHz  | Level<br>dBuV/m | Limit / Detector<br>dBuV/m |             |
| 4810.000  | 46.5            | 74.0 / PK                  |             |
| 4810.000  | 22.9            | 54.0 / AV                  |             |

| Fundamental Frequency 2439MHz |                 | Vertical Polarization      |  |
|-------------------------------|-----------------|----------------------------|--|
| Frequency<br>MHz              | Level<br>dBuV/m | Limit / Detector<br>dBuV/m |  |
| 2439.038                      | 76.5            | 114.0 / PK                 |  |
| 2439.038                      | 40.5            | 94.0 / AV                  |  |
| Fundamental Frequency 2439MHz |                 | Horizontal Polarization    |  |
| Frequency<br>MHz              | Level<br>dBuV/m | Limit / Detector<br>dBuV/m |  |
| 2438.945                      | 79.1            | 114.0 / PK                 |  |
| 2438.945                      | 43.1            | 94.0 / AV                  |  |
| Harmonics 2439MHz             |                 | Vertical Polarization      |  |
| Frequency<br>MHz              | Level<br>dBuV/m | Limit / Detector<br>dBuV/m |  |
| No peak found                 | ---             | 74.0 / PK                  |  |
| No peak found                 | ---             | 54.0 / AV                  |  |
| Harmonics 2439MHz             |                 | Horizontal Polarization    |  |
| Frequency<br>MHz              | Level<br>dBuV/m | Limit / Detector<br>dBuV/m |  |
| No peak found                 | ---             | 74.0 / PK                  |  |
| No peak found                 | ---             | 54.0 / AV                  |  |

| Fundamental Frequency 2475MHz |                 | Vertical Polarization      |  |
|-------------------------------|-----------------|----------------------------|--|
| Frequency<br>MHz              | Level<br>dBuV/m | Limit / Detector<br>dBuV/m |  |
| 2474.814                      | 77.8            | 114.0 / PK                 |  |
| 2474.814                      | 41.6            | 94.0 / AV                  |  |
| Fundamental Frequency 2475MHz |                 | Horizontal Polarization    |  |
| Frequency<br>MHz              | Level<br>dBuV/m | Limit / Detector<br>dBuV/m |  |
| 2475.054                      | 79.9            | 114.0 / PK                 |  |
| 2475.054                      | 44.1            | 94.0 / AV                  |  |
| Harmonics 2475MHz             |                 | Vertical Polarization      |  |
| Frequency<br>MHz              | Level<br>dBuV/m | Limit / Detector<br>dBuV/m |  |
| 4949.519                      | 49.2            | 74.0 / PK                  |  |
| 4949.519                      | 28.3            | 54.0 / AV                  |  |
| Harmonics 2475MHz             |                 | Horizontal Polarization    |  |
| Frequency<br>MHz              | Level<br>dBuV/m | Limit / Detector<br>dBuV/m |  |
| No peak found                 | ---             | 74.0 / PK                  |  |
| No peak found                 | ---             | 54.0 / AV                  |  |

| <b>FCC 15.249(d), 15.205 / RSS-210 B.10(b) – Out Of Band Radiated Emission</b>   |                     | <b>Pass</b>                    |
|--|---------------------|--------------------------------|
| Test Specification : ANSI C63.10 – 2013<br>Test date : 27.04.2023<br>Mode of operation : Tx mode<br>Port of testing : Enclosure<br>Frequency range : 9kHz – 25GHz<br>Supply voltage : 3.0 VDC<br>Temperature : 21°C<br>Humidity : 59%                                      |                     |                                |
| Requirement: Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation. |                     |                                |
| <b>Results:</b> All three transmit frequency modes comply with the field strength limit of section 15.209. There is no spurious found below 30MHz.   |                     |                                |
| Tx frequency 2405MHz   |                     | Vertical Polarization          |
| <b>Frequency MHz</b>   | <b>Level dBuV/m</b> | <b>Limit / Detector dBuV/m</b> |
| 2400.000   | 50.0                | 74.0 / PK                      |
| 2400.000   | 25.9                | 54.0 / AV                      |
| Tx frequency 2405MHz   |                     | Horizontal Polarization        |
| <b>Frequency MHz</b>   | <b>Level dBuV/m</b> | <b>Limit / Detector dBuV/m</b> |
| 2400.000   | 46.9                | 74.0 / PK                      |
| 2400.000   | 25.9                | 54.0 / AV                      |
| Tx frequency 2439MHz   |                     | Vertical Polarization          |
| <b>Frequency MHz</b>   | <b>Level dBuV/m</b> | <b>Limit / Detector dBuV/m</b> |
| No peak found  | ---                 | 74.0 / PK                      |
| No peak found  | ---                 | 54.0 / AV                      |
| Tx frequency 2439MHz   |                     | Horizontal Polarization        |
| <b>Frequency MHz</b>   | <b>Level dBuV/m</b> | <b>Limit / Detector dBuV/m</b> |
| No peak found  | ---                 | 74.0 / PK                      |
| No peak found  | ---                 | 54.0 / AV                      |
| Tx frequency 2475MHz   |                     | Vertical Polarization          |
| <b>Frequency MHz</b>   | <b>Level dBuV/m</b> | <b>Limit / Detector dBuV/m</b> |
| 2483.500   | 45.7                | 74.0 / PK                      |
| 2483.500   | 26.1                | 54.0 / AV                      |
| Tx frequency 2475MHz   |                     | Horizontal Polarization        |
| <b>Frequency MHz</b>   | <b>Level dBuV/m</b> | <b>Limit / Detector dBuV/m</b> |
| 2483.500   | 40.2                | 74.0 / PK                      |
| 2483.500   | 26.1                | 54.0 / AV                      |




# Appendix 1

## Test Results


# 20dB Bandwidth

Tx frequency: 2405MHz




Date: 28.APR.2023 17:46:00

Tx frequency: 2439MHz



Date: 28.APR.2023 17:54:19


Tx frequency: 2475MHz



Date: 28.APR.2023 18:32:21


# 99% Bandwidth

Tx frequency: 2405MHz




Date: 28.APR.2023 17:38:54

Tx frequency: 2439MHz



Date: 28.APR.2023 17:57:53

Tx frequency: 2475MHz




Date: 28.APR.2023 18:08:52

## **Appendix 2**

# **Test Setup Photos**




Set-up for Radiated Emission (9k-30MHz)




Set-up for Radiated Emission (30-200MHz)





Set-up for Radiated Emission (200-1000MHz)



Set-up for Radiated Emission (1GHz above)



# Appendix 3

## EUT External Photos

FCC ID: YFA370410539  
IC ID: 12260A-370410539



External View



External View



External View



External View



External View



External View


# Appendix 4

## EUT Internal Photos

FCC ID: YFA370410539  
IC ID: 12260A-370410539




Internal View




Internal View







Internal View



Internal View



Internal View



Internal View



# Appendix 5

## RF Exposure Information

FCC ID: YFA370410539  
IC ID: 12260A-370410539

**Maximum transmitter power:**

| Frequency (MHz) | Maximum peak output power (dBm) | Output power (mW) |
|-----------------|---------------------------------|-------------------|
| 2405            | -14.33                          | 0.0369            |
| 2439            | -16.13                          | 0.0244            |
| 2475            | -15.33                          | 0.0293            |

Note: The maximum peak field strength was taken from table of "Subclause 15.249(a)/RSS-210 B.10(a) – Field Strength of Fundamental and Harmonics".

**For FCC**

According to KDB 447498 D01:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 5 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$   
 ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

**Result:**

$$(0.0369/5) \cdot \sqrt{2.405} = 0.012 < 3.0$$

$$(0.0244/5) \cdot \sqrt{2.439} = 0.008 < 3.0$$

$$(0.0293/5) \cdot \sqrt{2.475} = 0.009 < 3.0$$

**Conclusion:**

No SAR is required.

**For ISED**

According to table 1 in RSS-102 Issue 5, below exemption limit is applied

Frequency: 2405 MHz

At separation distance of ≤ 5mm

Exemption limits: 4mW

**Results:**

max. power of channel = 0.0369 mW < 4mW

**Conclusion:**

The maximum peak output power of the transmitter is less than the SAR evaluation exemption threshold and hence it complies with the RSS-102 RF exposure requirement