



Produkte  
Products

<b>Prüfbericht - Nr.:</b> 14039872 001 <i>Test Report No.:</i>		Seite 1 von 10 Page 1 of 10	
<b>Auftraggeber:</b> <i>Client:</i>	Stadlbauer Marketing + Vertrieb Ges.M.B.H Rennbahnallee 1 5412 Puch Salzburg Austria		
<b>Gegenstand der Prüfung:</b> <i>Test Item:</i>	Short Range Device - Radio Control Toy Transmitter (2.4GHz)		
<b>Bezeichnung:</b> <i>Identification:</i>	Please refer to "Models" on page 3	<b>Serien-Nr.:</b> <i>Serial No.:</i>	Engineering sample
<b>Wareneingangs-Nr.:</b> <i>Receipt No.:</i>	A000230684-001	<b>Eingangsdatum:</b> <i>Date of Receipt:</i>	21.07.2015
<b>Zustand des Prüfgegenstandes bei Anlieferung:</b> <i>Condition of test item at delivery:</i>	Test sample received is not damaged and suitable for testing.		
<b>Prüfört:</b> <i>Testing Location:</i>	TÜV Rheinland Hong Kong Ltd. 8/F, First Group Centre, 14 Wang Tai Road, Kowloon Bay, Kowloon, Hong Kong <b>Global United Technology Services Co., Ltd.</b> 2nd Floor, Block No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, China		
<b>Prüfgrundlage:</b> <i>Test Specification:</i>	FCC Part 15 Subpart C ANSI C63.4-2009		
<b>Prüfergebnis:</b> <i>Test Results:</i>	Das vorstehend beschriebene Gerät wurde geprüft und entspricht oben genannter Prüfgrundlage. The above mentioned product was tested and <b>passed</b> .		
<b>Prüflaboratorium:</b> <i>Testing Laboratory:</i>	TÜV Rheinland Hong Kong Ltd. 8 - 10/F., Goldin Financial Global Square, 7 Wang Tai Road, Kowloon Bay, Kowloon, Hong Kong		
<b>geprüft/ tested by:</b>	<b>kontrolliert/ reviewed by:</b>		
12.08.2015 <i>Date</i>	Joey Leung Project Engineer <i>Name/Position</i>	 <i>Unterschrift</i> Signature	12.08.2015 <i>Date</i>
			Benny Lau Senior Project Manager <i>Name/Position</i>
			 <i>Unterschrift</i> Signature
<b>Sonstiges:</b> Other Aspects	FCCID: YFA370900025		
<b>Abkürzungen:</b>	P(ass) = entspricht Prüfgrundlage F(ail) = entspricht nicht Prüfgrundlage N/A = nicht anwendbar N/T = nicht getestet	<b>Abbreviations:</b>	P(ass) = passed F(ail) = failed N/A = not applicable N/T = not tested
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any safety mark on this or similar products.</i>			

## Table of Content

	<b>Page</b>
<b>Cover Page</b> .....	<b>1</b>
<b>Table of Content</b> .....	<b>2</b>
<b>Product information</b> .....	<b>3</b>
Manufacturers declarations .....	3
Product function and intended use .....	3
Submitted documents.....	3
Special accessories and auxiliary equipment .....	3
Independent Operation Modes .....	4
Related Submittal(s) Grants .....	4
<b>List of Test and Measurement Instruments</b> .....	<b>5</b>
<b>Results FCC Part 15 – Subpart C</b> .....	<b>6</b>
Subclause 15.207 – Disturbance Voltage on AC Mains.....	N/A ..... 6
Subclause 15.249(d) – Spurious Emissions – Band edge.....	Pass ..... 6
Subclause 15.215 (c) – 20 dB Bandwidth.....	Pass ..... 7
Subclause 15.249 (a) – Field Strength of Fundamental and Harmonics.....	Pass ..... 7
Subclause 15.249 (d) – Emissions radiated outside of the specified frequency bands .	Pass ..... 9
Appendix 1 – Test Results.....	3 pages
Appendix 2 – Test Setup Photos.....	3 pages
Appendix 3 – Photo documentation.....	7 pages
Appendix 4 – Product documentation.....	19 pages
Appendix 5 – RF Exposure Information.....	2 pages

## Product information

### Manufacturers declarations

	<b>Transmitter</b>
Operating frequency range	2402 - 2475 MHz
Type of modulation	GFSK
Number of channels	6
Type of antenna	Integral Antenna
Power level	fix
Connection to public utility power line	No
Nominal voltage	3.0 V

### Product function and intended use

The equipment under test (EUT) is a radio control toy transmitter operating at 2.4GHz. It is powered by battery only.

#### FCCID: YFA370900025

<b>Models</b>	<b>Product description</b>
900025, 370900025	Radio Controlled Toy Transmitter

### Submitted documents

Circuit Diagram  
 Block Diagram  
 Bill of material  
 User manual  
 Rating Label

### Special accessories and auxiliary equipment

The product has been tested together with the following additional accessory:

Nil

### **Independent Operation Modes**

The basic operation mode is transmitting control signal for the RC toy Car.

For further information refer to User Manual

### **Related Submittal(s) Grants**

This is a single application for certification of the transmitter.

## List of Test and Measurement Instruments

Global United Technology Services Co., Ltd. (Registration number: 600491)

### Radiated Emission

Equipment	Manufacturer	Type	S/N	Cal. interval	Last cal.
3m Semi- Anechoic Chamber	ZhongYu Electron	9.0(L)*6.0(W)* 6.0(H)	---	2 year	05 Apr 2015
Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	---	N/A	N/A
ESU EMI Test Receiver	R&S	ESU26	---	1 year	08 Jun 2015
Loop Antenna	Zhinan	ZN30900A	---	1 year	08 Jun 2015
Bi-log Hybrid Antenna	SCHWARZBECK	VULB9163	---	1 year	09 Mar 2015
Double-ridged horn antenna	SCHWARZBECK	9120D	---	1 year	09 Mar 2015
RF Amplifier	HP	8347A	---	1 year	08 Jun 2015
RF Amplifier	HP	8349B	---	1 year	08 Jun 2015
EMI Test Software	AUDIX	E3	---	1 year	N/A
Coaxial cable	GTS	N/A	---	1 year	08 Jun 2015
Coaxial Cable	GTS	N/A	---	1 year	08 Jun 2015
Thermo meter	N/A	N/A	---	1 year	08 Jun 2015

### TÜV Rheinland Hong Kong Ltd.

#### Radio Test

Equipment	Manufacturer	Type	S/N	Cal. interval	Last cal.
Spectrum Analyzer	Rohde & Schwarz	FSP30	100007	1 year	12 Jan 2015

## Results FCC Part 15 – Subpart C

<b>Subclause 15.207 – Disturbance Voltage on AC Mains</b>	<b>N/A</b>
There is no AC power input or output ports on the EUT.	

<b>Subclause 15.249(d) – Spurious Emissions – Band edge</b>	<b>Pass</b>	
Test Specification : ANSI C63.4 – 2009 Mode of operation : Tx mode Port of testing : Enclosure Detector : Peak RBW/VBW : 100 kHz / 300 kHz for $f < 1$ GHz 1 MHz / 3 MHz for $f > 1$ GHz Supply voltage : 3.0VDC, 2 x 1.5V AAA size new battery Temperature : 23°C Humidity : 50%		
Requirement:	Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.	
<b>Results:</b>	PASS	
Tx frequency 2402MHz Vertical Polarization		
<b>Freq MHz</b>	<b>Level dBuV/m</b>	<b>Limit/ Detector dBuV/m</b>
2400.000	71.62	74.0 / P
2400.000	40.34	54.0 / A
Tx frequency 2402MHz Horizontal Polarization		
<b>Freq MHz</b>	<b>Level dBuV/m</b>	<b>Limit/ Detector dBuV/m</b>
2400.000	71.21	74.0 / P
2400.000	42.05	54.0 / A
Tx frequency 2475MHz Vertical Polarization		
<b>Freq MHz</b>	<b>Level dBuV/m</b>	<b>Limit/ Detector dBuV/m</b>
2483.500	44.85	74.0 / P
2483.500	27.81	54.0 / A
Tx frequency 2475MHz Horizontal Polarization		
<b>Freq MHz</b>	<b>Level dBuV/m</b>	<b>Limit/ Detector dBuV/m</b>
2483.500	43.13	74.0 / P
2483.500	26.35	54.0 / A

<b>Subclause 15.215 (c) – 20 dB Bandwidth</b>		<b>Pass</b>		
Test Specification : ANSI C63.4 – 2009 Mode of operation : Tx mode Port of testing : Enclosure RBW/VBW : 100 kHz / 300 kHz Supply voltage : 3.0VDC, 2 x 1.5V AAA size new battery Temperature : 23°C Humidity : 50%				
Requirement: The intentional radiators must be designed to ensure that the 20dB bandwidth of the emission, is contained within the frequency band designated in the rule section under which the equipment is operated.				
<b>Results:</b> For test protocols refer to Appendix 1, page 2-3.				
Frequency (MHz)	20 dB left (MHz)	Limit (MHz)	20 dB right (MHz)	Limit (MHz)
2402	2401.250	> 2400	2402.490	< 2483.5
2433	2432.160	> 2400	2433.500	< 2483.5
2475	2474.100	> 2400	2475.510	< 2483.5

<b>Subclause 15.249 (a) – Field Strength of Fundamental and Harmonics</b>		<b>Pass</b>		
Test Specification : ANSI C63.4 – 2009 Mode of operation : Tx mode Port of testing : Enclosure RBW/VBW : 100 kHz / 300 kHz for f < 1 GHz 1 MHz / 3 MHz for f > 1 GHz Supply voltage : 3.0VDC, 2 x 1.5V AAA size new battery Temperature : 23°C Humidity : 50%				
Requirement: The field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following limit.				
<b>Results:</b> PASS				
Fundamental Frequency 2402MHz		Vertical Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m		
2401.795	72.98	114.0 / P		
2401.795	58.94	94.0 / A		
Fundamental Frequency 2402MHz		Horizontal Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m		
2401.795	82.07	114.0 / P		
2401.795	65.03	94.0 / A		
Harmonics 2402MHz		Vertical Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m		
4804.000	43.79	74.0 / P		

4804.000	34.07	54.0 / A
Harmonics 2402MHz Horizontal Polarization		
<b>Freq MHz</b>	<b>Level dBuV/m</b>	<b>Limit/ Detector dBuV/m</b>
4804.000	43.95	74.0 / P
4804.000	35.24	54.0 / A
Fundamental Frequency 2433MHz Vertical Polarization		
<b>Freq MHz</b>	<b>Level dBuV/m</b>	<b>Limit/ Detector dBuV/m</b>
2432.570	71.06	114.0 / P
2432.570	58.01	94.0 / A
Fundamental Frequency 2433MHz Horizontal Polarization		
<b>Freq MHz</b>	<b>Level dBuV/m</b>	<b>Limit/ Detector dBuV/m</b>
2432.570	79.63	114.0 / P
2432.570	64.58	94.0 / A
Harmonics 2433MHz Vertical Polarization		
<b>Freq MHz</b>	<b>Level dBuV/m</b>	<b>Limit/ Detector dBuV/m</b>
4866.000	43.76	74.0 / P
4866.000	34.12	54.0 / A
Harmonics 2433MHz Horizontal Polarization		
<b>Freq MHz</b>	<b>Level dBuV/m</b>	<b>Limit/ Detector dBuV/m</b>
4866.000	44.40	74.0 / P
4866.000	33.76	54.0 / A
Fundamental Frequency 2475MHz Vertical Polarization		
<b>Freq MHz</b>	<b>Level dBuV/m</b>	<b>Limit/ Detector dBuV/m</b>
2474.795	71.60	114.0 / P
2474.795	58.67	94.0 / A
Fundamental Frequency 2475MHz Horizontal Polarization		
<b>Freq MHz</b>	<b>Level dBuV/m</b>	<b>Limit/ Detector dBuV/m</b>
2474.795	79.42	114.0 / P
2474.795	64.48	94.0 / A
Harmonics 2475MHz Vertical Polarization		
<b>Freq MHz</b>	<b>Level dBuV/m</b>	<b>Limit/ Detector dBuV/m</b>
4950.000	43.33	74.0 / P
4950.000	31.80	54.0 / A
Harmonics 2475MHz Horizontal Polarization		
<b>Freq MHz</b>	<b>Level dBuV/m</b>	<b>Limit/ Detector dBuV/m</b>
4950.000	45.50	74.0 / P
4950.000	32.97	54.0 / A



Subclause 15.249 (d) – Emissions radiated outside of the specified frequency bands Pass		
Test Specification : ANSI C63.4 - 2009 Mode of operation : Tx mode Port of testing : Enclosure Detector : Peak RBW/VBW : 100 kHz / 300 kHz for f < 1 GHz 1 MHz / 3 MHz for f > 1 GHz Supply voltage : 3.0VDC, 2 x 1.5V AAA size new battery Temperature : 23°C Humidity : 50%		
Requirement: Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.		
<b>Results:</b> All three transmit frequency modes comply with the field strength within the restricted bands. There is no spurious found below 30MHz.		
Tx frequency 2402MHz Vertical Polarization		
<b>Freq MHz</b>	<b>Level dBuV/m</b>	<b>Limit/ Detector dBuV/m</b>
No peak found	---	74.0 / P
No peak found	---	54.0 / A
Tx frequency 2402MHz Horizontal Polarization		
<b>Freq MHz</b>	<b>Level dBuV/m</b>	<b>Limit/ Detector dBuV/m</b>
No peak found	---	74.0 / P
No peak found	---	54.0 / A
Tx frequency 2433MHz Vertical Polarization		
<b>Freq MHz</b>	<b>Level dBuV/m</b>	<b>Limit/ Detector dBuV/m</b>
No peak found	---	74.0 / P
No peak found	---	54.0 / A
Tx frequency 2433MHz Horizontal Polarization		
<b>Freq MHz</b>	<b>Level dBuV/m</b>	<b>Limit/ Detector dBuV/m</b>
No peak found	---	74.0 / P
No peak found	---	54.0 / A
Tx frequency 2475MHz Vertical Polarization		
<b>Freq MHz</b>	<b>Level dBuV/m</b>	<b>Limit/ Detector dBuV/m</b>
No peak found	---	74.0 / P
No peak found	---	54.0 / A
Tx frequency 2475MHz Horizontal Polarization		
<b>Freq MHz</b>	<b>Level dBuV/m</b>	<b>Limit/ Detector dBuV/m</b>
No peak found	---	74.0 / P

No peak found	---	54.0 / A
---------------	-----	----------