

# Appendix 5

## RF Exposure Information

FCC ID: YFA370900026I  
IC: 12260A-370900026I

**Maximum transmitter power:**

Frequency (MHz)	Maximum peak output power (dBuV/m)	Output power (mW)
2408	77.88	0.0184
2440	74.78	0.0090
2472	74.79	0.0090

**For FCC**

According to KDB 447498 D01:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and ≤7.5 for 10-g extremity SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2

**Result:**

$$(0.0184/5) \cdot \sqrt{2.408} = 0.006 < 3.0$$

$$(0.0090/5) \cdot \sqrt{2.440} = 0.003 < 3.0$$

$$(0.0090/5) \cdot \sqrt{2.472} = 0.003 < 3.0$$

**Conclusion:**

No SAR is required.

**For ISED**

According to table 1 in RSS-102 Issue 5, below exemption limit at separation distance of ≤ 5mm is applied:

Frequency (MHz)	Exemption limits (mW, by linear interpolation)
2400	4.273
2483.5	3.936

**Conclusion:**

The maximum peak output power of the transmitter is less than the SAR evaluation exemption threshold and hence it complies with the RSS-102 RF exposure requirement without SAR evaluation.