

Produkte
Products

Prüfbericht - Nr.: 14024158 001 <i>Test Report No.:</i>		Seite 1 von 8 <i>Page 1 of 8</i>			
Auftraggeber: <i>Client:</i>		Stadlbauer Marketing + Vertrieb Gesellschaft m.b.H. A-5027 Salzburg Magazinstrasse 4 Austria			
Gegenstand der Prüfung: <i>Test Item:</i>		Short Range Device - Radio Control Toys Transmitter (2.4GHz)			
Bezeichnung: <i>Identification:</i>	900003	Serien-Nr.: <i>Serial No.:</i>	Engineering sample		
Wareneingangs-Nr.: <i>Receipt No.:</i>	00100809092-001	Eingangsdatum: <i>Date of Receipt:</i>	09.08.2010		
Prüfort: <i>Testing Location:</i>	TÜV Rheinland Hong Kong Ltd. 8/F., Niche Centre, 14 Wang Tai Road, Kowloon Bay, Kowloon, Hong Kong Hong Kong Productivity Council HKPC Building, 78 Tat Chee Avenue, Kowloon, Hong Kong				
Prüfgrundlage: <i>Test Specification:</i>	FCC Part 15 Subpart C ANSI C63.4-2003 CISPR 22:1997				
Prüfergebnis: <i>Test Results:</i>	Das vorstehend beschriebene Gerät wurde geprüft und entspricht oben genannter Prüfgrundlage. The above mentioned product was tested and passed .				
Prüflaboratorium: <i>Testing Laboratory:</i>	TÜV Rheinland Hong Kong Ltd. 9-10/F., Emperor International Square , 7 Wang Tai Road, Kowloon Bay, Kowloon, Hong Kong				
geprüft/ tested by:		kontrolliert/ reviewed by:			
18.08.2010	Sharon Li Project Manager	18.08.2010	Thomas Berns Manager		
Datum <i>Date</i>	Name/Stellung <i>Name/Position</i>	Unterschrift <i>Signature</i>	Datum <i>Date</i>	Name/Stellung <i>Name/Position</i>	Unterschrift <i>Signature</i>
Sonstiges: Other Aspects		FCCID: YFA900003			
Abkürzungen:	P(ass) = entspricht Prüfgrundlage F(ail) = entspricht nicht Prüfgrundlage N/A = nicht anwendbar N/T = nicht getestet	Abbreviations:	P(ass) = passed F(ail) = failed N/A = not applicable N/T = not tested		
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any safety mark on this or similar products.</i>					

www.tuv.com

Table of Content

	Page
Cover Page	1
Table of Content	2
Product information	3
Manufacturers declarations	3
Product function and intended use	3
Submitted documents	3
List of Test and Measurement Instruments	4
Results FCC Part 15 – Subpart C	5
Subclause 15.207 – Disturbance Voltage on AC Mains N/A.....	5
Subclause 15.249 (a) – Radiated Emission (Fundamental and Harmonics) Pass.....	6
Subclause 15.249 (d) – Spurious Radiated Emissions Pass.....	7
Appendix 1 – Test Results	7 pages
Appendix 2 – Test Setup Photos	2 pages
Appendix 3 – Photo documentation	8 pages
Appendix 4 – Product documentation	15 pages

www.tuv.com

Product information

Manufacturers declarations

	Transceiver
Operating frequency range	2410 - 2481 MHz
Type of modulation	FSK
Number of channels	64
Type of antenna	Integral
Power level	fix
Connection to public utility power line	No
Nominal voltage	V_{nor} : 6.0 V

Product function and intended use

The equipment under test (EUT) is a radio control toy transmitter operating at 2.4GHz. It is powered by batteries only.

Submitted documents

- Circuit Diagram
- Block Diagram
- Bill of material
- User manual
- Rating Label

List of Test and Measurement Instruments

	Equipment used	Manufacturer	Model No.	S/N	Due Date
<input checked="" type="checkbox"/>	Semi-anechoic Chamber	Albatross Projects GmbH	Nil	9460000.9	16-Mar-11
<input checked="" type="checkbox"/>	EMI Test Receiver	R & S	ESCI	100216	16-Mar-11
<input checked="" type="checkbox"/>	Trilog-Broadband Antenna	Schwarzbeck	VULB9168	209	21-Aug-11
<input checked="" type="checkbox"/>	Double-Ridged Waveguide Horn Antenna	R & S	HF 906	100407	16-Mar-11
<input checked="" type="checkbox"/>	Pre-Amplifier	MITEQ	AFS42-00101800-25S-42	1101599	16-Mar-11
<input checked="" type="checkbox"/>	Pre-Amplifier	MITEQ	AFS42-00101800-25S-44	1108282	16-Mar-11
<input checked="" type="checkbox"/>	Band Reject Filter	Micro-Tronics	BRM50702	023	16-Mar-11
<input checked="" type="checkbox"/>	Horn Antenna	EMCO	3160-09	21642	26-Jun-14
<input checked="" type="checkbox"/>	FSP 30 Spectrum Analyser	R & S	FSP 30	100286	16-Mar-11
<input checked="" type="checkbox"/>	EMI Test Receiver	R & S	ESCS 30	100316	16-Mar-11
<input checked="" type="checkbox"/>	Artificial Mains Network	R & S	ESH3-Z5	100114	16-Mar-11
<input checked="" type="checkbox"/>	Pulse Limiter	R & S	ESH3-Z2	100701	16-Mar-11
<input checked="" type="checkbox"/>	Loop Antenna	R & S	HFH2-Z2	9107-2651	16-Mar-11

Results FCC Part 15 – Subpart C

Subclause 15.207 – Disturbance Voltage on AC Mains	N/A
There is no AC power input or output ports on the EUT.	

Subclause 15.205 – Band edge compliance of radiated emissions	Pass
Test Specification : ANSI C63.4 – 2003 Mode of operation : Tx mode Port of testing : Enclosure Detector : Peak RBW/VBW : 100 kHz / 300 kHz for $f < 1$ GHz : 1 MHz / 3 MHz for $f > 1$ GHz Supply voltage : internal batteries has been activated Temperature : 23°C Humidity : 50%	
Requirement:	Radiated emissions which fall in the restricted bans, as defined in 15.205 (a), must also comply with the radiated emission limits specified in 15.209(a).
Results:	There is no peak found in the restricted bands. For test protocols refer to Appendix 1, page 4-7.

Subclause 15.215 (c) – 20 dB Bandwidth	Pass			
Requirement:	The intentional radiators must be designed to ensure that the 20dB bandwidth of the emission, is contained within the frequency band designated in the rule section under which the equipment is operated.			
Test Specification : ANSI C63.4 – 2003 Mode of operation : Tx mode Port of testing : Enclosure RBW/VBW : 100 kHz / 300 kHz for $f < 1$ GHz : 1 MHz / 3 MHz for $f > 1$ GHz Supply voltage : internal batteries has been activated Temperature : 23°C Humidity : 50%				
Results:	For test protocols refer to Appendix 1, page 1-3.			
Frequency (MHz)	20 dB left (MHz)	Limit (MHz)	20 dB right (MHz)	Limit (MHz)
2410	2409.616	> 2400	2410.498	< 2483.5
2450	2450.017	> 2400	2450.380	< 2483.5
2481	2480.756	> 2400	2481.548	< 2483.5

Subclause 15.249 (a) – Radiated Emission (Fundamental and Harmonics)		Pass
Test Specification : ANSI C63.4 – 2003 Mode of operation : Tx mode Port of testing : Enclosure RBW/VBW : 100 kHz / 300 kHz for f < 1 GHz 1 MHz / 3 MHz for f > 1 GHz Supply voltage : internal batteries has been activated Temperature : 23°C Humidity : 50%		
Requirement: The field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following limit.		
Results: PASS		
Fundamental Frequency 2410MHz		Vertical Polarization
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
2410.000	78.57	114.0 / P
2410.160	27.36	94.0 / A
Fundamental Frequency 2410MHz		Horizontal Polarization
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
2410.288	71.18	114.0 / P
2410.064	27.07	94.0 / A
Harmonics 2410MHz		Vertical Polarization
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
4820.513	49.75	74.0 / P
4819.407	40.25	54.0 / A
Harmonics 2410MHz		Horizontal Polarization
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
4819.375	50.71	74.0 / P
4819.391	42.49	54.0 / A
Fundamental Frequency 2450MHz		Vertical Polarization
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
2450.304	74.99	114.0 / P
2450.465	27.30	94.0 / A
Fundamental Frequency 2450MHz		Horizontal Polarization
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
2450.529	68.16	114.0 / P
2450.385	27.05	94.0 / A
Harmonics 2450MHz		Vertical Polarization

Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
no peak found	---	74.0 / P
no peak found	---	54.0 / A
Harmonics 2450MHz Horizontal Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
no peak found	---	74.0 / P
no peak found	---	54.0 / A
Fundamental Frequency 2481MHz Vertical Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
2481.410	71.70	114.0 / P
2480.978	27.09	94.0 / A
Fundamental Frequency 2481MHz Horizontal Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
2481.010	71.84	114.0 / P
2480.929	27.14	94.0 / A
Harmonics 2481MHz Vertical Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
no peak found	---	74.0 / P
no peak found	---	54.0 / A
Harmonics 2481MHz Horizontal Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
4962.083	52.38	74.0 / P
4961.651	42.97	54.0 / A

Subclause 15.249 (d) – Spurious Radiated Emissions		Pass
Test Specification : ANSI C63.4 - 2003 Mode of operation : Tx mode Port of testing : Enclosure Detector : Peak RBW/VBW : 100 kHz / 300 kHz for f < 1 GHz 1 MHz / 3 MHz for f > 1 GHz Supply voltage : internal batteries has been activated Temperature : 23°C Humidity : 50%		
Requirement:	Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.	
Results:	All three transmit frequency modes comply with the field strength within the restricted bands. There is no spurious found below 30MHz.	

Tx frequency 2410MHz			Vertical Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m			
no peak found	---	74.0 / P			
no peak found	---	54.0 / A			
Tx frequency 2410MHz			Horizontal Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m			
no peak found	---	74.0 / P			
no peak found	---	54.0 / A			
Tx frequency 2450MHz			Vertical Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m			
no peak found	---	74.0 / P			
no peak found	---	54.0 / A			
Tx frequency 2450MHz			Horizontal Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m			
no peak found	---	74.0 / P			
no peak found	---	54.0 / A			
Tx frequency 2481MHz			Vertical Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m			
no peak found	---	74.0 / P			
no peak found	---	54.0 / A			
Tx frequency 2481MHz			Horizontal Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m			
no peak found	---	74.0 / P			
no peak found	---	54.0 / A			