

## SAR Test exclusion documentation according to FCC KDB 447498, RSS-102

Report identification number: 1-1776/21-03-10 Exclusion (FCC)

<b>contains the module with the following certification numbers</b>	
FCC ID	YFJANT100824

This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

### Document authorised:

Thomas Vogler  
Lab Manager  
Radio Communications & EMC

Marco Scigliano  
Testing Manager  
Radio Communications & EMC

**EUT technologies:**

Technologies:	Max. declared cond. AVG Power	Max. measured EIRP @ 30m <sup>1)</sup>	Antenna gain	MAX EIRP for RF exposure
NFC 13.56 MHz	23.01 dBm (200.0 mW) <sup>3)</sup>	32.2 dBµV (Peak) = -41.63 dBm	< 0 dBi	23.01 dBm (200.0 mW)
Proprietary 2450 MHz <sup>2)</sup>	18.6 dBm (72.44 mW)	--	3.5 dBi	22.1 dBm (162.18 mW)

**NOTE:**

The measured PEAK EIRP @30m proves that the EUT antenna gain is far below 0dBi and that considering the max. declared output power of 23.01dBm (=200mW) is by far larger than the EIRP. Thus for it is correct to use the conducted value as the worst case base for the RF exposure calculation.

- 1) Test result taken from CTC advanced GmbH report 1-1776/21-03-05.
- 2) Test results for Proprietary 2450 MHz can be seen in CTC advanced GmbH report 1-1776/21-03-04
- 3) Max. power from data sheet – NXP PN512 (page 111)

**Collocation overview:**

Active scenario: Technology	1	2	3	4
NFC 13.56 MHz	x		x	
Proprietary 2450 MHz	x	x		

**Declared minimum safety distance: 20cm**

According the manual a safety distance of 20cm shall be applied between the user (and/or bystanders) to the EUT antenna whilst active transmitting.

**SAR test exclusion according to KDB447498 (General RF Exposure Guidance v06)**

(3a) Standalone SAR test exclusion below 100 MHz at test separation distances > 50mm and < 200mm

$$( \text{Threshold}_{100\text{MHz} > 50\text{mm}} ) \times ( 1 + \log(100/f) )$$

where

Threshold<sub>1-g;10-g</sub> is 3 for 1-g; 7.5 for 10-g  
 d<sub>separation</sub> is the min. test separation distance ( >50mm and <200mm )  
 f is the RF channel transmit frequency  
 Threshold<sub>50mm; 100MHz < 50mm</sub> is Threshold<sub>1-g;10-g</sub> × d / f<sup>0.5</sup>  
 with f = 100MHz and d=50mm  
 Threshold<sub>100MHz > 50mm</sub> is (Threshold<sub>50mm; 100MHz < 50mm</sub>) + (d<sub>separation</sub> - 50mm) × f / 150  
 with f = 100MHz

The table below gives the calculated maximal power that could be used for source based time averaged conducted power, adjusted for tune up tolerance. If this is below the calculated value SAR testing is excluded.

frequency [MHz]	d <sub>separation</sub> [mm]	Threshold <sub>1-g</sub>	Threshold <sub>50mm</sub> (100MHz)		Powerlimit [mW]	P <sub>max-declared</sub>		Exclusion
			< 50mm	> 50mm		[dBm]	[mW]	
13.56	199.99	3	128.64	228.63	427.03	23.01	199.99	yes

2b) Standalone SAR test exclusion for 1.5 GHz to 6 GHz at test separation distances ≥ 50mm

$$[ \text{Threshold}_{50\text{mm}} + ( d_{\text{separation}} - 50\text{mm} ) \times 10 ]$$

where

Threshold<sub>1-g;10-g</sub> is 3 for 1-g; 7.5 for 10-g  
 d<sub>separation</sub> is the min. test separation distance; not less than 50mm  
 f is the RF channel transmit frequency  
 Threshold<sub>50mm</sub> is Threshold<sub>1-g;10-g</sub> × d / f<sup>0.5</sup> ; with d = 50mm

The table below gives the calculated maximal power that could be used for source based time averaged conducted power, adjusted for tune up tolerance. If this is below the calculated value SAR testing is excluded.

frequency [MHz]	d <sub>separation</sub> [mm]	Threshold <sub>1-g</sub>	Threshold <sub>50mm</sub>	Powerlimit [mW]	P <sub>max-declared</sub>		Exclusion
					[dBm]	[mW]	
2450.00	200	3	95.83	1595.83	22.10	162.18	yes

**Collocation:**Overview:

Technology , [MHz]	NFC, 13.56 MHz	Proprietary, 2450
Exemption based on	SAR , 200 mm distance	SAR , 200mm distance
Limit EIRP [mW]:	427.03	1595.83
Result EIRP [mW]:	200.0	162.18
Limit-Exhaustion [%]	46.8	10.2
Collocated percentage [%]	57.0	
Verdict:	PASS	