

cetecom
advanced

TEST REPORT

Test report no.: 1-7494-24-01-09_TR1-R02



Testing laboratory

cetecom advanced GmbH

Untertuerkheimer Strasse 6 – 10
66117 Saarbruecken / Germany

Phone: + 49 681 5 98 - 0

Fax: + 49 681 5 98 - 9075

Internet: <https://cetecomadvanced.com>

e-mail: mail@cetecomadvanced.com

Accredited Testing Laboratory:

The testing laboratory (area of testing) is accredited according to DIN EN ISO/IEC 17025 (2018-03) by the Deutsche Akkreditierungsstelle GmbH (DAkkS).

The accreditation is valid for the scope of testing procedures as stated in the accreditation certificate with the registration number:

D-PL-12047-01-00.

ISED Testing Laboratory Recognized Listing Number: DE0001

FCC designation number: DE0002

Applicant

Riedel Communications GmbH & Co. KG

Uellendahler Strasse 353
42109 Wuppertal / GERMANY

Phone: -/-

Contact: Wolfgang Fritz

e-mail: certification@riedel.net

Manufacturer

Riedel Communications GmbH & Co. KG

Uellendahler Strasse 353
42109 Wuppertal / GERMANY

Test standard/s

FCC - Title 47 CFR Part 15 FCC - Title 47 of the Code of Federal Regulations; Chapter I; Part 15 - Radio frequency devices

RSS - 210 Issue 10 Spectrum Management and Telecommunications Radio Standards Specification - Licence-Exempt Radio Apparatus: Category I Equipment

For further applied test standards please refer to section 3 of this test report.

Test Item

| | |
|---------------------------|---------------------------------|
| Kind of test item: | Beltpack Standard |
| Model name: | BL-BPK-1006-24 |
| FCC ID: | YFJBPK100624H |
| IC: | 8706A-BPK100624H |
| Frequency: | 13.56 MHz |
| Technology tested: | RFID |
| Antenna: | Integrated antenna |
| Power supply: | 3.6 V DC by Li-Ion battery pack |
| Temperature range: | -10°C to +45°C |

This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

Test report authorized:

Christoph Schneider
Lab Manager
Radio Communications

Test performed:

On behalf of

Tobias Wittenmeier
Testing Manager
Radio Communications

1 Table of contents

| | | |
|-----------|---|-----------|
| 1 | Table of contents | 2 |
| 2 | General information | 3 |
| 2.1 | Notes and disclaimer | 3 |
| 2.2 | Application details | 3 |
| 2.3 | Test laboratories sub-contracted | 3 |
| 3 | Test standard/s, references and accreditations | 4 |
| 4 | Reporting statements of conformity – decision rule | 5 |
| 5 | Test environment | 6 |
| 6 | Test item | 6 |
| 6.1 | General description | 6 |
| 6.2 | Additional information | 6 |
| 7 | Description of the test setup | 7 |
| 7.1 | Shielded semi anechoic chamber | 8 |
| 7.2 | Shielded fully anechoic chamber | 10 |
| 7.3 | RF measurements normal and extreme conditions | 11 |
| 8 | Sequence of testing | 12 |
| 8.1 | Sequence of testing radiated spurious 9 kHz to 30 MHz | 12 |
| 8.2 | Sequence of testing radiated spurious 30 MHz to 1 GHz | 13 |
| 9 | Measurement uncertainty | 14 |
| 10 | Summary of measurement results | 15 |
| 11 | Additional comments | 16 |
| 12 | Measurement results | 17 |
| 12.1 | Occupied bandwidth | 17 |
| 12.2 | Field strength of the fundamental | 19 |
| 12.3 | Field strength of the harmonics and spurious | 20 |
| 12.4 | Frequency error | 23 |
| 13 | Observations | 24 |
| 14 | Glossary | 25 |
| 15 | Document history | 26 |
| 16 | Dol | 27 |

2 General information

2.1 Notes and disclaimer

The test results of this test report relate exclusively to the test item specified in this test report. cetecom advanced GmbH does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item.

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of cetecom advanced GmbH.

The testing service provided by cetecom advanced GmbH has been rendered under the current "General Terms and Conditions for cetecom advanced GmbH".

cetecom advanced GmbH will not be liable for any loss or damage resulting from false, inaccurate, inappropriate or incomplete product information provided by the customer.

Under no circumstances does the cetecom advanced GmbH test report include any endorsement or warranty regarding the functionality, quality or performance of any other product or service provided.

Under no circumstances does the cetecom advanced GmbH test report include or imply any product or service warranties from cetecom advanced GmbH, including, without limitation, any implied warranties of merchantability, fitness for purpose, or non-infringement, all of which are expressly disclaimed by cetecom advanced GmbH.

All rights and remedies regarding vendor's products and services for which cetecom advanced GmbH has prepared this test report shall be provided by the party offering such products or services and not by cetecom advanced GmbH.

In no case this test report can be considered as a Letter of Approval.

This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

This test report replaces the test report with the number 1-7494-24-01-09_TR1-R01 and dated 2024-06-20.

2.2 Application details

| | |
|------------------------------------|------------|
| Date of receipt of order: | 2021-03-29 |
| Date of receipt of test item: | 2021-05-11 |
| Start of test:* | 2021-06-22 |
| End of test:* | 2021-07-28 |
| Person(s) present during the test: | -/- |

*Date of each measurement, if not shown in the plot, can be requested. Dates are stored in the measurement software.

2.3 Test laboratories sub-contracted

None

3 Test standard/s, references and accreditations


| Test standard | Date | Description |
|---|---------------|---|
| FCC - Title 47 CFR Part 15 | | FCC - Title 47 of the Code of Federal Regulations; Chapter I; Part 15 - Radio frequency devices |
| RSS - 210 Issue 10 | December 2019 | Spectrum Management and Telecommunications Radio Standards Specification - Licence-Exempt Radio Apparatus: Category I Equipment |
| RSS - Gen Issue 5 incl. Amendment 1 & 2 | February 2021 | Spectrum Management and Telecommunications Radio Standards Specification - General Requirements for Compliance of Radio Apparatus |
| Guidance | Version | Description |
| ANSI C63.4-2014 | -/- | American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz |
| ANSI C63.10-2013 | -/- | American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices |

4 Reporting statements of conformity – decision rule

Only the measured values related to their corresponding limits will be used to decide whether the equipment under test meets the requirements of the test standards listed in chapter 3.

The measurement uncertainty is mentioned in this test report, see chapter 9, but is not taken into account - neither to the limits nor to the measurement results. Measurement results with a smaller margin to the corresponding limits than the measurement uncertainty have a potential risk of more than 5% that the decision might be wrong."

measured value, measurement uncertainty, verdict



5 Test environment

| | | |
|-----------------------------|------------------|--------------------------------------|
| Temperature : | T_{nom} | +22 °C during room temperature tests |
| | T_{max} | +50 °C during high temperature tests |
| | T_{min} | -20 °C during low temperature tests |
| Relative humidity content : | | 55 % |
| Barometric pressure : | | 1021 hpa |
| Power supply : | V_{nom} | 3.60 V DC by Li-Ion battery pack |
| | V_{max} | 4.20 V |
| | V_{min} | 3.06 V |

6 Test item

6.1 General description

| | |
|------------------------------|--|
| Kind of test item : | Beltpack Standard |
| Model name : | BL-BPK-1006-24 |
| HMN : | -/- |
| PMN : | BL-BPK-1006-24 (Bolero 2G4 Beltpack) |
| HVIN : | BL-BPK-1006-24-H |
| FVIN : | -/- |
| S/N serial number : | 3304035200259 |
| Hardware status : | 10.06 |
| Software status : | 3.0.0 |
| Firmware status : | 0618 |
| Frequency band : | 13.56 MHz |
| Type of radio transmission : | modulated carrier |
| Use of frequency spectrum : | |
| Type of modulation : | ASK |
| Number of channels : | 1 |
| Antenna : | Integrated antenna |
| Power supply : | 3.06 V to 4.20 V DC by Li-Ion battery pack |
| Temperature range : | -10°C to +45°C |

6.2 Additional information

The content of the following annexes is defined in the QA. It may be that not all of the listed annexes are necessary for this report, thus some values in between may be missing.

Test setup and EUT photos are included in test report: 1-1776/21-01-01_AnnexA
1-1776/21-01-01_AnnexD

7 Description of the test setup

Typically, the calibrations of the test apparatus are commissioned to and performed by an accredited calibration laboratory. The calibration intervals are determined in accordance with the DIN EN ISO/IEC 17025. In addition to the external calibrations, the laboratory executes comparison measurements with other calibrated test systems or effective verifications. Weekly chamber inspections and range calibrations are performed. Where possible, RF generating and signaling equipment as well as measuring receivers and analyzers are connected to an external high-precision 10 MHz reference (GPS-based or rubidium frequency standard).

In order to simplify the identification of the equipment used at some special tests, some items of test equipment and ancillaries can be provided with an identifier or number in the equipment list below (Lab/Item).


Each block diagram listed can contain several test setup configurations. All devices belonging to a test setup are identified with the same letter syntax. For example: Column Setup and all devices with an A.

Agenda: Kind of Calibration

| | | | |
|-------|--|-----|--|
| k | calibration / calibrated | EK | limited calibration |
| ne | not required (k, ev, izw, zw not required) | zw | cyclical maintenance (external cyclical maintenance) |
| ev | periodic self verification | izw | internal cyclical maintenance |
| Ve | long-term stability recognized | g | blocked for accredited testing |
| vlkl! | Attention: extended calibration interval | * | next calibration ordered / currently in progress |
| NK! | Attention: not calibrated | | |

7.1 Shielded semi anechoic chamber

The radiated measurements are performed in vertical and horizontal plane in the frequency range from 30 MHz to 1 GHz in semi-anechoic chambers. The EUT is positioned on a non-conductive support with a height of 0.80 m above a conductive ground plane that covers the whole chamber. The receiving antennas are conform to specifications ANSI C63. These antennas can be moved over the height range between 1.0 m and 4.0 m in order to search for maximum field strength emitted from EUT. The measurement distances between EUT and receiving antennas are indicated in the test setups for the various frequency ranges. For each measurement, the EUT is rotated in all three axes until the maximum field strength is received. The wanted and unwanted emissions are received by spectrum analyzers where the detector modes and resolution bandwidths over various frequency ranges are set according to requirement ANSI C63.



Measurement distance: tri-log antenna 10 meter

EMC32 software version: 10.59.00

FS = UR + CL + AF

(FS-field strength; UR-voltage at the receiver; CL-loss of the cable; AF-antenna factor)


Example calculation:

$$\text{FS [dB}\mu\text{V/m]} = 12.35 \text{ [dB}\mu\text{V/m]} + 1.90 \text{ [dB]} + 16.80 \text{ [dB/m]} = 31.05 \text{ [dB}\mu\text{V/m]} (35.69 \mu\text{V/m})$$

Equipment table:

| No. | Setup | Equipment | Type | Manufacturer | Serial No. | INV. No. | Kind of Calibration | Last Calibration | Next Calibration |
|-----|-------|---|--------------|-------------------------------|-----------------|-----------|---------------------|------------------|------------------|
| 1 | A | Double-Ridged Waveguide Horn Antenna 1-18.0GHz | 3115 | EMCO | 8812-3088 | 300001032 | vlKI! | 05.07.2019 | 04.07.2021 |
| 2 | A | Switch-Unit | 3488A | HP | 2719A14505 | 300000368 | ev | -/- | -/- |
| 3 | A | Semi anechoic chamber | 3000023 | MWB AG | | 300000551 | ne | -/- | -/- |
| 4 | A | Analyzer-Reference-System (Harmonics and Flicker) | ARS 16/1 | SPS | A3509 07/0 0205 | 300003314 | vlKI! | 17.01.2020 | 16.01.2022 |
| 5 | A | Antenna Tower | Model 2175 | ETS-Lindgren | 64762 | 300003745 | izw | -/- | -/- |
| 6 | A | Positioning Controller | Model 2090 | ETS-Lindgren | 64672 | 300003746 | izw | -/- | -/- |
| 7 | A | Turntable Interface-Box | Model 105637 | ETS-Lindgren | 44583 | 300003747 | izw | -/- | -/- |
| 8 | A | TRILOG Broadband Test-Antenna 30 MHz - 3 GHz | VULB9163 | Schwarzbeck Mess - Elektronik | 318 | 300003696 | vlKI! | 04.09.2019 | 03.09.2021 |
| 9 | A | TRILOG Broadband Test-Antenna 30 MHz - 3 GHz | VULB9163 | Schwarzbeck Mess - Elektronik | 295 | 300003787 | vlKI! | 19.02.2021 | 18.02.2023 |
| 10 | A | PC | TecLine | F+W | | 300004388 | ne | -/- | -/- |
| 11 | A | EMI Test Receiver | ESR3 | Rohde & Schwarz | 102587 | 300005771 | k | 10.12.2020 | 09.06.2022 |

7.2 Shielded fully anechoic chamber



Measurement distance: loop antenna 3 meter

FS = UR + CA + AF

(FS-field strength; UR-voltage at the receiver; CA-loss of the signal path; AF-antenna factor)

Example calculation:


$$\text{FS [dB}\mu\text{V/m]} = 40.0 \text{ [dB}\mu\text{V/m]} + (-35.8) \text{ [dB]} + 32.9 \text{ [dB/m]} = 37.1 \text{ [dB}\mu\text{V/m]} (71.61 \mu\text{V/m})$$

Equipment table:

| No. | Setup | Equipment | Type | Manufacturer | Serial No. | INV. No. | Kind of Calibration | Last Calibration | Next Calibration |
|-----|-------|--|--------------------|----------------------|----------------|-----------|---------------------|------------------|------------------|
| 1 | A | Active Loop Antenna 9 kHz to 30 MHz | 6502 | EMCO | 2210 | 300001015 | viKI! | 13.06.2019 | 12.06.2022 |
| 2 | A | Anechoic chamber | FAC 3/5m | MWB / TDK | 87400/02 | 300000996 | ev | -/- | -/- |
| 3 | A | Switch / Control Unit | 3488A | HP | * | 300000199 | ne | -/- | -/- |
| 4 | A | EMI Test Receiver 20Hz- 26,5GHz | ESU26 | R&S | 100037 | 300003555 | k | 11.12.2020 | 10.12.2021 |
| 5 | A | 4U RF Switch Platform | L4491A | Agilent Technologies | MY50000037 | 300004509 | ne | -/- | -/- |
| 6 | A | NEXIO EMV-Software | BAT EMC V3.20.0.26 | EMCO | | 300004682 | ne | -/- | -/- |
| 7 | A | Open Switch and Control Unit and Power Sensors | OSP120 incl. B157 | Rohde & Schwarz | 101274, 100877 | 300004825 | viKI! | 16.12.2020 | 15.12.2022 |
| 8 | A | PC | ExOne | F+W | | 300004703 | ne | -/- | -/- |

7.3 RF measurements normal and extreme conditions

Conducted measurements normal & extreme conditions



OP = AV + CA
 (OP-output power; AV-analyzer value; CA-loss signal path)

Example calculation:
 OP [dBm] = 6.0 [dBm] + 11.7 [dB] = 17.7 [dBm] (58.88 mW)

Equipment table:

| No. | Setup | Equipment | Type | Manufacturer | Serial No. | INV. No. | Kind of Calibration | Last Calibration | Next Calibration |
|-----|-------|--------------------------|---------|--------------------------|--------------------|-----------|---------------------|------------------|------------------|
| 1 | A,B | Loop Antenna | | ZEG TS Steinfurt | | 400001208 | ev | -/- | -/- |
| 2 | A,B | RF Cable BNC | RG58 | Huber & Suhner | | 400001209 | ev | -/- | -/- |
| 3 | B | Temperature Test Chamber | VT 4011 | Voetsch Industrietechnik | 585662306000 10 | 300005363 | ev | 08.05.2020 | 07.05.2022 |
| 4 | A,B | Signal analyzer | FSV30 | Rohde&Schwarz | 104365 | 300005923 | k | 16.12.2020 | 15.12.2021 |
| 5 | B | Power Supply | HMP2020 | Rohde & Schwarz | 101961 | 300006102 | k | 04.08.2020 | 03.08.2022 |

8 Sequence of testing

8.1 Sequence of testing radiated spurious 9 kHz to 30 MHz

Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- If the EUT is a tabletop system, it is placed on a table with 0.8 m height.
- If the EUT is a floor standing device, it is placed directly on the turn table.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- Measurement distance is 3 m (see ANSI C 63.4) – see test details.
- EUT is set into operation.

Premereasurement*

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna height is 1 m.
- At each turntable position the analyzer sweeps with positive-peak detector to find the maximum of all emissions.

Final measurement

- Identified emissions during the pre-measurement are maximized by the software by rotating the turntable from 0° to 360°.
- Loop antenna is rotated about its vertical axis for maximum response at each azimuth about the EUT. (For certain applications, the loop antenna plane may also need to be positioned horizontally at the specified distance from the EUT)
- The final measurement is done in the position (turntable and elevation) causing the highest emissions with quasi-peak (as described in ANSI C 63.4).
- Final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. A plot with the graph of the premeasurement and the limit is stored.

^{*)}Note: The sequence will be repeated three times with different EUT orientations.

8.2 Sequence of testing radiated spurious 30 MHz to 1 GHz

Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- Measurement distance is 10 m or 3 m (see ANSI C 63.4) – see test details.
- EUT is set into operation.

Premereasurement

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height changes from 1 m to 3 m.
- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

Final measurement

- The final measurement is performed for at least six highest peaks according to the requirements of the ANSI C63.4.
- Based on antenna and turntable positions at which the peak values are measured the software maximize the peaks by changing turntable position $\pm 45^\circ$ and antenna height between 1 and 4 m.
- The final measurement is done with quasi-peak detector (as described in ANSI C 63.4).
- Final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit are recorded. A plot with the graph of the premeasurement with marked maximum final results and the limit is stored.

9 Measurement uncertainty

| Measurement uncertainty | |
|--|-------------|
| Test case | Uncertainty |
| Occupied bandwidth | ± used RBW |
| Field strength of the fundamental | ± 3 dB |
| Field strength of the harmonics and spurious | ± 3 dB |
| Receiver spurious emissions and cabinet radiations | ± 3 dB |
| Conducted limits | ± 2.6 dB |

10 Summary of measurement results

| | |
|-------------------------------------|---|
| <input checked="" type="checkbox"/> | No deviations from the technical specifications were ascertained |
| <input type="checkbox"/> | There were deviations from the technical specifications ascertained |
| <input type="checkbox"/> | This test report is only a partial test report. The content and verdict of the performed test cases are listed below. |

| TC Identifier | Description | Verdict | Date | Remark |
|---------------|--|------------|------------|--------|
| RF-Testing | CFR Part 15 RSS 210 Issue 10 RSS Gen Issue 5 | See table! | 2024-06-26 | -/- |

| Test specification clause | Test case | Temperature conditions | Power source conditions | C | NC | NA | NP | Remark |
|----------------------------------|--|-----------------------------|-----------------------------|-------------------------------------|--------------------------|-------------------------------------|--------------------------|--------|
| RSS Gen Issue 5 | Occupied bandwidth | Nominal | Nominal | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | -/- |
| § 15.225 (a) RSS 210 Issue 10 | Field strength of the fundamental | Nominal | Nominal | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | -/- |
| § 15.209 & § 15.225 (b-d) | Field strength of the harmonics and spurious | Nominal | Nominal | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | -/- |
| § 15.109 | Receiver spurious emissions and cabinet radiations | Nominal | Nominal | <input type="checkbox"/> | <input type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> | -/- |
| §15.107 §15.207 | Conducted limits | Nominal | Nominal | <input type="checkbox"/> | <input type="checkbox"/> | <input checked="" type="checkbox"/> | <input type="checkbox"/> | -/- |
| § 15.225 (a) RSS 210 Issue 10 | Frequency tolerance | Normal & extreme conditions | Normal & extreme conditions | <input checked="" type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | -/- |

Note:

C Compliant
 NC Not compliant
 NA Not applicable
 NP Not performed

11 Additional comments

Reference documents: Original test report: 1-1776_21-01-06
 New test report was created for certification purposes. See also Chapter 16. Dol
 for more information.

Special test descriptions: None

Configuration descriptions: None

12 Measurement results

12.1 Occupied bandwidth

Measurement:

The emission bandwidth (x dB) is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated x dB below the maximum in-band spectral density of the modulated signal.

| Measurement parameters | |
|--------------------------|-------------------------------------|
| Detector: | Peak |
| Resolution bandwidth: | 1 % – 5 % of the occupied bandwidth |
| Video bandwidth: | $\geq 3 \times$ RBW |
| Trace mode: | Max hold |
| Analyser function: | 99 % power function |
| Used equipment: | See chapter 7.3A |
| Measurement uncertainty: | See chapter 9 |

Limit:

| IC |
|---|
| for RSP-100 test report coversheet only |

Result:

| 99% emission bandwidth |
|------------------------|
| 877.78 kHz |

Plot:**Plot 1: 99 % emission bandwidth**

12.2 Field strength of the fundamental

Measurement:

The maximum detected field strength for the carrier signal.

| Measurement parameters | |
|--------------------------|------------------|
| Detector: | average |
| Resolution bandwidth: | 120 kHz |
| Video bandwidth: | $\geq 3x$ RBW |
| Trace mode: | Max hold |
| Used equipment: | See chapter 7.2A |
| Measurement uncertainty: | See chapter 9 |

Limit:

| FCC & IC | | |
|--------------------|--------------------------------|-----------------------------|
| Frequency (MHz) | Field strength (μ V/m) | Measurement distance (m) |
| 13.553 to 13.567 | 15,848 (84 dB μ V/m) | 30 |

Recalculation:

| According to ANSI C63.10 | | |
|--------------------------|---|-------------------------|
| Frequency | Formula | Correction value |
| 13.56 MHz | $FS_{limit} = FS_{max} - 40 \log\left(\frac{d_{nearfield}}{d_{measure}}\right) - 20 \log\left(\frac{d_{limit}}{d_{nearfield}}\right)$ <p> FS_{limit} is the calculation of field strength at the limit distance, expressed in dBμV/m FS_{max} is the measured field strength, expressed in dBμV/m $d_{nearfield}$ is the $\lambda/2\pi$ distance $d_{measure}$ is the distance of the measurement point from EUT d_{limit} is the reference limit distance </p> | -21.4 dB from 3m to 30m |

Result:

| Field strength of the fundamental | | |
|-----------------------------------|--------------------|--------------------|
| Frequency | 13.56 MHz | |
| Distance | @ 3 m | @ 30 m |
| Measured / calculated value | 55.16 dB μ V/m | 33.76 dB μ V/m |

12.3 Field strength of the harmonics and spurious

Measurement:

The maximum detected field strength for the harmonics and spurious.

| Measurement parameters | |
|--------------------------|--|
| Detector: | Quasi peak / average or peak (worst case – pre-scan) |
| Resolution bandwidth: | F < 150 kHz: 200 Hz 150 kHz < F < 30 MHz: 9 kHz 30 MHz < F < 1 GHz: 120 kHz |
| Video bandwidth: | F < 150 kHz: 1 kHz 150 kHz < F < 30 MHz: 100 kHz 30 MHz < F < 1 GHz: 300 kHz |
| Trace mode: | Max hold |
| Used equipment: | See chapter 7.1A & 7.2A & 7.3A |
| Measurement uncertainty: | See chapter 9 |



Limit:

| FCC & IC | | |
|--------------------|----------------------------------|-----------------------------|
| Frequency (MHz) | Field strength (dB μ V/m) | Measurement distance (m) |
| 0.009 – 0.490 | 2400/F(kHz) | 300 |
| 0.490 – 1.705 | 24000/F(kHz) | 30 |
| 1.705 – 30 | 30 (29.5 dB μ V/m) | 30 |
| 30 – 88 | 100 (40 dB μ V/m) | 3 |
| 88 – 216 | 150 (43.5 dB μ V/m) | 3 |
| 216 – 960 | 200 (46 dB μ V/m) | 3 |


Note: For a reduced measurement distance, please take a look at the limit line and the ANSI C63.10-2013 sub clause 6.4 radiated emissions from unlicensed wireless devices below 30 MHz.

Result: For frequency of the spurious > 30 MHz see table below plot.

| Detected emissions < 30 MHz | | | |
|-----------------------------|----------|-------------------------------|---------------------------------------|
| Frequency (MHz) | Detector | Resolution bandwidth (kHz) | Detected value (dB μ V/m @ 3m) |
| No peaks detected. | | | |
| | | | |

Plots:**Plot 1:** 9 kHz – 30 MHz, magnetic emissions**Plot 2:** Spectrum mask (the limits are recalculated according to the ANSI C63.10-2013 sub clause 6.4)

Plot 3: 30 MHz – 1 GHz, vertical and horizontal polarization



Final_Result

| Frequency (MHz) | QuasiPeak (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) | Meas. Time (ms) | Bandwidth (kHz) | Height (cm) | Pol | Azimuth (deg) | Corr. (dB/m) |
|-----------------|--------------------------|----------------------|-------------|-----------------|-----------------|-------------|-----|---------------|--------------|
| 33.348 | 18.16 | 30.0 | 11.8 | 1000 | 120.0 | 122.0 | H | 3 | 12 |
| 530.586 | 24.40 | 36.0 | 11.6 | 1000 | 120.0 | 165.0 | H | 268 | 19 |
| 674.625 | 35.59 | 36.0 | 0.4 | 1000 | 120.0 | 129.0 | H | 271 | 21 |
| 692.516 | 30.68 | 36.0 | 5.3 | 1000 | 120.0 | 170.0 | H | 256 | 21 |
| 710.133 | 32.16 | 36.0 | 3.8 | 1000 | 120.0 | 103.0 | H | 270 | 21 |
| 716.012 | 32.43 | 36.0 | 3.6 | 1000 | 120.0 | 138.0 | H | 254 | 21 |
| 727.889 | 30.92 | 36.0 | 5.1 | 1000 | 120.0 | 107.0 | H | 273 | 21 |

12.4 Frequency error

Measurement:

The maximum detected field strength for the spurious.

| Measurement parameters | |
|--------------------------|-------------------|
| Detector: | Peak detector |
| Resolution bandwidth: | 10 Hz / 100 Hz |
| Video bandwidth: | > RBW |
| Trace mode: | Max hold |
| Used equipment: | See chapter 7.3 A |
| Measurement uncertainty: | See chapter 9 |

Limit:

FCC & IC

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. (± 1.356 kHz)

Carrier frequency stability shall be maintained to $\pm 0.01\%$ (± 100 ppm)

Result: Temperature variation

| Frequency tolerance | | | |
|---------------------|-----------------|-----------------------|-----------|
| Measured frequency | Frequency error | Conditions | Result |
| 13.5602138 MHz | 0.214 kHz | -20 °C & 100% voltage | compliant |
| 13.5602118 MHz | 0.212 kHz | -10 °C & 100% voltage | compliant |
| 13.5602138 MHz | 0.214 kHz | 0 °C & 100% voltage | compliant |
| 13.5602158 MHz | 0.216 kHz | +10 °C & 100% voltage | compliant |
| 13.5602158 MHz | 0.216 kHz | +20 °C & 100% voltage | compliant |
| 13.5602138 MHz | 0.214 kHz | +30 °C & 100% voltage | compliant |
| 13.5602198 MHz | 0.220 kHz | +40 °C & 100% voltage | compliant |
| 13.5602398 MHz | 0.240 kHz | +50 °C & 100% voltage | compliant |

Result: Voltage variation

| Frequency tolerance | | | |
|---------------------|-----------------|-----------------------|-----------|
| Measured frequency | Frequency error | Conditions | Result |
| 13.5602158 MHz | 0.216 kHz | +20 °C & 85% voltage | compliant |
| 13.5602158 MHz | 0.216 kHz | +20 °C & 100% voltage | compliant |
| 13.5602158 MHz | 0.216 kHz | +20 °C & 115% voltage | compliant |

13 Observations

No observations except those reported with the single test cases have been made.

14 Glossary

| | |
|------------------------|--|
| EUT | Equipment under test |
| DUT | Device under test |
| UUT | Unit under test |
| GUE | GNSS User Equipment |
| ETSI | European Telecommunications Standards Institute |
| EN | European Standard |
| FCC | Federal Communications Commission |
| FCC ID | Company Identifier at FCC |
| IC | Industry Canada |
| PMN | Product marketing name |
| HMN | Host marketing name |
| HVIN | Hardware version identification number |
| FVIN | Firmware version identification number |
| EMC | Electromagnetic Compatibility |
| HW | Hardware |
| SW | Software |
| Inv. No. | Inventory number |
| S/N or SN | Serial number |
| C | Compliant |
| NC | Not compliant |
| NA | Not applicable |
| NP | Not performed |
| PP | Positive peak |
| QP | Quasi peak |
| AVG | Average |
| OC | Operating channel |
| OCW | Operating channel bandwidth |
| OBW | Occupied bandwidth |
| OOB | Out of band |
| DFS | Dynamic frequency selection |
| CAC | Channel availability check |
| OP | Occupancy period |
| NOP | Non occupancy period |
| DC | Duty cycle |
| PER | Packet error rate |
| CW | Clean wave |
| MC | Modulated carrier |
| WLAN | Wireless local area network |
| RLAN | Radio local area network |
| DSSS | Dynamic sequence spread spectrum |
| OFDM | Orthogonal frequency division multiplexing |
| FHSS | Frequency hopping spread spectrum |
| GNSS | Global Navigation Satellite System |
| C/N₀ | Carrier to noise-density ratio, expressed in dB-Hz |

15 Document history

| Version | Applied changes | Date of release |
|---------|-----------------|-----------------|
| -/- | Initial release | 2024-06-20 |
| R02 | Updated HVIN | 2024-06-26 |

16 Dol



RIEDEL Communications International GmbH | Uellendahler Str. 353 | 42109 Wuppertal

To
Cetecom Advanced GmbH
Untertuerkheimer Str. 6-10
66117 Saarbruecken |
Germany

Name/Telefon
 Wolfgang Fritz
 +49 202 292 90

Datum
 Wuppertal,
 June 5, 2024

Declaration of Identity

Re: Bolero BL-BPK-1006-24

The manufacturer Riedel Communications GmbH & Co.KG, located at Uellendahler Str. 353-Wuppertal-Germany, DE 814906984 as being the manufacturer of product Bolero Wireless Beltpack, model BL-BPK-1006-24, hereby declares that the product BL-BPK-1006-24 in HVIN G2 is in all relevant Radio- and Terminal approval parameters for RFID (according to the FCC - Title 47 CFR Part 15 and RSS-210, Issue 10) identical to the product BL-BPK-1006-24 certified under:

- FCC ID: YFJBPK100624
- ISED certification number: 8706A-BPK100624

Furthermore, the current RFID reports can also be used for approval under new IDs due to the identical design.

Regards,

Signature of the responsible (of manufacturer)
 Wolfgang Fritz
 Senior Product Manager, Wireless Intercom

| | |
|---------|------------------------------------|
| Company | Riedel Communications GmbH & Co KG |
| Name | Wolfgang Fritz |
| Phone | +49 202 292 90 |
| Email | Wolfgang.fritz@riedel.net |
| Datum | June 5, 2024 |