

## INTERTEK TESTING SERVICES

---

### RF Exposure

The equipment under test (EUT) is a Classic Wireless Controller for Atari VCS with Bluetooth function operating in 2402-2480MHz. The EUT is powered by DC 3.7V (1 x 3.7V rechargeable battery). The Bluetooth function will be disabled during charging. For more detail information pls. refer to the user manual

Antenna Type: Integral antenna

Modulation Type: GFSK,  $\pi/4$  - DQPSK and 8 - DPSK

Antenna Gain: 2dBi Max

Bluetooth Version: 2.1 + EDR

The normal radiated output power (e.i.r.p) is: -4.0dBm (tolerance: +/- 3dB).

The normal conducted output power is -6.0dBm (tolerance: +/- 3dB).

According to the KDB 447498:

The Maximum peak radiated emission for the EUT is 92.7 dB $\mu$ V/m at 3m in the frequency 2480MHz

The EIRP =  $[(FS \cdot D)^2 / 30]$  mW = -2.53dBm

which is within the production variation.

The Minimum peak radiated emission for the EUT is 89.5dB $\mu$ V/m at 3m in the frequency 2402MHz

The EIRP =  $[(FS \cdot D)^2 / 30]$  mW = -5.73dBm

which is within the production variation.

The maximum conducted output power specified is -3.0dBm= 1.26mW

The source- based time-averaging conducted output power

=1.26\* Duty cycle mW =1.26 mW(Duty cycle =100%)

The SAR Exclusion Threshold Level:

= 3.0 \* (min. test separation distance, mm) / sqrt(freq. in GHz)

= 3.0 \* 5 / sqrt (2.480) mW

= 9.53 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

---

FCC ID: YFK-1511233DA