

RF Exposure Evaluation declaration

Product Name : Full HD Video Wireless Transmitter Module

Model No. : ZRF-31100F

FCC ID : YG7ZRF31100F

Applicant : ZINWELL CORPORATION

Address : 7F 512, Yuan Shan Road, Chung Ho City, Taipei Hsien 235, Taiwan

Date of Receipt : Oct. 14, 2010

Date of Declaration : Nov. 03, 2010

Report No. : 10B253R-RFUSP46V01

The declaration results relate only to the samples calculated.

The declaration shall not be reproduced except in full without the written approval of Quietek Corporation.

This report must not be used to claim product endorsement by NVLAP any agency of the U.S. Government

1. RF Exposure Evaluation

1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

1.3. Test Result of RF Exposure Evaluation

Product : Full HD Video Wireless Transmitter Module
 Test Item : RF Exposure Evaluation
 Test Site : No.3 OATS

Operation band 5745MHz-5825MHz -20MHz BW

Output Power Into Antenna & RF Exposure Evaluation Distance (3.83dBi):

Channel	Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
1	5745.00	517.6068	0.248731
3	5785.00	436.5158	0.209764
5	5825.00	421.6965	0.202642

Operation band 5745MHz-5825MHz -40MHz BW

Output Power Into Antenna & RF Exposure Evaluation Distance (3.83dBi):

Channel	Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
1	5755.00	441.5704	0.212193
2	5795.00	406.4433	0.195313

Operation band 5180MHz-5240MHz -20MHz BW

Output Power Into Antenna & RF Exposure Evaluation Distance (3.42dBi):

Channel	Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
1	5180.00	41.7830	0.018270
2	5200.00	40.0867	0.017528
4	5240.00	42.6580	0.018652

Operation band 5180MHz-5240MHz -40MHz BW

Output Power Into Antenna & RF Exposure Evaluation Distance (3.42dBi):

Channel	Frequency (MHz)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)
1	5190.00	32.3594	0.014149
2	5230.00	40.8319	0.017854