

1.2. Operational Description

The EUT is a Full HD Video Wireless Receiver Module with a built-in 5GHz transceiver, together with Full HD Video Wireless Transmitter Module. It has a MISO design of five channel and one slow rate output wireless channel, which generates an upstream channel for data content transmissions.

The data modulation is OFDM, using five antennas to support 1(Transmit) * 5(Receive) technology. The device only provided one transmitting speed 30kbps in 20MHz bandwidth mode and 60kbps in 40MHz bandwidth mode.

Presents the ultimate solution for converting any High Definition (HD) system, including Full HD, into a wireless one. These add-on modules enable wireless A/V applications that fit easily into the living room and eliminate traditional A/V wiring. The perfect HD video and audio quality and the high robustness are unmatched by any other wireless technology and present a true alternative to cable. The WHDI system transmits uncompressed video and audio streams wirelessly and thus simplifies and eliminates system issues, such as: lip-sync, large buffers and other burdens like retransmissions or error propagation.

The device can receive audio and video signal from associate equipment, device will transmit signal to request associate equipment change transmission frequency.

The IC AMN2220 WHDI baseband receiver chip is the heart of the ZRF32100 WHDI Receiver module. The AMN2220 interfaces the A/V sink through the WHDI connector and is controlled by the internal MAC uC. The AMN2220 is based on MIMO technology receiving up to five input channels. Five analog-to-digital converters and one digital-to-analog converter are embedded within the chip.

The AMN2220 internal PLL accepts an input clock frequency of 40MHz. The input frequency is multiplied and then used as an internal system clock.

The IC AMN3210 is a fully-integrated Zero-IF MIMO receiver specifically designed for WHDI applications using OFDM modulation for single-band 4.9 GHz to 5.9 GHz. The device consists of:

- Five Complete Downlink Zero-IF Receivers.
- One Uplink Direct Conversion Transmitter.
- Integrated Synthesizer/VCO.
- Internal DC Servo Loops.
- RSSI, RF and Baseband Control Interface.
- Power Management Unit.
- 3-Wire SPI Interface.

To complete the RF front-end solution, the AMN3210 uses external PA, RF Band Pass Filters (BPF), RF BALUNs and a few passive components.

The device antenna are use five FIFA and printed on PCB; for receiver function there are support two external antenna which can instead of printed antenna.

The frequency band 5250-5350MHz and 5470 – 5725MHz are not support 20M bandwidth mode. This device is Master equipment.

The major change filed under this application is:

Change #1: Add the plastics Cover

Product Name: Full HD Video Wireless Receiver

Model number: ZWD-2222R, ZWD-2322R, ZWD-2422R, ZWD-2522R, ZWD-2622R,
ZWD-2722R, ZWD-2822R, ZWD-1222R, BV-2222R, BV-2322R,
BV-2422R, BV-2522R, BV-2622R, BV-2722R, BV-2822R,
BV-1222R

Trade name: ZINWELL, brite-view

Change #2: Add the frequency band from 5250-5350MHz and 5470 – 5725MHz by software.