

RF Exposure evaluation

Exposure category: General population/uncontrolled environment

EUT Type: Production Unit

Device Type: Mobile Device

Refer Standard: KDB 447498 D01 General RF Exposure Guidance v06

FCC Part 2 §2.1091

FCC ID: YGM-E300A

1. Reference

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

KDB447498 D01: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies

2. Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

3. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

4. Antenna Information

use antennas certificated as follows provided by manufacturer;

Internal Identification	Antenna Identification in Internal photos	Antenna type and antenna number	Operate frequency band	Maximum antenna gain
Antenna 1	2.4G Wifi	PCB Antenna	2412~2462MHz	3.5 dBi
Antenna 1	BT	PCB Antenna	2402~2480MHz	3.5 dBi
Antenna 2	5G Wifi	PCB Antenna	5180~5825MHz	5.9 dBi

Note :2.4G Wifi & BT antenna and 5G Wifi antenna cannot transmit at the same time. 2.4G WLAN and BT share the same antenna port and cannot transmit simultaneously.

5. Result

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r = 20\text{cm}$, as well as the gain of the used BT antenna is 3.5dBi, the RF power density can be obtained.

EDR

Freq. (MHz)	Output Power (dBm)	Target power W/ tolerance (dBm)	Max tune up power tolerance (dBm)	Output power to antenna (mW)	Ant Gain (dBi)	Power Density at R=20cm (mW/cm ²)	Limit (mW/c m ²)	Result
GFSK								
2402	2.132	2±1.0	3	1.995	3.5	0.00089	1	Pass
2441	2.895	3±1.0	4	2.512	3.5	0.00112	1	Pass
2480	3.742	4±1.0	5	3.162	3.5	0.00141	1	Pass
$\pi/4$ DQPSK								
2402	2.704	3±1.0	4	2.512	3.5	0.00112	1	Pass
2441	3.322	3±1.0	4	2.512	3.5	0.00112	1	Pass
2480	3.904	4±1.0	5	3.162	3.5	0.00141	1	Pass
8DPSK								
2402	2.959	3±1.0	4	2.512	3.5	0.00112	1	Pass
2441	3.595	4±1.0	5	3.162	3.5	0.00141	1	Pass
2480	4.212	4±1.0	5	3.162	3.5	0.00141	1	Pass

BLE

Freq. (MHz)	Output Power (dBm)	Target power W/ tolerance (dBm)	Max tune up power tolerance (dBm)	Output power to antenna (mW)	Ant Gain (dBi)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
GFSK								
2402	1.933	2±1.0	3	1.995	3.5	0.00089	1	Pass
2440	2.720	3±1.0	4	2.512	3.5	0.00112	1	Pass
2480	3.486	3±1.0	4	2.512	3.5	0.00112	1	Pass

2.412GHz – 2.462 GHz

Modulation Type	Target power W/ tolerance (dBm)	Max tune up power tolerance (dBm)	Max Output power to antenna (mW)	Antenna Gain	Antenna Gain (linear)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
802.11b								
2412	16±1.0	17	50.119	3.5	2.2387	0.02232	1	Pass
2437	17±1.0	18	63.096	3.5	2.2387	0.02810	1	Pass
2462	17±1.0	18	63.096	3.5	2.2387	0.02810	1	Pass
802.11g								
2412	18±1.0	19	79.433	3.5	2.2387	0.03538	1	Pass
2437	19±1.0	20	100.000	3.5	2.2387	0.04454	1	Pass
2462	19±1.0	20	100.000	3.5	2.2387	0.04454	1	Pass
802.11n20								
2412	18±1.0	19	79.433	3.5	2.2387	0.03538	1	Pass
2437	19±1.0	20	100.000	3.5	2.2387	0.04454	1	Pass
2462	19±1.0	20	100.000	3.5	2.2387	0.04454	1	Pass
802.11n40								
2422	19±1.0	20	100.000	3.5	2.2387	0.04454	1	Pass
2437	20±1.0	21	125.893	3.5	2.2387	0.05607	1	Pass
2452	20±1.0	21	125.893	3.5	2.2387	0.05607	1	Pass

5.18 GHz -5.24 GHz

Modulation Type	Target power W/ tolerance (dBm)	Max tune up power tolerance (dBm)	Max Output power to antenna (mW)	Antenna Gain	Antenna Gain (linear)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
802.11a								
5180	4±1.0	5	3.162	5.9	3.8905	0.00245	1	Pass
5200	3±1.0	4	2.512	5.9	3.8905	0.00194	1	Pass
5240	4±1.0	5	3.162	5.9	3.8905	0.00245	1	Pass
802.11n20								
5180	6±1.0	7	5.012	5.9	3.8905	0.00388	1	Pass
5200	7±1.0	8	6.310	5.9	3.8905	0.00488	1	Pass
5240	8±1.0	9	7.943	5.9	3.8905	0.00615	1	Pass
802.11n40								
5190	3±1.0	4	2.512	5.9	3.8905	0.00194	1	Pass
5230	4±1.0	5	2.512	5.9	3.8905	0.00245	1	Pass

802.11ac20								
5180	3±1.0	4	2.512	5.9	3.8905	0.00194	1	Pass
5200	3±1.0	4	2.512	5.9	3.8905	0.00194	1	Pass
5240	4±1.0	5	3.162	5.9	3.8905	0.00245	1	Pass
802.11ac40								
5190	3±1.0	4	2.512	5.9	3.8905	0.00194	1	Pass
5230	4±1.0	5	3.162	5.9	3.8905	0.00245	1	Pass
802.11ac80								
5210	1±1.0	2	1.585	5.9	3.8905	0.00123	1	Pass

5.745 GHz -5.825 GHz								
Modulation Type	Target power W/ tolerance (dBm)	Max tune up power tolerance (dBm)	Max Output power to antenna (mW)	Antenna Gain	Antenna Gain (linear)	Power Density at R=20cm (mW/cm ²)	Limit (mW/cm ²)	Result
802.11a								
5745	7±1.0	8	6.310	5.9	3.8905	0.00488	1	Pass
5785	7±1.0	8	6.310	5.9	3.8905	0.00488	1	Pass
5825	8±1.0	9	7.943	5.9	3.8905	0.00615	1	Pass
802.11n20								
5745	6±1.0	7	5.012	5.9	3.8905	0.00388	1	Pass
5785	6±1.0	7	5.012	5.9	3.8905	0.00388	1	Pass
5825	7±1.0	8	6.310	5.9	3.8905	0.00619	1	Pass
802.11n40								
5755	5±1.0	6	3.981	5.9	3.8905	0.00308	1	Pass
5795	5±1.0	6	3.981	5.9	3.8905	0.00308	1	Pass
802.11ac20								
5745	5±1.0	6	3.981	5.9	3.8905	0.00308	1	Pass
5785	5±1.0	6	3.981	5.9	3.8905	0.00308	1	Pass
5825	5±1.0	6	3.981	5.9	3.8905	0.00308	1	Pass
802.11ac40								
5755	11±1.0	12	15.849	5.9	3.8905	0.01227	1	Pass
5795	11±1.0	12	15.849	5.9	3.8905	0.01227	1	Pass
802.11ac80								
5775	5±1.0	6	3.981	5.9	3.8905	0.00308	1	Pass

Note: The estimation distance is 20cm

6. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.