







ISO/IEC17025Accredited Lab.

Report No: FCC/IC 1210109-01 File reference No: 2012-09-03

Applicant: Kobian Canada INC.

Product: MID

Model No: HS-10DTB2, HS-10DTB3, HS-10DTB4

Trademark: Hipstreet

Test Standards: FCC Part 15 Subpart C, Paragraph 15.247

RSS-210 Issue 8

Test result:

It is herewith confirmed and found to comply with the

requirements set up by ANSI C63.4,FCC Part 15 Subpart C, Paragraph 15.247 regulations and RSS-210 Issue 8 for the

evaluation of electromagnetic compatibility

Approved By

Jack Chung

Jack Chung Manager

Dated: Sep 03, 2012

Results appearing herein relate only to the sample tested The technical reports is issued errors and omissions exempt and is subject to withdrawal at

SHENZHEN TIMEWAY TECHNOLOGY CONSULTING CO., LTD

5/F,Block 4, Anhua Industrial Zone.,No.8 TaiRan Rd.CheGongMiao,FuTian District, Shenzhen,CHINA.

Tel (755) 83448688 Fax (755) 83442996

Report No: 1210109-01 Page 2 of 126

Date: 2012-09-03



Special Statement:

The testing quality ability of our laboratory meet with "Quality Law of People's Republic of China" Clause 19.

The testing quality system of our laboratory meet with ISO/IEC-17025 requirements, which is approved by CNAL. This approval result is accepted by MRA of APLAC.

Our test facility is recognized, certified, or accredited by the following organizations:

CNAL-LAB Code: L2292

The EMC Laboratory has been assessed and in compliance with CNAL/AC01:2002 accreditation criteria for testing Laboratories (identical to ISO/IEC 17025:1999 General Requirements) for the Competence of testing Laboratories.

FCC-Registration No.: 899988

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 899988.

IC-Registration No.: IC5205A-02

The EMC Laboratory has been registered and fully described in a report filed with the (IC) Industry Canada. The acceptance letter from the IC is maintained in our files. Registration IC No.: 5205A-02.

Page 3 of 126

Report No: 1210109-01

Date: 2012-09-03



Test Report Conclusion

Content

1.0	General Details	4
1.1	Test Lab Details.	4
1.2	Applicant Details.	4
1.3	Description of EUT	4
1.4	Submitted Sample.	5
1.5	Test Duration.	5
1.6	Test Uncertainty.	5
1.7	Test By	5
2.0	List of Measurement Equipment	6
3.0	Technical Details	9
3.1	Summary of Test Results.	9
3.2	Test Standards.	9
4.0	EUT Modification.	9
5.0	Power Line Conducted Emission Test.	10
5.1	Schematics of the Test.	10
5.2	Test Method and Test Procedure.	10
5.3	Configuration of the EUT.	10
5.4	EUT Operating Condition.	11
5.5	Conducted Emission Limit.	11
5.6	Test Result.	11
6.0	Radiated Emission test.	14
6.1	Test Method and Test Procedure.	14
5.2	Configuration of the EUT.	14
6.3	EUT Operation Condition.	14
6.4	Radiated Emission Limit.	15
7.0	6dB Bandwidth Measurement.	42
8.0	Maximum Peak Output Power	79
9.0	Power Spectral Density Measurement.	82
10.0	Out of Band Measurement.	100
11.0	Antenna Requirement.	117
12.0	FCC ID Label.	118
13.0	Photo of Test Setup and EUT View	119

Report No: 1210109-01 Page 4 of 126

Report No: 1210109-01 Date: 2012-09-03

1.0 General Details

1.1 Test Lab Details

Name: SHENZHEN TIMEWAY TECHNOLOGY CONSULTING CO., LTD

Address: 5/F,Block 4, Anhua Industrial Zone.,No.8 TaiRan Rd.CheGongMiao,FuTian District,

Shenzhen, CHINA.

Telephone: (755) 83448688 Fax: (755) 83442996

Site on File with the Federal Communications Commission – United Sates

Registration Number: 899988

For 3m & 10 m OATS

Site Listed with Industry Canada of Ottawa, Canada

Registration Number: IC: 5205A-02

For 3m & 10 m OATS

1.2 Applicant Details

Applicant: Kobian Canada INC.

Address: 560 Denison Street, Unit 5, Markham, Ontario, L3R 2M8, Canada

Telephone: (001) 905-948-9967 Fax: (001) 905-948-1601

1.3 Description of EUT

Product: MID

Manufacturer: Kobian Canada INC.

Address: 560 Denison Street, Unit 5, Markham, Ontario, L3R 2M8, Canada

Brand Name: Hipstreet
Model Number: HS-10DTB2

Additional Model Number: HS-10DTB3, HS-10DTB4

Power Adapter Input: DC5V, with 2 Li-ion Battery 3.7V, 6500mAh

(Recharge with AC/DC Adapter Input: AC 100-240V~, 50/60Hz, 0.32A;

Output: DC5V, 2000mA)

Type of Modulation IEEE 802.11b : DSSS (CCK, QPSK, DBPSK)

IEEE 802.11g/n (HT20/HT40) : OFDM(64QAM, 16QAM, QPSK, BPSK)

Frequency range IEEE 802.11b/g/n (HT20) : 2412-2462MHz;

IEEE 802.11n HT40: 2422MHz-2452MHz

Channel Spacing IEEE 802.11b/g/n (HT20/40): 5MHz

Air Data Rate IEEE 802.11b : 11, 5.5, 2, 1 Mbps

IEEE 802.11g: 54, 48,36, 24, 18, 12, 9, 6 Mbps

IEEE 802.11n HT20: 150, 117, 104, 78, 65, 58.5, 52, 39, 26, 19.5, 13, 6 Mbps

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No: 1210109-01 Page 5 of 126

Date: 2012-09-03



IEEE 802.11n HT40: 150, 117, 104, 78, 65, 58.5, 52, 39, 26, 19.5, 13, 6 Mbps

Frequency Selection By software

Channel Number IEEE 802.11b/g/n (HT20): 11 Channels

IEEE 802.11n HT40: 7 Channels

Antenna: PCB Antenna with maximum gain 2.0dBi

1.4 Submitted Sample: 2 Samples

1.5 Test Duration

2012-08-20 to 2012-09-03

1.6 Test Uncertainty

Conducted Emissions Uncertainty = 3.6dB Radiated Emissions Uncertainty = 4.7dB

1.7 Test Engineer

Terry Tang

The sample tested by

Print Name: Terry Tang

Page 6 of 126

Report No: 1210109-01

Date: 2012-09-03



2.0		Test Equip	ments		
Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
ESPI Test Receiver	ROHDE&SCHWARZ	ESPI 3	100379	2012-04-21	2013-04-20
TWO Line-V-NETW	ROHDE&SCHWARZ	EZH3-Z5	100294	2012-04-21	2013-04-20
TWO Line-V-NETW	ROHDE&SCHWARZ	EZH3-Z5	100253	2012-04-21	2013-04-20
Ultra Broadband ANT	ROHDE&SCHWARZ	HL562	100157	2012-04-21	2013-04-20
ESDV Test Receiver	ROHDE&SCHWARZ	ESDV	100008	2012-04-21	2013-04-20
Impuls-Begrenzer	ROHDE&SCHWARZ	ESH3-Z2	100281	2012-04-21	2013-04-20
System Controller	CT	SC100	-		
Printer	EPSON	РНОТО ЕХЗ	CFNH234850		
Computer	IBM	8434	1S8434KCE99BLXL O*	-	-
Loop Antenna	EMCO	6502	00042960	2012-04-21	2013-04-20
ESPI Test Receiver	ROHDE&SCHWARZ	ESI26	838786/013	2012-04-21	2013-04-20
3m OATS			N/A	2012-04-21	2013-04-20
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170265	2012-04-21	2013-04-20
Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-631	2012-04-21	2013-04-20
Power meter	Anritsu	ML2487A	6K00003613	2012-04-21	2013-04-20
Power sensor	Anritsu	MA2491A	32263	2012-04-21	2013-04-20
Bilog Antenna	Schwarebeck	VULB9163	9163/340	2012-04-21	2013-04-20
LISN	AFJ	LS16C	10010947251	2012-04-21	2013-04-20
LISN (Three Phase)	Schwarebeck	NSLK 8126	8126453	2012-04-21	2013-04-20
9*6*6 Anechoic			N/A	2012-04-21	2013-04-20
EMI Test Receiver	RS	ESCS30	100139	2012-04-21	2013-04-20
LISN	AFJ	LS16C	10010947251	2012-04-21	2013-04-20
LISN (Three Phase)	Schwarebeck	NSLK 8126	8126453	2012-04-21	2013-04-20

Report No: 1210109-01 Page 7 of 126



2.1 **Auxiliary Equipment**

Date: 2012-09-03

Name	Model No.	Serial No.	Manufacturer	Cable	FCC ID/DOC
TF Card			Kingston		
Earphone					
LCD Monitor	P2450		SAMSUNG		FCC DOC

Report No: 1210109-01 Page 8 of 126

Date: 2012-09-03



3. DESCRIPTION OF TEST MODES

IEEE 802.11b, 802.11g, 802.11n (HT20) mode

The EUT had been tested under operating condition. There are three channels have been tested as following:

Channel	Frequency (MHz)
Low	2412
Middle	2437
High	2462

IEEE 802.11b mode: 11Mbps data rate (worst case) was chosen for full testing. IEEE 802.11g mode: 54Mbps data rate (worst case) was chosen for full testing. IEEE 802.11n (HT20) mode: 65Mbps data rate (worst case) were chosen for full testing

IEEE 802.11n HT40

The EUT had been tested under operating condition. There are three channels have been tested as following:

Channel	Frequency (MHz)
Low	2422
Mid	2437
High	2452

IEEE 802.11n HT40 mode: 65Mbps data rate (worst case) was chosen for full testing.

The worst-case data rates are determined according to the description above, based on the investigations by measuring the PSD and average power across all the data rates, bandwidths, modulations and spatial stream modes.

Page 9 of 126

Report No: 1210109-01

Date: 2012-09-03



3.0 **Technical Details**

3.1 **Summary of test results**

Standard	Test Type	Result	Notes
FCC Part 15, Paragraph 15.107	Conducted Emission Test	PASS	Complies
& 15.207 & RSS-210 Issue 8			
	Spectrum bandwidth of a		Complies
FCC Part 15 Subpart C	Orthogonal Frequency		
Paragraph 15.247(a)(2) Limit &	Division Multiplex System	PASS	
RSS-210 Issue 8	Limit: 6dB		
	bandwidth>500kHz		
FCC Part 15, Paragraph	Maximum peak output		
15.247(b) & RSS-210 Issue 8	power	PASS	Complies
12.217(3) & 135 210 15546 0	Limit: max. 30dBm		
FCC Part 15, Paragraph	Transmitter Radiated	PASS	Complies
15.109,15.205 & 15.209 &	Emission		
RSS-210 Issue 8	Limit: Table 15.209		
FCC Part 15, Paragraph	Power Spectral Density	PASS	Complies
15.247(e) & RSS-210 Issue 8	Limit: max. 8dBm		
FCC Part 15, Paragraph	Out of Band Emission and	PASS	Complies
15.247(d) & RSS-210 Issue 8	Restricted Band		
	Radiation		
	Limit: 20dB less than		
	peak value of fundamental		
	frequency		
	Restricted band limit:		
	Table 15.209		

3.2 **Test Standards**

FCC Part 15 Subpart & Subpart C, Paragraph 15.247 & RSS-210 Issue 8

EUT Modification 4.0


No modification by Shenzhen Timeway Technology Consulting Co., Ltd

Page 10 of 126

Report No: 1210109-01 Date: 2012-09-03 草 TIMEWAY TESTING LABS

5. Power Line Conducted Emission Test

5.1 Schematics of the test




EUT: Equipment Under Test

5.2 Test Method and test Procedure

The EUT was tested according to ANSI C63.4-2003. The Frequency spectrum From 0.15MHz to 30MHz was investigated. The LISN used was 50ohm/50uH as specified by section 5.1 of ANSI C63.4 –2003.

Test Voltage: 120V~, 60Hz Block diagram of Test setup



5.3 Configuration of The EUT

The EUT was configured according to ANSI C63.4-2003. All interface ports were connected to the appropriate peripherals. All peripherals and cables are listed below.

A. EUT

Device	Manufacturer	Model	FCC ID/IC
MID	Kobian Canada INC.	HS-10DTB2, HS-10DTB3,	IC: 8012A-10DTB2
MID		HS-10DTB4	FCC ID: YH5-10DTB2

B. Internal Device

Device	Manufacturer	Model	FCC ID/DOC
N/A			

The report refers only to the sample tested and does not apply to the bulk.

Report No: 1210109-01 Page 11 of 126

Date: 2012-09-03



C. Peripherals

Device	Manufacturer	Model	FCC ID/DOC	Cable
N/A				

5.4 EUT Operating Condition

Operating condition is according to ANSI C63.4 -2003.

- A Setup the EUT and simulators as shown on follow
- B Enable AF signal and confirm EUT active to normal condition

5.5 Power line conducted Emission Limit according to Paragraph 15.207 and 15.107 and RSS-210

Frequency	Class A Lim	its (dB µ V)	Class B Limits (dB µ V)		
(MHz)	Quasi-peak Level Average Level		Quasi-peak Level	Average Level	
$0.15 \sim 0.50$	79.0	66.0	66.0~56.0*	56.0~46.0*	
$0.50 \sim 5.00$	73.0	60.0	56.0	46.0	
$5.00 \sim 30.00$	73.0	60.0	60.0	50.0	

Notes:

- 1. *Decreasing linearly with logarithm of frequency.
- 2. The tighter limit shall apply at the transition frequencies

5.6 Test Results

The frequency spectrum from 0.15MHz to 30MHz was investigated. All reading are quasi-peak values with a resolution bandwidth of 9kHz.

Date: 2012-09-03



A: Conducted Emission on Live Terminal (150kHz to 30MHz)

EUT Operating Environment


Temperature: 26°C Humidity: 65%RH Atmospheric Pressure: 101 KPa

EUT set Condition: Charging Mode

Equipment Level: Class B

Results: PASS

Please refer to following diagram for individual



Frequency	Line	Reading(dBμV)		Limit(dBµV)	
(MHz)		Quasi-peak	Average	Quasi-peak	Average
0.360	Live	43.12	28.52	58.73	48.73
1.165	Live	40.97	26.87	56.00	46.00
2.594	Live	38.44	26.44	56.00	46.00
4.925	Live	41.37	26.87	56.00	46.00

Report No: 1210109-01 Page 13 of 126

Date: 2012-09-03



B: Conducted Emission on Neutral Terminal (150kHz to 30MHz)

EUT Operating Environment


Temperature: 26°C Humidity: 65%RH Atmospheric Pressure: 101 KPa

EUT set Condition: Charging Mode

Equipment Level: Class B

Results: Pass

Please refer to following diagram for individual



Frequency	Lina	Line Reading(dBµV)		Limit(dBµV)	
(MHz)	Line	Quasi-peak	Average	Quasi-peak	Average
0.446	Neutral	41.21	36.71	56.95	46.95
1.073	Neutral	41.83	32.83	56.00	46.00
2.592	Neutral	40.14	31.44	56.00	46.00
4.739	Neutral	39.00	28.40	56.00	46.00

Report No: 1210109-01 Page 14 of 126

Date: 2012-09-03



6 Radiated Emission Test

- 6.1 Test Method and test Procedure:
- (1) The EUT was tested according to ANSI C63.4 –2003. The radiated test was performed at Timeway Laboratory. This site is on file with the FCC laboratory division, Registration No.899988
- (2) The EUT, peripherals were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m. All set up is according to ANSI C63.4-2003.
- (3) The frequency spectrum from 30 MHz to 25 GHz was investigated. All readings from 30 MHz to 1 GHz are Quasi-peak values with a resolution bandwidth of 120 kHz. For measurement above 1GHz, peak values with RBW=VBW=1MHz and PK detector. AV value with RBW=1MHz, VBW=10Hz and PK detector. Measurements were made at 3 meters.
- (4) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- (5) Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance is with all installation combinations. All data was recorded in the peak detection mode. Quasi-peak readings was performed only when an emission was found to be marginal (within -4 dB of specification limit), and are distinguished with a "QP" in the data table.
- (6) The antenna polarization : Vertical polarization and Horizontal polarization.

Block diagram of Test setup Distance = 3m Computer Pre -Amplifier Furn-table Receiver

- 6.2 Configuration of The EUT

 Same as section 5.3 of this report
- 6.3 EUT Operating Condition
 Same as section 5.4 of this report.

Report No: 1210109-01 Page 15 of 126

Date: 2012-09-03



6.4 Radiated Emission Limit

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below:

Frequencies in restricted band are complied to limit on Paragraph 15.209 and 15.109 and RSS-210

Frequency Range (MHz)	Distance (m)	Field strength (dB µ V/m)
30-88	3	40.0
88-216	3	43.5
216-960	3	46.0
Above 960	3	54.0

Note:

- 1. RF Voltage (dBuV) = 20 log RF Voltage (uV)
- 2. In the Above Table, the higher limit applies at the band edges.
- 3. Distance refers to the distance in meters between the measuring instrument antenna and the EUT
- 4. This is a handhold device. The radiated emissions should be tested under 3-axes position (Lying, Side, and Stand), After pre-test. It was found that the worse radiated emission was get at the lying position.

Report No: 1210109-01 Page 16 of 126

Date: 2012-09-03



Test result

General Radiated Emission Data and Harmonics Radiated Emission Data

Radiated Emission In Horizontal (30MHz----1000MHz)

EUT set Condition: Keep WIFI Transmitting

Results: Pass

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \u03b4 V/m)
202.175	31.81	Н	43.50
362.225	32.73	Н	46.00
403.450	35.72	Н	46.00
505.300	39.84	Н	46.00
682.325	38.26	Н	46.00
505.300	40.09	V	46.00
679.900	38.26	V	46.00
401.025	36.56	V	46.00
202.175	33.82	V	43.50
139.125	32.28	V	43.50
481.050	37.45	V	46.00

Page 17 of 126


Report No: 1210109-01

Date: 2012-09-03




Test Figure:

H



Test Figure:

V



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No: 1210109-01 Page 18 of 126

Date: 2012-09-03



Test result

General Radiated Emission Data and Harmonics Radiated Emission Data

Radiated Emission In Horizontal (30MHz----1000MHz)

EUT set Condition: Keep WIFI Receiving and Full Load

Results: Pass

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \u03b4 V/m)
559.991	38.82	Н	46.00
321.000	37.01	Н	46.00
401.025	39.48	Н	46.00
641.100	38.70	Н	46.00
505.300	38.23	Н	46.00
39.024	34.34	V	40.00
202.175	31.69	V	43.50
403.450	36.96	V	46.00
505.300	39.52	V	46.00
563.500	39.73	V	46.00
641.100	39.65	V	46.00

Page 19 of 126


Report No: 1210109-01

Date: 2012-09-03




Test Figure:

Н



Test Figure:

V



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No: 1210109-01 Page 20 of 126

Date: 2012-09-03



Operation Mode: Transmitting & Receiving under CH01 for 11g at 54Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \u03b4 V/m)
2412.00	96.33 (PK)	Н	Fundamental Frequency
2412.00	97.12 (PK)	V	Fundamental Frequency
4824.00	47.85 (PK)	Н	74(Peak)/ 54(AV)
4824.00	46.36 (PK)	V	74(Peak)/ 54(AV)
7236.00		H/V	74(Peak)/ 54(AV)
9648.00		H/V	74(Peak)/ 54(AV)
12060		H/V	74(Peak)/ 54(AV)
14472		H/V	74(Peak)/ 54(AV)
16884		H/V	74(Peak)/ 54(AV)
19296		H/V	74(Peak)/ 54(AV)
21708		H/V	74(Peak)/ 54(AV)
24120		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11g mode 54Mbps

Date: 2012-09-03



Operation Mode: Transmitting & Receiving under CH06 for 11g at 54Mbps

	8 8	Ü	
Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \mu V/m)
2437.00	95.47 (PK)	Н	Eundamental Eragueney
2437.00	95.94 (PK)	V	Fundamental Frequency
4874.00	46.43 (PK)	Н	74(Peak)/ 54(AV)
4874.00	49.20 (PK)	V	74(Peak)/ 54(AV)
7311.00		H/V	74(Peak)/ 54(AV)
9748.00		H/V	74(Peak)/ 54(AV)
12185	-	H/V	74(Peak)/ 54(AV)
14622	-	H/V	74(Peak)/ 54(AV)
17059		H/V	74(Peak)/ 54(AV)
19496		H/V	74(Peak)/ 54(AV)
21933		H/V	74(Peak)/ 54(AV)
24370		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11g mode 54 Mbps

Operation Mode: Transmitting & Receiving under CH11 for 11g at 54Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \(\mu \)V/m)
2462.00	95.45 (PK)	Н	Fundamental Frequency
2462.00	97.36 (PK)	V	Fundamental Frequency
4924	49.81 (PK)	Н	74(Peak)/ 54(AV)
4924	(PK)	V	74(Peak)/ 54(AV)
7368	-	H/V	74(Peak)/ 54(AV)
9848	1	H/V	74(Peak)/ 54(AV)
12310	•	H/V	74(Peak)/ 54(AV)
14772	•	H/V	74(Peak)/ 54(AV)
17234	-	H/V	74(Peak)/ 54(AV)
19696	-	H/V	74(Peak)/ 54(AV)
22158		H/V	74(Peak)/ 54(AV)
24650	-	H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11g mode at 54 Mbps

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Date: 2012-09-03




Please refer to the following test plots for details:

CH01 for 11g at 54Mbps: Horizontal



CH01 for 11g at 54Mbps: Vertical



The report refers only to the sample tested and does not apply to the bulk.


Page 23 of 126

Report No: 1210109-01


Date: 2012-09-03



CH06 for 11g at 54Mbps: Vertical



CH06 for 11g at 54Mbps: Horizontal



The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.


Date: 2012-09-03



CH11 for 11g at 54Mbps: Vertical



CH11 for 11g at 54Mbps: Horizontal



Note: For radiated Emissions from 18-25GHz, it is only the floor noise.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Date: 2012-09-03



Operation Mode: Transmitting & Receiving under CH01 for 11b at 11Mbps

_				_
	Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \mu V/m)
	2412.00	95.76 (PK)	V	Even do montal Engavon av
	2412.00	98.71 (PK)	Н	Fundamental Frequency
	4824.00	47.32 (PK)	Н	74(Peak)/ 54(AV)
	4824.00	49.29 (PK)	V	74(Peak)/ 54(AV)
	7236.00		H/V	74(Peak)/ 54(AV)
	9648.00		H/V	74(Peak)/ 54(AV)
	12060		H/V	74(Peak)/ 54(AV)
	14472	-	H/V	74(Peak)/ 54(AV)
	16684		H/V	74(Peak)/ 54(AV)
	19296		H/V	74(Peak)/ 54(AV)
	21708		H/V	74(Peak)/ 54(AV)
	24120		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11b mode 11Mbps

Operation Mode: Transmitting & Receiving under CH06 for 11b at 11Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \(\mu \) V/m)
2437.00	91.13 (PK)	Н	Fundamental Frequency
2437.00	94.65 (PK)	V	Fundamental Frequency
4874.00	45.01 (PK)	Н	74(Peak)/ 54(AV)
4874.00	47.50 (PK)	V	74(Peak)/ 54(AV)
7311.00	-	H/V	74(Peak)/ 54(AV)
9748.00	1	H/V	74(Peak)/ 54(AV)
12185	•	H/V	74(Peak)/ 54(AV)
14622	•	H/V	74(Peak)/ 54(AV)
17059	-	H/V	74(Peak)/ 54(AV)
19496	-	H/V	74(Peak)/ 54(AV)
21933		H/V	74(Peak)/ 54(AV)
24370	-	H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11b mode 11Mbps

The report refers only to the sample tested and does not apply to the bulk.

Report No: 1210109-01 Page 26 of 126

Date: 2012-09-03



Operation Mode: Transmitting & Receiving under CH11 for 11b at 11Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \mu V/m)
2462.00	96.24 (PK)	Н	Fundamental Frequency
2462.00	96.45 (PK)	V	rundamental Frequency
4924	50.29 (PK)	Н	74(Peak)/ 54(AV)
4924	52.13 (PK)	V	74(Peak)/ 54(AV)
7368		H/V	74(Peak)/ 54(AV)
9848		H/V	74(Peak)/ 54(AV)
12310		H/V	74(Peak)/ 54(AV)
14772		H/V	74(Peak)/ 54(AV)
17234		H/V	74(Peak)/ 54(AV)
19696		H/V	74(Peak)/ 54(AV)
22158		H/V	74(Peak)/ 54(AV)
24650		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit


- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11b mode at 11Mbps

Date: 2012-09-03




Please refer to the following test plots for details:

CH01 for 11b at 11Mbps: Horizontal



CH01 for 11b at 11Mbps: Vertical



The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.


Date: 2012-09-03



CH06 for 11b at 11Mbps: Vertical



CH06 for 11b at 11Mbps: Horizontal




The report refers only to the sample tested and does not apply to the bulk.


Date: 2012-09-03



CH11 for 11b at 11Mbps: Vertical



CH11 for 11b at 11Mbps: Horizontal



Note: For radiated Emissions from 18-25GHz, it is only the floor noise.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Date: 2012-09-03



Operation Mode: Transmitting & Receiving under CH01 for 11n HT20 at 65Mbps

Frequency (MHz)	Level@3m (dB \u03ba V/m)	Antenna Polarity	Limit@3m (dB \(\mu \)V/m)
2412.00	92.38 (PK)	Н	Fundamental Frequency
2412.00	95.92 (PK)	V	Fundamental Frequency
4824.00	48.12 (PK)	Н	74(Peak)/ 54(AV)
4824.00	48.10 (PK)	V	74(Peak)/ 54(AV)
7236.00		H/V	74(Peak)/ 54(AV)
9648.00		H/V	74(Peak)/ 54(AV)
12060		H/V	74(Peak)/ 54(AV)
14472	-	H/V	74(Peak)/ 54(AV)
16684		H/V	74(Peak)/ 54(AV)
19296		H/V	74(Peak)/ 54(AV)
21708		H/V	74(Peak)/ 54(AV)
24120		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11n (HT20) mode 65Mbps

Operation Mode: Transmitting & Receiving under CH06 for 11n HT20 at 65Mbps

Frequency (MHz)	Level@3m (dB \u03bc V/m)	Antenna Polarity	Limit@3m (dB \(\mu \) V/m)
2437.00	96.05 (PK)	V	Fundamental Frequency
2437.00	93.51 (PK)	Н	Fundamental Frequency
4874.00	46.14 (PK)	V	74(Peak)/ 54(AV)
4874.00	49.19 (PK)	Н	74(Peak)/ 54(AV)
7311.00	1	H/V	74(Peak)/ 54(AV)
9748.00	-	H/V	74(Peak)/ 54(AV)
12185	1	H/V	74(Peak)/ 54(AV)
14622	1	H/V	74(Peak)/ 54(AV)
17059		H/V	74(Peak)/ 54(AV)
19496	-	H/V	74(Peak)/ 54(AV)
21933		H/V	74(Peak)/ 54(AV)
24370		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11n (HT20) mode 65Mbps

The report refers only to the sample tested and does not apply to the bulk.

Report No: 1210109-01 Page 31 of 126

Date: 2012-09-03



Operation Mode: Transmitting & Receiving under CH11 for 11n HT20 at 65Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB µ V/m)
2462.00	96.12 (PK)	Н	Γ
2462.00	95.39 (PK)	V	Fundamental Frequency
4924	48.63 (PK)	Н	74(Peak)/ 54(AV)
4924	49.34 (PK)	V	74(Peak)/ 54(AV)
7368		H/V	74(Peak)/ 54(AV)
9848		H/V	74(Peak)/ 54(AV)
12310		H/V	74(Peak)/ 54(AV)
14772		H/V	74(Peak)/ 54(AV)
17234		H/V	74(Peak)/ 54(AV)
19696		H/V	74(Peak)/ 54(AV)
22158		H/V	74(Peak)/ 54(AV)
24650		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit


- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11n (HT20) mode 65Mbps

Date: 2012-09-03




Please refer to the following test plots for details:

CH01 for 11n HT20 at 65Mbps: Horizontal



CH01 for 11n HT20 at 65Mbps: Vertical




The report refers only to the sample tested and does not apply to the bulk.


Date: 2012-09-03



CH06 for 11n HT20 at 65Mbps: Horizontal



CH06 for 11n HT20 at 65Mbps: Vertical



The report refers only to the sample tested and does not apply to the bulk.


Page 34 of 126

Report No: 1210109-01


Date: 2012-09-03



CH11 for 11n HT20 at 65Mbps: Vertical



CH11 for 11n HT20 at 65Mbps: Horizontal



Note: For radiated Emissions from 18-25GHz, it is only the floor noise.

Date: 2012-09-03



Operation Mode: Transmitting & Receiving under CH01 for 11n HT40 at 65Mbps

			_
Frequency (MHz)	Level@3m (dB \u03bc V/m)	Antenna Polarity	Limit@3m (dB \(\mu \)V/m)
2422.00	95.86 (PK)	V	Fundamental Frequency
2422.00	95.01 (PK)	Н	
4844.00	(PK)	V	74(Peak)/ 54(AV)
4844.00	47.05 (PK)	Н	74(Peak)/ 54(AV)
7266.00		H/V	74(Peak)/ 54(AV)
9688.00		H/V	74(Peak)/ 54(AV)
12110		H/V	74(Peak)/ 54(AV)
14532		H/V	74(Peak)/ 54(AV)
16954		H/V	74(Peak)/ 54(AV)
19376		H/V	74(Peak)/ 54(AV)
21798		H/V	74(Peak)/ 54(AV)
24220		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11n (HT40) mode 65Mbps

Operation Mode: Transmitting & Receiving under CH04 for 11n HT40 at 65Mbps

Frequency (MHz)	Level@3m (dB μ V/m)	Antenna Polarity	Limit@3m (dB \(\mu \) V/m)
2437.00	96.72 (PK)	Н	Fundamental Frequency
2437.00	97.13 (PK)	V	
4874.00	(PK)	Н	74(Peak)/ 54(AV)
4874.00	48.63 (PK)	V	74(Peak)/ 54(AV)
7311.00		H/V	74(Peak)/ 54(AV)
9748.00		H/V	74(Peak)/ 54(AV)
12185		H/V	74(Peak)/ 54(AV)
14622		H/V	74(Peak)/ 54(AV)
17059		H/V	74(Peak)/ 54(AV)
19496		H/V	74(Peak)/ 54(AV)
21933		H/V	74(Peak)/ 54(AV)
24370		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11n (HT40) mode 65Mbps

The report refers only to the sample tested and does not apply to the bulk.

Report No: 1210109-01 Page 36 of 126

Date: 2012-09-03



Operation Mode: Transmitting & Receiving under CH7 for 11n HT40 at 65Mbps

Frequency (MHz)	Level@3m (dB \u03bc V/m)	Antenna Polarity	Limit@3m (dB \u03b4 V/m)
2452.00	97.16 (PK)	Н	Fundamental Frequency
2452.00	95.69 (PK)	V	
4904	50.03 (PK)	Н	74(Peak)/ 54(AV)
4904	42.92 (PK)	V	74(Peak)/ 54(AV)
7356		H/V	74(Peak)/ 54(AV)
9808		H/V	74(Peak)/ 54(AV)
12260		H/V	74(Peak)/ 54(AV)
14712		H/V	74(Peak)/ 54(AV)
17164		H/V	74(Peak)/ 54(AV)
19616		H/V	74(Peak)/ 54(AV)
22068		H/V	74(Peak)/ 54(AV)
24520		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11n (HT40) mode 65Mbps


Report No: 1210109-01

Date: 2012-09-03




Please refer to the following test plots for details:

CH01 for 11n HT40 at 65Mbps: Vertical



CH01 for 11n HT40 at 65Mbps: Horizontal



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


Page 38 of 126

Report No: 1210109-01


Date: 2012-09-03



CH04 for 11n HT40 at 65Mbps: Vertical



CH04 for 11n HT40 at 65Mbps: Horizontal



The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No: 1210109-01


Date: 2012-09-03



CH7 for 11n HT40 at 65Mbps: Vertical



CH7 for 11n HT40 at 65Mbps: Horizontal



Note: For radiated Emissions from 18-25GHz, it is only the floor noise.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No: 1210109-01 Page 40 of 126

Date: 2012-09-03



Radiated Disturbance (1000MHz----18000MHz)

EUT Operating Environment


Temperature:25°C Humidity: 75%RH Atmospheric Pressure: 101 KPa

EUT set Condition: Keep WIFI Receiving and Full Load

Equipment Level: Class B

Results: Pass

Please refer to following diagram for individual



Frequency (MHz)	Level@3m (dBµV/m)	Antenna Polarity	Limit@3m (dBµV/m)	
		Н	54(AV)	

Note: 1. Due to the final radiated level much less than the limit, so necessary take down final radiated level

2. For radiated Emissions from 18-25GHz, it is only the floor noise.

Report No: 1210109-01 Page 41 of 126

Date: 2012-09-03



Radiated Disturbance (1000MHz----18000MHz)


EUT Operating Environment

Temperature:25°C Humidity: 75%RH Atmospheric Pressure: 101 KPa

EUT set Condition: Keep WIFI Receiving and Full Load

Equipment Level: Class B

Results: Pass



Please refer to following diagram for individual

Frequency (MHz)	Level@3m (dBµV/m)	Antenna Polarity	Limit@3m (dBµV/m)
		V	54(AV)

Note: 1. Due to the final radiated level much less than the limit, so necessary take down final radiated level

2. For radiated Emissions from 18-25GHz, it is only the floor noise.


Report No: 1210109-01 Page 42 of 126

Date: 2012-09-03



7.0 6dB and 99% Bandwidth Measurement

7.1 Test Setup



7.2 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is >500 kHz

7.3 Test Procedure

- 1. Set resolution bandwidth (RBW) = 100 kHz
- 2. Set the video bandwidth (VBW) \geq 3 x RBW.
- 3. Detector = Peak.
- 4. Trace mode = max hold.
- 5. Sweep = auto couple.
- 6. Allow the trace to stabilize.
- 7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

7.4 Test Result

Report No: 1210109-01 Page 43 of 126

Date: 2012-09-03




6dB Occupied Bandwidth

EUT		MID		Model		HS-10DTB2		
Mode 8		02.11b		Input Voltage		AC 120V		
Temperat	ure	24	24 deg. C,			,	56% RH	
Channel		el Frequency (MHz)	Data Transfer Rate (Mbps)		andwidth Hz)	Minimum Limit (MHz)		Pass/ Fail
1		2412	1	10.10		0.5		Pass
6		2437	1	10	.08		0.5	Pass
11		2462	1	10.08		10.08 0.5		Pass
1		2412	11	10.04		0.04 0.5		Pass
6		2437	11	10.02		10.02 0.5		Pass
11		2462	11	10	10.02 0.		0.5	Pass

Report No: 1210109-01 Page 44 of 126

Date: 2012-09-03






Page 45 of 126

Report No: 1210109-01

Date: 2012-09-03






Page 46 of 126

Report No: 1210109-01

Date: 2012-09-03






Report No: 1210109-01 Page 47 of 126

Date: 2012-09-03






Report No: 1210109-01 Page 48 of 126

Date: 2012-09-03






Report No: 1210109-01 Page 49 of 126

Date: 2012-09-03





Report No: 1210109-01 Page 50 of 126

Date: 2012-09-03



6dB Occupied Bandwidth


EUT	CUT		MID		Model		HS-10DTB2	
Mode	Mode 8		802.11g		Input Voltage		AC 120V	
Temperat	ure	24	24 deg. C,		Humidity		56% RH	
Channel		el Frequency (MHz)	Data Transfer Rate (Mbps)		andwidth Hz)		Minimum Limit (MHz) Pass.	
1		2412	6	16	16.58		0.5	Pass
6		2437	6	16.68		68 0.5		Pass
11		2462	6	16.68			0.5	Pass

Report No: 1210109-01 Page 51 of 126

Date: 2012-09-03




Test Plots:



Report No: 1210109-01 Page 52 of 126

Date: 2012-09-03






Report No: 1210109-01 Page 53 of 126

Date: 2012-09-03





Report No: 1210109-01 Page 54 of 126

Date: 2012-09-03



6dB Occupied Bandwidth

EUT	EUT		MID		Model		HS-10DTB2	
Mode	Mode 8		02.11n		Input Voltage		AC 120V	
Temperat	ure	24	4 deg. C,		Humidity		56% RH	
Channel		Channel Frequency (MHz)		6 dB Bandwidth (MHz)		Minimum Limit (MHz)		Pass/ Fail
1		2412	HT20	17.80		0.5		Pass
6		2437 HT20		17.82			0.5	Pass
11		2462	HT20	17	.76		0.5	Pass
1		2422	HT40	36.50		50 0.5		Pass
4		2437	HT40	36.50		.50 0.5		Pass
7		2452	HT40	36	.50	0.5		Pass


Report No: 1210109-01 Page 55 of 126

Date: 2012-09-03



Test Plots:

1. 802.11n at HT20 of CH01




Report No: 1210109-01 Page 56 of 126

Date: 2012-09-03



2. 802.11n at HT20 of CH06




Report No: 1210109-01 Page 57 of 126

Date: 2012-09-03



3. 802.11n at HT20 of CH11




Report No: 1210109-01 Page 58 of 126

Date: 2012-09-03



4. 802.11n at HT40 of CH01




Report No: 1210109-01 Page 59 of 126

Date: 2012-09-03



5. 802.11n at HT40 of CH04




Report No: 1210109-01 Page 60 of 126

Date: 2012-09-03



6. 802.11n at HT40 of CH07



Report No: 1210109-01 Page 61 of 126

Date: 2012-09-03




99% Occupied Bandwidth

EUT		MID			Model		HS-10DTB2	
Mode		8	302.11b		Input Voltage		AC 120V	
Temperat	ure	24 deg. C,			Humidity		56%	6 RH
Channel		el Frequency (MHz)	Data Transfer Rate (Mbps)	ransfer 99% Ba Rate (M		andwidth Minir Hz) (Pass/ Fail
1		2412	1	13.80				Pass
6		2437	1	13.80		.80		Pass
11		2462	1	13.80				Pass
1		2412	11	13.56				Pass
6		2437	11	13.56				Pass
11		2437	11	13	.56			Pass

Report No: 1210109-01 Page 62 of 126

Date: 2012-09-03






Report No: 1210109-01 Page 63 of 126

Date: 2012-09-03






Page 64 of 126

Report No: 1210109-01

Date: 2012-09-03






Page 65 of 126

Report No: 1210109-01

Date: 2012-09-03






Page 66 of 126

Report No: 1210109-01

Date: 2012-09-03






Page 67 of 126

Report No: 1210109-01

Date: 2012-09-03





Report No: 1210109-01 Page 68 of 126

Date: 2012-09-03



99% Occupied Bandwidth


EUT	UT		MID		Model		HS-10DTB2	
Mode		802.11g			Input Voltage		AC 120V	
Temperat	ure	24	4 deg. C,		Humidity		56% RH	
Channel		el Frequency (MHz)	Data Transfer Rate (Mbps)		ndwidth Hz)	dth Minimum Li (MHz)		Pass/ Fail
1		2412	6	16	5.56			Pass
6		2437	6	16.56		56		Pass
11		2462	6	16	.56			Pass

Page 69 of 126

Report No: 1210109-01

Date: 2012-09-03






Report No: 1210109-01 Page 70 of 126

Date: 2012-09-03






Report No: 1210109-01 Page 71 of 126

Date: 2012-09-03





Report No: 1210109-01 Page 72 of 126

Date: 2012-09-03




99% Occupied Bandwidth

EUT	Γ		MID		Model		HS-10DTB2	
Mode	Mode 8		302.11n		Input Voltage		AC 120V	
Temperat	ure	24	4 deg. C,		Humidity		56% RH	
Channel		el Frequency (MHz)	Data Transfer Rate (Mbps)	99% Bandwidth (MHz)		Minimum Limit (MHz)		Pass/ Fail
1		2412	HT20	17	.65			Pass
6		2437	HT20	17	.70			Pass
11		2462	HT20	17	.70	70		Pass
1		2422	HT40	36.00				Pass
4		2437	HT40	36.00				Pass
7		2452	HT40	36	5.00			Pass

Report No: 1210109-01 Page 73 of 126

Date: 2012-09-03






Report No: 1210109-01 Page 74 of 126

Date: 2012-09-03






Report No: 1210109-01 Page 75 of 126

Date: 2012-09-03






Report No: 1210109-01 Page 76 of 126

Date: 2012-09-03






Report No: 1210109-01 Page 77 of 126

Date: 2012-09-03






Report No: 1210109-01 Page 78 of 126

Date: 2012-09-03





Report No: 1210109-01


Date: 2012-09-03



Page 79 of 126

8. Maximum Peak Output Power

8.1 Test Setup



8.2 Limits of Maximum Peak Output Power

The Maximum Peak Output Power Measurement is 30dBm.

8.3 Test Procedure

The RF power output was measured with a Power meter connected to the RF Antenna connector (conducted measurement) while EUT was operating in transmit mode at the appropriate centre frequency.

Note: the peak power was measured

Page 80 of 126

Date: 2012-09-03

Report No: 1210109-01



8.4Test Results

EUT		MID Mo		odel HS		S-10DTB2	
Mode		802.1	1b	Input		S	ee Below
Temperati	ure	24 deg	g. C,	Humidity		;	56% RH
Channel	Cha	annel Frequency (MHz)	Peak Power C (dBm)	Output	Peak P Lin (dB	nit	Pass/ Fail
1		2412 10.14		30)	Pass
6		2437 10.25			30		Pass
11		2462	10.36		30)	Pass

Note: 1. At finial test to get the worst-case emission at 11Mbps for CH01, CH06 and CH11

The result basic equation calculation as follow:
 Peak Power Output = Peak Power Reading + Cable loss + Attenuator

3. The worse case was recorded

EUT		MII)	Model		HS-10DTB2	
Mode		802.1	1g	Input	Voltage S		ee Below
Temperati	ure	24 deg	g. C,	Humidity			56% RH
Channel	Cha	annel Frequency (MHz)	Peak Power (dBm)	Output	Peak F Lin (dB	nit	Pass/ Fail
1		2412	2412 9.69		30		Pass
6		2437	2437 8.73		30		Pass
11		2462	9.87		30)	Pass

Note: 1. At finial test to get the worst-case emission at 6Mbps for CH01, CH06 and CH11

- The result basic equation calculation as follow:
 Peak Power Output = Peak Power Reading + Cable loss + Attenuator
- 3. The worse case was recorded

Page 81 of 126

Report No: 1210109-01

Date: 2012-09-03



EUT		MID Mo		odel H		S-10DTB2	
Mode		802.11n (HT20)	Input	Voltage S		ee Below
Temperati	ure	24 deg	g. C,	Hur	Humidity		56% RH
Channel	Cha	annel Frequency (MHz)	Peak Power C (dBm)	Output	Peak Power Limit (dBm)		Pass/ Fail
1		2412 9.36			30		Pass
6		2437 9.51			30		Pass
11		2462	9.49		30)	Pass

Note: 1. At finial test to get the worst-case emission at 11n HT20 for CH01, CH06 and CH11

The result basic equation calculation as follow:
 Peak Power Output = Peak Power Reading + Cable loss + Attenuator

3. The worse case was recorded

EUT		MII	D	Model		HS-10DTB2	
Mode		802.11n ((HT40)	Input	Voltage S		ee Below
Temperat	ure	24 deg	g. C,	Humidity		:	56% RH
Channel	Cha	annel Frequency (MHz)	Peak Power (dBm)	Output	Peak F Lin (dB	nit	Pass/ Fail
1		2422	4.21		30		Pass
4		2437	4.36		30)	Pass
7		2452	4.29		30)	Pass

Note: 1. At finial test to get the worst-case emission at 11n HT40 for CH01, CH04 and CH07

- 2. The result basic equation calculation as follow:

 Peak Power Output = Peak Power Reading + Cable loss + Attenuator
- 3. The worse case was recorded


Report No: 1210109-01 Page 82 of 126

Date: 2012-09-03



9. Power Spectral Density Measurement

9.1 Test Setup



9.2 Limits of Power Spectral Density Measurement

The Maximum Power Spectral Density Measurement is 8dBm.

9.3 Test Procedure

- 1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
- 2. Set the RBW = 10 kHz.
- 3. Set the VBW \geq 30 kHz.
- 4. Set the span to 1.5 times the DTS channel bandwidth.
- 5. Detector = peak.
- 6. Sweep time = auto couple.
- 7. Trace mode = max hold.
- 8. Allow trace to fully stabilize.
- 9. Use the peak marker function to determine the maximum amplitude level.
- 10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.
- 11. The resulting peak PSD level must be ≤ 8 dBm.

Report No: 1210109-01 Page 83 of 126

Date: 2012-09-03



9.4Test Result

EUT		MII	MID Mo		odel	HS	HS-10DTB2	
Mode		802.11b 1	1Mbps	Input	ut Voltage		AC 120V	
Temperati	ure	24 deg	g. C,	Humidity		56% RH		
Channel	Ch	annel Frequency (MHz)	Final RF Po Level in 3kH: (dBm)	Maximur			Pass/ Fail	
			11Mbps					
1		2412	-13.26		8		Pass	
6		2437	-13.54		8		Pass	
11		2462	-13.55		8		Pass	

EUT		MII	MID Model		odel	HS	S-10DTB2
Mode		802.11b	1 Mbps	Input Voltage		I	AC 120V
Temperat	ure	24 deg	g. C,	Humidity		:	56% RH
Channel	Ch	annel Frequency (MHz)	Final RF Po Level in 3kH (dBm)	l Maximun			Pass/ Fail
			1Mbps				
1		2412	-17.67		8		Pass
6		2437	-17.45		8		Pass
11		2462	-17.43		8		Pass

Report No: 1210109-01

Date: 2012-09-03



EUT		MII	MID Mod		odel HS		S-10DTB2	
Mode		802.11g	2.11g 6Mbps Input V		Voltage A		AC 120V	
Temperat	ure	24 deg	g. C,	Humidity		:	56% RH	
Channel	Cha	annel Frequency (MHz)	Final RF Po Level in 3kH: (dBm)		Maximur		Pass/ Fail	
			6Mbps					
1		2412	-21.00		8		Pass	
6		2437	-20.01		8		Pass	
11		2462	-20.05		8		Pass	

EUT		MII	MID Mo		odel HS		S-10DTB2	
Mode		802.11n	HT20	Input Vol		A	AC 120V	
Temperat	ure	24 deg	g. C,	Humidity			56% RH	
Channel	Cha	annel Frequency (MHz)	Final RF Po Level in 3kH (dBm)		Maximur		Pass/ Fail	
			HT20					
1		2412	-24.67		8		Pass	
6		2437 -24.60			8		Pass	
11		2462	-23.93		8		Pass	

EUT		MII	O	Model		HS	S-10DTB2
Mode		802.11n HT40 Input V		Voltage A		AC 120V	
Temperat	ure	24 deg	g. C,	Humidity		:	56% RH
Channel	Cha	annel Frequency (MHz)	Final RF Po Level in 3kH: (dBm)	3kHz BW Max		m Limit m)	Pass/ Fail
			HT40				
1		2422	-35.86		8		Pass
6		2437	-35.05		8		Pass
11		2452	-35.57		8		Pass

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd vill not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate. Report No: 1210109-01 Page 85 of 126

Date: 2012-09-03



9.5 Photo of Power Spectral Density Measurement

1.802.11b at 11Mbps of CH01




Page 86 of 126

Report No: 1210109-01

Date: 2012-09-03



2. 802.11b at 11Mbps at CH06




Page 87 of 126

Report No: 1210109-01

Date: 2012-09-03



3. 802.11b at 11Mbps of CH11




Page 88 of 126

Report No: 1210109-01

Date: 2012-09-03



4. 802.11b at 1Mbps of CH1




Page 89 of 126

Report No: 1210109-01

Date: 2012-09-03



5. 802.11b at 1Mbps of CH6




Page 90 of 126

Report No: 1210109-01

Date: 2012-09-03



6. 802.11b at 1Mbps of CH11




Page 91 of 126

Report No: 1210109-01

Date: 2012-09-03



7. 802.11g at 6Mbps of CH1




Page 92 of 126

Report No: 1210109-01

Date: 2012-09-03



8. 802.11g at 6 Mbps of CH6




Page 93 of 126

Report No: 1210109-01

Date: 2012-09-03



9. 802.11g at 6 Mbps of CH11




Page 94 of 126

Report No: 1210109-01

Date: 2012-09-03






Page 95 of 126

Report No: 1210109-01

Date: 2012-09-03






Page 96 of 126

Report No: 1210109-01

Date: 2012-09-03






Page 97 of 126

Report No: 1210109-01

Date: 2012-09-03






Page 98 of 126

Report No: 1210109-01

Date: 2012-09-03






Page 99 of 126

Report No: 1210109-01

Date: 2012-09-03





Report No: 1210109-01


Date: 2012-09-03



Page 100 of 126

10 Out of Band Measurement

10.1 Test Setup for band edge



The restricted band requirement based on radiated emission test; please see the clause 6 for the test setup

10.2 Limits of Out of Band Emissions Measurement

- 1. Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).
- 2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

10.3 Test Procedure

For signals in the restricted bands above and below the 2.4-2.483GHz allocated band a measurement was made of radiated emission test.(Peak values with RBW=VBW=1MHz and PK detector. AV value with RBW=1MHz, VBW=10Hz and PK detector)

For bandage test, the spectrum set as follows: RBW=VBW=100 kHz. A conducted measurement used

10.4 Test Result

Please see next pages

Note: 1. this is a handhold device. The radiated emissions should be tested under 3-axes position (Lying, Side, and Stand), after pre-test. It was found that the worse radiated emission was get at the lying position.

2. The worse case was recorded

Page 101 of 126

Report No: 1210109-01

Date: 2012-09-03




For 802.11b mode

CH01 at 11Mbps

10.4 Band-edge and Restricted band Measurement

Product:	MID		Model:	HS-10DTB2
Mode	Keeping Transmitting		Input Voltage	AC 120V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
2400	PK (dBµV/m)	42.25	Limit	$74(dB\mu V/m)$
	AV (dBμV/m)		Limit	$54(dB\mu V/m)$
2390	PK (dBµV/m)	41.48	Limit	$74(dB\mu V/m)$
	$AV (dB\mu V/m)$		Limit	$54(dB\mu V/m)$

Test Figure:



Page 102 of 126

Report No: 1210109-01

Date: 2012-09-03




CH11 at 11Mbps

10.4 Band-edge and Restricted band Measurement

Product:	MID		Model:	HS-10DTB2
Mode	Keeping Transmitting		Input Voltage	AC 120V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:		Pass	Detector	PK
2483.5	PK (dBμV/m)	42.77	T ::4	$74(dB\mu V/m)$
	$AV (dB\mu V/m)$		Limit	$54(dB\mu V/m)$

Test Figure:



Page 103 of 126

Report No: 1210109-01

Date: 2012-09-03




For 802.11g mode

CH01 at 6Mbps

10.4 Band-edge and Restricted band Measurement

Product:		MID	Model:	HS-10DTB2
1 Toduct.		WIID		113-10D1B2
Mode	Keeping	g Transmitting	Input Voltage	AC 120V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:		Pass		PK
2400	PK (dBμV/m)	53.25	T ::4	$74(dB\mu V/m)$
	AV (dBμV/m)	37.52	Limit	$54(dB\mu V/m)$
2390	PK (dBμV/m)	42.23	Limit	$74(dB\mu V/m)$
	AV (dBμV/m)		Limit	54(dBμV/m)

Test Figure:



Page 104 of 126

Report No: 1210109-01

Date: 2012-09-03




CH11 at 6Mbps

10.4 Band-edge and Restricted band Measurement

Product:	MID		Model:	HS-10DTB2
Mode	Keeping Transmitting		Input Voltage	AC 120V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
2483.5	PK (dBµV/m)	43.17	T toota	74(dBµV/m)
	AV (dBμV/m)		Limit	$54(dB\mu V/m)$

Test Figure:



Page 105 of 126

Report No: 1210109-01

Date: 2012-09-03




For 802.11n (HT20) mode

CH01 at 65Mbps

10.4 Band-edge and Restricted band Measurement

Product:	MID		Model:	HS-10DTB2
Mode	Keeping Transmitting		Input Voltage	AC 120V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
2400	PK (dBμV/m)	51.86	Timil	$74(dB\mu V/m)$
	AV (dBμV/m)	37.01	Limit	54(dBμV/m)
2390	PK (dBμV/m)	41.76	Limit	$74(dB\mu V/m)$
	AV (dBμV/m)			54(dBµV/m)

Test Figure:



Page 106 of 126

Report No: 1210109-01

Date: 2012-09-03




CH11 at 65Mbps

10.4 Band-edge and Restricted band Measurement

Product:	MID		Model:	HS-10DTB2
Mode	Keeping Transmitting		Input Voltage	AC 120V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
2483.5	PK (dBμV/m)	43.75	T in it	$74(dB\mu V/m)$
	AV (dBμV/m)		Limit	$54(dB\mu V/m)$

Test Figure:



Page 107 of 126

Report No: 1210109-01

Date: 2012-09-03




For 802.11n (HT40) mode

CH01 at 65Mbps

10.4 Band-edge and Restricted band Measurement

2011 2011 Vago una recontivea coma rivologiament					
Product:	MID		Model:	HS-10DTB2	
Mode	Keeping Transmitting		Input Voltage	AC 120V	
Temperature	24 deg. C,		Humidity	56% RH	
Test Result:	Pass		Detector	PK	
2400	PK (dBμV/m)	44.15	Limit	$74(dB\mu V/m)$	
	AV (dBμV/m)			54(dBμV/m)	
2390	PK (dBμV/m)	40.62	Limit	74(dBμV/m)	
	AV (dBμV/m)			54(dBμV/m)	

Test Figure:



Page 108 of 126

Report No: 1210109-01

Date: 2012-09-03




CH7 at 65Mbps

10.4 Band-edge and Restricted band Measurement

Product:	MID		Model:	HS-10DTB2
Mode	Keeping Transmitting		Input Voltage	AC 120V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
2483.5	PK (dBµV/m)	42.76	T in it	74(dBµV/m)
	AV ($dB\mu V/m$)		Limit	54(dBµV/m)

Test Figure:



Page 109 of 126

Report No: 1210109-01


Date: 2012-09-03




10.4 Conducted Spurious Emissions

Product:	MID	Model:	HS-10DTB2
Mode	Keeping Transmitting	Input Voltage	AC 120V
Temperature	24 deg. C	Humidity	56% RH
Test Result:	Pass	Detector	PK

Test Figure: 802.11b ch1





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Page 110 of 126

Report No: 1210109-01


Date: 2012-09-03




10.4 Conducted Spurious Emissions

Product:	MID	Model:	HS-10DTB2
Mode	Keeping Transmitting	Input Voltage	AC 120V
Temperature	24 deg. C	Humidity	56% RH
Test Result:	Pass	Detector	PK

Test Figure: 802.11b ch11





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Page 111 of 126

Report No: 1210109-01


Date: 2012-09-03



10.4 Conducted Spurious Emissions

Product:	MID	Model:	HS-10DTB2
Mode	Keeping Transmitting	Input Voltage	AC 120V
Temperature	24 deg. C	Humidity	56% RH
Test Result:	Pass	Detector	PK

Test Figure: 802.11g ch1



Page 112 of 126

Report No: 1210109-01


Date: 2012-09-03



10.4 Conducted Spurious Emissions

Product:	MID	Model:	HS-10DTB2
Mode	Keeping Transmitting	Input Voltage	AC 120V
Temperature	24 deg. C	Humidity	56% RH
Test Result:	Pass	Detector	PK

Test Figure: 802.11g ch11



Page 113 of 126

Report No: 1210109-01


Date: 2012-09-03



10.4 Conducted Spurious Emissions

Product:	MID	Model:	HS-10DTB2
Mode	Keeping Transmitting	Input Voltage	AC 120V
Temperature	24 deg. C	Humidity	56% RH
Test Result:	Pass	Detector	PK

Test Figure: 802.11n HT20 ch1



Page 114 of 126

Report No: 1210109-01


Date: 2012-09-03



10.4 Conducted Spurious Emissions

Product:	MID	Model:	HS-10DTB2
Mode	Keeping Transmitting	Input Voltage	AC 120V
Temperature	24 deg. C	Humidity	56% RH
Test Result:	Pass	Detector	PK

Test Figure: 802.11n HT20 ch11



Page 115 of 126

Report No: 1210109-01


Date: 2012-09-03



10.4 Conducted Spurious Emissions

Product:	MID	Model:	HS-10DTB2
Mode	Keeping Transmitting	Input Voltage	AC 120V
Temperature	24 deg. C	Humidity	56% RH
Test Result:	Pass	Detector	PK

Test Figure: 802.11n HT40 ch1



Page 116 of 126

Report No: 1210109-01


Date: 2012-09-03



10.4 Conducted Spurious Emissions

Product:	MID	Model:	HS-10DTB2
Mode	Keeping Transmitting	Input Voltage	AC 120V
Temperature	24 deg. C	Humidity	56% RH
Test Result:	Pass	Detector	PK

Test Figure: 802.11n HT40 ch7



Report No: 1210109-01 Page 117 of 126

Date: 2012-09-03



11.0 Antenna Requirement

11.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitter antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the mount in dB that the directional gain of the antenna exceeds 6 dBi.

11.2 Antenna Connected construction

PCB antenna used. The maximum Gain of the antennas is 2.0dBi.

Page 118 of 126

Report No: 1210109-01

Date: 2012-09-03



12.0 FCC ID Label

FCC ID: YH5-10DTB2 IC: 8012A-10DTB2

This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

The label must not be a stick-on paper label. The label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

Mark Location:



Page 119 of 126

Report No: 1210109-01

Date: 2012-09-03



13.0 **Photo of testing**

Conducted Emission Test Setup:



Page 120 of 126

Report No: 1210109-01

Date: 2012-09-03



Radiated Emission Test Setup:





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to

adopt any other remedies which may be appropriate.

Page 121 of 126

Report No: 1210109-01

Date: 2012-09-03



Photographs - EUT

Outside view





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to

adopt any other remedies which may be appropriate.

Report No: 1210109-01 Page 122 of 126

Date: 2012-09-03



Outside view



Page 123 of 126


Report No: 1210109-01

Date: 2012-09-03



Inside view





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 124 of 126


Report No: 1210109-01

Date: 2012-09-03



Inside view





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to


adopt any other remedies which may be appropriate.

Report No: 1210109-01 Page 125 of 126

Date: 2012-09-03



Inside view



Report No: 1210109-01 Page 126 of 126

Date: 2012-09-03



Power Supply



End of the report