







ISO/IEC17025Accredited Lab.

Report No: FCC 1312117 File reference No: 2013-12-26

Applicant: Kobian Canada INC.

Product: MID

Model No: HS-7DTB10; HS-7DTB4A

Trademark: N/A

Test Standards: FCC Part 15.247 and RSS-210 Issue 8

Test result:

It is herewith confirmed and found to comply with the

requirements set up by ANSI C63.4, FCC Part 15.247 and RSS-210 Issue 8 for the evaluation of electromagnetic

compatibility

Approved By

Jack Chung

Jack Chung

Manager

Dated: December 26, 2013

Results appearing herein relate only to the sample tested

The technical reports is issued errors and omissions exempt and is subject to withdrawal at

SHENZHEN TIMEWAY TECHNOLOGY CONSULTING CO., LTD

5/F,Block 4, Anhua Industrial Zone.,No.8 TaiRan Rd.CheGongMiao,FuTian District, Shenzhen,CHINA.

Tel (755) 83448688 Fax (755) 83442996

Report No: 1312117 Page 2 of 117

Date: 2013-12-26



Special Statement:

The testing quality ability of our laboratory meet with "Quality Law of People's Republic of China" Clause 19.

The testing quality system of our laboratory meet with ISO/IEC-17025 requirements, which is approved by CNAL. This approval result is accepted by MRA of APLAC.

Our test facility is recognized, certified, or accredited by the following organizations:

CNAL-LAB Code: L2292

The EMC Laboratory has been assessed and in compliance with CNAL/AC01:2002 accreditation criteria for testing Laboratories (identical to ISO/IEC 17025:1999 General Requirements) for the Competence of testing Laboratories.

FCC-Registration No.: 899988

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 899988.

IC- Registration No.: IC5205A-02

The EMC Laboratory has been registered and fully described in a report filed with the (IC) Industry Canada. The acceptance letter from the IC is maintained in our files. Registration IC No.: 5205A-02.

Page 3 of 117

Report No: 1312117 Date: 2013-12-26



Test Report Conclusion

Content

1.0	General Details	4
1.1	Test Lab Details	4
1.2	Applicant Details	4
1.3	Description of EUT	4
1.4	Submitted Sample	5
1.5	Test Duration.	5
1.6	Test Uncertainty	5
1.7	Test By	5
2.0	List of Measurement Equipment	6
3.0	Technical Details	9
3.1	Summary of Test Results	9
3.2	Test Standards	9
4.0	EUT Modification.	9
5.0	Power Line Conducted Emission Test.	10
5.1	Schematics of the Test.	10
5.2	Test Method and Test Procedure.	10
5.3	Configuration of the EUT.	10
5.4	EUT Operating Condition.	11
5.5	Conducted Emission Limit.	11
5.6	Test Result.	11
6.0	Radiated Emission test	14
6.1	Test Method and Test Procedure	14
6.2	Configuration of the EUT.	14
6.3	EUT Operation Condition.	14
6.4	Radiated Emission Limit.	15
7.0	6dB and 99%Bandwidth Measurement.	39
8.0	Maximum Peak Output Power	76
9.0	Power Spectral Density Measurement.	79
10.0	Out of Band Measurement.	97
11.0	Antenna Requirement.	106
12.0	FCC/IC Label.	107
13.0	Photo of Test Setup and EUT View.	108

Date: 2013-12-26



1.0 General Details

1.1 Test Lab Details

Name: SHENZHEN TIMEWAY TECHNOLOGY CONSULTING CO., LTD

Address: 5/F,Block 4, Anhua Industrial Zone.,No.8 TaiRan Rd.CheGongMiao,FuTian District,

Shenzhen, CHINA.

Telephone: (755) 83448688 Fax: (755) 83442996

Site on File with the Federal Communications Commission – United Sates

Registration Number: 899988

For 3m & 10 m OATS

Site Listed with Industry Canada of Ottawa, Canada

Registration Number: IC: 5205A-02

For 3m & 10 m OATS

1.2 Applicant Details

Applicant: Kobian Canada INC.

Address: 560 Denison Street, Unit 5, Markham, Ontario, L3R 2M8, Canada

Telephone: (001) 905-948-9967 Fax: (001) 905-948-1601

1.3 Description of EUT

Product: MID

Manufacturer: Shenzhen Ballet Digital Technology Co., Ltd.

Address: 6 Floor F1 Building, Huafeng Industry Area, Hangcheng Street, Gushu

Xixiang, Bao'an District, Shenzhen

Brand Name: N/A

Model Number: HS-7DTB10
Additional Model Number: HS-7DTB4A

Power Adapter BSYB050200UU Input: 100-240V, 50/60Hz, 0.4A; Output: 5.0V, 2.0A

Type of Modulation IEEE 802.11b : DSSS (CCK, QPSK, DBPSK)

IEEE 802.11g/n (HT20/HT40) : OFDM(64QAM, 16QAM, QPSK, BPSK)

Frequency range IEEE 802.11b/g/n (HT20) : 2412-2462MHz;

IEEE 802.11n HT40 : 2422MHz-2452MHz

Channel Spacing IEEE 802.11b/g/n (HT20/HT40) : 5MHz

Air Data Rate IEEE 802.11b : 11, 5.5, 2, 1 Mbps

IEEE 802.11g: 54, 48,36, 24, 18, 12, 9, 6 Mbps

IEEE 802.11n HT20: 150, 117, 104, 78, 65, 58.5, 52, 39, 26, 19.5, 13, 6 Mbps IEEE 802.11n HT40: 150, 117, 104, 78, 65, 58.5, 52, 39, 26, 19.5, 13, 6 Mbps

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No: 1312117 Page 5 of 117

TIMEWAY YESTING LABS

Frequency Selection By software

Channel Number IEEE 802.11b/g/n (HT20): 11 Channels

IEEE 802.11n HT40: 7 Channels

Antenna: Integral Antenna with maximum gain 2.0dBi

Input Voltage: DC3.7V, 2700mAh powered by Lion-Battery

1.4 Submitted Sample: 2 Samples

1.5 Test Duration

Date: 2013-12-26

2013-12-23 to 2013-12-26

1.6 Test Uncertainty

Conducted Emissions Uncertainty =3.6dB

Radiated Emissions Uncertainty =4.7dB

1.7 Test Engineer

Terry Tang

The sample tested by

Print Name: Terry Tang

Page 6 of 117

Report No: 1312117 Date: 2013-12-26



2.0	2.0 Test Equipments					
Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date	
ESPI Test Receiver	ROHDE&SCHWARZ	ESPI 3	100379	2013-08-23	2014-08-22	
TWO Line-V-NETW	ROHDE&SCHWARZ	EZH3-Z5	100294	2013-08-23	2014-08-22	
TWO Line-V-NETW	ROHDE&SCHWARZ	EZH3-Z5	100253	2013-08-23	2014-08-22	
Ultra Broadband ANT	ROHDE&SCHWARZ	HL562	100157	2013-08-25	2014-08-24	
ESDV Test Receiver	ROHDE&SCHWARZ	ESDV	100008	2013-08-23	2014-08-22	
Impuls-Begrenzer	ROHDE&SCHWARZ	ESH3-Z2	100281	2013-08-24	2014-08-23	
System Controller	СТ	SC100	-			
Printer	EPSON	РНОТО ЕХЗ	CFNH234850			
Computer	IBM	8434	1S8434KCE99BLXL O*	-	-	
Loop Antenna	EMCO	6502	00042960	2013-08-23	2014-08-22	
ESPI Test Receiver	ROHDE&SCHWARZ	ESI26	838786/013	2013-08-23	2014-08-22	
3m OATS			N/A	2013-08-22	2014-08-21	
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170265	2013-08-24	2014-08-23	
Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-631	2013-08-24	2014-08-23	
Power meter	Anritsu	ML2487A	6K00003613	2013-08-24	2014-08-23	
Power sensor	Anritsu	MA2491A	32263	2013-08-24	2014-08-23	
Bilog Antenna	Schwarebeck	VULB9163	9163/340	2013-08-24	2014-08-23	
LISN	AFJ	LS16C	10010947251	2013-08-23	2014-08-22	
LISN (Three Phase)	Schwarebeck	NSLK 8126	8126453	2013-08-23	2014-08-22	
9*6*6 Anechoic			N/A	2013-08-22	2014-08-21	
EMI Test Receiver	RS	ESCS30	100139	2013-08-23	2014-08-22	
LISN	AFJ	LS16C	10010947251	2013-08-23	2014-08-22	
LISN (Three Phase)	Schwarebeck	NSLK 8126	8126453	2013-08-23	2014-08-22	

Page 7 of 117 Report No: 1312117



2.1 **Auxiliary Equipment**

Date: 2013-12-26

Name	Model No.	Serial No.	Manufacturer	Cable	FCC ID/DOC
Earphone					

Report No: 1312117 Page 8 of 117

Date: 2013-12-26



3. DESCRIPTION OF TEST MODES

IEEE 802.11b, 802.11g, 802.11n (HT20) mode

The EUT had been tested under operating condition. There are three channels have been tested as following:

Channel	Frequency (MHz)
Low	2412
Middle	2437
High	2462

IEEE 802.11b mode: 11Mbps data rate (worst case) was chosen for full testing. IEEE 802.11g mode: 54Mbps data rate (worst case) was chosen for full testing. IEEE 802.11n (HT20) mode: 65Mbps data rate (worst case) were chosen for full testing

IEEE 802.11n HT40

The EUT had been tested under operating condition. There are three channels have been tested as following:

Channel	Frequency (MHz)
Low	2422
Mid	2437
High	2452

IEEE 802.11n HT40 mode: 65Mbps data rate (worst case) was chosen for full testing.

The worst-case data rates are determined according to the description above, based on the investigations by measuring the PSD and average power across all the data rates, bandwidths, modulations and spatial stream modes.



3.0 **Technical Details**

3.1 **Summary of test results**

Standard	Test Type	Result	Notes
FCC Part 15, Paragraph 15.107	Conducted Emission Test	PASS	Complies
& 15.207 & RSS-210 Issue 8			
	Spectrum bandwidth of a		Complies
FCC Part 15 Subpart C	Orthogonal Frequency		
Paragraph 15.247(a)(2) Limit &	Division Multiplex System	PASS	
RSS-210 Issue 8	Limit: 6dB		
	bandwidth>500kHz		
FCC Part 15, Paragraph	Maximum peak output		
15.247(b) & RSS-210 Issue 8	power	PASS	Complies
15.247(b) & KSS-210 Issue 8	Limit: max. 30dBm		
FCC Part 15, Paragraph	Transmitter Radiated	PASS	Complies
15.109,15.205 & 15.209 &	Emission		
RSS-210 Issue 8	Limit: Table 15.209		
FCC Part 15, Paragraph	Power Spectral Density	PASS	Complies
15.247(e) & RSS-210 Issue 8	Limit: max. 8dBm		
FCC Part 15, Paragraph	Out of Band Emission and	PASS	Complies
15.247(d) & RSS-210 Issue 8	Restricted Band		
	Radiation		
	Limit: 20dB less than		
	peak value of fundamental		
	frequency		
	Restricted band limit:		
	Table 15.209		

3.2 **Test Standards**

FCC Part 15 Subpart & Subpart C, Paragraph 15.247 & RSS-210 Issue 8

EUT Modification 4.0

No modification by Shenzhen Timeway Technology Consulting Co., Ltd


Report No: 1312117 Page 10 of 117

Date: 2013-12-26



5. Power Line Conducted Emission Test

5.1 Schematics of the test




EUT: Equipment Under Test

5.2 Test Method and test Procedure

The EUT was tested according to ANSI C63.4-2003. The Frequency spectrum From 0.15MHz to 30MHz was investigated. The LISN used was 50ohm/50uH as specified by section 5.1 of ANSI C63.4 –2003.

Test Voltage: 120V~, 60Hz Block diagram of Test setup



5.3 Configuration of The EUT

The EUT was configured according to ANSI C63.4-2003. All interface ports were connected to the appropriate peripherals. All peripherals and cables are listed below.

A. EUT

Device	Manufacturer	Model	FCC/IC
MID	Shenzhen Ballet Digital	HS-7DTB10 ; HS-7DTB4A	FCC ID: YH5-7DTB108GB
WIID	Technology Co., Ltd.		IC: 8012A-7DTB108GB

B. Internal Device

Device	Manufacturer	Model	FCC ID/DOC
N/A			

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No: 1312117 Page 11 of 117

Date: 2013-12-26



C. Peripherals

Device	Manufacturer	Model	FCC ID/DOC	Cable

5.4 EUT Operating Condition

Operating condition is according to ANSI C63.4 -2003.

- A Setup the EUT and simulators as shown on follow
- B Enable AF signal and confirm EUT active to normal condition

5.5 Power line conducted Emission Limit according to Paragraph 15.207 and 15.107 and RSS-210

Frequency Class A Limits (dB μ)		its (dB µ V)	Class B Limits (dB µ V)		
(MHz)	Quasi-peak Level	Average Level	Quasi-peak Level	Average Level	
$0.15 \sim 0.50$	79.0	66.0	66.0~56.0*	56.0~46.0*	
$0.50 \sim 5.00$	73.0	60.0	56.0	46.0	
5.00 ~ 30.00	73.0	60.0	60.0	50.0	

Notes:

- 1. *Decreasing linearly with logarithm of frequency.
- 2. The tighter limit shall apply at the transition frequencies

5.6 Test Results

The frequency spectrum from 0.15MHz to 30MHz was investigated. All reading are quasi-peak values with a resolution bandwidth of 9kHz.

Date: 2013-12-26



A: Conducted Emission on Live Terminal (150kHz to 30MHz)

EUT Operating Environment


Temperature: 26°C Humidity: 65%RH Atmospheric Pressure: 101 Kpa


EUT set Condition: Keep WIFI Transmitting

Equipment Level: Class B

Results: PASS

Please refer to following diagram for individual





Date: 2013-12-26



B: Conducted Emission on Neutral Terminal (150kHz to 30MHz)

EUT Operating Environment


Temperature: 26°C Humidity: 65%RH Atmospheric Pressure: 101 Kpa

EUT set Condition: Keep WIFI Transmitting

Equipment Level: Class B

Results: Pass

Please refer to following diagram for individual



Frequency	Lina	Line Reading(dBμV)		Limit(dBµV)	
(MHz)	Line	Quasi-peak	Average	Quasi-peak	Average
0.323	Neutral	42.98	17.68	59.63	49.63
0.373	Neutral	41.04	17.34	58.42	48.42
1.045	Neutral	37.32	16.12	56.00	46.00
1.652	Neutral	36.56	15.66	56.00	46.00
2.555	Neutral	35.42	15.22	56.00	46.00
3.135	Neutral	35.15	16.75	56.00	46.00

Report No: 1312117 Page 14 of 117

Date: 2013-12-26



6 Radiated Emission Test

- 6.1 Test Method and test Procedure:
- (1) The EUT was tested according to ANSI C63.4 –2003. The radiated test was performed at Timeway Laboratory. This site is on file with the FCC laboratory division, Registration No.899988
- (2) The EUT, peripherals were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m. All set up is according to ANSI C63.4-2003.
- (3) The frequency spectrum from 30 MHz to 25 GHz was investigated. All readings from 30 MHz to 1 GHz are Quasi-peak values with a resolution bandwidth of 120 kHz. For measurement above 1GHz, peak values with RBW=VBW=1MHz and PK detector. AV value with RBW=1MHz, VBW=10Hz and PK detector. Measurements were made at 3 meters.
- (4) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- (5) Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance is with all installation combinations. All data was recorded in the peak detection mode. Quasi-peak readings was performed only when an emission was found to be marginal (within -4 dB of specification limit), and are distinguished with a "QP" in the data table.
- (6) The antenna polarization: Vertical polarization and Horizontal polarization.

Block diagram of Test setup Distance = 3m Computer Pre – Amplifier EUT Turn-table Receiver

- 6.2 Configuration of The EUT

 Same as section 5.3 of this report
- 6.3 EUT Operating Condition
 Same as section 5.4 of this report.

Report No: 1312117 Page 15 of 117



6.4 Radiated Emission Limit

Date: 2013-12-26

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below:

Frequencies in restricted band are complied to limit on Paragraph 15.209 and 15.109 and RSS-210

Frequency Range (MHz)	Distance (m)	Field strength (dB µ V/m)
30-88	3	40.0
88-216	3	43.5
216-960	3	46.0
Above 960	3	54.0

Note:

- 1. RF Voltage (dBuV) = 20 log RF Voltage (uV)
- 2. In the Above Table, the higher limit applies at the band edges.
- 3. Distance refers to the distance in meters between the measuring instrument antenna and the EUT
- 4. This is a handhold device. The radiated emissions should be tested under 3-axes position (Lying, Side, and Stand), After pre-test. It was found that the worse radiated emission was get at the lying position.

Report No: 1312117 Page 16 of 117

Date: 2013-12-26



Test result

General Radiated Emission Data and Harmonics Radiated Emission Data

Radiated Emission In Horizontal (30MHz----1000MHz)

EUT set Condition: Keep WIFI Transmitting

Results: Pass


Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB µ V/m)
148.520	33.99	Н	43.50
272.240	38.17	Н	46.00
198.000	29.16	Н	43.50
173.200	38.20	Н	43.50
148.520	40.38	V	43.50
99.080	33.10	V	43.50
123.920	40.07	V	43.50
173.600	39.06	V	43.50

Page 17 of 117

Report No: 1312117 Date: 2013-12-26



Test Figure:




Date: 26.DEC.2013 10:41:17

Page 18 of 117

Report No: 1312117 Date: 2013-12-26



Test Figure:



Date: 26.DEC.2013 10:47:33

Report No: 1312117 Page 19 of 117

Date: 2013-12-26



Operation Mode: Transmitting under CH01 for 11g at 54Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB µ V/m)
2412.00	95.24 (PK)	Н	Γ
2412.00	95.19 (PK)	V	Fundamental Frequency
4824.00	48.28 (PK)	Н	74(Peak)/ 54(AV)
4824.00	48.32 (PK)	V	74(Peak)/ 54(AV)
7236.00		H/V	74(Peak)/ 54(AV)
9648.00		H/V	74(Peak)/ 54(AV)
12060	1	H/V	74(Peak)/ 54(AV)
14472		H/V	74(Peak)/ 54(AV)
16884		H/V	74(Peak)/ 54(AV)
19296		H/V	74(Peak)/ 54(AV)
21708		H/V	74(Peak)/ 54(AV)
24120		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11g mode 54Mbps

Report No: 1312117 Page 20 of 117

Date: 2013-12-26



Operation Mode: Transmitting under CH06 for 11g at 54Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \mu V/m)
2437.00	93.88 (PK)	Н	E1
2437.00	93.70 (PK)	V	Fundamental Frequency
4874.00	48.47 (PK)	Н	74(Peak)/ 54(AV)
4874.00	48.57 (PK)	V	74(Peak)/ 54(AV)
7311.00		H/V	74(Peak)/ 54(AV)
9748.00		H/V	74(Peak)/ 54(AV)
12185		H/V	74(Peak)/ 54(AV)
14622		H/V	74(Peak)/ 54(AV)
17059		H/V	74(Peak)/ 54(AV)
19496		H/V	74(Peak)/ 54(AV)
21933		H/V	74(Peak)/ 54(AV)
24370		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11g mode 54 Mbps

Operation Mode: Transmitting under CH11 for 11g at 54Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \(\mu \)V/m)
2462.00	94.43 (PK)	Н	Fundamental Frequency
2462.00	94.36 (PK)	V	Fundamental Frequency
4924	47.58 (PK)	Н	74(Peak)/ 54(AV)
4924	47.64 (PK)	V	74(Peak)/ 54(AV)
7368		H/V	74(Peak)/ 54(AV)
9848	1	H/V	74(Peak)/ 54(AV)
12310	-	H/V	74(Peak)/ 54(AV)
14772	-	H/V	74(Peak)/ 54(AV)
17234		H/V	74(Peak)/ 54(AV)
19696		H/V	74(Peak)/ 54(AV)
22158		H/V	74(Peak)/ 54(AV)
24650		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11g mode at 54 Mbps

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


Report No: 1312117

Date: 2013-12-26




Please refer to the following test plots for details:

CH01 for 11g at 54Mbps: Horizontal



CH01 for 11g at 54Mbps: Vertical




The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



CH06 for 11g at 54Mbps: Vertical



CH06 for 11g at 54Mbps: Horizontal




The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.



CH11 for 11g at 54Mbps: Vertical



CH11 for 11g at 54Mbps: Horizontal



Note: For radiated Emissions from 18-25GHz, it is only the floor noise.

Report No: 1312117 Page 24 of 117

Date: 2013-12-26



Operation Mode: Transmitting under CH01 for 11b at 11Mbps

Frequency (MHz)	Level@3m (dB \u03ba V/m)	Antenna Polarity	Limit@3m (dB \u03bc V/m)
2412.00	94.31 (PK)	V	Fundamental Frequency
2412.00	94.26 (PK)	Н	
4824.00	47.82 (PK)	Н	74(Peak)/ 54(AV)
4824.00	47.59 (PK)	V	74(Peak)/ 54(AV)
7236.00	1	H/V	74(Peak)/ 54(AV)
9648.00	1	H/V	74(Peak)/ 54(AV)
12060	1	H/V	74(Peak)/ 54(AV)
14472	1	H/V	74(Peak)/ 54(AV)
16684		H/V	74(Peak)/ 54(AV)
19296		H/V	74(Peak)/ 54(AV)
21708		H/V	74(Peak)/ 54(AV)
24120		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11b mode 11Mbps

Operation Mode: Transmitting under CH06 for 11b at 11Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \(\mu \)V/m)
2437.00	95.13 (PK)	Н	Even dome antal Engavanov
2437.00	95.65 (PK)	V	Fundamental Frequency
4874.00	47.12 (PK)	Н	74(Peak)/ 54(AV)
4874.00	47.81 (PK)	V	74(Peak)/ 54(AV)
7311.00		H/V	74(Peak)/ 54(AV)
9748.00		H/V	74(Peak)/ 54(AV)
12185	-	H/V	74(Peak)/ 54(AV)
14622	-	H/V	74(Peak)/ 54(AV)
17059		H/V	74(Peak)/ 54(AV)
19496		H/V	74(Peak)/ 54(AV)
21933		H/V	74(Peak)/ 54(AV)
24370		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11b mode 11Mbps

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No: 1312117 Page 25 of 117

Date: 2013-12-26



Operation Mode: Transmitting under CH11 for 11b at 11Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \mu V/m)
2462.00	93.38 (PK)	Н	Fundamental Frequency
2462.00	93.67 (PK)	V	Fundamental Frequency
4924	48.72 (PK)	Н	74(Peak)/ 54(AV)
4924	48.13 (PK)	V	74(Peak)/ 54(AV)
7368		H/V	74(Peak)/ 54(AV)
9848		H/V	74(Peak)/ 54(AV)
12310		H/V	74(Peak)/ 54(AV)
14772		H/V	74(Peak)/ 54(AV)
17234		H/V	74(Peak)/ 54(AV)
19696		H/V	74(Peak)/ 54(AV)
22158		H/V	74(Peak)/ 54(AV)
24650		H/V	74(Peak)/ 54(AV)


Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11b mode at 11Mbps




Please refer to the following test plots for details:

CH01 for 11b at 11Mbps: Horizontal



CH01 for 11b at 11Mbps: Vertical




The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



CH06 for 11b at 11Mbps: Vertical



CH06 for 11b at 11Mbps: Horizontal




The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



CH11 for 11b at 11Mbps: Vertical



CH11 for 11b at 11Mbps: Horizontal



Note: For radiated Emissions from 18-25GHz, it is only the floor noise.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No: 1312117 Page 29 of 117

Date: 2013-12-26



Operation Mode: Transmitting under CH01 for 11n HT20 at 65Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \mu V/m)
2412.00	95.36 (PK)	Н	E1
2412.00	95.42 (PK)	V	Fundamental Frequency
4824.00	47.35 (PK)	Н	74(Peak)/ 54(AV)
4824.00	48.60 (PK)	V	74(Peak)/ 54(AV)
7236.00		H/V	74(Peak)/ 54(AV)
9648.00		H/V	74(Peak)/ 54(AV)
12060		H/V	74(Peak)/ 54(AV)
14472		H/V	74(Peak)/ 54(AV)
16684		H/V	74(Peak)/ 54(AV)
19296		H/V	74(Peak)/ 54(AV)
21708		H/V	74(Peak)/ 54(AV)
24120		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11n (HT20) mode 65Mbps

Operation Mode: Transmitting under CH06 for 11n HT20 at 65Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \(\mu \)V/m)
2437.00	94.55 (PK)	Н	Fundamental Frequency
2437.00	94.51 (PK)	V	Fundamental Frequency
4874.00	47.54 (PK)	Н	74(Peak)/ 54(AV)
4874.00	47.69 (PK)	V	74(Peak)/ 54(AV)
7311.00		H/V	74(Peak)/ 54(AV)
9748.00		H/V	74(Peak)/ 54(AV)
12185		H/V	74(Peak)/ 54(AV)
14622		H/V	74(Peak)/ 54(AV)
17059		H/V	74(Peak)/ 54(AV)
19496		H/V	74(Peak)/ 54(AV)
21933		H/V	74(Peak)/ 54(AV)
24370		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11n (HT20) mode 65Mbps

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No: 1312117 Page 30 of 117

Date: 2013-12-26



Operation Mode: Transmitting under CH11 for 11n HT20 at 65Mbps

Frequency (MHz)	Level@3m (dB μ V/m)	Antenna Polarity	Limit@3m (dB µ V/m)
2462.00	93.12 (PK)	Н	Γ
2462.00	93.31 (PK)	V	Fundamental Frequency
4924	48.69 (PK)	Н	74(Peak)/ 54(AV)
4924	47.64 (PK)	V	74(Peak)/ 54(AV)
7368		H/V	74(Peak)/ 54(AV)
9848		H/V	74(Peak)/ 54(AV)
12310		H/V	74(Peak)/ 54(AV)
14772		H/V	74(Peak)/ 54(AV)
17234		H/V	74(Peak)/ 54(AV)
19696		H/V	74(Peak)/ 54(AV)
22158		H/V	74(Peak)/ 54(AV)
24650		H/V	74(Peak)/ 54(AV)


Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11n (HT20) mode 65Mbps




Please refer to the following test plots for details:

CH01 for 11n HT20 at 65Mbps: Horizontal



CH01 for 11n HT20 at 65Mbps: Vertical



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 32 of 117


Report No: 1312117 Date: 2013-12-26



CH06 for 11n HT20 at 65Mbps: Vertical



CH06 for 11n HT20 at 65Mbps: Horizontal




The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.



CH11 for 11n HT20 at 65Mbps: Vertical



CH11 for 11n HT20 at 65Mbps: Horizontal



Note: For radiated Emissions from 18-25GHz, it is only the floor noise.

Report No: 1312117 Page 34 of 117

Date: 2013-12-26



Operation Mode: Transmitting under CH01 for 11n HT40 at 65Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \mu V/m)
2422.00	91.51 (PK)	Н	Fundamental Frequency
2422.00	91.44 (PK)	V	Fundamental Frequency
4844.00	47.01 (PK)	Н	74(Peak)/ 54(AV)
4844.00	48.77 (PK)	V	74(Peak)/ 54(AV)
7266.00		H/V	74(Peak)/ 54(AV)
9688.00		H/V	74(Peak)/ 54(AV)
12110		H/V	74(Peak)/ 54(AV)
14532		H/V	74(Peak)/ 54(AV)
16954		H/V	74(Peak)/ 54(AV)
19376		H/V	74(Peak)/ 54(AV)
21798		H/V	74(Peak)/ 54(AV)
24220		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11n (HT40) mode 65Mbps

Operation Mode: Transmitting under CH04 for 11n HT40 at 65Mbps

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \(\mu \)V/m)
2437.00	90.22 (PK)	Н	Fundamental Frequency
2437.00	90.56 (PK)	V	Fundamental Frequency
4874.00	46.66 (PK)	Н	74(Peak)/ 54(AV)
4874.00	47.53 (PK)	V	74(Peak)/ 54(AV)
7311.00		H/V	74(Peak)/ 54(AV)
9748.00		H/V	74(Peak)/ 54(AV)
12185		H/V	74(Peak)/ 54(AV)
14622		H/V	74(Peak)/ 54(AV)
17059		H/V	74(Peak)/ 54(AV)
19496		H/V	74(Peak)/ 54(AV)
21933		H/V	74(Peak)/ 54(AV)
24370		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11n (HT40) mode 65Mbps

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No: 1312117 Page 35 of 117

Date: 2013-12-26



Operation Mode: Transmitting under CH7 for 11n HT40 at 65Mbps

Frequency (MHz)	Level@3m (dB \u03bc V/m)	Antenna Polarity	Limit@3m (dB µ V/m)
2452.00	92.35 (PK)	Н	Fundamental Frequency
2452.00	92.56 (PK)	V	
4904	47.32 (PK)	Н	74(Peak)/ 54(AV)
4904	47.58 (PK)	V	74(Peak)/ 54(AV)
7356		H/V	74(Peak)/ 54(AV)
9808		H/V	74(Peak)/ 54(AV)
12260		H/V	74(Peak)/ 54(AV)
14712		H/V	74(Peak)/ 54(AV)
17164		H/V	74(Peak)/ 54(AV)
19616		H/V	74(Peak)/ 54(AV)
22068		H/V	74(Peak)/ 54(AV)
24520		H/V	74(Peak)/ 54(AV)


Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

- 2. Remark "---" means that the emissions level is too low to be measured
- 3. For 802.11n (HT40) mode 65Mbps




Please refer to the following test plots for details:

CH01 for 11n HT40 at 65Mbps: Vertical



CH01 for 11n HT40 at 65Mbps: Horizontal



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 37 of 117


Report No: 1312117 Date: 2013-12-26



CH04 for 11n HT40 at 65Mbps: Vertical



CH04 for 11n HT40 at 65Mbps: Horizontal



The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.


Report No: 1312117 Date: 2013-12-26



CH07 for 11n HT40 at 65Mbps: Vertical



CH07 for 11n HT40 at 65Mbps: Horizontal



Note: For radiated Emissions from 18-25GHz, it is only the floor noise.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.


Report No: 1312117 Page 39 of 117

Date: 2013-12-26



7.0 6dB and 99% Bandwidth Measurement

7.1 Test Setup



7.2 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is >500 kHz

7.3 Test Procedure

- 1. Set resolution bandwidth (RBW) = 100 kHz
- 2. Set the video bandwidth (VBW) \geq 3 x RBW.
- 3. Detector = Peak.
- 4. Trace mode = max hold.
- 5. Sweep = auto couple.
- 6. Allow the trace to stabilize.
- 7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

7.4 Test Result

Report No: 1312117 Page 40 of 117

Date: 2013-12-26



6dB Occupied Bandwidth


EUT		MID		Model	HS-7DTB10 ; HS-7DTB4A	
Mode		802.11b		Input Voltage	DC3.7V	
Temperature		24 deg. C,		Humidity	56% RH	
Channel	Channel Frequency (MHz)		Data Transfer Rate (Mbps)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass/ Fail
1	2412		1	10.08	0.5	Pass
6	2437		1	10.08	0.5	Pass
11	2462		1	10.08	0.5	Pass
1	2412		11	9.48	0.5	Pass
6	2437		11	9.48	0.5	Pass
11	2462		11	9.48	0.5	Pass

Report No: 1312117 Page 41 of 117

以 TIMEWAY TESTING LABO

1. 802.11b at 1Mbps of CH01

Date: 2013-12-26



Date: 24.DEC.2013 10:42:52

Report No: 1312117 Page 42 of 117

Date: 2013-12-26



2. 802.11b at 1Mbps of CH06




Date: 24.DEC.2013 10:54:26

Page 43 of 117

Report No: 1312117 Date: 2013-12-26



3. 802.11b at 1Mbps of CH11




Date: 24.DEC.2013 10:55:46

Report No: 1312117 Page 44 of 117

Date: 2013-12-26



4. 802.11b at 11Mbps of CH01




Date: 24.DEC.2013 10:49:14

Page 45 of 117

Report No: 1312117 Date: 2013-12-26



5. 802.11b at 11Mbps of CH06




Date: 24.DEC.2013 10:50:42

Page 46 of 117

Report No: 1312117 Date: 2013-12-26



6. 802.11b at 11Mbps of CH11



Date: 24.DEC.2013 10:59:19

Report No: 1312117 Page 47 of 117

Date: 2013-12-26



6dB Occupied Bandwidth

EUT		MID		Model	HS-7DTB10 ; HS-7DTB4A	
Mode		802.11g		Input Voltage	DC3.7V	
Temperati	ure	24 deg. C,		Humidity	56% RH	
Channel	Channel Frequency (MHz)		Data Transfer Rate (Mbps)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass/ Fail
1	2412		54	16.56	0.5	Pass
6	2437		54	16.56	0.5	Pass
11	2462		54	16.56	0.5	Pass

Page 48 of 117


Date: 2013-12-26

Report No: 1312117



Test Plots:

1. 802.11g at 54Mbps of CH01




Date: 24.DEC.2013 10:45:31

Page 49 of 117

Report No: 1312117 Date: 2013-12-26



2. 802.11g at 54Mbps of CH06




Date: 24.DEC.2013 10:53:13

Report No: 1312117 Page 50 of 117

Date: 2013-12-26



3. 802.11g at 54Mbps of CH11



Date: 24.DEC.2013 10:56:48

Report No: 1312117 Page 51 of 117

Date: 2013-12-26



6dB Occupied Bandwidth


EUT		MID		Model	HS-7DTB10; HS-7DTB4A	
Mode		802.11n HT20/HT40		Input Voltage	DC3.7V	
Temperature		24 deg. C,		Humidity	56% RH	
Channel	Channel Frequency (MHz)		Data Transfer Rate (Mbps)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass/ Fail
1	2412		65	17.76	0.5	Pass
6	2437		65	17.76	0.5	Pass
11	2462		65	17.76	0.5	Pass
1	2422		65	36.48	0.5	Pass
4	2437		65	36.48	0.5	Pass
7	2452		65	36.48	0.5	Pass

Page 52 of 117

Report No: 1312117 Date: 2013-12-26

Test Plots:

1. 802.11n at HT20 of CH01




24.DEC.2013 11:04:08 Date:

Report No: 1312117 Page 53 of 117

Date: 2013-12-26



2. 802.11n at HT20 of CH06




Date: 24.DEC.2013 11:02:28

Report No: 1312117 Page 54 of 117

Date: 2013-12-26



3. 802.11n at HT20 of CH11




Date: 24.DEC.2013 11:00:57

Report No: 1312117 Page 55 of 117

Date: 2013-12-26



4. 802.11n at HT40 of CH01




Date: 24.DEC.2013 11:06:17

Report No: 1312117 Page 56 of 117

Date: 2013-12-26



5. 802.11n at HT40 of CH04




Date: 24.DEC.2013 11:08:13

Report No: 1312117 Page 57 of 117

Date: 2013-12-26



6. 802.11n at HT40 of CH07



Date: 24.DEC.2013 11:09:59

Report No: 1312117 Page 58 of 117

Date: 2013-12-26



99% Occupied Bandwidth

EUT		MID		Model	HS-7DTB10; HS-7DTB4A	
Mode		802.11b		Input Voltage	DC3.7V	
Temperature		24 deg. C,		Humidity	56% R	Н
Channel	Channel Frequency (MHz)		Data Transfer Rate (Mbps)	99% Bandwidth (MHz)	Minimum Limit (MHz)	Pass/ Fail
1	2412		1	15.12		Pass
6	2437		1	15.12		Pass
11	2462		1	15.12		Pass
1	2412		11	14.88		Pass
6	2437		11	14.88		Pass
11	2462		11	14.94		Pass


Page 59 of 117

Date: 2013-12-26

Report No: 1312117



1. 802.11b at 1Mbps of CH1



Date: 24.DEC.2013 11:16:35


Page 60 of 117

Date: 2013-12-26

Report No: 1312117



2. 802.11b at 1Mbps of CH6




Date: 24.DEC.2013 11:21:10

Report No: 1312117 Page 61 of 117

Date: 2013-12-26



3. 802.11b at 1Mbps of CH11



Date: 24.DEC.2013 11:22:02

Report No: 1312117 Page 62 of 117

Date: 2013-12-26



4. 802.11b at 11Mbps of CH1




Date: 24.DEC.2013 11:18:07

Report No: 1312117 Page 63 of 117

Date: 2013-12-26



5. 802.11b at 11Mbps of CH6




Date: 24.DEC.2013 11:18:53

Report No: 1312117 Page 64 of 117

Date: 2013-12-26



6. 802.11b at 11Mbps of CH11



Date: 24.DEC.2013 11:23:59

Report No: 1312117 Page 65 of 117

Date: 2013-12-26



99% Occupied Bandwidth


EUT		MID		Model	HS-7DTB10; HS-7DTB4A	
Mode		802.11g		Input Voltage	DC3.7V	
Temperature		24 deg. C,		Humidity	56% RH	
Channel	Channel Frequency (MHz)		Data Transfer Rate (Mbps)	99% Bandwidth (MHz)	Minimum Limit (MHz)	Pass/ Fail
1	2412		54	16.56		Pass
6	2437		54	16.56		Pass
11	2462		54	16.50		Pass

Page 66 of 117

Report No: 1312117 Date: 2013-12-26



1. 802.11g at 54Mbps of CH1




Date: 24.DEC.2013 11:17:21

Report No: 1312117 Page 67 of 117

Date: 2013-12-26



2. 802.11g at 54Mbps of CH6




Date: 24.DEC.2013 11:19:56

Report No: 1312117 Page 68 of 117

Date: 2013-12-26



3. 802.11g at 54Mbps of CH11



Date: 24.DEC.2013 11:22:48

Report No: 1312117 Page 69 of 117

Date: 2013-12-26



99% Occupied Bandwidth


EUT		MID	Model	HS-7DTB10 ; HS-7DTB4A		
Mode	802.1	1n HT20/HT40	Input Voltage	DC3.7V		
Temperati	ure	24 deg. C,	Humidity	56% RH		
Channel	Channel Frequency (MHz)	Data Transfer Rate (Mbps)	99% Bandwidth (MHz)	Minimum Limit (MHz)	Pass/ Fail	
1	2412	HT20	17.76		Pass	
6	2437	HT20	17.76		Pass	
11	2462	HT20	17.76		Pass	
1	2422	HT40	36.10		Pass	
4	2437	HT40	36.20		Pass	
7	2452	HT40	36.20		Pass	

Report No: 1312117 Page 70 of 117

Date: 2013-12-26



1.802.11n at HT20 of CH1




Date: 24.DEC.2013 11:27:01

Report No: 1312117 Page 71 of 117

Date: 2013-12-26



2. 802.11n at HT20 of CH6




Date: 24.DEC.2013 11:25:36

Report No: 1312117 Page 72 of 117

Date: 2013-12-26



3. 802.11n at HT20 of CH11




Date: 24.DEC.2013 11:24:46

Report No: 1312117 Page 73 of 117

Date: 2013-12-26



4. 802.11n at HT40 of CH01




Date: 24.DEC.2013 11:15:10

Report No: 1312117 Page 74 of 117

Date: 2013-12-26



5. 802.11n at HT40 of CH04




Date: 24.DEC.2013 11:14:01

Report No: 1312117 Page 75 of 117

Date: 2013-12-26



6. 802.11n at HT40 of CH07




Date: 24.DEC.2013 11:12:39

Report No: 1312117 Page 76 of 117

Date: 2013-12-26

8. Maximum Peak Output Power

8.1 Test Setup



8.2 Limits of Maximum Peak Output Power

The Maximum Peak Output Power Measurement is 30dBm.

8.3 Test Procedure

The RF power output was measured with a Power meter connected to the RF Antenna connector (conducted measurement) while EUT was operating in transmit mode at the appropriate centre frequency.

Note: the peak power was measured

Report No: 1312117 Date: 2013-12-26



8.4Test Results

EUT		MID		Model		HS-7DTB10; HS-7DTB4A			
Mode		802.11b		Input Voltage		DC3.7V			
Temperatu	re	24 deg. C,		Humidity		56% RH		56% RH	
Channel	Cł	hannel Frequen (MHz)	су	Peak Power Output (dBm)		ık Power Limit Pass/ Fail (dBm)			
1		2412		9.30		30	Pass		
6		2437		9.34		30	Pass		
11		2462		9.34		30	Pass		

Note: 1. At finial test to get the worst-case emission at 11Mbps for CH01, CH06 and CH11

The result basic equation calculation as follow:
 Peak Power Output = Peak Power Reading + Cable loss + Attenuator

3. The worse case was recorded

EUT	EUT			Model		HS-7DTB10; HS-7DTB4A		
Mode		802.11g		Input Voltage			DC3.7V	
Temperat	ure	24 deg. C,		Humidity		56% RH		
Channel	Channel Frequency (MHz)		у	Peak Power Output (dBm)	Pea	ak Power Limit (dBm)	Pass/ Fail	
1		2412		6.53		30	Pass	
6		2437		6.50		30	Pass	
11		2462		6.51		30	Pass	

Note: 1. At finial test to get the worst-case emission at 54Mbps for CH01, CH06 and CH11

- The result basic equation calculation as follow:
 Peak Power Output = Peak Power Reading + Cable loss + Attenuator
- 3. The worse case was recorded

Page 78 of 117

Report No: 1312117 Date: 2013-12-26



EUT	T MID			Model		HS-7DTB10; HS-7DTB4A	
Mode	Mode 802.11n (HT20) Input		Input Voltage		DC3.7V		
Temperat	ure	24 deg. C	,	Humidity		y 56% RH	
Channel	Cha	Channel Frequency (MHz)		Peak Power Output (dBm)		Peak Power Limit (dBm)	Pass/ Fail
1		2412		6.78		30	Pass
6		2437	6.79			30	Pass
11		2462	6.78			30	Pass

Note: 1. At finial test to get the worst-case emission at 11n HT20 for CH01, CH06 and CH11

The result basic equation calculation as follow:
 Peak Power Output = Peak Power Reading + Cable loss + Attenuator

3. The worse case was recorded

EUT		MID	Model		HS-7DTB10; HS-7DTB4A	
Mode		802.11n (HT40)	2.11n (HT40) Input Voltag		DC3.7V	
Temperatu	re	24 deg. C,	Humidity		56% RH	
Channel	Channel Frequency (MHz)		Peak Power Output (dBm)	Peal Powe Lim (dBn	er it	Pass/ Fail
1		2422	6.71	30		Pass
4		2437	6.77	30		Pass
7		2452	6.74	30		Pass

Note: 1. At finial test to get the worst-case emission at 11n HT40 for CH01, CH04 and CH07

- The result basic equation calculation as follow:
 Peak Power Output = Peak Power Reading + Cable loss + Attenuator
- 3. The worse case was recorded


Report No: 1312117 Page 79 of 117

Date: 2013-12-26



9. Power Spectral Density Measurement

9.1 Test Setup



9.2 Limits of Power Spectral Density Measurement

The Maximum Power Spectral Density Measurement is 8dBm.

9.3 Test Procedure

- 1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
- 2. Set the RBW = 10 kHz.
- 3. Set the VBW \geq 30 kHz.
- 4. Set the span to 1.5 times the DTS channel bandwidth.
- 5. Detector = peak.
- 6. Sweep time = auto couple.
- 7. Trace mode = max hold.
- 8. Allow trace to fully stabilize.
- 9. Use the peak marker function to determine the maximum amplitude level.
- 10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.
- 11. The resulting peak PSD level must be ≤ 8 dBm.

Page 80 of 117

Report No: 1312117 Date: 2013-12-26



9.4Test Result

EUT	EUT MID Model			HS-7DTB10; H	S-7DTB4A	
Mode		802.11b 11Mbps	Input Voltage		DC3.7V	
Temperat	ure	24 deg. C,	Humidity		56% RH	
Channel	Cha	annel Frequency	Final RF Power Level	M	aximum Limit	Pass/ Fail
		(MHz)	(dBm)		(dBm)	
			11Mbps			
1		2412	-15.29		8	Pass
6		2437	-15.20		8	Pass
11		2462	-15.22		8	Pass

EUT		MID	MID Model		HS-7DTB10 ; HS-7DTB4A	
Mode		802.11b 1Mbps	Input Voltage		DC3.7V	
Temperat	ure	24 deg. C,	Humidity		56% RH	
Channel	Channel Frequency (MHz)		Final RF Power Level (dBm)			Pass/ Fail
			1Mbps			
1		2412	-16.98		8	Pass
6		2437	-16.99		8	Pass
11		2462	-16.74		8	Pass

EUT		MID	Model	Model		HS-7DTB10; HS-7DTB4A	
Mode		802.11g 54Mbps	Input Voltage		DC3.	7V	
Temperat	ure	24 deg. C,	Humidity		56% RH		
Channel	Channel Frequency		Final RF Power Level	Final RF Power Level Ma		Pass/ Fail	
Channel		(MHz)	(dBm)		(dBm)		
			54Mbps				
1		2412	-22.86		8	Pass	
6		2437	-22.77		8	Pass	
11		2462	-22.90		8	Pass	

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd vill not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 81 of 117

Report No: 1312117 Date: 2013-12-26



EUT		MID		Model	HS-7DTB10; HS-7DTB4A	
Mode		802.11n HT20 65	Mbps	Input Voltage	DC3.7V	
Temperat	ure	24 deg. C,		Humidity	56% RH	
Channel	Cha	Channel Frequency (MHz)		l RF Power Level (dBm)	Maximum Limit (dBm)	Pass/ Fail
				HT20		
1		2412	•	-22.13	8	Pass
6		2437	-22.20		8	Pass
11		2462		-22.33	8	Pass

EUT		MID		Model	HS-7DTB10; HS-7DTB4A	
Mode		802.11n HT40 65Mbps		Input Voltage	DC3.7V	
Temperati	ure	24 deg. C,		Humidity	56% RH	
Channel	Channel Frequency (MHz)		Final RF Power Level (dBm)		Maximum Limit (dBm)	Pass/ Fail
				HT40		
1		2422		-23.73	8	Pass
4		2437	•	-23.89	8	Pass
7		2452		-24.21	8	Pass


Report No: 1312117 Page 82 of 117



9.5 Photo of Power Spectral Density Measurement

1.802.11b at 11Mbps of CH01

Date: 2013-12-26




Date: 24.DEC.2013 12:04:50

Page 83 of 117

Report No: 1312117 Date: 2013-12-26



2. 802.11b at 11Mbps at CH06




Date: 24.DEC.2013 12:05:28

Page 84 of 117

Report No: 1312117 Date: 2013-12-26



3. 802.11b at 11Mbps of CH11




Date: 24.DEC.2013 12:09:06

Page 85 of 117

Report No: 1312117 Date: 2013-12-26



4. 802.11b at 1Mbps of CH1




Date: 24.DEC.2013 12:02:23

Page 86 of 117

Report No: 1312117 Date: 2013-12-26



5. 802.11b at 1Mbps of CH6




Date: 24.DEC.2013 12:06:58

Page 87 of 117

Report No: 1312117 Date: 2013-12-26



6. 802.11b at 1Mbps of CH11




Date: 24.DEC.2013 12:07:50

Page 88 of 117

Report No: 1312117 Date: 2013-12-26



7. 802.11g at 54Mbps of CH1




Date: 24.DEC.2013 12:03:46

Page 89 of 117

Report No: 1312117 Date: 2013-12-26



8. 802.11g at 54Mbps of CH6




Date: 24.DEC.2013 12:06:18

Page 90 of 117

Report No: 1312117 Date: 2013-12-26



9. 802.11g at 54Mbps of CH11




Date: 24.DEC.2013 12:08:32

Page 91 of 117

Report No: 1312117 Date: 2013-12-26



10. 802.11n at HT20 of CH01




Date: 24.DEC.2013 12:12:23

Page 92 of 117

Report No: 1312117 Date: 2013-12-26



11. 802.11n at HT20 of CH06




Date: 24.DEC.2013 12:11:04

Page 93 of 117

Report No: 1312117 Date: 2013-12-26



12. 802.11n at HT20 of CH11




Date: 24.DEC.2013 12:10:05

Report No: 1312117 Page 94 of 117

Date: 2013-12-26



13. 802.11n at HT40 of CH01




Date: 24.DEC.2013 12:14:12

Page 95 of 117

Report No: 1312117 Date: 2013-12-26



14. 802.11n at HT40 of CH04




Date: 24.DEC.2013 12:14:57

Page 96 of 117

Report No: 1312117 Date: 2013-12-26



15. 802.11n at HT40 of CH07



Date: 24.DEC.2013 12:15:58


Report No: 1312117 Page 97 of 117

Date: 2013-12-26



10 Out of Band Measurement

10.1 Test Setup for band edge



The restricted band requirement based on radiated emission test; please see the clause 6 for the test setup

10.2 Limits of Out of Band Emissions Measurement

- 1. Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).
- 2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

10.3 Test Procedure

For signals in the restricted bands above and below the 2.4-2.483GHz allocated band a measurement was made of radiated emission test.(Peak values with RBW=VBW=1MHz and PK detector. AV value with RBW=1MHz, VBW=10Hz and PK detector)

For bandage test, the spectrum set as follows: RBW=VBW=100 kHz. A conducted measurement used

10.4 Test Result

Please see next pages

Note: 1. this is a handhold device. The radiated emissions should be tested under 3-axes position (Lying, Side, and Stand), after pre-test. It was found that the worse radiated emission was get at the lying position.

2. The worse case was recorded

Report No: 1312117 Date: 2013-12-26




For 802.11b mode CH01 at 11Mbps

10.4 Band-edge and Restricted band Measurement

EUT		MID	Model	HS-7DTB10; HS-7DTB4A
				•
Mode	Keeping	g Transmitting	Input Voltage	DC3.7V
Temperature	24	deg. C,	Humidity	56% RH
Test Result:		Pass	Detector	PK
2400	PK (dBµV/m)	46.7	T ::4	$74(dB\mu V/m)$
	AV (dBμV/m)		Limit	54(dBμV/m)
2390	PK (dBµV/m)	40.1	Limit	74(dBμV/m)
	AV (dBμV/m)		Liffill	$54(dB\mu V/m)$

Test Figure:



Date: 24.DEC.2013 14:02:22

Page 99 of 117

Report No: 1312117 Date: 2013-12-26




CH11 at 11Mbps

10.4 Band-edge and Restricted band Measurement

EUT		MID	Model	HS-7DTB10; HS-7DTB4A
Mode	Keepin	g Transmitting	Input Voltage	DC3.7V
Temperature	24	4 deg. C,	Humidity	56% RH
Test Result:		Pass	Detector	PK
2483.5	PK (dBμV/m) 41.8		T ::4	$74(dB\mu V/m)$
	AV (dBμV/m)		Limit	$54(dB\mu V/m)$

Test Figure:



Date: 24.DEC.2013 14:07:44

Report No: 1312117 Date: 2013-12-26




For 802.11g mode CH01 at 54Mbps

10.4 Band-edge and Restricted band Measurement

EUT		MID	Model	HS-7DTB10; HS-7DTB4A
Mode	Keepin	g Transmitting	Input Voltage	DC3.7V
Temperature	24	4 deg. C,	Humidity	56% RH
Test Result:		Pass	Detector	PK
2400	PK (dBµV/m)	45.5	T ::4	$74(dB\mu V/m)$
	AV (dBμV/m)		Limit	$54(dB\mu V/m)$
2390	PK (dBµV/m)	39.9	Limit	$74(dB\mu V/m)$
	AV (dBμV/m)		Lillit	$54(dB\mu V/m)$

Test Figure:



Date: 24.DEC.2013 14:01:25

Page 101 of 117

Report No: 1312117 Date: 2013-12-26




CH11 at 54Mbps

10.4 Band-edge and Restricted band Measurement

EUT	MID		Model	HS-7DTB10; HS-7DTB4A
Mode	Keeping Transmitting		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
2483.5	PK (dBµV/m)	40.6	T imit	$74(dB\mu V/m)$
	AV (dBμV/m)		Limit	$54(dB\mu V/m)$

Test Figure:



Date: 24.DEC.2013 14:07:07

Report No: 1312117 Date: 2013-12-26




For 802.11n (HT20) mode CH01 at 65Mbps

10.4 Band-edge and Restricted band Measurement

EUT	MID		Model	HS-7DTB10; HS-7DTB4A
Mode	Keeping Transmitting		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
2400	PK (dBμV/m)	45.8	T ::4	74(dBμV/m)
	AV (dBμV/m)		Limit	$54(dB\mu V/m)$
2390	PK (dBμV/m)	38.8	Limit	$74(dB\mu V/m)$
	AV (dBμV/m)		LIIIII	$54(dB\mu V/m)$

Test Figure:



Date: 24.DEC.2013 14:03:31

Page 103 of 117

Report No: 1312117 Date: 2013-12-26




CH11 at 65Mbps

10.4 Band-edge and Restricted band Measurement

EUT	MID		Model	HS-7DTB10; HS-7DTB4A
Mode	Keeping Transmitting		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
2483.5	PK (dBµV/m)	41.8	T imit	$74(dB\mu V/m)$
	AV (dBμV/m)		Limit	$54(dB\mu V/m)$

Test Figure:



Date: 24.DEC.2013 14:08:48

Page 104 of 117

Report No: 1312117 Date: 2013-12-26




For 802.11n (HT40) mode CH01 at 65Mbps

10.4 Band-edge and Restricted band Measurement

EUT	MID		Model	HS-7DTB10; HS-7DTB4A
Mode	Keeping Transmitting		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
2400	PK (dBµV/m)	43.1	Limit	$74(dB\mu V/m)$
	AV (dBμV/m)		Lillit	54(dBµV/m)
2390	PK (dBμV/m)	38.7	Limit	74(dBμV/m)
	AV (dBμV/m)		Lillit	54(dBμV/m)

Test Figure:



Date: 24.DEC.2013 14:04:59

Note: The Max. FS in Restrict Band are measured in conventional method.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Page 105 of 117

Report No: 1312117 Date: 2013-12-26




CH07 at 65Mbps

10.4 Band-edge and Restricted band Measurement

EUT	MID		Model	HS-7DTB10; HS-7DTB4A
Mode	Keeping Transmitting		Input Voltage	DC3.7V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
2483.5	PK (dBµV/m)	39.7	T imit	$74(dB\mu V/m)$
	AV (dBμV/m)		Limit	$54(dB\mu V/m)$

Test Figure:



Date: 24.DEC.2013 14:09:43

Report No: 1312117 Page 106 of 117

Report No: 1312117 Date: 2013-12-26



11.0 Antenna Requirement

11.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitter antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the mount in dB that the directional gain of the antenna exceeds 6 dBi.

11.2 Antenna Connected construction

Integral antenna used. The maximum Gain of the antennas is 2.0dBi.

Page 107 of 117

Report No: 1312117 Date: 2013-12-26



12.0 FCC/IC Label

FCC ID: YH5-7DTB108GB **IC:** 8012A-7DTB108GB

This device complies with FCC Part 15 and Industry Canada licence-exempt RSS standard(s). Operation is subject to the following two conditions (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

The label must not be a stick-on paper label. The label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

Mark Location:




Page 108 of 117

Report No: 1312117 Date: 2013-12-26



13.0 **Photo of testing**

Conducted Emission Test Setup:



Page 109 of 117

Report No: 1312117 Date: 2013-12-26



Radiated Emission Test Setup:





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No: 1312117 Date: 2013-12-26



Photographs - EUT

Outside view





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to

Page 111 of 117

Report No: 1312117 Date: 2013-12-26



Outside view





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to

Page 112 of 117

Report No: 1312117 Date: 2013-12-26



Power Supply





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to

Report No: 1312117 Page 113 of 117

Date: 2013-12-26



Power Supply



Page 114 of 117

Report No: 1312117 Date: 2013-12-26



Inside view





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to


Page 115 of 117

Report No: 1312117 Date: 2013-12-26



Inside view





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it. or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd vill not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 116 of 117

Report No: 1312117 Date: 2013-12-26



Inside view





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to

Report No: 1312117 Page 117 of 117

Date: 2013-12-26



Inside view



End of the report