



Volume Control TEST REPORT

No.23T04Z80629-022

for

BLU Products,Inc.

Smart Phone

B160V

FCC ID: YHLBLUB160V

with

Hardware Version: V1.0

Software Version: BLU_B160V_V14.0.01.05.01.24_FSec

Issued Date: 2024-01-08

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

Test Laboratory:

CTTL-Telecommunication Technology Labs, CAICT

No. 52, Huayuan North Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512, Fax:+86(0)10-62304633-2504

Email: ctl_terminals@caict.ac.cn, website: www.caict.ac.cn



No. 23T04Z80629-022

REPORT HISTORY

Report Number	Revision	Description	Issue Date
23T04Z80629-022	Rev.0	1st edition	2024-01-08

Note: the latest revision of the test report supersedes all previous version.

CONTENTS

1. TEST LABORATORY	4
1.1. INTRODUCTION & ACCREDITATION	4
1.2. TESTING LOCATION	4
1.3. TESTING ENVIRONMENT.....	5
1.4. PROJECT DATA	5
1.5. SIGNATURE	5
2. CLIENT INFORMATION.....	6
2.1. APPLICANT INFORMATION	6
2.2. MANUFACTURER INFORMATION	6
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	7
3.1. ABOUT EUT	7
3.2. INTERNAL IDENTIFICATION OF EUT	7
3.3. INTERNAL IDENTIFICATION OF AE.....	7
4. REFERENCE DOCUMENTS.....	8
4.1. DOCUMENTS SUPPLIED BY APPLICANT	8
4.2. REFERENCE DOCUMENTS FOR TESTING	8
5. AIR INTERFACES / BANDS USED FOR TESTING.....	9
6. TEST RESULTS	9
6.1. TEST SUMMARY AND CONCLUSIONS.....	9
6.2. DESCRIPTION OF TEST SETUP	10
6.3. TEST DETAIL RESULTS	11
7. TEST FACILITIES UTILIZED	16
ANNEX A: EUT PHOTOGRAPH	17
ANNEX B: EUT PARAMETERS.....	18
ANNEX C: TEST LAYOUT	19
ANNEX D: THE WORST-CASE MEASUREMENT DATA OF THE CHOSEN CODEC OF TELEPHONY CALL	20
ANNEX E: THE WORST-CASE MEASUREMENT DATA OF OTHER CODECS OF TELEPHONY CALL	27
ANNEX F: FREQUENCY RESPONSE USED DF AND 1/12 OCTAVE	28
ANNEX G: HATS CERTIFICATE	30
ANNEX H: ACOUSTIC CHAMBER CERTIFICATE	31
ANNEX I: ACCREDITATION CERTIFICATE.....	32



1. Test Laboratory

1.1. Introduction & Accreditation

Telecommunication Technology Labs, CAICT is an ISO/IEC 17025:2017 accredited test laboratory under American Association for Laboratory Accreditation (A2LA) with lab code 7049.01, and is also an FCC accredited test laboratory (CN1349), and ISED accredited test laboratory (CAB identifier:CN0066). The detail accreditation scope can be found on A2LA website.

1.2. Testing Location

Location 1: CTTL(huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing,
P. R. China 100191


1.3. Testing Environment

Normal Temperature: 15-35°C
Extreme Temperature: -10/+55°C
Relative Humidity: 20-75%
Ambient noise of 14dB(A) and is compliance with requirement of standards
acoustic chamber (SEE ANNEX H)


1.4. Project data

Testing Start Date: 2023-12-13
Testing End Date: 2024-01-02


1.5. Signature



Zhu Hongye
(Prepared this test report)



Lu Yuping
(Reviewed this test report)



Zhao Xinglong
(Approved this test report)



2. Client Information

2.1. Applicant Information

Company Name: BLU Products, Inc.
Address: 8600 NW 36th Street, Suite #300 | Miami, FL 33166
City: Miami
Postal Code: /
Country: America
Telephone: 305.715.7171
Fax: 305.436.8819

2.2. Manufacturer Information

Company Name: BLU Products, Inc.
Address: 8600 NW 36th Street, Suite #300 | Miami, FL 33166
City: Miami
Postal Code: /
Country: America
Telephone: 305.715.7171
Fax: 305.436.8819

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

General Information:

Description	Smart Phone
Model name/HVIN	B160V
Marketing Name/PMN	/
Brand name	BLU
FCC ID	YHLBLUB160V
Extreme Temperature	0~45°C

Supported Bands:

UMTS Frequency Band(s)	Band 2/4/5
GSM Frequency Band(s)	GSM 850/1900
E-UTRA Frequency Band(s)	Band 02/04/05/12/13/66
Wi-Fi Frequency Band(s)	2.4G

Supported Codecs:

UMTS Audio Codec(s)	AMR NB/AMR WB
GSM Audio Codec (s)	EFR/AMR NB/AMR WB
E-UTRA Audio Codec(s)	AMR NB/AMR WB/EVS NB/EVS WB
Wi-Fi Audio Codec(s)	AMR NB/AMR WB/EVS NB/EVS WB
OTT	Google Meet

Note: Photographs of EUT are shown in ANNEX A of this test report.

3.2. Internal Identification of EUT

EUT ID*	SN or IMEI	HW Version	SW Version	Date of receipt
UT78a	IMEI:356197680005216	V1.0	BLU_B160V_V14.0.01.05.01.24_FSec	2023-12-08
UT92a	IMEI:356197680012147	V1.0	BLU_B160V_V14.0.01.05.01.24_FSec	2023-12-28

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE

AE ID*	Description	SN
/	/	/

*AE ID: is used to identify the test sample in the lab internally.

4. Reference Documents

4.1. Documents supplied by applicant

EUT parameters, referring to Annex B for detailed information, is supplied by the client or manufacturer, which is the basis of testing.

4.2. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
ANSI C63.19	American National Standard Methods of Measurement of Compatibility Between Wireless Communications Devices and Hearing Aids	2019
TIA 5050	Telecommunications Communications Products Receive Volume Control Requirements for Wireless (Mobile) Devices	2018 Edition
285076 D04 Volume Control v02	GUIDANCE FOR PERFORMING VOLUME CONTROL MEASUREMENTS ON MOBILE HANDSETS	2023.09.29
285076 D05 HAC Waiver DA 23-914 v01	HAC COMPLIANCE UNDER WAIVER DA 23-914	2023.09.29

5. Air Interfaces / Bands used for testing

The codec bit rates of the applicant's choosing are EVS-NB 13.2kbps and EVS-WB 13.2kbps.

Air-interface	Band	Tested Codec	Tested Rate(kbps)
GSM	850/1900	EFR	/
WCDMA (UMTS)	Band 2/4/5	AMR-NB	4.75/12.2
		AMR-WB	6.6/12.65
VoLTE	Band 2/4/5/12/13/66	AMR-NB	4.75/12.2
		AMR-WB	6.6/12.65
		EVS-NB	13.2
		EVS-WB	13.2
VoWiFi	802.11g/ac	AMR-NB	4.75
		EVS-NB	13.2

6. Test Results

6.1. Test summary and Conclusions

The volume control measurement method is in accordance with the TIA 5050-2018.

The EUT was tested in CTTL acoustics laboratory. All the detail results are showed in section 6.3.

I: Under the waiver, only CMRS narrowband and CMRS wideband voice codecs are required to comply with the volume control requirements of the TIA 5050-2018 Volume Control Standard as amended as follows:

- a. For the 2N mounting force test, one narrowband and one wideband voice codec embedded with the handset must pass with at least one volume control setting with a conversational gain of ≥ 6 dB for all voice services, bands of operation and air interfaces over which it operates using one codec bit rate of the applicant's choosing.
- b. For the 8N mounting force test, one narrowband and one wideband voice codec embedded with the handset must pass with at least one volume control setting with a conversational gain of ≥ 6 dB for all voice services, bands of operation and air interfaces over which they operate but is not required to meet or exceed the full 18 dB of conversational gain specified in section 5.1.1 of the TIA 5050 Volume Control Standard using one codec bit rate of the applicant's choosing.

II: For all other narrowband and wideband codecs not evaluated in I.a. above, TIA 5050-2018 Receive Distortion and Noise Performance and Receive Acoustic Frequency Response Performance evaluations are not required; however, these codecs shall be assessed for conversational gain and documented in the test report at the 2N and 8N levels with a gain of ≥ 6 dB for all voice services, bands of operation and air interfaces over which they operate. The handset volume setting used to comply with I.a. shall be used for these other CMRS codec evaluations.

III. Any other codec for voice services embedded in the handset, not identified in I and II above, is not required to comply or demonstrate in the test reports for conversational gain.

Table 6.1-1: the worst-case test results of the chosen codec of telephony call

Air-interface & Band	Channel	Band width	Modulation	RB Size	RB Offset	Volume Level	Codec	NB/WB	Bit Rate	2N/8N	Conv. Gain (ANN EX D)	FR (AN NEX D)	Min PN-SDNR (ANNEX D)		Verdict
		[kHz]							[kpbs]	[N]	[dB]	[Hz]	[dB]		
LTE Band 2	18900	10	QPSK	1	0	max	EVS	NB	13.2	2N	10.90	PASS	800	23.46	PASS
LTE Band 2	18900	10	QPSK	1	0	max	EVS	NB	13.2	8N	14.82	PASS	500	21.71	PASS
LTE Band 2	18900	10	QPSK	1	0	max	EVS	WB	13.2	2N	10.52	PASS	250	28.26	PASS
LTE Band 2	18900	10	QPSK	1	0	max	EVS	WB	13.2	8N	13.91	PASS	315	26.34	PASS

Table 6.1-2: the worst-case test results of other codecs of telephony call

Air-interface & Band	Channel	Band width	Modulation	RB Size	RB Offset	Volume Level	Codec	NB/WB	Bit Rate	2N/8N	Conv. Gain (ANN EX E)	FR (AN NEX E)	Min PN-SDNR (ANNEX E)		Verdict
		[MHz]							[kpbs]	[N]	[dB]	[Hz]	[dB]		
LTE Band 2	18900	10	QPSK	50	0	max	AMR	NB	4.75	2N	10.32	/	/	/	PASS
LTE Band 2	18900	10	QPSK	50	0	max	AMR	NB	4.75	8N	14.05	/	/	/	PASS
LTE Band 2	18900	10	QPSK	50	0	max	AMR	WB	6.6	2N	10.39	/	/	/	PASS
LTE Band 2	18900	10	QPSK	50	0	max	AMR	WB	6.6	8N	13.93	/	/	/	PASS
GSM 850	162	/	/	/	/	max	EFR	NB	/	2N	10.94	/	/	/	PASS
GSM 850	162	/	/	/	/	max	EFR	NB	/	8N	14.91	/	/	/	PASS

6.2. Description of Test Setup

In order to provide the complete information about the measurement environment within this report the setup is described in this chapter. Figure 6.2.1 shows a block diagram of the test arrangement.




Fig. 6.2.1: Block diagram of the test setup

An artificial head measurement system according to ITU-T Recommendation P.58 equipped with artificial ears (Type3.3 acc. ITU-T Rec. P.57) are used. The artificial head is placed in the center of an anechoic test room. The measurements are implemented in the HEAD acoustics software ACQUA and can be carried out automatically. They allow signal recording at the artificial ears and feeding at the network simulator.

The network simulators (e.g. Rohde & Schwarz CMW500, CMX500) establish the call to the mobile phone via an antenna connection. The EUT was tested using EFR/AMR-NB/AMR-WB/EVS-NB/EVS-WB codecs.

ANNEX C shows the handheld Positioner with mounted EUT. The application force between the phone and the artificial ear is adjusted. A mounting force of 2N or 8 N is adjusted.

6.3. Test Detail Results

6.3.1 VoLTE IMS call investigation

Table 6.3.1-1: the **Codec** and **Bandwidth** investigating results of **VoLTE** IMS call

Band	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Volume Level	Codec	NB/WB	Bit Rate	2N/8N	Conv. Gain	FR	Min PN-SDNR	
									[kbps]	[N]	[dB]		[Hz]	[dB]
Band 2	18900	10	QPSK	50	0	max	EVS	NB	13.2	2N	10.83	PASS	800	23.28
Band 2	18900	10	QPSK	50	0	max	EVS	NB	13.2	8N	14.44	PASS	800	22.61
Band 2	18900	10	QPSK	50	0	max	EVS	WB	13.2	2N	10.48	PASS	250	27.80
Band 2	18900	10	QPSK	50	0	max	EVS	WB	13.2	8N	13.95	PASS	250	28.35
Band 2	18900	10	QPSK	50	0	max	AMR	NB	4.75	2N	10.32	/	/	/

Band 2	18900	10	QPSK	50	0	max	AMR	NB	12.2	2N	11.16	/	/	/
Band 2	18900	10	QPSK	50	0	max	AMR	NB	4.75	8N	14.05	/	/	/
Band 2	18900	10	QPSK	50	0	max	AMR	NB	12.2	8N	14.80	/	/	/
Band 2	18900	10	QPSK	50	0	max	AMR	WB	6.6	2N	10.39	/	/	/
Band 2	18900	10	QPSK	50	0	max	AMR	WB	12.65	2N	10.53	/	/	/
Band 2	18900	10	QPSK	50	0	max	AMR	WB	6.6	8N	13.93	/	/	/
Band 2	18900	10	QPSK	50	0	max	AMR	WB	12.65	8N	14.09	/	/	/

 Table 6.3.1-2: the **Radio Configuration** investigating results of **VoLTE** IMS call

Band	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Volume Level	Code	NB/WB	Bit Rate	2N/8N	Conv. Gain	FR	Min PN-SDNR	
									[kbps]	[N]	[dB]		[Hz]	[dB]
Band 2	18900	10	QPSK	1	0	max	EVS	NB	13.2	8N	14.82	PASS	500	21.71
Band 2	18900	10	QPSK	1	49	max	EVS	NB	13.2	8N	14.63	PASS	800	23.59
Band 2	18900	10	16QAM	1	0	max	EVS	NB	13.2	8N	14.60	PASS	800	22.10
Band 2	18900	10	16QAM	1	49	max	EVS	NB	13.2	8N	14.62	PASS	800	22.44
Band 2	18900	10	16QAM	50	0	max	EVS	NB	13.2	8N	14.62	PASS	800	24.34
Band 2	18900	20	QPSK	100	0	max	EVS	NB	13.2	8N	14.53	PASS	800	23.56
Band 2	18900	20	QPSK	1	0	max	EVS	NB	13.2	8N	14.48	PASS	800	22.59
Band 2	18900	20	16QAM	1	0	max	EVS	NB	13.2	8N	14.55	PASS	800	23.32
Band 2	18900	15	QPSK	1	0	max	EVS	NB	13.2	8N	14.47	PASS	500	23.78
Band 2	18900	15	16QAM	1	0	max	EVS	NB	13.2	8N	14.44	PASS	800	24.02
Band 2	18900	5	QPSK	1	0	max	EVS	NB	13.2	8N	14.57	PASS	800	23.11
Band 2	18900	5	16QAM	1	0	max	EVS	NB	13.2	8N	14.41	PASS	800	23.95
Band 2	18900	10	QPSK	1	0	max	AMR	NB	4.75	2N	10.63	/	/	/
Band 2	18900	10	QPSK	1	49	max	AMR	NB	4.75	2N	10.68	/	/	/
Band 2	18900	10	16QAM	1	0	max	AMR	NB	4.75	2N	10.68	/	/	/
Band 2	18900	10	16QAM	1	49	max	AMR	NB	4.75	2N	10.44	/	/	/
Band 2	18900	10	16QAM	50	0	max	AMR	NB	4.75	2N	10.60	/	/	/
Band 2	18900	20	QPSK	100	0	max	AMR	NB	4.75	2N	10.56	/	/	/

Band 2	18900	20	QPSK	1	0	max	AMR	NB	4.75	2N	10.51	/	/	/
Band 2	18900	20	16QAM	1	0	max	AMR	NB	4.75	2N	10.39	/	/	/
Band 2	18900	15	QPSK	1	0	max	AMR	NB	4.75	2N	10.52	/	/	/
Band 2	18900	15	16QAM	1	0	max	AMR	NB	4.75	2N	10.51	/	/	/
Band 2	18900	5	QPSK	1	0	max	AMR	NB	4.75	2N	10.52	/	/	/
Band 2	18900	5	16QAM	1	0	max	AMR	NB	4.75	2N	10.57	/	/	/

 Table 6.3.1-3: the **LTE Band** investigating results of **VoLTE** IMS call

Band	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	Volume Level	Code	NB / WB	Bit Rate	2N/8N	Conv. Gain	FR	Min PN-SDNR	
									[kbps]	[N]	[dB]		[Hz]	[dB]
Band B4	20175	10	QPSK	1	0	max	EVS	NB	13.2	8N	14.60	PASS	800	24.92
Band B5	20525	10	QPSK	1	0	max	EVS	NB	13.2	8N	14.42	PASS	800	23.54
Band B12	23095	10	QPSK	1	0	max	EVS	NB	13.2	8N	14.37	PASS	800	22.95
Band B13	23230	10	QPSK	1	0	max	EVS	NB	13.2	8N	14.47	PASS	800	24.76
Band B66	132322	10	QPSK	1	0	max	EVS	NB	13.2	8N	14.30	PASS	800	23.73
Band B4	20175	10	QPSK	50	0	max	AMR	NB	4.75	2N	10.56	/	/	/
Band B5	20525	10	QPSK	50	0	max	AMR	NB	4.75	2N	10.50	/	/	/
Band B12	23095	10	QPSK	50	0	max	AMR	NB	4.75	2N	10.53	/	/	/
Band B13	23230	10	QPSK	50	0	max	AMR	NB	4.75	2N	10.52	/	/	/
Band B66	132322	10	QPSK	50	0	max	AMR	NB	4.75	2N	10.42	/	/	/

6.3.2 VoWiFi IMS call investigation

 Table 6.3.2: the investigating results of **VoWiFi** IMS call

Mode	Channel	Modulation	Data Rate	Volume Level	Codec	NB/WB	Bit Rate	2N/8N	Conv. Gain	FR	Min PN-SDNR	
			[Mbps]				[kbps]	[N]	[dB]		[Hz]	[dB]
802.11g	6	DSSS	1	max	EVS	NB	13.2	8N	14.89	PASS	800	23.13
802.11g	6	DSSS	2	max	EVS	NB	13.2	8N	14.82	PASS	800	22.97
802.11g	6	CCK	5.5	max	EVS	NB	13.2	8N	14.97	PASS	800	24.18
802.11g	6	CCK	11	max	EVS	NB	13.2	8N	14.71	PASS	800	24.16
802.11ac	1	BPSK	6	max	EVS	NB	13.2	8N	14.87	PASS	1250	30.88
802.11ac	1	BPSK	9	max	EVS	NB	13.2	8N	14.69	PASS	3150	30.94
802.11ac	1	QPSK	12	max	EVS	NB	13.2	8N	14.66	PASS	400	29.22
802.11ac	1	QPSK	18	max	EVS	NB	13.2	8N	14.55	PASS	1250	30.48
802.11ac	1	16-QAM	24	max	EVS	NB	13.2	8N	14.69	PASS	1250	29.96
802.11ac	1	16-QAM	36	max	EVS	NB	13.2	8N	14.57	PASS	1250	29.44
802.11ac	1	64-QAM	48	max	EVS	NB	13.2	8N	14.85	PASS	1250	31.14
802.11ac	1	64-QAM	54	max	EVS	NB	13.2	8N	14.45	PASS	1250	30.71
802.11g	6	DSSS	1	max	AMR	NB	4.75	2N	11.17	/	/	/
802.11g	6	DSSS	2	max	AMR	NB	4.75	2N	10.87	/	/	/
802.11g	6	CCK	5.5	max	AMR	NB	4.75	2N	11.01	/	/	/
802.11g	6	CCK	11	max	AMR	NB	4.75	2N	11.07	/	/	/
802.11ac	1	BPSK	6	max	AMR	NB	4.75	2N	11.30	/	/	/
802.11ac	1	BPSK	9	max	AMR	NB	4.75	2N	11.14	/	/	/
802.11ac	1	QPSK	12	max	AMR	NB	4.75	2N	11.00	/	/	/
802.11ac	1	QPSK	18	max	AMR	NB	4.75	2N	11.05	/	/	/
802.11ac	1	16-QAM	24	max	AMR	NB	4.75	2N	11.21	/	/	/
802.11ac	1	16-QAM	36	max	AMR	NB	4.75	2N	11.17	/	/	/
802.11ac	1	64-QAM	48	max	AMR	NB	4.75	2N	11.16	/	/	/
802.11ac	1	64-QAM	54	max	AMR	NB	4.75	2N	11.03	/	/	/

6.3.3 GSM call investigation

Table 6.3.3: the investigating results of **GSM** call

Band	Channel	Volume Level	Codec	Voice bandwidth	Bit Rate	2N/8N	Conv. Gain	FR	Min PN-SDNR	
					[kbps]	[N]	[dB]		[Hz]	[dB]
GSM850	162	max	EFR	NB	/	2N	10.94	/	/	/
GSM850	162	max	EFR	NB	/	8N	14.91	/	/	/
GSM1900	600	max	EFR	NB	/	2N	10.89	/	/	/
GSM1900	600	max	EFR	NB	/	8N	14.94	/	/	/

6.3.4 WCDMA call investigation

Table6.3.4: the investigating results of **WCDMA** call

air interface	Band	Channel	Volume Level	Code	Voice bandwidth	Bit Rate	2N/8N	Conv. Gain	FR	Min PN-SDNR	
						[kbps]	[N]	[dB]		[Hz]	[dB]
WCDMA	Band2	9262	max	AMR	NB	4.75	2N	10.45	/	/	/
WCDMA	Band2	9262	max	AMR	NB	12.2	2N	11.39	/	/	/
WCDMA	Band2	9262	max	AMR	NB	4.75	8N	13.92	/	/	/
WCDMA	Band2	9262	max	AMR	WB	6.6	2N	10.62	/	/	/
WCDMA	Band2	9262	max	AMR	WB	12.65	2N	11.14	/	/	/
WCDMA	Band2	9262	max	AMR	WB	6.6	8N	13.87	/	/	/
WCDMA	Band4	1312	max	AMR	NB	4.75	2N	10.56	/	/	/
WCDMA	Band5	4132	max	AMR	NB	4.75	2N	10.70	/	/	/

7. Test Facilities Utilized

No	Name	Type	SN	Manufacturer	Cal.Due Date
1	Measurement Frontend	Labcore	77000136	HEAD acoustics GmbH	2025-11-29
2	HEAD measurement system	HMS II.3	12306194 (torso137 40182)	HEAD acoustics GmbH	2024-10-25
3	Universal communication tester	CMW500	170430	Rohde&Schwarz	2024-08-03
4	Universal communication tester	CMX500	101626	Rohde&Schwarz	2024-08-05
5	Acoustic chamber	4.70 m×4.30 m×2.10 m	None	Ruisen	2026-10-26
Software					
Name		Version			
ACQUA		V 5.1.200			

END OF REPORT BODY

ANNEX A: EUT photograph



Pic A- 1 Mobile Phone(top)



Pic A- 2 Mobile Phone(back)

ANNEX B: EUT parameters

Disclaimer: The bands and codecs of EUT provided by the client may affect the validity of the measurement results in this report, and the client shall bear the impact and consequences arising therefrom.

General Information:

Description	Smart Phone
Model name/HVIN	B160V
Marketing Name/PMN	/
Brand name	BLU
FCC ID	YHLBLUB160V
Extreme Temperature	0~45°C

Supported Bands:

UMTS Frequency Band(s)	Band 2/4/5
GSM Frequency Band(s)	GSM 850/1900
E-UTRA Frequency Band(s)	Band 02/04/05/12/13/66
Wi-Fi Frequency Band(s)	2.4G

Supported Codecs:

UMTS Audio Codec(s)	AMR NB/AMR WB
GSM Audio Codec (s)	EFR/AMR NB/AMR WB
E-UTRA Audio Codec(s)	AMR NB/AMR WB/EVS NB/EVS WB
Wi-Fi Audio Codec(s)	AMR NB/AMR WB/EVS NB/EVS WB
OTT	Google Meet

ANNEX C: Test Layout

Artificial Ear Type		3.3
Mounting Force [N]		2 and 8
Center Fork Offset [°]		0
Volume Level		7/7(1-7)
Angle settings		
Xe [°]	Ye [°]	Ze[°]
0	0	5

NOTE: The handset shall be placed in either the standard test position as specified in IEEE Std 269 or a recommended test position specified by the manufacturer that complies with the recommended test position requirements in IEEE Std 269.




Pic C-1: Handset Positioner (HHPIII) with mounted EUT mobile phone


ANNEX D: The Worst-case Measurement Data of The Chosen Codec of Telephony Call

SMD	Status	Single Value Description	Single Value	Object
5.1 Receive Volume Control Performance 8N QPSK, RB Size=1, RB Offset=0; Table-2; Table-7	Done	Speech Level [dB[SPL]]	84.82	23T04Z80629 VoLTE EVS
5.1.1 -1 Conversation Gain 8N QPSK, RB Size=1, RB Offset=0; Table-2; Table-7	Ok	Calculated Value [dB]	14.82	23T04Z80629 VoLTE EVS
Receive path - distortion and noise 400Hz WB&NB QPSK, RB Size=1, RB Offset=0; Table-2; Table-7	Done	Distortion (Noise) [dB], 0.0 dB	25.91	23T04Z80629 VoLTE EVS
Receive path - distortion and noise 500Hz WB&NB QPSK, RB Size=1, RB Offset=0; Table-2; Table-7	Done	Distortion (Noise) [dB], 0.0 dB	21.71	23T04Z80629 VoLTE EVS
Receive path - distortion and noise 630Hz WB&NB QPSK, RB Size=1, RB Offset=0; Table-2; Table-7	Done	Distortion (Noise) [dB], 0.0 dB	25.35	23T04Z80629 VoLTE EVS
Receive path - distortion and noise 800Hz WB&NB QPSK, RB Size=1, RB Offset=0; Table-2; Table-7	Done	Distortion (Noise) [dB], 0.0 dB	24.20	23T04Z80629 VoLTE EVS
Receive path - distortion and noise 1000Hz WB&NB QPSK, RB Size=1, RB Offset=0; Table-2; Table-7	Done	Distortion (Noise) [dB], 0.0 dB	32.48	23T04Z80629 VoLTE EVS
Receive path - distortion and noise 1250Hz WB&NB QPSK, RB Size=1, RB Offset=0; Table-2; Table-7	Done	Distortion (Noise) [dB], 0.0 dB	29.92	23T04Z80629 VoLTE EVS
Receive path - distortion and noise 1600Hz WB&NB	Done	Distortion (Noise)	35.45	23T04Z80629 VoLTE EVS

QPSK, RB Size=1, RB Offset=0; Table-2; Table-7		[dB], 0.0 dB		
Receive path - distortion and noise 2000Hz WB&NB QPSK, RB Size=1, RB Offset=0; Table-2; Table-7	Done	Distortion (Noise) [dB], 0.0 dB	35.47	23T04Z80629 VoLTE EVS
Receive path - distortion and noise 2500Hz WB&NB QPSK, RB Size=1, RB Offset=0; Table-2; Table-7	Done	Distortion (Noise) [dB], 0.0 dB	32.36	23T04Z80629 VoLTE EVS
Receive path - distortion and noise 3150Hz WB&NB QPSK, RB Size=1, RB Offset=0; Table-2; Table-7	Done	Distortion (Noise) [dB], 0.0 dB	27.93	23T04Z80629 VoLTE EVS
5.2 Receive path – distortion and noise QPSK, RB Size=1, RB Offset=0; Table-2; Table-7	Ok			23T04Z80629 VoLTE EVS
5.3 Receive Acoustic Frequency response Performance QPSK, RB Size=1, RB Offset=0; Table-2; Table-7	Ok	Min. dist. to tolerance scheme [dB], 305.9 Hz	<p>2.44 dB at 305.9 Hz</p>	23T04Z80629 VoLTE EVS
5.1 Receive Volume Control Performance 8N Table-7	Done	Speech Level [dB[SPL]]	83.91	23T04Z80629 VoLTE EVS
5.1.1 -1 Conversation Gain 8N Table-7	Ok	Calculated Value [dB]	13.91	23T04Z80629 VoLTE EVS
Receive path - distortion and noise 250 WBonly Table-7	Done	Distortion (Noise) [dB], 0.0 dB	27.38	23T04Z80629 VoLTE EVS
Receive path - distortion and noise 315Hz WBonly Table-7	Done	Distortion (Noise) [dB], 0.0 dB	26.34	23T04Z80629 VoLTE EVS
Receive path - distortion and noise 400Hz WB&NB Table-7	Done	Distortion (Noise)	36.12	23T04Z80629 VoLTE EVS

		[dB], 0.0 dB		
Receive path - distortion and noise 500Hz WB&NB Table-7	Done	Distortion (Noise) [dB], 0.0 dB	33.46	23T04Z80629 VoLTE EVS
Receive path - distortion and noise 630Hz WB&NB Table-7	Done	Distortion (Noise) [dB], 0.0 dB	36.23	23T04Z80629 VoLTE EVS
Receive path - distortion and noise 800Hz WB&NB Table-7	Done	Distortion (Noise) [dB], 0.0 dB	36.47	23T04Z80629 VoLTE EVS
Receive path - distortion and noise 1000Hz WB&NB Table-7	Done	Distortion (Noise) [dB], 0.0 dB	33.58	23T04Z80629 VoLTE EVS
Receive path - distortion and noise 1250Hz WB&NB Table-7	Done	Distortion (Noise) [dB], 0.0 dB	31.99	23T04Z80629 VoLTE EVS
Receive path - distortion and noise 1600Hz WB&NB Table-7	Done	Distortion (Noise) [dB], 0.0 dB	38.29	23T04Z80629 VoLTE EVS
Receive path - distortion and noise 2000Hz WB&NB Table-7	Done	Distortion (Noise) [dB], 0.0 dB	38.41	23T04Z80629 VoLTE EVS
Receive path - distortion and noise 2500Hz WB&NB Table-7	Done	Distortion (Noise) [dB], 0.0 dB	34.40	23T04Z80629 VoLTE EVS
Receive path - distortion and noise 3150Hz WB&NB Table-7	Done	Distortion (Noise) [dB], 0.0 dB	33.02	23T04Z80629 VoLTE EVS
Receive path - distortion and noise 4000Hz WOnly Table-7	Done	Distortion (Noise) [dB], 0.0 dB	32.98	23T04Z80629 VoLTE EVS

Receive path - distortion and noise 5000Hz WBonly Table-7	Done	Distortion (Noise) [dB], 0.0 dB	34.49	23T04Z80629 VoLTE EVS
5.2 Receive path – distortion and noise Table-7	Ok			23T04Z80629 VoLTE EVS
5.3 Receive Acoustic Frequency response Performance Table-7	Ok	Min. dist. to tolerance scheme [dB], 205.7 Hz	 <p>2.75 dB at 205.7 Hz</p>	23T04Z80629 VoLTE EVS
5.1 Receive Volume Control Performance 2N Table-7	Done	Speech Level [dB[SPL]]	80.90	23T04Z80629 VoLTE EVS
5.1.1 -1 Conversation Gain 2N Table-7	Ok	Calculated Value [dB]	10.90	23T04Z80629 VoLTE EVS
Receive path - distortion and noise 400Hz WB&NB Table-7	Done	Distortion (Noise) [dB], 0.0 dB	26.88	23T04Z80629 VoLTE EVS
Receive path - distortion and noise 500Hz WB&NB Table-7	Done	Distortion (Noise) [dB], 0.0 dB	26.41	23T04Z80629 VoLTE EVS
Receive path - distortion and noise 630Hz WB&NB Table-7	Done	Distortion (Noise) [dB], 0.0 dB	25.40	23T04Z80629 VoLTE EVS
Receive path - distortion and noise 800Hz WB&NB Table-7	Done	Distortion (Noise) [dB], 0.0 dB	23.46	23T04Z80629 VoLTE EVS
Receive path - distortion and noise 1000Hz WB&NB Table-7	Done	Distortion (Noise) [dB], 0.0 dB	35.27	23T04Z80629 VoLTE EVS

Receive path - distortion and noise 1250Hz WB&NB Table-7	Done	Distortion (Noise) [dB], 0.0 dB	30.09	23T04Z80629 VoLTE EVS
Receive path - distortion and noise 1600Hz WB&NB Table-7	Done	Distortion (Noise) [dB], 0.0 dB	35.26	23T04Z80629 VoLTE EVS
Receive path - distortion and noise 2000Hz WB&NB Table-7	Done	Distortion (Noise) [dB], 0.0 dB	34.86	23T04Z80629 VoLTE EVS
Receive path - distortion and noise 2500Hz WB&NB Table-7	Done	Distortion (Noise) [dB], 0.0 dB	29.99	23T04Z80629 VoLTE EVS
Receive path - distortion and noise 3150Hz WB&NB Table-7	Done	Distortion (Noise) [dB], 0.0 dB	29.59	23T04Z80629 VoLTE EVS
5.2 Receive path – distortion and noise Table-7	Ok			23T04Z80629 VoLTE EVS
5.3 Receive Acoustic Frequency response Performance Table-7	Ok	Min. dist. to tolerance scheme [dB], 305.9 Hz	 <p>3.46 dB at 305.9 Hz</p>	23T04Z80629 VoLTE EVS
5.1 Receive Volume Control Performance 2N Table-7	Done	Speech Level [dB[SPL]]	80.52	23T04Z80629 VoLTE EVS
5.1.1 -1 Conversation Gain 2N Table-7	Ok	Calculated Value [dB]	10.52	23T04Z80629 VoLTE EVS
Receive path - distortion and noise 250 WBonly Table-7	Done	Distortion (Noise) [dB], 0.0 dB	28.26	23T04Z80629 VoLTE EVS


Receive path - distortion and noise 315Hz WBonly Table-7	Done	Distortion (Noise) [dB], 0.0 dB	28.33	23T04Z80629 VoLTE EVS
Receive path - distortion and noise 400Hz WBonly Table-7	Done	Distortion (Noise) [dB], 0.0 dB	33.84	23T04Z80629 VoLTE EVS
Receive path - distortion and noise 400Hz WB&NB Table-7	Done	Distortion (Noise) [dB], 0.0 dB	36.34	23T04Z80629 VoLTE EVS
Receive path - distortion and noise 500Hz WB&NB Table-7	Done	Distortion (Noise) [dB], 0.0 dB	35.92	23T04Z80629 VoLTE EVS
Receive path - distortion and noise 630Hz WB&NB Table-7	Done	Distortion (Noise) [dB], 0.0 dB	36.77	23T04Z80629 VoLTE EVS
Receive path - distortion and noise 800Hz WB&NB Table-7	Done	Distortion (Noise) [dB], 0.0 dB	37.35	23T04Z80629 VoLTE EVS
Receive path - distortion and noise 1000Hz WB&NB Table-7	Done	Distortion (Noise) [dB], 0.0 dB	35.28	23T04Z80629 VoLTE EVS
Receive path - distortion and noise 1250Hz WB&NB Table-7	Done	Distortion (Noise) [dB], 0.0 dB	32.08	23T04Z80629 VoLTE EVS
Receive path - distortion and noise 1600Hz WB&NB Table-7	Done	Distortion (Noise) [dB], 0.0 dB	37.55	23T04Z80629 VoLTE EVS
Receive path - distortion and noise 2000Hz WB&NB Table-7	Done	Distortion (Noise) [dB], 0.0 dB	37.48	23T04Z80629 VoLTE EVS

Receive path - distortion and noise 2500Hz WB&NB Table-7	Done	Distortion (Noise) [dB], 0.0 dB	35.17	23T04Z80629 VoLTE EVS
Receive path - distortion and noise 3150Hz WB&NB Table-7	Done	Distortion (Noise) [dB], 0.0 dB	33.13	23T04Z80629 VoLTE EVS
Receive path - distortion and noise 5000Hz WOnly Table-7	Done	Distortion (Noise) [dB], 0.0 dB	33.09	23T04Z80629 VoLTE EVS
5.2 Receive path – distortion and noise Table-7	Ok			23T04Z80629 VoLTE EVS
5.3 Receive Acoustic Frequency response Performance Table-7	Ok	Min. dist. to tolerance scheme [dB], 205.7 Hz	<p>1.64 dB at 205.7 Hz</p>	23T04Z80629 VoLTE EVS

ANNEX E: The Worst-case Measurement Data of Other Codecs of Telephony Call

SMD	Status	Single Value Description	Single Value	Object
5.1 Receive Volume Control Performance 8N 4.75kbps; Table-1	Done	Speech Level [dB[SPL]]	84.05	23T04Z80629 VoLTE AMR
5.1.1 -1 Conversation Gain 8N 4.75kbps; Table-1	Ok	Calculated Value [dB]	14.05	23T04Z80629 VoLTE AMR
5.1 Receive Volume Control Performance 8N 6.6kbps; Table-1	Done	Speech Level [dB[SPL]]	83.93	23T04Z80629 VoLTE AMR
5.1.1 -1 Conversation Gain 8N 6.6kbps; Table-1	Ok	Calculated Value [dB]	13.93	23T04Z80629 VoLTE AMR
5.1 Receive Volume Control Performance 2N 4.75kbps; Table-1	Done	Speech Level [dB[SPL]]	80.32	23T04Z80629 VoLTE AMR
5.1.1 -1 Conversation Gain 2N 4.75kbps; Table-1	Ok	Calculated Value [dB]	10.32	23T04Z80629 VoLTE AMR
5.1 Receive Volume Control Performance 2N 6.6kbps; Table-1	Done	Speech Level [dB[SPL]]	80.39	23T04Z80629 VoLTE AMR
5.1.1 -1 Conversation Gain 2N 6.6kbps; Table-1	Ok	Calculated Value [dB]	10.39	23T04Z80629 VoLTE AMR
5.1 Receive Volume Control Performance 8N 850	Done	Speech Level [dB[SPL]]	84.91	23T04Z80629 GSM
5.1.1 -1 Conversation Gain 8N 850	Ok	Calculated Value [dB]	14.91	23T04Z80629 GSM
5.1 Receive Volume Control Performance 2N 850	Done	Speech Level [dB[SPL]]	80.94	23T04Z80629 GSM
5.1.1 -1 Conversation Gain 2N 850	Ok	Calculated Value [dB]	10.94	23T04Z80629 GSM

ANNEX F: FREQUENCY RESPONSE USED DF and 1/12 OCTAVE



The screenshot shows a software configuration window for acoustic frequency response measurement. The window is titled "5.3 Receive Acoustic Frequency response Performance". It is divided into several sections:

- Title:** 5.3 Receive Acoustic Frequency response Performance
- Mode:** Do measurement
- File to analyse:** (empty field with a browse button)
- Signal:**
 - Source:** ieee_male_dual_wb, Adj. -90 dB; -4 dB
- Measurement:**
 - Direction:** Out 2 -> In 2
 - Run time info:** No
 - Pre measure info:** No
 - Filter:** FIR
- Analysis:**
 - Reference:** rcv_wb_ref1 (ext. created)
 - Time range:** 250.0..10450.0 ms
 - Transformation:** 12th octave, Hanning, FFT:16384, OV:75%
 - Tolerance scheme:** wb_fr_tol, adj. to upper, 100..8000 Hz
 - Calculate value:** No
- Result:**
 - Check min. dist.:** > 0.0 dB
 - Representation:** -5..5 , 100..8000 Hz, -50..50 dB
- Special features:**
 - Special features:** Comp.delay, Store to rcv_fr_wb.fft

Filter

FF/DF Average

Channel 1: Channel 2:

Filter measured signal

Use IIR filter 1: Mid./edge frequency: Hz

Kind: Quality:

Order: Amplification: dB

Type:

Filter 2

Use IIR filter 2: Mid./edge frequency: Hz

Kind: Quality:

Order: Amplification: dB

Type:

Filter 3

Use IIR filter 3: Mid./edge frequency: Hz

Kind: Quality:

Order: Amplification: dB

Type:

Filter 4

Use IIR filter 4: Mid./edge frequency: Hz

Kind: Quality:

Order: Amplification: dB

Type:

IIR Filter combination


Filter combination:

FIR Filter


Use FIR Filter: FIR filter: ...

OK

ANNEX G: HATS CERTIFICATE



ANNEX H: ACOUSTIC CHAMBER CERTIFICATE




中国计量科学研究院

证书编号 LSsx2021-19386

校准结果

二、背景噪声校准结果

正常情况下，消声室的 A 计权背景噪声为 14 dB，其 1/3 倍频频谱见图 2。



Autospectrum(zb) - Input
Working : Input ; Input : CPB Analyzer

图 2 背景噪声频谱图

声压级校准结果不确定度： $U=0.6\text{ dB } (k=2)$

-----以下空白-----

说明：
根据校准规范 JJF 1147-2006 的规定，通常情况下 60 个月校准一次。

声明：

1. 我院仅对加盖“中国计量科学研究院校准专用章”的完整证书负责。
2. 本证书的校准结果仅对本次所校准的计量器具有效。

校准员： 郑云山 核验员： 牛萍

2019-jz-R0520

第15页共15页

ANNEX I: Accreditation Certificate



Accredited Laboratory

A2LA has accredited

TELECOMMUNICATION TECHNOLOGY LABS, CAICT

Beijing, People's Republic of China

for technical competence in the field of

Electrical Testing

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 *General requirements for the competence of testing and calibration laboratories*. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated April 2017).



Presented this 26th day of June 2023.

Mr. Trace McInturf, Vice President, Accreditation Services
For the Accreditation Council
Certificate Number 7049.01
Valid to July 31, 2024

For the tests to which this accreditation applies, please refer to the laboratory's Electrical Scope of Accreditation.

END OF REPORT