



TEST REPORT

APPLICANT : BLU Products, Inc.
PRODUCT NAME : Smart Phone
MODEL NAME : G53
BRAND NAME : BLU
FCC ID : YHLBLUG53W851
STANDARD(S) : 47 CFR Part 2
: 47 CFR Part 90, Subpart S
RECEIPT DATE : 2023-10-20
TEST DATE : 2023-10-27 to 2023-11-17
ISSUE DATE : 2023-12-04



Edited by: Peng Mi
Peng Mi (Rapporteur)
Approved by: Shen Junsheng
Shen Junsheng (Supervisor)

NOTE: This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.





DIRECTORY

- 1. Technical Information 3**
- 1.1. Applicant and Manufacturer Information 3**
- 1.2. Equipment Under Test (EUT) Description 3**
- 1.3. Maximum E.R.P./E.I.R.P. and Emission Designator 4**
- 1.4. Test Standards and Results 5**
- 1.5. Environmental Conditions 6**
- 2. 47 CFR Part 2, Part 90S Requirements 7**
- 2.1. Transmitter Conducted Output Power and E.R.P./E.I.R.P. 7**
- 2.2. Occupied Bandwidth 16**
- 2.3. Frequency Stability 22**
- 2.4. Conducted Spurious Emissions 24**
- 2.5. Band Edge 27**
- 2.6. Radiated Spurious Emissions 31**
- Annex A Test Uncertainty 37**
- Annex B Testing Laboratory Information 38**

Change History		
Version	Date	Reason for change
1.0	2023-12-04	First edition



1. Technical Information

Note: Provide by applicant.

1.1. Applicant and Manufacturer Information

Applicant:	BLU Products, Inc.
Applicant Address:	8600 NW 36th Street, Suite #200 Doral, FL 33166, USA
Manufacturer:	BLU Products, Inc.
Manufacturer Address:	8600 NW 36th Street, Suite #200 Doral, FL 33166, USA

1.2. Equipment Under Test (EUT) Description

Product Name:	Smart Phone	
Sample No.:	2#	
Hardware Version:	YK310-MB-V0.1	
Software Version:	BLU_G0851_V13.0.04.04_GENERIC_22-11-2023_2030_DEBUG	
Modulation Type:	QPSK, 16QAM	
Operation Band:	Band 26	
Frequency Range:	LTE Band 26	Tx: 814MHz–824MHz
		Rx: 859MHz–869MHz
Channel Bandwidth	LTE Band 26	1.4MHz, 3MHz, 5MHz, 10MHz
Antenna Type:	PIFA Antenna	
Antenna Gain:	LTE Band 26	-1.90dBi
Accessory Information:	Battery	
	Brand Name:	BLU
	Model No.:	C966548500P
	Serial No.:	N/A
	Capacity:	5000mAh
	Rated Voltage:	3.85V
	Charge Limit:	4.4V
	Manufacturer:	Shenzhen Jiuliyuan Electronic Technology Co., Ltd.



Accessory Information:	AC Adapter		
	Brand Name:	BLU	
	Model No.:	US-TY-2001	
	Serial No.:	N/A	
	Rated Output:	5V \Rightarrow 2000A	
	Rated Input:	100-240V \sim 50/60Hz, 0.3A	
	Manufacturer:	SHENZHEN TIANYIN ELECTRONICS CO., LTD.	

Note 1: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

1.3. Maximum E.R.P./E.I.R.P. and Emission Designator

LTE Band 26	Maximum E.R.P./E.I.R.P. (W)		Emission Designator (99%OBW)	
	QPSK	16QAM	QPSK	16QAM
BW(MHz)				
10	0.077	0.060	9M00G7D	8M96W7D
5	0.077	0.059	4M50G7D	4M50W7D
3	0.077	0.060	2M69G7D	2M69W7D
1.4	0.076	0.059	1M10G7D	1M10W7D



1.4. Test Standards and Results

The objective of the report is to perform testing according to Part 2 and Part 90 for the EUT FCC ID Certification:

No	Identity	Document Title
1	47 CFR Part 2	Frequency Allocations and Radio Treaty Matters; General Rules and Regulations
2	47 CFR Part 90	Miscellaneous Wireless Communications Services

Test detailed items/section required by FCC rules and results are as below:

Section	Description	Test Date	Test Engineer	Result	Method Determination /Remark
2.1046, 90.635(b)	Transmitter Conducted Output Power and ERP/EIRP	Nov. 17, 2023	Yu Xiaoming	PASS	No deviation
90.209	Occupied Bandwidth	Nov. 17, 2023	Gan Jing	PASS	No deviation
2.1055, 90.213	Frequency Stability	Nov. 17, 2023	Gan Jing	PASS	No deviation
2.1051, 90.691	Conducted Spurious Emissions	Nov. 17, 2023	Gan Jing	PASS	No deviation
2.1051, 90.691	Band Edge	Nov. 17, 2023	Gan Jing	PASS	No deviation
2.1053, 90.691	Radiated Spurious Emissions	Nov. 03, 2023	Gao Jianrou	PASS	No deviation

Note 1: The tests were performed according to the method of measurements prescribed in KDB971168 D01 v03 and ANSI/TIA-603-E-2016.

Note 2: The path loss during the RF test is calibrated to correct the results by the offset setting in the test equipments. The ref offset 24.5dB contains two parts that cable loss 14.5dB and Attenuator 10dB.

Note 3: Additions to, deviation, or exclusions from the method shall be judged in the "method determination" column of add, deviate or exclude from the specific method shall be explained in the "Remark" of the above table.

Note 4: When the test result is a critical value, we will use the measurement uncertainty give the judgment result based on the 95% confidence intervals.



1.5. Environmental Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15-35
Relative Humidity (%):	30-60
Atmospheric Pressure (kPa):	86-106

**2.1.4. Result****Conducted Output Power**

LTE Band 26						
BW [MHz]	Modulation	RB Size	RB Offset	Average Power Low Ch. / Freq.	Average Power Middle Ch. / Freq.	Average Power High Ch. / Freq.
Channel				/	26740	/
Frequency (MHz)				/	819.0	/
10	QPSK	1	0	/	22.93	/
10	QPSK	1	25	/	22.68	/
10	QPSK	1	49	/	22.54	/
10	QPSK	25	0	/	21.64	/
10	QPSK	25	12	/	21.55	/
10	QPSK	25	25	/	21.43	/
10	QPSK	50	0	/	21.45	/
10	16QAM	1	0	/	21.81	/
10	16QAM	1	25	/	21.66	/
10	16QAM	1	49	/	21.48	/
10	16QAM	25	0	/	20.68	/
10	16QAM	25	12	/	20.51	/
10	16QAM	25	25	/	20.50	/
10	16QAM	50	0	/	20.26	/



LTE Band 26						
BW [MHz]	Modulation	RB Size	RB Offset	Average Power Low Ch. / Freq.	Average Power Middle Ch. / Freq.	Average Power High Ch. / Freq.
Channel				26715	26740	26765
Frequency (MHz)				816.5	819.0	821.5
5	QPSK	1	0	22.89	22.84	22.78
5	QPSK	1	12	22.74	22.68	22.62
5	QPSK	1	24	22.56	22.53	22.52
5	QPSK	12	0	21.66	21.65	21.63
5	QPSK	12	7	21.53	21.46	21.50
5	QPSK	12	13	21.43	21.31	21.36
5	QPSK	25	0	21.40	21.38	21.38
5	16QAM	1	0	21.78	21.71	21.67
5	16QAM	1	12	21.70	21.58	21.63
5	16QAM	1	24	21.50	21.42	21.47
5	16QAM	12	0	20.72	20.71	20.62
5	16QAM	12	7	20.50	20.43	20.46
5	16QAM	12	13	20.44	20.43	20.36
5	16QAM	25	0	20.30	20.18	20.23



LTE Band 26						
BW [MHz]	Modulation	RB Size	RB Offset	Average Power Low Ch. / Freq.	Average Power Middle Ch. / Freq.	Average Power High Ch. / Freq.
Channel				26705	26740	26775
Frequency (MHz)				815.5	819.0	822.5
3	QPSK	1	0	22.91	22.89	22.79
3	QPSK	1	8	22.68	22.59	22.58
3	QPSK	1	14	22.53	22.42	22.51
3	QPSK	8	0	21.68	21.59	21.56
3	QPSK	8	4	21.58	21.46	21.57
3	QPSK	8	7	21.45	21.37	21.37
3	QPSK	15	0	21.38	21.36	21.32
3	16QAM	1	0	21.81	21.78	21.78
3	16QAM	1	8	21.68	21.57	21.60
3	16QAM	1	14	21.46	21.40	21.41
3	16QAM	8	0	20.72	20.65	20.61
3	16QAM	8	4	20.49	20.45	20.42
3	16QAM	8	7	20.44	20.39	20.34
3	16QAM	15	0	20.29	20.19	20.21



LTE Band 26						
BW [MHz]	Modulation	RB Size	RB Offset	Average Power Low Ch. / Freq.	Average Power Middle Ch. / Freq.	Average Power High Ch. / Freq.
Channel				26697	26740	26783
Frequency (MHz)				814.7	819.0	823.3
1.4	QPSK	1	0	22.83	22.73	22.80
1.4	QPSK	1	3	22.66	22.65	22.55
1.4	QPSK	1	5	22.49	22.47	22.42
1.4	QPSK	3	0	22.09	21.98	22.00
1.4	QPSK	3	1	22.03	21.91	22.01
1.4	QPSK	3	3	22.02	21.93	22.00
1.4	QPSK	6	0	21.37	21.25	21.28
1.4	16QAM	1	0	21.76	21.69	21.66
1.4	16QAM	1	3	21.65	21.59	21.55
1.4	16QAM	1	5	21.43	21.36	21.34
1.4	16QAM	3	0	21.10	20.98	21.08
1.4	16QAM	3	1	21.01	20.90	20.93
1.4	16QAM	3	3	21.06	20.94	20.99
1.4	16QAM	6	0	20.28	20.23	20.23



Effective Radiated Power and Effective Isotropic Radiated Power

LTE Band 26				Measured E.R.P.			
BW [MHz]	Modulation	RB Size	RB Offset	Low Ch. / Freq.	Middle Ch. / Freq.	High Ch. / Freq.	
Channel				/	26740	/	
Frequency (MHz)				/	819	/	
				/	dBm	W	/
10	QPSK	1	0	/	18.88	0.077	/
10	QPSK	1	25	/	18.63	0.073	/
10	QPSK	1	49	/	18.49	0.071	/
10	QPSK	25	0	/	17.59	0.057	/
10	QPSK	25	12	/	17.50	0.056	/
10	QPSK	25	25	/	17.38	0.055	/
10	QPSK	50	0	/	17.40	0.055	/
10	16QAM	1	0	/	17.76	0.060	/
10	16QAM	1	25	/	17.61	0.058	/
10	16QAM	1	49	/	17.43	0.055	/
10	16QAM	25	0	/	16.63	0.046	/
10	16QAM	25	12	/	16.46	0.044	/
10	16QAM	25	25	/	16.45	0.044	/
10	16QAM	50	0	/	16.21	0.042	/



LTE Band 26				Measured E.R.P.					
BW [MHz]	Modulation	RB Size	RB Offset	Low Ch. / Freq.		Middle Ch. / Freq.		High Ch. / Freq.	
Channel				26715		26740		26765	
Frequency (MHz)				816.5		819.0		821.5	
				dBm	W	dBm	W	dBm	W
5	QPSK	1	0	18.84	0.077	18.79	0.076	18.73	0.075
5	QPSK	1	12	18.69	0.074	18.63	0.073	18.57	0.072
5	QPSK	1	24	18.51	0.071	18.48	0.070	18.47	0.070
5	QPSK	12	0	17.61	0.058	17.60	0.058	17.58	0.057
5	QPSK	12	7	17.48	0.056	17.41	0.055	17.45	0.056
5	QPSK	12	13	17.38	0.055	17.26	0.053	17.31	0.054
5	QPSK	25	0	17.35	0.054	17.33	0.054	17.33	0.054
5	16QAM	1	0	17.73	0.059	17.66	0.058	17.62	0.058
5	16QAM	1	12	17.65	0.058	17.53	0.057	17.58	0.057
5	16QAM	1	24	17.45	0.056	17.37	0.055	17.42	0.055
5	16QAM	12	0	16.67	0.046	16.66	0.046	16.57	0.045
5	16QAM	12	7	16.45	0.044	16.38	0.043	16.41	0.044
5	16QAM	12	13	16.39	0.044	16.38	0.043	16.31	0.043
5	16QAM	25	0	16.25	0.042	16.13	0.041	16.18	0.041



LTE Band 26				Measured E.R.P.					
BW [MHz]	Modulation	RB Size	RB Offset	Low Ch. / Freq.		Middle Ch. / Freq.		High Ch. / Freq.	
Channel				26705		26740		26775	
Frequency (MHz)				815.5		819.0		822.5	
				dBm	W	dBm	W	dBm	W
3	QPSK	1	0	18.86	0.077	18.84	0.077	18.74	0.075
3	QPSK	1	8	18.63	0.073	18.54	0.071	18.53	0.071
3	QPSK	1	14	18.48	0.070	18.37	0.069	18.46	0.070
3	QPSK	8	0	17.63	0.058	17.54	0.057	17.51	0.056
3	QPSK	8	4	17.53	0.057	17.41	0.055	17.52	0.056
3	QPSK	8	7	17.40	0.055	17.32	0.054	17.32	0.054
3	QPSK	15	0	17.33	0.054	17.31	0.054	17.27	0.053
3	16QAM	1	0	17.76	0.060	17.73	0.059	17.73	0.059
3	16QAM	1	8	17.63	0.058	17.52	0.056	17.55	0.057
3	16QAM	1	14	17.41	0.055	17.35	0.054	17.36	0.054
3	16QAM	8	0	16.67	0.046	16.60	0.046	16.56	0.045
3	16QAM	8	4	16.44	0.044	16.40	0.044	16.37	0.043
3	16QAM	8	7	16.39	0.044	16.34	0.043	16.29	0.043
3	16QAM	15	0	16.24	0.042	16.14	0.041	16.16	0.041




LTE Band 26				Measured E.R.P.					
BW [MHz]	Modulation	RB Size	RB Offset	Low Ch. / Freq.		Middle Ch. / Freq.		High Ch. / Freq.	
Channel				26697		26740		26783	
Frequency (MHz)				814.7		819.0		823.3	
				dBm	W	dBm	W	dBm	W
1.4	QPSK	1	0	18.78	0.076	18.68	0.074	18.75	0.075
1.4	QPSK	1	3	18.61	0.073	18.60	0.072	18.50	0.071
1.4	QPSK	1	5	18.44	0.070	18.42	0.070	18.37	0.069
1.4	QPSK	3	0	18.04	0.064	17.93	0.062	17.95	0.062
1.4	QPSK	3	1	17.98	0.063	17.86	0.061	17.96	0.063
1.4	QPSK	3	3	17.97	0.063	17.88	0.061	17.95	0.062
1.4	QPSK	6	0	17.32	0.054	17.20	0.052	17.23	0.053
1.4	16QAM	1	0	17.71	0.059	17.64	0.058	17.61	0.058
1.4	16QAM	1	3	17.60	0.058	17.54	0.057	17.50	0.056
1.4	16QAM	1	5	17.38	0.055	17.31	0.054	17.29	0.054
1.4	16QAM	3	0	17.05	0.051	16.93	0.049	17.03	0.050
1.4	16QAM	3	1	16.96	0.050	16.85	0.048	16.88	0.049
1.4	16QAM	3	3	17.01	0.050	16.89	0.049	16.94	0.049
1.4	16QAM	6	0	16.23	0.042	16.18	0.041	16.18	0.041

2.2. Occupied Bandwidth

2.2.1. Requirement

According to FCC section 2.1049, the occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission. Occupied bandwidth is also known as the 99% emission bandwidth.

2.2.2. Test Description



The EUT is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power. A call is established between the EUT and the SS.


2.2.3. Test procedure

KDB 971168 D01v03 Section 4.1 and ANSI/TIA-603-E-2016.




2.2.4. Test Result


LTE Band 26				
BW(MHz)	Channel Level	Modulation	99% BW(MHz)	26dB BW(MHz)
1.4	Low	QPSK	1.10	1.31
	Low	16QAM	1.10	1.30
	Mid	QPSK	1.09	1.29
	Mid	16QAM	1.10	1.29
	High	QPSK	1.09	1.29
	High	16QAM	1.10	1.28
3	Low	QPSK	2.69	2.92
	Low	16QAM	2.69	2.93
	Mid	QPSK	2.69	2.91
	Mid	16QAM	2.69	2.92
	High	QPSK	2.69	2.92
	High	16QAM	2.69	2.93
5	Low	QPSK	4.50	4.93
	Low	16QAM	4.50	4.88
	Mid	QPSK	4.50	4.91
	Mid	16QAM	4.49	4.90
	High	QPSK	4.50	4.92
	High	16QAM	4.50	5.00
10	Low	QPSK	9.00	9.75
	Low	16QAM	8.96	9.73
	Mid	QPSK	8.98	9.77
	Mid	16QAM	8.96	9.73
	High	QPSK	9.00	9.72
	High	16QAM	8.95	9.70




B26 Part90 / 1.4MHz / QPSK/ Low CH




B26 Part90 / 1.4MHz / 16QAM/ Low CH




B26 Part90 / 1.4MHz / QPSK/ Mid CH




B26 Part90 / 1.4MHz / 16QAM/ Mid CH




B26 Part90 / 1.4MHz / QPSK/ High CH




B26 Part90 / 1.4MHz / 16QAM/ High CH




B26 Part90 / 3MHz / QPSK/ Low CH




B26 Part90 / 3MHz / 16QAM/ Low CH




B26 Part90 / 3MHz / QPSK/ Mid CH




B26 Part90 / 3MHz / 16QAM/ Mid CH



B26 Part90 / 3MHz / QPSK/ High CH




B26 Part90 / 3MHz / 16QAM/ High CH




B26 Part90 / 5MHz / QPSK/ Low CH




B26 Part90 / 5MHz / 16QAM/ Low CH




B26 Part90 / 5MHz / QPSK/ Mid CH




B26 Part90 / 5MHz / 16QAM/ Mid CH




B26 Part90 / 5MHz / QPSK/ High CH



B26 Part90 / 5MHz / 16QAM/ High CH



B26 Part90 / 10MHz / QPSK/ Low CH




B26 Part90 / 10MHz / 16QAM/ Low CH




B26 Part90 / 10MHz / QPSK/ Mid CH



B26 Part90 / 10MHz / 16QAM/ Mid CH



B26 Part90 / 10MHz / QPSK/ High CH



B26 Part90 / 10MHz / 16QAM/ High CH

2.3. Frequency Stability


2.3.1. Requirement

According to FCC section 2.1055 & 90.213, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. According to FCC section 2.1055, the test conditions are:

- (a) The temperature is varied from -30°C to $+50^{\circ}\text{C}$ at intervals of not more than 10°C .
- (b) For hand carried battery powered equipment, the primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacture. The supply voltage shall be measured at the input to the cable normally provided with the equipment, or at the power supply terminals if cables are not normally provided.

Note: The operating temperature of EUT is from -10°C to 55°C , which are specified by the applicant.

2.3.2. Test Description



The EUT which is powered by the DC Power Supply directly, is located in the Temperature Chamber. The EUT is commanded by the System Simulator (SS) to operate at the maximum output power. A call is established between the EUT and the SS via a Common Antenna.

2.3.3. Test procedure

KDB 971168 D01v03 Section 9.0 and ANSI/TIA-603-E-2016.

**2.3.4. Test Result**

The nominal, highest and lowest extreme voltages are separately 3.85V, 4.40V and 3.60V, which are specified by the applicant; the normal temperature here used is 20°C.


LTE Band 26, QPSK, Channel 26740, Frequency 819MHz					
Limit =±2.5ppm					
Voltage (%)	Power (VDC)	Temp (°C)	Fre. Dev. (Hz)	Deviation (ppm)	Result
Normal	3.85	+20(Ref)	18	0.022	PASS
Normal		-10	-3	-0.004	
Normal		0	18	0.022	
Normal		+10	-18	-0.022	
Normal		+20	-9	-0.011	
Normal		+30	19	0.023	
Normal		+40	16	0.020	
Normal		+50	16	0.020	
Normal		+55	14	0.017	
High		4.40	+20	17	
BATT.ENDPOINT	3.60	+20	1	0.001	

2.4. Conducted Spurious Emissions

2.4.1. Requirement

According to FCC section 2.1051, the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43+10*\log(P)$ dB. This calculated to be -13dBm.

2.4.2. Test Description



The EUT is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power. A call is established between the EUT and the SS.


2.4.3. Test procedure

KDB 971168 D01v03 Section 6.0 and ANSI/TIA-603-E-2016.




2.4.4. Test Result







B26 Part90 / 5MHz / Low CH / QPSK




B26 Part90 / 5MHz / Mid CH / QPSK




B26 Part90 / 5MHz / High CH / QPSK



B26 Part90 / 10MHz / Low CH / QPSK



B26 Part90 / 10MHz / Mid CH / QPSK



B26 Part90 / 10MHz / High CH / QPSK


2.5. Band Edge

2.5.1. Requirement

Band26

According to FCC section 90.961(a), the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

2.5.2. Test Description




The EUT is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power. A call is established between the EUT and the SS.

2.5.3. Test procedure

KDB 971168 D01v03 Section 6.0 and ANSI/TIA-603-E-2016.




2.5.4. Test Result




B26 Part90 / 1.4MHz / Low CH / QPSK / 1 RB




B26 Part90 / 1.4MHz / Low CH / QPSK / FULL RB




B26 Part90 / 1.4MHz / High CH / QPSK / 1 RB



B26 Part90 / 1.4MHz / High CH / QPSK / FULL RB




B26 Part90 / 1.4MHz / Low CH / QPSK / 1 RB




B26 Part90 / 1.4MHz / Low CH / QPSK / FULL RB




B26 Part90 / 3MHz / Low CH / QPSK / 1 RB




B26 Part90 / 3MHz / Low CH / QPSK / FULL RB




B26 Part90 / 3MHz / High CH / QPSK / 1 RB




B26 Part90 / 3MHz / High CH / QPSK / FULL RB



B26 Part90 / 5MHz / Low CH / QPSK / 1 RB




B26 Part90 / 5MHz / Low CH / QPSK / FULL RB




B26 Part90 / 5MHz / High CH / QPSK / 1 RB


B26 Part90 / 5MHz / High CH / QPSK / FULL RB




B26 Part90 / 10MHz / Low CH / QPSK / 1 RB



B26 Part90 / 10MHz / Low CH / QPSK / FULL RB



B26 Part90 / 10MHz / High CH / QPSK / 1 RB




B26 Part90 / 10MHz / High CH / QPSK / FULL RB

2.6. Radiated Spurious Emissions


2.6.1. Requirement

According to FCC section 2.1051, the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43+10*\log(P)$ dB. This calculated to be -13dBm.

2.6.2. Test Description



(For the test frequency from 30MHz to 1GHz)



(For the test frequency above 1GHz)

The EUT is located in a 3m Full-Anechoic Chamber, the cable loss, air loss and so on of the site as factors are pre-calibrated using the "Substitution" method, and calculated to correct the reading. A call is established between the EUT and the SS via a Common Antenna. The EUT is commanded by the SS to operate at the maximum and minimum output power, and only the test result of the maximum output power was recorded.

In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground and the Turn Table is actuated to turn from 0° to 360° to determine the maximum value of the radiated power. The emission levels at both horizontal and vertical polarizations should be tested. The Filters consists of Notch Filters and High Pass Filter.

Note: when doing measurements above 1GHz, the EUT has been within the 3dB cone width of the horn antenna during horizontal antenna.

2.6.3. Test procedure

KDB 971168 D01v03 Section 5.8 and ANSI/TIA-603-E-2016.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements.

For measurements above 1GHz the resolution bandwidth is set to 1MHz, the video band width is set to 3MHz for peak measurements.



2.6.4. Test Result

The measurement frequency range is from 30MHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. The lowest, middle and highest channels are tested to verify the out of band emissions.

The substitution corrections are obtained as described below:

$$A_{\text{SUBST}} = P_{\text{SUBST_TX}} - P_{\text{SUBST_RX}} - L_{\text{SUBST_CABLES}} + G_{\text{SUBST_TX_ANT}}$$

$$A_{\text{TOT}} = L_{\text{CABLES}} + A_{\text{SUBST}}$$

Where A_{SUBST} is the final substitution correction including receive antenna gain.

$P_{\text{SUBST_TX}}$ is signal generator level,

$P_{\text{SUBST_RX}}$ is receiver level,

$L_{\text{SUBST_CABLES}}$ is cable losses including TX cable,

$G_{\text{SUBST_TX_ANT}}$ is substitution antenna gain.

A_{TOT} is total correction factor including cable loss and substitution correction

During the test, the data of A_{TOT} was added in the test spectrum analyze, so spectrum analyze reading is the final values which contain the data of A_{TOT} .

Note1: The power of the EUT transmitting frequency should be ignored.

Note2: All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.


Note3: All bandwidth and modulation were considered and evaluated respectively by performing full test for each band, only the worst cases (Max Bandwidth and QPSK mode) were recorded in this test report.

Note 4: N/A means the frequency is the basic frequency or the base station frequency, they are no need to verdict.


Note 5: The amplitude of emissions(18GHz to 10th harmonics) which are attenuated more than 20 dB below the limit are not be reported.



LTE Band 26, 5MHz BW, Low Channel, QPSK




No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	817.640	-56.50	-13.00	Horizontal	N/A
2	863.230	-46.54	-13.00	Horizontal	N/A
3	1637.055	-43.10	-13.00	Horizontal	PASS
4	3600.418	-50.63	-13.00	Horizontal	PASS
5	7491.344	-41.27	-13.00	Horizontal	PASS
6	8947.672	-38.22	-13.00	Horizontal	PASS




No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	816.670	-55.92	-13.00	Vertical	N/A
2	863.230	-62.33	-13.00	Vertical	N/A
3	1694.038	-43.10	-13.00	Vertical	PASS
4	3947.427	-49.08	-13.00	Vertical	PASS
5	6566.603	-43.51	-13.00	Vertical	PASS
6	9625.077	-39.14	-13.00	Vertical	PASS



LTE Band 26, 5MHz BW, Mid Channel, QPSK




No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	816.670	-55.44	-13.00	Horizontal	N/A
2	865.170	-47.00	-13.00	Horizontal	N/A
3	1501.321	-42.40	-13.00	Horizontal	PASS
4	3766.539	-49.16	-13.00	Horizontal	PASS
5	6396.790	-43.03	-13.00	Horizontal	PASS
6	11745.890	-38.45	-13.00	Horizontal	PASS




No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	816.670	-55.69	-13.00	Vertical	N/A
2	864.200	-61.65	-13.00	Vertical	N/A
3	1672.909	-43.56	-13.00	Vertical	PASS
4	3773.923	-49.31	-13.00	Vertical	PASS
5	7247.700	-41.31	-13.00	Vertical	PASS
6	11721.895	-38.81	-13.00	Vertical	PASS

LTE Band 26, 5MHz BW, High Channel, QPSK



No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	821.520	-57.41	-13.00	Horizontal	N/A
2	864.200	-47.67	-13.00	Horizontal	N/A
3	1659.464	-43.09	-13.00	Horizontal	PASS
4	3639.180	-49.02	-13.00	Horizontal	PASS
5	7077.887	-41.52	-13.00	Horizontal	PASS
6	10965.121	-38.35	-13.00	Horizontal	PASS



No.	Fre.(MHz)	PK (dBm)	Limit (dBm)	Antenna	Verdict
1	821.520	-54.77	-13.00	Vertical	N/A
2	868.080	-61.65	-13.00	Vertical	N/A
3	1571.749	-43.05	-13.00	Vertical	PASS
4	3677.941	-50.16	-13.00	Vertical	PASS
5	7094.499	-41.06	-13.00	Vertical	PASS
6	10856.219	-38.08	-13.00	Vertical	PASS



Annex A Test Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for test performed on the EUT as specified in CISPR 16-1-2:

Test items	Uncertainty
Output Power	± 2.22 dB
Bandwidth	$\pm 5\%$
Conducted Spurious Emission	± 2.77 dB
Band Edge	± 2.77 dB
Equivalent Isotropic Radiated Power	± 2.22 dB
Radiated Spurious Emissions	± 6 dB

This uncertainty represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.



Annex B Testing Laboratory Information

1. Identification of the Responsible Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Laboratory Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

3. Facilities and Accreditations

All measurement facilities used to collect the measurement data are located at FL.3, Building A, FeiYang Science Park, Block 67, BaoAn District, Shenzhen, 518101 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.10-2013 and CISPR Publication 22; the FCC designation number is CN1192, the test firm registration number is 226174.



4. Test Equipments Utilized

4.1 Conducted Test Equipments

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Due Date
EXA Signal Analyzer	MY51511149	N9020A	Agilent	2023.06.21	2024.06.20
Communication Test Station	6200995016	MT8820C	Anritsu	2023.09.19	2024.09.18
Temperature Chamber	S022177101 00089002	KMT-36LF 1A0	KOMEG	2023.09.19	2024.09.18

4.2 List of Software Used

Description	Manufacturer	Software Version
Morlab FCC LTE Test System	MORLAB	V6.45
MORLAB EMCR	MORLAB	V1.2

**4.3 Radiated Test Equipments**

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Due Date
System Simulator	152038	CMW500	R&S	2023.10.17	2024.10.16
Receiver	MY54130016	N9038A	Agilent	2023.06.21	2024.06.20
Test Antenna - Bi-Log	9163-519	VULB 9163	Schwarzbeck	2023.07.01	2024.06.30
Test Antenna - Horn	9120D-963	BBHA 9120D	Schwarzbeck	2023.06.27	2024.06.26
RF Coaxial Cable (DC-18GHz)	MRE001	PE330	Pasternack	2023.06.27	2024.06.26
RF Coaxial Cable (DC-18GHz)	MRE002	CLU18	Pasternack	2023.06.27	2024.06.26
RF Coaxial Cable (DC-18GHz)	MRE003	CLU18	Pasternack	2023.06.27	2024.06.26
RF Coaxial Cable (DC-40GHz)	22290045	QA360-40-KK-0.5	Qualwave	2023.07.04	2024.07.03
RF Coaxial Cable (DC-40GHz)	22290046	QA360-40-KK F-2	Qualwave	2023.07.04	2024.07.03
Preamplifier (10MHz-6GHz)	46732	S10M100L380 2	LUCIX CORP.	2023.07.04	2024.07.03
Preamplifier (2GHz-18GHz)	61171/61172	S020180L320 3	LUCIX CORP.	2023.06.27	2024.06.26
Preamplifier (18GHz-40GHz)	DS77209	DCLNA0118-4 0C-S	Decentest	2023.06.27	2024.06.26
Notch Filter	N/A	WRCGV -LTE 26	Wainwright	N/A	N/A
Anechoic Chamber	N/A	9m*6m*6m	CRT	2022.05.10	2025.05.09

END OF REPORT