






Band12 / 1.4MHz / High CH / QPSK



Band12 / 1.4MHz / High CH / 16QAM




Band12 / 1.4MHz / High CH / 64QAM




Band12 / 3MHz / Low CH / QPSK



Band12 / 3MHz / Low CH / 16QAM



Band12 / 3MHz / Low CH / 64QAM





Band12 / 3MHz / Mid CH / QPSK



Band12 / 3MHz / Mid CH / 16QAM




Band12 / 3MHz / Mid CH / 64QAM




Band12 / 3MHz / High CH / QPSK




Band12 / 3MHz / High CH / 16QAM




Band12 / 3MHz / High CH / 64QAM








Band12 / 5MHz / High CH / QPSK



Band12 / 5MHz / High CH / 16QAM




Band12 / 5MHz / High CH / 64QAM



Band12 / 10MHz / Low CH / QPSK



Band12 / 10MHz / Low CH / 16QAM




Band12 / 10MHz / Low CH / 64QAM






Band12 / 10MHz / Mid CH / QPSK



Band12 / 10MHz / Mid CH / 16QAM




Band12 / 10MHz / Mid CH / 64QAM



Band12 / 10MHz / High CH / QPSK




Band12 / 10MHz / High CH / 16QAM




Band12 / 10MHz / High CH / 64QAM








Band17 / 5MHz / High CH / QPSK



Band17 / 5MHz / High CH / 16QAM



Band17 / 5MHz / High CH / 64QAM




Band17 / 10MHz / Low CH / QPSK



Band17 / 10MHz / Low CH / 16QAM




Band17 / 10MHz / Low CH / 64QAM





Band17 / 10MHz / Mid CH / QPSK



Band17 / 10MHz / Mid CH / 16QAM




Band17 / 10MHz / Mid CH / 64QAM



Band17 / 10MHz / High CH / QPSK



Band17 / 10MHz / High CH / 16QAM



Band17 / 10MHz / High CH / 64QAM



2.5. Conducted Spurious Emissions

2.5.1. Requirement

According to FCC section 2.1051, the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43+10*\log(P)$ dB. This calculated to be -13dBm.


Additional requirement for LTE Band 7/38/41:

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $55 + 10 \log(P)$ dB. This calculated to be -25dBm.

Additional requirement for LTE Band 30/40:

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $70 + 10 \log(P)$ dB. This calculated to be -40dBm.

2.5.2. Test Description



The EUT is coupled to the Spectrum Analyzer (SA) and the System Simulator (SS) with Attenuators through the Power Splitter; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading. The EUT is commanded by the SS to operate at the maximum output power. A call is established between the EUT and the SS.




REPORT No. : SZ19100071W02

2.5.3. Test procedure

KDB 971168 D01v03 Section 6.0 and ANSI/TIA-603-E-2016.




2.5.4. Test Result







Band2 / 1.4MHz / High CH / QPSK




Band2 / 1.4MHz / High CH / 16QAM




Band2 / 1.4MHz / High CH / 64QAM



Band2 / 3MHz / Low CH / QPSK



Band2 / 3MHz / Low CH / 16QAM



Band2 / 3MHz / Low CH / 64QAM

