



TEST REPORT

APPLICANT : BLU Products, Inc.
PRODUCT NAME : Smart Phone
MODEL NAME : G71L
BRAND NAME : BLU
FCC ID : YHLBLUG71L
STANDARD(S) : 47 CFR Part 15 Subpart C
RECEIPT DATE : 2021-12-27
TEST DATE : 2021-12-31 to 2022-01-23
ISSUE DATE : 2022-01-24

Edited by: Zeng Xiaoying
Zeng Xiaoying (Rapporteur)

Approved by: Shen Junsheng
Shen Junsheng (Supervisor)

NOTE: This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.





DIRECTORY

- 1. Technical Information 3**
- 1.1. Applicant and Manufacturer Information 3**
- 1.2. Equipment Under Test (EUT) Description 3**
- 1.3. The Channel Number and Frequency 4**
- 1.4. Test Standards and Results 5**
- 1.5. Environmental Conditions 6**
- 2. 47 CFR Part 15C Requirements 7**
- 2.1. Antenna Requirement 7**
- 2.2. Duty Cycle of Test Signal 8**
- 2.3. Maximum Peak Conducted Output Power 9**
- 2.4. Maximum Average Conducted Output Power 12**
- 2.5. 6 dB Bandwidth 13**
- 2.6. Conducted Spurious Emissions and Band Edge 16**
- 2.7. Power Spectral Density 20**
- 2.8. Conducted Emission 23**
- 2.9. Restricted Frequency Bands 27**
- 2.10. Radiated Emission 31**
- Annex A Test Uncertainty 53**
- Annex B Testing Laboratory Information 54**

Change History		
Version	Date	Reason for change
1.0	2022-01-24	First edition



1. Technical Information

Note: Provide by applicant.

1.1. Applicant and Manufacturer Information

Applicant:	BLU Products, Inc.
Applicant Address:	10814 NW 33rd St # 100 Doral, FL 33172,USA
Manufacturer:	BLU Products, Inc.
Manufacturer Address:	10814 NW 33rd St # 100 Doral, FL 33172,USA

1.2. Equipment Under Test (EUT) Description

Product Name:	Smart Phone	
Sample No.:	6#	
Hardware Version:	V4.0	
Software Version:	BLU_G0710WW_V11.0.01.01_GENERIC 16-12-2021 01:35	
Equipment Type:	Bluetooth LE	
Bluetooth Version:	4.2	
Modulation Type:	GFSK	
Data Rate:	1Mbps	
Operating Frequency Range:	2402MHz-2480MHz	
Antenna Type:	PIFA Antenna	
Antenna Gain:	0.5dBi	
Accessory Information:	Battery	
	Brand Name:	BLU
	Model No.:	C886450500P
	Serial No.:	N/A
	Capacity:	5000mAh
	Rated Voltage:	3.85V
	Charge Limit:	4.4V
	Manufacturer:	Hunan Gaoyuan Battery.,Ltd



Accessory Information:	AC Adapter	
	Brand Name:	BLU
	Model No.:	UC-CR-2000
	Serial No.:	N/A
	Rated Output:	5.0V \pm 2A
	Rated Input:	100-240V \sim 50/60Hz, 0.3A
	Manufacturer:	Shenzhen BaiJunda Electronics Co., Ltd.

Note 1: We use the dedicated software to control the EUT continuous transmission.

Note 2: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

1.3. The Channel Number and Frequency

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

Note 1: The black bold channels were selected for test.



1.4. Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart C for the EUT FCC ID Certification:

No.	Identity	Document Title
1	47 CFR Part 15	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Test Date	Test Engineer	Result	Method Determination /Remark
1	15.203	Antenna Requirement	N/A	N/A	PASS	No deviation
2	N/A	Duty Cycle of Test Signal	Jan 04, 2022	Meng Shurui	PASS	No deviation
3	15.247(b)	Maximum Peak Conducted Output Power	Jan 04, 2022	Meng Shurui	PASS	No deviation
4	15.247(b)	Maximum Average Conducted Output Power	Jan 04, 2022	Meng Shurui	PASS	No deviation
5	15.247(a)	Bandwidth	Jan 06, 2022	Meng Shurui	PASS	No deviation
6	15.247(d)	Conducted Spurious Emission and Band Edge	Jan 06, 2022	Meng Shurui	PASS	No deviation
7	15.247(e)	Power Spectral Density	Jan 06, 2022	Meng Shurui	PASS	No deviation
8	15.207	Conducted Emission	Dec 31, 2021	Yang Lian	PASS	No deviation
9	15.247(d)	Restricted Frequency Bands	Jan 12&19, 2022	Yin Xiaogang	PASS	No deviation
10	15.209, 15.247(d)	Radiated Emission	Jan 18&23, 2022	Lin Jiayong	PASS	No deviation



Note 1: The tests were performed according to the method of measurements prescribed in ANSIC63.10-2013 and KDB558074 D01 v05r02.

Note 2: The path loss during the RF test is calibrated to correct the results by the offset setting in the test equipments. The Ref offset 1.0dB means the cable loss is 1.0dB.

Note 3: Additions to, deviation, or exclusions from the method shall be judged in the "method determination" column of add, deviate or exclude from the specific method shall be explained in the "Remark" of the above table.

Note 4: When the test result is a critical value, we will use the measurement uncertainty give the judgment result based on the 95% confidence intervals.

1.5. Environmental Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15-35
Relative Humidity (%):	30-60
Atmospheric Pressure (kPa):	86-106



2. 47 CFR Part 15C Requirements

2.1. Antenna Requirement

2.1.1. Applicable Standard

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

2.1.2. Test Result: Compliant

Inside of the EUT has a PIFA antenna coupled with the metal shrapnel. Please refer to the EUT internal photos.

2.2. Duty Cycle of Test Signal


2.2.1. Requirement

Preferably, all measurements of maximum conducted (average) output power will be performed with the EUT transmitting continuously (i.e., with a duty cycle of greater than or equal to 98%). When continuous operation cannot be realized, then the use of sweep triggering/signal gating techniques can be used to ensure that measurements are made only during transmissions at the maximum power control level. Such sweep triggering/signal gating techniques will require knowledge of the minimum transmission duration (T) over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation. Sweep triggering/signal gating techniques can then be used if the measurement/sweep time of the analyzer can be set such that it does not exceed T at any time that data are being acquired (i.e., no transmitter OFF-time is to be considered).

When continuous transmission cannot be achieved and sweep triggering/signal gating cannot be implemented, alternative procedures are provided that can be used to measure the average power; however, they will require an additional measurement of the transmitter duty cycle (D). Within this sub clause, the duty cycle refers to the fraction of time over which the transmitter is ON and is transmitting at its maximum power control level. The duty cycle is considered to be constant if variations are less than $\pm 2\%$; otherwise, the duty cycle is considered to be non constant.

2.2.2. Test Description

Test Setup:



ANSI C63.10 2013 Clause 11.6 was used in order to prove compliance.

2.2.3. Test Result

Test Mode	Duty Cycle(%) (D)	Duty Factor ($10 \cdot \lg[1/D]$)
GFSK	62.90	2.01

2.3. Maximum Peak Conducted Output Power


2.3.1. Requirement

According to FCC section 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum peak conducted output power of the intentional radiator shall not exceed 1 Watt.

2.3.2. Test Description

The measured output power was calculated by the reading of the spectrum analyzer and calibration.

Test Setup:



The EUT (Equipment under the test) is coupled to the Spectrum analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading, all test result in Spectrum analyzer.

2.3.3. Test Procedure

The measured output power was calculated by the reading of the spectrum analyzer and calibration. Following is the test procedure for Peak Output Power test on the spectrum analyzer:

- a) Set analyzer center frequency to channel center frequency
- b) Set RBW to 1MHz
- c) Set VBW to 3MHz
- d) Set span to 3MHz
- e) Sweep time = auto couple
- f) Detector = peak
- g) Trace mode = max hold
- h) Allow trace to fully stabilize
- i) Use peak marker function to determine the peak amplitude level



2.3.4. Test Result


A. Test Verdict:

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
0	2402	-1.16	0.0008	30	1	PASS
19	2440	1.87	0.0015			PASS
39	2480	1.01	0.0013			PASS

B. Test Plot:



(Channel 0, 2402MHz)



(Channel 19, 2440MHz)



(Channel 39, 2480MHz)

2.4. Maximum Average Conducted Output Power

2.4.1. Requirement

According to FCC section 15.247(b)(3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum average conducted output power of the intentional radiator shall not exceed 1 Watt.

2.4.2. Test Description

The measured output power was calculated by the reading of the spectrum analyzer and calibration.

Test Setup:



The EUT (Equipment under the test) is coupled to the Spectrum analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading, all test result in Spectrum analyzer.

2.4.3. Test Procedure

KDB 558074 Section 8.3.2 was used in order to prove compliance.

2.4.4. Test Result

Channel	Frequency (MHz)	Average Power				Limit		Verdict
		Measured dBm	Duty Factor	Duty Factor Calculated		dBm	W	
				dBm	W			
0	2402	-3.89	2.27	-1.88	0.0006	30	1	PASS
19	2440	-0.78		1.23	0.0013			PASS
39	2480	-1.65		0.36	0.0011			PASS


2.5. 6 dB Bandwidth

2.5.1. Requirement

According to FCC section 15.247(a) (2), systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6dB bandwidth shall be at least 500 kHz.

2.5.2. Test Description

Test Setup:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

2.5.3. Test Procedure

The steps for the first option are as follows:

- a) Set analyzer center frequency to channel center frequency
- b) Set RBW to 100kHz
- c) Set VBW to 300kHz
- d) Detector = peak
- e) Trace mode = max hold
- f) Sweep time = auto couple
- g) Allow the trace to fully stabilize
- h) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission



The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described in 11.8.1 (i.e., RBW = 100 kHz, VBW $\geq 3 \times$ RBW, and peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.

2.5.4. Test Result

A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits(kHz)	Verdict
0	2402	0.667	≥ 500	PASS
19	2440	0.664	≥ 500	PASS
39	2480	0.668	≥ 500	PASS

B. Test Plot:



(Channel 0, 2402MHz)



(Channel 19, 2440 MHz)



(Channel 39, 2480MHz)


2.6. Conducted Spurious Emissions and Band Edge

2.6.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

2.6.2. Test Description

Test Setup:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

2.6.3. Test Procedure

KDB 558074 Section 8.5 and 8.7 was used in order to prove compliance.




2.6.4. Test Result

A. Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
0	2402	-53.53	-2.94	-22.94	PASS
19	2440	-53.07	-0.11	-20.11	PASS
39	2480	-52.09	-0.60	-20.60	PASS


B. Test Plot:




(30MHz to 25GHz, Channel 0)



(Band Edge, Channel 0)



(30MHz to 25GHz, Channel 19)



(30MHz to 25GHz, Channel 39)



(Band Edge, Channel 39)

2.7. Power Spectral Density

2.7.1. Requirement

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

2.7.2. Test Description

Test Setup:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

2.7.3. Test Procedure

The measured power spectral density was calculated by the reading of the spectrum analyzer and calibration. Following is the test procedure for PSD test:

- a) Set analyzer center frequency to channel center frequency
- b) Set span to 1.5 times DTS
- c) Set RBW to 3kHz
- d) Set VBW to 10kHz
- e) Detector = peak
- f) Sweep time = auto couple
- g) Trace mode = max hold
- h) Allow trace to fully stabilize
- i) Use the peak marker function to determine the maximum amplitude level within the RBW



2.7.4. Test Result

A. Test Verdict:

Spectral Power Density (dBm/3kHz)				
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
0	2402	-15.90	8	PASS
19	2440	-12.70	8	PASS
39	2480	-13.34	8	PASS

B. Test Plot:



(Channel 0, 2402MHz)



(Channel 19, 2440MHz)



(Channel 39, 2480MHz)

2.8. Conducted Emission

2.8.1. Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).


Frequency Range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

Note:

- (a) The lower limit shall apply at the band edges.
- (b) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

2.8.2. Test Description

Test Setup:



The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.10: 2013.



2.8.3. Test Result

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Set RBW=9kHz, VBW=30kHz. Refer to recorded points and plots below.

Note: Both of the test voltage AC 120V/60Hz and AC 230V/50Hz were considered and tested respectively, only the results of the worst case AC 120V/60Hz were recorded in this report.

A. Test Setup:

Test Mode: EUT+Adapter+Earphone+ BT TX

Test Voltage: AC 120V/60Hz


The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V]} = U_R + L_{\text{Cable loss}} \text{ [dB]} + A_{\text{Factor}}$$

U_R : Receiver Reading


A_{Factor} : Voltage division factor of LISN

B. Test Plot:



(L Phase)

No.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.2128	36.91	29.51	63.09	53.09	Line	PASS
2	0.3838	34.27	25.19	58.20	48.20		PASS
3	0.5904	41.90	38.43	56.00	46.00		PASS
4	0.6135	40.75	37.90	56.00	46.00		PASS
5	0.9862	34.02	25.26	56.00	46.00		PASS
6	1.1260	36.55	30.90	56.00	46.00		PASS



(N Phase)

No.	Fre. (MHz)	Emission Level (dBµV)		Limit (dBµV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1634	38.72	27.38	65.29	55.29	Neutral	PASS
2	0.3703	34.36	22.95	58.49	48.49		PASS
3	0.4784	33.84	22.19	56.37	46.37		PASS
4	0.6769	33.18	23.39	56.00	46.00		PASS
5	1.2577	33.50	22.35	56.00	46.00		PASS
6	1.4922	32.70	21.54	56.00	46.00		PASS


2.9. Restricted Frequency Bands

2.9.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

2.9.2. Test Description

Test Setup



The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.

2.9.3. Test Result

The lowest and highest channels are tested to verify the Restricted Frequency Bands.

The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V/m]} = U_R + A_T + A_{\text{Factor}} \text{ [dB]}; A_T = L_{\text{Cable loss}} \text{ [dB]} - G_{\text{preamp}} \text{ [dB]}$$

A_T : Total correction Factor except Antenna


U_R : Receiver Reading

G_{preamp} : Preamplifier Gain


A_{Factor} : Antenna Factor at 3m

Note: The maximized peak measured value complies with the average limit, then it is unnecessary to perform an average measurement.

Plot for Channel 0




No.	Freq. [MHz]	Level [dBμV/m]	Factor [dB]	Limit [dBμV/m]	Polarity	Detector	Verdict
1	2387.5576	46.71	-2.86	74.00	Horizontal	PK	PASS
2	2390.0328	46.77	-2.87	74.00	Horizontal	PK	PASS




No.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Polarity	Detector	Verdict
1	2385.6856	47.17	-2.86	74.00	Vertical	PK	PASS
2	2390.2304	46.55	-2.87	74.00	Vertical	PK	PASS

Plot for Channel 39



No.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Polarity	Detector	Verdict
1	2483.6540	47.46	-2.66	74.00	Horizontal	PK	PASS
2	2484.9850	47.98	-2.65	74.00	Horizontal	PK	PASS



No.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Polarity	Detector	Verdict
1	2483.7464	47.07	-2.66	74.00	Vertical	PK	PASS
2	2486.1026	46.93	-2.64	74.00	Vertical	PK	PASS



2.10. Radiated Emission

2.10.1. Requirement

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V}/\text{m}$)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3


Note1: For above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.

Note2: For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK). In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table).


2.10.2. Test Description

Test Setup:


1) For radiated emissions from 9kHz to 30MHz



2) For radiated emissions from 30MHz to 1GHz



3) For radiated emissions above 1GHz



The EUT is placed on a non-conducting table 80 cm above the ground plane for measurement below 1GHz; 1.5 m above the ground plane for measurement above 1GHz. The antenna to EUT distance is 3 meters. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 30MHz, the emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9kHz-90 kHz, 110kHz-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

For measurements below 1GHz the resolution bandwidth is set to 100kHz for peak detection measurements or 120kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1GHz the resolution bandwidth is set to 1MHz, the video band width is set to 3MHz for peak measurements and as applicable for average measurements.

The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.



2.10.3. Test Result

According to ANSI C63.10, because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak (or average) limit, it is unnecessary to perform an quasi-peak measurement (or average).

The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V/m]} = U_R + A_T + A_{\text{Factor}} \text{ [dB]}; A_T = L_{\text{Cable loss}} \text{ [dB]} - G_{\text{preamp}} \text{ [dB]}$$

A_T : Total correction Factor except Antenna

U_R : Receiver Reading

G_{preamp} : Preamplifier Gain

A_{Factor} : Antenna Factor at 3m


During the test, the total correction Factor A_T and A_{Factor} were built in test software.

Note1: All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Note2: For the frequency, which started from 9kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.


Note3: For the frequency, which started from 18GHz to 40GHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.

Plot for Channel 0




(30MHz to 1GHz)

No.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Polarity	Detector	Verdict
1	58.7149	24.43	-8.16	40.00	Horizontal	PK	PASS
2	145.8296	33.11	-11.85	43.50	Horizontal	PK	PASS
3	234.3024	30.69	-7.57	46.00	Horizontal	PK	PASS
4	279.7030	29.88	-6.57	46.00	Horizontal	PK	PASS
5	478.6699	29.38	-1.70	46.00	Horizontal	PK	PASS
6	799.6750	32.77	3.29	46.00	Horizontal	PK	PASS




(1GHz to 3GHz)

No.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Polarity	Detector	Verdict
1	1122.2000	42.41	-7.96	74.00	Horizontal	PK	PASS
2	1362.2000	43.22	-7.01	74.00	Horizontal	PK	PASS
3	1648.2000	46.33	-3.12	74.00	Horizontal	PK	PASS
4	1994.8000	47.07	-2.53	74.00	Horizontal	PK	PASS
5	2401.8000	83.76	-2.89	74.00	N/A	PK	N/A
6	2917.4000	48.54	-1.79	74.00	Horizontal	PK	PASS




(3GHz to 18GHz)

No.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Polarity	Detector	Verdict
1	3994.5000	37.31	-7.98	74.00	Horizontal	PK	PASS
2	5607.0000	40.11	-4.11	74.00	Horizontal	PK	PASS
3	8287.5000	44.64	1.62	74.00	Horizontal	PK	PASS
4	10626.0000	48.24	5.47	74.00	Horizontal	PK	PASS
5	13042.5000	47.05	5.76	74.00	Horizontal	PK	PASS
6	17179.5000	48.47	11.60	74.00	Horizontal	PK	PASS




(30MHz to 1GHz)

No.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Polarity	Detector	Verdict
1	58.9089	30.46	-8.19	40.00	Vertical	PK	PASS
2	152.9113	30.21	-11.58	43.50	Vertical	PK	PASS
3	269.9050	24.11	-6.54	46.00	Vertical	PK	PASS
4	491.0871	28.87	-1.41	46.00	Vertical	PK	PASS
5	700.7251	33.60	1.71	46.00	Vertical	PK	PASS
6	971.1881	35.02	5.48	54.00	Vertical	PK	PASS



(1GHz to 3GHz)


No.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Polarity	Detector	Verdict
1	1108.4000	41.58	-8.00	74.00	Vertical	PK	PASS
2	1412.2000	42.70	-6.72	74.00	Vertical	PK	PASS
3	1879.0000	47.87	-1.51	74.00	Vertical	PK	PASS
4	2401.8000	73.18	-2.89	74.00	N/A	PK	N/A
5	2593.8000	47.49	-2.46	74.00	Vertical	PK	PASS
6	2926.4000	48.61	-1.81	74.00	Vertical	PK	PASS



(3GHz to 18GHz)


No.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Polarity	Detector	Verdict
1	3558.0000	37.49	-8.90	74.00	Vertical	PK	PASS
2	5476.5000	39.94	-4.01	74.00	Vertical	PK	PASS
3	6906.0000	42.19	-1.97	74.00	Vertical	PK	PASS
4	9474.0000	46.50	4.61	74.00	Vertical	PK	PASS
5	11926.5000	47.72	5.26	74.00	Vertical	PK	PASS
6	16572.0000	48.10	8.46	74.00	Vertical	PK	PASS

Plot for Channel 19




(30MHz to 1GHz)

No.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Polarity	Detector	Verdict
1	48.0438	23.26	-6.86	40.00	Horizontal	PK	PASS
2	58.9089	26.09	-8.19	40.00	Horizontal	PK	PASS
3	146.8967	33.83	-11.79	43.50	Horizontal	PK	PASS
4	235.9516	30.96	-7.48	46.00	Horizontal	PK	PASS
5	482.5503	28.91	-1.65	46.00	Horizontal	PK	PASS
6	796.5707	34.84	3.22	46.00	Horizontal	PK	PASS




(1GHz to 3GHz)

No.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Polarity	Detector	Verdict
1	1143.0000	42.14	-7.89	74.00	Horizontal	PK	PASS
2	1445.4000	42.60	-6.71	74.00	Horizontal	PK	PASS
3	1921.8000	48.14	-1.57	74.00	Horizontal	PK	PASS
4	2193.2000	47.01	-3.33	74.00	Horizontal	PK	PASS
5	2439.8000	86.78	-2.88	74.00	N/A	PK	N/A
6	2890.6000	48.23	-1.74	74.00	Horizontal	PK	PASS




(3GHz to 18GHz)

No.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Polarity	Detector	Verdict
1	3859.5000	38.48	-7.67	74.00	Horizontal	PK	PASS
2	5049.0000	38.89	-5.59	74.00	Horizontal	PK	PASS
3	8808.0000	44.70	2.01	74.00	Horizontal	PK	PASS
4	11142.0000	48.82	6.28	74.00	Horizontal	PK	PASS
5	13902.0000	47.85	7.93	74.00	Horizontal	PK	PASS
6	16471.5000	47.77	8.14	74.00	Horizontal	PK	PASS




(30MHz to 1GHz)

No.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Polarity	Detector	Verdict
1	32.1342	26.12	-10.59	40.00	Vertical	PK	PASS
2	58.9089	29.85	-8.19	40.00	Vertical	PK	PASS
3	150.8741	29.58	-11.65	43.50	Vertical	PK	PASS
4	268.8379	23.54	-6.54	46.00	Vertical	PK	PASS
5	462.6633	30.07	-2.01	46.00	Vertical	PK	PASS
6	896.1026	33.89	4.89	46.00	Vertical	PK	PASS



(1GHz to 3GHz)


No.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Polarity	Detector	Verdict
1	1119.0000	41.87	-7.97	74.00	Vertical	PK	PASS
2	1443.8000	42.59	-6.71	74.00	Vertical	PK	PASS
3	1801.4000	48.86	-1.35	74.00	Vertical	PK	PASS
4	2259.6000	46.83	-3.39	74.00	Vertical	PK	PASS
5	2440.0000	80.10	-2.88	74.00	N/A	PK	N/A
6	2917.2000	49.06	-1.79	74.00	Vertical	PK	PASS



(3GHz to 18GHz)


No.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Polarity	Detector	Verdict
1	3838.5000	38.45	-7.56	74.00	Vertical	PK	PASS
2	5788.5000	39.37	-4.59	74.00	Vertical	PK	PASS
3	8683.5000	44.15	1.98	74.00	Vertical	PK	PASS
4	11428.5000	48.46	6.11	74.00	Vertical	PK	PASS
5	14080.5000	48.97	8.55	74.00	Vertical	PK	PASS
6	16804.5000	48.52	10.01	74.00	Vertical	PK	PASS

Plot for Channel 39




(30MHz to 1GHz)

No.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Polarity	Detector	Verdict
1	44.1634	21.57	-7.49	40.00	Horizontal	PK	PASS
2	58.9089	24.78	-8.19	40.00	Horizontal	PK	PASS
3	146.8967	32.75	-11.79	43.50	Horizontal	PK	PASS
4	233.9144	31.29	-7.60	46.00	Horizontal	PK	PASS
5	480.3190	28.90	-1.67	46.00	Horizontal	PK	PASS
6	893.4833	33.63	4.85	46.00	Horizontal	PK	PASS




(1GHz to 3GHz)

No.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Polarity	Detector	Verdict
1	1105.4000	43.02	-8.01	74.00	Horizontal	PK	PASS
2	1403.8000	43.53	-6.72	74.00	Horizontal	PK	PASS
3	1740.0000	48.01	-1.27	74.00	Horizontal	PK	PASS
4	2087.2000	46.01	-3.15	74.00	Horizontal	PK	PASS
5	2480.4000	87.22	-2.68	74.00	N/A	PK	N/A
6	2923.6000	48.71	-1.80	74.00	Horizontal	PK	PASS




(3GHz to 18GHz)

No.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Polarity	Detector	Verdict
1	3894.0000	37.92	-8.12	74.00	Horizontal	PK	PASS
2	6064.5000	41.22	-2.91	74.00	Horizontal	PK	PASS
3	9024.0000	45.63	3.53	74.00	Horizontal	PK	PASS
4	10855.5000	48.09	5.62	74.00	Horizontal	PK	PASS
5	13239.0000	48.17	5.66	74.00	Horizontal	PK	PASS
6	16321.5000	48.58	7.61	74.00	Horizontal	PK	PASS




(30MHz to 1GHz)

No.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Polarity	Detector	Verdict
1	32.0372	25.92	-10.63	40.00	Vertical	PK	PASS
2	58.9089	27.35	-8.19	40.00	Vertical	PK	PASS
3	150.8741	29.81	-11.65	43.50	Vertical	PK	PASS
4	288.8219	23.10	-6.36	46.00	Vertical	PK	PASS
5	510.0040	30.08	-0.94	46.00	Vertical	PK	PASS
6	700.2400	33.41	1.71	46.00	Vertical	PK	PASS



(1GHz to 3GHz)

No.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Polarity	Detector	Verdict
1	1108.8000	41.79	-8.00	74.00	Vertical	PK	PASS
2	1402.4000	42.65	-6.72	74.00	Vertical	PK	PASS
3	1854.6000	47.94	-1.65	74.00	Vertical	PK	PASS
4	2115.8000	46.40	-3.42	74.00	Vertical	PK	PASS
5	2479.8000	81.98	-2.68	74.00	N/A	PK	N/A
6	2876.0000	48.57	-1.69	74.00	Vertical	PK	PASS



(3GHz to 18GHz)

No.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Polarity	Detector	Verdict
1	3832.5000	37.80	-7.57	74.00	Vertical	PK	PASS
2	6111.0000	42.15	-2.65	74.00	Vertical	PK	PASS
3	8067.0000	45.65	1.27	74.00	Vertical	PK	PASS
4	10804.5000	48.41	5.84	74.00	Vertical	PK	PASS
5	12916.5000	47.24	5.37	74.00	Vertical	PK	PASS
6	17064.0000	48.73	10.80	74.00	Vertical	PK	PASS



Annex A Test Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for test performed on the EUT as specified in CISPR 16-1-2:

Test Items	Uncertainty
Peak Output Power	$\pm 2.22\text{dB}$
Power Spectral Density	$\pm 2.22\text{dB}$
Bandwidth	$\pm 5\%$
Conducted Spurious Emission	$\pm 2.77\text{dB}$
Restricted Frequency Bands	$\pm 5\%$
Radiated Emission	$\pm 2.95\text{dB}$
Conducted Emission	$\pm 2.44\text{dB}$

This uncertainty represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.



Annex B Testing Laboratory Information

1. Identification of the Responsible Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Laboratory Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

3. Facilities and Accreditations

All measurement facilities used to collect the measurement data are located at FL.3, Building A, FeiYang Science Park, Block 67, BaoAn District, Shenzhen, 518101 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.10-2013 and CISPR Publication 22; the FCC designation number is CN1192, the test firm registration number is 226174.



4. Test Equipments Utilized

4.1 Conducted Test Equipments

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Due Date
EXA Signal Analyzer	MY53470836	N9010A	Agilent	2021.03.25	2022.03.24
RF Cable (30MHz-26GHz)	CB01	RF01	Morlab	N/A	N/A
Coaxial Cable	CB02	RF02	Morlab	N/A	N/A
SMA Connector	CN01	RF03	HUBER-SUHNE R	N/A	N/A
Computer	T430i	Think Pad	Lenovo	N/A	N/A

4.2 List of Software Used

Description	Manufacturer	Software Version
Test System	Tonscend	V2.5.77.0418
TS+ -[JS32-CE]	Tonscend	V2.5.0.0
TS+ -[JS32-RE]	Tonscend	V2.5.5.0.6

**4.3 Radiated Test Equipments**

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Receiver	MY54130016	N9038A	Agilent	2021.07.16	2022.07.15
Test Antenna - Bi-Log	9163-520	VULB 9163	Schwarzbeck	2019.05.24	2022.05.23
Test Antenna - Loop	1520-022	FMZB1520	Schwarzbeck	2019.02.14	2022.02.13
Test Antenna – Horn	01774	BBHA 9120D	Schwarzbeck	2019.07.26	2022.07.25
Test Antenna – Horn	BBHA9170 #774	BBHA 9170	Schwarzbeck	2019.07.26	2022.07.25
Coaxial Cable (N male) (9KHz-30MHz)	CB04	EMC04	Morlab	N/A	N/A
Coaxial Cable (N male) (30MHz-26GHz)	CB02	EMC02	Morlab	N/A	N/A
Coaxial Cable (N male) (30MHz-26GHz)	CB03	EMC03	Morlab	N/A	N/A
Coaxial Cable (N male) (30MHz-40GHz)	CB05	EMC05	Morlab	N/A	N/A
1-18GHz pre-Amplifier	61171/61172	S020180L32 03	Tonscend	2021.07.16	2022.07.15
18-26.5GHz pre-Amplifier	46732	S10M100L38 02	Tonscend	2021.07.16	2022.07.15
26-40GHz pre-Amplifier	56774	S40M400L40 02	Tonscend	2021.07.16	2022.07.15
Notch Filter	N/A	WRCG-2400-2483.5-60SS	Wainwright	2021.07.16	2022.07.15
Anechoic Chamber	N/A	9m*6m*6m	CRT	2020.01.06	2023.01.05

END OF REPORT