

FCC TEST REPORT

Product Name: Smart Phone
Trade Mark: BOLD, BLU
Model No.: K10
Add. Model No.: G54
Report Number: 24040810587RFM-1
Test Standards: FCC 47 CFR Part 22 Subpart H
 FCC 47 CFR Part 24 Subpart E
 FCC 47 CFR Part 27 Subpart L
FCC ID: YHLBLUK10K
Test Result: PASS
Date of Issue: June 5, 2024

Prepared for:

BLU Products, Inc.
8600 NW 36th Street, Suite #300 | Miami, FL 33166

Prepared by:

Shenzhen UnionTrust Quality and Technology Co., Ltd.
Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

TEL: +86-755-2823 0888

FAX: +86-755-2823 0886

Prepared by: David Chen
 David Chen
 Senior Project Engineer

Reviewed by: Henry Lu
 Henry Lu
 Team Leader

Approved by: Robben Chen
 Robben Chen
 Assistant Manager

Date: June 5, 2024

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Version

| Version No. | Date | Description |
|-------------|--------------|-------------|
| V1.0 | June 5, 2024 | Original |

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com<http://www.uttlab.com>

UTTR-RF-FCC23G-V1.1

CONTENTS

- 1. GENERAL INFORMATION4**
- 1.1 CLIENT INFORMATION4**
- 1.2 EUT INFORMATION4**
 - 1.2.1 GENERAL DESCRIPTION OF EUT4
 - 1.2.2 DESCRIPTION OF ACCESSORIES.....5
- 1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD6**
- 1.4 DESCRIPTION OF SUPPORT UNITS7**
- 1.5 TEST LOCATION.....7**
- 1.6 TEST FACILITY.....7**
- 1.7 DEVIATION FROM STANDARDS7**
- 1.8 ABNORMALITIES FROM STANDARD CONDITIONS.....7**
- 1.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER7**
- 1.10 MEASUREMENT UNCERTAINTY8**
- 2. TEST SUMMARY9**
- 3. EQUIPMENT LIST11**
- 4. TEST CONFIGURATION12**
 - 4.1 ENVIRONMENTAL CONDITIONS FOR TESTING12**
 - 4.2 TEST SETUP13**
 - 4.2.1 FOR RADIATED EMISSIONS TEST SETUP13
 - 4.2.2 FOR CONDUCTED RF TEST SETUP14
 - 4.3 TEST CHANNELS15**
 - 4.4 SYSTEM TEST CONFIGURATION15**
 - 4.5 PRE-SCAN.....16**
- 5. RADIO TECHNICAL REQUIREMENTS SPECIFICATION18**
 - 5.1 REFERENCE DOCUMENTS FOR TESTING18**
 - 5.2 MAXIMUM ERP/EIRP18**
 - 5.3 CONDUCTED OUTPUT POWER20**
 - 5.4 PEAK-TO-AVERAGE RATIO21**
 - 5.5 99%&26dB BANDWIDTH.....22**
 - 5.6 BAND EDGE AT ANTENNA TERMINALS23**
 - 5.7 SPURIOUS EMISSIONS AT ANTENNA TERMINALS24**
 - 5.8 FIELD STRENGTH OF SPURIOUS RADIATION.....25**
 - 5.9 FREQUENCY STABILITY30**
- APPENDIX A RF TEST DATA.....31**
 - A.1 GSM 850.....31**
 - A.2 PCS 190039**
 - A.3 WCDMA BAND II/ BAND IV/ BAND V47**
- APPENDIX 1 PHOTOS OF TEST SETUP55**
- APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS55**

1. GENERAL INFORMATION

1.1 CLIENT INFORMATION

| | |
|---------------------------------|---|
| Applicant: | BLU Products, Inc. |
| Address of Applicant: | 8600 NW 36th Street, Suite #300 Miami, FL 33166 |
| Manufacturer: | BLU Products, Inc. |
| Address of Manufacturer: | 8600 NW 36th Street, Suite #300 Miami, FL 33166 |

1.2 EUT INFORMATION

1.2.1 General Description of EUT

| | | | | |
|---|--|---|----------------------------|--|
| Product Name: | Smart Phone | | | |
| Model No.: | K10 | | | |
| Add. Model No.: | G54 | | | |
| Trade Mark: | BOLD, BLU | | | |
| DUT Stage: | Identical Prototype | | | |
| EUT Supports Function: (Provided by the customer) | GSM Bands: | GSM850/PCS 1900 | | |
| | UTRA Bands: | WCDMA Band II/ Band IV/ Band V | | |
| | E-UTRA Bands: | FDD Band 2/ Band 4/ Band 5/ Band 7/ Band 12/ / Band 13/ Band 17/ Band 66/ Band 71 | | |
| | 2.4 GHz ISM Band: | IEEE 802.11b/g/n | | |
| | | Bluetooth 5.0 | | |
| | 5 GHz U-NII Bands: | 5 150 MHz to 5 250 MHz | IEEE 802.11a/n/ac | |
| | | 5 250 MHz to 5 350 MHz | IEEE 802.11a/n/ac | |
| | | 5 470 MHz to 5 725 MHz | IEEE 802.11a/n/ac | |
| | | 5 725 MHz to 5 850 MHz | IEEE 802.11a/n/ac | |
| | RNSS Band: | 1559 MHz to 1610 MHz | BDS/ Galileo/ GPS/ GLONASS | |
| BSR: | VHF Band II | FM | | |
| Software Version: | BOLD_K0110_V13.0.03.01_GENERIC 28-04-2024 23:21(Provided by the customer) | | | |
| Hardware Version: | KE15Z_02A (Provided by the customer) | | | |
| Sample Received Date: | April 7, 2024 | | | |
| Sample Tested Date: | April 7, 2024 to May 20, 2024 | | | |
| Note: | The additional model G54 is identical with the test model K10 except the model number for marketing purpose. | | | |

Remark:

The above EUT's information was provided by customer. Please refer to the specifications or user's manual for more detailed description.

1.2.2 Description of Accessories

| Adapter | |
|------------|-----------------------------------|
| Model No.: | US-HJ-2024 |
| Input: | 100-240 V~50/60 Hz 0.3 A |
| Output: | 5.0 V \Rightarrow 2000 mA 10.0W |

| Cable | |
|-------------|----------------------------|
| Connector: | USB Cable |
| Cable Type: | Unshielded without ferrite |
| Length: | 1.0 Meter |

| Battery | |
|-------------------|-----------------------------|
| Model No.: | C906548500P |
| Battery Type: | Lithium-ion Polymer Battery |
| Rated Voltage: | 3.87 Vdc |
| Typical Capacity: | 5000 mAh |
| Rated Capacity: | 4900 mAh |

| Earphone | |
|----------|-----------|
| | 1.2 Meter |

1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD

| | | |
|--|--------------------------------------|-------------------|
| Support Networks: | GSM, GPRS, EDGE, WCDMA, HSDPA, HSUPA | |
| Type of Modulation: | GSM/GPRS: | GMSK |
| | EDGE: | GMSK, 8PSK |
| | WCDMA | BPSK |
| | HSDPA: | QPSK |
| | HSUPA: | QPSK |
| Frequency Range: | GSM/GPRS/EDGE 850: | 824.2-848.8 MHz |
| | GSM/GPRS/EDGE 1900: | 1850.2-1909.8 MHz |
| | WCDMA Band II: | 1852.4-1907.6 MHz |
| | WCDMA Band IV: | 1712.4-1752.6 MHz |
| | WCDMA Band V: | 826.4-846.6 MHz |
| Max RF Output Power (ERP/EIRP): | GSM/GPRS 850: | 27.28 dBm |
| | EDGE 850: | 20.59 dBm |
| | GSM/GPRS 1900: | 28.38 dBm |
| | EDGE 1900: | 25.76 dBm |
| | WCDMA Band II: | 21.49 dBm |
| | WCDMA Band IV: | 21.46 dBm |
| | WCDMA Band V: | 17.21 dBm |
| Emission Designator: | GSM/GPRS 850: | 243KGXW |
| | EDGE 850: | 243KG7W |
| | GSM/GPRS 1900: | 244KGXW |
| | EDGE 1900: | 245KG7W |
| | WCDMA Band II: | 4M17F9W |
| | WCDMA Band IV: | 4M17F9W |
| | WCDMA Band V: | 4M16F9W |
| Antenna Type: (Provided by the customer) | PIFA Antenna | |
| Antenna Gain: (Provided by the customer) | GSM 850: | -3.7 dBi |
| | PCS 1900: | -1.2 dBi |
| | WCDMA Band II: | -1.2 dBi |
| | WCDMA Band IV: | -1.4 dBi |
| | WCDMA Band V: | -3.7 dBi |
| GPRS/EDGE Class: | Class 12 | |
| Sample No.: | Radiated: S202404073065-ZJA01/6 | |
| | Conducted: S202404073065-ZJA05/6 | |
| Normal Test Voltage: | 3.87 Vdc | |
| Extreme Test Voltage: | 3.4 to 4.45Vdc | |
| Extreme Test Temperature: | -20 °C to +60 °C | |

1.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested with associated equipment below.

1) Support Equipment

| Description | Manufacturer | Model No. | Serial Number | Supplied by |
|-------------|--------------|-----------|---------------|-------------|
| -- | -- | -- | -- | -- |

2) Support Cable

| Cable No. | Description | Connector | Length | Supplied by |
|-----------|---------------|-----------|-----------|-------------|
| 1 | Antenna Cable | SMA | 0.1 Meter | Applicant |

1.5 TEST LOCATION

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China 518109

Telephone: +86 (0) 755 2823 0888

Fax: +86 (0) 755 2823 0886

1.6 TEST FACILITY

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L9069

The measuring equipment utilized to perform the tests documented in this report has been calibrated once a year or in accordance with the manufacturer's recommendations, and is traceable under the ISO/IEC 17025 to international or national standards. Equipment has been calibrated by accredited calibration laboratories.

A2LA-Lab Certificate No.: 4312.01

Shenzhen UnionTrust Quality and Technology Co., Ltd. has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

ISED Wireless Device Testing Laboratories

CAB identifier: CN0032

FCC Accredited Lab.

Designation Number: CN1194

Test Firm Registration Number: 259480

1.7 DEVIATION FROM STANDARDS

None.

1.8 ABNORMALITIES FROM STANDARD CONDITIONS

None.

1.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCC23G-V1.1

None.

1.10 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

| No. | Item | Measurement Uncertainty |
|-----|---|--|
| 1 | Conducted Output Power | ±0.7 dB |
| 2 | 99%&26dB Bandwidth | ±1.86 % |
| 3 | Emission Mask | ±2.7 dBm |
| 4 | Spurious emissions at antenna terminals | ±2.7 dBm |
| 5 | Field strength of spurious radiation | 30 MHz-1 GHz: ±4.9 dB 1 GHz-18 GHz: ±4.8 dB 18 GHz-40 GHz: ±5.1 dB |
| 6 | Frequency stability | ±6.5 x 10 ⁻⁸ |
| 7 | Humidity | ±3.9 % |
| 8 | Temperature | ±0.62 °C |
| 9 | DC Voltages | ±0.68 % |

2. TEST SUMMARY

| FCC 47 CFR Part 22 Subpart H Test Cases | | | |
|---|---|---|--------|
| Test Item | Test Requirement | Test Method | Result |
| Effective Radiated Power (ERP) | FCC 47 CFR Part 2.1046(a) & FCC 47 CFR Part 22.913(a) | ANSI C63.26-2015 & KDB 971168 D01v03r01 | PASS |
| Conducted Output Power | FCC 47 CFR Part 2.1046(a) & FCC 47 CFR Part 22.913(a) | ANSI C63.26-2015 & KDB 971168 D01v03r01 | PASS |
| Peak-to-average ratio | FCC 47 CFR Part 22.913(a) | ANSI C63.26-2015 & KDB 971168 D01v03r01 | PASS |
| 99%&26dB Bandwidth | FCC 47 CFR Part 2.1049(h) | ANSI C63.26-2015 & KDB 971168 D01v03r01 | PASS |
| Band Edge at antenna terminals | FCC 47 CFR Part 2.1051 & FCC 47 CFR Part 22.917(a) | ANSI C63.26-2015 & KDB 971168 D01v03r01 | PASS |
| Spurious emissions at antenna terminals | FCC 47 CFR Part 2.1051 & FCC 47 CFR Part 22.917(a)(b) | ANSI C63.26-2015 & KDB 971168 D01v03r01 | PASS |
| Field strength of spurious radiation | FCC 47 CFR Part 2.1053 & FCC 47 CFR Part 22.917(a)(b) | ANSI C63.26-2015 & KDB 971168 D01v03r01 | PASS |
| Frequency stability | FCC 47 CFR Part 2.1055 & FCC 47 CFR Part 22.355 | ANSI C63.26-2015 & KDB 971168 D01v03r01 | PASS |

| FCC 47 CFR Part 24 Subpart E Test Cases | | | |
|--|---|---|--------|
| Test Item | Test Requirement | Test Method | Result |
| Equivalent Isotropic Radiated Power (EIRP) | FCC 47 CFR Part 2.1046(a) & FCC 47 CFR Part 24.232(c) | ANSI C63.26-2015 & KDB 971168 D01v03r01 | PASS |
| Conducted Output Power | FCC 47 CFR Part 2.1046(a) & FCC 47 CFR Part 24.232(c) | ANSI C63.26-2015 & KDB 971168 D01v03r01 | PASS |
| Peak-to-average ratio | FCC 47 CFR Part 24.232(d) | KDB 971168 D01v03r01 | PASS |
| 99%&26dB Bandwidth | FCC 47 CFR Part 2.1049(h) & FCC 47 CFR Part 24.238(b) | ANSI C63.26-2015 & KDB 971168 D01v03r01 | PASS |
| Band Edge at antenna terminals | FCC 47 CFR Part 2.1051 & FCC 47 CFR Part 24.238(a) | ANSI C63.26-2015 & KDB 971168 D01v03r01 | PASS |
| Spurious emissions at antenna terminals | FCC 47 CFR Part 2.1051 & FCC 47 CFR Part 24.238(a)(b) | ANSI C63.26-2015 & KDB 971168 D01v03r01 | PASS |
| Field strength of spurious radiation | FCC 47 CFR Part 2.1053 & FCC 47 CFR Part 24.238(a)(b) | ANSI C63.26-2015 & KDB 971168 D01v03r01 | PASS |
| Frequency stability | FCC 47 CFR Part 2.1055 & FCC 47 CFR Part 24.235 | ANSI C63.26-2015 & KDB 971168 D01v03r01 | PASS |

| FCC 47 CFR Part 27 Subpart L Test Cases | | | |
|--|---|---|--------|
| Test Item | Test Requirement | Test Method | Result |
| Equivalent Isotropic Radiated Power (EIRP) | FCC 47 CFR Part 2.1046(a) & FCC 47 CFR Part 27.50(d)(4) | ANSI C63.26-2015 & KDB 971168 D01v03r01 | PASS |
| Conducted Output Power | FCC 47 CFR Part 2.1046(a) & FCC 47 CFR Part 27.50(d)(4) | ANSI C63.26-2015 & KDB 971168 D01v03r01 | PASS |
| Peak-to-average ratio | FCC 47 CFR Part 27.50(d)(5) | KDB 971168 D01v03r01 | PASS |
| 99%&26dB Bandwidth | FCC 47 CFR Part 2.1049(h) & FCC 47 CFR Part 27.53(h) | ANSI C63.26-2015 & KDB 971168 D01v03r01 | PASS |
| Band Edge at antenna terminals | FCC 47 CFR Part 27.53(h)(1) | ANSI C63.26-2015 & KDB 971168 D01v03r01 | PASS |
| Spurious emissions at antenna terminals | FCC 47 CFR Part 2.1051 & FCC 47 CFR Part 27.53(h) | ANSI C63.26-2015 & KDB 971168 D01v03r01 | PASS |
| Field strength of spurious radiation | FCC 47 CFR Part 2.1053 & FCC 47 CFR Part 27.53(h) | ANSI C63.26-2015 & KDB 971168 D01v03r01 | PASS |
| Frequency stability | FCC 47 CFR Part 2.1055 & FCC 47 CFR Part 27.54 | ANSI C63.26-2015 & KDB 971168 D01v03r01 | PASS |

Disclaimer and Explanations:

The declared of product specification and data (e.g. antenna gain, RF specification, etc) for EUT presented in the report are provided by the customer, and the customer takes all the responsibilities for the accuracy of product specification.

3. EQUIPMENT LIST

| Radiated Emission Test Equipment List | | | | | | |
|---------------------------------------|--|--------------|------------|----------------------------|-------------|---------------|
| Used | Equipment | Manufacturer | Model No. | Serial Number | Cal. date | Cal. Due date |
| <input checked="" type="checkbox"/> | 3m SAC | ETS-LINDGREN | 3M | Euroshiedpn-CT001270-1317 | 11-Nov-2023 | 10-Nov-2026 |
| <input checked="" type="checkbox"/> | Receiver | R&S | ESIB26 | 100114 | 27-Oct-2023 | 26-Oct-2024 |
| <input checked="" type="checkbox"/> | EXA Spectrum Analyzer | KEYSIGHT | N9010A | MY51440197 | 29-Mar-2024 | 28-Mar-2025 |
| <input checked="" type="checkbox"/> | Broadband Antenna | ETS-LINDGREN | 3142E | 00201566 | 30-Oct-2023 | 29-Oct-2024 |
| <input checked="" type="checkbox"/> | 6dB Attenuator | Talent | RA6A5-N-18 | 18103001 | 30-Oct-2023 | 29-Oct-2024 |
| <input checked="" type="checkbox"/> | Preamplifier | HP | 8447F | 2805A02960 | 31-Oct-2023 | 30-Oct-2024 |
| <input checked="" type="checkbox"/> | Double-Ridged Waveguide Horn Antenna (Pre-amplifier) | ETS-LINDGREN | 3117-PA | 00201541 | 1-Apr-2024 | 31-Mar-2025 |
| <input checked="" type="checkbox"/> | Pre-amplifier | ETS-Lindgren | 00118385 | 00201874 | 1-Apr-2024 | 31-Mar-2025 |
| <input checked="" type="checkbox"/> | Double-Ridged Waveguide Horn Antenna (Pre-amplifier) | ETS-LINDGREN | 3116C-PA | 00202652 | 30-Oct-2023 | 29-Oct-2024 |
| <input checked="" type="checkbox"/> | Pre-amplifier | ETS-Lindgren | 00118384 | 00202652 | 30-Oct-2023 | 29-Oct-2024 |
| <input checked="" type="checkbox"/> | Multi device Controller | ETS-LINDGREN | 7006-001 | 00160105 | N/A | N/A |
| <input checked="" type="checkbox"/> | Test Software | Audix | e3 | Software Version: 9.160323 | | |

| RF Conducted Test Equipment List | | | | | | |
|-------------------------------------|-------------------------------------|--------------|-----------|----------------|-------------|---------------|
| Used | Equipment | Manufacturer | Model No. | Serial Number | Cal. date | Cal. Due date |
| <input checked="" type="checkbox"/> | EXA Signal Analyzer | KEYSIGHT | N9010B | MY62060155 | 29-Mar-2024 | 28-Mar-2025 |
| <input checked="" type="checkbox"/> | DC Source | KIKUSUI | PWR400L | LK003024 | N/A | N/A |
| <input checked="" type="checkbox"/> | Digital multimeter | FLUKE | 15B+ | 30701460WS15 | 31-Oct-2023 | 30-Oct-2024 |
| <input checked="" type="checkbox"/> | Temp & Humidity chamber | Votisch | VT4002 | 58566133290020 | 29-Mar-2024 | 28-Mar-2025 |
| <input checked="" type="checkbox"/> | Wideband Radio Communication Tester | R&S | CMW500 | 119583 | 29-Mar-2024 | 28-Mar-2025 |
| <input checked="" type="checkbox"/> | Wideband Radio Communication Tester | R&S | CMW500 | 120932 | 29-Mar-2024 | 28-Mar-2025 |

4. TEST CONFIGURATION

4.1 ENVIRONMENTAL CONDITIONS FOR TESTING


| Test Environment | Selected Values During Tests | | |
|------------------|------------------------------|-------------|-----------------------|
| Test Condition | Ambient | | |
| | Temperature (°C) | Voltage (V) | Relative Humidity (%) |
| TN/VN | +15 to +35 | 3.87 | 20 to 75 |
| TL/VL | -20 | 3.4 | 20 to 75 |
| TH/VL | +60 | 3.4 | 20 to 75 |
| TL/VH | -20 | 4.45 | 20 to 75 |
| TH/VH | +60 | 4.45 | 20 to 75 |

Remark:


- 1) The EUT just work in such extreme temperature of -20 °C to +60 °C and the extreme voltage of 3.4 V to 4.45 V, so here the EUT is tested in the temperature of -20 °C to +60 °C and the voltage of 3.4 V to 4.45 V.
- 2) VN: Normal Voltage; TN: Normal Temperature;
 TL: Low Extreme Test Temperature; TH: High Extreme Test Temperature;
 VL: Low Extreme Test Voltage; VH: High Extreme Test Voltage.

4.2 TEST SETUP

4.2.1 For Radiated Emissions test setup



4.2.2 For Conducted RF test setup



4.3 TEST CHANNELS

| Bands | Tx/Rx Frequency | RF Channel | | |
|----------------------|---------------------------|--------------|--------------|--------------|
| | | Low(L) | Middle(M) | High(H) |
| GSM/GPRS/ EDGE850 | Tx (824 MHz ~ 849 MHz) | Channel 128 | Channel 190 | Channel 251 |
| | | 824.2 MHz | 836.6 MHz | 848.8 MHz |
| WCDMA band V | Tx (824 MHz ~ 849 MHz) | Channel 4132 | Channel 4182 | Channel 4233 |
| | | 826.4 MHz | 836.4 MHz | 846.6 MHz |

| Bands | Tx/Rx Frequency | RF Channel | | |
|-----------------------|---------------------------|--------------|--------------|--------------|
| | | Low(L) | Middle(M) | High(H) |
| GSM/GPRS/ EDGE1900 | Tx (1850 MHz-1910 MHz) | Channel 512 | Channel 661 | Channel 810 |
| | | 1850.2 MHz | 1880.0 MHz | 1909.8 MHz |
| WCDMA Band II | Tx (1850 MHz-1910 MHz) | Channel 9262 | Channel 9400 | Channel 9538 |
| | | 1852.4 MHz | 1880.0 MHz | 1907.6 MHz |

| Bands | Tx/Rx Frequency | RF Channel | | |
|---------------|---------------------------|--------------|--------------|--------------|
| | | Low(L) | Middle(M) | High(H) |
| WCDMA Band IV | Tx (1710 MHz-1755 MHz) | Channel 1312 | Channel 1412 | Channel 1513 |
| | | 1712.4 MHz | 1732.4 MHz | 1752.6 MHz |

4.4 SYSTEM TEST CONFIGURATION

For emissions testing, the equipment under test (EUT) setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, radiated emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario. It was powered by a 3.87Vdc battery. Only the worst case data were recorded in this test report.

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, X/Y/Z axis, and antenna ports.

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000MHz. The resolution is 1 MHz or greater for frequencies above 1000MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

Radiated emission measurement were performed from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

4.5 PRE-SCAN

Pre-scan under all rate at lowest middle and highest channel, find the transmitter power as below:
SIM 1 Card Conducted transmitter power measurement result.

| GSM 850 Maximum Average Power (dBm) | | | |
|-------------------------------------|-----------|-----------|--------------|
| Channel | 128 | 190 | 251 |
| Frequency(MHz) | 824.2 MHz | 836.6 MHz | 848.8 MHz |
| GSM (GMSK, 1Tx-slot) | 33.07 | 33.06 | 33.13 |
| GPRS (GMSK, 1Tx-slot) | 33.04 | 33.05 | 33.13 |
| GPRS (GMSK, 2Tx-slot) | 30.97 | 31.02 | 31.10 |
| GPRS (GMSK, 3Tx-slot) | 29.10 | 29.19 | 29.30 |
| GPRS (GMSK, 4Tx-slot) | 27.04 | 27.12 | 27.22 |
| EDGE (8PSK, 1Tx-slot) | 25.91 | 25.74 | 26.44 |
| EDGE (8PSK, 2Tx-slot) | 24.30 | 23.93 | 24.74 |
| EDGE (8PSK, 3Tx-slot) | 22.45 | 22.59 | 22.95 |
| EDGE (8PSK, 4Tx-slot) | 19.68 | 19.71 | 20.01 |

| PCS 1900 Maximum Average Power (dBm) | | | |
|--------------------------------------|--------------|------------|------------|
| Channel | 512 | 661 | 810 |
| Frequency(MHz) | 1850.2 MHz | 1880.0 MHz | 1909.8 MHz |
| GSM (GMSK, 1Tx-slot) | 29.58 | 29.52 | 29.48 |
| GPRS (GMSK, 1Tx-slot) | 29.56 | 29.52 | 29.48 |
| GPRS (GMSK, 2Tx-slot) | 27.42 | 27.42 | 27.38 |
| GPRS (GMSK, 3Tx-slot) | 25.91 | 25.89 | 25.88 |
| GPRS (GMSK, 4Tx-slot) | 23.92 | 23.90 | 23.89 |
| EDGE (8PSK, 1Tx-slot) | 26.96 | 26.74 | 26.81 |
| EDGE (8PSK, 2Tx-slot) | 25.52 | 25.22 | 25.08 |
| EDGE (8PSK, 3Tx-slot) | 22.50 | 22.85 | 21.59 |
| EDGE (8PSK, 4Tx-slot) | 20.03 | 19.58 | 19.78 |

| WCDMA Band II Maximum Average Power (dBm) | | | |
|---|------------|--------------|------------|
| Channel | 9262 | 9400 | 9538 |
| Frequency (MHz) | 1852.4 MHz | 1880.0 MHz | 1907.6 MHz |
| RMC 12.2K | 22.64 | 22.69 | 22.56 |
| HSDPA Subtest-1 | 22.01 | 22.17 | 21.99 |
| HSDPA Subtest-2 | 21.74 | 21.86 | 21.68 |
| HSDPA Subtest-3 | 21.53 | 21.66 | 21.48 |
| HSDPA Subtest-4 | 21.53 | 21.55 | 21.34 |
| HSUPA Subtest-1 | 21.75 | 21.82 | 21.56 |
| HSUPA Subtest-2 | 21.87 | 21.98 | 21.75 |
| HSUPA Subtest-3 | 22.00 | 22.07 | 21.80 |
| HSUPA Subtest-4 | 21.84 | 21.95 | 21.71 |
| HSUPA Subtest-5 | 21.97 | 22.15 | 21.86 |

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCC23G-V1.1

| WCDMA Band IV Maximum Average Power (dBm) | | | |
|---|------------|------------|------------|
| Channel | 1312 | 1412 | 1513 |
| Frequency (MHz) | 1712.4 MHz | 1732.4 MHz | 1752.6 MHz |
| RMC 12.2K | 22.86 | 22.84 | 22.83 |
| HSDPA Subtest-1 | 22.16 | 22.25 | 22.29 |
| HSDPA Subtest-2 | 22.30 | 22.38 | 22.34 |
| HSDPA Subtest-3 | 22.23 | 22.34 | 22.25 |
| HSDPA Subtest-4 | 22.16 | 22.27 | 22.16 |
| HSUPA Subtest-1 | 21.93 | 22.02 | 21.78 |
| HSUPA Subtest-2 | 22.07 | 22.16 | 22.10 |
| HSUPA Subtest-3 | 22.07 | 22.21 | 22.13 |
| HSUPA Subtest-4 | 22.03 | 22.20 | 22.09 |
| HSUPA Subtest-5 | 22.18 | 22.25 | 22.16 |

| WCDMA Band V Maximum Average Power (dBm) | | | |
|--|-----------|-----------|-----------|
| Channel | 4132 | 4182 | 4233 |
| Frequency (MHz) | 826.4 MHz | 836.4 MHz | 846.6 MHz |
| RMC 12.2K | 23.06 | 23.03 | 23.05 |
| HSDPA Subtest-1 | 21.86 | 21.81 | 21.83 |
| HSDPA Subtest-2 | 21.59 | 21.53 | 21.74 |
| HSDPA Subtest-3 | 21.29 | 21.10 | 20.99 |
| HSDPA Subtest-4 | 21.17 | 21.12 | 20.99 |
| HSUPA Subtest-1 | 22.31 | 22.32 | 22.53 |
| HSUPA Subtest-2 | 22.68 | 22.60 | 22.80 |
| HSUPA Subtest-3 | 22.70 | 22.62 | 22.81 |
| HSUPA Subtest-4 | 22.66 | 22.53 | 22.75 |
| HSUPA Subtest-5 | 22.08 | 22.06 | 22.08 |

Pre-scan all bandwidth and RB, find worse case mode are chosen to the report, the worse mode applicability and tested channel detail as below:

| Band | Radiated | Conducted |
|------------------------|--|---|
| GSM/GPRS/EDGE 850/1900 | 1) GSM (GMSK, 1Tx-slot) Link 2) GPRS (GMSK, 1Tx-slot) Link 3) EDGE (8PSK, 1Tx-slot) Link | 1) GSM (GMSK,1Tx-slot) Link 2) GPRS (GMSK, 1Tx-slot) Link 3) EDGE (8PSK, 1Tx-slot) Link |
| WCDMA Band II/IV/V | RMC 12.2kbps Link | RMC 12.2kbps Link |

5. RADIO TECHNICAL REQUIREMENTS SPECIFICATION

5.1 REFERENCE DOCUMENTS FOR TESTING

| No. | Identity | Document Title |
|-----|--|--|
| 1 | FCC 47 CFR Part 2 | Frequency allocations and radio treaty matters; general rules and regulations |
| 2 | FCC 47 CFR Part 22 | Public Mobile Services |
| 3 | FCC 47 CFR Part 27 | Miscellaneous Wireless Communications Services |
| 4 | FCC 47 CFR Part 24 | Personal Communications Services |
| 5 | ANSI C63.26-2015 | American National Standard for Compliance Testing of Transmitters Used in Licensed Radio Services |
| 6 | KDB 971168 D01 | KDB 971168 D01 Power Meas License Digital Systems v03r01 |
| 7 | KDB 412172 D01 Determining ERP and EIRP v01r01 | Guidelines for determining the effective radiated power (ERP) and isotropically radiated power (EIRP) of an RF transmitting system |

5.2 MAXIMUM ERP/EIRP

Test Requirement: FCC 47 CFR Part 2.1046(a),
 FCC 47 CFR Part 22.913(a),
 FCC 47 CFR Part 24.232(c),
 FCC 47 CFR Part 27.50(d)(4)

Test Method: KDB 971168 D01v03r01 Section 5.6 & ANSI C63.26-2015

Limit:

FCC 47 CFR Part 22.913(a)

The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts.

FCC 47 CFR Part 24.232(c)

Mobile and portable stations are limited to 2 watts EIRP.

FCC 47 CFR Part 27.50(d)(4)

Fixed, mobile, and portable (hand-held) stations operating in the 1710-1755 MHz band and mobile and portable stations operating in the 1695-1710 MHz and 1755-1780 MHz bands are limited to 1 watt EIRP.

Test Procedure:

According to KDB 412172 D01 Power Approach,

- **ERP or EIRP = P_T + G_T - L_C**
- **ERP = EIRP -2.15**

where

- **P_T** = transmitter output power, expressed in dBW, dBm, or PSD;
- **G_T** = gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP);
- **L_C** = signal attenuation in the connecting cable between the transmitter and antenna, in dB.

Test Setup: Refer to section 4.2.1 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Link mode

Test Results: Pass

Test Data: See table below

| Band | | Ant. Gain (dBi) | Maximum ERP/EIRP (dBm) | | | | Maximum ERP/EIRP (W) | | | | Result |
|----------|-------|-----------------|------------------------|-------|-------|-------------|----------------------|--------|--------|-----------|--------|
| | | | Low | Mid | High | Limit (dBm) | Low | Mid | High | Limit (W) | |
| PCS 1900 | GSM | -1.2 | 28.38 | 28.32 | 28.28 | 33.01 | 0.6887 | 0.6792 | 0.6730 | 2 | Pass |
| | GPRS | | 28.36 | 28.32 | 28.28 | 33.01 | 0.6855 | 0.6792 | 0.6730 | 2 | Pass |
| | EGPRS | | 25.76 | 25.54 | 25.61 | 33.01 | 0.3767 | 0.3581 | 0.3639 | 2 | Pass |
| GSM 850 | GSM | -3.7 | 27.22 | 27.21 | 27.28 | 38.45 | 0.5272 | 0.5260 | 0.5346 | 7 | Pass |
| | GPRS | | 27.19 | 27.20 | 27.28 | 38.45 | 0.5236 | 0.5248 | 0.5346 | 7 | Pass |
| | EGPRS | | 20.06 | 19.89 | 20.59 | 38.45 | 0.1014 | 0.0975 | 0.1146 | 7 | Pass |

| Band | | Ant. Gain (dBi) | Maximum ERP/EIRP (dBm) | | | | Maximum ERP/EIRP (W) | | | | Result |
|---------------|-----------|-----------------|------------------------|-------|-------|-------------|----------------------|--------|--------|-----------|--------|
| | | | Low | Mid | High | Limit (dBm) | Low | Mid | High | Limit (W) | |
| WCDMA Band II | RMC 12.2K | -1.2 | 21.44 | 21.49 | 21.36 | 33.01 | 0.1393 | 0.1409 | 0.1368 | 2 | Pass |
| | HSDPA | | 20.81 | 20.97 | 20.79 | 33.01 | 0.1205 | 0.1250 | 0.1199 | 2 | Pass |
| | HSUPA | | 20.80 | 20.95 | 20.66 | 33.01 | 0.1202 | 0.1245 | 0.1164 | 2 | Pass |
| WCDMA Band IV | RMC 12.2K | -1.4 | 21.46 | 21.44 | 21.43 | 30 | 0.1400 | 0.1393 | 0.1390 | 1 | Pass |
| | HSDPA | | 20.90 | 20.98 | 20.94 | 30 | 0.1230 | 0.1253 | 0.1242 | 1 | Pass |
| | HSUPA | | 20.78 | 20.85 | 20.76 | 30 | 0.1197 | 0.1216 | 0.1191 | 1 | Pass |
| WCDMA Band V | RMC 12.2K | -3.7 | 17.21 | 17.18 | 17.20 | 38.45 | 0.0526 | 0.0522 | 0.0525 | 7 | Pass |
| | HSDPA | | 16.01 | 15.96 | 15.98 | 38.45 | 0.0399 | 0.0394 | 0.0396 | 7 | Pass |
| | HSUPA | | 16.85 | 16.77 | 16.96 | 38.45 | 0.0484 | 0.0475 | 0.0497 | 7 | Pass |

Note: The maximum ERP/EIRP is calculated from max output power and antenna gain, the antenna gain provided by the customer, and the customer takes all the responsibilities for the accuracy of antenna gain.

5.3 CONDUCTED OUTPUT POWER

Test Requirement: FCC 47 CFR Part 2.1046(a),
FCC 47 CFR Part 22.913(a),
FCC 47 CFR Part 24.232(c),
FCC 47 CFR Part 27.50(d)(4)

Test Method: KDB 971168 D01v03r01 & ANSI C63.26-2015

Limit:

FCC 47 CFR Part 22.913(a)

The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts.

FCC 47 CFR Part 24.232(c)

Mobile and portable stations are limited to 2 watts EIRP.

FCC 47 CFR Part 27.50(d)(4)

Fixed, mobile, and portable (hand-held) stations operating in the 1710-1755 MHz band and mobile and portable stations operating in the 1695-1710 MHz and 1755-1780 MHz bands are limited to 1 watt EIRP.

Test Procedure:

The EUT was set up for the maximum power with GSM, GPRS, EDGE, WCDMA, CDMA2000, and LTE link data modulation and link up with simulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.2.2 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Link mode

Test Results: Pass

Test Data: The full result refer to section 4.5 for details.

5.4 PEAK-TO-AVERAGE RATIO

Test Requirement: FCC 47 CFR Part 22.913(a),
FCC 47 CFR Part 24.232(c),
FCC 47 CFR Part 27.50(d)(5)

Test Method: KDB 971168 D01v03r01 Section 5.7

Limit: In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB

Test Procedure:

The transmitter output was connected to a calibrated coaxial cable and coupler, the other end of which was connected to a spectrum analyzer.

- a) Set resolution/measurement bandwidth \geq signal's occupied bandwidth
- b) Set the number of counts to a value that stabilizes the measured CCDF curve
- c) Record the maximum PAPR level associated with a probability of 0.1 %

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.2.2 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Link mode

Test Results: Pass

Test Data: Please refer to Appendix A

5.599%&26DB BANDWIDTH

Test Requirement: FCC 47 CFR Part 2.1049(h),
FCC 47 CFR Part 22.917(b),
FCC 47 CFR Part 24.238(b),
FCC 47 CFR Part 27.53(h)

Test Method: ANSI C63.26-2015 & KDB 971168 D01v03r01 Section 4

Limit: No Limit, for reporting purposes only.

Test Procedure:
The transmitter output was connected to a calibrated coaxial cable and coupler, the other end of which was connected to a spectrum analyzer. The occupied bandwidth was measured with the spectrum analyzer at the low, middle and high channel in each band. The 99% and -26dB bandwidths was also measured and recorded.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.2.2 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Link mode

Test Results: Pass

Test Data: Please refer to Appendix A

5.6 BAND EDGE AT ANTENNA TERMINALS

Test Requirement: FCC 47 CFR Part 2.1051,
 FCC 47 CFR Part 22.917(a),
 FCC 47 CFR Part 24.238(a),
 FCC 47 CFR Part 27.53(h)(1)

Test Method: ANSI C63.26-2015 & KDB 971168 D01v03r01

Limit:

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13 dBm.

Test Procedure:

The transmitter output was connected to a calibrated coaxial cable and coupler, the other end of which was connected to a spectrum analyzer.

For each band edge measurement:

- 1) Set the spectrum analyzer span to include the block edge frequency.
- 2) Set a marker to point the corresponding band edge frequency in each test case.
- 3) Set display line at -13 dBm
- 4) Set resolution bandwidth to at least 1% of emission bandwidth.
- 5) Set spectrum analyzer with RMS detector.
- 6) Record the max trace plot into the test report

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.2.2 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Link mode

Test Results: Please refer to Appendix A

5.7 SPURIOUS EMISSIONS AT ANTENNA TERMINALS

Test Requirement: FCC 47 CFR Part 2.1051,
 FCC 47 CFR Part 22.917(a)(b),
 FCC 47 CFR Part 24.238(a)(b),
 FCC 47 CFR Part 27.53(h)(1)

Test Method: ANSI C63.26-2015 & KDB 971168 D01v03r01

Limit:
 The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13 dBm.

Test Procedure:
 The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range. b. Measuring frequency range is from 30 MHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower. Set RBW & VBW to 100 kHz for the measurement below 1 GHz, and 1 MHz for the measurement above 1 GHz.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.2.2 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Link mode

Test Results: **Please refer to Appendix A**

5.8 FIELD STRENGTH OF SPURIOUS RADIATION

Test Requirement: FCC 47 CFR Part 2.1053,
 FCC 47 CFR Part 22.917(a)(b),
 FCC 47 CFR Part 24.238(a)(b),
 FCC 47 CFR Part 27.53(h)(1)

Test Method: ANSI C63.26-2015 & KDB 971168 D01v03r01 Section 7

Limits:

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB. The emission limit equal to -13 dBm.

Test Setup: Refer to section 4.2.1 for details.

Test Procedures: KDB 971168 D01v03r01 Section 7

Equipment Used: Refer to section 3 for details.

Test Result: Pass

The worst measurement data as follows:

| GSM 850 | | | | | | | |
|------------------------|-----------|------------|-------------------|-------------|--------|--------|------------|
| No. | Frequency | SA Reading | Correction factor | EIRP Result | Limit | Margin | Ant. Pol. |
| | (MHz) | (dBm) | (dB/m) | (dBm) | (dBm) | (dB) | |
| Lowest Channel | | | | | | | |
| 1 | 754.963 | -86.58 | 40.87 | -45.71 | -13.00 | -32.71 | Horizontal |
| 2 | 776.485 | -86.32 | 41.14 | -45.18 | -13.00 | -32.18 | Horizontal |
| 3 | 992.997 | -86.66 | 44.47 | -42.19 | -13.00 | -29.19 | Horizontal |
| 4 | 1648.400 | -51.48 | 0.79 | -50.69 | -13.00 | -37.69 | Horizontal |
| 5 | 2472.600 | -54.29 | 4.70 | -49.59 | -13.00 | -36.59 | Horizontal |
| 6 | 776.485 | -87.02 | 41.14 | -45.88 | -13.00 | -32.88 | Vertical |
| 7 | 958.714 | -86.54 | 43.89 | -42.65 | -13.00 | -29.65 | Vertical |
| 8 | 1000.000 | -85.97 | 44.50 | -41.47 | -13.00 | -28.47 | Vertical |
| 9 | 1648.400 | -55.10 | 0.79 | -54.31 | -13.00 | -41.31 | Vertical |
| 10 | 2472.600 | -51.56 | 4.70 | -46.86 | -13.00 | -33.86 | Vertical |
| Middle Channel | | | | | | | |
| 1 | 809.924 | -86.80 | 42.08 | -44.72 | -13.00 | -31.72 | Horizontal |
| 2 | 906.304 | -86.97 | 43.57 | -43.40 | -13.00 | -30.40 | Horizontal |
| 3 | 992.997 | -86.66 | 44.47 | -42.19 | -13.00 | -29.19 | Horizontal |
| 4 | 1673.200 | -55.09 | 0.88 | -54.21 | -13.00 | -41.21 | Horizontal |
| 5 | 2509.800 | -49.75 | 4.90 | -44.85 | -13.00 | -31.85 | Horizontal |
| 6 | 906.304 | -86.31 | 43.57 | -42.74 | -13.00 | -29.74 | Vertical |
| 7 | 925.613 | -86.37 | 43.47 | -42.90 | -13.00 | -29.90 | Vertical |
| 8 | 958.714 | -86.71 | 43.89 | -42.82 | -13.00 | -29.82 | Vertical |
| 9 | 1673.200 | -53.19 | 0.88 | -52.31 | -13.00 | -39.31 | Vertical |
| 10 | 2497.244 | -46.07 | 4.88 | -41.19 | -13.00 | -28.19 | Vertical |
| Highest Channel | | | | | | | |
| 1 | 637.795 | -86.99 | 39.10 | -47.89 | -13.00 | -34.89 | Horizontal |
| 2 | 787.475 | -86.69 | 41.53 | -45.16 | -13.00 | -32.16 | Horizontal |
| 3 | 925.613 | -86.93 | 43.47 | -43.46 | -13.00 | -30.46 | Horizontal |
| 4 | 1697.600 | -46.20 | 0.97 | -45.23 | -13.00 | -32.23 | Horizontal |
| 5 | 2546.400 | -50.15 | 4.94 | -45.21 | -13.00 | -32.21 | Horizontal |
| 6 | 598.707 | -87.35 | 38.31 | -49.04 | -13.00 | -36.04 | Vertical |
| 7 | 798.620 | -87.19 | 41.73 | -45.46 | -13.00 | -32.46 | Vertical |
| 8 | 938.714 | -85.39 | 43.51 | -41.88 | -13.00 | -28.88 | Vertical |
| 9 | 1697.600 | -57.59 | 0.97 | -56.62 | -13.00 | -43.62 | Vertical |
| 10 | 2546.400 | -42.03 | 4.94 | -37.09 | -13.00 | -24.09 | Vertical |

| PCS 1900 | | | | | | | |
|------------------------|-----------|------------|-------------------|-------------|--------|--------|------------|
| No. | Frequency | SA Reading | Correction factor | EIRP Result | Limit | Margin | Ant. Pol. |
| | (MHz) | (dBm) | (dB/m) | (dBm) | (dBm) | (dB) | |
| Lowest Channel | | | | | | | |
| 1 | 844.803 | -80.21 | 13.42 | -66.79 | -13.00 | -53.79 | Horizontal |
| 2 | 899.958 | -80.26 | 14.32 | -65.94 | -13.00 | -52.94 | Horizontal |
| 3 | 986.044 | -80.85 | 15.44 | -65.41 | -13.00 | -52.41 | Horizontal |
| 4 | 3700.400 | -64.31 | 8.94 | -55.37 | -13.00 | -42.37 | Horizontal |
| 5 | 5550.600 | -64.11 | 12.43 | -51.68 | -13.00 | -38.68 | Horizontal |
| 6 | 637.795 | -79.33 | 9.66 | -69.67 | -13.00 | -56.67 | Vertical |
| 7 | 945.334 | -81.24 | 14.69 | -66.55 | -13.00 | -53.55 | Vertical |
| 8 | 979.139 | -81.19 | 15.25 | -65.94 | -13.00 | -52.94 | Vertical |
| 9 | 3700.400 | -64.42 | 8.94 | -55.48 | -13.00 | -42.48 | Vertical |
| 10 | 5550.600 | -66.10 | 12.43 | -53.67 | -13.00 | -40.67 | Vertical |
| Middle Channel | | | | | | | |
| 1 | 793.028 | -79.56 | 12.44 | -67.12 | -13.00 | -54.12 | Horizontal |
| 2 | 838.887 | -79.56 | 13.30 | -66.26 | -13.00 | -53.26 | Horizontal |
| 3 | 992.997 | -80.50 | 15.56 | -64.94 | -13.00 | -51.94 | Horizontal |
| 4 | 3760.000 | -62.78 | 9.14 | -53.64 | -13.00 | -40.64 | Horizontal |
| 5 | 5640.000 | -62.83 | 12.33 | -50.50 | -13.00 | -37.50 | Horizontal |
| 6 | 713.692 | -79.30 | 11.53 | -67.77 | -13.00 | -54.77 | Vertical |
| 7 | 739.214 | -79.16 | 11.58 | -67.58 | -13.00 | -54.58 | Vertical |
| 8 | 979.139 | -80.36 | 15.25 | -65.11 | -13.00 | -52.11 | Vertical |
| 9 | 3760.000 | -63.54 | 9.14 | -54.40 | -13.00 | -41.40 | Vertical |
| 10 | 5640.000 | -64.10 | 12.33 | -51.77 | -13.00 | -38.77 | Vertical |
| Highest Channel | | | | | | | |
| 1 | 798.620 | -80.18 | 12.53 | -67.65 | -13.00 | -54.65 | Horizontal |
| 2 | 912.695 | -81.27 | 14.49 | -66.78 | -13.00 | -53.78 | Horizontal |
| 3 | 965.474 | -81.40 | 14.91 | -66.49 | -13.00 | -53.49 | Horizontal |
| 4 | 3819.600 | -65.70 | 9.34 | -56.36 | -13.00 | -43.36 | Horizontal |
| 5 | 5729.400 | -63.84 | 12.23 | -51.61 | -13.00 | -38.61 | Horizontal |
| 6 | 787.475 | -78.87 | 12.31 | -66.56 | -13.00 | -53.56 | Vertical |
| 7 | 906.304 | -80.48 | 14.53 | -65.95 | -13.00 | -52.95 | Vertical |
| 8 | 979.139 | -81.59 | 15.25 | -66.34 | -13.00 | -53.34 | Vertical |
| 9 | 3819.600 | -63.39 | 9.34 | -54.05 | -13.00 | -41.05 | Vertical |
| 10 | 5729.400 | -65.32 | 12.23 | -53.09 | -13.00 | -40.09 | Vertical |

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: Unit D/E of 9/F and 16/F, Block A, Building 6, Baoneng science and technology park, Longhua district, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

<http://www.uttlab.com>

UTTR-RF-FCC23G-V1.1

| WCDMA Band II | | | | | | | |
|---------------------------------------|-----------|------------|-------------------|-------------|--------|--------|------------|
| No. | Frequency | SA Reading | Correction factor | EIRP Result | Limit | Margin | Ant. Pol. |
| | (MHz) | (dBm) | (dB/m) | (dBm) | (dBm) | (dB) | |
| RMC 12.2kbps _ Lowest Channel | | | | | | | |
| 1 | 793.028 | -79.35 | 12.44 | -66.91 | -13.00 | -53.91 | Horizontal |
| 2 | 821.387 | -79.62 | 13.20 | -66.42 | -13.00 | -53.42 | Horizontal |
| 3 | 862.802 | -79.62 | 13.74 | -65.88 | -13.00 | -52.88 | Horizontal |
| 4 | 3704.8 | -65.78 | 8.95 | -56.83 | -13.00 | -43.83 | Horizontal |
| 5 | 5557.2 | -66.60 | 12.43 | -54.17 | -13.00 | -41.17 | Horizontal |
| 6 | 868.886 | -80.11 | 13.80 | -66.31 | -13.00 | -53.31 | Vertical |
| 7 | 925.613 | -80.77 | 14.46 | -66.31 | -13.00 | -53.31 | Vertical |
| 8 | 986.044 | -81.05 | 15.44 | -65.61 | -13.00 | -52.61 | Vertical |
| 9 | 3704.8 | -65.21 | 8.95 | -56.26 | -13.00 | -43.26 | Vertical |
| 10 | 5557.2 | -67.47 | 12.43 | -55.04 | -13.00 | -42.04 | Vertical |
| RMC 12.2kbps _ Middle Channel | | | | | | | |
| 1 | 856.76 | -80.81 | 13.67 | -67.14 | -13.00 | -54.14 | Horizontal |
| 2 | 887.398 | -80.58 | 14.17 | -66.41 | -13.00 | -53.41 | Horizontal |
| 3 | 938.714 | -80.84 | 14.52 | -66.32 | -13.00 | -53.32 | Horizontal |
| 4 | 3760 | -64.78 | 9.14 | -55.64 | -13.00 | -42.64 | Horizontal |
| 5 | 5640 | -67.70 | 12.33 | -55.37 | -13.00 | -42.37 | Horizontal |
| 6 | 862.802 | -80.73 | 13.74 | -66.99 | -13.00 | -53.99 | Vertical |
| 7 | 899.958 | -81.05 | 14.32 | -66.73 | -13.00 | -53.73 | Vertical |
| 8 | 972.283 | -81.29 | 15.04 | -66.25 | -13.00 | -53.25 | Vertical |
| 9 | 3760 | -64.62 | 9.14 | -55.48 | -13.00 | -42.48 | Vertical |
| 10 | 5640 | -67.59 | 12.33 | -55.26 | -13.00 | -42.26 | Vertical |
| RMC 12.2kbps _ Highest Channel | | | | | | | |
| 1 | 771.047 | -80.57 | 11.94 | -68.63 | -13.00 | -55.63 | Horizontal |
| 2 | 827.179 | -80.88 | 13.16 | -67.72 | -13.00 | -54.72 | Horizontal |
| 3 | 919.132 | -80.16 | 14.53 | -65.63 | -13.00 | -52.63 | Horizontal |
| 4 | 3815.2 | -63.27 | 9.32 | -53.95 | -13.00 | -40.95 | Horizontal |
| 5 | 5722.8 | -68.03 | 12.25 | -55.78 | -13.00 | -42.78 | Horizontal |
| 6 | 815.635 | -80.73 | 13.04 | -67.69 | -13.00 | -54.69 | Vertical |
| 7 | 868.886 | -80.89 | 13.80 | -67.09 | -13.00 | -54.09 | Vertical |
| 8 | 1000.000 | -81.17 | 15.60 | -65.57 | -13.00 | -52.57 | Vertical |
| 9 | 3815.2 | -62.35 | 9.32 | -53.03 | -13.00 | -40.03 | Vertical |
| 10 | 5722.8 | -67.68 | 12.25 | -55.43 | -13.00 | -42.43 | Vertical |

| WCDMA Band IV | | | | | | | |
|--------------------------------------|-----------|------------|-------------------|-------------|--------|--------|------------|
| No. | Frequency | SA Reading | Correction factor | EIRP Result | Limit | Margin | Ant. Pol. |
| | (MHz) | (dBm) | (dB/m) | (dBm) | (dBm) | (dB) | |
| RMC 12.2kbps_ Lowest Channel | | | | | | | |
| 1 | 708.694 | -79.99 | 11.44 | -68.55 | -13.00 | -55.55 | Horizontal |
| 2 | 754.963 | -79.98 | 11.60 | -68.38 | -13.00 | -55.38 | Horizontal |
| 3 | 912.695 | -80.92 | 14.49 | -66.43 | -13.00 | -53.43 | Horizontal |
| 4 | 3424.8 | -63.39 | 7.74 | -55.65 | -13.00 | -42.65 | Horizontal |
| 5 | 5137.2 | -65.55 | 11.35 | -54.20 | -13.00 | -41.20 | Horizontal |
| 6 | 833.013 | -80.28 | 13.24 | -67.04 | -13.00 | -54.04 | Vertical |
| 7 | 875.013 | -80.40 | 13.93 | -66.47 | -13.00 | -53.47 | Vertical |
| 8 | 919.132 | -80.98 | 14.53 | -66.45 | -13.00 | -53.45 | Vertical |
| 9 | 3424.8 | -64.10 | 7.74 | -56.36 | -13.00 | -43.36 | Vertical |
| 10 | 5137.2 | -66.42 | 11.35 | -55.07 | -13.00 | -42.07 | Vertical |
| RMC 12.2kbps_ Middle Channel | | | | | | | |
| 1 | 602.929 | -79.50 | 8.92 | -70.58 | -13.00 | -57.58 | Horizontal |
| 2 | 787.475 | -80.63 | 12.31 | -68.32 | -13.00 | -55.32 | Horizontal |
| 3 | 906.304 | -81.40 | 14.53 | -66.87 | -13.00 | -53.87 | Horizontal |
| 4 | 3464.8 | -63.21 | 7.96 | -55.25 | -13.00 | -42.25 | Horizontal |
| 5 | 5197.2 | -66.41 | 11.45 | -54.96 | -13.00 | -41.96 | Horizontal |
| 6 | 713.692 | -79.53 | 11.53 | -68.00 | -13.00 | -55.00 | Vertical |
| 7 | 776.485 | -79.62 | 11.90 | -67.72 | -13.00 | -54.72 | Vertical |
| 8 | 856.76 | -79.89 | 13.67 | -66.22 | -13.00 | -53.22 | Vertical |
| 9 | 3464.8 | -63.02 | 7.96 | -55.06 | -13.00 | -42.06 | Vertical |
| 10 | 5197.2 | -65.49 | 11.45 | -54.04 | -13.00 | -41.04 | Vertical |
| RMC 12.2kbps_ Highest Channel | | | | | | | |
| 1 | 821.387 | -79.65 | 13.20 | -66.45 | -13.00 | -53.45 | Horizontal |
| 2 | 868.886 | -79.22 | 13.80 | -65.42 | -13.00 | -52.42 | Horizontal |
| 3 | 945.334 | -79.67 | 14.69 | -64.98 | -13.00 | -51.98 | Horizontal |
| 4 | 3505.2 | -63.08 | 8.17 | -54.91 | -13.00 | -41.91 | Horizontal |
| 5 | 5257.8 | -65.01 | 11.65 | -53.36 | -13.00 | -40.36 | Horizontal |
| 6 | 703.731 | -80.01 | 11.46 | -68.55 | -13.00 | -55.55 | Vertical |
| 7 | 821.387 | -80.52 | 13.20 | -67.32 | -13.00 | -54.32 | Vertical |
| 8 | 958.714 | -80.34 | 14.93 | -65.41 | -13.00 | -52.41 | Vertical |
| 9 | 3505.2 | -64.33 | 8.17 | -56.16 | -13.00 | -43.16 | Vertical |
| 10 | 5257.8 | -64.63 | 11.65 | -52.98 | -13.00 | -39.98 | Vertical |

| WCDMA Band V | | | | | | | |
|---------------------------------------|-----------|------------|-------------------|-------------|--------|--------|------------|
| No. | Frequency | SA Reading | Correction factor | EIRP Result | Limit | Margin | Ant. Pol. |
| | (MHz) | (dBm) | (dB/m) | (dBm) | (dBm) | (dB) | |
| RMC 12.2kbps _ Lowest Channel | | | | | | | |
| 1 | 739.214 | -87.30 | 40.87 | -46.43 | -13.00 | -33.43 | Horizontal |
| 2 | 793.028 | -86.40 | 41.65 | -44.75 | -13.00 | -31.75 | Horizontal |
| 3 | 925.613 | -86.34 | 43.47 | -42.87 | -13.00 | -29.87 | Horizontal |
| 4 | 2479.2 | -60.15 | 4.75 | -55.40 | -13.00 | -42.40 | Horizontal |
| 5 | 3305.6 | -55.54 | 7.17 | -48.37 | -13.00 | -35.37 | Horizontal |
| 6 | 611.462 | -87.34 | 38.60 | -48.74 | -13.00 | -35.74 | Vertical |
| 7 | 669.952 | -87.22 | 39.73 | -47.49 | -13.00 | -34.49 | Vertical |
| 8 | 952.000 | -86.20 | 43.79 | -42.41 | -13.00 | -29.41 | Vertical |
| 9 | 2479.2 | -60.52 | 4.75 | -55.77 | -13.00 | -42.77 | Vertical |
| 10 | 3296.8 | -58.82 | 7.12 | -51.70 | -13.00 | -38.70 | Vertical |
| RMC 12.2kbps _ Middle Channel | | | | | | | |
| 1 | 718.725 | -87.43 | 40.83 | -46.60 | -13.00 | -33.60 | Horizontal |
| 2 | 804.252 | -87.09 | 41.94 | -45.15 | -13.00 | -32.15 | Horizontal |
| 3 | 958.714 | -86.68 | 43.89 | -42.79 | -13.00 | -29.79 | Horizontal |
| 4 | 2509.2 | -62.32 | 4.90 | -57.42 | -13.00 | -44.42 | Horizontal |
| 5 | 3345.6 | -56.02 | 7.36 | -48.66 | -13.00 | -35.66 | Horizontal |
| 6 | 684.226 | -87.20 | 40.19 | -47.01 | -13.00 | -34.01 | Vertical |
| 7 | 862.802 | -87.14 | 42.85 | -44.29 | -13.00 | -31.29 | Vertical |
| 8 | 912.695 | -86.73 | 43.52 | -43.21 | -13.00 | -30.21 | Vertical |
| 9 | 2509.2 | -60.85 | 4.90 | -55.95 | -13.00 | -42.95 | Vertical |
| 10 | 3345.6 | -58.03 | 7.36 | -50.67 | -13.00 | -37.67 | Vertical |
| RMC 12.2kbps _ Highest Channel | | | | | | | |
| 1 | 523.876 | -87.68 | 37.10 | -50.58 | -13.00 | -37.58 | Horizontal |
| 2 | 887.398 | -86.82 | 43.24 | -43.58 | -13.00 | -30.58 | Horizontal |
| 3 | 992.997 | -87.52 | 44.47 | -43.05 | -13.00 | -30.05 | Horizontal |
| 4 | 2539.8 | -61.63 | 4.93 | -56.70 | -13.00 | -43.70 | Horizontal |
| 5 | 3386.4 | -58.78 | 7.56 | -51.22 | -13.00 | -38.22 | Horizontal |
| 6 | 35.762 | -82.20 | 31.76 | -50.44 | -13.00 | -37.44 | Vertical |
| 7 | 703.731 | -87.58 | 40.80 | -46.78 | -13.00 | -33.78 | Vertical |
| 8 | 804.252 | -86.95 | 41.94 | -45.01 | -13.00 | -32.01 | Vertical |
| 9 | 2539.8 | -62.36 | 4.93 | -57.43 | -13.00 | -44.43 | Vertical |
| 10 | 3386.4 | -59.76 | 7.56 | -52.20 | -13.00 | -39.20 | Vertical |

Remark:

1. Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain, the value was added to Original Receiver Reading by the software automatically.
2. Result = Reading + Correct Factor.
3. Margin = Result - Limit

5.9 FREQUENCY STABILITY

Test Requirement: FCC 47 CFR Part 2.1055 &
FCC 47 CFR Part 22.355 &
FCC 47 CFR Part 24.235 &
FCC 47 CFR Part 27.54

Test Method: ANSI C63.26-2015 & KDB 971168 D01v03r01

Limits:

FCC 47 CFR Part 22.355,

The carrier frequency shall not depart from the reference frequency in excess of ± 2.5 ppm for mobile stations.

FCC 47 CFR Part 24.235, FCC 47 CFR Part 27.54

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

Test Setup: Refer to section 4.2.2 for details.

Test Procedures:

- 1) Use CMW 500 with Frequency Error measurement capability.
 - a) Temp. = -30° to $+50^{\circ}$ C
 - b) Voltage = low voltage, 3.4 Vdc, Normal, 3.87 Vdc and High voltage, 4.45 Vdc.

- 2) Frequency Stability vs Temperature:

The EUT is placed inside a temperature chamber. The temperature is set to 20° C and allowed to stabilize.

After sufficient soak time, the transmitting frequency error is measured. The temperature is increased by 10 degrees, allowed to stabilize and soak, and then the measurement is repeated. This is repeated until $+50^{\circ}$ C is reached.

- 3) Frequency Stability vs Voltage:

The peak frequency error is recorded (worst-case).

Equipment Used: Refer to section 3 for details.

Test Results: Please refer to Appendix A

APPENDIX A RF TEST DATA

A.1 GSM 850

Frequency Stability

| Band | Channel | Freq (MHz) | Deviation (Hz) | Deviation (ppm) | Limit(ppm) | Verdict | Environment |
|---------|---------|------------|----------------|-----------------|------------|---------|-------------|
| GSM 850 | 190 | 836.6 | -12.72 | -0.01521 | ±2.5 | PASS | VL |
| GSM 850 | 190 | 836.6 | -13.88 | -0.01659 | ±2.5 | PASS | VN |
| GSM 850 | 190 | 836.6 | -11.43 | -0.01366 | ±2.5 | PASS | VH |
| GSM 850 | 190 | 836.6 | -9.07 | -0.01084 | ±2.5 | PASS | -30°C |
| GSM 850 | 190 | 836.6 | -12.17 | -0.01455 | ±2.5 | PASS | -20°C |
| GSM 850 | 190 | 836.6 | -11.4 | -0.01362 | ±2.5 | PASS | -10°C |
| GSM 850 | 190 | 836.6 | -12.43 | -0.01486 | ±2.5 | PASS | 0°C |
| GSM 850 | 190 | 836.6 | -8.94 | -0.01069 | ±2.5 | PASS | 10°C |
| GSM 850 | 190 | 836.6 | -11.56 | -0.01382 | ±2.5 | PASS | 20°C |
| GSM 850 | 190 | 836.6 | -9.65 | -0.01154 | ±2.5 | PASS | 30°C |
| GSM 850 | 190 | 836.6 | -9.72 | -0.01162 | ±2.5 | PASS | 40°C |
| GSM 850 | 190 | 836.6 | -8.2 | -0.0098 | ±2.5 | PASS | 50°C |

Frequency Stability EGPRS


| Band | Channel | Freq (MHz) | Slots | Deviation (Hz) | Deviation (ppm) | Limit(ppm) | Verdict | Environment |
|---------|---------|------------|-------|----------------|-----------------|------------|---------|-------------|
| GSM 850 | 190 | 836.6 | 1 Tx | -0.97 | -0.00116 | ±2.5 | PASS | VL |
| GSM 850 | 190 | 836.6 | 1 Tx | -5.13 | -0.00614 | ±2.5 | PASS | VN |
| GSM 850 | 190 | 836.6 | 1 Tx | 0.68 | 0.00081 | ±2.5 | PASS | VH |
| GSM 850 | 190 | 836.6 | 1 Tx | 0.32 | 0.00039 | ±2.5 | PASS | -30°C |
| GSM 850 | 190 | 836.6 | 1 Tx | -0.84 | -0.001 | ±2.5 | PASS | -20°C |
| GSM 850 | 190 | 836.6 | 1 Tx | 1.58 | 0.00189 | ±2.5 | PASS | -10°C |
| GSM 850 | 190 | 836.6 | 1 Tx | 0.32 | 0.00038 | ±2.5 | PASS | 0°C |
| GSM 850 | 190 | 836.6 | 1 Tx | -1.49 | -0.00178 | ±2.5 | PASS | 10°C |
| GSM 850 | 190 | 836.6 | 1 Tx | -1.13 | -0.00135 | ±2.5 | PASS | 20°C |
| GSM 850 | 190 | 836.6 | 1 Tx | 1.81 | 0.00216 | ±2.5 | PASS | 30°C |
| GSM 850 | 190 | 836.6 | 1 Tx | 1.0 | 0.0012 | ±2.5 | PASS | 40°C |
| GSM 850 | 190 | 836.6 | 1 Tx | -0.71 | -0.00085 | ±2.5 | PASS | 50°C |

Peak to Average Ratio


| Band | Channel | Freq (MHz) | Slots | Result (dB) | Limit (dB) | Verdict |
|-----------|---------|------------|-------|-------------|------------|---------|
| GSM 850 | 190 | 836.6 | 1 Tx | 0.11 | 13 | PASS |
| GSM 850 | 251 | 848.8 | 1 Tx | 0.11 | 13 | PASS |
| GSM 850 | 128 | 824.2 | 1 Tx | 0.11 | 13 | PASS |
| GPRS 850 | 190 | 836.6 | 1 Tx | 0.11 | 13 | PASS |
| GPRS 850 | 251 | 848.8 | 1 Tx | 0.11 | 13 | PASS |
| GPRS 850 | 128 | 824.2 | 1 Tx | 0.10 | 13 | PASS |
| EGPRS 850 | 190 | 836.6 | 1 Tx | 6.17 | 13 | PASS |
| EGPRS 850 | 251 | 848.8 | 1 Tx | 5.55 | 13 | PASS |
| EGPRS 850 | 128 | 824.2 | 1 Tx | 6.53 | 13 | PASS |

Test Graphs


GSM850_Channel190




GSM850_Channel251




GSM850_Channel128




GPRS850_Channel190




GPRS850_Channel251




GPRS850_Channel128




EGPRS850_Channel190



EGPRS850_Channel251



EGPRS850_Channel128



Occupied Bandwidth

| Band | Channel | Freq (MHz) | Slots | OBW (MHz) | 26dB BW (MHz) |
|-----------|---------|------------|-------|-----------|---------------|
| GSM 850 | 128 | 824.2 | 1 Tx | 0.24255 | 0.3156 |
| GSM 850 | 190 | 836.6 | 1 Tx | 0.24203 | 0.3105 |
| GSM 850 | 251 | 848.8 | 1 Tx | 0.24229 | 0.3093 |
| GPRS 850 | 190 | 836.6 | 1 Tx | 0.24342 | 0.3148 |
| GPRS 850 | 251 | 848.8 | 1 Tx | 0.24319 | 0.3154 |
| GPRS 850 | 128 | 824.2 | 1 Tx | 0.24289 | 0.3159 |
| EGPRS 850 | 190 | 836.6 | 1 Tx | 0.23423 | 0.3112 |
| EGPRS 850 | 251 | 848.8 | 1 Tx | 0.23651 | 0.3035 |
| EGPRS 850 | 128 | 824.2 | 1 Tx | 0.24277 | 0.315 |

Test Graphs

GSM850_Channel128




GSM850_Channel190



GSM850_Channel251



GPRS850_Channel190



GPRS850_Channel251



GPRS850_Channel128




EGPRS850_Channel190



EGPRS850_Channel251



EGPRS850_Channel128




Conducted Spurious Emissions


| Band | Channel | Freq (MHz) | Slots | Result (dBm) | Limit (dBm) | Verdict |
|-----------|---------|------------|-------|--------------|-------------|---------|
| GSM 850 | 128 | 824.2 | 1 Tx | -29.93 | -13 | PASS |
| GSM 850 | 190 | 836.6 | 1 Tx | -29.72 | -13 | PASS |
| GSM 850 | 251 | 848.8 | 1 Tx | -29.5 | -13 | PASS |
| GPRS 850 | 190 | 836.6 | 1 Tx | -30.01 | -13 | PASS |
| GPRS 850 | 251 | 848.8 | 1 Tx | -29.86 | -13 | PASS |
| GPRS 850 | 128 | 824.2 | 1 Tx | -30.05 | -13 | PASS |
| EGPRS 850 | 128 | 824.2 | 1 Tx | -29.65 | -13 | PASS |
| EGPRS 850 | 251 | 848.8 | 1 Tx | -29.96 | -13 | PASS |
| EGPRS 850 | 190 | 836.6 | 1 Tx | -29.12 | -13 | PASS |

Test Graphs


GSM850_Channel128




GSM850_Channel190



GSM850_Channel251




GPRS850_Channel190



GPRS850_Channel251



GPRS850_Channel128




EGPRS850_Channel128



EGPRS850_Channel251



EGPRS850_Channel190



Conducted Band Edge


| Band | Channel | Freq (MHz) | Slots | Result | Verdict |
|-----------|---------|------------|-------|-----------|---------|
| GSM 850 | 128 | 824.2 | 1 Tx | see graph | PASS |
| GSM 850 | 251 | 848.8 | 1 Tx | see graph | PASS |
| GPRS 850 | 251 | 848.8 | 1 Tx | see graph | PASS |
| GPRS 850 | 128 | 824.2 | 1 Tx | see graph | PASS |
| EGPRS 850 | 251 | 848.8 | 1 Tx | see graph | PASS |
| EGPRS 850 | 128 | 824.2 | 1 Tx | see graph | PASS |

Test Graphs

GSM850_Channel128



GSM850_Channel251



GPRS850_Channel251



GPRS850_Channel128



EGPRS850_Channel251



EGPRS850_Channel128



A.2 PCS 1900

Frequency Stability

| Band | Channel | Freq (MHz) | Deviation (Hz) | Deviation (ppm) | Limit(ppm) | Verdict | Environment |
|----------|---------|------------|----------------|-----------------|------------|---------|-------------|
| PCS 1900 | 661 | 1880.0 | 0.32 | 0.00017 | ±2.5 | PASS | VL |
| PCS 1900 | 661 | 1880.0 | 0.32 | 0.00017 | ±2.5 | PASS | VN |
| PCS 1900 | 661 | 1880.0 | 5.62 | 0.00299 | ±2.5 | PASS | VH |
| PCS 1900 | 661 | 1880.0 | 11.36 | 0.00605 | ±2.5 | PASS | -30°C |
| PCS 1900 | 661 | 1880.0 | 13.69 | 0.00728 | ±2.5 | PASS | -20°C |
| PCS 1900 | 661 | 1880.0 | 13.27 | 0.00706 | ±2.5 | PASS | -10°C |
| PCS 1900 | 661 | 1880.0 | 17.21 | 0.00915 | ±2.5 | PASS | 0°C |
| PCS 1900 | 661 | 1880.0 | 4.36 | 0.00232 | ±2.5 | PASS | 10°C |
| PCS 1900 | 661 | 1880.0 | -3.2 | -0.0017 | ±2.5 | PASS | 20°C |
| PCS 1900 | 661 | 1880.0 | 10.85 | 0.00577 | ±2.5 | PASS | 30°C |
| PCS 1900 | 661 | 1880.0 | 12.4 | 0.00659 | ±2.5 | PASS | 40°C |
| PCS 1900 | 661 | 1880.0 | 5.59 | 0.00297 | ±2.5 | PASS | 50°C |


| Band | Channel | Freq (MHz) | Slots | Deviation (Hz) | Deviation (ppm) | Limit(ppm) | Verdict | Environment |
|----------|---------|------------|-------|----------------|-----------------|------------|---------|-------------|
| PCS 1900 | 661 | 1880.0 | 1 Tx | -999.99 | -0.53191 | ±2.5 | PASS | VL |
| PCS 1900 | 661 | 1880.0 | 1 Tx | -999.99 | -0.53191 | ±2.5 | PASS | VN |
| PCS 1900 | 661 | 1880.0 | 1 Tx | -999.99 | -0.53191 | ±2.5 | PASS | VH |
| PCS 1900 | 661 | 1880.0 | 1 Tx | -999.99 | -0.53191 | ±2.5 | PASS | -30°C |
| PCS 1900 | 661 | 1880.0 | 1 Tx | -999.99 | -0.53191 | ±2.5 | PASS | -20°C |
| PCS 1900 | 661 | 1880.0 | 1 Tx | -999.99 | -0.53191 | ±2.5 | PASS | -10°C |
| PCS 1900 | 661 | 1880.0 | 1 Tx | -999.99 | -0.53191 | ±2.5 | PASS | 0°C |
| PCS 1900 | 661 | 1880.0 | 1 Tx | -999.99 | -0.53191 | ±2.5 | PASS | 10°C |
| PCS 1900 | 661 | 1880.0 | 1 Tx | -999.99 | -0.53191 | ±2.5 | PASS | 20°C |
| PCS 1900 | 661 | 1880.0 | 1 Tx | -999.99 | -0.53191 | ±2.5 | PASS | 30°C |
| PCS 1900 | 661 | 1880.0 | 1 Tx | -999.99 | -0.53191 | ±2.5 | PASS | 40°C |
| PCS 1900 | 661 | 1880.0 | 1 Tx | -999.99 | -0.53191 | ±2.5 | PASS | 50°C |

Peak to Average Ratio

| Band | Channel | Freq (MHz) | Slots | Result (dB) | Limit (dB) | Verdict |
|------------|---------|------------|-------|-------------|------------|---------|
| PCS 1900 | 661 | 1880.0 | 1 Tx | 0.10 | 13 | PASS |
| PCS 1900 | 810 | 1909.8 | 1 Tx | 0.11 | 13 | PASS |
| PCS 1900 | 512 | 1850.2 | 1 Tx | 0.10 | 13 | PASS |
| GPRS 1900 | 661 | 1880.0 | 1 Tx | 0.11 | 13 | PASS |
| GPRS 1900 | 810 | 1909.8 | 1 Tx | 0.11 | 13 | PASS |
| GPRS 1900 | 512 | 1850.2 | 1 Tx | 0.10 | 13 | PASS |
| EGPRS 1900 | 661 | 1880.0 | 1 Tx | 3.24 | 13 | PASS |
| EGPRS 1900 | 810 | 1909.8 | 1 Tx | 3.39 | 13 | PASS |
| EGPRS 1900 | 512 | 1850.2 | 1 Tx | 3.16 | 13 | PASS |

Test Graphs


PCS1900_Channel661




PCS1900_Channel810




PCS1900_Channel512



GPRS1900_Channel661



GPRS1900_Channel810



GPRS1900_Channel512

