

# TEST REPORT

**Reference No.**..... : WTX24X04087264W001  
**FCC ID**..... : YHLBLUK50K  
**Applicant**..... : BLU Products, Inc.  
**Address**..... : 8600 NW 36th Street, Suite #300 | Miami, FL 33166, USA  
**Manufacturer**..... : The same as Applicant  
**Address**..... : The same as Applicant  
**Product Name**..... : Smart Phone  
**Model No.**..... : K50  
**Standards**..... : FCC Part 22H, FCC Part 24E, FCC Part 27  
**Date of Receipt sample**..... : 2024-04-18  
**Date of Test**..... : 2024-04-18 to 2024-06-04  
**Date of Issue**..... : 2024-06-04  
**Test Report Form No.**..... : WTX\_Part 22\_Part 24\_Part 27W  
**Test Result**..... : **Pass**

Remarks:


The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of approver.

**Prepared By:**

**Waltek Testing Group (Shenzhen) Co., Ltd.**

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,  
Block 70 Bao'an District, Shenzhen, Guangdong, China  
Tel.: +86-755-33663308 Fax.: +86-755-33663309 Email: sem@waltek.com.cn

Tested by:



Mike Shi

Approved by:



Jason Su

**TABLE OF CONTENTS**

**1. GENERAL INFORMATION..... 4**  
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) ..... 4  
1.2 TEST STANDARDS .....7  
1.3 TEST METHODOLOGY .....7  
1.4 TEST FACILITY ..... 7  
1.5 EUT SETUP AND TEST MODE ..... 8  
1.6 MEASUREMENT UNCERTAINTY ..... 10  
1.7 TEST EQUIPMENT LIST AND DETAILS ..... 11

**2. SUMMARY OF TEST RESULTS .....14**

**3. RF OUTPUT POWER..... 15**  
3.1 STANDARD APPLICABLE ..... 15  
3.2 TEST PROCEDURE ..... 15  
3.3 SUMMARY OF TEST RESULTS/PLOTS ..... 15

**4. PEAK-TO-AVERAGE RATIO (PAR) OF TRANSMITTER..... 19**  
4.1 STANDARD APPLICABLE ..... 19  
4.2 TEST PROCEDURE ..... 19  
4.3 SUMMARY OF TEST RESULTS ..... 19

**5. EMISSION BANDWIDTH ..... 20**  
5.1 STANDARD APPLICABLE ..... 20  
5.2 TEST PROCEDURE ..... 20  
5.3 SUMMARY OF TEST RESULTS/PLOTS ..... 20

**6. OUT OF BAND EMISSIONS AT ANTENNA TERMINAL ..... 21**  
6.1 STANDARD APPLICABLE ..... 21  
6.2 TEST PROCEDURE ..... 21  
6.3 SUMMARY OF TEST RESULTS/PLOTS ..... 21

**7. SPURIOUS RADIATED EMISSIONS ..... 22**  
7.1 STANDARD APPLICABLE ..... 22  
7.2 TEST PROCEDURE ..... 22  
7.3 SUMMARY OF TEST RESULTS/PLOTS ..... 22

**8. FREQUENCY STABILITY ..... 36**  
8.1 STANDARD APPLICABLE ..... 36  
8.2 TEST PROCEDURE ..... 36  
8.3 SUMMARY OF TEST RESULTS/PLOTS ..... 36

**9. MODULATION CHARACTERISTICS ..... 37**  
9.1 STANDARD APPLICABLE ..... 37  
9.2 TEST PROCEDURE ..... 37  
9.3 SUMMARY OF TEST RESULTS/PLOTS ..... 37

**APPENDIX PHOTOGRAPHS ..... 38**

**Report version**

Version No.	Date of issue	Description
Rev.00	2024-06-04	Original
/	/	/

## 1. GENERAL INFORMATION

---

### 1.1 Product Description for Equipment Under Test (EUT)

General Description of EUT:	
Product Name:	Smart Phone
Trade Name:	BOLD
Model No.:	K50
Adding Model(s):	/
Rated Voltage:	DC3.87V
Battery Capacity:	5000mAh (C886351500P)
Adapter Model:	US-HJ-3024Q Input:AC100-240v~50/60Hz 0.8A Output:DC5V3000mA; OR DC9V3000mA; OR DC12V2750mA
<i>The test data is gathered from a production sample provided by the manufacturer.</i>	

<b>Technical Characteristics of EUT:</b>	
<b>2G</b>	
Support Networks:	GSM, GPRS, EDGE
Support Band:	GSM850/PCS1900
Uplink Frequency:	GSM/GPRS/EDGE 850: 824~849MHz GSM/GPRS/EDGE 1900: 1850~1910MHz
Downlink Frequency:	GSM/GPRS/EDGE 850: 869~894MHz GSM/GPRS/EDGE 1900: 1930~1990MHz
Max RF Output Power:	GSM850: 32.86dBm, GSM1900: 29.89dBm EDGE850: 26.50dBm, EDGE1900: 24.91dBm
Max RF Output Power(Hotspot ON):	GSM1900: 26.97dBm, GPRS1900: 26.67dBm EGPRS1900: 24.62dBm
Type of Emission:	GSM850: 246KGXW, GSM1900: 245KGXW EDGE850: 247KG7W, EDGE1900: 246KG7W
Type of Modulation:	GMSK, 8PSK
Type of Antenna:	Integral Antenna
Antenna Gain:	GSM850: -3.7dBi; GSM1900: -1.5dBi
GPRS/EDGE Class:	Class 12
<b>3G</b>	
Support Networks:	WCDMA, HSDPA, HSUPA
Support Band:	WCDMA Band 2, WCDMA Band 4, WCDMA Band 5
Uplink Frequency:	WCDMA Band 2: 1850~1910MHz WCDMA Band 4: 1710~1755MHz WCDMA Band 5: 824~849MHz
Downlink Frequency:	WCDMA Band 2: 1930~1990MHz WCDMA Band 4: 2110~2155MHz WCDMA Band 5: 869~894MHz
RF Output Power:	WCDMA Band 2: 22.62dBm, WCDMA Band 4: 22.88dBm WCDMA Band 5: 22.25dBm
	Sensor ON: WCDMA Band 2: 20.64dBm, WCDMA Band 4: 20.87dBm
	Hotspot ON: WCDMA Band 2: 19.65dBm, WCDMA Band 4: 19.87dBm
Type of Emission:	WCDMA Band 2: 4M16F9W WCDMA Band 4: 4M15F9W WCDMA Band 5: 4M15F9W
Type of Modulation:	BPSK, QPSK, 16QAM
Antenna Type:	Integral Antenna
Antenna Gain:	WCDMA Band 2: -1.5dBi, WCDMA Band 4: -1.7dBi,

Reference No.: WTX24X04087264W001

	WCDMA Band 5: -3.7dBi
<i>Note The Antenna Gain is provided by the customer and can affect the validity of results.</i>	

## 1.2 Test Standards

The tests were performed according to following standards:

**FCC Rules Part 2:** Frequency Allocations and Radio Treaty Matters; General Rules and Regulations.

**FCC Rules Part 22:** Private Land Mobile Radio Services.

**FCC Rules Part 24:** Public Mobile Services.

**FCC Rules Part 27:** Miscellaneous Wireless Communications Services.

**TIA/EIA 603 E March 2016:** Land Mobile FM or PM Communications Equipment Measurement and Performance Standards.

**ANSI C63.26-2015:** American National Standard for Compliance Testing of Transmitters Used in Licensed Radio Services

**KDB 971168 D01 Power Meas License Digital Systems v03r01:** Measurement Guidance for Certification of Licensed Digital Transmitters.

**Maintenance of compliance** is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

## 1.3 Test Methodology

All measurements contained in this report were conducted with TIA/EIA 603 E/ KDB 971168/ ANSI C63.26. The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

## 1.4 Test Facility

### Address of the test laboratory

Laboratory: Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road, Block 70 Bao'an District, Shenzhen, Guangdong, China

### FCC – Registration No.: 125990

Waltek Testing Group (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010, and Test Firm Registration Number is 125990.

### Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Waltek Testing Group (Shenzhen) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A and the CAB identifier is CN0057.

## 1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	GSM 850	Low, Middle, High Channels
TM2	GPRS 850	Low, Middle, High Channels
TM3	EDGE 850	Low, Middle, High Channels
TM4	GSM 1900	Low, Middle, High Channels
TM5	GPRS 1900	Low, Middle, High Channels
TM6	EDGE 1900	Low, Middle, High Channels
TM7	WCDMA Band 5	Low, Middle, High Channels
TM8	HSDPA Band 5	Low, Middle, High Channels
TM9	HSUPA Band 5	Low, Middle, High Channels
TM10	WCDMA Band 4	Low, Middle, High Channels
TM11	HSDPA Band 4	Low, Middle, High Channels
TM12	HSUPA Band 4	Low, Middle, High Channels
TM13	WCDMA Band 2	Low, Middle, High Channels
TM14	HSDPA Band 2	Low, Middle, High Channels
TM15	HSUPA Band 2	Low, Middle, High Channels



<b>Testing Configure</b>			
Support Band	Support Standard	Channel Frequency	Channel Number
GSM 850	GSM/GPRS/EDGE	824.2 MHz	128
		836.6 MHz	190
		848.8 MHz	251
PCS 1900	GSM/GPRS/EDGE	1850.2 MHz	512
		1880.0 MHz	661
		1909.8 MHz	810
WCDMA Band 5	WCDMA/HSDPA/HSUPA	826.4 MHz	4132
		836.6 MHz	4183
		846.6 MHz	4233
WCDMA Band 4	WCDMA/HSDPA/HSUPA	1712.4 MHz	1312
		1732.4 MHz	1412
		1752.6 MHz	1513
WCDMA Band 2	WCDMA/HSDPA/HSUPA	1852.4 MHz	9262
		1880.0 MHz	9400
		1907.6 MHz	9538

Note: the transmitter has been tested on the communications mode of GSM, GPRS, EDGE, WCDMA, HSDPA, HSUPA compliance test and record the worst case.

<b>Test Conditions</b>	
Temperature:	22~25 °C
Relative Humidity:	50~55 %.
ATM Pressure:	1019 mbar

<b>EUT Cable List and Details</b>			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
Type-C Cable	1.0	Shielded	Without Ferrite
Headset Cable	1.2	Unshielded	Without Ferrite

<b>Special Cable List and Details</b>			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

<b>Auxiliary Equipment List and Details</b>			
Description	Manufacturer	Model	Serial Number
Notebook	ASUS	MT7921	/

## 1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	$\pm 0.42\text{dB}$
Occupied Bandwidth	Conducted	$\pm 1.5\%$
Frequency Stability	Conducted	2.3%
Transmitter Spurious Emissions	Conducted	$\pm 0.42\text{dB}$
Transmitter Spurious Emissions	Radiated	30-200MHz $\pm 4.52\text{dB}$
		0.2-1GHz $\pm 5.56\text{dB}$
		1-6GHz $\pm 3.84\text{dB}$
		6-18GHz $\pm 3.92\text{dB}$

**1.7 Test Equipment List and Details**

Fixed asset Number	Description	Manufacturer	Model	Serial No.	Cal Date	Due. Date
WTXE1041 A1001	Communication Tester	Rohde & Schwarz	CMW500	148650	2024-02-24	2025-02-23
WTXE1022 A1002	GSM Tester	Rohde & Schwarz	CMU200	114403	2024-02-27	2025-02-26
WTXE1104 A1001	MXG Vector Signal Generator	Agilent	N5182A	MY47420108	2024-02-24	2025-02-23
WTXE1104 A1002	DC Power Supply	Agilent	E3634A	MY40009294	2024-02-24	2025-02-23
WTXE1104 A1003	EXG Analog Signal Generator	KEYSIGHT	N5173B	MY61252892	2024-02-24	2025-02-23
WTXE1104 A1004	Spectrum Analyzer	Rohde&Schwarz	FSV40-N	101559	2024-02-24	2025-02-23
WTXE1104 A1005-2	Band Reject Filter Group	Tonscend	JS0806-F	23A806F0658	2024-03-23	2025-03-22
<input type="checkbox"/> Chamber A: Below 1GHz						
WTXE1005 A1003	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2024-02-24	2025-02-23
WTXE1001 A1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2024-03-19	2025-03-18
WTXE1007 A1001	Amplifier	HP	8447F	2805A03475	2024-02-24	2025-02-23
WTXE1010 A1007	Loop Antenna	Schwarz beck	FMZB 1516	9773	2024-02-26	2025-02-25
WTXE1010 A1006	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2024-02-24	2025-02-23
<input type="checkbox"/> Chamber A: Above 1GHz						
WTXE1005 A1003	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2024-02-24	2025-02-23
WTXE1001 A1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2024-03-19	2025-03-18
WTXE1065 A1001	Amplifier	C&D	PAP-1G18	2002	2024-02-27	2025-02-26
WTXE1010 A1005	Horn Antenna	ETS	3117	00086197	2024-02-26	2025-02-25
WTXE1010 A1010	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2024-03-17	2025-03-16
WTXE1003 A1001	Pre-amplifier	Schwarzbeck	BBV 9721	9721-031	2024-02-29	2025-02-28

WTXE1004 A1-001	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2024-02-27	2025-02-26
<input type="checkbox"/> Chamber B:Below 1GHz						
WTXE1010 A1006	Trilog Broadband Antenna	Schwarz beck	VULB9163(B)	9163-635	2024-03-17	2027-03-16
WTXE1038 A1001	Amplifier	Agilent	8447D	2944A104 57	2024-02-24	2025-02-23
WTXE1001 A1002	EMI Test Receiver	Rohde & Schwarz	ESPI	101391	2024-02-24	2025-02-23
<input checked="" type="checkbox"/> Chamber C:Below 1GHz						
WTXE1093 A1001	EMI Test Receiver	Rohde & Schwarz	ESIB 26	100401	2024-02-27	2025-02-26
WTXE1010 A1013-1	Trilog Broadband Antenna	Schwarz beck	VULB 9168	1194	2024-04-18	2027-04-17
WTXE1007 A1002	Amplifier	HP	8447F	2944A038 69	2024-02-24	2025-02-23
WTXE1010 A1007	Loop Antenna	Schwarz beck	FMZB 1516	9773	2024-02-26	2025-02-25
<input checked="" type="checkbox"/> Chamber C: Above 1GHz						
WTXE1093 A1001	EMI Test Receiver	Rohde & Schwarz	ESIB 26	100401	2024-02-27	2025-02-26
WTXE1103 A1005	Horn Antenna	POAM	RTF-118A	1820	2023-03-10	2026-03-09
WTXE1103 A1006	Amplifier	Tonscend	TAP01018050	AP22E806 235	2024-02-27	2025-02-26
WTXE1010 A1010	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2024-03-17	2025-03-16
WTXE1003 A1001	Pre-amplifier	Schwarzbeck	BBV 9721	9721-031	2024-02-29	2025-02-28
<input type="checkbox"/> Conducted Room 1#						
WTXE1104 A1029	EMI Test Receiver	Rohde & Schwarz	ESCI	100525	2023-12-12	2024-12-11
WTXE1002 A1001	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2024-02-24	2025-02-23
WTXE1003 A1001	AC LISN	Schwarz beck	NSLK8126	8126-279	2024-02-24	2025-02-23
<input checked="" type="checkbox"/> Conducted Room 2#						
WTXE1001 A1004	EMI Test Receiver	Rohde & Schwarz	ESPI	101259	2024-02-24	2025-02-23
WTXE1003	LISN	Rohde &	ENV 216	100097	2024-02-24	2025-02-23

Reference No.: WTX24X04087264W001

A1003		Schwarz				
-------	--	---------	--	--	--	--

Software List			
Description	Manufacturer	Model	Version
EMI Test Software (Radiated Emission)*	Farad	EZ-EMC	RA-03A1

\*Remark: indicates software version used in the compliance certification testing.

## 2. SUMMARY OF TEST RESULTS

---

FCC Rules	Description of Test Item	Result
§22.913(a), §24.232(c), §27.50(d)	RF Output Power	Compliant
§24.51, §27.50	Peak-to-average Ratio (PAR) of Transmitter	Compliant
§22.917(b), §24.238(b), §27.53	Emission Bandwidth	Compliant
§22.917(a), §24.238(a), §27.53(h)	Spurious Emissions at Antenna Terminal	Compliant
§22.917(a), §24.238(a), §27.53(h)	Spurious Radiation Emissions	Compliant
§22.917(a), §24.238(a), §27.53(h)	Out of Band Emissions	Compliant
§22.355, §24.235, §27.54	Frequency Stability	Compliant

### 3. RF Output Power

---

#### 3.1 Standard Applicable


According to §22.913(a)(2), the ERP of mobile and portable stations transmitters and auxiliary test transmitters must not exceed 7 Watts.

According to §24.232(c), mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.

According to §27.50(d)(4), fixed, mobile, and portable (hand-held) stations operating in the 1710-1755MHz band and mobile and portable stations operating in the 1695-1710MHz and 1755-1780MHz bands are limited to 1 watt EIRP.

#### 3.2 Test Procedure

- Conducted output power test method:



- Radiated power test method:

1. The setup of EUT is according with per ANSI/TIA Standard 603E and ANSI C63.26 measurement procedure.
2. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.
3. The frequency range up to tenth harmonic of the fundamental frequency was investigated.
4. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

#### 3.3 Summary of Test Results/Plots

➤ **Max. Radiated Power**

Mode	Channel	Antenna Polar	ERP (dBm)	Limit (dBm)	Result
GSM850	128	V	29.45	<38.45	Pass
		H	23.98		
	190	V	29.45		
		H	23.21		
	251	V	29.51		
		H	23.15		
GPRS850	128	V	29.68	<38.45	Pass
		H	23.45		
	190	V	29.25		
		H	23.35		
	251	V	29.48		
		H	23.21		
EGPRS850	128	V	23.48	<38.45	Pass
		H	17.65		
	190	V	23.12		
		H	17.56		
	251	V	23.45		
		H	17.19		



Mode	Channel	Antenna Polar	EIRP (dBm)	Limit (dBm)	Result
PCS1900	512	V	28.42	<33.00	Pass
		H	21.15		
	661	V	28.21		
		H	21.25		
	810	V	28.36		
		H	21.45		
GPRS1900	512	V	28.25	<33.00	Pass
		H	21.31		
	661	V	28.24		
		H	21.25		
	810	V	28.36		
		H	21.54		
EGPRS1900	512	V	21.25	<33.00	Pass
		H	16.15		
	661	V	21.26		
		H	16.25		
	810	V	21.42		
		H	16.36		

Mode	Channel	Antenna Polar	ERP	Limit (dBm)	Result
WCDMA Band V	4132	V	19.41	<38.45	Pass
		H	15.54		
	4183	V	19.65		
		H	15.23		
	4233	V	19.45		
		H	15.34		

Mode	Channel	Antenna Polar	EIRP	Limit (dBm)	Result
WCDMA Band IV	1312	V	19.54	<30.00	Pass
		H	15.12		
	1412	V	19.26		
		H	15.25		
	1513	V	19.15		
		H	15.26		

Mode	Channel	Antenna Polar	EIRP	Limit (dBm)	Result
WCDMA Band II	9262	V	19.15	<33.00	Pass
		H	14.26		
	9400	V	19.35		
		H	14.47		
	9538	V	19.21		
		H	14.64		

➤ **Max. Conducted Power (Average power)**

**Please refer to Appendix A**

## 4. Peak-to-average Ratio (PAR) of Transmitter

---

### 4.1 Standard Applicable

According to §24.232(d), power measurements for transmissions by stations authorized under this section may be made either in accordance with a Commission-approved average power technique or in compliance with paragraph (e) of this section. In both instances, equipment employed must be authorized in accordance with the provisions of §24.51, in measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13dB.


According to §27.50(B), the peak-to-average power ratio (PAPR) of the transmitter output power must not exceed 13dB. The PAPR measurements should be made using either an instrument with complementary cumulative distribution function (CCDF) capabilities to determine that PAPR will not exceed 13dB for more than 0.1 percent of the time or other Commission approved procedure. The measurement must be performed using a signal corresponding to the highest PAPR expected during periods of continuous transmission.

### 4.2 Test Procedure

According with KDB 971168

1. The signal analyzer's CCDF measurement profile is enabled.
2. Frequency = carrier center frequency.
3. Measurement BW > Emission bandwidth of signal.
4. The signal analyzer was set to collect one million samples to generate the CCDF curve.
5. The measurement interval was set depending on the type of signal analyzed. For continuous signals (>98% duty cycle), the measurement interval was set to 1ms. For burst transmissions, the spectrum analyzer is set to use an internal "RF Burst" trigger that is synced with an incoming pulse and the measurement interval is set to less than the duration of the "on time" of one burst to ensure that energy is only captured during a time in which the transmitter is operating at maximum power.

Test Configuration for the emission bandwidth testing:



### 4.3 Summary of Test Results

Please refer to Appendix B.

Waltek Testing Group (Shenzhen) Co., Ltd.

[Http://www.waltek.com.cn](http://www.waltek.com.cn)

Page 19 of 38

## 5. Emission Bandwidth

---

### 5.1 Standard Applicable

According to §22.917(b), the emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26dB below the transmitter power.


According to §24.238(b), the emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26dB below the transmitter power.

According to §27.53, the emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26dB below the transmitter power.

### 5.2 Test Procedure

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 10kHz for GSM mode and 100kHz for WCDMA mode, VBW shall be at least 3 times the RBW, and the 26dB bandwidth was recorded.

Test Configuration for the emission bandwidth testing:



### 5.3 Summary of Test Results/Plots

Please refer to Appendix C.

## 6. Out of Band Emissions at Antenna Terminal

---

### 6.1 Standard Applicable

According to §22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.


According to §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.

According to §27.53 (h), the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least  $43 + 10 \log_{10}(P)$  dB.

### 6.2 Test Procedure

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 100kHz and 1MHz for the scan frequency from 30MHz to 1GHz and the scan frequency from 1GHz to up to 10<sup>th</sup> harmonic.

Test Configuration for the out of band emissions testing:



### 6.3 Summary of Test Results/Plots

Please refer to Appendix D.

## 7. Spurious Radiated Emissions

---

### 7.1 Standard Applicable

According to §22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.

According to §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.

According to §27.53 (h), the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least  $43 + 10 \log_{10}(P)$  dB.

### 7.2 Test Procedure

1. The setup of EUT is according with per ANSI/TIA Standard 603E and ANSI C63.26 measurement procedure.
2. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.
3. The frequency range up to tenth harmonic of the fundamental frequency was investigated.
4. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.


$$\text{Spurious attenuation limit in dB} = 43 + 10 \log_{10}(\text{power out in Watts})$$

### 7.3 Summary of Test Results/Plots

*Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.*


➤ Spurious Emissions Below 1GHz

For Cellular Band			
Test Channel	GSM850	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBm)	Correct Factor(dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	56.0708	-77.04	2.76	-74.28	-13.00	-61.28	ERP
2	98.3752	-75.85	-4.08	-79.93	-13.00	-66.93	ERP
3	191.7841	-73.44	0.38	-73.06	-13.00	-60.06	ERP
4	252.2523	-76.34	8.36	-67.98	-13.00	-54.98	ERP
5	520.2079	-75.11	7.47	-67.64	-13.00	-54.64	ERP
6	833.0127	-75.66	13.37	-62.29	-13.00	-49.29	ERP


For Cellular Band			
Test Channel	GSM850	Polarity:	Vertical



No.	Frequency (MHz)	Reading (dBm)	Correct Factor(dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	35.7617	-76.09	2.15	-73.94	-13.00	-60.94	ERP
2	52.6345	-76.57	3.45	-73.12	-13.00	-60.12	ERP
3	74.2696	-74.99	1.94	-73.05	-13.00	-60.05	ERP
4	162.0197	-77.98	7.57	-70.41	-13.00	-57.41	ERP
5	373.8862	-74.74	4.83	-69.91	-13.00	-56.91	ERP
6	804.2523	-75.90	12.43	-63.47	-13.00	-50.47	ERP




For Cellular Band			
Test Channel	GSM1900	Polarity:	Horizontal



No.	Frequency (MHz)	Reading (dBm)	Correct Factor(dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	48.7191	-78.18	3.38	-74.80	-13.00	-61.80	ERP
2	87.2980	-77.59	-1.97	-79.56	-13.00	-66.56	ERP
3	144.7899	-77.58	0.25	-77.33	-13.00	-64.33	ERP
4	280.2936	-74.66	6.03	-68.63	-13.00	-55.63	ERP
5	538.8107	-77.62	7.64	-69.98	-13.00	-56.98	ERP
6	827.1795	-75.64	13.24	-62.40	-13.00	-49.40	ERP


For Cellular Band			
Test Channel	GSM1900	Polarity:	Vertical



No.	Frequency (MHz)	Reading (dBm)	Correct Factor(dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	51.8999	-77.94	3.46	-74.48	-13.00	-61.48	ERP
2	74.2696	-74.34	1.94	-72.40	-13.00	-59.40	ERP
3	160.8852	-77.13	7.77	-69.36	-13.00	-56.36	ERP
4	373.8862	-75.75	4.83	-70.92	-13.00	-57.92	ERP
5	573.9882	-77.34	8.40	-68.94	-13.00	-55.94	ERP
6	899.9577	-75.52	12.24	-63.28	-13.00	-50.28	ERP


Note: Margin= (Reading+ Correct)- Limit

Test Channel	WCDMA Band V	Polarity:	Horizontal
--------------	--------------	-----------	------------




No.	Frequency (MHz)	Reading (dBm)	Correct Factor(dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	48.3780	-78.24	3.35	-74.89	-13.00	-61.89	ERP
2	71.7054	-79.11	0.77	-78.34	-13.00	-65.34	ERP
3	159.7586	-77.94	0.98	-76.96	-13.00	-63.96	ERP
4	286.2653	-74.70	5.53	-69.17	-13.00	-56.17	ERP
5	502.2473	-76.98	7.31	-69.67	-13.00	-56.67	ERP
6	833.0127	-74.81	13.37	-61.44	-13.00	-48.44	ERP

Test Channel	WCDMA Band V	Polarity:	Vertical
--------------	--------------	-----------	----------




No.	Frequency (MHz)	Reading (dBm)	Correct (dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	35.7617	-75.20	2.15	-73.05	-13.00	-60.05	ERP
2	74.2696	-74.33	1.94	-72.39	-13.00	-59.39	ERP
3	100.4712	-72.21	-1.66	-73.87	-13.00	-60.87	ERP
4	159.7586	-76.91	7.83	-69.08	-13.00	-56.08	ERP
5	373.8862	-74.11	4.83	-69.28	-13.00	-56.28	ERP
6	881.1838	-74.51	12.10	-62.41	-13.00	-49.41	ERP

Test Channel	WCDMA Band IV	Polarity:	Horizontal
--------------	---------------	-----------	------------



No.	Frequency (MHz)	Reading (dBm)	Correct (dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	38.3651	-78.31	2.39	-75.92	-13.00	-62.92	ERP
2	58.0759	-77.99	2.52	-75.47	-13.00	-62.47	ERP
3	159.7586	-78.16	0.98	-77.18	-13.00	-64.18	ERP
4	245.2606	-77.45	7.74	-69.71	-13.00	-56.71	ERP
5	535.0377	-76.26	7.61	-68.65	-13.00	-55.65	ERP
6	838.8870	-75.52	13.50	-62.02	-13.00	-49.02	ERP


Test Channel	WCDMA Band IV	Polarity:	Vertical
--------------	---------------	-----------	----------



No.	Frequency (MHz)	Reading (dBm)	Correct Factor(dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	35.7617	-77.31	2.15	-75.16	-13.00	-62.16	ERP
2	52.6345	-76.78	3.45	-73.33	-13.00	-60.33	ERP
3	100.4712	-73.78	-1.66	-75.44	-13.00	-62.44	ERP
4	160.8852	-77.25	7.77	-69.48	-13.00	-56.48	ERP
5	373.8862	-74.19	4.83	-69.36	-13.00	-56.36	ERP
6	776.4849	-75.86	12.06	-63.80	-13.00	-50.80	ERP


Note: Margin= (Reading+ Correct)- Limit

Test Channel	WCDMA Band II	Polarity:	Horizontal
--------------	---------------	-----------	------------



No.	Frequency (MHz)	Reading (dBm)	Correct (dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	38.0965	-77.93	2.37	-75.56	-13.00	-62.56	ERP
2	78.0143	-77.70	-0.34	-78.04	-13.00	-65.04	ERP
3	159.7586	-77.54	0.98	-76.56	-13.00	-63.56	ERP
4	261.2730	-76.64	7.61	-69.03	-13.00	-56.03	ERP
5	502.2473	-75.94	7.31	-68.63	-13.00	-55.63	ERP
6	838.8870	-75.69	13.50	-62.19	-13.00	-49.19	ERP

Test Channel	WCDMA Band II	Polarity:	Vertical
--------------	---------------	-----------	----------



No.	Frequency (MHz)	Reading (dBm)	Correct Factor(dB)	Result (dBm)	Limit (dBm)	Margin (dB)	Remark
1	36.0139	-76.04	2.17	-73.87	-13.00	-60.87	ERP
2	53.3794	-76.40	3.43	-72.97	-13.00	-59.97	ERP
3	74.2696	-74.26	1.94	-72.32	-13.00	-59.32	ERP
4	168.9970	-75.49	6.35	-69.14	-13.00	-56.14	ERP
5	373.8862	-74.38	4.83	-69.55	-13.00	-56.55	ERP
6	798.6205	-76.18	12.62	-63.56	-13.00	-50.56	ERP

Note: Margin= (Reading+ Correct)- Limit



- Spurious Emissions Above 1GHz
- For Cellular Band\_GSM850 Mode

Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Polar H/V
Low Channel (824.2MHz)						
1648.4	-37.37	4.94	-32.43	-13	-19.43	H
2472.6	-44.28	8.46	-35.82	-13	-22.82	H
1648.4	-36.2	4.94	-31.26	-13	-18.26	V
2472.6	-42.01	8.46	-33.55	-13	-20.55	V
Middle Channel (836.6MHz)						
1673.2	-34.79	5.11	-29.68	-13	-16.68	H
2509.8	-41.57	8.54	-33.03	-13	-20.03	H
1673.2	-37.39	5.11	-32.28	-13	-19.28	V
2509.8	-42.46	8.54	-33.92	-13	-20.92	V
High Channel (848.8MHz)						
1697.6	-37.38	5.25	-32.13	-13	-19.13	H
2546.4	-43.16	8.57	-34.59	-13	-21.59	H
1697.6	-35.13	5.25	-29.88	-13	-16.88	V
2546.4	-42.87	8.57	-34.3	-13	-21.3	V

- For PCS Band\_GSM1900 Mode

Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Polar H/V
Low Channel (1850.2MHz)						
3700.4	-39.16	10.54	-28.62	-13	-15.62	H
5550.6	-44.98	13.37	-31.61	-13	-18.61	H
3700.4	-39.72	10.54	-29.18	-13	-16.18	V
5550.6	-44.74	13.37	-31.37	-13	-18.37	V
Middle Channel (1880MHz)						
3760.0	-36.82	5.11	-31.71	-13	-18.71	H
5640.0	-45.31	10.64	-34.67	-13	-21.67	H
3760.0	-37.34	13.54	-23.8	-13	-10.80	V
5640.0	-47.15	10.64	-36.51	-13	-23.51	V
High Channel (1909.8MHz)						
3819.6	-37.34	10.74	-26.6	-13	-13.60	H
5729.4	-46.83	13.71	-33.12	-13	-20.12	H
3819.6	-37.93	10.74	-27.19	-13	-14.19	V
5729.4	-47.25	13.71	-33.54	-13	-20.54	V

## ➤ For WCDMA Band V Mode

Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Polar H/V
Low Channel (826.4MHz)						
1652.8	-37.75	4.94	-32.81	-13	-19.81	H
2479.2	-44.21	8.46	-35.75	-13	-22.75	H
1652.8	-34.42	4.94	-29.48	-13	-16.48	V
2479.2	-41.98	8.46	-33.52	-13	-20.52	V
Middle Channel (836.6MHz)						
1672.8	-35.53	5.11	-30.42	-13	-17.42	H
2509.2	-41.07	8.54	-32.53	-13	-19.53	H
1672.8	-37.22	5.11	-32.11	-13	-19.11	V
2509.2	-42.20	8.54	-33.66	-13	-20.66	V
High Channel (846.6MHz)						
1693.2	-34.71	5.25	-29.46	-13	-16.46	H
2539.8	-41.05	8.57	-32.48	-13	-19.48	H
1693.2	-35.44	5.25	-30.19	-13	-17.19	V
2539.8	-43.72	8.57	-35.15	-13	-22.15	V

## ➤ For WCDMA Band IV Mode

Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Polar H/V
Low Channel (1712.4MHz)						
3424.8	-34.79	8.65	-26.14	-13	-13.14	H
5137.2	-43.32	12.03	-31.29	-13	-18.29	H
3424.8	-37.92	8.65	-29.27	-13	-16.27	V
5137.2	-44.61	12.03	-32.58	-13	-19.58	V
Middle Channel (1732.4MHz)						
3466.8	-37.57	8.91	-28.66	-13	-15.66	H
5200.2	-42.76	12.29	-30.47	-13	-17.47	H
3466.8	-36.15	8.91	-27.24	-13	-14.24	V
5200.2	-44.03	12.29	-31.74	-13	-18.74	V
High Channel (1752.6MHz)						
3505.2	-34.36	9.11	-25.25	-13	-12.25	H
5257.8	-41.8	12.56	-29.24	-13	-16.24	H
3505.2	-36.46	9.11	-27.35	-13	-14.35	V
5257.8	-43.51	12.56	-30.95	-13	-17.95	V

## ➤ For WCDMA Band II Mode

Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Polar H/V
Low Channel (1852.4MHz)						
3704.8	-37.32	10.54	-26.78	-13	-13.78	H
5557.2	-45.01	13.37	-31.64	-13	-18.64	H
3704.8	-38.26	10.54	-27.72	-13	-14.72	V
5557.2	-46.63	13.37	-33.26	-13	-20.26	V
Middle Channel (1880MHz)						
3760.0	-39.78	5.11	-34.67	-13	-21.67	H
5640.0	-47.23	10.64	-36.59	-13	-23.59	H
3760.0	-37.73	13.54	-24.19	-13	-11.19	V
5640.0	-47.16	10.64	-36.52	-13	-23.52	V
High Channel (1907.6MHz)						
3815.2	-37.53	10.74	-26.79	-13	-13.79	H
5722.8	-44.84	13.71	-31.13	-13	-18.13	H
3815.2	-36.42	10.74	-25.68	-13	-12.68	V
5722.8	-47.53	13.71	-33.82	-13	-20.82	H

Note:  $Result = Reading + Correct$ ,  $Margin = Result - Limit$

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

## **8. Frequency Stability**

---

### **8.1 Standard Applicable**

According to §22.355, §24.235, §27.54 the limit is 2.5ppm.

### **8.2 Test Procedure**

According to §2.1055, the following test procedure was performed.

The Frequency Stability is measured directly with a Frequency Domain Analyzer. Frequency Deviation in ppm is calculated from the measured peak to peak value.

The Carrier Frequency Stability over Power Supply Voltage and over Temperature is measured with a Frequency Domain Analyzer in histogram mode.

### **8.3 Summary of Test Results/Plots**

**Please refer to Appendix E**

## 9. Modulation characteristics

---

### 9.1 Standard Applicable

According to §2.1047, measurements required: Modulation characteristics is given below:

(a) Voice modulated communication equipment. A curve or equivalent data showing the frequency response of the audio modulating circuit over a range of 100 to 5000Hz shall be submitted. For equipment required to have an audio low-pass filter, a curve showing the frequency response of the filter, or of all circuitry installed between the modulation limiter and the modulated stage shall be submitted.


(b) Equipment which employs modulation limiting. A curve or family of curves showing the percentage of modulation versus the modulation input voltage shall be supplied. The information submitted shall be sufficient to show modulation limiting capability throughout the range of modulating frequencies and input modulating signal levels employed.

(c) Single sideband and independent sideband radiotelephone transmitters which employ a device or circuit to limit peak envelope power. A curve showing the peak envelope power output versus the modulation input voltage shall be supplied. The modulating signals shall be the same in frequency as specified in paragraph (c) of §2.1049 for the occupied bandwidth tests.

(d) Other types of equipment. A curve or equivalent data which shows that the equipment will meet the modulation requirements of the rules under which the equipment is to be licensed.

### 9.2 Test Procedure

According to ANSI C63.26-2015 section 5.3.2, the following test setup was performed.



### 9.3 Summary of Test Results/Plots

Please refer to Appendix F

## APPENDIX PHOTOGRAPHS

---

Please refer to "ANNEX"

\*\*\*\* END OF REPORT \*\*\*\*