



RF TEST REPORT



Report No.: 17070203-FCC-R2

Supersede Report No.: N/A

Applicant	BLU Products, Inc.	
Product Name	Mobile Phone	
Model No.	STUDIO MEGA	
Serial No.	N/A	
Test Standard	FCC Part 15.247: 2016, ANSI C63.10: 2013	
Test Date	March 30 to April 18, 2017	
Issue Date	April 19, 2017	
Test Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	
Equipment complied with the specification	<input checked="" type="checkbox"/>	
Equipment did not comply with the specification	<input type="checkbox"/>	
		
Loren Lou Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report No.	17070203-FCC-R2
Page	3 of 62

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY	5
2. CUSTOMER INFORMATION.....	5
3. TEST SITE INFORMATION	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5. TEST SUMMARY	9
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS.....	10
6.1 ANTENNA REQUIREMENT	10
6.2 DTS (6 DB&20 DB) CHANNEL BANDWIDTH	11
6.3 MAXIMUM OUTPUT POWER.....	17
6.4 POWER SPECTRAL DENSITY	21
6.5 BAND-EDGE & UNWANTED EMISSIONS INTO RESTRICTED FREQUENCY BANDS	25
6.6 AC POWER LINE CONDUCTED EMISSIONS.....	31
6.7 RADIATED SPURIOUS EMISSIONS & RESTRICTED BAND.....	37
ANNEX A. TEST INSTRUMENT	43
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS.....	44
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT.....	57
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST	61
ANNEX E. DECLARATION OF SIMILARITY	62

1. Report Revision History

Report No.	Report Version	Description	Issue Date
17070203-FCC-R2	NONE	Original	April 19, 2017

2. Customer information

Applicant Name	BLU Products, Inc.
Applicant Add	10814 NW 33rd St # 100 Doral, FL 33172
Manufacturer	BLU Products, Inc.
Manufacturer Add	10814 NW 33rd St # 100 Doral, FL 33172

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software of Radiated Emission	Radiated Emission Program-To Shenzhen v2.0
Test Software of Conducted Emission	EZ-EMC(ver.lcp-03A1)

4. Equipment under Test (EUT) Information

Description of EUT:	Mobile Phone
Main Model:	STUDIO MEGA
Serial Model:	N/A
Date EUT received:	March 29,2017
Test Date(s):	March 30 to April 18, 2017
Equipment Category :	DTS
Antenna Gain:	GSM850: -0.57dBi PCS1900: -0.96dBi UMTS-FDD Band V: -0.6dBi UMTS-FDD Band IV: -1.71dBi UMTS-FDD Band II: -1dBi WIFI: -1.52dBi Bluetooth/BLE:-1.42dBi GPS: -0.96dBi
Antenna Type:	PIFA antenna
Type of Modulation:	GSM / GPRS: GMSK EGPRS: GMSK,8PSK UMTS-FDD: QPSK 802.11b/g/n: DSSS, OFDM Bluetooth: GFSK, π /4DQPSK, 8DPSK BLE: GFSK GPS:BPSK

	GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz
	PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz
	UMTS-FDD Band V TX: 826.4 ~ 846.6 MHz; RX: 871.4 ~ 891.6 MHz
	UMTS-FDD Band IV TX:1712.4 ~ 1752.6 MHz;
	RX : 2112.4 ~ 2152.6 MHz
RF Operating Frequency (ies):	UMTS-FDD Band II TX:1852.4 ~ 1907.6 MHz;
	RX: 1932.4 ~ 1987.6 MHz
	WIFI: 802.11b/g/n(20M): 2412-2462 MHz
	WIFI: 802.11n(40M): 2422-2452 MHz
	Bluetooth& BLE: 2402-2480 MHz
	GPS: 1575.42 MHz
Max. Output Power:	802.11b: 15.50dBm
	802.11g: 13.00dBm
	802.11n(20M): 11.05dBm
	802.11n(40M): 10.59dBm
Number of Channels:	GSM 850: 124CH
	PCS1900: 299CH
	UMTS-FDD Band V: 102CH
	UMTS-FDD Band IV: 202CH
	UMTS-FDD Band II: 277CH
	WIFI :802.11b/g/n(20M): 11CH
	WIFI :802.11n(40M): 7CH
	Bluetooth: 79CH
	BLE: 40CH
	GPS:1CH
Port:	USB Port, Earphone Port
Input Power:	Adapter:
	Model:TPA-46B050100UU
	Input: AC100-240V~50/60Hz,0.2A
	Output: DC 5.0V,1.0A
	Battery:
	Model:C986241250L
	Spec:3.8V,9.5Wh,2500mAh

Test Report No.	17070203-FCC-R2
Page	8 of 62

Trade Name : BLU

FCC ID: YHLBLUSTUDIOMEG

GPRS/EGPRS Multi-slot class 8/10/12

5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.247 (a)(2)	DTS (6 dB&20 dB) CHANNEL BANDWIDTH	Compliance
§15.247(b)(3)	Conducted Maximum Output Power	Compliance
§15.247(e)	Power Spectral Density	Compliance
§15.247(d)	Band-Edge & Unwanted Emissions into Restricted Frequency Bands	Compliance
§15.207 (a),	AC Power Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Radiated Emissions & Unwanted Emissions into Restricted Frequency Bands	Compliance

Measurement Uncertainty

Emissions		
Test Item	Description	Uncertainty
Band-Edge & Unwanted Emissions into Restricted Frequency Bands and Radiated Emissions & Unwanted Emissions into Restricted Frequency Bands	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-

6. Measurements, Examination And Derived Results

6.1 Antenna Requirement

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has 3 antennas:

A permanently attached PIFA antenna for Bluetooth/BLE/WIFI, the gain is -1.42dBi for Bluetooth and BLE, -1.52dBi for WIFI.

A permanently attached PIFA antenna for GSM/PCS/UMTS, the gain is -0.57dBi for GSM850, -0.96Bi for PCS1900, -0.6dBi for UMTS-FDD Band V, -1.71dBi for UMTS-FDD Band IV, -1dBi for UMTS-FDD Band II.


A permanently attached PIFA antenna for GPS, the gain is -0.96dBi.

The antenna meets up with the ANTENNA REQUIREMENT.

Result: Compliance.

6.2 DTS (6 dB&20 dB) Channel Bandwidth

Temperature	22°C
Relative Humidity	55%
Atmospheric Pressure	1005mbar
Test date :	April 06, 2017
Tested By :	Loren Lou

Spec	Item	Requirement	Applicable
§ 15.247(a)(2)	a)	6dB BW ≥ 500kHz; 20dB BW ≥ 500kHz;	<input checked="" type="checkbox"/>
RSS Gen(4.6.1)	b)	99% BW: For FCC reference only; required by IC.	<input checked="" type="checkbox"/>
Test Setup	 <p style="text-align: center;">Spectrum Analyzer EUT</p>		
Test Procedure	<p>558074 D01 DTS MEAS Guidance v03r03, 8.1 DTS bandwidth</p> <p><u>6dB bandwidth</u></p> <ol style="list-style-type: none"> Set RBW = 100 kHz. Set the video bandwidth (VBW) ≥ 3 × RBW. Detector = Peak. Trace mode = max hold. Sweep = auto couple. Allow the trace to stabilize. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission. <p><u>20dB bandwidth</u></p> <p>C63.10 Occupied Bandwidth (OBW=20dB bandwidth)</p> <ol style="list-style-type: none"> Set RBW = 1%-5% OBW. Set the video bandwidth (VBW) ≥ 3 x RBW. Set the span range between 2 times and 5 times of the OBW. Sweep time=Auto, Detector=PK, Trace=Max hold. Once the reference level is established, the equipment is conditioned with typical modulating signals to produce the worst- 		

	case (i.e., the widest) bandwidth. Unless otherwise specified for an unlicensed wireless device, measure the bandwidth at the 20 dB levels with respect to the reference level.
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data Yes N/A



Test Plot Yes (See below) N/A

Measurement result

Test mode	CH	Freq (MHz)	6dB Bandwidth (MHz)	20dB Bandwidth (MHz)	Limit (MHz)
802.11b	Low	2412	9.568	14.390	≥ 0.5
	Mid	2437	9.593	14.383	≥ 0.5
	High	2462	9.563	14.399	≥ 0.5
802.11g	Low	2412	15.690	18.837	≥ 0.5
	Mid	2437	15.553	18.759	≥ 0.5
	High	2462	15.122	18.895	≥ 0.5
802.11n (20M)	Low	2412	15.459	19.361	≥ 0.5
	Mid	2437	15.953	19.367	≥ 0.5
	High	2462	16.242	19.313	≥ 0.5
802.11n (40M)	Low	2422	35.489	39.970	≥ 0.5
	Mid	2437	35.198	39.584	≥ 0.5
	High	2452	35.192	39.817	≥ 0.5



Test Plots

6dB Bandwidth measurement result





802.11b 6dB Bandwidth - Low CH 2412

802.11b 6dB Bandwidth - Mid CH 2437




802.11b 6dB Bandwidth - High CH 2462

802.11g 6dB Bandwidth - Low CH 2412




802.11g 6dB Bandwidth - Mid CH 2437


802.11g 6dB Bandwidth - High CH 2462




802.11n20 6dB Bandwidth - Low CH 2412




802.11n20 6dB Bandwidth - Mid CH 2437




802.11n20 6dB Bandwidth - High CH 2462



802.11n40 6dB Bandwidth - Low CH 2422




802.11n40 6dB Bandwidth - Mid CH 2437




802.11n40 6dB Bandwidth - High CH 2452


20 dB Bandwidth measurement result




802.11b 20dB Bandwidth - Low CH 2412




802.11b 20dB Bandwidth - Mid CH 2437




802.11b 20dB Bandwidth - High CH 2462




802.11g 20dB Bandwidth - Low CH 2412




802.11g 20dB Bandwidth - Mid CH 2437




802.11g 20dB Bandwidth - High CH 2462




802.11n20 20dB Bandwidth - Low CH 2412




802.11n20 20dB Bandwidth - Mid CH 2437




802.11n20 20dB Bandwidth - High CH 2462



802.11n40 20dB Bandwidth - Low CH 2422



802.11n40 20dB Bandwidth - Mid CH 2437




802.11n40 20dB Bandwidth - High CH 2452

6.3 Maximum Output Power

Temperature	23°C
Relative Humidity	51%
Atmospheric Pressure	1002mbar
Test date :	April 01, 2017
Tested By :	Loren Lou

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(b) (3),RSS210 (A8.4)	a)	FHSS in 2400-2483.5MHz with ≥ 75 channels: ≤ 1 Watt	<input type="checkbox"/>
	b)	FHSS in 5725-5850MHz: ≤ 1 Watt	<input type="checkbox"/>
	c)	For all other FHSS in the 2400-2483.5MHz band: ≤ 0.125 Watt.	<input type="checkbox"/>
	d)	FHSS in 902-928MHz with ≥ 50 channels: ≤ 1 Watt	<input type="checkbox"/>
	e)	FHSS in 902-928MHz with ≥ 25 & <50 channels: ≤ 0.25 Watt	<input type="checkbox"/>
	f)	DTS in 902-928MHz, 2400-2483.5MHz: ≤ 1 Watt	<input checked="" type="checkbox"/>

Test Setup	 <p style="text-align: center;">Spectrum Analyzer EUT</p>
------------	--

Test Procedure	<p>558074 D01 DTS MEAS Guidance v03r03, 9.1.2 Integrated band power method Maximum output power measurement procedure</p> <ul style="list-style-type: none"> - a) Set span to at least 1.5 times the OBW. - b) Set RBW = 1-5% of the OBW, not to exceed 1 MHz. - c) Set VBW $\geq 3 \times$ RBW. - d) Number of points in sweep $\geq 2 \times$ span / RBW. (This gives bin-to-bin spacing \leq RBW/2, so that narrowband signals are not lost between frequency bins.) - e) Sweep time = auto. - f) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode. - g) If transmit duty cycle $< 98\%$, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum
----------------	---

	<p>power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle $\geq 98\%$, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “ free run” .</p> <ul style="list-style-type: none"> - h) Trace average at least 100 traces in power averaging (i.e., RMS) mode. - i) Compute power by integrating the spectrum across the OBW of the signal using the instrument’ s band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data Yes N/A


Test Plot Yes (See below) N/A

Output Power measurement result


Type	Test mode	CH	Frequency (MHz)	Conducted Power (dBm)	Limit (dBm)	Result
Output power	802.11b	Low	2412	15.18	30	Pass
		Mid	2437	14.67	30	Pass
		High	2462	15.50	30	Pass
	802.11g	Low	2412	12.36	30	Pass
		Mid	2437	12.69	30	Pass
		High	2462	13.00	30	Pass
	802.11n (20M)	Low	2412	11.05	30	Pass
		Mid	2437	11.03	30	Pass
		High	2462	11.02	30	Pass
	802.11n (40M)	Low	2422	10.30	30	Pass
		Mid	2437	10.31	30	Pass
		High	2452	10.59	30	Pass

Test Plots


The Average Power




802.11b - AV Output power - Low CH 2412




802.11b - AV Output power - Mid CH 2437




802.11b - AV Output power - High CH 2462




802.11g - AV Output power - Low CH 2412




802.11g - AV Output power - Mid CH 2437




802.11g - AV Output power - High CH 2462




802.11n20 - AV Output power - Low CH 2412




802.11n20 - AV Output power - Mid CH 2437




802.11n20 - AV Output power - High CH 2462



802.11n40 - AV Output power - Low CH 2422




802.11n40 - AV Output power - Mid CH 2437



802.11n40 - AV Output power - High CH 2452

6.4 Power Spectral Density

Temperature	23°C
Relative Humidity	51%
Atmospheric Pressure	1002mbar
Test date :	April 01, 2017
Tested By :	Loren Lou

Spec	Item	Requirement	Applicable
§15.247(e)	a)	The power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.	<input checked="" type="checkbox"/>
Test Setup	 <p style="text-align: center;">Spectrum Analyzer EUT</p>		
Test Procedure	<p>558074 D01 DTS MEAS Guidance v03r03, 10.2 power spectral density method power spectral density measurement procedure</p> <ul style="list-style-type: none"> - a) Set analyzer center frequency to DTS channel center frequency. - b) Set the span to 1.5 times the DTS bandwidth. - c) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$. - d) Set the VBW $\geq 3 \times \text{RBW}$. - e) Detector = peak. - f) Sweep time = auto couple. - g) Trace mode = max hold. - h) Allow trace to fully stabilize. - i) Use the peak marker function to determine the maximum amplitude level within the RBW. - j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat. 		
Remark			
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail		


Test Data Yes N/A
 Test Plot Yes (See below) N/A

Power Spectral Density measurement result


Type	Test mode	CH	Freq (MHz)	PSD	Limit (dBm)	Result
				(dBm)		
PSD	802.11b	Low	2412	-7.791	8	Pass
		Mid	2437	-7.734	8	Pass
		High	2462	-6.859	8	Pass
	802.11g	Low	2412	-13.46	8	Pass
		Mid	2437	-11.10	8	Pass
		High	2462	-10.38	8	Pass
	802.11n (20M)	Low	2412	-13.47	8	Pass
		Mid	2437	-13.71	8	Pass
		High	2462	-12.48	8	Pass
	802.11n (40M)	Low	2422	-13.88	8	Pass
		Mid	2437	-14.60	8	Pass
		High	2452	-12.97	8	Pass

Test Plots


Power Spectral Density measurement result




PSD - Low CH 2412 - 802.11b




PSD - Mid CH 2437 - 802.11b




PSD - High CH 2462 - 802.11b




PSD - Low CH 2412 - 802.11g




PSD - Mid CH 2437 - 802.11g




PSD - High CH 2462 - 802.11g




PSD - Low CH 2412 - 802.11n20




PSD - Mid CH 2437 - 802.11n20




PSD - High CH 2472 - 802.11n20



PSD - Low CH 2422 - 802.11n40



PSD - Mid CH 2437 - 802.11n40




PSD - High CH 2452 - 802.11n40

6.5 Band-Edge & Unwanted Emissions into Restricted Frequency Bands

Temperature	24°C
Relative Humidity	52%
Atmospheric Pressure	1022mbar
Test date :	April 30, 2017
Tested By :	Loren Lou

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(d)	a)	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.	<input checked="" type="checkbox"/>

Test Setup	
------------	--

Test Procedure	<p>Radiated Method Only</p> <ul style="list-style-type: none"> - 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator. - 2. Position the EUT without connection to measurement instrument. Put it on the Rotated table and turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
----------------	---



Test Report No.	17070203-FCC-R2
Page	26 of 62


	<ul style="list-style-type: none"> - 3. First, set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, check the emission of EUT, if pass then set Spectrum Analyzer as below: <ul style="list-style-type: none"> a. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi Peak detection at frequency below 1GHz. b. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. c. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz. - 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency. - 5. Repeat above procedures until all measured frequencies were complete.
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data Yes N/A
 Test Plot Yes (See below) N/A


Test Plots

Band Edge measurement result

 <p>Date: 30.MAR.2017 15:00:03</p>	 <p>Date: 30.MAR.2017 15:14:26</p>
<p>Band Edge, Left Side (Peak) - 802.11b</p> <p>Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz</p>	<p>Band Edge, Right Side (Peak) - 802.11b</p> <p>Note: F1 is frequency 2483.5MHz</p>
<p>Note: (no need if PK value less than the AV limit)</p>	<p>Note: (no need if PK value less than the AV limit)</p>
<p>Band Edge, Left Side (Average) - 802.11b</p>	<p>Band Edge, Right Side (Average) - 802.11b</p>



Date: 30.MAR.2017 15:06:14



Date: 30.MAR.2017 15:16:03

Band Edge, Left Side (Peak) - 802.11g
Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz



Band Edge, Right Side (Peak) - 802.11g
Note: F1 is frequency 2483.5MHz

Note: (no need if PK value less than the AV limit)

Note: (no need if PK value less than the AV limit)

Band Edge, Left Side (Average) - 802.11g
Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz

Band Edge, Right Side (Average) - 802.11g
Note: F1 is frequency 2483.5MHz



Band Edge, Left Side (Peak) - 802.11n20
 Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz



Band Edge, Right Side (Peak) - 802.11n20
 Note: F1 is frequency 2483.5MHz

Note: (no need if PK value less than the AV limit)

Note: (no need if PK value less than the AV limit)

Band Edge, Left Side (Average) - 802.11n20
 Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz


Band Edge, Right Side (Average) - 802.11n20
 Note: F1 is frequency 2483.5MHz



Band Edge, Left Side (Peak) - 802.11n40
 Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz

Band Edge, Right Side (Peak) - 802.11n40
 Note: F1 is frequency 2483.5MHz

Note: (no need if PK value less than the AV limit)



Band Edge, Left Side (Average) - 802.11n40
 Note: F1 is frequency 2390MHz; F2 is frequency 2400MHz


Band Edge, Right Side (Average) - 802.11n40
 Note: F1 is frequency 2483.5MHz

6.6 AC Power Line Conducted Emissions

Temperature	24°C
Relative Humidity	55%
Atmospheric Pressure	1013mbar
Test date :	April 12, 2017
Tested By :	Loren Lou

Requirement(s):

Spec	Item	Requirement	Applicable														
47CFR§15.207, RSS210 (A8.1)	a)	For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 [mu] H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequencies ranges.	<input checked="" type="checkbox"/>														
		<table border="1"> <thead> <tr> <th rowspan="2">Frequency ranges (MHz)</th> <th colspan="2">Limit (dBµV)</th> </tr> <tr> <th>QP</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15 ~ 0.5</td> <td>66 – 56</td> <td>56 – 46</td> </tr> <tr> <td>0.5 ~ 5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5 ~ 30</td> <td>60</td> <td>50</td> </tr> </tbody> </table>		Frequency ranges (MHz)	Limit (dBµV)		QP	Average	0.15 ~ 0.5	66 – 56	56 – 46	0.5 ~ 5	56	46	5 ~ 30	60	50
		Frequency ranges (MHz)			Limit (dBµV)												
				QP	Average												
0.15 ~ 0.5	66 – 56	56 – 46															
0.5 ~ 5	56	46															
5 ~ 30	60	50															



Procedure	<ol style="list-style-type: none"> The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table. The power supply for the EUT was fed through a 50W/50mH EUT LISN, connected to filtered mains. The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss
-----------	---


Test Report No.	17070203-FCC-R2
Page	32 of 62

	<p>coaxial cable.</p> <ol style="list-style-type: none"> 4. All other supporting equipment were powered separately from another main supply. 5. The EUT was switched on and allowed to warm up to its normal operating condition. 6. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver. 7. High peaks, relative to the limit line, The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz. 8. Step 7 was then repeated for the LIVE line (for AC mains) or DC line (for DC power).
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data Yes N/A

Test Plot Yes (See below) N/A

Test Mode:	Transmitting Mode
-------------------	--------------------------




Test Data

Phase Line Plot at 120Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dBμV)	Detector	Corrected (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)
1	L1	0.5244	32.46	QP	10.03	42.49	56.00	-13.51
2	L1	0.5244	24.10	AVG	10.03	34.13	46.00	-11.87
3	L1	0.5712	35.32	QP	10.03	45.35	56.00	-10.65
4	L1	0.5712	23.81	AVG	10.03	33.84	46.00	-12.16
5	L1	0.6531	31.46	QP	10.03	41.49	56.00	-14.51
6	L1	0.6531	21.10	AVG	10.03	31.13	46.00	-14.87
7	L1	1.1172	28.38	QP	10.03	38.41	56.00	-17.59
8	L1	1.1172	15.88	AVG	10.03	25.91	46.00	-20.09
9	L1	2.6577	32.56	QP	10.05	42.61	56.00	-13.39
10	L1	2.6577	18.28	AVG	10.05	28.33	46.00	-17.67
11	L1	19.0212	31.97	QP	10.29	42.26	60.00	-17.74
12	L1	19.0212	18.64	AVG	10.29	28.93	50.00	-21.07

Test Mode:	Transmitting Mode
-------------------	--------------------------




Test Data

Phase Neutral Plot at 120Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dBµV)	Detector	Corrected (dB)	Result (dBµV)	Limit (dBµV)	Margin (dB)
1	N	0.5790	31.82	QP	10.02	41.84	56.00	-14.16
2	N	0.5790	15.29	AVG	10.02	25.31	46.00	-20.69
3	N	0.6921	28.62	QP	10.02	38.64	56.00	-17.36
4	N	0.6921	12.27	AVG	10.02	22.29	46.00	-23.71
5	N	1.1796	25.51	QP	10.03	35.54	56.00	-20.46
6	N	1.1796	9.09	AVG	10.03	19.12	46.00	-26.88
7	N	2.1663	28.61	QP	10.04	38.65	56.00	-17.35
8	N	2.1663	14.24	AVG	10.04	24.28	46.00	-21.72
9	N	2.9541	30.10	QP	10.05	40.15	56.00	-15.85
10	N	2.9541	13.81	AVG	10.05	23.86	46.00	-22.14
11	N	19.6881	29.58	QP	10.26	39.84	60.00	-20.16
12	N	19.6881	19.22	AVG	10.26	29.48	50.00	-20.52

Test Mode:	Transmitting Mode
-------------------	--------------------------




Test Data

Phase Line Plot at 240Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dBµV)	Detector	Corrected (dB)	Result (dBµV)	Limit (dBµV)	Margin (dB)
1	L1	0.2280	38.99	QP	10.03	49.02	62.52	-13.50
2	L1	0.2280	30.57	AVG	10.03	40.60	52.52	-11.92
3	L1	0.3216	35.77	QP	10.03	45.80	59.67	-13.87
4	L1	0.3216	29.33	AVG	10.03	39.36	49.67	-10.31
5	L1	0.7038	28.67	QP	10.03	38.70	56.00	-17.30
6	L1	0.7038	13.79	AVG	10.03	23.82	46.00	-22.18
7	L1	2.9346	29.96	QP	10.05	40.01	56.00	-15.99
8	L1	2.9346	19.39	AVG	10.05	29.44	46.00	-16.56
9	L1	5.2893	23.42	QP	10.08	33.50	60.00	-26.50
10	L1	5.2893	7.19	AVG	10.08	17.27	50.00	-32.73
11	L1	19.0368	29.99	QP	10.29	40.28	60.00	-19.72
12	L1	19.0368	15.61	AVG	10.29	25.90	50.00	-24.10

Test Mode:	Transmitting Mode
-------------------	--------------------------



Test Data

Phase Neutral Plot at 240Vac, 60Hz


No.	P/L	Frequency (MHz)	Reading (dBμV)	Detector	Corrected (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)
1	N	0.2280	40.99	QP	10.02	51.01	62.52	-11.51
2	N	0.2280	33.03	AVG	10.02	43.05	52.52	-9.47
3	N	0.5829	36.62	QP	10.02	46.64	56.00	-9.36
4	N	0.5829	29.09	AVG	10.02	39.11	46.00	-6.89
5	N	1.3707	29.29	QP	10.03	39.32	56.00	-16.68
6	N	1.3707	21.86	AVG	10.03	31.89	46.00	-14.11
7	N	2.0220	30.23	QP	10.04	40.27	56.00	-15.73
8	N	2.0220	21.00	AVG	10.04	31.04	46.00	-14.96
9	N	2.5251	36.30	QP	10.05	46.35	56.00	-9.65
10	N	2.5251	28.91	AVG	10.05	38.96	46.00	-7.04
11	N	4.1700	34.01	QP	10.06	44.07	56.00	-11.93
12	N	4.1700	24.59	AVG	10.06	34.65	46.00	-11.35

6.7 Radiated Spurious Emissions & Restricted Band

Temperature	24°C
Relative Humidity	55%
Atmospheric Pressure	1013mbar
Test date :	April 12, 2017
Tested By :	Loren Lou

Requirement(s):

Spec	Item	Requirement	Applicable										
47CFR§15.247(d), RSS210 (A8.5)	a)	<p>Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges</p> <table border="1"> <thead> <tr> <th>Frequency range (MHz)</th> <th>Field Strength (µV/m)</th> </tr> </thead> <tbody> <tr> <td>30 – 88</td> <td>100</td> </tr> <tr> <td>88 – 216</td> <td>150</td> </tr> <tr> <td>216 960</td> <td>200</td> </tr> <tr> <td>Above 960</td> <td>500</td> </tr> </tbody> </table>	Frequency range (MHz)	Field Strength (µV/m)	30 – 88	100	88 – 216	150	216 960	200	Above 960	500	<input checked="" type="checkbox"/>
	Frequency range (MHz)	Field Strength (µV/m)											
	30 – 88	100											
88 – 216	150												
216 960	200												
Above 960	500												
b)	<p>For non-restricted band, In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB or 30dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, determined by the measurement method on output power to be used. Attenuation below the general limits specified in § 15.209(a) is not required</p> <p><input checked="" type="checkbox"/> 20 dB down <input type="checkbox"/> 30 dB down</p>	<input checked="" type="checkbox"/>											
c)	<p>or restricted band, emission must also comply with the radiated emission limits specified in 15.209</p>	<input checked="" type="checkbox"/>											


<p>Test Setup</p>	
<p>Procedure</p>	<ol style="list-style-type: none"> 1. The EUT was switched on and allowed to warm up to its normal operating condition. 2. The test was carried out at the selected frequency points obtained from the EUT characterization. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner: <ol style="list-style-type: none"> a. Vertical or horizontal polarization (whichever gave the higher emission level over a full rotation of the EUT) was chosen. b. The EUT was then rotated to the direction that gave the maximum emission. c. Finally, the antenna height was adjusted to the height that gave the maximum emission. 3. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz. 4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz. 5. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.
<p>Remark</p>	<p>Different RF configuration has been evaluated but not much difference was found. The data presented here is the worst case data with EUT under 802.11n – HT20-2437MHz mode.</p>
<p>Result</p>	<p><input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail</p>

Test Data Yes N/A

Test Plot Yes (See below) N/A

Test Mode:	Transmitting Mode
-------------------	--------------------------

(Below 1GHz)




Test Data

Horizontal Polarity Plot @3m

No.	P/L	Frequency	Reading	Detect or	Ant_F	PA_G	Cab_L	Result	Limit	Margin	Height	Degree
		(MHz)	(dBuV/m)		(dB/m)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(°)
1	H	31.7313	29.77	peak	20.07	22.27	0.67	28.24	40.00	-11.76	100	70
2	H	52.5753	31.81	peak	8.12	22.39	0.79	18.33	40.00	-21.67	100	298
3	H	100.9340	31.64	peak	10.56	22.32	1.12	21.00	43.50	-22.50	100	104
4	H	156.4578	32.53	peak	12.60	22.29	1.37	24.21	43.50	-19.29	100	175
5	H	189.7385	35.55	peak	11.54	22.31	1.54	26.32	43.50	-17.18	100	77
6	H	790.6188	28.84	peak	21.29	21.17	2.94	31.90	46.00	-14.10	100	302

(Below 1GHz)



Test Data

Vertical Polarity Plot @3m

No.	P/L	Frequency	Reading	Detect or	Ant_F	PA_G	Cab_L	Result	Limit	Margin	Height	Degr ee
		(MHz)	(dBuV/m)		(dB/m)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(°)
1	V	32.4059	34.07	peak	19.55	22.27	0.69	32.04	40.00	-7.96	100	250
2	V	49.8814	44.07	peak	8.45	22.38	0.80	30.94	40.00	-9.06	200	183
3	V	89.5900	38.23	peak	7.98	22.32	0.96	24.85	43.50	-18.65	100	32
4	V	100.5806	33.55	peak	10.50	22.32	1.12	22.85	43.50	-20.65	100	62
5	V	169.0054	32.65	peak	11.88	22.26	1.36	23.63	43.50	-19.87	100	335
6	V	839.1818	29.88	peak	21.83	21.04	2.89	33.56	46.00	-12.44	100	98

Above 1GHz

Test Mode:	Transmitting Mode
-------------------	--------------------------

Low Channel (2412 MHz) (b mode worst case)

Frequency (MHz)	S.A. Reading (dB μ V)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord Amp. (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
4824	38.92	AV	V	33.8	6.86	32.69	46.89	54	-7.11
4824	38.53	AV	H	33.8	6.86	32.69	46.5	54	-7.5
4824	48.18	PK	V	33.8	6.86	32.69	56.15	74	-17.85
4824	47.49	PK	H	33.8	6.86	32.69	55.46	74	-18.54
17902	23.73	AV	V	45.12	11.57	32.11	48.31	54	-5.69
17902	22.5	AV	H	45.12	11.57	32.11	47.08	54	-6.92
17902	40.51	PK	V	45.12	11.57	32.11	65.09	74	-8.91
17902	39.47	PK	H	45.12	11.57	32.11	64.05	74	-9.95

Middle Channel (2437 MHz) (b mode worst case)

Frequency (MHz)	S.A. Reading (dB μ V)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord Amp. (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
4874	38.88	AV	V	33.6	6.82	32.71	46.59	54	-7.41
4874	38.58	AV	H	33.6	6.82	32.71	46.29	54	-7.71
4874	48.25	PK	V	33.6	6.82	32.71	55.96	74	-18.04
4874	47.72	PK	H	33.6	6.82	32.71	55.43	74	-18.57
17927	24.55	AV	V	45.17	11.63	32.18	49.17	54	-4.83
17927	22.3	AV	H	45.17	11.63	32.18	46.92	54	-7.08
17927	40.01	PK	V	45.17	11.63	32.18	64.63	74	-9.37
17927	39.97	PK	H	45.17	11.63	32.18	64.59	74	-9.41

High Channel (2462 MHz) (b mode worst case)

Frequency (MHz)	S.A. Reading (dB μ V)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord Amp. (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
4924	39.41	AV	V	33.83	6.95	32.79	47.4	54	-6.6
4924	39.38	AV	H	33.83	6.95	32.79	47.37	54	-6.63
4924	47.89	PK	V	33.83	6.95	32.79	55.88	74	-18.12
4924	47.39	PK	H	33.83	6.95	32.79	55.38	74	-18.62
17921	23.48	AV	V	45.19	11.61	32.24	48.04	54	-5.96
17921	22.93	AV	H	45.19	11.61	32.24	47.49	54	-6.51
17921	40.35	PK	V	45.19	11.61	32.24	64.91	74	-9.09
17921	39.71	PK	H	45.19	11.61	32.24	64.27	74	-9.73

Note:

- 1, The testing has been conformed to $10 \times 2462 \text{MHz} = 24,620 \text{MHz}$
- 2, All other emissions more than 30 dB below the limit
- 3, X-Axis, Y-Axis and Z-Axis were investigated. The results above show only the worst case.

Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
AC Line Conducted					
EMI test receiver	ESCS30	8471241027	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
Line Impedance	LI-125A	191106	09/24/2016	09/23/2017	<input checked="" type="checkbox"/>
Line Impedance	LI-125A	191107	09/24/2016	09/23/2017	<input checked="" type="checkbox"/>
LISN	ISN T800	34373	09/24/2016	09/23/2017	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/23/2016	09/22/2017	<input checked="" type="checkbox"/>
Transient Limiter	LIT-153	531118	08/31/2016	08/30/2017	<input checked="" type="checkbox"/>
RF conducted test					
Agilent ESA-E SERIES	E4407B	MY45108319	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
Power Splitter	1#	1#	08/31/2016	08/30/2017	<input checked="" type="checkbox"/>
DC Power Supply	E3640A	MY40004013	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
Radiated Emissions					
EMI test receiver	ESL6	100262	09/16/2016	09/15/2017	<input checked="" type="checkbox"/>
Positioning Controller	UC3000	MF780208282	11/18/2016	11/17/2017	<input checked="" type="checkbox"/>
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	08/31/2016	08/30/2017	<input checked="" type="checkbox"/>
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/23/2017	03/22/2018	<input checked="" type="checkbox"/>
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/20/2016	09/19/2017	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/23/2016	09/22/2017	<input checked="" type="checkbox"/>
Universal Radio Communication Tester	CMU200	121393	09/24/2016	09/23/2017	<input checked="" type="checkbox"/>


Annex B. EUT and Test Setup Photographs

Annex B.i. Photograph: EUT External Photo

Whole Package View




Adapter - Label View



Test Report No.	17070203-FCC-R2
Page	45 of 62

Adapter - Front View




EUT - Front View




EUT - Rear View



EUT - Top View



EUT - Bottom View



EUT - Left View




Test Report No.	17070203-FCC-R2
Page	48 of 62

EUT - Right View




Annex B.ii. Photograph: EUT Internal Photo

Cover Off - Top View 1




Cover Off - Top View 2



Test Report No.	17070203-FCC-R2
Page	50 of 62

Battery - Front View



Battery - Rear View




LCD - Front View




LCD - Rear View




Mainboard with Shielding - Front View




Mainboard without Shielding - Front View




Mainboard – Rear View



Small Mainboard - Front View




Small Mainboard – Rear View




GSM/PCS/UMTS-FDD Antenna View



WiFi/BT/BLE - Antenna View



GPS- Antenna View




Annex B.iii. Photograph: Test Setup Photo




Conducted Emissions Test Setup Front View



Conducted Emissions Test Setup Side View



Radiated Spurious Emissions Test Setup Below 1GHz




Radiated Spurious Emissions Test Setup Above
1GHz


Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

Annex C.ii. TEST SET UP BLOCK


Block Configuration Diagram for AC Line Conducted Emissions



Block Configuration Diagram for Radiated Emissions (Below 1GHz) .



Block Configuration Diagram for Radiated Emissions (Above 1GHz) .



Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Supporting Equipment:

Manufacturer	Equipment Description	Model	Serial No
BLU Products, Inc.	Adapter	TPA-46B050100UU	100UU

Supporting Cable:

Cable type	Shield Type	Ferrite Core	Length	Serial No
USB Cable	Un-shielding	No	0.8m	100UU

Test Report No.	17070203-FCC-R2
Page	61 of 62

Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see the attachment

Test Report No.	17070203-FCC-R2
Page	62 of 62

Annex E. DECLARATION OF SIMILARITY

N/A