

## RF Exposure Evaluation declaration

Product Name : iDEA<sup>+</sup> Docking Station

Model No. : PTI-7018N,PTI-7018NC,TEW-713RE,TEW-714RE

FCC ID : YHYPTI-7018N

Applicant : PARADIGM TECHNOLOGY INC.

Address : 3F.-1, No.49, Ln. 35, Jihu Rd., Neihu Dist., Taipei City  
114, Taiwan (R.O.C.)

Date of Receipt : Nov. 15, 2012

Date of Declaration : Jan. 22, 2013

Report No. : 12B261R-RFUSP42V01-A

The declaration results relate only to the samples calculated.

The declaration shall not be reproduced except in full without the written approval of Quietek Corporation.

This report must not be used to claim product endorsement by NVLAP any agency of the U.S. Government

## 1. RF Exposure Evaluation

### 1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

#### LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	F/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	F/1500	6
1500-100,000	--	--	1	30

F= Frequency in MHz

Friis Formula

Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

G = gain of antenna in linear scale

$\pi$  = 3.1416

R = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

### 1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

### 1.3. Test Result of RF Exposure Evaluation

Product : iDEA<sup>+</sup> Docking Station  
Test Item : RF Exposure Evaluation  
Test Site : No.3 OATS

#### Output Power Into Antenna & RF Exposure Evaluation Distance (2.12dBi):

Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )
250.0345	0.081046

Power density in column 4 is much lower than the limit (1 mW/cm<sup>2</sup>).