

FCC 47 CFR PART 15 SUBPART C

RF Test Report

Applicant : SHENZHEN JEHE TECHNOLOGY DEVELOPMENT CO.,LTD.
Product Type : MiniPC
Trade Name : GIADA
Model Number : F21XX (The mark“X”represents any letter A-Z ,any alphanumeric character or blank)
Applicable Standard : FCC 47 CFR PART 15 SUBPART C
ANSI C63.10:2013
KDB 558074 D01 v03r04
Receive Date : Dec. 01, 2015
Test Period : Dec. 11 ~ Dec. 14, 2015
Issue Date : Jan. 14, 2016

Issue by

A Test Lab Techno Corp.
No. 140-1, Changan Street, Bade District,
Taoyuan City 33465, Taiwan (R.O.C)
Tel : +886-3-2710188 / Fax : +886-3-2710190



Taiwan Accreditation Foundation accreditation number: 1330

Note: This report shall not be reproduced except in full, without the written approval of A Test Lab Techno Corp. This document may be altered or revised by A Test Lab Techno Corp. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF, or any government agencies. The test results in the report only apply to the tested sample.

Revision History

Rev.	Issue Date	Revisions	Revised By
00	Dec. 24, 2015	Initial Issue	
01	Jan. 14, 2016	Revised report information.	Peggy Chang

TABLE OF CONTENTS

1	General Information.....	6
2	EUT Description	7
3	Test Methodology	8
	3.1. Mode of Operation.....	8
	3.2. EUT Exercise Software	12
	3.3. Configuration of Test System Details.....	13
	3.4. Test Site Environment.....	14
4	Conducted Emission Measurement.....	15
	4.1. Limit.....	15
	4.2. Test Instruments	15
	4.3. Test Setup	15
	4.4. Test Procedure	16
	4.5. Test Result.....	17
5	Radiated Emission Measurement.....	19
	5.1. Limit.....	19
	5.2. Test Instruments	19
	5.3. Setup.....	20
	5.4. Test Procedure	22
	5.5. Test Result.....	24
6	Maximum Conducted Output Power Measurement.....	35
	6.1. Limit.....	35
	6.2. Test Setup	35
	6.3. Test Instruments	35
	6.4. Test Procedure	35
	6.5. Test Result.....	36
7	6dB RF Bandwidth Measurement.....	38
	7.1. Limit.....	38
	7.2. Test Setup	38
	7.3. Test Instruments	38
	7.4. Test Procedure	38
	7.5. Test Result.....	39
	7.6. Test Graphs	40

8	Maximum Power Density Measurement	44
8.1.	Limit.....	44
8.2.	Test Setup	44
8.3.	Test Instruments	44
8.4.	Test Procedure	44
8.5.	Test Result.....	45
8.6.	Test Graphs	46
9	Out of Band Conducted Emissions Measurement.....	50
9.1.	Limit.....	50
9.2.	Test Setup	50
9.3.	Test Instruments	50
9.4.	Test Procedure	50
9.5.	Test Graphs	51
10	Antenna Measurement	63
10.1.	Limit.....	63
10.2.	Antenna Connector Construction	63

1 General Information

1.1 Summary of Test Result

Standard	Item	Result	Remark
15.247			
15.207	AC Power Conducted Emission	PASS	-----
Standard	Item	Result	Remark
15.247			
15.247(d)	Transmitter Radiated Emissions	PASS	-----
15.247(b)(3)	Max. Output Power	PASS	-----
15.247(a)(2)	6dB RF Bandwidth	PASS	-----
15.247(e)	Power Spectral Density	PASS	-----
15.247(d)	Out of Band Conducted Spurious Emission	PASS	-----
15.203	Antenna Requirement	PASS	-----

The test results of this report relate only to the tested sample(s) identified in this report. Manufacturer or whom it may concern should recognize the pass or fail of the test result.

1.2 Measurement Uncertainty

Test Item	Frequency Range	Uncertainty (dB)
Conducted Emission	9kHz ~ 150KHz	2.7
	150kHz ~ 30MHz	2.8
Radiated Emission	30MHz ~ 1000MHz	6.300
	1000MHz ~ 18000MHz	5.474
	18000MHz ~ 26500MHz	5.630
	26500MHz ~ 40000MHz	5.054

2 EUT Description

Applicant	SHENZHEN JEHE TECHNOLOGY DEVELOPMENT CO.,LTD. 2/F, block A, Tsinghua Information Harbor, North Section, Shenzhen Hi-tech Park, Nanshan District, Shenzhen, China			
Manufacturer	CHEER ASCENT ELECTRONICS (SHENZHEN) CO., LTD. A1 Building, FuHai Industrial Estate, FuHai Road, FuYong, BaoAn, ShenZhen, China			
Product Type	MiniPC			
Trade Name	GIADA			
Model Number	F21XX (The mark "X" represents any letter A-Z ,any alphanumeric character or blank)			
FCC ID	YIKF210			
Operate Freq. Band	Frequency Range (MHz)	Modulation	Channel Bandwidth	Data Rate 400 GI (ns)
IEEE 802.11b	2412 ~ 2462	DSSS	20MHz	Up to 11Mbps
IEEE 802.11g	2412 ~ 2462	DSSS+OFDM	20MHz	Up to 54Mbps
IEEE 802.11n 2.4GHz 20MHz	2412 ~ 2462	OFDM	20MHz	Up to 72.2Mbps
IEEE 802.11n 2.4GHz 40MHz	2422 ~ 2452	OFDM	40MHz	Up to 150Mbps
Antenna Delivery	1TX + 1RX			
Antenna Type	Omni Directional Antenna (Reversed-SMA Connector)			
Antenna Gain	2 dBi			
RF Output Power	IEEE 802.11b: 0.017 W /12.26 dBm IEEE 802.11g: 0.147 W / 21.68 dBm IEEE 802.11n 2.4GHz 20MHz: 0.142 W / 21.53 dBm IEEE 802.11n 2.4GHz 40MHz: 0.109 W / 20.37 dBm			

3 Test Methodology

3.1. Mode of Operation

Decision of Test ATL has verified the construction and function in typical operation. All the test modes were carried out with the EUT in normal operation, which was shown in this test report and defined as:

Test Mode
Mode 1: Normal operation mode
Mode 2: IEEE 802.11b link mode
Mode 3: IEEE 802.11g link mode
Mode 4: IEEE 802.11n 2.4GHz 20MHz link mode
Mode 5: IEEE 802.11n 2.4GHz 40MHz link mode

Software used to control the EUT for staying in continuous transmitting mode was programmed.


After verification, all tests were carried out with the worst case test modes as shown below except radiated spurious emission below 1GHz and power line conducted emissions below 30MHz, which worst case was in normal link mode only.


Test Mode	Antenna Delivery	Test Channel	Data Rate 400G1 (ns)
Mode 2: IEEE 802.11b link mode	1TX / 1RX	1, 6, 11	1
Mode 3: IEEE 802.11g link mode	1TX / 1RX	1, 6, 11	6
Mode 4: IEEE 802.11n 2.4GHz 20MHz link mode	1TX / 1RX	1, 6, 11	6.5
Mode 5: IEEE 802.11n 2.4GHz 40MHz link mode	1TX / 1RX	3, 6, 9	13.5

Duty cycle

Test Mode	Frequency (MHz)	on time (ms)	on+off time (ms)	Duty cycle	Duty Factor (dB)	1/T Minimum VBW (kHz)
Mode 2: IEEE 802.11b link mode	2412.0	1.000	1.000	1.000	0.000	0.010
Mode 3: IEEE 802.11g link mode	2412.0	1.000	1.000	1.000	0.000	0.010
Mode 4: IEEE 802.11n 2.4GHz 20MHz link mode	2412.0	1.000	1.000	1.000	0.000	0.010
Mode 5: IEEE 802.11n 2.4GHz 40MHz link mode	2422.0	1.000	1.000	1.000	0.000	0.010


Duty Cycle Graphs





Mode 4: IEEE 802.11n 2.4GHz 20MHz Mode

<p>On time</p>	
<p>On+off time</p>	




3.2. EUT Exercise Software

1	Setup the EUT shown on 3.3.
2	Turn on the power of all equipment.
3	Turn on Wi-Fi function.
4	EUT run test program.


Measurement Software	
1	EZ-EMC Ver. ATL-03A1-1
2	EZ-EMC Ver ATL-ITC-3A1-1

3.3. Configuration of Test System Details

Conducted Emissions



Radiated Emissions



3.4. Test Site Environment

Items	Required (IEC 60068-1)	Actual
Temperature (°C)	15-35	26
Humidity (%RH)	25-75	60
Barometric pressure (mbar)	860-1060	950

4 Conducted Emission Measurement

4.1. Limit

Frequency (MHz)	Quasi-peak	Average
0.15 - 0.5	66 to 56	56 to 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50


4.2. Test Instruments

Describe	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
Test Receiver	R&S	ESCI	100367	06/25/2015	(1)
LISN	R&S	ENV216	101040	03/10/2015	(1)
LISN	R&S	ENV216	101041	03/06/2015	(1)
RF Cable	Woken	00100D1380194M	TE-02-02	06/26/2015	(1)
Test Site	ATL	TE02	TE02	N.C.R.	-----

Remark: (1) Calibration period 1 year. (2) Calibration period 2 years. (3) Calibration period 3 years.

Note: N.C.R. = No Calibration Request.

4.3. Test Setup



4.4. Test Procedure

The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination.


For A.C. mains conducted interference, measured both sides of A.C. lines and carried out using quasi-peak and average detector receivers of maximum conducted interference.

Conducted emissions were investigated over the frequency range from 0.15 MHz to 30 MHz using a receiver bandwidth of 9 kHz. The equipment under test (EUT) shall meet the limits in section 4.1, as applicable, including the average limit and the quasi-peak limit when using respectively, an average detector and quasi-peak detector measured in accordance with the methods described of related standard. The voltage limits shall be met. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.

If the reading of the measuring receiver shows fluctuations close to the limit, the reading shall be observed for at least 15 s at each measurement frequency; the higher reading shall be recorded with the exception of any brief isolated high reading which shall be ignored.

4.5. Test Result

Standard:	FCC Part 15C	Line:	L1
Test item:	Conducted Emission	Power:	AC 120V/60Hz
Model Number:	F210	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 1	Date:	12/14/2015
		Test By:	Eric Ou Yang
Description:			




No.	Frequency (MHz)	QP reading (dBuV)	AVG reading (dBuV)	Correction factor (dB)	QP result (dBuV)	AVG result (dBuV)	QP limit (dBuV)	AVG limit (dBuV)	QP margin (dB)	AVG margin (dB)	Remark
1	0.1540	41.06	19.41	9.69	50.75	29.10	65.78	55.78	-15.03	-26.68	Pass
2	0.4740	39.49	31.48	9.70	49.19	41.18	56.44	46.44	-7.25	-5.26	Pass
3	0.6460	33.99	26.95	9.70	43.69	36.65	56.00	46.00	-12.31	-9.35	Pass
4	1.1420	34.25	28.05	9.73	43.98	37.78	56.00	46.00	-12.02	-8.22	Pass
5	1.5580	33.64	27.47	9.75	43.39	37.22	56.00	46.00	-12.61	-8.78	Pass
6	2.5140	33.88	27.90	9.79	43.67	37.69	56.00	46.00	-12.33	-8.31	Pass

Note: 1. Result (dBuV) = Correction factor (dB) + Reading(dBuV).

2. Correction factor (dB) = Cable loss (dB) + L.I.S.N. factor (dB).

Standard:	FCC Part 15C	Line:	N
Test item:	Conducted Emission	Power:	AC 120V/60Hz
Model Number:	F210	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 1	Date:	12/14/2015
		Test By:	Eric Ou Yang
Description:			



No.	Frequency (MHz)	QP reading (dBuV)	AVG reading (dBuV)	Correction factor (dB)	QP result (dBuV)	AVG result (dBuV)	QP limit (dBuV)	AVG limit (dBuV)	QP margin (dB)	AVG margin (dB)	Remark
1	0.1620	40.16	25.99	9.66	49.82	35.65	65.36	55.36	-15.54	-19.71	Pass
2	0.1900	36.68	23.16	9.65	46.33	32.81	64.04	54.04	-17.71	-21.23	Pass
3	0.4700	39.20	32.40	9.67	48.87	42.07	56.51	46.51	-7.64	-4.44	Pass
4	0.7220	34.29	27.80	9.68	43.97	37.48	56.00	46.00	-12.03	-8.52	Pass
5	1.0500	32.00	25.37	9.69	41.69	35.06	56.00	46.00	-14.31	-10.94	Pass
6	1.5300	33.44	27.03	9.72	43.16	36.75	56.00	46.00	-12.84	-9.25	Pass

Note: 1. Result (dBuV) = Correction factor (dB) + Reading(dBuV).

2. Correction factor (dB) = Cable loss (dB) + L.I.S.N. factor (dB).

5 Radiated Emission Measurement

5.1. Limit

According to §15.209(a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V}/\text{m}$ at meter)	Measurement Distance (meters)
0.009 – 0.490	2400 / F (kHz)	300
0.490 – 1.705	24000 / F (kHz)	30
1.705 – 30.0	30	30
30 - 88	100**	3
88-216	150**	3
216-960	200**	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

5.2. Test Instruments


3 Meter Chamber					
Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
RF Pre-selector	Agilent	N9039A	MY46520256	01/06/2015	(1)
Spectrum Analyzer	Agilent	E4446A	MY46180578	01/06/2015	(1)
Pre Amplifier	Agilent	8449B	3008A02237	02/24/2015	(1)
Pre Amplifier	Agilent	8447D	2944A10961	02/24/2015	(1)
Broadband Antenna (30MHz~1GHz)	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	9163-270	08/11/2015	(1)
Horn Antenna (1~18GHz)	SCHWARZBECK MESS-ELEKTRONIK	BBHA9120D	9120D-550	06/12/2015	(1)
Horn Antenna (18~40GHz)	SCHWARZBECK MESS-ELEKTRONIK	BBHA9170	9170-320	07/06/2015	(1)
Loop Antenna	COM-POWER CORPORATION	AL-130	121014	02/02/2015	(1)
Microwave Cable	EMCI	EMC-104-SM-S M-14000	140202	02/24/2015	(1)
Microwave Cable	EMCI	EMC104-SM-S M-600	140301	02/24/2015	(1)
Test Site	ATL	TE01	888001	08/27/2015	(1)

Remark: (1) Calibration period 1 year. (2) Calibration period 2 years. (3) Calibration period 3 years.


Note: N.C.R. = No Calibration Request.

5.3. Setup


9kHz ~ 30MHz



Below 1GHz



Above 1GHz



5.4. Test Procedure

Final radiation measurements were made on a three-meter, Semi Anechoic Chamber. The EUT system was placed on a nonconductive turntable which is 0.8 or 1.5 meters height (below 1GHz use 0.8m turntable / above 1GHz use 1.5m turntable), top surface 1.0 x 1.5 meter. The spectrum was examined from 250 MHz to 2.5 GHz in order to cover the whole spectrum below 10th harmonic which could generate from the EUT. During the test, EUT was set to transmit continuously & Measurements spectrum range from 9 kHz to 26.5 GHz is investigated.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, and then the video bandwidth is set to 1 MHz for peak measurements and 10 Hz for average measurements when Duty cycle >0.98 / $1/T$ for average measurements when Duty cycle <0.98 . A nonconductive material surrounded the EUT to supporting the EUT for standing on three orthogonal planes. At each condition, the EUT was rotated 360 degrees, and the antenna was raised and lowered from one to four meters to find the maximum emission levels. Measurements were taken using both horizontal and vertical antenna polarization.

SCHWARZBECK MESS-ELEKTRONIK Biconilog Antenna (mode VULB9163) at 3 Meter and the SCHWARZBECK Double Ridged Guide Antenna (model BBHA9120D&9170) was used in frequencies 1 –26.5 GHz at a distance of 3 meter. The antenna at an angle toward the source of the emission. All test results were extrapolated to equivalent signal at 3 meters utilizing an inverse linear distance extrapolation Factor (20dB/decade).

For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

Appropriate preamplifiers were used for improving sensitivity and precautions were taken to avoid overloading or desensitizing the spectrum analyzer. No post – detector video filters were used in the test.

The spectrum analyzer's 6 dB bandwidth was set to 1 MHz, and the analyzer was operated in the peak detection mode, for frequencies both below and up 1 GHz. The average levels were obtained by subtracting the duty cycle correction factor from the peak readings.

The following procedures were used to convert the emission levels measured in decibels referenced to 1 microvolt (dBuV) into field intensity in micro volts pre meter ($\mu\text{V}/\text{m}$).

The actual field intensity in decibels referenced to 1 microvolt in to field intensity in micro volts per meter (dBuV/m).

The actual field intensity in referenced to 1 microvolt per meter (dBuV/m) is determined by algebraically adding the measured reading in dBuV, the antenna factor (dB), and cable loss (dB) and Subtracting the gain of preamplifier (dB) is auto calculate in spectrum analyzer.

(1) $\text{Amplitude (dBuV/m)} = \text{FI (dBuV)} + \text{AF (dBuV)} + \text{CL (dBuV)} - \text{Gain (dB)}$

FI= Reading of the field intensity.

AF= Antenna factor.

CL= Cable loss.

P.S Amplitude is auto calculate in spectrum analyzer.

(2) $\text{Actual Amplitude (dBuV/m)} = \text{Amplitude (dBuV)} - \text{Dis(dB)}$

The FCC specified emission limits were calculated according the EUT operating frequency and by following linear interpolation equations:

(a) For fundamental frequency : Transmitter Output < +30dBm

(b) For spurious frequency : Spurious emission limits = fundamental emission limit /10

Data of measurement within this frequency range without mark in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

5.5. Test Result
Below 1GHz

Standard:	FCC Part 15C	Test Distance:	3m
Test item:	Radiated Emission	Power:	AC 120V/60Hz
Model Number:	F210	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 1	Date:	12/11/2015
		Test By:	Eric Ou Yang

Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
148.5000	47.80	-11.29	36.51	43.50	-6.99	QP	H
180.0000	46.28	-12.38	33.90	43.50	-9.60	QP	H
297.0000	40.81	-9.27	31.54	46.00	-14.46	QP	H
445.0000	42.94	-6.30	36.64	46.00	-9.36	QP	H
672.0000	36.82	-1.86	34.96	46.00	-11.04	QP	H
742.0000	39.36	-0.34	39.02	46.00	-6.98	QP	H
148.5000	45.59	-11.29	34.30	43.50	-9.20	QP	V
296.5000	39.15	-9.27	29.88	46.00	-16.12	QP	V
445.0000	43.84	-6.30	37.54	46.00	-8.46	QP	V
593.5000	40.16	-3.29	36.87	46.00	-9.13	QP	V
768.0000	34.36	0.09	34.45	46.00	-11.55	QP	V
890.0000	36.61	2.55	39.16	46.00	-6.84	QP	V

Note: No emission found between lowest internal used/generated frequency to 30MHz (9kHz~30MHz).

Above 1GHz

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	F210			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	Mode 2			Date:	12/11/2015		
Frequency:	2412MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
3002.000	37.99	1.32	39.31	74.00	-34.69	peak	H
4647.000	31.96	6.83	38.79	74.00	-35.21	peak	H
6705.000	32.60	12.04	44.64	74.00	-29.36	peak	H
3009.000	36.88	1.35	38.23	74.00	-35.77	peak	V
4598.000	32.53	6.67	39.20	74.00	-34.80	peak	V
6754.000	33.04	12.15	45.19	74.00	-28.81	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	F210			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	Mode 2			Date:	12/11/2015		
Frequency:	2437MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
3051.000	35.90	1.55	37.45	74.00	-36.55	peak	H
4619.000	31.78	6.74	38.52	74.00	-35.48	peak	H
6719.000	32.11	12.07	44.18	74.00	-29.82	peak	H
3065.000	34.75	1.62	36.37	74.00	-37.63	peak	V
4591.000	31.89	6.64	38.53	74.00	-35.47	peak	V
6691.000	30.80	12.00	42.80	74.00	-31.20	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	F210			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	Mode 2			Date:	12/11/2015		
Frequency:	2462MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
3030.000	37.89	1.46	39.35	74.00	-34.65	peak	H
4598.000	31.52	6.67	38.19	74.00	-35.81	peak	H
6677.000	32.80	11.97	44.77	74.00	-29.23	peak	H
3030.000	37.04	1.46	38.50	74.00	-35.50	peak	V
4577.000	30.07	6.59	36.66	74.00	-37.34	peak	V
6642.000	32.09	11.90	43.99	74.00	-30.01	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	F210			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	Mode 3			Date:	12/11/2015		
Frequency:	2412MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
3058.000	35.52	1.58	37.10	74.00	-36.90	peak	H
4605.000	30.44	6.69	37.13	74.00	-36.87	peak	H
6733.000	31.87	12.11	43.98	74.00	-30.02	peak	H
3058.000	37.26	1.58	38.84	74.00	-35.16	peak	V
4605.000	32.70	6.69	39.39	74.00	-34.61	peak	V
6677.000	32.94	11.97	44.91	74.00	-29.09	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	F210			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	Mode 3			Date:	12/11/2015		
Frequency:	2437MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
3009.000	35.68	1.35	37.03	74.00	-36.97	peak	H
4654.000	30.79	6.86	37.65	74.00	-36.35	peak	H
6670.000	31.95	11.96	43.91	74.00	-30.09	peak	H
3065.000	35.30	1.62	36.92	74.00	-37.08	peak	V
4605.000	29.98	6.69	36.67	74.00	-37.33	peak	V
6747.000	30.80	12.13	42.93	74.00	-31.07	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	F210			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	Mode 3			Date:	12/11/2015		
Frequency:	2462MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
3002.000	35.54	1.32	36.86	74.00	-37.14	peak	H
4619.000	31.75	6.74	38.49	74.00	-35.51	peak	H
6691.000	32.09	12.00	44.09	74.00	-29.91	peak	H
3037.000	36.89	1.48	38.37	74.00	-35.63	peak	V
4619.000	31.05	6.74	37.79	74.00	-36.21	peak	V
6705.000	30.15	12.04	42.19	74.00	-31.81	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	F210			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	Mode 4			Date:	12/11/2015		
Frequency:	2412MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
3023.000	36.29	1.42	37.71	74.00	-36.29	peak	H
4598.000	31.66	6.67	38.33	74.00	-35.67	peak	H
6691.000	31.23	12.00	43.23	74.00	-30.77	peak	H
3037.000	35.93	1.48	37.41	74.00	-36.59	peak	V
4605.000	30.47	6.69	37.16	74.00	-36.84	peak	V
6754.000	31.29	12.15	43.44	74.00	-30.56	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	F210			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	Mode 4			Date:	12/11/2015		
Frequency:	2437MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
3030.000	36.24	1.46	37.70	74.00	-36.30	peak	H
4577.000	31.74	6.59	38.33	74.00	-35.67	peak	H
6726.000	31.17	12.09	43.26	74.00	-30.74	peak	H
3051.000	36.29	1.55	37.84	74.00	-36.16	peak	V
4577.000	31.13	6.59	37.72	74.00	-36.28	peak	V
6705.000	30.97	12.04	43.01	74.00	-30.99	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	F210			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	Mode 4			Date:	12/11/2015		
Frequency:	2462MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
3030.000	36.74	1.46	38.20	74.00	-35.80	peak	H
4577.000	29.54	6.59	36.13	74.00	-37.87	peak	H
6649.000	31.24	11.90	43.14	74.00	-30.86	peak	H
3037.000	35.83	1.48	37.31	74.00	-36.69	peak	V
4598.000	30.08	6.67	36.75	74.00	-37.25	peak	V
6726.000	30.35	12.09	42.44	74.00	-31.56	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	F210			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	Mode 5			Date:	12/11/2015		
Frequency:	2422MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
3023.000	37.14	1.42	38.56	74.00	-35.44	peak	H
4647.000	30.34	6.83	37.17	74.00	-36.83	peak	H
6565.000	30.75	11.71	42.46	74.00	-31.54	peak	H
3023.000	37.38	1.42	38.80	74.00	-35.20	peak	V
4605.000	33.09	6.69	39.78	74.00	-34.22	peak	V
6691.000	32.03	12.00	44.03	74.00	-29.97	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	F210			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	Mode 5			Date:	12/11/2015		
Frequency:	2437MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
3065.000	34.69	1.62	36.31	74.00	-37.69	peak	H
4605.000	31.25	6.69	37.94	74.00	-36.06	peak	H
6663.000	31.81	11.93	43.74	74.00	-30.26	peak	H
3009.000	36.88	1.35	38.23	74.00	-35.77	peak	V
4619.000	32.37	6.74	39.11	74.00	-34.89	peak	V
6691.000	32.72	12.00	44.72	74.00	-29.28	peak	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	F210			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	Mode 5			Date:	12/11/2015		
Frequency:	2452MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
3051.000	34.80	1.55	36.35	74.00	-37.65	peak	H
4619.000	29.95	6.74	36.69	74.00	-37.31	peak	H
6789.000	30.41	12.23	42.64	74.00	-31.36	peak	H
3030.000	36.62	1.46	38.08	74.00	-35.92	peak	V
4626.000	31.60	6.77	38.37	74.00	-35.63	peak	V
6726.000	30.71	12.09	42.80	74.00	-31.20	peak	V

Band Edge

Standard:	FCC Part 15C	Test Distance:	3m
Test item:	Radiated Emission	Power:	AC 120V/60Hz
Model Number:	F210	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 2	Date:	12/11/2015
Frequency:	2412 MHz	Test By:	Eric Ou Yang

Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
2373.470	56.02	-0.39	55.63	74.00	-18.37	peak	H
2373.470	46.06	-0.39	45.67	54.00	-8.33	AVG	H
2390.000	48.60	-0.33	48.27	74.00	-25.73	peak	H
2373.800	55.48	-0.39	55.09	74.00	-18.91	peak	V
2373.800	44.14	-0.39	43.75	54.00	-10.25	AVG	V
2390.000	52.94	-0.33	52.61	74.00	-21.39	peak	V
2390.000	41.34	-0.33	41.01	54.00	-12.99	AVG	V

Standard:	FCC Part 15C	Test Distance:	3m
Test item:	Radiated Emission	Power:	AC 120V/60Hz
Model Number:	F210	Temp.(°C)/Hum.(%RH):	26(°C)/60%RH
Mode:	Mode 2	Date:	12/11/2015
Frequency:	2462 MHz	Test By:	Eric Ou Yang

Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
2483.500	50.21	0.03	50.24	74.00	-23.76	peak	H
2487.600	51.65	0.04	51.69	74.00	-22.31	peak	H
2483.500	49.82	0.03	49.85	74.00	-24.15	peak	V
2488.600	53.42	0.05	53.47	74.00	-20.53	peak	V
2488.600	45.18	0.05	45.23	54.00	-8.77	AVG	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	F210			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	Mode 3			Date:	12/11/2015		
Frequency:	2412 MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
2373.690	56.00	-0.39	55.61	74.00	-18.39	peak	H
2373.690	45.98	-0.39	45.59	54.00	-8.41	AVG	H
2390.000	61.42	-0.33	61.09	74.00	-12.91	peak	H
2390.000	47.38	-0.33	47.05	54.00	-6.95	AVG	H
2389.310	67.35	-0.33	67.02	74.00	-6.98	peak	V
2389.310	50.62	-0.33	50.29	54.00	-3.71	AVG	V
2390.000	67.79	-0.33	67.46	74.00	-6.54	peak	V
2390.000	51.96	-0.33	51.63	54.00	-2.37	AVG	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	F210			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	Mode 3			Date:	12/11/2015		
Frequency:	2462 MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
2483.500	62.24	0.03	62.27	74.00	-11.73	peak	H
2483.500	47.79	0.03	47.82	54.00	-6.18	AVG	H
2483.800	62.49	0.03	62.52	74.00	-11.48	peak	H
2483.800	47.44	0.03	47.47	54.00	-6.53	AVG	H
2483.500	63.78	0.03	63.81	74.00	-10.19	peak	V
2483.500	49.80	0.03	49.83	54.00	-4.17	AVG	V
2484.320	65.58	0.03	65.61	74.00	-8.39	peak	V
2484.320	48.67	0.03	48.70	54.00	-5.30	AVG	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	F210			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	Mode 4			Date:	12/11/2015		
Frequency:	2412 MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
2373.690	57.18	-0.39	56.79	74.00	-17.21	peak	H
2373.690	46.65	-0.39	46.26	54.00	-7.74	AVG	H
2390.000	62.42	-0.33	62.09	74.00	-11.91	peak	H
2390.000	45.48	-0.33	45.15	54.00	-8.85	AVG	H
2389.420	69.68	-0.33	69.35	74.00	-4.65	peak	V
2389.420	51.13	-0.33	50.80	54.00	-3.20	AVG	V
2390.000	69.32	-0.33	68.99	74.00	-5.01	peak	V
2390.000	52.03	-0.33	51.70	54.00	-2.30	AVG	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	F210			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	Mode 4			Date:	12/11/2015		
Frequency:	2462 MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
2483.500	60.96	0.03	60.99	74.00	-13.01	peak	H
2483.500	46.37	0.03	46.40	54.00	-7.60	AVG	H
2484.240	64.60	0.03	64.63	74.00	-9.37	peak	H
2484.240	45.88	0.03	45.91	54.00	-8.09	AVG	H
2483.500	65.42	0.03	65.45	74.00	-8.55	peak	V
2483.500	48.50	0.03	48.53	54.00	-5.47	AVG	V
2484.520	66.28	0.03	66.31	74.00	-7.69	peak	V
2484.520	47.63	0.03	47.66	54.00	-6.34	AVG	V

Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	F210			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	Mode 5			Date:	12/11/2015		
Frequency:	2422 MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
2388.840	60.67	-0.33	60.34	74.00	-13.66	peak	H
2388.840	44.59	-0.33	44.26	54.00	-9.74	AVG	H
2390.000	56.56	-0.33	56.23	74.00	-17.77	peak	H
2390.000	45.63	-0.33	45.30	54.00	-8.70	AVG	H
2388.960	69.44	-0.33	69.11	74.00	-4.89	peak	V
2388.960	52.00	-0.33	51.67	54.00	-2.33	AVG	V
2390.000	65.28	-0.33	64.95	74.00	-9.05	peak	V
2390.000	52.85	-0.33	52.52	54.00	-1.48	AVG	V


Standard:	FCC Part 15C			Test Distance:	3m		
Test item:	Radiated Emission			Power:	AC 120V/60Hz		
Model Number:	F210			Temp.(°C)/Hum.(%RH):	26(°C)/60%RH		
Mode:	Mode 5			Date:	12/11/2015		
Frequency:	2452 MHz			Test By:	Eric Ou Yang		
Frequency (MHz)	Reading (dBuV)	Correct Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Polar. H / V
2483.500	54.06	0.03	54.09	74.00	-19.91	peak	H
2483.500	42.55	0.03	42.58	54.00	-11.42	AVG	H
2484.400	57.63	0.03	57.66	74.00	-16.34	peak	H
2484.400	42.45	0.03	42.48	54.00	-11.52	AVG	H
2483.500	57.44	0.03	57.47	74.00	-16.53	peak	V
2483.500	44.14	0.03	44.17	54.00	-9.83	AVG	V
2485.750	60.52	0.03	60.55	74.00	-13.45	peak	V
2485.750	43.90	0.03	43.93	54.00	-10.07	AVG	V

6 Maximum Conducted Output Power Measurement

6.1. Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for maximum output power is 30dBm.

6.2. Test Setup



6.3. Test Instruments

Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
Single Channel PK Power Sensor	Agilent	N1911A	MY45101619	12/15/2014	(1)
Wideband Power Meter	Agilent	N1921A	MY45241957	12/15/2014	(1)
Microwave Cable	EMCI	EMC104-SM-S M-1500	140303	02/24/2015	(1)
Test Site	ATL	TE05	TE05	N.C.R.	-----

Remark: (1) Calibration period 1 year. (2) Calibration period 2 years. (3) Calibration period 3 years.

Note: N.C.R. = No Calibration Request.

6.4. Test Procedure

The tests below are run with the EUT's transmitter set at high power in TX mode. The EUT is needed to force selection of output power level and channel number. While testing, EUT was set to transmit continuously. Remove the Subjective device's antenna and connect the RF output port to power sensor. The maximum output power shall not exceed 1 watt.

Use a direct connection between the antenna port of transmitter and the power sensor, for prevent the power sensor input attenuation 40-50 dB. Set the RBW Bandwidth of the emission or use a channel power meter mode.

For antennas with gains of 6 dBi or less, maximum allowed transmitter output is 1 watt (+30 dBm). For antennas with gains greater than 6 dBi, transmitter output level must be decreased by an amount equal to (GAIN - 6)/3 dBm.

The antenna port of the EUT was connected to the input of a power sensor. Power was read directly and cable loss correction was added to the reading to obtain power at the EUT antenna terminals.

6.5. Test Result

Model Number	F210					
Test Item	Maximum Conducted Output Power					
Test Mode	Mode 2: IEEE 802.11b link mode					
Date of Test	12/11/2015				Test Site	TE05
Frequency (MHz)	Data Rate	Average Power		Peak Power		Limit (dBm)
		(dBm)	(W)	(dBm)	(W)	
2412	1M	10.20	0.010	12.26	0.017	< 30
2437		9.74	0.009	11.68	0.015	< 30
2462		9.18	0.008	10.92	0.012	< 30
2437	2M	9.68	0.009	11.55	0.014	< 30
2437	5.5M	9.62	0.009	11.47	0.014	< 30
2437	11M	9.57	0.009	11.40	0.014	< 30

Model Number	F210					
Test Item	Maximum Conducted Output Power					
Test Mode	Mode 3: IEEE 802.11g link mode					
Date of Test	12/11/2015				Test Site	TE05
Frequency (MHz)	Data Rate	Average Power		Peak Power		Limit (dBm)
		(dBm)	(W)	(dBm)	(W)	
2412	6M	14.73	0.030	21.68	0.147	< 30
2437		14.30	0.027	21.35	0.136	< 30
2462		14.01	0.025	21.00	0.126	< 30
2437	9M	14.27	0.027	21.32	0.136	< 30
2437	12M	14.19	0.026	21.20	0.132	< 30
2437	18M	14.22	0.026	21.23	0.133	< 30
2437	24M	14.04	0.025	21.05	0.127	< 30
2437	36M	14.00	0.025	20.98	0.125	< 30
2437	48M	13.89	0.024	20.85	0.122	< 30
2437	54M	13.95	0.025	20.92	0.124	< 30

Model Number	F210					
Test Item	Maximum Conducted Output Power					
Test Mode	Mode 4: IEEE 802.11n 2.4GHz 20MHz link mode					
Date of Test	12/11/2015				Test Site	TE05
Frequency (MHz)	Data Rate	Average Power		Peak Power		Limit (dBm)
		(dBm)	(W)	(dBm)	(W)	
2412	6.5M	14.57	0.029	21.53	0.142	< 30
2437		14.43	0.028	21.45	0.140	< 30
2462		13.73	0.024	20.79	0.120	< 30
2437	13M	14.41	0.028	21.40	0.138	< 30
2437	19.5M	14.37	0.027	21.38	0.137	< 30
2437	26M	14.25	0.027	21.29	0.135	< 30
2437	39M	14.22	0.026	21.24	0.133	< 30
2437	52M	14.30	0.027	21.34	0.136	< 30
2437	58.5M	14.17	0.026	21.16	0.131	< 30
2437	65M	14.21	0.026	21.23	0.133	< 30


Model Number	F210					
Test Item	Maximum Conducted Output Power					
Test Mode	Mode 5: IEEE 802.11n 2.4GHz 40MHz link mode					
Date of Test	12/11/2015				Test Site	TE05
Frequency (MHz)	Data Rate	Average Power		Peak Power		Limit (dBm)
		(dBm)	(W)	(dBm)	(W)	
2422	13.5M	12.71	0.019	20.37	0.109	< 30
2437		12.36	0.017	20.04	0.101	< 30
2452		12.22	0.017	19.87	0.097	< 30
2437	27M	12.32	0.017	20.01	0.100	< 30
2437	40.5M	12.30	0.017	19.98	0.100	< 30
2437	54M	12.17	0.016	19.82	0.096	< 30
2437	81M	12.22	0.017	19.88	0.097	< 30
2437	108M	12.29	0.017	19.95	0.099	< 30
2437	121.5M	12.10	0.016	19.77	0.095	< 30
2437	135M	12.05	0.016	19.71	0.094	< 30

7 6dB RF Bandwidth Measurement

7.1. Limit

6dB RF Bandwidth: Systems using digital modulation techniques may operate in the 2400–2483.5 MHz bands. The minimum 6 dB band-width shall be at least 500 kHz.

7.2. Test Setup



7.3. Test Instruments

Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
Spectrum Analyzer	Agilent	E4445A	MY45300744	12/16/2014	(1)
Test Site	ATL	TE05	TE05	N.C.R.	----

dRemark: (1) Calibration period 1 year. (2) Calibration period 2 years. (3) Calibration period 3 years.

Note: N.C.R. = No Calibration Request.

7.4. Test Procedure

The EUT tested to DTS test procedure of KDB558074D01 for compliance to FCC 47CFR 15.247 requirements.

6dB RF Bandwidth: The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RES RBW was set to 100 kHz. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A peak output reading was taken, a DISPLAY line was drawn 6 dB lower than peak level. The 6 dB bandwidth was determined from where the channel output spectrum intersected the display line.

The test was performed at 3 channels (Channel low, middle, high)

99 % Occupied Bandwidth: The transmitter shall be operated at its maximum carrier power measured under normal test conditions.

The video bandwidth shall be set to 3 times the resolution bandwidth. Video averaging is not permitted. Where practical, a sampling detector shall be used since a peak or, peak hold, may produce a wider bandwidth than actual.

The trace data points are recovered and are directly summed in linear terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached and that frequency recorded. The process is repeated for the highest frequency data points. This frequency is recorded.

7.5. Test Result

Model Number	F210		
Test Item	6dB RF Bandwidth		
Test Mode	Mode 2: IEEE 802.11b link mode Mode 3: IEEE 802.11g link mode Mode 4: IEEE 802.11n 2.4GHz 20MHz link mode Mode 5: IEEE 802.11n 2.4GHz 40MHz link mode		
Date of Test	12/11/2015	Test Site	TE05
Test Mode	Frequency (MHz)	Measurement (kHz)	Limit (kHz)
Mode 2	2412	10061	> 500
	2437	10049	> 500
	2462	9590	> 500
Mode 3	2412	16572	> 500
	2437	16620	> 500
	2462	16598	> 500
Mode 4	2412	17877	> 500
	2437	17821	> 500
	2462	17821	> 500
Mode 5	2422	36452	> 500
	2437	36494	> 500
	2452	36473	> 500

7.6. Test Graphs

Mode 2: IEEE 802.11b link mode	
2412	<p>Agilent R T</p> <p>Ch Freq 2.412 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 15 dBm Atten 15 dB</p> <p>#Peak Log dB/Offset 12 dB</p> <p>Center 2.412 GHz Span 30 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 4 ms (401 pts)</p> <p>Occupied Bandwidth 15.0306 MHz</p> <p>Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error 70.592 kHz</p> <p>x dB Bandwidth 10.061 MHz</p> <p>Freq/Channel</p> <p>Center Freq 2.41200000 GHz</p> <p>Start Freq 2.39700000 GHz</p> <p>Stop Freq 2.42700000 GHz</p> <p>CF Step 3.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>
2437	<p>Agilent R T</p> <p>Ch Freq 2.437 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 15 dBm Atten 15 dB</p> <p>#Peak Log dB/Offset 12 dB</p> <p>Center 2.437 GHz Span 30 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 4 ms (401 pts)</p> <p>Occupied Bandwidth 15.0297 MHz</p> <p>Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error 39.848 kHz</p> <p>x dB Bandwidth 10.049 MHz</p> <p>Freq/Channel</p> <p>Center Freq 2.43700000 GHz</p> <p>Start Freq 2.42200000 GHz</p> <p>Stop Freq 2.45200000 GHz</p> <p>CF Step 3.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>
2462	<p>Agilent R T</p> <p>Ch Freq 2.462 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 15 dBm Atten 15 dB</p> <p>#Peak Log dB/Offset 12 dB</p> <p>Center 2.462 GHz Span 30 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 4 ms (401 pts)</p> <p>Occupied Bandwidth 15.0693 MHz</p> <p>Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error 37.107 kHz</p> <p>x dB Bandwidth 9.590 MHz</p> <p>Freq/Channel</p> <p>Center Freq 2.46200000 GHz</p> <p>Start Freq 2.44700000 GHz</p> <p>Stop Freq 2.47700000 GHz</p> <p>CF Step 3.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>

Mode 3: IEEE 802.11g link mode

<p>2412</p>	
<p>2437</p>	
<p>2462</p>	

Mode 4: IEEE 802.11n 2.4GHz 20MHz link mode

<p>2412</p>	<p>Agilent R T</p> <p>Ch Freq 2.412 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 15 dBm Atten 15 dB</p> <p>#Peak Log 10 dB/Offst 12 dB</p> <p>Center 2.412 GHz Span 30 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 4 ms (401 pts)</p> <p>Occupied Bandwidth 17.7233 MHz</p> <p>Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error 70.671 kHz</p> <p>x dB Bandwidth 17.877 MHz</p> <p>Freq/Channel</p> <p>Center Freq 2.41200000 GHz</p> <p>Start Freq 2.39700000 GHz</p> <p>Stop Freq 2.42700000 GHz</p> <p>CF Step 3.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>
<p>2437</p>	<p>Agilent R T</p> <p>Ch Freq 2.437 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 15 dBm Atten 15 dB</p> <p>#Peak Log 10 dB/Offst 12 dB</p> <p>Center 2.437 GHz Span 30 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 4 ms (401 pts)</p> <p>Occupied Bandwidth 17.7122 MHz</p> <p>Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error 45.526 kHz</p> <p>x dB Bandwidth 17.821 MHz</p> <p>Freq/Channel</p> <p>Center Freq 2.43700000 GHz</p> <p>Start Freq 2.42200000 GHz</p> <p>Stop Freq 2.45200000 GHz</p> <p>CF Step 3.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>
<p>2462</p>	<p>Agilent R T</p> <p>Ch Freq 2.462 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 15 dBm Atten 15 dB</p> <p>#Peak Log 10 dB/Offst 12 dB</p> <p>Center 2.462 GHz Span 30 MHz</p> <p>#Res BW 100 kHz #VBW 300 kHz Sweep 4 ms (401 pts)</p> <p>Occupied Bandwidth 17.7047 MHz</p> <p>Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error 49.061 kHz</p> <p>x dB Bandwidth 17.821 MHz</p> <p>Freq/Channel</p> <p>Center Freq 2.46200000 GHz</p> <p>Start Freq 2.44700000 GHz</p> <p>Stop Freq 2.47700000 GHz</p> <p>CF Step 3.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>

Mode 5: IEEE 802.11n 2.4GHz 40MHz link mode


<p>2422</p>	<p>Agilent R T</p> <p>Ch Freq 2.422 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 15 dBm Atten 15 dB</p> <p>#Peak Log 10 dB/Offst 12 dB</p> <p>Center 2.422 GHz Span 50 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 4 ms (401 pts)</p> <p>Occupied Bandwidth 35.9706 MHz</p> <p>Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error 120.799 kHz x dB Bandwidth 36.452 MHz</p> <p>Freq/Channel</p> <p>Center Freq 2.42200000 GHz</p> <p>Start Freq 2.39700000 GHz</p> <p>Stop Freq 2.44700000 GHz</p> <p>CF Step 5.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>
<p>2437</p>	<p>Agilent R T</p> <p>Ch Freq 2.437 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 15 dBm Atten 15 dB</p> <p>#Peak Log 10 dB/Offst 12 dB</p> <p>Center 2.437 GHz Span 50 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 4 ms (401 pts)</p> <p>Occupied Bandwidth 35.9604 MHz</p> <p>Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error 75.497 kHz x dB Bandwidth 36.494 MHz</p> <p>Freq/Channel</p> <p>Center Freq 2.43700000 GHz</p> <p>Start Freq 2.41200000 GHz</p> <p>Stop Freq 2.46200000 GHz</p> <p>CF Step 5.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>
<p>2452</p>	<p>Agilent R T</p> <p>Ch Freq 2.452 GHz Trig Free</p> <p>Occupied Bandwidth</p> <p>Ref 15 dBm Atten 15 dB</p> <p>#Peak Log 10 dB/Offst 12 dB</p> <p>Center 2.452 GHz Span 50 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 4 ms (401 pts)</p> <p>Occupied Bandwidth 35.9883 MHz</p> <p>Occ BW % Pwr 99.00 % x dB -6.00 dB</p> <p>Transmit Freq Error 82.706 kHz x dB Bandwidth 36.473 MHz</p> <p>Freq/Channel</p> <p>Center Freq 2.45200000 GHz</p> <p>Start Freq 2.42700000 GHz</p> <p>Stop Freq 2.47700000 GHz</p> <p>CF Step 5.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>

8 Maximum Power Density Measurement

8.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

8.2. Test Setup



8.3. Test Instruments

Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
Spectrum Analyzer	Agilent	E4445A	MY45300744	12/16/2014	(1)
Test Site	ATL	TE05	TE05	N.C.R.	-----

Remark: (1) Calibration period 1 year. (2) Calibration period 2 years. (3) Calibration period 3 years.

Note: N.C.R. = No Calibration Request.

8.4. Test Procedure

The EUT tested to DTS test procedure of KDB558074D01 for compliance to FCC 47CFR 15.247 requirements.

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
4. Set the VBW $\geq 3 \times \text{RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

8.5. Test Result

Model Number	F210		
Test Item	Maximum Power Density		
Test Mode	Mode 2: IEEE 802.11b link mode Mode 3: IEEE 802.11g link mode Mode 4: IEEE 802.11n 2.4GHz 20MHz link mode Mode 5: IEEE 802.11n 2.4GHz 40MHz link mode		
Date of Test	12/11/2015	Test Site	TE05
Test Mode	Frequency (MHz)	Measurement (dBm/3KHz)	Limit (dBm/3KHz)
Mode 2	2412	-13.22	< 8
	2437	-13.53	< 8
	2462	-14.27	< 8
Mode 3	2412	-12.53	< 8
	2437	-12.59	< 8
	2462	-13.30	< 8
Mode 4	2412	-13.98	< 8
	2437	-14.70	< 8
	2462	-15.20	< 8
Mode 5	2422	-18.47	< 8
	2437	-18.61	< 8
	2452	-18.90	< 8

8.6. Test Graphs

Mode 2: IEEE 802.11b link mode	
2412	<p>Agilent R T Ref 15 dBm Atten 15 dB Mkr1 2.4127425 GHz Peak -13.22 dBm Log 10 dB/ Offset 12 dB M1 S2 S3 FC AA Center 2.412 GHz Span 27 MHz #Res BW 3 kHz #VBW 10 kHz Sweep 80.4 ms (401 pts)</p> <p>Freq/Channel Center Freq 2.41200000 GHz Start Freq 2.39850000 GHz Stop Freq 2.42550000 GHz CF Step 2.70000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off</p>
2437	<p>Agilent R T Ref 15 dBm Atten 15 dB Mkr1 2.4377425 GHz Peak -13.53 dBm Log 10 dB/ Offset 12 dB M1 S2 S3 FC AA Center 2.437 GHz Span 27 MHz #Res BW 3 kHz #VBW 10 kHz Sweep 80.4 ms (401 pts)</p> <p>Freq/Channel Center Freq 2.43700000 GHz Start Freq 2.42350000 GHz Stop Freq 2.45050000 GHz CF Step 2.70000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off</p>
2462	<p>Agilent R T Ref 15 dBm Atten 15 dB Mkr1 2.4627425 GHz Peak -14.27 dBm Log 10 dB/ Offset 12 dB M1 S2 S3 FC AA Center 2.462 GHz Span 27 MHz #Res BW 3 kHz #VBW 10 kHz Sweep 80.4 ms (401 pts)</p> <p>Freq/Channel Center Freq 2.46200000 GHz Start Freq 2.44850000 GHz Stop Freq 2.47550000 GHz CF Step 2.70000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off</p>

Mode 3: IEEE 802.11g link mode

<p>2412</p>	<p>Agilent R T</p> <p>Ref 15 dBm Atten 15 dB Mkr1 2.4161175 GHz -12.53 dBm</p> <p>Peak Log 10 dB/Offset 12 dB</p> <p>M1 S2 S3 FC AA</p> <p>Center 2.412 GHz Span 27 MHz #Res BW 3 kHz #VBW 10 kHz Sweep 80.4 ms (401 pts)</p> <table border="1"> <thead> <tr> <th colspan="2">Freq/Channel</th> </tr> </thead> <tbody> <tr> <td>Center Freq</td> <td>2.41200000 GHz</td> </tr> <tr> <td>Start Freq</td> <td>2.39850000 GHz</td> </tr> <tr> <td>Stop Freq</td> <td>2.42550000 GHz</td> </tr> <tr> <td>CF Step</td> <td>2.70000000 MHz Auto Man</td> </tr> <tr> <td>Freq Offset</td> <td>0.00000000 Hz</td> </tr> <tr> <td>Signal Track</td> <td>On Off</td> </tr> </tbody> </table>	Freq/Channel		Center Freq	2.41200000 GHz	Start Freq	2.39850000 GHz	Stop Freq	2.42550000 GHz	CF Step	2.70000000 MHz Auto Man	Freq Offset	0.00000000 Hz	Signal Track	On Off
Freq/Channel															
Center Freq	2.41200000 GHz														
Start Freq	2.39850000 GHz														
Stop Freq	2.42550000 GHz														
CF Step	2.70000000 MHz Auto Man														
Freq Offset	0.00000000 Hz														
Signal Track	On Off														
<p>2437</p>	<p>Agilent R T</p> <p>Ref 15 dBm Atten 15 dB Mkr1 2.4411175 GHz -12.59 dBm</p> <p>Peak Log 10 dB/Offset 12 dB</p> <p>M1 S2 S3 FC AA</p> <p>Center 2.437 GHz Span 27 MHz #Res BW 3 kHz #VBW 10 kHz Sweep 80.4 ms (401 pts)</p> <table border="1"> <thead> <tr> <th colspan="2">Freq/Channel</th> </tr> </thead> <tbody> <tr> <td>Center Freq</td> <td>2.43700000 GHz</td> </tr> <tr> <td>Start Freq</td> <td>2.42350000 GHz</td> </tr> <tr> <td>Stop Freq</td> <td>2.45050000 GHz</td> </tr> <tr> <td>CF Step</td> <td>2.70000000 MHz Auto Man</td> </tr> <tr> <td>Freq Offset</td> <td>0.00000000 Hz</td> </tr> <tr> <td>Signal Track</td> <td>On Off</td> </tr> </tbody> </table>	Freq/Channel		Center Freq	2.43700000 GHz	Start Freq	2.42350000 GHz	Stop Freq	2.45050000 GHz	CF Step	2.70000000 MHz Auto Man	Freq Offset	0.00000000 Hz	Signal Track	On Off
Freq/Channel															
Center Freq	2.43700000 GHz														
Start Freq	2.42350000 GHz														
Stop Freq	2.45050000 GHz														
CF Step	2.70000000 MHz Auto Man														
Freq Offset	0.00000000 Hz														
Signal Track	On Off														
<p>2462</p>	<p>Agilent R T</p> <p>Ref 15 dBm Atten 15 dB Mkr1 2.4574100 GHz -13.3 dBm</p> <p>Peak Log 10 dB/Offset 12 dB</p> <p>M1 S2 S3 FC AA</p> <p>Center 2.462 GHz Span 27 MHz #Res BW 3 kHz #VBW 10 kHz Sweep 80.4 ms (401 pts)</p> <table border="1"> <thead> <tr> <th colspan="2">Freq/Channel</th> </tr> </thead> <tbody> <tr> <td>Center Freq</td> <td>2.46200000 GHz</td> </tr> <tr> <td>Start Freq</td> <td>2.44850000 GHz</td> </tr> <tr> <td>Stop Freq</td> <td>2.47550000 GHz</td> </tr> <tr> <td>CF Step</td> <td>2.70000000 MHz Auto Man</td> </tr> <tr> <td>Freq Offset</td> <td>0.00000000 Hz</td> </tr> <tr> <td>Signal Track</td> <td>On Off</td> </tr> </tbody> </table>	Freq/Channel		Center Freq	2.46200000 GHz	Start Freq	2.44850000 GHz	Stop Freq	2.47550000 GHz	CF Step	2.70000000 MHz Auto Man	Freq Offset	0.00000000 Hz	Signal Track	On Off
Freq/Channel															
Center Freq	2.46200000 GHz														
Start Freq	2.44850000 GHz														
Stop Freq	2.47550000 GHz														
CF Step	2.70000000 MHz Auto Man														
Freq Offset	0.00000000 Hz														
Signal Track	On Off														

Mode 4: IEEE 802.11n 2.4GHz 20MHz link mode

<p>2412</p>	<p>Agilent R T</p> <p>Ref 15 dBm Atten 15 dB Mkr1 2.4142950 GHz -13.98 dBm</p> <p>Peak Log 10 dB/Offset 12 dB</p> <p>M1 S2 S3 FC AA</p> <p>Center 2.412 GHz Span 27 MHz #Res BW 3 kHz #VBW 10 kHz Sweep 80.4 ms (401 pts)</p> <p>Freq/Channel</p> <p>Center Freq 2.41200000 GHz</p> <p>Start Freq 2.39850000 GHz</p> <p>Stop Freq 2.42550000 GHz</p> <p>CF Step 2.70000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>
<p>2437</p>	<p>Agilent R T</p> <p>Ref 15 dBm Atten 15 dB Mkr1 2.4304525 GHz -14.7 dBm</p> <p>Peak Log 10 dB/Offset 12 dB</p> <p>M1 S2 S3 FC AA</p> <p>Center 2.437 GHz Span 27 MHz #Res BW 3 kHz #VBW 10 kHz Sweep 80.4 ms (401 pts)</p> <p>Freq/Channel</p> <p>Center Freq 2.43700000 GHz</p> <p>Start Freq 2.42350000 GHz</p> <p>Stop Freq 2.45050000 GHz</p> <p>CF Step 2.70000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>
<p>2462</p>	<p>Agilent R T</p> <p>Ref 15 dBm Atten 15 dB Mkr1 2.4599750 GHz -15.2 dBm</p> <p>Peak Log 10 dB/Offset 12 dB</p> <p>M1 S2 S3 FC AA</p> <p>Center 2.462 GHz Span 27 MHz #Res BW 3 kHz #VBW 10 kHz Sweep 80.4 ms (401 pts)</p> <p>Freq/Channel</p> <p>Center Freq 2.46200000 GHz</p> <p>Start Freq 2.44850000 GHz</p> <p>Stop Freq 2.47550000 GHz</p> <p>CF Step 2.70000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>

Mode 5: IEEE 802.11n 2.4GHz 40MHz link mode


<p>2422</p>	<p>Agilent R T</p> <p>Ref 15 dBm Atten 15 dB Mkr1 2.42035 GHz -18.47 dBm</p> <p>Peak Log 10 dB/Offset 12 dB</p> <p>M1 S2 S3 FC AA</p> <p>Center 2.422 GHz Span 55 MHz #Res BW 3 kHz #VBW 10 kHz Sweep 80.4 ms (401 pts)</p> <p>Freq/Channel</p> <p>Center Freq 2.42200000 GHz</p> <p>Start Freq 2.39450000 GHz</p> <p>Stop Freq 2.44950000 GHz</p> <p>CF Step 5.50000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>
<p>2437</p>	<p>Agilent R T</p> <p>Ref 15 dBm Atten 15 dB Mkr1 2.43906 GHz -18.61 dBm</p> <p>Peak Log 10 dB/Offset 12 dB</p> <p>M1 S2 S3 FC AA</p> <p>Center 2.437 GHz Span 55 MHz #Res BW 3 kHz #VBW 10 kHz Sweep 80.4 ms (401 pts)</p> <p>Freq/Channel</p> <p>Center Freq 2.43700000 GHz</p> <p>Start Freq 2.40950000 GHz</p> <p>Stop Freq 2.46450000 GHz</p> <p>CF Step 5.50000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>
<p>2452</p>	<p>Agilent R T</p> <p>Ref 15 dBm Atten 15 dB Mkr1 2.45406 GHz -18.9 dBm</p> <p>Peak Log 10 dB/Offset 12 dB</p> <p>M1 S2 S3 FC AA</p> <p>Center 2.452 GHz Span 55 MHz #Res BW 3 kHz #VBW 10 kHz Sweep 80.4 ms (401 pts)</p> <p>Freq/Channel</p> <p>Center Freq 2.45200000 GHz</p> <p>Start Freq 2.42450000 GHz</p> <p>Stop Freq 2.47950000 GHz</p> <p>CF Step 5.50000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>

9 Out of Band Conducted Emissions Measurement

9.1. Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

9.2. Test Setup



9.3. Test Instruments

Equipment	Manufacturer	Model Number	Serial Number	Cal. Date	Remark
Spectrum Analyzer	Agilent	E4445A	MY45300744	12/16/2014	(1)
Spectrum Analyzer	Agilent	E4408B	MY45107753	07/27/2015	(1)
Test Site	ATL	TE05	TE05	N.C.R.	-----

Remark: (1) Calibration period 1 year. (2) Calibration period 2 years. (3) Calibration period 3 years.

Note: N.C.R. = No Calibration Request.

9.4. Test Procedure

In any 100 kHz bandwidth outside the EUT pass band, the RF power produced by the modulation products of the spreading sequence, the information sequence, and the carrier frequency shall be at least 20 dB below that of the maximum in-band 100 kHz emission, antenna output of the EUT was coupled directly to spectrum analyzer; if an external attenuator and/or cable was used, these losses are compensated for with the analyzer OFFSET function.

All other types of emissions from the EUT shall meet the general limits for radiated frequencies outside the pass band.

The test was performed at 3 channels.

9.5. Test Graphs

Reference level

Mode 2: IEEE 802.11b link mode	
2412	<p>Agilent R T Ref 15 dBm Atten 15 dB Mkr1 2.4115275 GHz Peak Log 10 dB/Offset 12 dB M1 S2 S3 FC AA Center 2.412 GHz Span 27 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 4 ms (401 pts)</p> <p>Freq/Channel Center Freq 2.41200000 GHz Start Freq 2.39850000 GHz Stop Freq 2.42550000 GHz CF Step 2.70000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off</p>
2437	<p>Agilent R T Ref 15 dBm Atten 15 dB Mkr1 2.4365275 GHz Peak Log 10 dB/Offset 12 dB M1 S2 S3 FC AA Center 2.437 GHz Span 27 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 4 ms (401 pts)</p> <p>Freq/Channel Center Freq 2.43700000 GHz Start Freq 2.42350000 GHz Stop Freq 2.45050000 GHz CF Step 2.70000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off</p>
2462	<p>Agilent R T Ref 15 dBm Atten 15 dB Mkr1 2.4615275 GHz Peak Log 10 dB/Offset 12 dB M1 S2 S3 FC AA Center 2.462 GHz Span 27 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 4 ms (401 pts)</p> <p>Freq/Channel Center Freq 2.46200000 GHz Start Freq 2.44850000 GHz Stop Freq 2.47550000 GHz CF Step 2.70000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off</p>

Mode 3: IEEE 802.11g link mode

2412	<p>Agilent R T</p> <p>Ref 15 dBm Atten 15 dB Mkr1 2.4136875 GHz Peak Log 10 dB/Offset 12 dB -0.889 dBm</p> <p>M1 S2 S3 FC AA</p> <p>Center 2.412 GHz Span 27 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 4 ms (401 pts)</p> <p>Freq/Channel Center Freq 2.41200000 GHz Start Freq 2.39850000 GHz Stop Freq 2.42550000 GHz CF Step 2.70000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off</p>
2437	<p>Agilent R T</p> <p>Ref 15 dBm Atten 15 dB Mkr1 2.4386875 GHz Peak Log 10 dB/Offset 12 dB -0.993 dBm</p> <p>M1 S2 S3 FC AA</p> <p>Center 2.437 GHz Span 27 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 4 ms (401 pts)</p> <p>Freq/Channel Center Freq 2.43700000 GHz Start Freq 2.42350000 GHz Stop Freq 2.45050000 GHz CF Step 2.70000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off</p>
2462	<p>Agilent R T</p> <p>Ref 15 dBm Atten 15 dB Mkr1 2.4568025 GHz Peak Log 10 dB/Offset 12 dB -1.59 dBm</p> <p>M1 S2 S3 FC AA</p> <p>Center 2.462 GHz Span 27 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 4 ms (401 pts)</p> <p>Freq/Channel Center Freq 2.46200000 GHz Start Freq 2.44850000 GHz Stop Freq 2.47550000 GHz CF Step 2.70000000 MHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off</p>

Mode 4: IEEE 802.11n 2.4GHz 20MHz link mode

2412	<p>Agilent R T</p> <p>Ref 15 dBm Atten 15 dB Mkr1 2.4186825 GHz -1.692 dBm</p> <p>Peak Log 10 dB/Offset 12 dB</p> <p>M1 S2 S3 FC AA</p> <p>Center 2.412 GHz Span 27 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 4 ms (401 pts)</p> <p>Freq/Channel</p> <p>Center Freq 2.41200000 GHz</p> <p>Start Freq 2.39850000 GHz</p> <p>Stop Freq 2.42550000 GHz</p> <p>CF Step 2.70000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>
2437	<p>Agilent R T</p> <p>Ref 15 dBm Atten 15 dB Mkr1 2.4336925 GHz -1.819 dBm</p> <p>Peak Log 10 dB/Offset 12 dB</p> <p>M1 S2 S3 FC AA</p> <p>Center 2.437 GHz Span 27 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 4 ms (401 pts)</p> <p>Freq/Channel</p> <p>Center Freq 2.43700000 GHz</p> <p>Start Freq 2.42350000 GHz</p> <p>Stop Freq 2.45050000 GHz</p> <p>CF Step 2.70000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>
2462	<p>Agilent R T</p> <p>Ref 15 dBm Atten 15 dB Mkr1 2.4541700 GHz -2.213 dBm</p> <p>Peak Log 10 dB/Offset 12 dB</p> <p>M1 S2 S3 FC AA</p> <p>Center 2.462 GHz Span 27 MHz #Res BW 100 kHz #VBW 300 kHz Sweep 4 ms (401 pts)</p> <p>Freq/Channel</p> <p>Center Freq 2.46200000 GHz</p> <p>Start Freq 2.44850000 GHz</p> <p>Stop Freq 2.47550000 GHz</p> <p>CF Step 2.70000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p>

Mode 5: IEEE 802.11n 2.4GHz 40MHz link mode

<p>2422</p>	
<p>2437</p>	
<p>2452</p>	

Out of Band Conducted Emissions

Mode 2: IEEE 802.11b link mode

<p>2412</p>	<p>Agilent R T</p> <p>Ref 15 dBm Atten 15 dB Mkr1 2.41 GHz -1.609 dBm</p> <p>Peak Log dB/Offst dB DI -20.2 dBm</p> <p>Start 30 MHz #Res BW 100 kHz #VBW 300 kHz Stop 26.5 GHz Sweep 2.742 s (401 pts)</p> <table border="1"> <thead> <tr> <th>Marker</th> <th>Trace</th> <th>Type</th> <th>X Axis</th> <th>Amplitude</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>(1)</td> <td>Freq</td> <td>2.41 GHz</td> <td>-1.609 dBm</td> </tr> </tbody> </table> <p>Freq/Channel</p> <p>Center Freq 13.2650000 GHz</p> <p>Start Freq 30.0000000 MHz</p> <p>Stop Freq 26.5000000 GHz</p> <p>CF Step 2.64700000 GHz Auto Man</p> <p>Freq Offset 0.0000000 Hz</p> <p>Signal Track On Off</p>	Marker	Trace	Type	X Axis	Amplitude	1	(1)	Freq	2.41 GHz	-1.609 dBm
Marker	Trace	Type	X Axis	Amplitude							
1	(1)	Freq	2.41 GHz	-1.609 dBm							
<p>2437</p>	<p>Agilent R T</p> <p>Ref 15 dBm Atten 15 dB Mkr1 2.44 GHz -0.26 dBm</p> <p>Peak Log dB/Offst dB DI -20.9 dBm</p> <p>Start 30 MHz #Res BW 100 kHz #VBW 300 kHz Stop 26.5 GHz Sweep 2.742 s (401 pts)</p> <table border="1"> <thead> <tr> <th>Marker</th> <th>Trace</th> <th>Type</th> <th>X Axis</th> <th>Amplitude</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>(1)</td> <td>Freq</td> <td>2.44 GHz</td> <td>-0.26 dBm</td> </tr> </tbody> </table> <p>Freq/Channel</p> <p>Center Freq 13.2650000 GHz</p> <p>Start Freq 30.0000000 MHz</p> <p>Stop Freq 26.5000000 GHz</p> <p>CF Step 2.64700000 GHz Auto Man</p> <p>Freq Offset 0.0000000 Hz</p> <p>Signal Track On Off</p>	Marker	Trace	Type	X Axis	Amplitude	1	(1)	Freq	2.44 GHz	-0.26 dBm
Marker	Trace	Type	X Axis	Amplitude							
1	(1)	Freq	2.44 GHz	-0.26 dBm							
<p>2462</p>	<p>Agilent R T</p> <p>Ref 15 dBm Atten 15 dB Mkr1 2.46 GHz -1.203 dBm</p> <p>Peak Log dB/Offst dB DI -21.9 dBm</p> <p>Start 30 MHz #Res BW 100 kHz #VBW 300 kHz Stop 26.5 GHz Sweep 2.742 s (401 pts)</p> <table border="1"> <thead> <tr> <th>Marker</th> <th>Trace</th> <th>Type</th> <th>X Axis</th> <th>Amplitude</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>(1)</td> <td>Freq</td> <td>2.46 GHz</td> <td>-1.203 dBm</td> </tr> </tbody> </table> <p>Freq/Channel</p> <p>Center Freq 13.2650000 GHz</p> <p>Start Freq 30.0000000 MHz</p> <p>Stop Freq 26.5000000 GHz</p> <p>CF Step 2.64700000 GHz Auto Man</p> <p>Freq Offset 0.0000000 Hz</p> <p>Signal Track On Off</p>	Marker	Trace	Type	X Axis	Amplitude	1	(1)	Freq	2.46 GHz	-1.203 dBm
Marker	Trace	Type	X Axis	Amplitude							
1	(1)	Freq	2.46 GHz	-1.203 dBm							

Mode 3: IEEE 802.11g link mode

<p>2412</p>	
<p>2437</p>	
<p>2462</p>	

Mode 4: IEEE 802.11n 2.4GHz 20MHz link mode

2412	<p>Agilent R T Ref 15 dBm Atten 15 dB Mkr1 2.41 GHz -1.828 dBm Peak Log 10 dB/Offset 12 dB DI -21.7 dBm Start 30 MHz Stop 26.5 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 2.742 s (401 pts)</p> <table border="1"> <thead> <tr> <th>Marker</th> <th>Trace</th> <th>Type</th> <th>X Axis</th> <th>Amplitude</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>(1)</td> <td>Freq</td> <td>2.41 GHz</td> <td>-1.828 dBm</td> </tr> </tbody> </table> <p>Freq/Channel Center Freq 13.2650000 GHz Start Freq 30.0000000 MHz Stop Freq 26.5000000 GHz CF Step 2.64700000 GHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off</p>	Marker	Trace	Type	X Axis	Amplitude	1	(1)	Freq	2.41 GHz	-1.828 dBm
Marker	Trace	Type	X Axis	Amplitude							
1	(1)	Freq	2.41 GHz	-1.828 dBm							
2437	<p>Agilent R T Ref 15 dBm Atten 15 dB Mkr1 2.44 GHz -1.393 dBm Peak Log 10 dB/Offset 12 dB DI -21.8 dBm Start 30 MHz Stop 26.5 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 2.742 s (401 pts)</p> <table border="1"> <thead> <tr> <th>Marker</th> <th>Trace</th> <th>Type</th> <th>X Axis</th> <th>Amplitude</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>(1)</td> <td>Freq</td> <td>2.44 GHz</td> <td>-1.393 dBm</td> </tr> </tbody> </table> <p>Freq/Channel Center Freq 13.2650000 GHz Start Freq 30.0000000 MHz Stop Freq 26.5000000 GHz CF Step 2.64700000 GHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off</p>	Marker	Trace	Type	X Axis	Amplitude	1	(1)	Freq	2.44 GHz	-1.393 dBm
Marker	Trace	Type	X Axis	Amplitude							
1	(1)	Freq	2.44 GHz	-1.393 dBm							
2462	<p>Agilent R T Ref 15 dBm Atten 15 dB Mkr1 2.46 GHz -2.486 dBm Peak Log 10 dB/Offset 12 dB DI -22.2 dBm Start 30 MHz Stop 26.5 GHz #Res BW 100 kHz #VBW 300 kHz Sweep 2.742 s (401 pts)</p> <table border="1"> <thead> <tr> <th>Marker</th> <th>Trace</th> <th>Type</th> <th>X Axis</th> <th>Amplitude</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>(1)</td> <td>Freq</td> <td>2.46 GHz</td> <td>-2.486 dBm</td> </tr> </tbody> </table> <p>Freq/Channel Center Freq 13.2650000 GHz Start Freq 30.0000000 MHz Stop Freq 26.5000000 GHz CF Step 2.64700000 GHz Auto Man Freq Offset 0.00000000 Hz Signal Track On Off</p>	Marker	Trace	Type	X Axis	Amplitude	1	(1)	Freq	2.46 GHz	-2.486 dBm
Marker	Trace	Type	X Axis	Amplitude							
1	(1)	Freq	2.46 GHz	-2.486 dBm							


Mode 5: IEEE 802.11n 2.4GHz 40MHz link mode

<p>2422</p>	
<p>2437</p>	
<p>2452</p>	


Conducted Band Edge

Mode 2: IEEE 802.11b link mode

2412




2462




Mode 3: IEEE 802.11g link mode

2412




2462




Mode 4: IEEE 802.11n 2.4GHz 20MHz link mode

2412




2462




Mode 5: IEEE 802.11n 2.4GHz 40MHz link mode

2422



2452



10 Antenna Measurement

10.1.Limit

For intentional device, according to 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And According to 15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

10.2.Antenna Connector Construction

The antenna used in this product is Omni Directional Antenna (Reversed-SMA Connector). And the maximum Gain of this antenna is only 2 dBi.