



No. 1 Workshop, M-10, Middle section, Science & Technology Park,
Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
Email: sgs_internet_operations@sgs.com

Report No.: SZEMO10060336601
Page: 1 of 21


FCC REPORT

Application No. : SZEMO100603366RF
Applicant: SHENZHEN CHEGNYAN SCIENCE AND TECHNOLOGY CO., LTD
Product Name: Wireless Headphone
Operation Frequency: 913.5MHz, 914MHz, 914.5MHz
FCC ID: YILMH2001H
Standards: FCC CFR Title 47 Part 15 Subpart C Section 15.249: 2008
Date of Receipt 2010-06-07
Date of Test 2010-06-08 to 2010-07-28
Date of Issue 2010-07-28

Test Result :	PASS *
----------------------	---------------

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



July, 2010

Jack Zhang
Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



2 Contents

	Page
1 COVER PAGE	1
2 CONTENTS	2
3 TEST SUMMARY	3
4 GENERAL INFORMATION	4
4.1 CLIENT INFORMATION	4
4.2 GENERAL DESCRIPTION OF E.U.T.	4
4.3 E.U.T OPERATION MODE	5
4.4 TEST FACILITY	6
4.5 TEST LOCATION	6
4.6 OTHER INFORMATION REQUESTED BY THE CUSTOMER	6
4.7 TEST INSTRUMENTS LIST:	7
5 TEST RESULTS AND MEASUREMENT DATA	8
5.1 ANTENNA REQUIREMENT:	8
5.2 CONDUCTED EMISSIONS	9
5.3 RADIATED EMISSION	12
5.3.1 <i>Field Strength Of The Fundamental Signal</i>	14
5.3.2 <i>Spurious Emissions</i>	15
5.4 20DB BANDWIDTH	19-21



3 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203	Passed
AC Power Line Conducted Emission	15.207	Passed
Field strength of the fundamental signal	15.249 (a)	Passed
Spurious emissions	15.249 (a)/15.209	Passed
20dB Occupied Bandwidth	15.215 (c)	Passed

Remark: Passed: The EUT complies with the essential requirements in the standard.

Failed: The EUT does not comply with the essential requirements in the standard.

Remark:

Item No.: MH-2001H, 20199

Only the Item MH-2001H in the picture 5.3 was tested, since the electrical circuit design, layout, components used and internal wiring were identical for the above items.



4 General Information

4.1 Client Information

Applicant:	SHENZHEN CHENGYAN SCIENCE AND TECHNOLOGY CO., LTD
Address of Applicant:	Room 1808, Shenhua Commercial Building, Jiabin Rd., Luohu District, Shenzhen, P.R.China
Manufacturer/ Factory:	SHENZHEN YANXI SCIENCE AND TECHNOLOGY CO., LTD
Address of Manufacturer/ Factory:	2/F, Building E, Zhonghaixin Industrial Park, Shengbao Road, Longgang District, Shenzhen

4.2 General Description of E.U.T.

Product Name:	Wireless Headphone
Trade Name:	N/A
Item No.:	MH-2001H, 20199
Operation Frequency:	913.5MHz, 914MHz, 914.5MHz
Channel numbers:	3
Channel separation:	0.5MHz
Modulation type:	FM
Antenna Type:	Integral
Antenna gain:	1dBi
Transmitter Adapter	Input: AC 120V 60Hz 0.5A Output: DC 9.0 V 200mA
Receiver Power supply:	DC3.0V(2*1.5V"AA" Size Batteries)



4.3 E.U.T Operation mode

Operating Environment:

Temperature:	24.0 °C
Humidity:	52 % RH
Atmospheric Pressure:	1008 mbar

Test mode:

On mode:	Transmitter playing test signal with ipod, headphone set receiving
----------	--



4.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS (No. CNAS L2929)

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

VCCI

The 3m Semi-anechoic chamber and Shielded Room (7.5m x 4.0m x 3.0m) of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2197 and C-2383 respectively.

Date of Registration: September 29, 2008. Valid until September 28, 2011.

FCC – Registration No.: 556682

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 556682, June 27, 2008.

Industry Canada (IC)

The 3m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1.

4.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch E&E Lab

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China
518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

No tests were sub-contracted.

4.6 Other Information Requested by the Customer

None.



SGS-CSTC Standards Technical Services Ltd.

Report No.: SZEMO10060336601

Page: 7 of 21

4.7 Test Instruments list:

RE in Chamber						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (yyyy-mm-dd)	Cal.Due date (yyyy-mm-dd)
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEL0017	2010-06-17	2011-06-17
2	EMI Test Receiver	Rohde & Schwarz	ESIB26	SEL0023	2009-11-05	2010-11-05
3	EMI Test software	AUDIX	E3	SEL0050	N/A	N/A
4	Coaxial cable	SGS	N/A	SEL0028	2008-06-18	2011-06-18
5	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEL0015	2009-11-05	2010-11-05
6	Double-ridged horn (1-18GHz)	ETS-LINDGREN	3117	SEL0006	2009-11-10	2011-11-10
7	Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEL0053	2010-06-02	2011-06-02


Conducted Emission						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (yyyy-mm-dd)	Cal.Due date (yyyy-mm-dd)
1	Shielding Room	ZhongYu Electron	GB-88	SEL0042	N/A	N/A
2	LISN	ETS-LINDGREN	3816/2	SEL0021	2010-06-02	2011-06-02
3	Two-Line V-Network	Rohde & Schwarz	ENV216	SEL0152	2009-10-22	2010-10-22
4	EMI Test Receiver	Rohde & Schwarz	ESCI	SEL0022	2010-06-02	2011-06-02
5	Coaxial Cable	SGS	N/A	SEL0024	2008-06-18	2011-06-18

RF conducted						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (yyyy-mm-dd)	Cal.Due date (yyyy-mm-dd)
1	Spectrum Analyzer	Rohde & Schwarz	FSP 30	SEL0154	2009-10-22	2010-10-22
2	Coaxial cable	SGS	N/A	SEL0028	2008-06-18	2011-06-18


"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

5 Test results and Measurement Data

5.1 Antenna requirement:

Standard requirement:	FCC Part15 C Section 15.203
<p>15.203 requirement: <i>An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</i></p>	
E.U.T Antenna:	

5.2 Conducted Emissions

Test Requirement:	FCC Part15 C Section 15.207		
Test Method:	ANSI C63.4: 2003		
Test Frequency Range:	150KHz to 30MHz		
Class / Severity:	Class B		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
* Decreases with the logarithm of the frequency.			
Test procedure	The E.U.T and simulators are connected to the main power through a line impedance stabilization network(L.I.S.N.). The provide a 50ohm/50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs). Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2003 on conducted measurement.		
Test setup:	 <p>Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p>		
Test mode:	On mode		
Test Instruments:	Refer to section 4.7 for details		
Test results:	Passed		

Measurement Data

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.




SGS-CSTC Standards Technical Services Ltd.

Report No.: SZEMO10060336601

Page: 10 of 21

Live Line:



Site : Shielding Room
Condition : FCC PART15B QP CE LINE
EUT : MP3 PLAYER
Job NO. : 3366RF
MODE : ON

	Freq	Cable Loss	LISN Factor	Read Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.22437	0.04	-0.04	15.48	15.47	62.66	-47.18	QP
2	0.22437	0.04	-0.04	8.50	8.50	52.66	-44.16	Average
3	0.48632	0.06	-0.04	11.05	11.07	46.23	-35.16	Average
4	0.48632	0.06	-0.04	17.05	17.07	56.23	-39.16	QP
5	1.707	0.11	-0.06	11.10	11.15	46.00	-34.85	Average
6	1.707	0.11	-0.06	16.97	17.02	56.00	-38.98	QP
7	2.334	0.13	-0.07	10.54	10.60	46.00	-35.40	Average
8	2.334	0.13	-0.07	16.54	16.60	56.00	-39.40	QP
9	3.985	0.16	-0.09	16.03	16.09	56.00	-39.91	QP
10	3.985	0.16	-0.09	10.20	10.27	46.00	-35.73	Average
11	14.063	0.24	-0.47	18.31	18.09	60.00	-41.91	QP
12	14.063	0.24	-0.47	10.50	10.28	50.00	-39.72	Average

Notes:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.




SGS-CSTC Standards Technical Services Ltd.

Report No.: SZEMO10060336601

Page: 11 of 21

Neutral Line:



Site : Shielding Room
Condition : FCC PART15B QP CE NEUTRAL
EUT : MP3 PLAYER
Job NO. : 3366RF
MODE : ON

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.26303	0.05	-0.04	16.72	16.72	61.34	-44.61	QP
2	0.26303	0.05	-0.04	10.90	10.91	51.34	-40.43	Average
3	0.61726	0.06	-0.04	17.28	17.29	56.00	-38.71	QP
4 @	0.61726	0.06	-0.04	11.40	11.42	46.00	-34.58	Average
5	0.89441	0.07	-0.04	17.20	17.22	56.00	-38.78	QP
6	0.89441	0.07	-0.04	11.20	11.22	46.00	-34.78	Average
7	2.225	0.12	-0.06	17.80	17.86	56.00	-38.14	QP
8	2.225	0.12	-0.06	10.90	10.96	46.00	-35.04	Average
9	6.805	0.19	-0.17	17.20	17.21	60.00	-42.79	QP
10	6.805	0.19	-0.17	12.20	12.21	50.00	-37.79	Average
11	13.479	0.24	-0.42	18.31	18.13	60.00	-41.87	QP
12	13.479	0.24	-0.42	12.50	12.32	50.00	-37.68	Average

Notes:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.



SGS-CSTC Standards Technical Services Ltd.



Report No.: SZEMO10060336601

Page: 12 of 21

5.3 Radiated Emission

Test Requirement:	FCC Part15 C Section 15.249 and 15.209																								
Test Method:	ANSI C63.4: 2003																								
Test Frequency Range:	30MHz to 25000MHz																								
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)																								
Receiver setup:	<table><tr><td>Frequency</td><td>Detector</td><td>RBW</td><td>VBW</td><td>Remark</td></tr><tr><td>30MHz-1GHz</td><td>Quasi-peak</td><td>100KHz</td><td>300KHz</td><td>Quasi-peak Value</td></tr><tr><td rowspan="2">Above 1GHz</td><td>Peak</td><td>1MHz</td><td>3MHz</td><td>Peak Value</td></tr><tr><td>Peak</td><td>1MHz</td><td>10Hz</td><td>Average Value</td></tr></table>					Frequency	Detector	RBW	VBW	Remark	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak Value	Above 1GHz	Peak	1MHz	3MHz	Peak Value	Peak	1MHz	10Hz	Average Value	
Frequency	Detector	RBW	VBW	Remark																					
30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak Value																					
Above 1GHz	Peak	1MHz	3MHz	Peak Value																					
	Peak	1MHz	10Hz	Average Value																					
Limit: (Field strength of the fundamental signal)	<table><tr><td>Frequency</td><td>Limit (dBuV/m @3m)</td><td>Remark</td></tr><tr><td>902MHz to 928MHz</td><td>94.0</td><td>Quasi-peak Value</td></tr></table>					Frequency	Limit (dBuV/m @3m)	Remark	902MHz to 928MHz	94.0	Quasi-peak Value														
Frequency	Limit (dBuV/m @3m)	Remark																							
902MHz to 928MHz	94.0	Quasi-peak Value																							
Limit: (Spurious Emissions)	<table><tr><td>Frequency</td><td>Limit (dBuV/m @3m)</td><td>Remark</td></tr><tr><td>30MHz-88MHz</td><td>40.0</td><td>Quasi-peak Value</td></tr><tr><td>88MHz-216MHz</td><td>43.5</td><td>Quasi-peak Value</td></tr><tr><td>216MHz-960MHz</td><td>46.0</td><td>Quasi-peak Value</td></tr><tr><td>960MHz-1GHz</td><td>54.0</td><td>Quasi-peak Value</td></tr><tr><td rowspan="2">Above 1GHz</td><td>54.0</td><td>Average Value</td></tr><tr><td>74.0</td><td>Peak Value</td></tr></table>					Frequency	Limit (dBuV/m @3m)	Remark	30MHz-88MHz	40.0	Quasi-peak Value	88MHz-216MHz	43.5	Quasi-peak Value	216MHz-960MHz	46.0	Quasi-peak Value	960MHz-1GHz	54.0	Quasi-peak Value	Above 1GHz	54.0	Average Value	74.0	Peak Value
Frequency	Limit (dBuV/m @3m)	Remark																							
30MHz-88MHz	40.0	Quasi-peak Value																							
88MHz-216MHz	43.5	Quasi-peak Value																							
216MHz-960MHz	46.0	Quasi-peak Value																							
960MHz-1GHz	54.0	Quasi-peak Value																							
Above 1GHz	54.0	Average Value																							
	74.0	Peak Value																							
Limit: (band edge)	Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.																								
Test mode:	On mode																								
Test Procedure:	<p>a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.</p> <p>b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</p> <p>c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</p> <p>d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</p> <p>e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</p> <p>f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</p>																								
Test Instruments:	Refer to section 4.7 for details																								

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

Test results:	Passed
Test setup:	<p>Below 1GHz</p>  <p>Above 1GHz</p> 

Note:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

$$\text{Final Test Level} = \text{Receiver Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Preamplifier Factor}$$



SGS-CSTC Standards Technical Services Ltd.

Report No.: SZEMO10060336601

Page: 14 of 21

Measurement Data

5.3.1 Field Strength Of The Fundamental Signal

QP value:

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamplifier Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
913.5	3.62	23.25	26.43	81.27	81.71	94.00	-12.29	Horizontal
913.5	3.62	23.25	26.43	77.99	78.43	94.00	-15.57	Vertical
914.0	3.62	23.26	26.43	76.92	77.37	94.00	-16.63	Horizontal
914.0	3.62	23.26	26.43	79.12	79.57	94.00	-14.43	Vertical
914.5	3.62	23.26	26.43	79.69	80.14	94.00	-13.86	Horizontal
914.5	3.62	23.26	26.43	78.81	79.26	94.00	-14.74	Vertical



SGS-CSTC Standards Technical Services Ltd.

Report No.: SZEMO10060336601

Page: 15 of 21

5.3.2 Spurious Emissions	
30MHz~1GHz	
Test mode:	On mode

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamplifier Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
86.425	1.10	8.36	27.97	38.76	20.25	40.00	-19.75	Vertical
260.950	1.73	12.53	26.87	32.09	19.48	46.00	-26.52	Vertical
455.950	2.43	17.09	27.58	40.29	32.23	46.00	-13.77	Vertical
609.025	2.72	20.05	27.59	32.10	27.28	46.00	-18.72	Vertical
721.150	2.97	21.60	27.21	32.16	29.52	46.00	-16.48	Vertical
831.325	3.34	22.40	26.77	33.22	32.19	46.00	-13.81	Vertical
238.525	1.62	11.93	26.96	31.49	18.08	46.00	-27.92	Horizontal
359.425	2.09	15.65	27.15	30.96	21.55	46.00	-24.45	Horizontal
455.950	2.43	17.09	27.58	43.89	35.83	46.00	-10.17	Horizontal
550.525	2.65	18.90	27.66	31.77	25.66	46.00	-20.34	Horizontal
670.450	2.84	21.32	27.37	32.31	29.10	46.00	-16.90	Horizontal
795.250	3.19	22.08	26.96	32.43	30.74	46.00	-15.26	Horizontal

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



SGS-CSTC Standards Technical Services Ltd.

Report No.: SZEMO10060336601

Page: 16 of 21

Above 1GHz					
Test mode:	Transmitting	Test channel:	Lowest	Remark:	Peak

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamplifier Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
1351.000	4.49	26.63	39.14	54.99	46.97	74.00	-27.03	Vertical
1810.000	5.63	28.02	38.79	56.89	51.75	74.00	-22.25	Vertical
2719.000	6.23	31.07	39.03	59.15	57.42	74.00	-16.58	Vertical
3187.000	7.08	32.15	39.48	57.37	57.12	74.00	-16.88	Vertical
4567.490	9.44	33.94	41.17	57.00	59.21	74.00	-14.79	Vertical
5480.901	12.29	35.16	41.71	51.64	57.38	74.00	-16.62	Vertical
1351.000	4.49	26.63	39.14	52.58	44.56	74.00	-29.44	Horizontal
1810.000	5.63	28.02	38.79	53.09	47.95	74.00	-26.05	Horizontal
2719.000	6.23	31.07	39.03	54.38	52.65	74.00	-21.35	Horizontal
3187.000	7.08	32.15	39.48	52.56	52.31	74.00	-21.69	Horizontal
4555.000	9.35	33.92	40.91	53.13	55.49	74.00	-18.51	Horizontal
5024.060	9.95	34.52	41.21	56.00	59.26	74.00	-14.74	Horizontal

Test mode:	Transmitting	Test channel:	Lowest	Remark:	average
------------	--------------	---------------	--------	---------	---------

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamplifier Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
1351.000	4.49	26.63	39.14	46.32	38.30	54.00	-15.70	Vertical
1810.000	5.63	28.02	38.79	49.22	44.08	54.00	-9.92	Vertical
2719.000	6.23	31.07	39.03	50.24	48.51	54.00	-5.49	Vertical
3187.000	7.08	32.15	39.48	50.12	49.87	54.00	-4.13	Vertical
4567.490	9.44	33.94	41.17	49.00	51.21	54.00	-2.79	Vertical
5480.901	12.29	35.16	41.71	42.00	47.74	54.00	-6.26	Vertical
1351.000	4.49	26.63	39.14	41.26	33.24	54.00	-20.76	Horizontal
1810.000	5.63	28.02	38.79	43.58	38.44	54.00	-15.56	Horizontal
2719.000	6.23	31.07	39.03	43.88	42.15	54.00	-11.85	Horizontal
3187.000	7.08	32.15	39.48	45.48	45.23	54.00	-8.77	Horizontal
4555.000	9.35	33.92	40.91	44.10	46.46	54.00	-7.54	Horizontal
5024.060	9.95	34.52	41.21	41.50	44.76	54.00	-9.24	Horizontal

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



SGS-CSTC Standards Technical Services Ltd.

Report No.: SZEMO10060336601

Page: 17 of 21

Test mode:	Transmitting	Test channel:	Middle	Remark:	Peak
------------	--------------	---------------	--------	---------	------

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
1378.000	4.47	26.73	38.87	54.65	46.98	74.00	-27.02	Vertical
1819.000	5.62	28.05	38.92	56.63	51.38	74.00	-22.62	Vertical
2746.000	6.29	31.15	39.02	55.79	54.21	74.00	-19.79	Vertical
3187.000	7.08	32.15	39.48	56.35	56.10	74.00	-17.90	Vertical
4570.020	9.44	33.94	41.17	57.00	59.21	74.00	-14.79	Vertical
5483.893	12.29	35.16	41.71	56.57	62.31	74.00	-11.69	Vertical
1351.000	4.49	26.63	39.14	51.58	43.56	74.00	-30.44	Horizontal
1810.000	5.63	28.02	38.79	52.97	47.83	74.00	-26.17	Horizontal
3187.000	7.08	32.15	39.48	54.62	54.37	74.00	-19.63	Horizontal
3646.000	7.92	32.72	40.07	52.44	53.01	74.00	-20.99	Horizontal
4555.000	9.35	33.92	40.91	54.90	57.26	74.00	-16.74	Horizontal
5014.000	9.95	34.52	41.21	55.46	58.72	74.00	-15.28	Horizontal

Test mode:	Transmitting	Test channel:	Middle	Remark:	average
------------	--------------	---------------	--------	---------	---------

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
1378.000	4.47	26.73	38.87	48.32	40.65	54.00	-13.35	Vertical
1819.000	5.62	28.05	38.92	49.99	44.74	54.00	-9.26	Vertical
2746.000	6.29	31.15	39.02	48.34	46.76	54.00	-7.24	Vertical
3187.000	7.08	32.15	39.48	47.54	47.29	54.00	-6.71	Vertical
4570.020	9.44	33.94	41.17	48.21	50.42	54.00	-3.58	Vertical
5483.893	12.29	35.16	41.71	40.22	45.96	54.00	-8.04	Vertical
1351.000	4.49	26.63	39.14	42.99	34.97	54.00	-19.03	Horizontal
1810.000	5.63	28.02	38.79	43.15	38.01	54.00	-15.99	Horizontal
3187.000	7.08	32.15	39.48	44.66	44.41	54.00	-9.59	Horizontal
3646.000	7.92	32.72	40.07	44.25	44.82	54.00	-9.18	Horizontal
4555.000	9.35	33.92	40.91	44.15	46.51	54.00	-7.49	Horizontal
5014.000	9.95	34.52	41.21	42.15	45.41	54.00	-8.59	Horizontal

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."



SGS-CSTC Standards Technical Services Ltd.

Report No.: SZEMO10060336601

Page: 18 of 21

Test mode:	Transmitting	Test channel:	Highest	Remark:	Peak
------------	--------------	---------------	---------	---------	------


Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamplifier Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
1351.000	4.49	26.63	39.14	55.76	47.74	74.00	-26.26	Vertical
1819.000	5.62	28.05	38.92	57.13	51.88	74.00	-22.12	Vertical
2719.000	6.23	31.07	39.03	57.53	55.80	74.00	-18.20	Vertical
3187.000	7.08	32.15	39.48	59.52	59.27	74.00	-14.73	Vertical
4572.637	9.44	33.94	41.17	59.68	61.89	74.00	-12.11	Vertical
5486.979	12.29	35.16	41.71	54.37	60.11	74.00	-13.89	Vertical
1819.000	5.62	28.05	38.92	52.65	47.40	74.00	-26.60	Horizontal
2719.000	6.23	31.07	39.03	52.23	50.50	74.00	-23.50	Horizontal
3187.000	7.08	32.15	39.48	55.46	55.21	74.00	-18.79	Horizontal
4572.515	9.44	33.94	41.17	57.60	59.81	74.00	-14.19	Horizontal
5014.000	9.95	34.52	41.21	56.55	59.81	74.00	-14.19	Horizontal
5554.000	12.54	35.24	41.89	52.50	58.39	74.00	-15.61	Horizontal

Test mode:	Transmitting	Test channel:	Highest	Remark:	average
------------	--------------	---------------	---------	---------	---------

Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamplifier Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
1351.000	4.49	26.63	39.14	46.57	38.55	54.00	-15.45	Vertical
1819.000	5.62	28.05	38.92	48.21	42.96	54.00	-11.04	Vertical
2719.000	6.23	31.07	39.03	47.58	45.85	54.00	-8.15	Vertical
3187.000	7.08	32.15	39.48	50.24	49.99	54.00	-4.01	Vertical
4572.637	9.44	33.94	41.17	48.95	51.16	54.00	-2.84	Vertical
5486.979	12.29	35.16	41.71	40.98	46.72	54.00	-7.28	Vertical
1819.000	5.62	28.05	38.92	43.37	38.12	54.00	-15.88	Horizontal
2719.000	6.23	31.07	39.03	44.35	42.62	54.00	-11.38	Horizontal
3187.000	7.08	32.15	39.48	43.68	43.43	54.00	-10.57	Horizontal
4572.515	9.44	33.94	41.17	45.32	47.53	54.00	-6.47	Horizontal
5014.000	9.95	34.52	41.21	42.35	45.61	54.00	-8.39	Horizontal
5554.000	12.54	35.24	41.89	38.32	44.21	54.00	-9.79	Horizontal

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

5.4 20dB Bandwidth

Test Requirement:	FCC Part15 C Section 15.249/15.215
Test Method:	ANSI C63.4:2003
Limit:	Operation Frequency range 902MHz to 928MHz
Test Procedure:	<ol style="list-style-type: none"> 1. According to the follow Test-setup, keep the relative position between the artificial antenna and the EUT. 2. Set the EUT to proper test channel. 3. Max hold the radiated emissions, mark the peak power frequency point and the -20dB upper and lower frequency points. 4. Read 20dB bandwidth.
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected via a red cable to an E.U.T. (Equipment Under Test). Both are placed on a Non-Conducted Table. Below the table is a Ground Reference Plane.</p>
Test Instruments:	Refer to section 4.7 for details
Test mode:	On mode
Test results:	Passed

Measurement Data

Test channel	20dB bandwidth (MHz)	Results
Lowest	0.282	PASS
Middle	0.288	PASS
Highest	0.282	PASS




SGS-CSTC Standards Technical Services Ltd.

Report No.: SZEMO10060336601

Page: 20 of 21


Test plot as follows:

Test channel:	Lowest
---------------	--------



Date: 27.JUL.2010 14:10:08

Test channel:	Middle
---------------	--------



Date: 27.JUL.2010 14:09:08

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."




SGS-CSTC Standards Technical Services Ltd.

Report No.: SZEMO10060336601

Page: 21 of 21

Test channel:

Highest



Date: 27.JUL.2010 14:07:51

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."