

GENERAL INSTRUCTIONS:
 SUPPLIER TO INSURE CORRECT REVISION LEVEL DWG FOR PRODUCTION. CONTACT SB&D PURCHASING DEPT. FOR LATEST REVISION LEVEL DWG.
 CONTACT SB&D GRAPHICS DESIGN FOR ORIGINAL ARTWORK, COLOR STANDARDS AND CORPORATE GUIDELINES.
 PROOFS OF ALL REVISIONS THAT AFFECT ARTWORK AND ALL NEW COLOR FORMULATIONS MUST BE SUBMITTED TO SB&D GRAPHICS DESIGN FOR APPROVAL PRIOR TO MAKING PRODUCTION PARTS. SEE EP-1006.
 SUPPLIER TO PROVIDE SB&D GRAPHICS DESIGN WITH 6 SAMPLES OF ALL PRODUCTION PARTS. MARK SB&D PART NO. AND REVISION LEVEL.

COLOR VARIATIONS:

■ = PMS Black ■ = ANSI Orange (Pantone 172)
 ■ = DEWALT Yellow

LABEL APPLICATION


<input type="checkbox"/> TEXTURED	<input checked="" type="checkbox"/> RULED (one curve)	<input type="checkbox"/> OUTDOOR USE
<input checked="" type="checkbox"/> NON-TEXTURED	<input type="checkbox"/> FLAT	<input checked="" type="checkbox"/> INDOOR USE
ADHESION: <input checked="" type="checkbox"/> PERMANENT <input type="checkbox"/> REMOVEABLE <input type="checkbox"/> OTHER		

SYNTHETIC LABEL CONSTRUCTION:

SUPPLIER NAME:	LABEL MATERIAL:
TBD	5 MIL MATTE POLYCARBONATE, SUB-SURFACED PRINTED, 2 MIL ACRYLIC ADHESIVE MATTE TEXTURED

SPECIAL NOTES:

- SERIAL NO'S TO BE SUB-SURFACE PRINTED. 4 DIGITS MIN. (START WITH 1001). RANDOM ORDER ACCEPTABLE. NO TWO NAMEPLATES TO HAVE IDENTICAL NO'S. SEQUENCE TO BE ASSIGNED BY SB&D PURCHASING DEPT. (APPLICABLE TO DEWALT PRODUCT ONLY.)
- FINISHED LABEL MUST BE A "UL" AND "CSA" RECOGNIZED LABELING SYSTEM (UL STANDARD: UL969, UL CATEGORY CODE: P0002; CSA STANDARD: C22.2 NO. 0.15, CSA CLASS: 7921) AND APPROVED FOR THE SURFACE THAT THE LABEL WILL BE APPLIED TO UNLESS STANLEY BLACK & DECKER AGREES TO A DEVIATION.
- LABEL MANUFACTURER IS RESPONSIBLE TO PLACE THEIR MANUFACTURER'S CODE ON LABEL IN THE SIZE AND LOCATION INDICATED ON THIS DOCUMENT.
- INK USED MUST BE UV STABILIZED.
- ALL MATERIALS MUST COMPLY WITH ES100118.
- LABELS SHALL BE LEGIBLE, SHALL NOT WORK LOOSE, AND SHALL NOT BECOME CURLED AT THE EDGES AFTER BEING RUBBED BY HAND FOR 15 SECONDS WITH A CLOTH SOAKED IN WATER AND AGAIN FOR 15 SECONDS WITH A CLOTH SOAKED IN PETROLEUM SPIRIT. THE PETROLEUM SPIRIT TO BE USED FOR THE TEST SHALL BE A REAGENT GRADE HEXANE WITH A MINIMUM OF 85% AS N-HEXANE.
- LABEL CONSTRUCTION: WILL MEET THE DURABILITY REQUIREMENTS AND ALSO PROVIDES THE VISUAL CONSISTENCY WITH OTHER DEWALT BRAND PRODUCTS.
- LABEL MUST SATISFY LUBRICATING OIL IMMERSION TEST PER UL969 OR CSA C22.2 # 0.15
- LABEL MUST SATISFY 80C MAX TEMPERATURE RATING PER UL969 OR CSA C22.2 #0.15.
- LABEL MUST BE APPROVED FOR NON-DRY INDOOR USE PER UL969 AND CSA C22.2 NO. 0.15
- ALL SHIPPING BOXES AND ROLL CORES OR LABEL SHEETS MUST BE MARKED WITH VENDOR'S NAME, TRADE NAME, DATE OF MANUFACTURE AND MATERIAL IDENTIFICATION.



DCL074 ALL-PURPOSE LIGHT 20V == (Max) TYPE 1

⚠ WARNING TO REDUCE THE RISK OF INJURY, USER MUST READ INSTRUCTION MANUAL. ONLY USE WITH DEWALT BATTERY. DO NOT OPEN. FOR COMMERCIAL AND HOUSEHOLD USE. DO NOT EXPOSE TO RAIN. STORE INDOORS. WHEN USING SCHEDULER, ENSURE ILLUMINATED AREA IS FREE OF PERSONNEL BEFORE SCHEDULED TURN OFF.

⚠ ADVERTENCIA PARA REDUCIR EL RIESGO DE LESIONES, EL USUARIO DEBERÁ LEER EL MANUAL DE INSTRUCCIONES. UTILIZAR CON UNA BATERIA DEWALT. NO ABRIR. PARA USO COMERCIAL Y DOMESTICO. NO EXPONER A LA LLUVIA. ALMACENAR BAJO TECHO. CONECTAR SOLO A TOMAS DE CORRIENTE CON CONEXION A TIERRA APROPIADA. AL UTILIZAR EL PROGRAMADOR, ASEGURESE DE QUE NO HAYA PERSONAL EN EL AREA ILUMINADA ANTES DEL APAGADO PROGRAMADO.

⚠ AVERTISSEMENT À TITRE PRÉVENTIF, LIRE LE GUIDE. UTILISER AVEC UN BLOC-PILE DEWALT. NE PAS OUVRIR. POUR LE COMMERCIAL ET PLUIE, ENREGISTRER À L'INTÉRIEUR, À BRANCHER UNIQUEMENT SUR UNE PRISE CORRECTEMENT MISE À LA TERRE. LORSQUE LE PROGRAMMATEUR EST UTILISÉ, S'ASSURER QUE LA ZONE À ILLUMINER NE COMPORTE PLUS PERSONNE AVANT D'EN PROGRAMMER L'ARRÊT.

MODEL: DCL074 THIS DEVICE COMPLIES WITH PART 15 OF THE FCC RULES AND INDUSTRY CANADA LICENSE-EXEMPT RSS STANDARD(S). OPERATION IS SUBJECT TO THE FOLLOWING TWO CONDITIONS: 1) THIS DEVICE MAY NOT CAUSE HARMFUL INTERFERENCE AND 2) THIS DEVICE MUST ACCEPT ANY INTERFERENCE RECEIVED INCLUDING INTERFERENCE THAT MAY CAUSE UNDESIRE OPERATION.
 FCC ID: YJ7-DCL074
 IC: 9082A-DCL074 ESTE DISPOSITIVO CUMPLE CON LA SECCIÓN 15 DE LAS NORMAS DE LA COMISIÓN FEDERAL DE COMUNICACIONES (FCC) Y LAS NORMAS RSS DE EXENCIÓN DE LICENCIA DEL MINISTERIO DE INDUSTRIA DE CANADA. SU OPERACIÓN ESTÁ SUJETA A LAS SIGUIENTES DOS CONDICIONES: 1) ESTE DISPOSITIVO NO PUEDE CAUSAR INTERFERENCIA DAÑINA Y 2) ESTE DISPOSITIVO DEBE INTERFERENCIA QUE PODRÍA PRODUCIR UNA OPERACION NO DESEADA.
 CET APPAREIL EST CONFORME AU PARAGRAPHE 15 DU RÈGLEMENT DU FCC ET À LA (AUX) NORME(S) RSS EXEMPTÉ(S) DE LICENCE D'INDUSTRIE CANADA. SON UTILISATION EST SUJETTE AUX DEUX CONDITIONS SUIVANTES : 1) CE DISPOSITIF NE DOIT PAS CAUSER D'INTERFERENCES NUISIBLES; 2) CE DISPOSITIF DOIT ACCEPTER TOUTE INTERFERENCE REÇUE, Y COMPRIS TOUTE INTERFERENCE POUVANT CAUSER UN FONCTIONNEMENT INDÉSIRABLE.

DEWALT INDUSTRIAL TOOL CO., TOWSON, MD 21286 U.S.A. FOR SERVICE INFORMATION, CALL 1-800-4-DEWALT www.DEWALT.com MADE IN CHINA SER. []

THIS DOCUMENT IS THE PROPERTY OF STANLEY BLACK & DECKER INC. THE CONTENTS OF THIS DOCUMENT ARE CONFIDENTIAL AND CONSTITUTE TRADE SECRETS PROPRIETARY TO STANLEY BLACK & DECKER INC. NEITHER THIS DOCUMENT NOR ITS' CONTENTS SHALL BE DISCLOSED TO ANY UNAUTHORIZED PERSON, COPIED OR PUBLISHED WITHOUT PRIOR WRITTEN CONSENT OF STANLEY BLACK & DECKER INC. COPYRIGHT © 2018 STANLEY BLACK & DECKER INC.	TOL UNLESS SPECIFIED	
	0 & 1 PLC DEC: ± 0.4	
	ANGLES: ± 1°	
	ALL DIMENSIONS mm	FOR ITEM DATA SEE PRINTED REPORT
SIZE:		
SHEET:	1 of 1	

NXXXXXX