



MPE TEST REPORT

for the

STANLEY BLACK & DECKER, INC

FCC ID: YJ7-DCR010C

IC ID: 9082A-DCR010C

WLL REPORT# 18554-01 REV 2

Prepared for:

Stanley Black & Decker, Inc

701 E. Joppa Road

Towson, Maryland 21286

Prepared By:

Washington Laboratories, Ltd.

4840 Winchester Boulevard. Suite #5

Frederick, Maryland 21703



Testing Certificate AT-1448



MPE Test Report

for the
Stanley Black & Decker, Inc
DCR010C

FCC ID: YJ7DCR010C
ISED ID: 9082A-DCR010C

June 7, 2024

WLL Report# 18554-01 Rev 2

Prepared by:

A handwritten signature in blue ink, appearing to read 'Ryan Mascaro', written over a horizontal line.

Ryan Mascaro
RF Test Engineer

Reviewed by:

A handwritten signature in blue ink, appearing to read 'Steven D. Koster', written over a horizontal line.

Steven D. Koster
President



Abstract

This report has been prepared on behalf of Stanley Black & Decker, Inc to document the findings of the maximum permissible exposure evaluation on the Stanley Black & Decker, Inc DCR010C. The information provided in this report is only applicable to the device herein documented, as the EUT.

The purpose of this evaluation is to establish a minimum safe distance as per the RF exposure requirements as defined in FCC §1.1307 & §1.1310 and in RSS-102.

This report documents the results of testing to the requirements of:

- CFR Title 47 Volume 1 Practice and Procedure; (1.1307) Environmental Assessments
- RSS-102 Radio Frequency (RF) Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands)

The Evaluation was performed by Washington Laboratories, Ltd, 4840 Winchester Blvd., Suite 5, Frederick, MD 21703. Washington Laboratories, Ltd. has been accepted as an EMC Conformity Assessment Body (CAB) under the United States/European Union Memorandum of Agreement. Washington Laboratories, Ltd. has been accepted by the FCC and approved by ANAB under Testing Certificate AT-1448 as an independent FCC test laboratory.

Revision History	Description of Change	Date
Rev 0	Initial Release	June 7, 2024
Rev 1	TCB Comments; dated: 6/18/2024	June 20, 2024
Rev 2	Power increased by 1.08dB	July 17, 2024



Table of Contents

Abstract	iii
Table of Contents	iv
1 Introduction	5
2 Requirements	5
2.1 Transmitter Categories	5
2.1.1 Fixed Installations	5
2.1.2 Mobile Devices	5
2.1.3 Portable Devices	6
2.2 Exposure Categories	6
2.2.1 Occupational/Controlled Exposure	6
2.2.2 General Population/Uncontrolled Exposure	6
3 Device Summary	9
4 Radio Frequency Radiation Exposure Evaluation	10

List of Tables

Table 1: MPE Limits (FCC)	7
Table 2: MPE Limits (ISED)	8
Table 3: Device Summary, DCR010C	9
Table 4: Transmitter MPE Calculation Summary (FCC)	11
Table 5: Transmitter MPE Calculation Summary (ISED)	11



1 Introduction

This report has been prepared on behalf of Stanley Black & Decker, Inc for the DCR010C (FCC ID: YJ7DCR010C) to show compliance with the RF exposure requirements as defined in FCC §1.1307 & §1.1310 and in RSS-102.

The testing in-support of this evaluation was performed by Washington Laboratories, Ltd. Located at: 4840 Winchester Blvd., Suite #5. Frederick, Maryland 21703.

Washington Laboratories, Ltd. has been accepted as an EMC Conformity Assessment Body (CAB) under the United States/European Union Memorandum of Agreement. Washington Laboratories, Ltd. is accredited with ANAB under Testing Certificate AT-1448.

2 Requirements

2.1 Transmitter Categories

2.1.1 Fixed Installations

A fixed location means that the device, including its antenna, is physically secured at a permanent location and is not able to be easily moved to another location. Additionally, distance to humans from the antenna is maintained to at least 2 meters.

2.1.2 Mobile Devices

A mobile device is defined as a transmitting device designed to be used in other than fixed locations and to be generally used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structures and the body of the user or nearby persons. Transmitters designed to be used by consumers or workers that can be easily re-located, such as a wireless modem operating in a laptop computer, are considered mobile devices if they meet the 20-centimeter separation requirement. The FCC rules for evaluating mobile devices for RF compliance are found in 47 CFR §2.1091.



2.1.3 Portable Devices

A portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user. Portable device requirements are found in Section 2.1093 of the FCC's Rules (47 CFR§2.1093).

2.2 Exposure Categories

The limits for exposure are determined by the type of situation in which the individual is exposed. Table 1 lists the limits for the particular environment.

2.2.1 Occupational/Controlled Exposure

In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means. Awareness of the potential for RF exposure in a workplace or similar environment can be provided through specific training as part of a RF safety program. If appropriate, warning signs and labels can also be used to establish such awareness by providing prominent information on the risk of potential exposure and instructions on methods to minimize such exposure risks.

2.2.2 General Population/Uncontrolled Exposure

The general population / uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general-public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category and the general population/uncontrolled exposure limits apply to these devices.



Table 1: MPE Limits (FCC)

Frequency Range (MHz)	Electric field Strength (V/m)	Magnetic field Strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1	6
300–1500	N/A	N/A	f/300	6
1500–100,000	N/A	N/A	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	N/A	N/A	f/1500	30
1500–100,000	N/A	N/A	1	30



Table 2: MPE Limits (ISED)

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m ²)	Reference Period (minutes)
Limits for General Population/Uncontrolled Exposure				
0.003-10	83	90	-	Instantaneous*
0.1-10	-	0.73/ <i>f</i>	-	6**
1.1-10	87/ <i>f</i> ^{0.5}	-	-	6**
10-20	27.46	0.0728	2	6
20-48	58.07/ <i>f</i> ^{0.25}	0.1540/ <i>f</i> ^{0.25}	8.944/ <i>f</i> ^{0.5}	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 <i>f</i> ^{0.3417}	0.008335 <i>f</i> ^{0.3417}	0.02619 <i>f</i> ^{0.6834}	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/ <i>f</i> ^{1.2}
150000-300000	0.158 <i>f</i> ^{0.5}	4.21 x 10 ⁻⁴ <i>f</i> ^{0.5}	6.67 x 10 ⁻⁵ <i>f</i>	616000/ <i>f</i> ^{1.2}
Note: <i>f</i> is frequency in MHz.				
*Based on nerve stimulation (NS). ** Based on specific absorption rate (SAR).				
Frequency Range(MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m ²)	Reference Period (minutes)
Limits for Occupational/Controlled Exposures				
0.003-1023	170	180	-	Instantaneous*
0.1-10	-	1.6/ <i>f</i>	-	6**
1.29-10	193/ <i>f</i> ^{0.5}	-	-	6**
10-20	61.4	0.163	10	6
20-48	129.8/ <i>f</i> ^{0.25}	0.3444/ <i>f</i> ^{0.25}	44.72/ <i>f</i> ^{0.5}	6
48-100	49.33	0.1309	6.455	6
100-6000	15.60 <i>f</i> ^{0.25}	0.04138 <i>f</i> ^{0.25}	0.6455 <i>f</i> ^{0.5}	6
6000-15000	137	0.364	50	6
15000-150000	137	0.364	50	616000/ <i>f</i> ^{1.2}
150000-300000	0.354 <i>f</i> ^{0.5}	9.40 x 10 ⁻⁴ <i>f</i> ^{0.5}	3.33 x 10 ⁻⁴ <i>f</i>	616000/ <i>f</i> ^{1.2}
Note: <i>f</i> is frequency in MHz.				
*Based on nerve stimulation (NS). ** Based on specific absorption rate (SAR).				



3 Device Summary

The table below summarizes the criteria used to evaluate the EUT.

Table 3: Device Summary, DCR010C

Transmitter Category:	Unlicensed
Exposure Category:	General
Antenna Gain:	3.34 dBi
Power Output (dBm):	8.84 dBm (7.66 mW)
Tune-up Tolerance:	±1.12 dB
Evaluation Distance:	20 cm
Frequency Range:	2402 MHz – 2480 MHz
FCC Limit:	1.0 mW/cm ²
ISED Limit:	0.535 mW/cm ²

From above:

$$8.84 \text{ dBm} + 3.34 \text{ dBi} + 1.12 \text{ dB} = 13.30 \text{ dBm (maximum possible EIRP)}$$



4 Radio Frequency Radiation Exposure Evaluation

The highest RF output power of the unit was measured and recorded. According to §1.1310 of the FCC rules, the power density limit for General Population/Uncontrolled Exposure is 1mW/cm². According to §1.1310 of the FCC rules, the power density limit for Occupational/Controlled Exposure is 5mW/cm².

The MPE shall be calculated at 20cm to show compliance with the power density limit. The following formula was used to calculate the Power Density:

$$S = \frac{PG}{4\pi R^2}$$

where,

S = Power Density

P = Output Power at the Antenna Terminals

G = Gain of Transmit Antenna (linear gain-isotropic)

R = Distance from Transmitting Antenna



Table 4: Transmitter MPE Calculation Summary (FCC)

One Transmitter			
Frequency	2402	MHz	
Limit	1.000	mW/cm ²	
Distance (cm), R =	20	cm	
Power (dBm), P =	9.96	dBm	
TX Ant Gain (dBi), G =	3.34	dB	
Power Density:	0.004	mW/cm ²	Separation<20 cm

Table 5: Transmitter MPE Calculation Summary (ISED)

One Transmitter			
Frequency	2402	MHz	
Limit	0.535	mW/cm ²	
Distance (cm), R =	20	cm	
Power (dBm), P =	9.96	dBm	
TX Ant Gain (dBi), G =	3.34	dB	
Power Density:	0.004	mW/cm ²	Separation<20 cm