

**XB Series Evaluation of International Compliance for General  
Public Exposure to Electromagnetic Fields**



45 Sale Street, Level 1, Freemans Bay 1010  
PO Box 91164, Victoria Street West 1142  
Auckland, New Zealand

Phone: +64 (0)9 950 4848  
Fax: +64 (0)9 950 4085

[www.vespermarine.com](http://www.vespermarine.com)

**Version History**

Version	Date	Comment
1	09/11/12	First revision
2	10/13/2017	Update UHF exposure limit calculations for Nemo Rev E

**Copyright Notice**

Copyright © 2017, Vesper Marine Ltd. All rights are reserved.

The information contained within this document is the copyright of Vesper Marine Ltd

No part of this document may be disclosed, reproduced or transmitted in any form, or by any means without the written permission of Vesper Marine Ltd. The term document extends to all forms of media in which information may be embodied.

## Introduction

This report evaluates the requirement under the R&TTE Directive for the XB Series of Class B AIS transceivers with integrated 802.11b/g connectivity to comply to the levels for public exposure to electromagnetic radiation as defined in EN 50385. The exposure assessment has been performed according to EN 50383 Section 8 to show that the XB9000, XB8000 and XB6000 will not generate electromagnetic emissions above the reference level as specified in EC Council Recommendation (1999/519/EC) in both the VHF and UHF transmission bands used by the AIS and 802.11b/g transmitters respectively.

It also compares this to the US requirements under the FCC Rule Parts 1.1310, 2.1091 and 2.1093 for radio frequency exposure limits for the general public.

## EUT Description

Products	<i>WatchMate</i> Vision, XB-8000, X-6000
Trade Name	Vesper Marine Ltd
Model Numbers	XB9000, XB8000, XB6000
Power Supply	12-24V DC
VHF Frequency Range	161.500 – 162.025 MHz
VHF Transmit Power	33dBm (2W)
VHF Modulation Technique	FM GMSK
VHF Channel Spacing	25kHz
VHF Antenna Gain Specification	3dBi
Antenna Designation	Monopole
UHF Transmit Power	15dBm (30mW)
VHF Antenna Gain Specification	1.2dBi
Antenna Designation	PCB SMT
Temperature Range	-25 - +55 deg C
Intended Users	General Public
Equipment type	Fixed (non-portable)

Typical distance of use	40cm
-------------------------	------

For more details please refer to the user manual

## VHF Limits

System must operate in Europe under the reference levels as outlined by the Council Recommendation 1999/519/EC and in the US under the FCC limits which can be summarized as follows:

Table 1 – International Exposure Limits

Region	Frequency Range	E-Field Strength (V/m)	H-Field Strength (A/m)
Europe	30 – 300 MHz	28	0.07
FCC	30 – 300 MHz	27.5	0.07

Furthermore EN 50385 stipulates that if the average power emitted by the system is less than 20mW, the system is deemed to comply with the standard without testing.

## VHF Exposure Evaluation

Since the maximum average power at the antenna permitted by IEC 62287-1 for a TDMA Class B AIS Transponder can be calculated as 10.28dBm (33dBm, 5 second reporting interval, 26.67ms slot time), the XB series automatically complies with EN 50385 for a nominal antenna gain of 3dBi. However for completeness and user manual documentation the compliance boundary is also examined.

The compliance boundary can be determined from the following with the results shown in Table 2 below,

$$D = \sqrt{30 \times G \times P} / E$$

where,

D = distance from the antenna (m)

G = numerical antenna gain

P = power at the antenna (W)

E = E-Field strength (V / m)

The assumptions are as follows,

- The far field model applies
- The antenna gain is typically 3dBi

- The antenna length is typically equal to half a wavelength
- Nominal operating frequency of 162MHz

Table 2 – Evaluation Results

Radiating Far Field boundary*	0.93 m
E-Field at Far Field boundary	11.77 V/m
H-Field at Far Field boundary	0.03 A/m
EU Compliance Boundary	0.39 m
US Compliance Boundary	0.40 m

\* The boundary between the Near and Far Fields for which at distances greater than this the Far Field model can be applied

Under the Far-Field model the system E-Field and H-Field are well below the limits as shown in Table 1. An maximum permissible exposure (MPE) radius of 1m is practical for system installation and will ensure the limits are never breached.

### UHF Limits and Exposure Evaluation

In accordance with the test reports covering EN 300 328 and FCC 15.247 compliance the maximum summed output power of the 802.11b/g transmitter is 15dBm (32mW) at 2452MHz. Exposure at a typical operating distance 40cm is well below the limits for both FCC and EU as can be seen in Table 4 below.

Table 3 – FCC Exposure Limits

Region	Frequency Range	Power Density (mW/cm <sup>2</sup> )
FCC	1500 – 100000 MHz	5
EU	2000-300000 MHz	10

Table 4 – Evaluation Results

Radiating Far Field boundary	0.06 m
E-Field at Far Field boundary	17.9 V/m
Power Density at boundary	0.0932 mW/cm <sup>2</sup>

Results were calculated using the same equations as specified in VHF Exposure evaluation with the following differences:

- Antenna gain of 1.2dBi used

- *Nominal operating frequency 2462MHz*

## **User Manual Warnings**

In addition to the installation instructions in the user manual and in accordance with Section 7 of EN 50385 the following has been included in the manual under General Warnings:

### *“RF Emissions*

*Caution: This device generates and radiates electromagnetic energy. This device must be installed and operated according to the instructions contained in this handbook. Failure to do so can result in product malfunction and / or exposure to potentially harmful levels of radio frequency radiation.*

*Caution: Never operate the this device unless it is connected to a VHF antenna.*

*The system has a Maximum Permissible exposure (MPE) radius of 1m from the antenna. This has been determined assuming the maximum power of the transponder and using a standard monopole VHF antenna with a maximum gain of 3dBi and termination impedance of 50 ohms.*

*When installing the antenna and operating the equipment consider the following,*

- *The antenna should be mounted as high above the deck as possible*
- *Higher gain VHF antennas will require a larger MPE radius*
- *Do not operate the unit when anyone is within the MPE radius of the antenna*
- *The antenna should not be collocated or operated in conjunction with any other transmitting antenna”*

## **Conclusion**

The XB Series complies with the international standards for general public exposure to electromagnetic fields.